EGG-WTD-9923
January 1992

APR 27 1992

*Managed
by the U.S.
Department
of Energy*

Technology Evaluation Report for the Buried Waste Robotics Program Subsurface Mapping Project

B. E. Griebenow

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

This document contains new concepts or the author(s) interpretation of new calculations and/or measurements; accordingly, EG&G Idaho, Inc. is required by the United States Government to include the following disclaimer:

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

EGG-WID--9923

DE92 012523

**TECHNOLOGY EVALUATION REPORT
FOR THE
BURIED WASTE ROBOTICS PROGRAM
SUBSURFACE MAPPING PROJECT**

B. E. Griebenow

Published January 1992

Idaho National Engineering Laboratory
EG&G Idaho, Inc.
Idaho Falls, ID 83415

Prepared for the
U.S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Idaho Field Office
Contract DE-AC07-76ID01570

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TECHNOLOGY EVALUATION REPORT FOR THE BURIED WASTE ROBOTICS PROGRAM SUBSURFACE MAPPING PROJECT

EGG-WTD-9923

Prepared by:

Brad Griebenow

12-18-91
Date

Reviewed by:

Kevin Kostelnik

Dec 17, 91
Date

Approved by:

David Shropshire

1-8-92
Date

ABSTRACT

This document presents a summary of the work performed in support of the Buried Waste Robotics Program Subsurface Mapping Project. The project objective was to demonstrate the feasibility of remotely characterizing buried waste sites. To fulfill this objective, a remotely-operated vehicle, equipped with several sensors, was deployed at the Idaho National Engineering Laboratory. Descriptions of the equipment and areas involved in the project are included in this report. Additionally, this document provides data that was obtained during characterization operations at the Cold Test Pit and the Subsurface Disposal Area, both at the Idaho National Engineering Laboratory's Radioactive Waste Management Complex, and at the Idaho Chemical Processing Plant. The knowledge gained from the experience, that can be applied to the next generation remote-characterization system, is extensive and is presented in this report.

SUMMARY

The Subsurface Mapping Project was performed as part of the Buried Waste Robotics Program for the Office of Technology Development. The project used a remotely-operated vehicle provided by the U.S. Army Human Engineering Laboratory, the Soldier Robot Interface Project (SRIP) vehicle, to demonstrate the technology necessary to nonintrusively map buried waste pits and trenches and buried piping systems using remote operations. The objective of the project was to demonstrate the feasibility of using a remote, multi-sensor device to characterize buried waste. The desired result of the project was to establish realistic and appropriate functional and operational requirements for the development of technology to support future characterization efforts.

The SRIP vehicle was equipped with ground-penetrating radar (GPR), an EM31 terrain conductivity meter (EM31), a magnetometer, a sodium iodide gamma detector, and a photo-ionization organic vapor detector. These sensors were chosen based on data objectives supplied by the Buried Waste Integrated Demonstration Program and information expected to be of value at other sites. After integration of the components, the system was deployed at the Idaho National Engineering Laboratory (INEL) in three locations: the Cold Test Pit (CTP) and Pit 9 of the Subsurface Disposal Area, both located at the INEL's Radioactive Waste Management Complex, and the Idaho Chemical Processing Plant (ICPP).

Operations conducted at the INEL resulted in a better understanding of the requirements related to vehicle and control station configuration, sensor deployment, and data analysis. Sensor interactions were examined and adjustments were made to minimize interference. The knowledge gained from the demonstration will be applied to the Remote Characterization System, the next generation system planned for development in FY-92.

It was made clear during the project planning sessions that the soil present at the INEL was a strong absorber of electromagnetic signals in the normal GPR frequency range and that detection, mapping, and characterization of buried wastes was not likely. It was agreed, however, that despite the low probability of obtaining useful waste-related information from the GPR system, it would be

useful and important to include the GPR system in the sensor package. In a more conducive environment, the GPR is capable of providing geophysical data that is more quantitative in nature than the data provided by the EM-31 or the magnetometer. Particularly of interest is depth-related data available through GPR analysis. Although the processed GPR profiles obtained at the CTP showed apparent reflection anomalies at the approximate locations where targets were known to be buried, similar anomalies occurred at locations where no targets had been buried. This is a clear indication that the recorded GPR signals were dominated by clutter and noise. No useful GPR data were recorded at Pit 9. The data collected at the ICPP are currently being processed and analyzed.

Both the quadrature and inphase components of the EM31 data showed anomalies at both the CTP and Pit 9 that correspond closely with anomalies measured by conventional means, but with a slightly higher noise level due to the presence of the vehicle. The data can be used to locate metallic objects and estimate pit boundaries with resolution that is comparable to conventionally collected data. At Pit 9, EM31 inphase anomalies clearly indicate the presence of large metallic objects and groups of objects throughout the pit. A strong EM31 quadrature anomaly occurs in the central portion of Pit 9. The coincidence of strong inphase and quadrature anomalies can be caused by the presence of shallow objects, massive objects, or by the presence of conductive materials or fluids within or around containers. Pit 9 boundaries are not clearly defined by the EM31 data because the survey did not extend far enough beyond the Pit 9 area to characterize background conductivity levels.

No useful data was collected by the magnetometer at the CTP due to magnetic interference from the vehicle and to fundamental limitations of the magnetometer. The sensor was not mounted on the vehicle during operations at Pit 9 and the ICPP.

The gamma detector found no radiological waste at the CTP; however, it easily detected the natural thorium series and potassium radionuclides and trace cesium. Comparisons with earlier manual measurements indicated no significant data error caused by operation on the vehicle. Pit 9 radiological data provided evidence of buried waste, but allowed no isotopic determinations due to soil shielding. Both the depth of soil overburden and the paucity of collateral radiological data hindered a source strength estimate of the radiological waste.

Radiological information was not of interest at the ICPP; therefore, the sensor was not deployed at that location.

At both the CTP and Pit 9, there was no evidence of surface-evolving organics sensitive to photo-ionization detection. Manual measurement comparisons indicated that the data were not compromised by vehicle mounting.

The simultaneous collection of data from multiple sensors was found to be an efficient means for collecting site data. The high data acquisition rates that are possible using a vehicle constitute a significant advantage over conventional surveying. Only the magnetometer was adversely affected by deployment on the vehicle. Future activities will involve the development of a vehicle with low ferromagnetic content to reduce the vehicle-induced noise levels. Additionally, the response time of the sensors to be mounted on the vehicle will be improved to allow higher quality data collection while the vehicle is in motion.

ACKNOWLEDGEMENTS

The author would like to extend his appreciation to the many people who assisted in the compilation of this report. This was truly a team effort, with text and data provided by personnel from Lawrence Livermore National Laboratory (LLNL), Oak Ridge National Laboratory (ORNL), Pacific Northwest Laboratory (PNL), Sandia National Laboratories (SNL), and Science Applications International Corporation (SAIC) in addition to that provided by personnel from the Idaho National Engineering Laboratory (INEL). Special thanks to the following:

Jodie Boyce, INEL
Bruce Clegg, SAIC
Julie Conner, INEL
John Feddema, SNL
Doug Jorgensen, INEL
Nick Josten, INEL
Kevin Kostelnik, INEL
Lori Martinson, INEL
Thom Nash, INEL
Janalee Nelson, INEL
Mark Noakes, ORNL
Jon Pence, LLNL
William Quapp, INEL
Brad Richardson, ORNL
Gerald Sandness, PNL
Tim Stewart, PNL
Chuck Urbanski, INEL

Mark Noakes and Jodie Boyce are especially commended for their perseverance during the summer. They worked long hours in a poor operating environment to provide the data that is contained in this report. Without their dedication, this project would have been a catastrophe.

The project was only able to achieve success through collaboration between the Robotics Technology Development Program and the Buried Waste Integrated Demonstration (BWID) Program. Without all the support offered by BWID, the project would have fallen short of the desired achievements. Julie Conner and Kevin Kostelnik were significant in their contributions through BWID.

CONTENTS

ABSTRACT	iii
SUMMARY	v
ACKNOWLEDGEMENTS	ix
ACRONYMS	xv
INTRODUCTION	1
The Buried Waste Robotics Program	1
The Subsurface Mapping Project	2
DESCRIPTION	4
Vehicle	4
Navigation	4
Sensors	5
Data Display	5
SURVEY AREAS	7
The Cold Test Pit	7
Pit 9	8
Idaho Chemical Processing Plant	8
DATA RESULTS	10
Cold Test Pit	10
Pit 9	14
Idaho Chemical Processing Plant	15
QUALITY CONTROL	16
Instrument Calibration	16
Data Management	16
Data Quality	17

LESSONS LEARNED	19
Vehicle	19
Communications	21
Operator Control Station	22
Sensors	23
Development Activities	24
RECOMMENDATIONS	26
CONCLUSION	27
BIBLIOGRAPHY	55

FIGURES

1. Soldier Robot Interface Project (SRIP) vehicle.	29
2. EM31 data versus vehicle position	31
3. Three-dimensional and respective two-dimensional plots of EM31 data	33
4. Example GPR data plot (data obtained from Hanford)	35
5. GPR data from the Cold Test Pit: (a) raw data, and (b) filtered data	37
6. GPR profiles from the Cold Test Pit	38
7. EM31 quadrature data from the Cold Test Pit: (a) SRIP and (b) conventional. Dots show data points. Contour interval = 5 mmhos/meter.	40
8. EM31 inphase data from the Cold Test Pit: (a) SRIP, (b) conventional. Dots show data points. Contour interval = 5 (unitless).	41
9. Robot (a) speed and (b) heading during one hour Cold Test experiment	42
10. Total magnetic field data from the Cold Test Pit: (a) conventional, (b) SRIP. Dots show data points. Contour interval = 500 gammas.	43
11. Cold Pit Test manually read, surface radiological exposure, μ Rad/h, calculated by the energy method. (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views	44

12.	Surface radiological exposure, $\mu\text{Rad/h}$, calculated by the energy method. INEL, Cold Test Pit. (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views	45
13.	Am-241 gamma data, in counts/s, Am region-of-interest. INEL, Cold Test Pit. (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views. (<i>All data found below the limit of detection.</i>)	46
14.	Cs-137 gamma data (world-wide fallout), in counts/s, Cs-137 region-of-interest. INEL, Cold Test Pit. (a) 30-deg. (b) 120-deg., (c) 210-deg., and (d) 300-deg. views. (<i>All data found below the limit of detection.</i>)	47
15.	K-40 gamma data (natural, soil-borne), in counts/s, K-40 region-of-interest. INEL, Cold Test Pit. (a) 30-deg. (b) 120-deg., (c) 210-deg., and (d) 300-deg. views. (<i>All data found below the limit of detection.</i>)	48
16.	Tl-208 gamma data (natural, soil-borne thorium series), in counts/s, Tl-208 region-of-interest. INEL, Cold Test Pit. (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views . .	49
17.	GPR data from Pit 9: (a) raw data, (b) raw averaged data, (c) running averaged data	50
18.	EM31 inphase data from Pit 9	51
19.	EM31 quadrature data from Pit 9	52
20.	Surface radiological exposure $\mu\text{Rad/h}$, calculated by the energy method. INEL, Subsurface Disposal Area, Pit 9, (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views	53
21.	Surface organic vapor, detected by a photo-ionization detector. INEL, Subsurface Disposal Area, Pit 9, (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views. (<i>All data found below the limit of detection.</i>)	54

TABLE

1.	Remote characterization sensors	5
----	---	---

ACRONYMS

BWID	Buried Waste Integrated Demonstration
BWRP	Buried Waste Robotics Program
CTP	Cold Test Pit
DAU	digital data acquisition unit
DOE	Department of Energy
GPR	ground-penetrating radar
GSSI	Geophysical Survey Systems, Inc.
HLWTR	High-Level Waste Tank Farm Replacement
ICPP	Idaho Chemical Processing Plant
INEL	Idaho National Engineering Laboratory
LLNL	Lawrence Livermore National Laboratory
ORNL	Oak Ridge National Laboratory
OTD	Office of Technology Development
PC	portable computer
PNL	Pacific Northwest Laboratory
RF	radio frequency
RTDP	Robotic Technology Development Program
RWMC	Radioactive Waste Management Complex
SAIC	Science Applications International Corporation
SDA	Subsurface Disposal Area
SNL	Sandia National Laboratory
SRIP	Soldier Robot Interface Project
SRS	Savannah River Site
USRADS	Ultrasonic Ranging and Data System
WINCO	Westinghouse Idaho Nuclear Company, Inc.

TECHNOLOGY EVALUATION REPORT FOR THE BURIED WASTE ROBOTICS PROGRAM SUBSURFACE MAPPING PROJECT

INTRODUCTION

The Buried Waste Robotics Program

The Robotics Technology Development Program (RTDP) was established by the Department of Energy (DOE) Office of Technology Development (OTD) to integrate DOE robotic development activities. The purpose of the program is to provide needs-oriented, timely, and economical robotics technology to support environmental and waste operations activities at DOE sites and provide the focus and direction for the near term (less than five years) and guidance for the long term (five to twenty years) development efforts for site-specific problems. The RTDP objectives are to develop, test, evaluate, and make available robotic technologies that allow removal of workers from hazards, increase speed and productivity, increase safety of operations, and reduce life-cycle costs compared to alternate methods and technologies.

The initial RTDP five-year plan concentrates on needs in the following areas: (a) underground storage tanks, (b) buried waste, (c) contaminant analysis automation, (d) waste minimization, (e) decontamination and decommissioning, and (f) advanced technology development. A lead laboratory has been designated for each of these areas. The lead laboratory for buried waste is the Idaho National Engineering Laboratory (INEL) in support of the remediation of the Subsurface Disposal Area (SDA) located at the Radioactive Waste Management Complex (RWMC). The preliminary focus of the technology development is in support of the remediation effort at the SDA, but the technology will also have application at other sites where similar buried waste problems exist.

The objective of the Buried Waste Robotics Program (BWRP) is to identify, develop, and demonstrate robotic technologies which will support environmental remediation of buried waste. Buried waste, for the purposes of the program,

includes all forms of subsurface contamination—waste disposed of in pits and trenches, waste stored on pads and covered with soil, contaminated soil, and underground piping. The technology developed under BWRP will allow operations personnel to perform the necessary functions while removed from the hazardous environment.

A team of seven organizations participated in the demonstrations performed for the BWRP. These organizations were as follows:

- Idaho National Engineering Laboratory (INEL)
- Lawrence Livermore National Laboratory (LLNL)
- Oak Ridge National Laboratory (ORNL)
- Pacific Northwest Laboratory (PNL)
- Sandia National Laboratory (SNL)
- Savannah River Site (SRS)
- Science Applications International Company (SAIC).

The OTD organization primarily responsible for development of technology to be applied to buried waste remediation is the Buried Waste Integrated Demonstration (BWID). BWID has the task of evaluating potential technologies and sponsoring the most promising candidates to demonstrate better, faster, and cheaper buried waste remediation. In light of this role, BWID provided some of the requirements for the BWRP technology development, as well as providing partial funding.

The Subsurface Mapping Project

This document describes one of the projects performed as part of BWRP, the Subsurface Mapping Project. The objective of the Subsurface Mapping Project is to demonstrate the feasibility of using a remotely-operated vehicle to perform characterization operations. Present non-invasive subsurface mapping techniques are labor intensive and time consuming. The Subsurface Mapping Project applied current state-of-the-art robotic technologies to reduce the time required to perform mapping exercises. The applied technologies also allowed improved data quality, via more dense data maps, through automated data acquisition at a rate

higher than typical manual operations. The sensors applied to this effort were off-the-shelf technology and, as such, did not provide any advanced capabilities.

The Subsurface Mapping Project was evaluated at three locations: the Cold Test Pit (CTP) near the RWMC, Pit 9 located in the SDA, and the Idaho Chemical Processing Plant (ICPP). The main purpose of the CTP evaluation, described more fully in a separate section of this document, was to demonstrate that coherent geophysical data could be collected using the remote vehicle. Additionally, the CTP provided an opportunity to optimize the instrument configuration on board the vehicle, to establish the accuracy of the sensors installed, and to develop a strategy for the editing and processing of the raw data. The CTP was ideally suited for this purpose because it had been previously surveyed by conventional methods. The data collected using remote operations were verified by comparison to data collected using conventional methods and the documentation available on the CTP. After the sensors had been optimized at the CTP, the vehicle was taken to Pit 9, one of the buried waste pits located in the SDA. Multiple passes were made on Pit 9 to obtain the desired data integrity. Finally, the vehicle was deployed at the ICPP to map underground piping and other objects of interest to the High-Level Waste Tank Farm Replacement (HLWTFR) Project.

DESCRIPTION

Vehicle

An existing vehicle, developed jointly by the U.S. Army Human Engineering Laboratory, Oak Ridge National Laboratory (ORNL), and Tooele Army Depot for the U.S. Army Soldier Robot Interface Project (SRIP) was used for the Subsurface Mapping Project. The SRIP vehicle, shown in Figure 1, was developed as a research testbed to be used for studying mobile manipulation with respect to military applications. The vehicle is an eight-wheeled, skid-steered, utility vehicle powered by a 15 horsepower diesel engine. The vehicle was modified extensively from its purchased configuration to accommodate the addition of a manipulator and the onboard electronics required for remote operation as a research testbed. An onboard power conversion system, with 110 volts ac and a number of dc voltages, was available to power the sensors deployed on the vehicle. The vehicle control system was implemented on VME busses (two onboard and a third at the control station) using Motorola 68020 processors. The vehicle was equipped with a radio-frequency (rf) communications link for vehicle control. The vehicle was modified by ORNL to integrate the subsurface mapping sensors identified for the project.

The configuration and design of the SRIP vehicle was not optimal for deployment of characterization sensors. The complexity of the vehicle systems compromised operational reliability and the metallic content effected instrument data. The decision to use the SRIP vehicle was based on funding constraints, combined with the ability to meet the project objective of demonstrating the feasibility of remote characterization.

Navigation

ORNL's Ultrasonic Ranging and Data System (USRADS) was used to determine the x-y position of the vehicle on the test site and to transmit sensor data, by radio, to the USRADS control station. The USRADS was developed to facilitate the collection of radiological and geophysical data at hazardous waste sites. The USRADS consists of an onboard module with an ultrasonic transmitter and instrumentation interfaces, and a portable computer (PC) with an rf link to the

onboard module and up to 15 stationary ultrasonic receivers. An ultrasonic signal emitted by the onboard module triggers the receivers to send a radio signal to the PC indicating reception of the signal. The time-of-flight data from the receivers is used to determine the position of the vehicle, which is correlated with the sensor data transmitted from the onboard module. A real-time plot showing the position of the receivers and the vehicle is displayed on the PC screen. Sensor readings above a predetermined threshold are highlighted on the screen in real-time.

Sensors

The SRIP vehicle was equipped with subsurface geophysical sensors and sensors for detecting surface radiation and organic vapors. Information on each of the sensors is summarized in Table 1.

Table 1. Remote characterization sensors.

Sensor	From	Information Obtained	Data Display
Ground-penetrating radar	PNL	Reflections from subsurface anomalies	Post processing required
EM31 Terrain conductivity meter	INEL	Presence of conductive material	Real time and contours after post processing
Magnetometer	INEL	Presence of ferrous material	Post processing required
NaI gamma-based spectrum detector	LLNL	Indication of specific radiological isotopes	Post processing required
Photo-ionization organic vapor detector	LLNL	Presence of organic vapors	Post processing required
NaI gamma detector	ORNL	Presence of gamma radiation	Real time

Data Display

A customized data visualization package for viewing both real-time and off-line sensor data was developed by Sandia National Laboratories. This package used the general visualization software *PV-Wave* running on a Silicon Graphics computer. The menu-driven software allowed the user to view simultaneously USRADS, ground-penetrating radar (GPR), organic detector, gamma spectrometer, and

magnetometer data. The software also allowed the user to make daily backups of data collected or retrieve previously collected data for display.

The USRADS data was displayed in real-time. The five USRADS channels consisted of the x and y position of the SRIP vehicle, quadrature and in-phase readings of the EM31 terrain conductivity sensor, and measurements from an NaI broadband gamma sensor. The EM31 and broadband gamma data were plotted versus the vehicle's position on a 40 by 40 grid with color varying with signal intensity (see Figure 2). When the data collection was completed, the display software would interpolate the data, plot a contour map, and display a 3-D colored surface of the data, as shown in Figure 3.

The GPR, organic, gamma spectrometer, and magnetometer data were displayed off-line after the SRIP vehicle returned to the base station. The data from these sensors were manipulated into a form which could be displayed as a function of the vehicle's position and then transferred to the Silicon Graphics computer. Since none of the off-line sensors displayed any indication of subsurface materials, GPR data from Hanford, Washington, was used to demonstrate the visualization package's ability to display GPR data. An example of the GPR data display is shown in Figure 4.

SURVEY AREAS

The Cold Test Pit

The CTP was constructed in 1988 to provide a cold (nonradioactive/nonhazardous) testbed for retrieval and other remedial action scenarios. The test pit was constructed, filled with simulated waste, and backfilled in the same manner in which the RWMC SDA waste pits were constructed between 1952 and 1970. The simulated waste forms included metal scrap, asphalt, concrete blocks, cinder blocks, scrap wood, cloth, paper, glass, and HEPA filters. Simulated waste was loaded by hand and with heavy equipment into mostly cardboard 55-gallon drums and cardboard 4 x 4 x 8 ft boxes. In addition, about 40 metal drums were buried. Cardboard was used as the simulated waste container material to promote rapid deterioration of the containers. This was done to simulate the 35 years of burial in shallow land-filled pits in the SDA of the original metal drums and plywood boxes. To further promote deterioration, water was extensively sprayed on the waste forms while the pit was being backfilled with moist dirt. After emplacing the waste forms and back filling the pit, a contoured cap of earth was placed on the top of the pit.

The physical excavated area of the pit was approximately 150 feet long by 50 feet wide with an approximate depth of 10 feet. The pit was compartmentalized into five zones. The compartments were reserved as a large object zone, a stacked large box zone, a stacked 55-gallon drum zone, a randomly dumped drums and boxes zone, and a randomly dumped drum zone.

Mapping the CTP was essential for demonstrating the effectiveness and efficiency of remote subsurface mapping. The accurate records of buried waste type and location at the CTP allowed for comparisons with the data obtained with the SRIP vehicle. In addition, previous conventional surveys of the CTP allowed for comparisons of data quality, data integrity, and operational efficiency of the remotely-obtained data relative to the conventional data.

Pit 9

During the period of 1954 to 1970, a wide variety of wastes and waste types were shipped to the SDA for disposal. Waste disposed at the SDA included organics, inorganics, toxic metals, and radionuclides. A variety of containers were utilized for the shipment of wastes to the SDA, including steel drums (30, 40, and 55-gallon), cardboard cartons, and wooden boxes. Larger individual items were disposed separately as loose trash. It is estimated that the combined volume of wastes and contaminated soils at the SDA is 12.1 million cubic feet. Limited historical data of the waste buried within the SDA exist, but have not been verified and are believed to be incorrect or incomplete in many cases.

Pit 9, one of the buried waste pits in the SDA, is believed to contain over 6,000 containers, with a waste container volume in excess of 150,000 cubic feet. The pit, approximately 130 feet wide and 330 feet long, was excavated to a depth of 8 feet. The volume of contaminated soil in the pit has been estimated at approximately 600,000 cubic feet. Therefore, the total contaminated volume at Pit 9 is estimated to be 750,000 cubic feet.

Pit 9 was mapped with the SRIP vehicle to gather information that could be used for planning future remediation efforts. Conventional surveys of Pit 9 were available for comparison with the remotely-obtained data. Information desired from the Pit 9 survey was supplied by BWID and was the primary driver in determining the sensors deployed.

Idaho Chemical Processing Plant

Westinghouse Idaho Nuclear Company, Inc., (WINCO) operates the Idaho Chemical Processing Plant (ICPP) for DOE. WINCO's mission is to process government-owned spent nuclear fuel. The process involves dissolving the fuel, extracting uranium, and calcining the waste to a solid form for storage. Prior to calcining, the high-level radioactive liquid waste generated by the fuel dissolution and separation processes is temporarily stored in 11 high-level liquid waste tanks. The tanks were put into service between 1953 and 1966 and are currently operating 10 to 15 years beyond their design life.

WINCO is replacing these tanks because of their age and the fact that they do not meet current design requirements. The High-Level Waste Tank Farm Replacement (HLWTFR) Project plans to replace five of the existing tanks with four new tank and vault systems. The HLWTFR Project established the Subsurface Imaging Program with the goal of identifying the location of underground pipes, ductbanks, and other obstructions in the HLWTFR Project excavation areas and environmental characterization borehole areas. With the collected information, there will be a reduced risk of damaging underground utilities and pipes in the excavation and drilling areas, and improved efficiency of excavation operations.

DATA RESULTS

Cold Test Pit

GPR. Figure 5 shows an example of the GPR data that was collected at the Cold Test Pit. These data are shown in the form of profiles. The horizontal axis corresponds to distance along the survey line; the vertical axis corresponds to the signal travel time in the ground, or to depth. The amplitude of the oscillatory bipolar GPR signal is displayed as a gray scale; the maximum positive amplitude is displayed as white; the maximum negative amplitude is displayed as black. The upper profile shows the raw data that was collected along the approximate centerline of the test pit. The lower profile shows the same data after high-pass filtering to remove unchanging signal components. The filtering process involved the subtraction of a running average of the amplitude along each horizontal (constant time) row of the two-dimensional data set.

The profiles in Figure 5 show several features that can be interpreted as reflections from buried objects. However, such interpretations should be made with caution. If the anomalous reflection patterns do correspond to buried objects, the reflecting surfaces of those objects would have been relatively shallow, probably at depths less than 3 ft. Deeper objects or deposits of simulated waste materials were not detected.

Figure 6 shows a set of 10 processed GPR profiles from the Cold Test Pit. These are similar to the profiles shown in Figure 5, but represent a more extensive set of measurements. These profiles suggest that there is some correlation of reflection patterns from one survey line to the next. This supports the conclusion that the reflection anomalies were produced by buried objects. Unfortunately, this assessment is complicated by uncertainties in the starting and stopping points of the vehicle and the data recordings along the survey lines. This is largely a consequence of the fact that time and funds did not permit the GPR control unit to be fully interfaced to the onboard SRIP computer. The GPR digital data acquisition unit (DAU) was manually controlled, but its on/off functions were not always closely synchronized with the movement of the vehicle.

An extensive series of tests were performed at the Cold Test Pit. A Geophysical Survey Systems, Inc., (GSSI) SIR System 10 radar unit and several antennas were used in an attempt to determine an optimal combination of antenna and control settings that would improve the quality of the data collected by the SRIP system. Three conclusions were drawn from this work, (a) the 120-MHz antenna seemed to perform better than any of the others that were available, (b) the target detection depth was only a few feet for highly reflective targets such as a pyramid of steel 55-gallon drums, and (c) that interpretation of GPR data collected at this site would be ambiguous and unreliable at best. Although the test profiles showed apparent reflection anomalies at the approximate locations where targets were known to be buried, similar anomalies occurred at locations where no targets had been buried. This is a clear indication that the recorded GPR signals were dominated by clutter and noise.

EM31. Robotic and conventionally collected EM31 data are shown in Figure 7 (quadrature component) and Figure 8 (inphase component). The SRIP data show the same configuration of anomalies as the conventional data, though noise levels for the SRIP data are slightly higher. Possible reasons for this are discussed below.

The most significant errors in the initial SRIP EM31 data were positioning related. Positioning errors had two components, (a) error due to the time lag between when the EM31 initiates a reading and when the reading is completed and sent to the USRADS positioning system and (b) error due to the physical offset between the USRADS positioning equipment and the boom-mounted EM31.

The initial time lag error occurred because the EM31 requires several seconds to obtain a stable reading and during this time the SRIP moves approximately two to four feet. The magnitude of the time lag error is dependent on the speed of the vehicle, the direction of travel, and, to a lesser extent, on the type of anomaly being traversed. There are currently no standard procedures for correcting the lag effect. A strategy for correcting the time lag error was developed based on instrument response curves provided by the EM31 manufacturer. This correction was applied to the data of Figures 7 and 8 and to all subsequent data collected by the SRIP. Development of this correction resulted in a major improvement of the EM31 data quality.

The initial offset error occurred because the EM31 and the USRADS positioning system were mounted several feet apart on the SRIP vehicle. To obtain the position of the EM31, the USRADS position data had to be corrected for this offset. An offset correction was calculated based on the instantaneous heading of the SRIP at the time of each EM31 measurement. This correction was only approximate because the speed and heading of the SRIP fluctuate rapidly, making the instantaneous heading difficult to determine (see Figure 9). A better solution to this problem was to mount the USRADS and EM31 at the same location on the SRIP so that the offset is zero, eliminating the offset error. The data in Figures 7 and 8 and all subsequent data were collected with zero offset.

EM31 inphase data were compensated for the effect of the conductive SRIP vehicle during calibration procedures. This compensation was effective because the distance and relative orientation of EM31 and SRIP did not change during the survey, i.e., the EM31 was fixed to the SRIP boom. However, the GPR antenna was suspended directly below the EM31 and was able to shift and twist constantly during SRIP operations. The antenna was located in a zone that strongly influenced the EM31 reading, and may have been a source of random noise in the EM31 data. An improved GPR antenna carriage was implemented for the surveys of Pit 9 and ICPP.

The EM31 quadrature data cannot be compensated for by the effect of the vehicle. As a result, the instrument constantly sensed the SRIP causing a slight bias in the quadrature data that was not directly related to ground conductivity. It is conceivable that the amount of bias could be determined by a calibration procedure in an area of known conductivity. The bias could then be removed yielding quadrature data that was directly related to ground conductivity. No attempt was made to develop a calibration procedure of this type.

Despite the higher noise level observed in the SRIP collected EM31 data, the general configuration of anomalies was quite similar to the anomalies observed in the conventional (manually acquired) data. From a practical standpoint, it seems probable that large areas of buried metallic waste could be detected and located by a SRIP survey. In the case of a pit filled with metallic waste, the pit boundaries could be reasonably estimated. However, detailed anomaly analysis such as resolving closely spaced objects or estimating depths, which are difficult with noise-free data, would be more difficult with the SRIP data.

Magnetometer. The SRIP vehicle, being composed partly of ferrous metal, is a significant noise source. This noise is manifested in two ways, (a) the magnetometer constantly senses the strong local magnetic field of the SRIP, which serves to mask lower level signals from buried metal, and (b) the SRIP creates strong magnetic-field gradients that can cause the magnetometer to become unstable and produce rapidly fluctuating, erratic data. A further complication is that the magnetic field and magnetic field gradient due to the SRIP are both strongly dependent on the orientation of the vehicle.

The total field magnetic data collected by the SRIP are shown in Figure 10b. Conventionally collected total field data are shown in Figure 10a for comparison. The large anomalies (up to 10,000 gammas) observed in the SRIP data have no counterparts in the conventional data and are clearly unrelated to geologic or buried metal sources. The SRIP data show no indication of the lower amplitude features (up to 1000 gammas) that are observed in the conventional data. Although the origin of the anomalies in the SRIP data is unknown, it is clear that the magnetometer, as currently deployed, yields no useful information on buried metallic objects.

Radiological. Initial measurements were taken manually at the CTP for later comparisons to data obtained remotely. Figure 11 shows the sparse gamma-ray data from the manual survey. Subsequently, the instrumentation was mounted on the SRIP and provided data for surface radiological exposure calculations, using the energy method, shown in Figure 12. Figures 13, 14, 15, and 16 show the Am-241, Cs-137, K-40, and Tl-208 regions-of-interest radionuclide. The presence of Am-241 was below detectable limits, indicating no plutonium surface contamination—an expected result since the CTP did not contain any radiological waste. The remaining trace radionuclides, found above the level of detection, were natural thorium series and world-wide background amounts of Cs-137. The remotely-obtained data matched the manual data, but with a slight change in gamma efficiency. No vehicle-provoked noise or interference was found.

Organics. As expected, no organic vapors were detected at the CTP. However, vehicle exhaust interfered with the organic measurements causing occasional readings above the limit-of-detection.

Pit 9

GPR. No useful GPR data were recorded at Pit 9. Figure 17 shows an example of the data collected at that site. As indicated at the base of the bottom profile, some reflection patterns seem to have been recorded from a depth of several feet. However, an apparent misadjustment of the GPR amplifier gain resulted in a saturation of the output amplifier and a loss of information at shallow depths. This is the cause of the pronounced striping that is present in the processed profiles (the stripes would normally be removed by the filtering process).

EM31. Locations of metallic debris can be delineated from the EM31 inphase data (see Figure 18). A corresponding EM31 quadrature anomaly in the central portion of the survey area (see Figure 19) indicates that conductive materials could be present throughout a relatively large volume of the subsurface at this location. Possible scenarios include (a) drums or containers filled with conductive materials or fluids, (b) conductive materials or fluids in the soil between and beneath containers, or (c) the presence of shallow or massive metallic objects. A more detailed evaluation of these anomalies would require careful comparison of the EM31 data with historical records for Pit 9 and the use of other geophysical data sets. These efforts are beyond the scope of the current report.

Pit boundaries cannot be delineated using the SRIP EM31 data because the survey does not extend far enough beyond the perimeter of the Pit 9 area. Data must be collected well beyond the area of interest so that background conductivities can be observed and used to make a uniform evaluation of the pit boundary on all sides.

Magnetometer. The magnetometer was not operated while mapping Pit 9 due to vehicle interference shown at the CTP.

Radiological. To test the efficacy of surface radiological measurement on the SDA, high quality gamma-ray measurements were made manually using a germanium spectroscopic system. These measurements exhibited a 30-fold increase of photon flux. This spectrum reveals no new energy lines, other than the naturals given

in the background data. Therefore, the surface radiological survey attests only to the existence of radiological waste sources, but does not reveal their isotopic content or size.

Remotely gathered gamma spectroscopic data were reduced to calculated exposure. The earlier high resolution germanium measurements indicated that more thorough isotope analysis was not warranted. Figure 20 shows exposure on Pit 9. More detailed soil mechanical and chemistry analysis would enable a more exact exposure calculation for Pit 9, but is outside the scope of this report.

Organics. No volatile organic data were found above the limit of detection other than those attributed to vehicle exhaust. Figure 21 shows typical data from the photo-ionization organics detector.

Idaho Chemical Processing Plant

Only the GPR and the EM31 were used during mapping operations at the ICPP. Information that could have been obtained from the additional instruments was not of interest to the High-Level Waste Tank Farm Replacement Project.

GPR. On August 22, 1991, the GPR system was tested at a CPP test site. The site contained a steel pipe and a plastic pipe that were buried at a depth of 8 ft. Repeated traverses of these targets yielded a set of control settings that were believed to be optimum. These settings were used for subsequent GPR surveys at several CPP locations. The data collected at these locations are currently being processed and analyzed.

EM31. Processing and evaluating the ICPP data are currently in progress. The deployment of the EM31 for the ICPP work was identical to that used for Pit 9. The quality of the ICPP data is similar to previous results. Buried utilities are clearly detected by the EM31 data in several locations where they are known to exist from engineering records. Linear anomalies occur in some locations where there are no records of buried utilities. The evaluation of these anomalies is in progress.

QUALITY CONTROL

Instrument Calibration

Each instrument package used in the Subsurface Mapping Project was supplied by an expert who also provided training, operating instructions, and calibration procedures. During operation, each instrument was calibrated as dictated per instructions and expert recommendations. The location and orientation of the calibration point (different for each test site) was repeated each time to maintain a reference. At approximately one hour intervals, the vehicle was returned to the calibration point for reference data collection.

Data Management

Due to the fact that instruments were contributed by many laboratories, data was collected on a variety of computers during SRIP operation. However, all data acquisition instruments utilized IBM-compatible computers either directly or for data analysis. USRADS data was transmitted in real-time to the IBM-AT base station where it was stored in an USRADS-compatible format. LLNL's instrument applications, the NaI spectral detector and the organic detector, required that a time stamp be added to the USRADS positional data. The time stamp allowed the data files, which included the time a sample was taken, to be correlated to the vehicle position. Files were named appropriately to the date of testing and/or tied to the test site and were transferred to floppy disk as necessary. Generally, one copy was kept by the SRIP operating team for backup and two copies were supplied for analysis and distribution. Time-stamped organic and NaI spectrum data were sent to LLNL for analysis. GPR data was collected on a ruggedized hard disk mounted on the vehicle. Data transfer required removal of the hard disk and transfer of the data to a floppy disk. The data was then transferred for archive and a copy sent to PNL for analysis.

Data Quality

Data analysis in support of the Subsurface Mapping Project consisted primarily of comparisons of the remotely-obtained data to conventionally-obtained data. Quantitative analysis of the data to determine information such as sensor accuracy was not part of the project scope. The information provided below, therefore, is qualitative in nature.

GPR. The quality of the GPR data was not affected by operation on the SRIP vehicle. The data, however, did not provide useful information. The lack of anomalies in the data stream was attributed to the soil type present at the INEL.

EM31. The overall quality of the EM31 data was considerably improved from the quality observed in the initial Cold Test Pit experiment. The main reason for this quality improvement is the successful application of the time-lag correction and modification of the SRIP to eliminate the offset correction.

The noise level for the SRIP collected data is still somewhat higher than for conventionally-collected data, as evidenced by the erratic anomalies that appear in the low amplitude portions of the SRIP data sets. The specific source of the remaining noise is unknown. However, the low-level noise does not affect interpretation of metallic debris and probably will not substantially affect interpretation of pit boundaries.

The anomaly resolution provided by the closely spaced SRIP data is a clear improvement over the resolution produced by typical conventional surveys. Conventional data can be collected at closer spacing but not at the rate possible with the SRIP Vehicle. The significance of the additional anomaly details obtained from the closely spaced SRIP data has not been evaluated.

Magnetometer. The quality of the magnetometer data was completely degraded by vehicle interference. It is likely that significant changes, both in the magnetometer and in the method of deployment, will be required to successfully collect magnetic data using the SRIP.

Radiological. The surface gamma survey revealed surface maps of areas of gamma-producing waste, while the actual source remained obscure by other unknown factors of soil overburden and isotopic composition. The data taken from the vehicle matched manual data, but with a slight change in gamma efficiency. No vehicle-provoked noise or interference was found.

Organic. The organic data quality was reduced due to occasional readings above the limit-of-detection caused by vehicle exhaust.

LESSONS LEARNED

The lessons learned consist of an evaluation of the specific mobile vehicle utilized in the demonstration, comments on sensor use and integration, and comments on the integration of development staff and their hardware into an operations environment. SRIP and its associated operator interface were used for this particular demonstration because it was a package that could be delivered relatively quickly and inexpensively. When the demonstration was originated, it was agreed that this platform would not be ideal for subsurface mapping and that there would be limitations to what the vehicle could accomplish. Some sensor problems were anticipated, while others were not; but part of the commission of the task plan for FY-91 included a survey of sensors and an evaluation of their usefulness with an identification of problems to overcome. The difficulties in interfacing development hardware and staff into an operations environment were not sufficiently anticipated. Necessary support for future operation of development hardware under such conditions and the transition from development hardware to operating hardware will be discussed.

Vehicle

The SRIP was specifically developed as a general purpose test platform for military robotics. The constraints for that design task led to a large, heavy, and complex vehicle with a diesel engine and skid steering. The vehicle has undergone extensive modifications almost on a yearly basis as project needs have shifted. As these changes have occurred, vehicle weight and electrical power consumption have risen dramatically, taxing the originally satisfactory 15 hp diesel engine past its limit. The INEL soft dirt caused bogging down during turns, compounded by the underpowered drive capability, frustrating some skid steering motions. This required a back and forth motion to navigate 180 degree turns if the vehicle dug into the surface.

The undersized and overtaxed engine also contributed to a habitual overheating problem. Computer cabinets on SRIP were found frequently to exceed 100°F and to go as high as 115°F. Even though no electronics failure occurred on SRIP, these temperatures are unacceptable for this kind of equipment, dictating the use of active cooling.

Onboard control electronics should be impervious to weather and capable of running for extended periods of time in order to support survey requirements. SRIP design criteria required power-hungry, full height VME computer boards that required extensive air exchange for cooling and opened the control boxes to the environment. Totally sealed enclosures are a must for the environment encountered to prevent dust and moisture from entering either during operation or storage. It is also very likely that decontamination requirements will eventually dictate that any platform be capable of being washed down.

Vehicle size and configuration are another significant issue. SRIP weighs approximately 4,500 pounds and is physically about the size of a Volkswagen Beetle. This size and weight make it impossible to store in a small, enclosed trailer. The vehicle weight and track also make it difficult to use normal car trailers for local transport. Vehicle speed is acceptable for survey, but too slow for self transport from storage to the survey site. In the future, considerations must be made for adequate transport and protection of the sensor deployment vehicle, preferably a closed trailer into which the vehicle could be driven. No auxiliary equipment should be necessary to load and unload equipment from the storage trailer.

Vehicle and engine size and fuel tank size effect the available runtime of the platform during surveys. It is important that a full day survey be accomplished without having to refuel. Fuel is a controlled hazardous substance on site that cannot be obtained on short notice. Surveys should not be affected by the need for fuel stops. Runtime capacity at full load should be four to eight hours. SRIP was frequently run six hours a day in two 3-hour sessions.

While skid steering allows the vehicle to turn within its own length, the rigid axle system does not allow smooth transitions over rough terrain. This increases the shock on computers and delicate sensor data acquisition equipment. The vehicle is also prone to skewing back and forth and bucking up and down as the terrain changes and individual wheels leave the ground. The change in sensor orientation and elevation from the ground has been deemed unacceptable by the sensor experts. The ideal approach would include independent suspension on all wheels. However, this would probably reduce the maneuverability of the vehicle, as well as increase the weight.

The vehicle should be highly maneuverable. Subsidence, marker posts, drainage ditches, dikes, hills, and banks were all present during survey operations. For maximum maneuverability, with the ability to take data as close as possible to the various obstructions, vehicle appendages should be minimized and trailers should be avoided.

One issue that is difficult to resolve is the level of acceptable complexity. The fielded vehicle should be as simple as possible in order to maximize reliability. From the SRIP experience, a few general recommendations may be made. The number of switches, buttons, and relays should be minimized. These components are highly susceptible to corrosion and soiling. "Sealed" switches and relays frequently failed due to dust contamination. Mechanical systems should also be as simple as possible, using readily-available commercial components whenever possible. Hydraulics are a possible solution to many drive requirements. A major leak on a DOE waste site, however, could become a major reportable occurrence that could stop work and divert efforts to the generation of volumes of paperwork. A final note on complexity addresses ease of daily maintenance and ready access to all components. For example, SRIP had all engine access features--engine oil, gear oil, hydraulic fluid, etc.--under a large heavy metal shroud which required the removal of several screws. These functions were checked daily. Vehicle design should accommodate repair and maintenance of all modules.

Communications

Radio frequency transmission required daily cabling and antenna setup. The wind frequently knocked down antennas, sometimes damaging them. If possible, antennas should be permanently mounted on the control van. In the deployed position, they should be as high as practical. SRIP operation is desirable at the RWMC at ranges over one mile. Frequencies for data and video must be high enough to allow adequate data transmission and bandwidth, but low enough such that line of sight is not required for transmission. Buildings, valleys, and hills can frequently block the operator's direct view. An additional convenience would be the availability of two-way headset radios.

Operator Control Station

The SRIP operator console was specifically designed to maximize functionality and to provide forklift transportability within the constraints of specific military customer requests. It was not optimized for long-term operations with respect to human factors. Survey activities at INEL sometimes included more than six hours of run-time in one day.

Remote viewing is a focal point of teleoperated systems. The operator's remote driving efficiency is dependent on the quality and positioning capability of the viewing system. The SRIP console has two 13 in. monitors mounted one over the other. The viewing angles are relatively comfortable, but not optimal. Human factor guidelines state that for the given viewing distance, the 13 in. monitor size should be adequate. It appeared, however, that distortion from radio frequency interference, reflections, and non-line-of-sight transmission would have made it easier to view if the monitor had been larger. Side-by-side monitoring of the main viewing monitors would have been preferable. Situations frequently arose that required a quick look to either side of the vehicle as it passed an obstacle. This could not be accomplished with the slow moving pan and tilts with multiplexed controls mounted on the SRIP. At the very least, pan and tilts should have separate joystick controls. A hands-off method would be even better—either head-mounted or voice command control. Any hand controls should be readily accessible and not require the driver to remove his eyes from the video monitor.

Menus seem to suit status displays and major function selections, such as initial setup. However, they are not really appropriate for functions such as forward/neutral/reverse selection when changes have to be made in the middle of a survey. A lever would have been better. A control chair should be integrated into the control console with all displays and controls within easy reach. On the SRIP console, the chair was always in the way of some equipment and never part of the system since it was not built in. The remote driving controls were intuitive and easy to use—a simple steering wheel and accelerator pedal. Welcome added features would have included a slow-speed cruise control for surveys and an overall map showing the path the vehicle traversed. The USRADS

computer-generated map was available and useful, but had to be set off to the side where viewing was not comfortable.

Since this was a temporary installation, the SRIP hardware was mounted in a Ryder rental moving van with a rollup rear door, a translucent top, and no air conditioning capacity for the rear compartment. Dust, temperatures inside the van as high as 105°F, and a light level too bright to conveniently view screens were daily hindrances to operation. A permanent control vehicle should be provided for future work in order to reduce equipment failures and provide proper support for operators. The van should be sealed from dust and have a normal human access door to provide a clean environment for computer equipment. Temperature control must also be provided with enough capacity to manage personnel and the large cooling load required for equipment, as well as solar load. Where possible, equipment should be built-in or self-deployable to minimize setup/breakdown times. Power generation should be built into the control van, complete with adequate fuel storage for a full day of operation and a clean uninterruptable power supply for protection against temporary dropouts and noise. Ideally, the van would also be capable of minimal fuel and support fluid storage for the remote vehicle's maintenance. Organized storage space should be provided to store spare parts and documentation without interfering with the operational area. A work table for equipment repair and data analysis should be included and rudimentary bathroom facilities would be appreciated.

Sensors

Most findings regarding sensors were suspected prior to the survey. It must be emphasized that the primary objective of the project was to prove the feasibility of remote surveillance, not the collection of data. It was simply deemed appropriate to obtain useable data in the process, if possible. As expected, the magnetometer did not work with a ferrous metallic object such as SRIP in close proximity. The magnetometer is an important geophysical sensor, but further vehicle and sensor development is necessary before it will become effective in automated surveys. Even the EM31, which overall worked very well, is affected somewhat by the metallic presence of SRIP.

All instruments that were not tied directly into the USRADS real-time data acquisition computer could have benefitted from more complete integration. However, physically separate control modules, proprietary software, borrowed hardware that could not be cannibalized, and limited time and funding constrained overall system integration. Future efforts should emphasize combining the instrumentation and data acquisition tasks onto as few processors as possible. This is a nontrivial task which requires the writing of significant software.

The real-time data display was useful during the surveys. Its worth, however, may have been overestimated. Realtime displays identify areas of interest and provide a gross perspective of site condition. The actual requirement should be for fast turn-around data analysis and detailed hard copy output for documentation of the completed survey. Most of the people who will need to examine the collected information will not normally be present at the survey site. Data archiving should also be an issue that receives attention.

Development Activities

Through this project, development personnel from many DOE laboratories have invested an extensive amount of time in the field in an operations-oriented environment. Developmental equipment and personnel are typically used in more accommodating situations. Field use during most developmental activities is usually restricted to short-duration endeavors where the reality of site requirements are not fully realized. The value of this investment, therefore, should not be underestimated.

The DOE field operations environment is a difficult one for development activities to flourish. Development of robotics technology obviously centers on the deployment of hardware and software for specific tasks. In a controlled environment, little else needs to be considered. In the operations environment, however, a much larger percentage of available time must be devoted to peripheral activities such as training and interfacing/coordination with operations personnel. Available facilities support must be evaluated. Weather conditions can certainly not be excluded.

Developmental activities in support of operations will be expected to meet all applicable regulations. OSHA training, site specific training, and radiation worker training were all required for the Subsurface Mapping Project personnel. These requirements will only increase as the environmental, safety, and health issues are progressively implemented by OSHA and DOE Tiger Teams. In addition, daily/weekly constraints on activities at operations sites are regulated by work permits designed to ensure worker safety in the hazardous operating environment. Development personnel must make adjustments to their estimates and expected schedules to accommodate these requirements of the operations logistics.

Available facility support also has significant impact on development activities. At the RWMC, only open sheds were available with moderate protection from wind, rain, and temperature extremes. The storage areas were sometimes a significant distance from the test site. For the distant sites, the equipment was either left on-site or a long daily transport time had to be tolerated. The availability of electrical power and vehicle support fluids was also a constraint. Fuel, engine oil, antifreeze, etc., were all restricted items on-site and obtainable only on requests which then required negotiating a delivery time. It is important to note that all fuel had to be stored in proper flammable fluids control cabinets. At RWMC, diesel fuel was more readily available than gasoline due to the prevalence of construction equipment in the area.

Finally, operations personnel should be instructed on the purpose, focus, and requirements of development hardware. This is especially important since it will be necessary to use development hardware for much of the initial work performed in support of environmental remediation. Development personnel should realize that most people do not understand the current state of robotics and sensor technology. Development vehicles do not typically exhibit good reliability. Limited funding for development vehicles tend to push design decisions in the direction of capability at the expense of reliability, maximizing the ability to achieve research goals. Production vehicles minimize costs by forcing design decisions in the direction of simplicity, which limits capability, for the sake of reliability. Mission success depends on the reliability of the platform for the length of the expected performance. Typical development platforms should not be used for anything but minimal demonstrations. Substantial schedule and budget margins should be provided for unexpected maintenance and operational inefficiencies incurred while using such platforms.

RECOMMENDATIONS

The Subsurface Mapping Project has led to direct changes in suggestions for future work. A new deployment vehicle should be used for future characterization work. It should be smaller, lighter, less complex, more reliable, more environmentally tolerant, and have a lower metallic content than SRIP. The operator console and control van should be designed as an ergonomic package able to support extended operations with minimum external facility support. The control van should also provide environmental controls sufficient for both personnel and equipment. Multiple sensor integration must be more complete, but this task will require extensive development of both hardware and software. Current real-time data display is adequate, but more effort needs to be spent on data analysis and hard copy presentation.

The high data acquisition rates that are possible using the SRIP vehicle constitute a significant advantage over conventional surveying. It is, therefore, preferable to increase the speed of the sensors (rather than slowing the vehicle) in cases where sensor time lag is a concern. Editing and processing of sensor data should be made integral with the vehicle positioning system so that real-time display is achieved. This work should be part of a versatile data display work station that provides options for the display and comparison of the multiple data sets acquired by the vehicle.

Data transfer between the data acquisition system and the data display should be improved. This proved to be a painfully slow process. In the future, the conversion of data to an ASCII file should be automated with columns corresponding to the x, y position of the vehicle and the sensor's measurement. A 3.5-in. disk drive should be available to transfer data from the data acquisition system to floppy disks for distribution and analysis.

The visualization field is new and improving daily. In the future, it would be wise to continue to observe other visualization products such as *AVS*, *Explorer*, *VoxelView*, and *Data Visualizer*. One function which *PV-Wave* does not presently support, but some of the other products do, is semi-transparent volume rendering of data. This function may be used to combine individual GPR scans into a 3-D volumetric image.

CONCLUSION

Deployment of multiple sensors on a vehicle was found to be an efficient means to collect surface characterization data. However, the vehicle and associated instrumentation must meet the demands of the task for efficient use. The surface data results fell well short of adequate characterization to help with site cleanup.

While operations-related goals for the subsurface mapping task were overly optimistic, significant progress was achieved in understanding the requirements for vehicle and control station configuration, sensor deployment, and data analysis. Reliability and maintainability requirements for future platforms have been identified. Sensor interactions and performance characteristics have been examined. Information from the Subsurface Mapping Project is currently being incorporated into the design scope for FY-92 work.

Efforts are underway to develop a Remote Characterization System (RCS) which will feature multiple sensors, a platform design that minimizes effects on sensor performance, modular and reusable subsystems, and integrated real-time data display. This effort is being driven by the lessons learned during the testing at the INEL. The ultimate goal of this effort is to provide a means for conducting buried waste site characterization that is safer, faster, and cheaper than current methods.

Figure 1. Soldier Robot Interface Project (SRIP) vehicle.

Figure 2. EM31 data versus vehicle position.

Figure 3. Three dimensional and respective two-dimensional plots of EM31 data

Figure 4. Example GPR data plot (data obtained from Hanford).

Figure 5. GPR data from the Cold Test Pit: (a) raw data, and (b) filtered data.

Figure 6. GPR profiles from the Cold Test Pit.

Figure 6. (continued).

Figure 7. EM31 quadrature data from the Cold Test Pit: (a) SRIP and (b) conventional. Dots show data points. Contour interval = 5 mmhos/meter.

Figure 8. EM31 inphase data from the Cold Test Pit: (a) SRIP, (b) conventional. Dots show data points. Contour interval = 5 (unitless).

Figure 9. Robot (a) speed and (b) heading during one hour Cold Test experiment.

Figure 10. Total magnetic field data from the Cold Test Pit: (a) conventional, (b) SRIP. Dots show data points. Contour interval = 500 gammas.

Figure 11. Cold Pit Test manually read, surface radiological exposure, $\mu\text{Rad/h}$, calculated by the energy method. (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views.

Figure 12. Surface radiological exposure, $\mu\text{Rad/h}$, calculated by the energy method. INEL, Cold Test Pit. (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views.

Figure 13. Am-241 gamma data, in counts/s, Am region-of-interest. INEL, Cold Test Pit. (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views. (All data found below the limit of detection.)

Figure 14. Cs-137 gamma data (world-wide fallout), in counts/s, Cs-137 region-of-interest. INEL, Cold Test Pit. (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views. (All data found below the limit of detection.)

(a)

(b)

(c)

(d)

Figure 15. K-40 gamma data (natural, soil-borne), in counts/s, K-40 region-of-interest. INEL, Cold Test Pit. (a) 30-deg. (b) 120-deg., (c) 210-deg., and (d) 300-deg. views. (All data found below the limit of detection.)

Figure 16. Tl-208 gamma data (natural, soil-borne thorium series), in counts/s, Tl-208 region-of-interest. INEL, Cold Test Pit. (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views.

Figure 17. GPR data from Pit 9: (a) raw data. (b) raw averaged data. (c) running averaged data.

Figure 18. EM31 inphase data from Pit 9.

(a)

(b)

(c)

(d)

Figure 20. Surface radiological exposure $\mu\text{Rad/h}$, calculated by the energy method. INEL, Subsurface Disposal Area, Pit 9, (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views.

Figure 21. Surface organic vapor, detected by a photo-ionization detector. INEL, Subsurface Disposal Area, Pit 9, (a) 30-deg., (b) 120-deg., (c) 210-deg., and (d) 300-deg. views. (All data found below the limit of detection.)

BIBLIOGRAPHY

Department of Energy, Environmental Restoration and Waste Management Robotics Technology Development Program, Robotics 5-Year Program Plan (DOE/CE-0007T).

D. A. Arrenholz, J. L. Knight, (1991), A Brief Analysis and Description of Transuranic Wastes in the Subsurface Disposal Area of the Radioactive Waste Management Complex at INEL, EGG-WTD-9438, Rev. 1.

Grace, J. W., 1978, "Evaluation of Methods for Subsurface Exploration at the RWMC," EG&G Idaho, Inc., Report No. PR-2-78-011.

Horton, K., Isaacson, L., Morey, R., and Finnegan, E., 1981, "An Evaluation of Ground Penetrating Radar and Electrical Resistivity for Assessment of the Radioactivity Waste Management Complex, Idaho National Engineering Laboratory," Geo-Centers, Report No. GC-TR-81-188/3.

Sandness, G. A., Rising, J. L., and Kimbrough, J. R., 1979, "Geophysical Surveys for Buried Waste Detection at the Idaho National Engineering Laboratory," Pacific Northwest Laboratory, Report No. PNL-3227.

END

**DATE
FILMED**

6/02/92