2

WSRC-IM--90-83-2

DE92 009961

Reviews of Computing Technology

The Role of Imaging Technology in Advanced Document Systems (U)

WSRC-IM-90-83-2

December 1991

Westinghouse Savannah River Company
P. O. Box 616
Aiken, SC 29802

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Received by OSTI
MAR 19 1992

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

MASTER

Reviews of Computing Technology:

The Role of Imaging in Advanced Document Systems (U)

by B. J. Hudson

WSRC-IM-90-83-2

December 3, 1990

Authorized Derivative Classifier

G. F. Hayhoe

Westinghouse Savannah River Company
P. O. Box 616
Aiken, SC 29802

Table of Contents

1 Introduction	1
Overview of the Technology	1
Advantages	1
Disadvantages	2
2 Supporting Technology	3
Image Systems	3
Raster Scanning	3
Workstations	3
Networks	4
Databases	5
Optical Disk Storage	5
Optical Character Recognition	6
3 Current State of Image Systems	9
Applications Areas	9
Costs	9
Level of Integration with Existing Computing Systems	10
4 Future Directions of Image Systems	11
Image Retrieval Times	11
Integrating Images into the Office Document Architecture	12

5 Conclusions	15
--------------------------------	-----------

1 Introduction

Overview of the Technology

For each of the past three years, publications and conferences in the records management field have proclaimed that "Imaging has arrived" and predicted over \$1 billion in sales for the coming year. Although image system sales are increasing, the industry has not yet seen the predicted boom in sales or in everyday use of image systems by significant numbers of users.

The fundamental concept of an image storage and retrieval system is the scanning of paper images into black and white dots stored in a computer file. A conventional database in which the bibliographic characteristics of the pages has been indexed (perhaps a memo, manual, insurance policy, or newspaper clipping) also points to the image file which can be displayed on high-resolution workstation monitors. The technology is based on the same concepts as the FAX machine, except that the images are stored on disk for later retrieval rather than being transmitted. Others liken it more to a digital microfilm viewer or electronic xerox copies. Regardless of the analogy used, the technology holds potential for anyone to view the image of any page produced or received by an organization within seconds at the desk, and the ability to print it, route it for others to see, or combine it into a new document.

Advantages

Perhaps the most appealing aspect of image systems is the full and faithful reproduction of the form and content of the pages stored. Current systems offer the capability to scan page sizes as small as credit card receipts and as large as E-sized drawings (34 by 44 inches). Any graphics, illustrations, text, forms, or tables are exactly reproduced. Images of photographs are slightly less sharp but highly legible. The pages are available to multiple users simultaneously, so there is no "out of file" condition or misfiled documents as typically found in paper storage and retrieval systems. Given proper database design and protection schemes, designated users may have full and free access to all

documents, while others may be restricted to only the documents or pages for which they have permission.

For over a decade, there has been talk of the "paperless office," and image technology may play a major role in approaching that goal. There is no doubt—and it has been demonstrated at several Westinghouse sites during the past year—that much of the paper routed can be eliminated with image technology. Also, the time between the delivery of a document to the scanning room and its availability to recipients can be under one hour, with subsequent retrievals in under 10 seconds. As will be discussed later, however, image systems are only a part of the total approach to advanced document management systems and actually decrease in use as supplementing technologies become prevalent over the next ten years.

Disadvantages

Perhaps the greatest disadvantage of an imaging system is what has also been cited as a major advantage: the full fidelity reproduction of the page's image. Although the text and graphics on the displayed page appear to be letters, words, or vector graphic information, the image is merely a collection of black and white dots. The text of such pages lacks intelligence and revisability, nor can the content of the documents be searched or browsed for the occurrence of keywords or phrases. While a typed page of characters stored in a word processing file occupy less than 5,000 bytes on a disk, the bitmap image of the same 8 1/2 by 11 inch page would require (when scanned at 200 dots per inch) almost 500,000 bytes of storage. Fortunately, compression algorithms developed by the FAX industry allow this information to be stored in about 50,000 bytes. These image files take 10 times longer to transmit and can be viewed only on high-powered workstations which may require nonstandard monitors. Overall, imaging pays the price by a factor of 10 over text processing for a file that looks good, but has no potential for browsing, self-indexing, revision, or viewing on a conventional character-cell terminal.

2 Supporting Technology

Image Systems

The major components of an image system involve the classical three phases of data processing: input, processing/storage, and output. The input is accomplished by a scanner connected to a PC which processes, then transmits the image file to the host for storage. The host allows retrieval of image files based on text index fields, and transmits images either to a workstation for viewing or to a printer, based on the user request to the index database. The host computer is typically a conventional multipurpose minicomputer with peripherals and drivers to support the specialized aspects of image file compressions and large file storage.

Raster Scanning

A digital scanning device utilizes an intense light source and a sensing device to determine the reflectivity of the paper being scanned. In its simplest and most common form, the scanner determines that if the amount of light reflected is below a certain threshold, the spot on the paper is black. Raster scanning saves the page information as a series of zeroes or ones, each bit depicting the pixel (or dot) in an on or off state. A scan made at 300 dots per inch (dpi) requires about 90,000 bits per square inch, or over 8 million bits (or one million 8-bit bytes) for an 8 1/2 by 11 page. Compression algorithms significantly reduce the actual amount of disk space used to store the image, but in imaging, a picture is worth a million bytes.

Workstations

The demand of image systems for power at the desktop, high resolution monitors, graphic user interfaces, multi-tasking windows, and high-speed data transfer rates may be the driving force to install a new generation of worksta-

tions on all information users' desks in the next five years. At SRS, in anticipation of this and other predicted applications, most workgroups have been installing workstations such as the IBM PS/2 (Model 70 and 80), or the Apple Macintosh II platforms for the past several years, but no application has truly tested the sustained high power demand on storage, memory, and processing speeds that imaging will require. A great deal of speed is needed throughout the file transfer and image display process to achieve user expectations of 4-second-per-page retrieval times. Simply decompressing an image page requires millions of calculations after a compressed 50,000 byte file transfer from the image host. Even under ideal conditions, these two steps alone may require three or four seconds. Although early image systems required the use of proprietary, single purpose platforms, current trends in workstation performance enhancements and vendors' recognition of utilization of industry standard workstations assure that there will no longer be a need for such specialized workstations.

Networks

WSRC, like most major companies, has been exploring highspeed networking (utilizing greater than 4 megabit per second transfer rates) for more than five years. The amount of traffic on such systems has been relatively low, with most traffic consisting of combined terminal traffic and occasional file transfers, seldom exceeding 100,000 bytes. Under these conditions, network performance has been exceedingly good (with peak utilizations under 20%), and during the past few years, vendor products, site network configurations, and predominant networking architectures (Ethernet and token ring) have stabilized. The initial problems of spanning campuses or even facilities miles apart have been solved with the introduction of routers, T1 and T3 lines from commercial carriers, and recently the introduction of fiber distributed data interface (FDDI) products.

Since most network architectures encourage the bridging of the network into smaller LANs which see only local traffic and traffic directed specifically to that leg, the traffic on user LANs will continue to be controllable. However, if all the images in an imaging system are stored on a single host and those images are transferred to workstations that may reside anywhere in the infrastructure, and the LAN which supports the image server (host) will likely be saturated long before any other segment of the LAN if the LAN controller on the host does not become saturated. Calculations for 100 simultaneous users, each requesting a page every 10 seconds, indicate that sustained data transfer rates of 4 megabits per second would be required. Compared to a typical current electronic mail user load of over 500, this activity level may actually be a conservative estimate. Architectural considerations for avoiding this problem are discussed in a later section. Nonetheless, should a higher speed network become available (100 megabit per second FDDI), it should be installed first on the LAN segments which support the image server (and likely other data servers) in the vicinity of data centers and central computers.

Databases

Databases for image systems need not be any different than conventional database systems, with the exception that most products cannot hold a variable-length 50,000 byte field in FAX-compressed format. Therefore, most image system databases hold a pointer to the image file, and that file is retrieved when a user makes a query to the database. There is much discussion whether SQL databases, distributed databases, or any others have particular advantages in an image file environment. Experience has shown that utilizing existing database applications (such as document control, library listings, or accounts payable) which are modified to add the extension to link to the image files hold the most promise for success. A key decision in image system installation is not to get "locked-in" to a particular vendor's so-called image database. By creating a system that is an extension of an existing database, users will continue to use familiar commands, functionality will remain at non-image workstations, and the image files will be unattached and free for transport to any other host or linking from other databases.

Most importantly, for anticipated distributed database applications, the index data and image data might not reside on the same server. Future directions for image systems will lead to distributing image data closer to the user (perhaps on LAN file servers) with a centralized database pointing to those file locations. Also, later transition to another product line, file transportability to other databases, or conversion of media to alternate types would be more difficult if the image data were part of the data file itself. Such an integrated approach is discouraged unless it implements OSI standards for compound documents (discussed below).

Optical Disk Storage

A technology closely associated with image systems is the optical disk. To many, the terms are synonymous, but that is not the case. An optical disk can be used to store any type of digital data (of which an image is one type and a word processing file is another). Optical disks are typically stored online, and mounted on a drive only upon request. In some respects, they are like tapes, but differ in a fundamental respect because they are random access devices. Any file can be directly accessed as soon as the disk is spun up to speed.

When optical disks were originally introduced, their primary selling points were their capabilities for permanent and compact storage. Since a laser beam burns pits into a metal surface of the disk and is used to read the data, the disks are virtually indestructible and should last over 20 years. Over 1 billion bytes (1 gigabyte) of information could be stored on each side of an optical disk and never be erased. The 2-sided platter costs less than \$500 and is 12

inches in diameter. This translates to well under a penny per page for materials (most observers overlook the 20 cents in labor to put it there) to store a document that can never be lost. This phenomenon has been a records manager's dream come true. Since their introduction, the capacity of a platter has tripled for the same price, and rewritable disks are now available. Fourteen inch and 5 1/2 inch disks are also emerging and increasing in popularity. Since the optical platters are semi-transparent and the laser may bleed through the platter, optical disk drives can only read one side at a time, and a platter must be flipped to read or write to the back side.

The most interesting part of any tour of an optical disk-based image system is the "jukebox," a mechanical device for mounting the optical disk platters into the drives when a retrieval request is made. The jukebox consists of three parts: a storage bay (shelves that hold the platters, usually about 80 of them), a robot arm for retrieving and loading the disks into the drives, and the drive bay which holds between two and five disk drives. The mounting of a platter and retrieval of the first page to a workstation typically requires 20 seconds. Next page retrieval and display from a mounted platter takes under five seconds.

The jukebox itself may be the bottleneck in a large image storage and retrieval system. Given 160 separate sides that could be mounted for a retrieval, and only four drives to satisfy requests, there is only a 2.5% chance that the side a user wants will already be mounted when a request is made. If there are 100 users, it is also likely that the side one user just read will be dismounted to satisfy a request by another user before the first user asks to see the next page of the document. More sophisticated systems load the entire file from optical disk to magnetic cache before the platter is dismounted, and service all outstanding requests on a platter while it is mounted. This technique reduces the second and subsequent page retrieval and display times to under five seconds.

The organization of files among the platters must be planned so that the majority of requests can be serviced with the minimum of platters, and the most frequent requests must be staged permanently to a large magnetic drive which supplements the optical storage and acts as a cache. The most elegant approach to image caching is to load the subsequent pages of a document to the workstation memory or disk drive while a page is being viewed, freeing up both the optical drives and host for other processing, and achieving "local" (sub-second) access speed for subsequent page retrievals. This method is not widely available, but if implemented can mask the delays of disk access, as well as network delays.

Optical Character Recognition

A partial solution to the problem of nonintelligent bitmaps representing text characters is now available. Optical character recognition (OCR) can analyze

the bitmaps of typed documents on a line-by-line basis and successfully recognize 98% of the characters on a scanned page, subject to certain restrictions. The image must be crisp—that is, no characters may be touching, and there must be good contrast between the white page and black text. Since OCR algorithms use character features and context-sensitive rules (checking candidate characters and words against a dictionary of correctly spelled words), variable character width and heights usually cause no problems, but acronyms and mixtures of numbers and alpha characters produce unreliable results.

The best application for OCR at present is for self-indexing of documents where the index field is in a pre-defined location on a page and adheres to certain rules (e. g., three letters, a dash, two numbers, or a date) where the number of possible correct results can be limited. Utilizing OCR to produce revisable form word processing files has not proven cost-effective. Due to the variations in margins, rulers, tabs, and hard-returns versus soft returns in a word processing file, the resulting document requires extensive clean-up. Also, 2% of characters are usually not recognized correctly (usually l and 1, S and 8, O and 0, and punctuation marks); as a result, as many as 10 mistakes can be generated on each page.

One interesting possibility for OCR being developed at SRS is the use of OCR to create a text document for browsing, which will lead to the display of the page image on which an item of interest resides. This approach offers advantages over conventional image access using keyword searches which lead to the first page of the document, and require subsequent searching for the content of interest. In this hybrid approach, if the OCR file is sufficiently accurate, it would be made available to users on character-cell terminals or on low-speed network workstations, with optional access to the image of the page if it contains graphic or other non-character regions.

3 Current State of Image Systems

Applications Areas

Image system vendors focus on paper intensive industries such as insurance, legal, drug development, government, and records applications. Increasingly, image systems are also being used for scanning and routing of mail. The image technology is the same, but the software associated with the systems may allow for a simple scan, store, and retrieval application, or complex routing schemes.

Costs

Typically, a medium volume system capable of scanning 4,000 pages per shift, and storage of 3 million pages costs about \$700,000, with software accounting for half that amount. The jukebox may cost about \$200,000 and the scanners about \$35,000 each. Locally attached printers producing 10 to 12 pages per minute cost about \$8,000; higher speed printers are available, but actual printer speeds can seldom exceed 12 pages per minute due to data transfer and decompression rates. A networked printer requires a dedicated PC or minicomputer server costing another \$8,000. An existing host may often be adapted for image use, but eventually, imaging would need to be a dedicated application on a host. Dedicated workstations are recommended for intensive users of the system, particularly those who are involved in the image scanning, indexing, and image quality assurance phases of the system. Such a PC-based workstation, with a 19 inch monitor for full page viewing and high-speed network connection costs about \$8,000. For general use, adaptation of an existing PC for network connection (\$600) and an optional large monitor (\$1,000) is sufficient.

Level of Integration with Existing Computing Systems

To provide wide access to image information, the image architecture and application should allow existing workstations, ranging from terminals to image-capable windowing workstations, to have some form of access to the data. By adding imaging as an extension to an existing database application, a dumb terminal should be able to conduct all database searches and select the documents to view or print. Instead of interactive viewing, dumb terminal users must have the capability to print the images or for pre-fetching the images for later viewing at an image workstation. Many users will treat the system as a "demand printing" system and will never interactively browse images. Although that may not be the ideal utilization of the technology, it will provide an immediate benefit to many people without adaptation of workstations, excessive network use, or involvement of personnel to pull files, make copies, and mail envelopes.

This phased approach to providing full interactive image capability to users allows time for the scanning of the bulk of the documents, during which time the upgrading of networks and workstations can occur. An image system that satisfies less than 50% of the requests made may not be highly utilized since the user would still have to wait for other documents through conventional channels before a search task would be complete. The size of the "critical mass" for image system optimization is unknown, but users must be assured that they will find what they need from the system before they will use it. For this reason, the time between purchase of a system and availability to users is sometimes over six months, time spent loading all the images.

4 Future Directions of Image Systems

Image Retrieval Times

Even though an image system provides access to an image in under 20 seconds rather than the hours or days required by a paper system, users tend to be impatient with an interactive computer process that takes more than a second. At least two components of image technology must change before sub-second response times can be achieved. The workstations must provide higher processing speeds for image decompression, perhaps in the form of co-processors for that task, RAM-disk caches, or more raw processing power. Second, the methods of transferring images to the workstations must be improved. By building on the cache concepts discussed earlier, the image that a user needs next can be moved closer to the user either initially, through distributed image servers, or in the background while other pages are being viewed. While the actual times for transfer and processing may not improve, by accomplishing these tasks in the background, the user will achieve quicker demand response. As long as the jukebox relies on the mechanical arm for mounting, the delay time for first page retrieval will always be longer than that for subsequent page retrievals. Manufacturers anticipate that this delay will decrease to under five seconds in the next few years. If all frequent or recent retrievals are saved in a magnetic shared cache pool, many jukebox retrievals can be avoided.

Recall that a typed screen of text can be viewed on a \$200 terminal over a 9600 baud line in about a second. Capitalizing on this fact, one should not overlook a low-tech solution to document access: the storage and retrieval of text files. With proper administrative procedures, over half of the documents created internally in an organization can be stored in a revisable text form, with imaging reserved for non-text pages, pages with signatures or other hand notations, correspondence and documents received from outside sources, and older documents created before text was being shared or archived. Aside from the obvious advantages of speed and accessibility, the text documents are available for browsing the content, making it easier to retrieve only the portion of a document that is desired. When text processing is coupled with a demand printing system which creates a fully formatted original at speeds up to 90 pages per minute, the unformatted text of documents can

be browsed and retrieved, and the formatted version of the document created and printed at any time.

Integrating Images into the Office Document Architecture

Although image systems are usually standalone applications today, images will soon be treated as another form of data within documents, and systems will allow users to view any part of any document, regardless of data type or origin. A hybrid document concept called compound document architecture (CDA) allows the creation, storage, and retrieval of documents containing text, vector graphic, spreadsheet, image, and even voice data, all accessible to a user through a compound document viewer on a workstation. Current CDA viewers provide content-based searches and retrievals, live links between documents (where the display of a spreadsheet is not contained within the document, but is a view of the spreadsheet stored elsewhere), and adaptive capabilities depending on the capabilities of the accessing workstation. International standards in this area called Office Document Interchange Format (ODIF) are emerging, and products are available now.

A similar document architecture, based on the Department of Defense CALS (Computer Aided Logistic Support) standard SGML (standard generalized markup language), creates documents in a structured format, where, for example, a title text string is automatically "tagged" as a title, and various other parts of a document are identified by "component" type (e. g., illustration, bullet item, text paragraph). Each component type's final format information (font, size, margins, rulers) is contained in header information common to the document, and the document itself consists solely of content. By exploiting SGML methods, a user could conduct a content-based search on only the titles of chapters, or find only the illustration labels (and the associated illustrations) which contain content of interest.

The following observations have been made regarding the state of document processing systems:

- Once a document has been typed, it should never have to be retyped.
- When a document is typed, it is usually intended to be printed.

As long as this second observation is true, there is little hope for a fully electronic document solution. Instead, it should read:

- When a document is typed, it should be typed with consideration of how it may eventually be retrieved electronically.

5 Conclusions

Imaging will have a permanent role in information processing; there may be no stopping it. To prepare for it, the supporting infrastructure must be built. By installing high-speed LANs, and getting users familiar with windowed applications on higher-powered workstations, divisions will be prepared for pilot imaging implementations. It is never too soon to begin identifying the areas for which imaging can provide a complete solution, get the associated databases in order, and begin a plan to completely replace an existing manual system. Be aware that due to the lack of standards, image files must be in an open format for later transfer to a replacement system. Existing image systems will become obsolete within five years as speeds increase, costs fall, and standards are embraced.

Although the emphasis today may be on image system performance improvements, it seems that improving the corporate approach to information and document management has great potential. Creation of "smart" documents and storage of read-only forms of these documents in a compound document architecture coupled with CDA viewers and demand printing may be a more complete solution to document management. With the assistance of compound document architectures, corporations should begin treating documents as unstructured data, and begin efforts to capture, store, share, and index this data in much the same way numerical data is indexed. The advantages of such an approach should be obvious from the foregoing discussion. If image applications are reserved for data which cannot be obtained in a textual or revisable form, imaging may grow for a few years, stabilizing at a level of about 50% of document retrievals.

END

**DATE
FILMED**

4 / 21 / 92