MECHANISMS GOVERNING FINE PARTICULATE EMISSIONS
FROM COAL FLAMES

Quarterly Technical Progress Reports Nos. 3 and 4
Reporting Period: April 1, 1988 - September 30, 1988

DE-AC22-87PC 79743

Prepared for:

U. S. Department of Energy
Pittsburgh Energy Technology Center

Prepared by:

W. D. Clark
S. L. Chen
J. C. Kramlich
G. H. Newton
W. R. Seeker

Energy and Environmental Research Corporation
18 Mason
Irvine, California 92718

and

G. S. Samuelsen
University of California, Irvine

November, 1988

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

Section	Page
ABSTRACT.	ii
1.0 INTRODUCTION.	1-1
2.0 ENGINEERING ANALYSIS.	2-1
3.0 EXPERIMENTAL PROGRAM.	3-1
4.0 FUTURE WORK	4-1
5.0 REFERENCES.	5-1

ABSTRACT

Efforts in this period focussed on modification of the breakup model to accommodate detailed coal and coal mineral matter characterization data available from PSI (1988). Shakedown work on the experimental reactor was completed, as were the modifications to the sizing apparatus, and the global experiments have begun.

Analysis and interpretation of detailed characterization data for Beulah coal has allowed estimation of the loading and size distribution of extraneous mineral matter, the mineral fraction of the coal as a function of the coal size, and the mineral inclusion size distribution of the coal as a whole. This information has been used in a modified Breakup model to estimate the size distribution of flyash resulting from the combustion of Beulah coal. These calculations suggest that both the degree of fragmentation and inhomogeneity of the mineral matter distribution may affect the fine particle yield.

The Isothermal Reactor (ITR), the reactor to be used in the fundamental experiments, has been successfully fired with pulverized coal; and the laser diffraction particle sizer has been applied to measure the flyash size distribution over the 0.5 to 50 micron size range of interest. It has been decided to perform the optical particle sizing measurements off-line on extracted particulate samples in order to alleviate problems encountered in shakedown of the apparatus including: particle accumulation on the windows of the sample cell; insufficient diffraction signal to the particle sizer; and loss of diffraction signal from the smallest particles due to internal reflection in the lens.

In the next reporting period, Engineering Analysis efforts will concentrate on investigating the effects of coal cleaning, and in the Experimental Program the global experiments will continue.

1.0 INTRODUCTION

The overall objectives of this project are to:

- provide a basic understanding of the principal processes that govern fine particulate formation in pulverized coal flames
- develop procedures to predict the levels of emission of fine particles from pulverized coal combustors

Particles in the 0.5 to 10 micron size are of interest because:

- 1) A significant fraction of flyash generated in the combustion of pulverized coal falls in this size range.
- 2) Electrostatic precipitators are least efficient in this size range.
- 3) Particles in this size range are most likely to penetrate to and be deposited in the aveolar passages of the human lung.
- 4) Volatile toxic metals tend to concentrate on the surfaces of fine particles.
- 5) It is not clear which mechanisms contribute to formation of flyash particles in this size range.

The project objective will be accomplished through a combination of literature research, experimentation, and model development and application. The remaining tasks in this program include:

Task 2. Engineering Analysis

Task 3. Experimental Program

Task 4. Reporting

This report describes the work performed during the period from April 1, 1988 to September 30, 1988. Efforts in this period focussed on modification of the breakup model to accommodate detailed coal and coal mineral matter characterization data available from PSI (1988) and on shakedown of the experimental apparatus in preparation for the global experiments.

2.0 ENGINEERING ANALYSIS

The objective of this task is to modify an existing model to allow the formation of fine particulate in pulverized coal flames to be predicted as a function of coal type and firing conditions. This objective will be accomplished in three subtasks:

- Initial Definition, in which a review of the current state-of-the-art of modeling fine particulate formation will be conducted and the requirements for an improved model will be defined.
- Model Adaptation and Development, in which the model outlined in the initial definition subtask will be assembled.
- Data Interpretation and Scaling, in which the model will be exercised against data generated in the experimental program to help interpret and scale the data and to refine the model.

Efforts in this period were concentrated on the model adaptation and development subtask, specifically on the adaptation of the breakup model.

2.1 Breakup

The breakup mechanism as described by Flagan (1978) has been used to adequately describe the size distribution of flyash particles larger than 2 microns. In its simplest form, as shown in equation 2-1, the breakup model assumes that each coal particle breaks up into a certain number (typically 3-5) of burning char particles. The mineral inclusions in each char particle coalesce into a single flyash particle. The resulting flyash size distribution is proportional to the original coal size distribution with the proportionality factor determined by the fraction of ash in the coal, the ratio of ash to coal density, and the number of char particles formed from each coal particle.

$$n(d_p) = p(p/\alpha_v)^{1/3} n_c[d_p(p/\alpha_v)^{1/3}] \quad (2-1)$$

where: n is the flyash particle size distribution
 d_p is the flyash particle diameter
 p is the number of char particles formed from each coal particle
 α_v is the volume fraction of ash in the coal
 n_c is the coal particle size distribution

However, the breakup model in its traditional form tends to underpredict the smaller (0.5 - 2 micron) end of the size range of interest. It is possible that particles in this size range are formed by another mechanism, or it is possible that particles in the 0.5 to 2 micron size range can be adequately described by a more complex form of the breakup model. Equation 2-1 has several simplifying assumptions which may lead to its underprediction of 0.5 to 2 micron particles:

- 1) Mineral inclusions are homogeneously distributed throughout the coal.
- 2) The number of char particles resulting from a single coal particle is a constant, independent of fuel characteristics or flame conditions.
- 3) The char particles resulting from the breakup of a single coal particle are all of equal size.

Workers at the University of Kentucky and Foster Wheeler Development Corporation have performed detailed characterization of several coals under DOE Contract DE-AC22-86PC90751 administered by PSI (1988). One of the most extensively characterized coals to date has been Beulah lignite which has been selected for study in this (EER's) program. Data are available on mineral matter fraction and mineral inclusion size distribution as a function of coal size cut and coal float/sink fraction.

Analysis and interpretation of this data has allowed estimation of:

- the loading and size distribution of extraneous mineral matter;
- the mineral fraction of the coal as a function of the coal size;
- the mineral inclusion size distribution of the coal as a whole.

These estimations are preliminary because certain assumptions were made in the interpretation of the reported data, including:

- The coal size distribution, given on a Rosin Rammler graph, could be extrapolated from 40 microns to 5 microns, and the properties of all coal and mineral matter in the minus 400 mesh (minus 37 micron coal size cut were consistent throughout the extrapolated region.
- The minimum coal particle size was 5 microns and the maximum coal particle size was 250 microns.
- The minimum inclusion particle size was 0.5 microns and the maximum inclusion particle size was 100 microns.
- The size and gravity fractions reported accounted for the entire coal.
- Effects of discrepancies due to interpretation errors and data inconsistencies could be minimized by normalization.

Based on the above characterization of the as-fired coal, the breakup model was applied to predict the size distribution resulting from the combustion of Beulah coal under three extreme cases:

1) The coal is homogeneous and the original breakup model applies. Each coal particle forms a single char particle and the mineral matter in that char particle coalesces to form a single ash particle. This is the classic

breakup model with $p=1$ and α_v constant. Results of this prediction are shown in Figure 2-1 along with the original coal size distribution.

2) Each coal particle forms a single char particle and the mineral matter in that char particle coalesces to form a single ash particle. This is the classic breakup model with $p=1$, except that α_v is no longer a constant, but is input as a distribution which varies with coal particle size and sink/float fraction. Results of this prediction are shown in Figure 2-2. In this prediction, the extraneous mineral matter is considered to retain its original size distribution and the organically bound and included mineral matter are assumed to be homogeneously distributed within a given coal size fraction. It should be noted that the extraneous mineral matter for this coal contributes negligibly to loading of flyash particles smaller than 10 microns.

3) Each coal particle breaks up into a large number of char particles resulting in a single flyash particle for each mineral inclusion. It is assumed that the organically bound mineral matter coalesces with the inclusions in proportion to the inclusion mass. Results of this prediction are shown in Figure 2-3. The inclusion size distribution is relatively flat in the 1-100 micron size range. More than half of the inclusions (and the resulting flyash) fall in the fine particle (less than 10 micron) size range.

Results of the three calculations are compared in Figure 2-4. As expected, the one ash particle per mineral inclusion calculation (Case 3) results in the most fine particles. The distributions resulting from the one ash particle per coal particle assumption as calculated by the original (Case 1) and modified (Case 2) breakup models are generally similar to each other, with a few significant differences. The modified breakup model predicts a sharper peak at about 20 microns, but predicts somewhat broader tails above 70 microns and below 5 microns.

These calculations suggest that both the degree of fragmentation and inhomogeneity of the mineral matter distribution may affect the fine particle yield.

Figure 2-1. Beulah coal and flyash size distributions from breakup model based on homogeneous mineral matter distribution.

Figure 2-2. Beulah flyash size distribution from modified breakup model based on measured mineral matter distribution.

Figure 2-3. Beulah flyash size distribution assuming one flyash particle per mineral inclusion.

Figure 2-4. Comparison of breakup model predictions for Beulah flyash.

Future plans for the breakup model include:

- Adaptation of the model to span the gap between the two fragmentation extremes (no fragmentation and complete fragmentation) using correlations developed based on data from the fundamental experiments and on predictions from MIT's fragmentation model (Sarofim, et al, 1988).
- Expansion of the capability of the model to handle inhomogeneous mineral matter distributions to account for inhomogeneities which must result when the coal (or char fragment) particle size approaches the mineral inclusion particle size.

3.0 EXPERIMENTAL PROGRAM

The experimental portion of this project consists of a study of the fundamental mechanisms followed by a process simulation study conducted at bench-scale. Information from both of these efforts will be correlated with data obtained in another program at three full scale boilers.

During this reporting period the modification of the particle sizing technique has been completed, as have the initial reactor tests. The following section presents a comprehensive overview of the sizing approach, while the next section identifies the results of the initial reactor tests.

3.1 Particle Sizing

The purpose of the particle sizing work is to develop a rapid and reliable means of resolving coal ash particle size distributions. The approach is to modify an existing laser diffraction apparatus. This involves both theoretical and hardware oriented issues. During the past period the theoretical issues involved in the modification have been resolved and the hardware assembled and tested.

3.1.1 Theoretical Background

The purpose of the following discussion is to outline the theory by which the laser diffraction instrument operates. The implications of reducing the size range can then be developed.

The scattering and absorption of light by particles is one of the classical problems of physics. In general, the interaction of light with solid particles or liquid droplets can come about through a number of mechanisms. These include:

- Diffraction
- Refraction

- Scatter via induced dipole moment
- Reflection.

To first principle, all of these processes are described by Maxwell's equations. These equations were solved for the region within and near spherical particles in 1908 to yield the Mie equations. The Mie equations therefore provide a complete description of the interaction of light with spherical particles, independent of wavelength.

The extreme complexity of the Mie equations has led to the development of simplified forms that are appropriate for specialized cases. If the particle is small relative to the wavelength, then most of the light scattering is due to the induced dipole within the particle. This leads to Rayleigh scattering. Of more practical importance for the present case is diffraction, which dominates when the particle is much larger than the wavelength. Diffraction can be thought of as arising from the bending of the light around the edge of an obstruction. This leads both to scattering (i.e., a change in light direction from the original course) and to interference (i.e., light scattered from different particle surfaces may add or interfere).

The Malvern instrument is generally based on diffraction. Specifically, this is Fraunhofer diffraction, which is a simplification which results when the light approaching the particle is parallel, and the scattering is obtained at distances which are large relative to the particle diameter. Figure 3-1 illustrates the geometry that describes Fraunhofer diffraction. The diffraction from the particle will cause a pattern to form on the spherical screen which will consist of a central maximum and a series of light and dark concentric rings. (Note that we exclude any non-diffracted incident light. As shall be seen shortly, this exclusion can be accomplished by use of lenses.)

The maximum intensity occurs at $\omega = 0$ and is called I_0 . The diffracted light at any angle can thus be represented as the product of I_0 and a

Figure 3-1. Conceptual setup for evaluating diffracted light intensity at any angle ω from the initial light direction.

function that gives the shape of the scattering curve. For Fraunhofer diffraction this is:

$$I(\omega) = I_0 [2J_1(\pi d \omega / \lambda)] / (\pi d \omega / \lambda)]^2 \quad (3-1)$$

Here, λ is the light wavelength and J is the Bessel function of the first kind of order one. The value of I_0 is related only to the incident light intensity and wavelength, and to the size of the particle. In general, larger particles are characterized by a higher I_0 and a narrower scattering angle.

The Malvern instrument makes use of these scattering properties by the configuration shown in Figure 3-2. A collimated laser beam falls on a lens. The beam is focused through a pinhole in the detector board which is located one focal length behind the lens. The board is covered with an array of circular detectors, each of which is located at a given radius from the centerline. This setup allows undiffracted light to be dumped into a light trap. The particle shown in Figure 3-2 will exhibit a certain scattering intensity vs. angle relationship. Let us say we wish to characterize the intensity at 3° from centerline. Ray 1 and Ray 2 both emerge from the particle at 3° from centerline. Ray 1 proceeds through the lens and strikes Diode 4 on the detector board. Ray 2 also goes through the lens and also strikes Diode No. 4. Thus, the signal from Diode No. 4 will always represent light that was scattered at 3° from centerline. This means that the signal from the various diodes can represent the $I(\omega)$ vs. ω characteristic for this particle. If two particles are present in the field, the diode signal will represent the sum of the scattering characteristic for the two particles. The following features summarize the optical approach.

- The diode signal is independent of the location of the scattering particle within the field.
- The diode signal represents the sum of the scattering characteristics of all of the particles within the field.

Figure 3-2. Configuration for diffraction sizing instrument.

The instrument operates by (1) assuming a size distribution for the particles, (2) calculating the expected scattering from the assumed distribution, (3) comparing the calculated vs. measured scattering, and (4) adjusting the assumed distribution. These steps are repeated iteratively until the assumed particle size distribution yields scattering behavior which matches the measured value.

The calculation of the scattering from the assumed size distribution is the key point. It is accomplished by use of the "T" matrix as follows:

$$\bar{E} = [T]\bar{X} \quad (3-2)$$

Here, $\bar{X}$ is a vector containing as members the assumed size distribution, as represented by mass fraction in each of the 16 size bins. The T-matrix contains elements which relate a series of scattering angles against a series of particle sizes. As an example consider the situation in which only three diodes are used and it is desired to resolve data into three particle size "bins". The calculation then has the form:

$$\begin{bmatrix} E_1 \\ E_2 \\ E_3 \end{bmatrix} = \begin{bmatrix} T_{11} & T_{12} & T_{13} \\ T_{21} & T_{22} & T_{23} \\ T_{31} & T_{32} & T_{33} \end{bmatrix} \begin{bmatrix} X_1 \\ X_2 \\ X_3 \end{bmatrix} \quad (3-3)$$

Thus, the light energy onto E_1 , the inner diode, will be calculated as follows:

$$E_1 = T_{11}X_1 + T_{12}X_2 + T_{13}X_3 \quad (3-4)$$

Since E_1 is made up of light scattered to only one angle (or more correctly, light scattered to a small range of angles), then it is calculated by summing the scattering contribution from each size class into that specific angle. Thus, T_{11} represents the energy/unit mass of light scattered into the angle associated with E_1 from particles of size class X_1 . The sum of the contributions from each size class will give the total amount of energy onto Diode 1.

The dynamic range of the instrument covers about two orders of magnitude. Thus, a given configuration can, for example, resolve size distributions between 5 and 500 microns. This two order of magnitude resolution band can be adjusted to any point within the range of 1.2 to 1800 microns by choice of lens focal length and by concurrent adjustment of the T-matrix. Thus, the simplistic approach to resolving the 0.5 - 10 micron size range would be to reduce the focal length of the lens to 26 mm. A number of theoretical and hardware issues must be addressed to do this.

3.1.2 Theoretical Issues

The He/Ne laser light used by the Malvern is 0.6328 microns in wavelength. Thus, a 0.5 micron particle is well within the regime of comparable wavelength vs. particle size. This requires the use of rigorous Mie theory to calculate scattering characteristics. The first step is to determine how the Mie calculations compare with those on which the Malvern data reduction algorithm is based in the 0.5-10 micron range.

Diffraction is essentially independent of the composition of the particle. With Mie scattering, however, the induced dipole moment of the particle begins to assume importance. Thus, the calculations require an assumed value of the complex index of refraction ($n = m - iK$) for the coal ash. The value of m is normally about 1.55, while the value for K varies with both ash composition and wavelength. We have elected to treat K as a parameter which is allowed to range between 0 and 0.4. As the Mie equations are complex and extremely laborious to evaluate, a Mie code at the University of California - Irvine was used to develop the plots contained here.

Figure 3-3 compares the I/I_0 vs. angle characteristic for Fraunhofer and Mie scattering. The plot shows that the shape of the energy vs. angle characteristic for these small particles is only minimally affected by the use of the more rigorous and complex Mie equations. The change represents only a few percent, which is well within the error associated with the

Figure 3-3. Scattering angle/intensity relationship.

various experimental parameters. Thus, no alteration of the shape of the scattering characteristic need be considered.

Figure 3-4, however, brings up two problems. This is a plot of the total power scattered per particle, which may be thought of as being proportional to I_0 . The apparent deviation between Mie and Fraunhofer is significant on this log scale. In absolute terms, this figure shows that the smaller particles scatter more efficiently (by a factor of 2-3) than they would based on a strictly Fraunhofer calculation. This is a consequence of the fact that in the Mie range the particles both diffract and emit due to their dipole moment. This means that the results will be at least somewhat dependent on the choice of value for index of refraction. The second difficulty is that signal detection becomes increasingly difficult below 1 micron. Thus, a 0.5 micron particle scatters only about 10 percent of the energy as a 1.0 micron particle when exposed to the same incident light flux. Given a "reasonable" ash size distribution, this problem is mitigated by the fact that the number density for the smaller particles will be much higher than that for the larger particles. Thus, if Figure 3-4 is replotted on a total energy scattered basis rather than on an energy/particle basis, the curve will be much more horizontal.

In summary, the theoretical portion of the approach contains the following elements:

- Change the geometry of the receiving apparatus such that the higher angles associated with the smaller particles can be accommodated by the optics.
- Alter the software to accommodate the increased scattering intensity from the small particles (relative to the Fraunhofer level).

It is key to note that Malvern has introduced Mie considerations into the T-matrix for the shorter focal length lenses. The results are insensitive to index of refraction (e.g., see Figure 3-4 for sizes above about 1 micron). Pure Fraunhofer is included only for focal lengths at or above 600 mm.

Figure 3-4. Mie scattering comparison to Fraunhofer.

3.1.3 Modification Approach

The original approach was to place the sample cell in front of the collection lens, and use a short focal length lens as a means of collecting the widely scattered light. A number of problems were associated with this approach:

- At these short focal lengths, only a short sample cell can be accommodated. This limits the amount of material that can be characterized at any one time.
- The high angles associated with the proposed configuration introduced coma distortion into the scattering result. Coma comes about when parallel light beams arriving at different points on the lens face are focused to different points on the focal plane. This aberration is easily corrected in commercial 35 mm lenses, but only at the price of a substantial reduction in f-number, which renders the lens inappropriate for the present needs.

One means around this is to locate the sample cell behind the lens. As shown in Figure 3-5, the converging light from the lens interacts with the thin sample holder to yield the same scattering result as occurred when the sample was placed before the lens. The size range is then selected by adjusting the distance between the sample cell and the detector ("f" on the figure). Note that the entire arrangement is independent of the focal length of the lens.

The principal difficulty with this approach was the lack of sensitivity associated with the thin sample cell. Under reasonable coal loading conditions, not enough sample was present to yield an adequate signal. A secondary problem was the difficulty in keeping the windows clean.

A single solution to all of the difficulties of dirty windows, inadequate signal, and special lenses was developed. This solution is to perform the optical particle sizing measurements off-line on extracted particle samples. The samples are resuspended in a surfactant solution

Figure 3-5. Optical configuration for sample cell between lens and detector.

designed to eliminate agglomeration. Since the concentration of the particles can be controlled independently, the sensitivity threshold problems are eliminated. By mounting the sample cell between the lens and the detector, the requirements for a special lens are avoided. Finally, if the system is mounted vertically, as shown in Figure 3-6, then only a lower transparent window is needed; the upper surface can be exposed to the ambient. Lastly, since settling within the sample cell can occur only in the vertical direction, the settling that occurs during analysis will not effect either the amount of material within the measurement volume, or its size distribution.

This approach has been implemented and tested on well sized limestone samples with good results. The ability to rapidly collect samples, suspend them, and obtain results will preserve the rapid turnaround goal, while meeting the objectives of high resolution in the targeted size distribution.

One final hardware oriented correction has been incorporated into the data reduction algorithm. Figure 3-7 shows the pathway associated with an individual light beam in the present sampling arrangement. The diffraction of the light will not be affected by the fact that the surrounding medium is water or air. Thus, the light intensity vs. angle characteristic will be the same in both water and air. The difficulty arises when the diffracted light is refracted upon passing through the water/air interface. As shown on the figure, light scattered at 30° from the axis will be shifted to about 42° upon passing through the interface. If the holder is located at the nominal 26 mm from the detector, this light, which would otherwise strike the outermost diode, would miss the entire array. This can be corrected to first order by moving the sample cell to 16 mm from the detector. This will ensure that the light scattered from the particle at 30° will be intercepted by the outside detector.

3.2 Shakedown

The Isothermal Reactor (ITR), the reactor to be used in the fundamental experiments, has been successfully fired with pulverized coal; and the laser

Figure 3-6. Orientation of the laser diffraction system.

Figure 3-7. Schematic showing the influence of refraction at the liquid/air interface on the angle of scatter.

diffraction particle sizer has been applied to measure the flyash size distribution over the 0.5 to 50 micron size range of interest.

In the fundamental experiments, coal is injected into hot combustion gas provided by a precombustor as shown in Figure 3-8. The original plan called for injecting the coal into a combustion gas with an oxygen concentration representative of post-flame concentrations in a coal fired boiler. When this was attempted in the ITR, the coal consumed a significant amount of the available oxygen, and insufficient oxygen remained to allow complete burnout of the coal. This problem was resolved by operating the precombustor to provide a combustion gas of a higher oxygen concentration. Under these conditions, the additional oxygen consumed by the injected coal brought the postflame oxygen concentration down to levels typical of coal-fired boilers. Also, the off-line analysis particle size allows the coal flow rate to be reduced to a lower level so that high oxygen demand is avoided and adequate sampling sensitivity is still available. Adequate coal burnout was observed under these conditions.

Under this experimental format the global experiments have begun. The first variable is oxygen concentration on Utah coal at 1100°C.

3-17

Figure 3-8. Isothermal reactor and precombustor assembly.

4.0 FUTURE WORK

In the next reporting period, Engineering Analysis efforts will concentrate on investigating the effects of coal cleaning, and in the Experimental Program the global experiments will be performed.

5.0 REFERENCES

Flagan, R. C. "Submicron Particles from Coal Combustion." 17th Int. Symp. Combust., p. 97, The Combustion Institute (1978).

PSI Technology Company. Transformations of Inorganic Coal Constituents in Combustion Systems, Quarterly Report No. 5. DOE Contract DE-AC22-86PC90751, January (1988).

Sarofim, A. F., J. M. Beer, and S. G. Kang. "Fundamental Studies of Mineral Matter Vaporization and Residual Ash Formation." Transformations of Inorganic Coal Constituents in Combustion Systems, Quarterly Report No. 5. PSI Technology Company, DOE Contract DE-AC22-86PC90751, January (1988).

ABSTRACT

Efforts in this period focussed on modification of the breakup model to accommodate detailed coal and coal mineral matter characterization data available from PSI (1988). Shakedown work on the experimental reactor was completed, as were the modifications to the sizing apparatus, and the global experiments have begun.

Analysis and interpretation of detailed characterization data for Beulah coal has allowed estimation of the loading and size distribution of extraneous mineral matter, the mineral fraction of the coal as a function of the coal size, and the mineral inclusion size distribution of the coal as a whole. This information has been used in a modified Breakup model to estimate the size distribution of flyash resulting from the combustion of Beulah coal. These calculations suggest that both the degree of fragmentation and inhomogeneity of the mineral matter distribution may affect the fine particle yield.

The Isothermal Reactor (ITR), the reactor to be used in the fundamental experiments, has been successfully fired with pulverized coal; and the laser diffraction particle sizer has been applied to measure the flyash size distribution over the 0.5 to 50 micron size range of interest. It has been decided to perform the optical particle sizing measurements off-line on extracted particulate samples in order to alleviate problems encountered in shakedown of the apparatus including: particle accumulation on the windows of the sample cell; insufficient diffraction signal to the particle sizer; and loss of diffraction signal from the smallest particles due to internal reflection in the lens.

In the next reporting period, Engineering Analysis efforts will concentrate on investigating the effects of coal cleaning, and in the Experimental Program the global experiments will continue.

END

**DATE
FILMED**

6 / 11 / 92