DATE 03 1992

**EVALUATION OF CARBON DIOXIDE EMISSION
CONTROL STRATEGIES IN NEW YORK STATE**

Final Report of 1990-91 Work

S. C. Morris, J. Lee, G. Goldstein, and D. Hill

January 1992

**Biomedical and Environmental
Assessment Group**

Analytical Sciences Division

NOT A COMMITMENT TO A SPECIFIC REPORT

BNL--47110

DE92 010162

**EVALUATION OF CARBON DIOXIDE
EMISSION CONTROL STRATEGIES
IN NEW YORK STATE
FINAL REPORT OF 1990-91 WORK**

S.C. Morris, J. Lee, G. Goldstein, and D. Hill

January 1992

Biomedical and Environmental Assessment Group
Analytical Sciences Division
Department of Applied Science
Brookhaven National Laboratory
Associated Universities University, Inc.

Research Supported Jointly by Empire State Electric Energy Research Corporation,
New York State Energy Research and Development Authority, and the U.S.
Environmental Protection Agency

This research was performed under the auspices of the United States Department of
Energy under Contract No. DE-AC02-76CH00016

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

402

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, sub-contractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency, contractor, or subcontractor thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency, contractor or subcontractor thereof.

ABSTRACT

A MARKAL model was developed for the State of New York. It represents the state's energy system as a set of typical technologies for generating, converting, and using energy as it evolves over a 45-year period. NYMARKAL was applied here in demonstration analyses to explore strategies to reduce CO₂ emissions. NYMARKAL was installed at the State Energy Office and in the Offices of the New York Power Pool. Staff members from both organizations and other state agencies were trained in its use. Example scenarios showed that It is more difficult and more expensive to reduce carbon emissions in New York State than in the United States as a whole. Were a common carbon tax instituted, it would have less effect in New York and most carbon emissions reduction would take place elsewhere in the country where it is more cost-effective. Alternatively, were all states required to reduce CO₂ emission an equal percentage (say by 20%), the cost per unit emissions reduction to New York would be much greater than in the rest of the country.

ACKNOWLEDGMENTS

Several people are due thanks for getting this project started. These include S. Baron and F. Salzano at Brookhaven; P. Torpey of ESEERCO, P. Coffey of the New York Power Pool who as the ESEERCO project officer got the project off the ground and kept it moving; D. Najewicz who, as the initial NYSERDA project officer shepherded the proposal through several rounds of approval at that agency, and B. Solomon of EPA who supported the initial phases of the study. Fred Strnisa and Janet Joseph of NYSERDA took over from D. Najewicz when he left government service. John Lydick, a student intern with our group, made valuable contributions to the initial stages of the study. M. Garrell of Adelphi University contributed to the database on municipal solid waste, landfill gas, solar and wind energy.

The progress and applicability of the work were greatly enhanced by the regular participation of representatives of numerous other state and federal people including J. E. Smith and A. Sanghi of the State Energy Office, A.J. Domaracki of the Public Service Commission, R. Twaddell of the Department of Environmental Conservation, and J. Scheraga of the US Environmental Protection Agency.

We especially thank the New York State Energy Office staff for their interest, cooperation, and assistance throughout the study. In addition to J.E. Smith and A. Sanghi mentioned above, we wish to name the following SEO staff in our thanks: M. Schultz, M. Bowman, H. Sheevers, P. Smith, J. Parmelee, and J. Wang.

We also thank E. Williams of the US Department of Energy Office of Policy, Planning and Analysis who provided approval and DOE oversight for our participation in this study and who funded parallel work on the US MARKAL model that helped to maintain a critical mass of effort at Brookhaven directed toward work on energy systems modeling.

Others whom we thank for their assistance in providing data and/or many helpful discussions include K. Anderson, A. Desell, R. A. Hiney, T. Larson, T. E. Link, J. Ralston, P. Schwengels, R. Stewart, F. Vitale, G. Walmet, and C-O. Wene.

EXECUTIVE SUMMARY

NYMARKAL is a model of the New York State energy system. It represents the State's energy system as a set of typical technologies for generating, converting, and using energy as it evolves over a 45-year period. In a variety of scenarios, the model chooses from a menu of several hundred candidate technologies and energy resources to select the set that meets projected demands for energy services, environmental restrictions, and other constraints at least cost. Among numerous options available are fuel switching, improved efficiency of supply-side and demand-side technologies, end-use conservation, increased use of renewable energy, reforestation, and pollution taxes such as a carbon tax. NYMARKAL was applied here in demonstration analyses to explore strategies to reduce CO₂ emissions. The analyses begin with the same economic forecast used in the State Energy Plan. The energy plan forecasts of fuel and technology trends, however, are based on projections of current trends, modified by environmental regulations and behavioral factors. MARKAL takes a different approach. Its results are based more rigidly on least-cost decision-making. By avoiding some assumptions about behavior and current societal trends, MARKAL is freed to seek potentially better futures. This is especially appropriate when looking 20 to 40 years ahead, an important time-frame for considerations of greenhouse gas emissions. MARKAL can be made to match projections of current trends, but doing that would decrease its real power. Some of the important lessons from a MARKAL analysis can be gained by comparing MARKAL scenarios with trend projections.

MARKAL, an acronym for MARKet ALlocation, is a sophisticated linear program optimization model that captures the complex inter-relationships of energy systems across the spectrum from primary energy supply to energy service demands. It treats demand-side and supply-side investments equally. MARKAL is an inherently flexible model able to address a wide range of energy and environmental issues. It has been adapted for use in many countries to model national, provincial, and local energy systems. Coupled with the MARKAL Users Support System on a microcomputer, MARKAL is a responsive, "user-friendly" modeling system for energy-environmental analysis, planning, and policy use.

Development work consisted of configuring the New York State energy system in MARKAL, developing a database of energy resources and technologies and environmental emission coefficients for New York State, testing the configured model, and developing and analyzing example scenarios. This report describes and documents the development of NYMARKAL and the associated data, and reports the results of example analyses. The actual data and full results of the scenarios analyzed were provided separately in electronic media form.

The objective was to provide a tool for continuing analysis and planning, however, not a one-time report. Analyses reported here serve only as a starting point. NYMARKAL is installed and running at the State Energy Office and in the Offices of the New York Power Pool. Staff members from the Power Pool, New York State Energy Research and Development Authority, the State Energy Office, Department of Environmental Conservation, and Public Service Commission received hands-on training as part of the project.

Several scenarios were analyzed. They were designed to address important issues and to illustrate different ways to use MARKAL. Scenarios examined are listed and described in Table S-1. Each scenario was run without CO₂ constraint and against four different levels of CO₂ constraint: stable at 1990 levels and 10%, 20%, and 30% reduction from 1990 levels in 2008 and thereafter. Not all scenarios had feasible results for all CO₂ reduction levels. The ability to demonstrate the point of technical infeasibility is a useful MARKAL feature. A scenario-CO₂ constraint combination is called a case.

We call the unconstrained case of the Conventional Technology Scenario the "Reference Case" since it is the case most of the alternative scenarios are built upon (by adding technologies or tightening or relaxing constraints on technologies). The reference case is not meant to be a business-as-usual simulation, but it needs to be sufficiently realistic that the results are meaningful lessons to guide future policy. MARKAL produces a least-cost solution under conditions of perfect foresight and perfect economic "rationality." We do not have perfect foresight, but we can use alternative scenarios to test the robustness of decisions under different future conditions. As a society, we base our decisions on a broad range of factors, many of which cannot be easily included in a computer model. We gladly give up some economic rationality or efficiency to address other goals, such as equity or environmental protection.

Table S-1. Scenarios examined and their description.		
File Name	Scenario	Description
BNYS	Conventional Technology	Allows substantial increases in nuclear and 1.8 GW imports of hydropower.
TREE	Reforestation	Adds ability to sequester carbon by planting trees.
QUEB	More Hydroelectric Imports	Imports from Quebec allowed to grow from 1000 MWe in 1993 to 10,000 MWe in 2028. Additional Nuclear also allowed.
TAXC	Carbon Tax	Same as Reference Case with the addition of a \$15/ton carbon tax in 1993, escalating 10%/year. This scenario is an alternative approach to the usual method of fixed emission constraints.
CONS	Increased End-use Conservation	Double end-use conservation opportunities at higher cost added to Reference Case.
NNQB	More Hydroelectric; no new nuclear	Imports from Quebec allowed to grow to 15,000 MWe in 2028. No new nuclear power.

MARKAL points the direction of increased "rationality" and shows how far the system can go in that direction, thus helping to identify the most attractive alternatives to gain specified objectives. In an alternative scenario, we can force a solution that MARKAL, from its narrow view, considers less than optimal (for example, no new nuclear power); this allows us to determine how much we are giving up from the rigid economic efficiency viewpoint. Experimentation with the model may help us find other solutions that achieve the same goals at lesser cost.

Climate change is a global issue. It is being addressed in international, national, and state forums. New York may, on its own, decide to take action to reduce CO₂ emissions. New York may also be required to take action based on national legislation or international agreements entered into by the United States. It is important to understand the costs and other implications for the State and how New York compares with the rest of the U.S. We draw upon our MARKAL analysis of the U.S. as a comparison. It is more difficult and more expensive to reduce carbon emissions in New York State than in the United States as a whole. This can be illustrated by three different comparisons between the two studies:

- Greater emission reductions were feasible in the US than in New York.
- The average cost of achieving stated emissions reduction targets was lower in the U.S. than in New York.
- CO₂ reductions resulting from the same level carbon tax were greater in the U.S. than in New York.

The implication is that, were a common carbon tax instituted, it would have less effect in New York and most carbon emissions reduction would take place elsewhere in the country where it is more cost-effective. Alternatively, were all states required to reduce CO₂ emission an equal percentage (say by 20%), the cost per unit emissions reduction to New York would be much greater than in the rest of the country. If as a nation we wish to reduce carbon emissions, the most cost-effective approach would be to aim at greater emissions reduction outside of New York.

What makes reducing CO₂ emissions in New York more difficult and more expensive? Studies around the world have generally found that reducing CO₂ emissions invariably translates into reducing coal use. Coal provides a substantial fraction of primary energy in the United States and therefore the country as a whole has the capability of significant reductions in CO₂ emissions with the impact largely confined to this single sector. The US also has a bigger and more diverse arsenal of alternative technologies and resources than does New York. For example, geothermal and solar energy are more abundant in other parts of the country.

What do the MARKAL results so far say about *how* CO₂ emissions can be reduced in New York State? What must go, what new technologies or resources should come to the fore? We examined end-use conservation, increased efficiency in use of fossil fuels, fuel switching among fossil fuels (e.g., oil or coal to natural gas), nuclear power, hydroelectric power, other non-carbon energy sources, and sequestering carbon in trees. These are each discussed below.

Advocates of conservation and renewables often argue that these are "no regret" options, that is, even if CO₂ reductions were to prove unnecessary, investment in conservation and renewables will have been money well spent. MARKAL analyses

examine this issue in the following way: technologies that are indeed "no regret" will be selected in the cases with no CO₂ constraints. Our MARKAL analysis eliminates the institutional barriers that impede introduction of these technologies in the real world. Our findings are that conservation indeed enters the energy system rapidly even in the absence of CO₂ constraints. The additional conservation technologies available in the Enhanced Conservation Scenario are sufficient to allow MARKAL to achieve the 20% CO₂ reduction target.

Without CO₂ constraints, renewable energy use increases at a slower rate in New York than in the U.S., but renewables are added faster than in the US as CO₂ constraints are imposed.

Nuclear and Quebec hydropower were the two primary non-carbon fuels that could fill the gap left by reductions in coal and oil to meet CO₂ emissions constraints as demands for energy services continue to increase. Reductions in CO₂ emissions of 10% or more could not be sustained in the model without using one of these sources of energy. If the State wants or needs to do more than stabilize CO₂ emissions, and wants to avoid adding new nuclear capacity, importing hydroelectric power from Quebec or both, other options must be explored. Although solar, biomass, wind and municipal solid wastes are included in the model, opportunities to use these resources in New York are limited. Although MARKAL does not deal directly with behavioral and cultural changes that might decrease energy demands, it can analyze the technological and cost implications of scenarios that depict such changes.

Simply keeping track of emissions of other pollutants in NYMARKAL provides the opportunity to assess the effect of CO₂ constraints on sulfur dioxide, nitrogen oxides, and particulate pollution emissions. Reductions that occur as a result of the systems response to CO₂ constraints are dramatic, especially in SO₂ and particles. A 10% reduction in the level of CO₂ emissions can result in a reduction of other pollutants beyond what has been possible through existing clean air legislation. There are two sides to this result. First, CO₂ constraints can yield substantial collateral benefits in reducing emissions of other pollutants. As with energy conservation, CO₂ constraints tend to push in the direction of more general environmental quality improvement. On the other side, however, it must be remembered that greater air quality improvements have not been made to date largely because of the large costs involved. The fact that they occur automatically as the result of meeting CO₂ emission reduction targets does not make these costs any less burdensome to society.

How much of a reduction in New York State CO₂ emissions is technologically feasible? The demand for energy services in New York State is projected to grow. Without an unlimited supply of energy, at some point this increasing demand must exceed supply, resulting in a technically infeasible situation. When CO₂ emissions restrictions are added, the system becomes further constrained and the point of infeasibility comes closer in time to the present. The question of technological feasibility then is not if a reduction is infeasible, but at what point in the future will a given level of CO₂ emissions reduction become infeasible? The State Energy Office's usual planning horizon is about 20 years. That puts the point at which carbon emission controls are imposed in this study near the edge of the planning horizon, yet it appears that maintaining CO₂ emission goals beyond initial target dates may be harder than meeting initial targets. Therefore, this study looked two decades further into the future, to 2028. Beyond the third or fourth decade of the next century, social and

technological changes beyond our vision can be expected to intervene. New technologies or resources may emerge, technologies may advance beyond expectation, or population shifts, lifestyles or technological changes may result in lower demands for energy services. Global climate change is a problem that requires us to consider consequences much further into future, at least to 2100, but we cannot expect to make detailed projections that far ahead. We can and do need to consider detailed technological options over a 40-50 year future, however, and that is the task on which NYMARKAL focuses.

NYMARKAL helps to provide insight. Sometimes this confirms conventional wisdom but other times it points out overlooked possibilities and fills knowledge gaps. One can gain insight by reading about the results of model runs, but the model can be used to greater advantage. Energy system planning involves an interaction among complex technological, economic, environmental, social, and political considerations. It is through interaction among people from those areas that real advances can be made. NYMARKAL can provide a common framework of discussion for such interaction.

TABLE OF CONTENTS

INTRODUCTION	1
DESIGN AND CONFIGURATION OF NY MARKAL.....	2
Units.....	2
Demand Structure	3
Energy Resources and Carriers.....	3
End-use Conservation.....	4
Electric Power Plants	5
Process Technologies	5
Energy Storage Technologies.....	6
Environmental Emissions.....	6
Emissions Embodied in Energy Imports	7
Emissions During Construction and Embodied in Nonenergy Imports	8
NYMARKAL ENERGY RESOURCE AND TECHNOLOGY DATABASE.....	9
APPROACH AND SCENARIOS EXAMINED.....	9
INTERPRETING THE RESULTS	11
CONVENTIONAL TECHNOLOGY SCENARIO.....	12
Primary Energy Use	13
Single Family Residential Energy Use	18
Multi-Family Residential	21
Commercial	22
Industrial.....	25
Transportation.....	28
Electricity Generation.....	32
Emissions	37
Comparison of Reference Case with State Energy Plan.....	40
REFORESTATION SCENARIO	41
INCREASED HYDROELECTRIC IMPORTS SCENARIO	46
ADDITIONAL HYDRO BUT NO NEW NUCLEAR SCENARIO.....	49
ENHANCED BUILDING CONSERVATION SCENARIO.....	52
CARBON TAX SCENARIO	53
DISCUSSION AND CONCLUSIONS	55
REFERENCES	61

APPENDICES

I. LISTING AND DESCRIPTION OF NYMARKAL OUTPUT FILES.....	63
II. EMISSIONS OF OTHER GREENHOUSE GASES	64
Reference	65
III. DOCUMENTATION OF NYMARKAL DEMAND CATEGORIES AND PROJECTION DATA	66
Demand Categories.....	66
Demand Projections.....	68
IV. ENVIRONMENTAL EMISSIONS COEFFICIENTS	71
References	71
V. DOCUMENTATION OF TECHNOLOGY DATABASE	81
Data Structure And Sources.....	81
Energy Resource.....	82
Conversion Technologies.....	82
Process Technologies	83
Demand Technologies	83
Energy Conservation Data from EASI	84
Reference:	85

INTRODUCTION

New York MARKAL (NY MARKAL) uses the common MARKAL described by Fishbone and Abilock (1981) implemented on a microcomputer with the MARKAL Users Support System (MUSS) described by Goldstein (1991). MARKAL, an acronym for MARKet ALlocation, is a large scale linear program optimization model that captures the complex inter-relationships of energy systems across the spectrum from primary energy supply to energy service demands. MARKAL is an inherently flexible model able to address a wide range of energy and environmental issues. It has been adapted for use in many countries to model national, provincial, and local energy systems. Coupled with MUSS on a microcomputer, MARKAL is a responsive, "user-friendly" modeling system for energy-environmental analysis, planning, and policy use.

NY MARKAL implements MARKAL for the New York State Energy System. Development work consisted of configuring the New York State energy system in MARKAL, developing a database of energy resources and technologies and environmental emission coefficients for New York State, testing the configured model, and developing and analyzing example scenarios. This report describes and documents the development of NY MARKAL and the associated data and the example analyses. The actual data and full results of the scenarios analyzed are provided separately in electronic media format from which they can be reviewed and manipulated much easier by using MUSS. A listing and description of these files are given in Appendix I. The objective was to provide a tool for continuing analysis and planning, however, not a one-time report. Staff members from the New York Power Pool, New York State Energy Research and Development Authority (NYSERDA), the State Energy Office (SEO), Department of Environmental Conservation (DEC), and Public Service Commission (PSC) received hands-on training as part of the project. This report uses examples to provide guidance for further analyses. Detailed users' manuals were provided separately (Goldstein, 1991; Giesen et al., 1989; Fishbone et al., 1983).

The impetus for this work was to evaluate carbon dioxide (CO_2) emission control measures for New York State. The analyses explore least-cost strategies to reduce CO_2 emissions and evaluate the cost of CO_2 reduction under different conditions. Since the energy system is the principal source of CO_2 emissions, an energy systems model is the appropriate context in which to examine reduction strategies. Approaches available to the model to reduce CO_2 emissions include: fuel switching, improvements in technological efficiency, increased use of non-carbon energy sources, incentives for accelerating implementation of new technologies, and technological based energy conservation measures. Reforestation, a potential offset policy for CO_2 was incorporated directly in the model. Besides CO_2 emissions, emissions of sulfur dioxide (SO_2), nitrogen oxides (NO_x), and particles were calculated for each scenario. Although the model, at this point, only addresses CO_2 as a greenhouse gas, separate estimates were included of emissions in New York State of other greenhouse gases to provide prospective on the role of CO_2 emissions from the energy system (Appendix II).

DESIGN AND CONFIGURATION OF NY MARKAL

The configuration of MARKAL is defined by the demand structure and by the resource and technology characterization. The latter refers to the way technologies are defined as opposed to the values in the database, which are covered in the next section. The user has great flexibility in structuring MARKAL, from an aggregate structure with few demand categories and few technologies, each representing a group of technologies, to a highly detailed real-world structure that can get down to the individual plant level. The trade-off is that as the model gets more detailed it is more complex, more difficult to modify, longer to run, and more difficult to analyze the results. If the model is too simple, important distinctions and interdependencies will not be captured, leaving the model inadequate to do the job it was meant to do. NY MARKAL is not simple; it includes 37 demand categories and contains several hundred technologies. The results are still a broad-brush view of the state energy system. This level is suitable to provide a clear overall picture with enough technological detail for most purposes. The beauty of the modeling system is that the analyst can easily increase the level of detail in any specific area for a special study that requires a spyglass be put over a narrow sector, while maintaining the backdrop of the rest of the energy system at the more standard level. Decisions on the level of detail are often a function of the availability of data. For New York State, we matched the way the State gathers and reports data so that the model would fit into the data framework already in use.

NYMARKAL was designed with nine 5-year time periods, the first centered on 1988 and the last on 2028. The dates corresponded to those used in the 1989 State Energy Plan. The time horizon was longer than that of the State Energy Plan because the nature of the CO₂ emissions problem required it. Within limits, MARKAL gives the user control over selecting the number of time periods and their duration, but long usage has proven nine 5-year time periods to be an effective design for MARKAL models. A 45-year time horizon is reasonable for a technologically based model. Development and market penetration lead-times are such that one can confidently expect that, 45 years from now, the energy system will be composed primarily of technologies that are either now available or are well understood and can be characterized. As one goes beyond 50 years, it is more likely that larger and larger shares of the energy system will be based on technologies with characteristics we could not now predict.

Units

To maintain consistency with SEO data formats, energy units in the NYMARKAL database were entered in billion (10⁹) British thermal units (BBtu), electrical capacity units in megawatts (MW), and monetary units in thousands of 1988 US dollars. Pollution emission coefficients are entered in kilograms per BBtu, except for CO₂ emissions that, because of their larger size, are entered in metric tons per BBtu. Because the database deals with unit costs of individual technologies, while the results of the model generally provide aggregate numbers, units in the reports are scaled by a factor of 1000: energy is in trillion (10¹²) Btu (TBtu), capacity in gigawatt (GW), monetary units in millions of 1988 US dollars, pollution emissions in metric tons except for CO₂ emissions that are in thousands of metric tons. The scaling factors for the reports are under user control and can be changed in the MARKAL file "Units.NYS." That file is self-documented.

Demand Structure

Demands for energy services are what drives MARKAL. The basic demand structure includes two residential sectors (single and multiple family), three commercial sectors (office buildings, service buildings, other buildings), an industrial sector and a transportation sector (automobile, light and heavy trucks, bus, subway and urban rail, air, and water vessels). The residential, commercial, and industrial sectors are each further broken down into demand categories (e.g., space heat, water heat, process heat). There are 37 demand categories in all; these are detailed in Appendix III, along with the documentation of the demand projection data. These demands provide the basic drivers for NY MARKAL.

The demand structure is easily modified to suit special needs. For example, if one wished to do a special study of commercial lighting, the existing demand category "Lighting and Appliances" in each of the commercial sectors could be split into "lighting" and "other appliances." Lighting technologies in the data base would be re-labeled, and presumably a broader range of lighting technologies defined. Given the needed information was in hand, making this modification to the existing database would take an experienced analyst only a few minutes. The additional detail could be used either for a special study or could be maintained as a permanent part of the database.

Energy Resources and Carriers

In MARKAL, the term "energy carrier" is used instead of fuel because of its

broader connotations. Energy carriers include wind, solar and hydroelectric; high and low temperature heat used in industrial and district heating systems; and fuels such as coal and oil. End-use conservation is also treated as an energy carrier as discussed in the next section. Energy carriers included in NY MARKAL are listed in Table 1. In the case of renewable energy carriers, such as solar, wind, and hydro, a fossil equivalent energy is defined for accounting purposes, e.g., to calculate values such as total primary energy. Several nuclear energy carriers are defined, but only LWR fuel is currently included in the imports.

Table 1. Energy Carriers in NYMARKAL.

Electricity	Wood biomass
Coal	Residential Firewood
Coke	Herbaceous Crops
Coal-Water Mixture	Microalgae Diesel Equiv.
Carbon	Municipal Solid Waste
Crude Oil	Solar
Kerosene	Wind
Jet Fuel	Wave
Diesel Fuel	Hydroelectric
Light Distillate	LWR Fabricated Fuel
Heavy Distillate	High Temperature Heat
Residual Oil	Low Temperature Heat
Gasoline	Conservation
Liquid Petroleum Gas	Biogas
Natural Gas	Liquid Hydrogen
Pipeline Quality Gas	Hydrogen Gas
Medium Btu Synthetic Gas	Ethanol
Compressed Natural Gas	Methanol
Propane	

Several energy carriers are given distinct names in NYMARKAL for different end-uses for purposes of pollution emissions accounting as discussed below. Also, special energy carriers called "steam turbine fuels" and "combustion turbine fuels" were defined to handle dual-fueled and multi-fueled power plants (Figure 1). The latter processes allow the model to determine the fuel mix.

Figure 1 Schematic view of use of dummy processes (SE1 and SE2) and dummy fuel (CTF) for environmental emissions and optimization of fuel mix for dual-fuel device.

Energy resources are the limited resources from which fuels are obtained, e.g., oil fields and coal seams. New York State is not rich in energy resources. In the data base it was assumed that all fossil and nuclear fuels would be imported. NYMARKAL contains no oil or gas wells, no coal or uranium mines. Further, it includes no refineries or other fuel processing facilities. These assumptions are not strictly true. There is some oil refining in New York as well as some coal and gas production, but the amounts are insignificant when examining the state energy system as a whole. There may be cases in which one might want to consider opportunities for increased natural gas production in the state. These were not examined, but could easily be added.

While the sun, wind, and waves are potential energy resources, they are not generally included as such in MARKAL; constraints on use of these renewable resources are placed on the technologies that convert them to heat or electricity rather than limiting the resource itself. Domestic resources included in NYMARKAL are wood, herbaceous crops, and municipal solid waste.

End-use Conservation

Efficiency of end-use devices can be explicitly specified in the MARKAL database. Many technological approaches to end-use conservation, however, are not well characterized by changes in efficiency. The best examples are building shell conservation measures such as adding wall and ceiling insulation. These decrease the demand for energy services, in this case for space heat. Demands are exogenously specified in MARKAL, however, so to allow MARKAL control over building conservation, a dummy fuel called "conservation" was invented. Building shell conservation technologies, fueled by "conservation," are then characterized in the database in the same way as are other

technologies. MARKAL can choose to buy building conservation as a means of meeting space heat demands. Increased efficiency in motor vehicles are treated in the same way. Limits are placed on the amount of the total demand that can be met by conservation. Energy conservation is an energy savings from the norm. We assume building conservation in the base year (1988), for example, to be zero. This is not because 1988 buildings have no insulation, but because we take them as the standard; there is no absolute point for zero conservation. In the industrial sector, many of the conservation measures included are from SEO's database developed from the Energy Advisory Service to Industry (EASI). These are mostly retrofit measures. We assume that these retrofit conservation measures would be inappropriate for industrial facilities built after 1998, and so this conservation option dies as existing industrial facilities end their useful life.

Electric Power Plants

Existing electric power plants were characterized in NY MARKAL in more detail than in typical MARKAL applications. Existing plants are defined by vintage (10 year intervals) and type. This allows use of these plants to be tracked or characterized separately and facilitates analysis of questions of early or extended retirement and retrofitting of pollution control devices. Fifty-one types of electric generation plants are described. Twenty-seven of these are existing plants, of which 23 are described by vintage. Twenty-four plant types are new technologies, of which five are non-central facilities (local wind, local photovoltaic, and three types of fuel cells). MARKAL feeds electricity from non-central facilities directly into the distribution grid, avoiding transmission losses.

Process Technologies

Process technologies serve two purposes in MARKAL. The first is to characterize intermediate processes such as oil refineries and nuclear fuel fabrication. Since New York primarily imports finished fuels, few of these processes are included in the database. Ones that are included are hydrogen liquefaction, electrolytic hydrogen production, landfill gas production, production of biogas from herbaceous crops, and production of ethanol or methanol from wood and herbaceous crops and wood. Carbon sequestration is included as a process. Processes are also used to define district heating grids. Only one district heating grid is currently defined in NYMARKAL, but the number is not limited. Although MARKAL includes electric and district heating grids inherently, defining them separately provides greater user control over expansion of the grid. The same technique could be used to investigate expansion of the electrical or gas pipeline grid (transmission or distribution or both).

The second use of processes is as dummy technologies for modeling convenience, for example to provide a convenient place in the fuel cycle to designate environmental emissions or to allow the model flexibility in selecting the fuel mix for multi-fuel power plants. NYMARKAL contains 40 such dummy processes. Although we refer to them as "dummy" processes since they perform no work and incur no losses, most are not included in the MARKAL class "Dummy." If these processes are included in the Dummy Class, no capacity vectors are generated, thus making the problem smaller and faster to run. Their outputs, then, are not accessible by MUSS. By keeping them out of the Dummy Class, we sacrifice some run time to have them in the results tables where they can be accessed and

used in customized tables, for example to display fuel use for groups of electric power plants. Processes with environmental emissions will appear in the emissions tables of the results without regard to whether they are in the Dummy Class or not.

Energy Storage Technologies

Three types of storage technologies are included in NY MARKAL: hydroelectric pumped storage, electrolytic hydrogen production, and electric automobile batteries. The latter are included on the assumption that electric automobiles will be charged at night.

Environmental Emissions

Environmental emissions are included in NYMARKAL at the technology level and act on the activity of the technology. Emissions coefficients are included for carbon dioxide (CO_2), sulfur dioxide (SO_2), total suspended particles (TSP), and nitrogen oxides (NO_x). Activity for conversion technologies in MARKAL is expressed as electricity out, while emissions coefficients are more commonly expressed as fuel in. Modifying emissions coefficients to an output basis would require a change in the emission coefficient if the conversion process efficiency were to be changed. It is better to maintain the environmental coefficients in terms of fuel inputs. To do this, dummy processes were established in front of each conversion technology. These had a fuel input (e.g., residual oil) that was the same as the conversion technology, which was passed through at 100% efficiency to an output fuel that was exactly the same but was given a different name for identification purposes. The emission coefficients for the conversion technologies were then assigned to these associated processes (Figure 1). For demand technologies, activity is defined in terms of fuel in, so emissions coefficients could be assigned directly.

While this is the most common approach to emissions, MARKAL allows other methods. For example, were one interested in including land use as an environmental factor, MARKAL allows emissions to be associated with initial investment so that the land use would be counted only once for each facility.

CO_2 emissions coefficients were based on those used by the New York State Energy Office (NYSEO, 1991b). Each fossil fuel was given a single CO_2 emissions coefficient, although the coefficients were applied by technology. Negative coefficients were used for carbon sequestering or when fuels were used for industrial feed stock. Emissions coefficients for SO_2 , NO_x and total particles were taken primarily from the U.S. Environmental Protection Agency's Source Classification Codes and Emission Factor Listing (AFSEF), based on the recommendation of the Department of Environmental Conservation. AFSEF was provided by EPA on a diskette. In some cases the AFSEF coefficients were too specific and were aggregated to the level of the technology defined in the MARKAL database. In other cases, the AFSEF did not include technologies in the MARKAL database, and coefficients were obtained elsewhere, including DOE technology characterization handbooks (DOE, 1980a; 1980b; 1981; 1983; 1988), Butcher and Ellenbeker (1982), DeLuchi et al. (1987), University of Oklahoma (1975), Moskowitz and Hamilton (1988), Beller (1975). Even within AFSEF, different coefficients are stated in different units, generally mass of pollutant per unit weight or volume of fuel. These were all transformed to units of kilograms per million Btu (Kg/mmBtu).

The existing automobile fleet posed a special problem. Cars were not specifically "vintaged" in the model, but it was assumed that as the existing fleet aged, the older cars would drop out and the fleet average miles per gallon and emissions per mile would improve. A spread-sheet model was developed to step through this process, and emissions per unit energy from the existing fleet were calculated for each period. The rate of loss was calculated by a statistical regression of the age of cars of different model years in the 1987 US fleet. New cars are essentially "vintaged" within the model and a separate outside calculation was not necessary.

A complete listing of the emissions coefficients used, keyed to sources, and the spread-sheet for the existing automobile fleet, is provided in Appendix IV.

Emissions Embodied in Energy Imports

A key concern for New York State in considering approaches to CO₂ emissions reduction is to assure that policies are not adopted that simply move the emissions out of state. For example, New York imports some electricity from coal fired power plants in Pennsylvania; it would be silly to reduce in-state coal-fired power plant operations and increase these imports. Emissions coefficients are thus associated with imports. Imports of Pennsylvania electricity are given the same emissions coefficient as domestic coal-fired power plants (adjusted for the fact that the power plant emissions are imposed on the fuel inputs while the electricity import emissions are imposed on the electricity output of the plants).

Nuclear power involves the use of oil and coal-fired electricity in mining, milling conversion, enrichment, fuel fabrication, waste storage and processing and transportation. In the U.S. MARKAL model, these requirements are explicitly characterized as part of these processes so that most such emissions are captured endogenously. For New York, however, it is assumed that only the nuclear power plants are in the state, all other parts of the nuclear fuel cycle existing elsewhere in the United States. A CO₂ emissions coefficient was associated with nuclear fuel imports to include these fuel-cycle emissions. The emission factor used was based on data reported by Perry et al. (1977) detailing electricity and oil use in mining, milling, conversion, enrichment, fabrication, transportation, and waste disposal. Oil and electric requirements in mining and milling are highly dependent on the grade of the uranium ore; poorer ores require more fuel. It has been suggested that expanding nuclear power would require exploitation of lower grade ores, leading to higher fuel use and increased CO₂ emissions (Mortimer, 1991). Oil and coal consumption for two cases reported by Perry et al. were multiplied by our coefficients for CO₂ emissions for oil and coal. The coefficients used depend on assumptions of how the electricity is produced (Table 2); we assumed that all electric power is provided by coal. For our analysis we chose to use a value between high-grade and low-grade ore, but closer to the low grade: 0.001 Kton/BBtu.

Essentially all electric power for the nuclear fuel cycle is today provided by coal, but this could change in the future. It is probably reasonable to assume that were CO₂ emission constraints imposed in New York and if this led to an increased use of nuclear power, the same would hold true for the U.S. as a whole. Our analysis of the U.S. energy system suggests that, under these circumstances, the percentage contribution of nuclear to the nation's electric supply would increase substantially relative to coal. Electricity supply

for the nuclear fuel cycle would tend to be more from nuclear than coal. This would result in a decrease in the CO₂ emissions coefficient for nuclear fuel imports to New York. We have not assumed any such decrease, however, probably resulting in an excessive penalty for nuclear under high CO₂ emissions constraint.

Table 2. CO₂ emissions coefficient for nuclear fuel. Emissions in Ktons carbon per BBtu fuel.

Ore Quality	0.18%	0.0006%
Emissions	0.000227	0.001317

Besides direct fuel and electricity use, Perry et al. (1977) also provide estimates on CO₂ produced in construction of facilities and embodied in the materials used. To be consistent with the use of other technologies, these were not included. The implications of these indirect emissions are discussed in the

next section.

For practical purposes, no CO₂ is emitted in the production of hydroelectric power. Reservoirs at hydroelectric projects may, however, lead to enhanced natural emissions of methane as a result of decay of vegetative matter covered when flooding the reservoir. CO₂ equivalent emissions of 55 pounds/Mwh were used in the analysis based on a study of the proposed Quebec Hydro reservoir sites (Thérien, 1990).

Oil, gas, and coal imports also involve out-of-state emissions in the extraction and processing stages, but these are such a small fraction of the in-state emissions associated with the combustion of these fuels that it is ignored.

Emissions During Construction and Embodied in Nonenergy Imports

Energy and pollution emissions are embodied in products and materials imported into the state. For example, automobiles purchased in New York State embody energy use and pollution emissions associated with their manufacture and with the manufacture of the steel, plastic, and other materials of which they are made. These are not direct effects of energy policy and are beyond the scope of the current work. An important factor in national and international considerations of CO₂ emissions reduction is that policy constraints on emissions in one country would tend to drive energy-intensive industry to places with less stringent emissions policies, or might otherwise put local industries at a disadvantage. This is an issue worthy of consideration in New York State, but does not loom as large as it does at the national level because heavy industry is not as important a part of the New York economy as it is for the U.S. as a whole.

New York State is a large consumer of the products of heavy industry, however, and a focus on energy and associated environmental emissions embodied in consumer products, while not an energy policy issue, could prove to be a useful approach to reducing greenhouse gas emissions.

Emissions during construction of energy facilities are, in general, small compared to emissions during operations. This issue of construction or manufacturing phase emissions is often raised when comparing fossil-fuel facilities with renewables. A photovoltaic cell produces no environmental emissions during its operation, but there are emissions during its manufacture. MARKAL can incorporate these effects but this kind of analysis is beyond the scope of the present work.

NYMARKAL ENERGY RESOURCE AND TECHNOLOGY DATABASE

The NYMARKAL resource and technology database draws on extensive experience with the U.S. MARKAL database and those from other countries, especially Sweden, but it reflects the characteristics of resources and technologies available in New York. Hundreds of energy technologies are characterized in the NYMARKAL database. Documentation of the database is provided in Appendix V. Technology characterization data are, in many cases, time specific. That is, when a new technology is expected to become available and how fast improvements in cost and performance are expected are explicitly specified in the database. These specifications are made in terms of the nine 5-year time periods (1988-2028) upon which NYMARKAL was designed. Alternative scenarios generally involve changes to the database, either adding a new technology not in the base scenario, e.g., another level of end-use conservation, or modifying the characterization of a technology, e.g., examining the effect of an accelerated R&D program by allowing the technology to enter the market sooner or at lower cost.

APPROACH AND SCENARIOS EXAMINED

Our general approach to MARKAL analysis is to fix the base year (1988 in this case) and then allow the model freedom to make decisions after that. When reviewing the results, the analyst must decide if unexpected results are valid signals of how the energy system could run better or are due to the model's limited understanding of reality. If the latter is the case, it is then appropriate to improve the model's understanding, for example by adding bounds on growth rates, investment, or other parameters that force the model into a more realistic solution. There are no exact rules on how rigorously this should be done. Our preference is to severely limit our interference with the model initially, then to impose more realistic bounds in sensitivity runs.

Several scenarios were analyzed. Scenarios examined are listed and described in Table 3. These are discussed in more detail in the individual sections below along with their analysis. Each scenario was run without CO₂ constraint and against four different levels of CO₂ constraint: stable at 1990 levels and 10%, 20%, and 30% reduction from 1990 levels in 2008 and thereafter (not all scenarios had feasible results for all CO₂ reduction levels). A scenario-CO₂ constraint combination is a case. We use a consistent approach for file names of each case: a four-letter mnemonic to represent the scenario (e.g., TREE), supplemented with a number to represent the CO₂ constraint level. Following the TREE example, the CO₂ unbounded case is TREE1; CO₂ stability is TREE10, 10% reduction is TREE110; 20% reduction is TREE120. Scenarios were selected in part because they address important energy issues for New York State, but also to serve as examples of how NYMARKAL can be used to analyze specific issues.

Other scenarios involve either more restrictive conditions (e.g., not allowing any further investment in nuclear power), addition of alternatives that were not appropriate to the base case because we did not want them associated with every scenario (e.g., greatly increased hydroelectric imports), or a different approach to CO₂ emissions reduction (e.g., carbon tax).

We call the unconstrained case of the Conventional Technology Scenario the "Reference Case" since it is the case most of the alternative scenarios are built upon (by adding technologies or tightening or relaxing constraints on technologies). The reference case is not meant to be a business-as-usual simulation, but it needs to be sufficiently realistic that the results are meaningful lessons to guide future policy. MARKAL produces a least-cost solution under conditions of perfect foresight and perfect economic "rationality." We do not have perfect foresight, but we can use alternative scenarios to test the robustness of decisions under different future conditions. As a society, we base our decisions on a broad range of factors, many of which cannot be easily included in a computer model. We gladly give up some economic rationality or efficiency to address other goals, such as equity or environmental protection. MARKAL points the direction of increased "rationality" and shows how far the system can go in that direction, thus helping to identify the most attractive alternatives to gain specified objectives. In an alternative scenario, we can force a solution that MARKAL, from its narrow view, considers less than optimal (for example, no new nuclear power); this allows us to determine how much we are giving up from the rigid economic efficiency viewpoint. Experimentation with the model may help us find other solutions that achieve the same goals at lesser cost.

Table 3. Scenarios examined and their description.		
File Name	Scenario	Description
BNYS	Conventional Technology	Allows substantial increases in nuclear and 1.8 GW imports of hydropower.
TREE	Reforestation	Adds ability to sequester carbon by planting trees.
QUEB	More Hydroelectric Imports	Imports from Quebec allowed to grow from 1000 MWe in 1993 to 10,000 MWe in 2028. Additional Nuclear also allowed.
TAXC	Carbon Tax	Same as Reference Case with the addition of a \$15/ton carbon tax escalating 10%/year. This scenario is an alternative approach to the usual method of fixed emission constraints.
CONS	Increased End-use Conservation	Double end-use conservation opportunities at higher cost added to Reference Case.
NNQB	More Hydroelectric; no new nuclear	Imports from Quebec allowed to grow to 15,000 MWe in 2028. No new nuclear power.

Table 4. Inclusion of nuclear and increased Quebec hydropower in scenarios.		
Scenario	Increased Nuclear	Increased Hydro
BNYS	X	
CONS	X	
TREE	X	
QUEB	X	10GW
NNUC		
NNQB		15 GW

Analysis of alternative scenarios has three purposes. The first is to examine how the energy system would respond to possible alternative futures. This might include future conditions driven by government policy, changes in the availability of technologies (either constraints on the use of existing technologies or introduction of new technologies) or changes in fuel cost assumptions. The second purpose is to help rank various alternatives identified by MARKAL. The third purpose is to determine the sensitivity of results to various assumptions and to investigate the effectiveness of potential

government policies.

Several custom tables were designed to facilitate understanding of the results. Custom tables are a strong feature of MUSS and it is hoped that these tables will guide and encourage New York State MARKAL users to design additional custom tables in NYMARKAL to meet their own needs for special kinds of information or analysis. The custom tables included with the NYMARKAL package and used in the following section are documented in Appendix VI.

The most controversial issues included are nuclear power and increased imports of Quebec hydroelectric power. All scenarios assume the additional 1 GW of hydropower currently being reconsidered will be available in 1993. This issue is a candidate for MARKAL analysis, but was not addressed here. The hydropower issue addressed is the much longer term issue of substantial (e.g., 10 MW) reliance on Quebec Hydro over the next 40 years. Table 4 shows which scenarios include each of these two energy sources. The design aims to show the implications of each independently and in competition with each other.

INTERPRETING THE RESULTS

A MARKAL run produces a massive amount of information (a typical output file from NYMARKAL is 750 KB and the linear program solution file is over 1 MB). A listing of output tables is given in Appendix I. Explanation of the MARKAL output tables can be found in the MARKAL Report Writer documentation (Giesen et al., 1989). Fortunately, MUSS provides the ability to quickly access key subsets of results and examine this information graphically. Graphs comparing results from several cases can be produced with a single keystroke.

Results are examined in stages:

First, summary statistics: use of primary fuels overall and by sector; environmental emissions; total costs and summary costs for fuels, supply-side technology and demand-side technology.

Second, a detailed examination of the activity of individual technologies. A strength of MARKAL is the ability to provide guidance on the value and role of individual technologies. Whether a specific technology is selected at all, whether it increases or decreases in use, and its relative increase or decrease under different scenarios are key indicators of the technology's value.

Third, a deeper look at the reduced costs of technologies. For technologies that were not selected, these indicate by how much they missed. This provides clues to sensitivity, e.g., how big a difference in cost estimates would have led to selection? It also provides clues to possible policy questions, e.g., how big a reduction in cost would have to be achieved through R&D to make this technology competitive? Among attractive technologies that the model brings into the system to their limit, reduced costs provide clues to how strongly the technology is wanted, e.g., how much the total system cost will be reduced if one additional unit of capacity could be added to the system.

Finally, other details in the results, some of which may be suggested by the preceding examination. This includes, for example, examining environmental emissions results to determine the specifics of how reductions in CO₂ are achieved.

NYMARKAL was run for nine 5-year time periods, from 1988 to 2028. Any model that "builds" capital items having a lifetime of more than one time step must address the question of how to end the model properly. For example, a model would be disinclined to build an expensive plant with a 40-year life near the end of the study period if it assumed that was also the end of the world. MARKAL addresses this problem by essentially selling the entire energy system at the end of the study period, thus getting credit for any residual capacity remaining. This is a well recognized and accepted approach that generally works well, but artifacts may still creep in. It is wise to treat any abrupt changes in the last period with caution. This is especially true in NYMARKAL because much of the front-end of the fuel cycles (e.g., mines, refineries) is missing so the system has less inertia than it otherwise might. On the other hand, one should not ignore possible information to be gained from the last period.

CONVENTIONAL TECHNOLOGY SCENARIO

The Conventional Technology scenario is designated BNYS1. It does not represent the recommended, preferred, or most realistic future. It simply consists of the basic set of technologies, resources, and emissions factors that the other scenarios build upon. For the most part, the model was allowed free rein in the reference case, choosing technologies with its least-cost blinders on. It allows substantial nuclear growth. MARKAL allows imports of electricity, but does not allow capacity to be associated with imports. Since the system must have adequate capacity to meet peaking and reserve requirements, electricity without associated capacity is not as valuable. Existing contractual imports from Quebec (equivalent to 800 MW_e) are configured in the model as imports and constrained to enter

the system. The additional planned 1000 MW_e is configured as a domestic hydropower plant (EQB), thus allowing it to contribute to the state's electrical capacity. Its costs, however, are all included as annual costs; the capacity charge included as a fixed annual cost. The 20% CO₂ reduction case was not feasible, although the infeasibility occurred only in the ninth period (2028). This indicates that a 20% reduction in CO₂ could be achieved in 2008, but it could not be sustained through 2028 without introduction of measures not included in the scenario.

Early runs indicated much greater use of coal and a parallel increase in pollutant emissions in future years than was predicted by the New York State Energy Office. A constraint was introduced to prevent SO₂ emissions from rising above current levels. This constraint is less stringent than state plans, but was sufficient to bring the model within the bounds of a more likely future. Implementing more detailed constraints on SO₂, NO_x and TSP would improve the reality of the model. This would require some adjustments to the model configuration, for example to fully implement the use of coals and oils of different sulfur content. Nonetheless, the single constraint on SO₂ is sufficient for the current purpose.

To summarize the results of the reference case, coal becomes the primary fuel for producing electricity, although renewables increase also. Natural gas, oil and nuclear decline as electrical power fuels. The system builds no new nuclear plants, a decision made solely on grounds of cost. End-use conservation increases. When CO₂ constraints are imposed, coal declines as an electric fuel, to be replaced primarily by nuclear. Electricity takes on a large role in the State's energy system, especially in the residential sector. More detail is given below.

Primary Energy Use

Primary energy use in the three cases of the Conventional Technology Scenario is summarized in Figure 2 and shown individually for each fuel in Figures 3-6. Growth rates, which are tabulated in Table 5, are calculated by the formula:

$$A_1 = A_0 e^{rt}$$

Where: A₀ = energy use in 1988
 A₁ = energy use in 2028
 t = interval (40 years)
 r = annual rate of increase

Solving for annual rate in percentage terms gives

$$r = 100 \left[\frac{\ln A_1 - \ln A_2}{t} \right]$$

Figure 2. Primary energy use in Conventional Technology Scenario.

Figure 3. Primary coal use in Conventional Technology Scenario.

Figure 4. Primary oil use in Conventional Technology Scenario.

Figure 5. Primary natural gas use in Conventional Technology Scenario.

Figure 6. Primary nuclear fuel use in Conventional Technology Scenario.

Figure 7. Primary renewable use (fossil equivalent) in Conventional Technology Scenario.

In the unconstrained case, oil remains, by far, the dominant energy source in the state, although its use grows at a slower rate than useful energy demand (1.3%/year). Coal averages 3.6%/year, quadrupling its 1988 level. Natural gas declines in use from 1988 to a low in 2003, but then increases. Its growth rate over the entire study period was 0.7%/year. Renewable technologies increase steadily at an average of 0.8%/year. Nuclear declines as existing plants reach the end of their useful life. The system makes no new investments in nuclear capacity. End-use conservation is the fastest growing "energy source," increasing its contribution at a rate of 4.9%/year.

As CO₂ constraints are imposed, the increase in coal use turns around and becomes a decrease. A similar effect happens with oil, although more slowly. Nuclear also reverses its downward trend and enters the system strongly (the implications of no new nuclear are explored in an alternative scenario). Natural gas, renewables, and conservation come into the energy system at an increased rate. The apparent growth in total primary energy reflects the use of fossil-fuel equivalents for primary fuel use of renewables since there is no satisfactory way to compare coal with solar on a "primary energy" basis.

Table 5. Primary energy growth rates 1988-2028, Conventional Technology Scenario.

Energy Type Case:	ANNUAL PERCENT INCREASE		
	REFERENCE	STABLE	- 10%
Conservation*	4.9	6.1	6.2
Coal	3.6	-0.8	-0.8
Natural Gas	0.7	1.1	1.0
Nuclear	-5.9	4.5	5.4
Oil	0.8	0.1	-0.2
Renewables	0.8	1.5	1.4
Total Primary**	1.1	1.0	1.2
*Rate over 35 years (1992-2018)			
**Excludes conservation.			

Another way to look at changes in primary use is by changes in the fractional use of each fuel. Figure 8 shows the change in the share of primary energy between the unconstrained and the 10% reduction case.

Figure 8. Primary energy use in 2008 for unconstrained (left) and 10% reduction case (right) in Conventional Technology Scenario.

Single Family Residential Energy Use

Figure 9 shows the energy mix in terms of useful energy supplied for single family residential. In the unconstrained case, gas increases at 1.2%/year and electric by 0.3%/year while oil remains essentially constant. Conservation (building shell improvements and more efficient space heating and air conditioning equipment) increases to satisfy 8.1% of total residential demand by 2028. Minor fuels (coal, propane, wood) disappear. The latter is an artifact of the model not recognizing the special niches these fuels fill; it has no significant effect on the overall result and could be fixed if one wished to examine the role of these fuels specifically. As CO₂ constraints are imposed, the most striking result is that oil decreases and disappears in the 10% reduction case. Gas increases after CO₂ constraints, but then decreases in favor of electricity over time, as non-carbon based sources, primarily nuclear in this scenario, increasingly dominate electricity production. Electricity use grows at 0.8%/year in the CO₂ stability case (more than double its growth rate in the reference case). In the 10% reduction case, electricity grows at the 0.8%/year rate through 2023, but then increases dramatically in the last period resulting in an overall growth rate of 2.4%/year. This last period increase in electric is made primarily at the expense of gas.

Figure 9. Useful energy supplied by energy source, single family residential, Conventional Technology Scenario.

Looking at the more detailed energy demand categories within single family residential, space heat is dominated by natural gas in the reference case. As CO₂ constraints are imposed, electric heat increases and, in the 10% CO₂ reduction case, essentially replaces gas (Figure 10). There is a significant difference among cases in the way gas and electric are used for space heating, however. Advanced gas burners did not enter the reference case. They enter after 2013 in the CO₂ stability case and after 2003 in the 10% reduction case. Gas heat pumps enter the CO₂ stability case in 2023, but in the 10% reduction case, as gas declines slowly as a space heating fuel and is replaced by electric heat. In the last two periods this process increases and electric heat pumps take over completely; gas heat pumps do not enter. Looking at electric heat, in the reference case existing electric heat declines, disappearing in 2008. This probably ignores some niches where electric heat is best. As CO₂ constraints are imposed, the more efficient electric devices (heat pumps and advanced heat pumps) begin to enter the system again. In the 10% CO₂ reduction case, however, there is a massive shift in the last period, with electric resistance heating taking over from gas. This results from the system trying to meet the growing energy demand without increasing CO₂ emissions. As shown below, MARKAL does this by shifting gas from the residential sector to the industrial sector where there are more limited opportunities to use electric. The size of the shift is clearly too big to occur in a single 5-year period in the real world, but it shows the extent to which the system must struggle to meet the CO₂ constraint. With CO₂ constraints, solar and wood appear as growth fuels, serving 4.3% and 6.0% of single family space heating demands in 2028 in the stability and 10% CO₂ reduction cases.

Figure 10. Space heating fuels, single family residential in Conventional Technology Scenario.

Although oil space heat essentially disappears by 2008, oil water heat increases its market share in the reference case until it is replaced by gas in the last period and only gradually disappears in the CO₂ constrained cases. Water and space heating are not linked in the model and this anomalous result makes it clear that they should be. Average efficiency of single family air conditioning increases for 20 years, levels off, then increases dramatically in the last period as the system switches to higher efficiency air conditioners. As with the gas-electric shift in heating, this last period shift is too abrupt to be realistic, but shows the direction the system is under pressure to move. Over the entire study period, air conditioner efficiency increased at a rate of 0.7%/year, reflecting a shift to higher efficiency air conditioning units. Gas takes over 100% of the market for cooking in 2003 and thereafter in the reference case. This shift reflects only economics and not other consumer preferences. Perhaps more important, the model does not at this point include the cost of extending the gas distribution system to serve this larger share of the market. This result should thus be interpreted as a reflection of the greater value of gas to achieving the objective function; a more complete accounting of all costs would undoubtedly decrease the tendency for gas to gain such a large market share. After CO₂ constraints are imposed, however, electric cooking increases in use and eventually drives out gas cooking stoves. Lighting and miscellaneous appliances also shift nearly 100% to improved types in 2003 and thereafter in both the reference and constrained cases. An alternative scenario could, of course, be constructed to reflect different policies or preferences for cooking or lighting technology.

Multi-Family Residential

Multi-family residential shares the same general pattern as single-family (Figure 11). There are some differences. Gas decreases, then increases rapidly in the reference case (overall growth rate 1.9%/year). A similar pattern is seen in the CO₂ constrained cases, but gas use declines after its increase, to be replaced with electricity. As in single family homes, gas use shifts initially to more efficient burners, then (only under CO₂ constraint) to gas heat pumps. Oil increases before it fades. In the reference case, oil does not disappear from the multi-family residential sector until 2028 but as CO₂ constraints increase, it leaves the scene sooner. In the 10% CO₂ reduction case, oil is gone by 2013. Although electricity grows more rapidly under CO₂ constraints, it never takes on as large a share as in single family homes. Electricity has a 1%/year growth in the reference case and a 2%/year growth in the 10% reduction case, in which it fills 55.% of the multi-family energy demand. Energy conservation never achieves as large a share (maximum 1.6% of total multi-family energy demand). Solar does not enter the reference case. It grows to 4.0% of demand in the stability case but only 2.6% in the 10% reduction case where it is partially displaced by electricity.

Figure 11. Useful energy supplied by energy source, multi-family residential in Conventional Technology Scenario

In the reference case, similar to the pattern in single family homes, gas water heating decreases, disappears, then reappears at the end of the study period. Its reappearance is earlier and stronger in the CO₂ stability case than in the reference case, but in the 10% reduction case gas water heat again exits the system in the last two periods, to be replaced primarily with electric and, to a much lesser extent, solar water heating. Solar heat eventually fills about 6% of the multi-family hot water demand. Oil water heat,

conversely, increases until 2018, then decreases and disappears in the last period in the reference case. Under CO₂ constraint it disappears earlier. Electric water heat disappears rapidly.

As in single family homes, air conditioning technology mix is similar in all cases. Efficiency in air conditioning technology increases for 20 years, then levels off, then increases in the last period for an overall growth rate of 0.9%/year.

Cooking in multi-family housing is dominated by electricity in both the reference and CO₂ constrained cases. Moreover, unlike single family, there is no shift to more efficient lighting and appliances in multi-family housing. This finding needs a more detailed analysis.

Commercial

Energy demand categories in the commercial sector include space heat, water heat, air conditioning and ventilation, and lighting and miscellaneous appliances. Technologies and fuels to supply energy service demands in these categories are estimated for three building types independently (office, service, and miscellaneous buildings) but results are combined here for the entire commercial sector.

Figure 12 shows the pattern of how commercial space heating is met by fuel. Conservation increases steadily at 4.6%/year in all cases. In the reference case, heavy oil becomes the dominant fuel over time. Other fuels are eliminated from the picture completely after 2008. Parts of the commercial sector may not be suitable for such a shift. This is a potential place for improvement in future updates of the model. As CO₂ constraints are imposed, heavy oil fuels decrease to be replaced primarily by gas and secondarily by electric. This shift takes place after 2008, with a tendency for the latter fuels to decline and then increase after 2008 when constraints are imposed. The shift to gas rather than electric is the opposite of what happens at the same time in single family residential.

For commercial water heating, conservation enters at a rate of 3.9%/year in all cases. Natural gas becomes the predominant fuel in the reference case (Figure 13). This decoupling of space and water heating fuels is similar to the result in single-family residential and should be corrected in later versions. Under CO₂ constraint, gas continues to be important, but electric water heating gradually dominates.

Electricity dominates commercial air conditioning and ventilation in all cases (Figure 14), growing at 1.3%/year in the reference and stability cases and slightly higher in the 10% reduction case. Conservation enters at 4.3%/year in all cases. Gas air conditioning grows at 1.7%/year in the reference case and the stability case, but declines in the last three periods in the 10% reduction case.

Commercial lighting and miscellaneous changes little among cases. Electric dominates the demand category; gas supplies about 10% of total energy service demand. The 10% CO₂ reduction case shows a slightly higher electrical growth and a correspondingly lower gas growth. Conservation grows through 2008 in all cases, then declines. The system does not invest in improved lighting systems in the commercial

sector, although after CO₂ constraints come in, reduced costs are low, indicating the decision was close. Even moreso than in multifamily housing, this finding is counter intuitive, seemingly in opposition to other evidence of the cost-effectiveness of more efficient lighting. A more detailed analysis is necessary.

Figure 12. Space heating fuels, commercial buildings in Conventional Technology Scenario.

Figure 13. Water heating fuels, commercial buildings in Conventional Technology Scenario.

Figure 14. Air conditioning and ventilation use by fuel, commercial buildings in Conventional Technology Scenario.

Industrial

The industrial energy mix is shown in Figure 15. Industrial use of electricity more than doubles between 1988 and 2028 in all cases (average 2.2%/year growth rate). Oil increases at 4.4%/year through 2008 in all cases. It continues to go up in the reference case, although not steadily, averaging 3%/year for the total study period. In the CO₂ stability case, it goes up faster, although leveling off in the last period, averaging 4.1%/year growth. This increase offsets the decrease in coal use. In the 10% reduction case, however, oil has too high a carbon content to be used to offset coal and, although it fluctuates, it finally declines (Figure 16). Coal use remains constant in the reference case until the last period, when there is a jump associated with introduction of improved coal burners that partly replace oil. Coal use drops rapidly after 2013 in the CO₂ stability case, and after 2003 in the 10% reduction case (Figure 17). Natural gas declines to zero in 2018 in the reference case. In the CO₂ constrained cases it grows again after 2018, capturing 46% of the industrial demand in 2028 in the 10% reduction case (Figure 18). Renewables enter only in the last period in the reference case, begin in 2018 in the stability case and in 2008 in the 10% reduction case. In the latter, their use increases at 6.5%/year over those last 20 years, ultimately capturing 4.8% of the market in 2028 (Figure 19).

Figure 15. Industrial energy mix in Conventional Technology Scenario.

Figure 16. Industrial oil use in Conventional Technology Scenario.

Figure 17. Industrial coal and coke use in Conventional Technology Scenario.

Figure 18. Industrial gas use in Conventional Technology Scenario.

Figure 19. Industrial use of renewable energy sources in Conventional Technology Scenario.

Transportation

The transportation sector continues to be dominated by petroleum products. While other fuels increase over time in all cases, they contribute less than 5% in 2028.

Automobiles. Gasoline continues to be the dominant fuel. Diesels contribute less than 10%, and less than that in the 10% reduction case. Electric cars grow steadily in all cases at 8.6%/year, approaching 10% of the market in 2028. Compressed natural gas cars also grow steadily at 6.6%/year in all cases, but reach a market share of under 4% in 2028. Methanol cars begin to enter the market in 2008, but in no case gain a significant market share. Hydrogen cars do not enter the market. Going behind the fuel categories, there is a clear shift to greater efficiency. The automobile sector overall exhibits a 1.3%/year increase in efficiency in the 10% CO₂ reduction case. Figures 20 and 21 illustrate this in the shift in gasoline fueled cars. In the reference case, the existing fleet is replaced by 10% more efficient cars, which are in turn replaced by 20% efficient cars. In the 10% CO₂ reduction case, the turnover is faster and after 2018 the 20% more efficient cars are replaced by 40% more efficient cars.

Figure 20. Market shift to more efficient gasoline-fueled cars for reference case. Use of other cars is also show.

Figure 21. Market shift to more efficient gasoline-fueled cars for 10% CO₂ reduction case, Conventional Technology Scenario. Use of other cars is also shown.

Trucks. Gasoline also continues to dominate the light truck market. Diesel fuel disappears as the existing fleet completes its useful life. Compressed natural gas comes in slowly in all cases and only achieves about 3% market share by 2028. There is a shift to more efficient trucks in all cases, occurring earlier when CO₂ constraints are imposed (Figures 22 and 23). Diesel remains the only fuel for heavy trucks. There is a shift to a higher efficiency truck in the reference case, but only under CO₂ constraint is there a further shift to an even higher efficiency model (Figures 24 and 25).

Figure 22. Light trucks, showing shift to more efficient gasoline powered types in reference case.

Figure 23. Light trucks, showing faster shift to more efficient gasoline powered types in 10% CO₂ reduction case, Conventional Technology Scenario.

Figure 24. Heavy trucks. Reference case.

Figure 25. Heavy trucks. 10% CO₂ reduction case in Conventional Technology Scenario.

Public Transportation. Public transportation modes are not as fully developed in the model as they could be, but still indicate some trends. Buses exhibit no change among cases; there is an early shift to gasoline to diesel followed by a shift to the most efficient diesel buses available. Both suburban and intercity rail exhibit a shift toward electrification. Energy use by aircraft and vessels are not treated in sufficient detail to yield useful information on these modes.

Electricity Generation

Figure 26 summarizes the mix of electrical generation technologies in terms of electricity produced. The reference case shows coal-fired electric growing rapidly after 2008, giving a 4.5%/year average growth rate over the full study period and moving from 23% to 71% of electrical production. The rapid growth is primarily in the introduction of new coal technologies that enter the market at a 11%/year growth rate between 2003 and 2028. The new coal technologies are coal combined cycle, atmospheric fluidized bed, and molten carbonate fuel cells integrated with coal gasification. The latter is a high efficiency decentralized technology that becomes available in 2013. Unlike other coal technologies, this technology becomes more attractive under CO₂ constraint, as can be seen by the reduced costs shown in Figure 27. Coal cogeneration units are a relatively small contributor to new coal technologies. These units are only attractive in the reference case (Figure 28). Recall that, although there is some constraint on SO₂ emissions, the base scenario does not consider other environmental restrictions that may work against such an increase in coal use.

Figure 26. Electricity output by period by fuel type in Conventional Technology Scenario.

The system builds no new nuclear power plants in the reference case; in the last period it uses only about half of the remaining nuclear capacity, leading to the virtual disappearance of nuclear. Oil and gas exhibit the same pattern in all cases. Gas declines to about 70% of its 1988 production and oil virtually disappears.

As CO₂ constraints are imposed, however, conventional coal plants disappear rapidly. New coal technologies experience a much lower growth rate (7.2%/year). At the same time, growth in electrical output increases from 1.35%/y in the reference case to 1.6%/year in the stability case, then to 2.4%/year in the 10% reduction case. The shortfall is made up primarily by nuclear (5.5%/year growth rate in the 10% reduction case, producing 70% of the electrical output in 2028). The system makes full use of existing nuclear plants and invests in new advanced reactors. Domestic hydroelectric power averages 0.5%/year growth in all cases, going from 81.8 TBtu domestic production in 1988 to 102 TBtu/year domestic production in 2028. The existing 800 MW contract with HydroQuebec is assumed to exist in all cases and an additional 1000 MW contract is assumed to be available after 1993 in all cases. The activity of the latter decreases in the last two periods in the reference case, but not in the CO₂ constrained case (Figures 29 and 30). Other renewables experience a similar growth rate (5.1%/year), but ultimately produce only 4.4% of electrical output in 2028.

Figure 27. Molten carbonate fuel cell: activity and reduced costs in Conventional Technology Scenario.

Figure 28. Coal cogeneration: activity and reduced costs in Conventional Technology Scenario.

Figure 29. Activity in Reference Case of conventional hydropower and non-utility hydropower in New York State, and of new Quebec hydropower (existing contract with Hydro-Quebec not shown).

Figure 30. Activity in 10% CO₂ Reduction Case, Conventional Technologis Scenario, of conventional hydropower and non-utility hydropower in New York State, and of new Quebec hydropower (existing contract with Hydro-Quebec not shown).

Figure 31 shows the pattern of renewable electric technologies other than hydroelectric. Hydroelectric is not included on this list since it is so much larger, it would be difficult to focus on differences among biomass, wind, solar thermal and photovoltaics. The pattern is much the same for all cases, although three technologies (biomass, wind, and photovoltaics) achieve greater market penetration under CO₂ constraints. Energy producing municipal solid waste incinerators are the largest single renewable technology after hydropower. They increase at a rate of 2.3%/year. They produce 1.9% of all electricity in 2028 in the reference case. Their percentage share decreases in the CO₂ constrained cases although their absolute production level remains the same.

Figure 31. Pattern of renewable electric technologies, Conventional Technology Scenario.

Emissions

Figure 32 indicates the resulting CO₂ emissions, without constraint, increase by 1.3%/year between 1988 and 2028 despite the substantial increase in conservation, Environmental factors, not fully considered in this scenario, could suppress the projected CO₂ growth rate by preventing the increase in coal use for electric power. Comparing the 10% CO₂ reduction case with the reference case, the largest contribution to CO₂ reduction is in the electrical generation sector (65% of total net reduction in 2008, 58% in 2028). In the near term (2008) the industrial sector is second (21% of the total net reduction) but in the longer term (2028) the residential (15%) and transport (11%) sectors are next in line.

Figures 33-35 show the corresponding emissions of SO₂, NO_x, and particles. SO₂ is constrained as discussed above, but NO_x and particles are simply tabulated. No attempt was made here to reflect the effect of regulations imposing additional controls on these pollutants, e.g., the potential of implementation of the Clean Air Act Amendments of 1990. The result is that, in the reference case, nitrogen oxides and particles increase as demand for energy services increases. Of interest here is the dramatic, automatic decreases in the emissions of these pollutants as CO₂ constraints are imposed. These decreases reflect the fuel shifts and conservation measures introduced to meet CO₂ constraints. The dramatic effect on other pollutants, especially particles and sulfur dioxide, illustrates the massive changes wrought in the energy system by CO₂ constraints. On the positive side, however, they illustrate the potential collateral environmental benefits of CO₂ constraints.

Figure 32. CO₂ emissions in Conventional Technology Scenario.

Figure 33. SO₂ emissions in Conventional Technology Scenario.

Figure 33. NO_x emissions in Conventional Technology Scenario.

Figure 35. Particulate emissions in Conventional Technology Scenario.

Comparison of Reference Case with State Energy Plan

MARKAL begins with the same economic forecast as the state energy plan and the same initial conditions. The energy plan forecasts of fuel and technology trends, however, are based on projection of current trends, modified by existing constraints associated with environmental laws and regulations. These take into account many behavioral factors. MARKAL results are based more rigidly on least-cost decision-making. History shows that many currently assumed constraints change over periods of three or four decades. By lifting some of the assumptions about behavior and current societal trends, MARKAL is freed to seek potentially better futures. This makes MARKAL a powerful model for evaluating the potential of alternative strategies and new technologies. MARKAL can be made to match current trends projections, but doing that would decrease its real power. Some of the important lessons from a MARKAL analysis can be gained by comparing MARKAL scenarios with current trends projections.

Table 6. Total fuel consumption, 2010. Comparison of SEO current trend and NYMARKAL reference case.

Fuel	SEO Current Trend	NYMARKAL (% Change from Trend)
Petroleum products	1797	2383 (+33%)
Natural gas	1143	752 (-34%)
Coal	335	645 (+98%)
Current trend data from Draft New York State Energy Plan, Vol. II, Impact Assessment, p. 8, July 1991.		

Table 6 compares total fossil fuel consumption in SEO current trends estimates for 2010 with MARKAL reference case results. MARKAL estimates are interpolated between 2008 and 2013. MARKAL uses more coal and oil and less natural gas than the current trends projection.

Table 7 compares the SEO current trend with NYMARKAL reference case for different types of electric power plants. Capacity assignments of Hydro Quebec plants are not included in the table. The correspondence is surprisingly good. MARKAL's lower estimate for oil steam plants but higher estimate for gas steam plants largely reflects differences in the use of multifuel steam plants. Since many renewable technologies are included under "other" in Table 7, the capacity of all renewable electric technologies (not just "other") in the NYMARKAL reference case are detailed in Table 8.

Table 7. Electric capacity (GWe) by type, 2008. Comparison of SEO current trend and NYMARKAL reference case.		
Plant type	Current Trend	NYMARKAL
Oil steam	12.8	7.4**
Other	6.0	1.2
Utility hydro	4.4	4.3
Coal steam	4.2	5.7*
Nuclear	3.9	3.8
Combustion turbines	3.8	4.8
Pumped storage	1.0	1.0
Gas steam	0.5	5.2**
Total installed capacity	36.6	33.4
*Includes coal combined cycle plants.		
**Includes multifuel steam plants in proportion to fuel use (24% oil, 75% gas).		
Current trends from SEO Draft New York State Energy Plan, Vol. II, Electricity Supply Assessment, July 1991, p. 58.		

Table 8. Capacity of renewable electric technologies in NYMARKAL reference case, 2008.	
Technology	Capacity (MW)
Utility Hydro	4,271.
Quebec Hydro	1,000.
Nonutility hydro	360.
Municipal Solid Waste	352.
Wind, local	100.
Solar steam electric	73.
Photovoltaic, central	73.
Photovoltaic, local	73.
Biogas	55.
Wind, local	49.

REFORESTATION SCENARIO

This scenario examines the implications of CO₂ offsets created by sequestering CO₂ in trees through reforestation. Reforestation is not strictly an energy technology, but it nonetheless can be implemented in MARKAL. One policy approach that has been

suggested is to require new large sources of CO₂ to offset their emissions by planting sufficient trees to sequester the lifetime emissions of the facility. This could be easily implemented in MARKAL by simply increasing the capital cost of new fossil power plants to include the appropriate cost of land acquisition, site preparation, seedlings, and planting. Another approach is to treat reforestation as an independent initiative, not tied to any specific energy facility. This approach provides the most information about reforestation as a CO₂ sequestering technology and allows the model to decide the most cost-effective place to take credit for the off-set. This latter approach was implemented. The model will invest in reforestation to allow higher emissions from the energy system. This approach allows MARKAL to find the most cost-effective way to take advantage of the allowable emissions rather than coupling them to a specific technology.

The reforestation resource availability and cost were taken from the State Energy Office analysis of carbon reduction in New York State (NYSEO, 1991b; Sanghi and Michael, 1991). Four resources were considered: (1) tropical forests; (2) forest upgrading, increasing the speed of reforestation and the growth of marketable species on under stocked acreage of mixed hardwoods in New York; (3) reforestation on public lands; and (4) reforestation on private lands. All costs were assumed to be initial costs and to include necessary site preparation, seedlings, labor, and, in the case of private land, land acquisition costs. Best estimates of costs were used and were treated as capital cost. The data used are shown in Table 9.

Reforestation was implemented in MARKAL by creating dummy processes representing each of the forest resources. These processes are characterized with a capital cost, a life of 40 years, and a negative carbon emission coefficient. They do not enter into any energy flows, but the model may choose them as a means of reducing CO₂. MARKAL requires that process technologies have an input and an output energy carrier. The input is a dummy energy carrier to prevent an artificial energy flow from being included in energy accounts. The process is assigned an efficiency of zero, so there is no output, although an output energy carrier must be assigned. The output can be any energy carrier since it will have zero flow. The current MARKAL is thus able to handle non-energy processes that have environmental emissions implications through what is essentially a modeling trick. The new version of MARKAL that will be available in 1992 will provide for materials flows independent of energy flow and so will be able to treat non-energy flows, e.g., material and financial flows, in a more straight-forward manner.

MARKAL invests in all four types of reforestation as soon as CO₂ constraints are imposed. The result is that a 20% reduction in CO₂ emissions becomes possible. Since the underlying technologies and limitations from the Conventional Technologies Scenario remain in place, the basic structure of the energy system is much like in that Scenario: coal decreases (Figure 36), nuclear (Figure 37) and renewables (Figure 38) increase sharply as CO₂ constraints increase. The overall mix of electrical technologies is shown in Figure 39. In the intermediate period (2008-2013), natural gas plays a larger role in the 20% reduction case (Figure 40). The pattern of switching from gas to electric space heating in single family residential, seen in the Conventional Technology Scenario, is accentuated in the 20% reduction case here, indicating the pressure was not an end-period phenomena (Figure 41).

Table 9. Reforestation Data (from NYSEO, 1991b).			
Resource	Cost/acre Dollars	CO ₂ Uptake Tons/acre/year	Available acres.
Forest Upgrade	120.	0.49	500,000.
Public Land	275.	0.95	500,000.
Private Land	775.	0.95	500,000.
Tropical Forest	160.	1.72	500,000.

Figure 36. Total coal use in Reforestation Scenario.

Figure 37. Total nuclear use in Reforestation Scenario.

Figure 38. Total use of renewables in Reforestation Scenario.

Figure 39. Electric output by energy source type in Reforestaion Scenario.

Figure 40. Total natural gas use in Reforestation Scenario.

Figure 41. Natural gas use in single family residential buildings, Reforestation Scenario.

INCREASED HYDROELECTRIC IMPORTS SCENARIO

Hydroelectric provides an essentially pollution-free energy resource. New York State now imports hydroelectric power from Quebec and there is the potential for greatly increased imports. Increased hydroelectric imports could fulfill the same role played by nuclear power in the Conventional Technologies Scenario. This scenario allows a competition between nuclear and hydroelectric. The next scenario (NNQB) explores an energy system with an abundance of hydro but no nuclear.

Like nuclear, hydroelectric power is not without impact or controversy. Issues surrounding import of Quebec hydropower are currently under debate. These involve flooding large land areas and displacing the people who live in those areas. In the case of Quebec hydropower, this is especially troublesome since the effect goes beyond displacing people to disrupting the culture of a native American people. In addition to the social and cultural effects, the proposed system of reservoirs would alter substantially the environment of northern Quebec, especially the character and quality of its water resources. A relatively minor environmental consideration, but pertinent to this study, is that decaying organic matter in the areas flooded yields an increased CO₂ emissions. As mentioned above, a CO₂ emissions factor was associated with this technology based on Thérien (1990).

A scenario was developed for New York State that examines the implications of large imports of hydroelectric power, eventually equivalent to 10 GW of electrical capacity. This is a sufficiently large amount of power that questions of reliability and capacity

reserves are important. Projected potential hydroelectric development in Quebec goes up to about 15 GW electrical capacity about 2010. This scenario allows imports from Quebec to grow linearly from the 1993 assumed level of 1800 MW to 10,800 MW electrical in 2028 (these include the current 800 MW import level). MARKAL associates no capacity with electrical imports, yet in reality imports essentially involve contracts for capacity allocation as well as kilowatt-hours. To take this into account, these imports were internalized into the New York State system by defining a technology called Quebec Hydro. What these imports would cost is a matter for future negotiation. This scenario begins in 1998 with 1 GW at a capacity cost of \$250 per year per Kw and an energy cost of \$0.02 per kwh. These costs are similar to those previously negotiated between Hydro Quebec and the New York Power Authority. The capacity cost remains constant, but the energy cost is increased overtime with increasing capacity availability in a manner similar to expected costs disclosed by Hydro-Quebec as new capacity is brought on line (Drouin, 1990).

The addition of 10 GW Quebec hydropower was insufficient to extend CO₂ reductions to 20% CO₂. The 20% CO₂ emissions reduction proved infeasible in 2028, although the infeasibility occurred only in the last period. The entire 10 GW of Quebec hydro was put in place during the last period of the 10% reduction case, so Quebec hydro could not contribute to the supply of additional low-CO₂ electricity to meet a further CO₂ reduction. Furthermore, it would appear that the reason for the infeasibility was the saturation of all available ways in which low-CO₂ electricity could substitute for direct use fossil fuels. This seems evident since nuclear power was not bounded. Future work should explore the implications of adding additional opportunities for electrification, e.g., expanding the upper bounds on electric automobiles.

The principal purpose of this scenario was to compare nuclear and hydro in "head-to-head" competition. The results are not entirely conclusive. Capacities by year are shown for each technology in Table 10. Annual output of conventional nuclear (LWR), advanced nuclear (HTR) and Quebec hydropower are shown for each case in Figure 42. In the unconstrained case, as in the reference case, no new nuclear plants are built and existing nuclear plants live out their useful life. Also as in the reference case, Quebec hydropower is similar, it never goes beyond the minimum 1 GW electrical capacity required, although additional power is available from Quebec. This is because the assumed cost of Quebec hydropower is more expensive than coal or nuclear options. At the CO₂ stability level, advanced reactors begin to rapidly enter the arena after 2003, but level off after 2018 as Quebec hydro begins to climb. As CO₂ constraints become more stringent, advanced reactors enter more rapidly, leveling off at a higher level after 2023 as Quebec hydro again enters. This time Quebec hydro enters later but reaches a higher level, its maximum allowed. One way to look at these results is that in the last period, nuclear fills a gap that Quebec hydroelectric power is unable to provide, even at the high level assumed here. How large that gap is in earlier years depends on how rapidly Quebec hydropower could be brought into the system. Further sensitivity analysis is necessary to better understand this behavior. The nuclear technologies are unbounded and so do not have reduced costs; Quebec hydro activities and reduced costs are shown in Figure 43.

Table 10. New Quebec Hydro and Nuclear capacity under 10% CO₂ emissions reduction in Conventional Technology and Additional Hydro Imports scenarios. New capacity includes all entering the energy system after 1988.

Scenario	New Nuclear			New Quebec Hydro		
	2018	2023	2028	2018	2023	2028
Conventional Tech	16.7	21.5	21.5	1.0*	1.0*	1.0*
Add'l QH Imports	16.7	21.5	21.5	1.0	1.1	10.0*

*Upper bound of available Quebec Hydro.

Figure 42. Activity of Quebec hydropower and existing nuclear in unconstrained case of Additional Quebec Hydro Scenario.

Figure 43. Activity and reduced costs of Quebec hydropower, Additional Quebec Hydro Scenario.

ADDITIONAL HYDRO BUT NO NEW NUCLEAR SCENARIO

The Conventional Technologies Scenario includes a nuclear power option. This scenario examines the implications of an energy future with no new nuclear plants. It was initially run with Quebec hydropower available at the same level as in the Increased Hydroelectric Imports Scenario (1.8 GW in 1993 increasing linearly to 10.8 GW in 2028). Even the CO₂ Stability Case, however, was infeasible in that scenario. Note that the finding of infeasibility is, in itself, useful information. We then increased the availability of Quebec hydropower to 15 GW electrical capacity in 2028. This approximates the expected total availability of Quebec hydropower (although it becomes available at a slower rate than planned). While New York State cannot expect to import this much hydropower from Quebec, one can think of it as an indication of the size of an energy gap that will exist.

Since no new nuclear plants are brought into the unconstrained CO₂ case of the More Hydroelectric Imports Scenario, this scenario is exactly the same as the previous one in the absence of CO₂ constraints. When CO₂ constraints are imposed, however, differences appear. The CO₂ Stability Case was the only feasible constrained case. Nuclear power use declines as existing plants reach the end of their useful lives. Most of the difference is made up with increased renewable energy sources, up 54% over the parallel case, QUEB10 in 2028 (growth rate of 4.5%/year compared with 3.4%/year in QUEB10). Essentially all of the increase in renewables consisted of increased use of Quebec

hydropower. As might be expected, under CO₂ constraint, Quebec hydropower becomes a more desired energy source when the nuclear alternative is not available; its activity and reduced costs are compared in Figure 45. Activity of end-use conservation is largely unchanged with or without nuclear power, although it was slightly higher in the latter for the last period. It filled in a gap between 2013 and 2028 in QUEB10, a target that could not be reached with Quebec hydro alone and did not seem to be necessary in the CO₂ stability case for either scenario. Figure 46 compares the reduced costs of Quebec hydropower and nuclear (LWRs) for the scenario with no new nuclear. This provides a direct comparison of the value of each technology to the system by period for a case when both are constrained (although the constraint on nuclear is more severe than that on Quebec hydropower). Oil products were up 3% by 2028. Electricity use was down 10% compared to QUEB10, down 37% in single family residential, and 21% in multi--family residential. Growth rate for electricity was 1.1%/year compared to 1.7%/year in QUEB10.

Figure 44. Comparison of nuclear power (LWR) use in Additional Quebec Hydro Scenarios with and without new nuclear power.

Figure 45. Comparison of activity and reduced cost of Quebec hydroelectric power in Additional Quebec Hydropower Scenarios with and without new nuclear power.

Figure 46. Comparison of reduced costs (change in total system cost in millions of dollars per additional GWe) of Quebec hydroelectric and nuclear power (LWR) in Additional Quebec Hydropower with No Nuclear Power..

Figure 47. Total end-use conservation in Additional Quebec Hydropower Scenarios with and without nuclear power.

ENHANCED BUILDING CONSERVATION SCENARIO

In the reference case, three levels of residential building conservation were included in the database, but only one was implemented; we believe that represented a reasonable characterization of building conservation technologies that are beginning to be implemented. Here the second level is implemented as a sensitivity run. We arbitrarily made this equal to the first level in the amount of energy savings allowed, i.e., another 15% of the residential heating demand, at a capital cost double the first 15%. We also delayed initial implementation until the third period (1998). Parallel technologies were applied to single family and multiple family space heating demands. In the commercial sector, two levels of building conservation were implemented in the reference case. Here we expanded this to three levels. These third level technologies were characterized by the same formula as in residential heating: they were limited to the same contribution to the heating demand as the second level conservation technologies at twice the cost, and were delayed in their initial implementation by one period. These were applied only to office and service buildings, the part of the commercial sector with the greatest opportunities for building conservation. Additional ratio equations were added to link the commercial building conservation to the air conditioning as well as the heating demand. Enhanced building conservation was not applied to the industrial sector since the primary source of end-use conservation there is seen to be improved efficiency rather than building conservation.

The Enhanced Building Conservation Scenario achieved a feasible result for 20% CO₂ reduction case, but not the 30% CO₂ reduction case. The model selected the full potential of the enhanced conservation even in the 10% CO₂ constraint case, indicating that conservation is the most cost effective approach in CO₂ reduction among the conventional technologies. Figure 48 shows the distribution and use of building conservation technologies in the Conventional Technologies Scenario and the Enhanced Conservation Scenario for the 10% CO₂ reduction case.

Figure 48. Building conservation contribution to useful energy demand in the 10% CO₂ reduction case for the Conventional Technologies and Enhanced Conservation Scenarios.

CARBON TAX SCENARIO

Carbon taxes are a policy instrument for reducing CO₂ emissions that have received much attention. Fuels are taxed in proportion to their carbon content (and thus their potential CO₂ emissions) effectively increasing their price and providing a disincentive for the use of high-carbon fuels. In NYMARKAL, a pollution emissions tax is implemented by inserting a cost line in the environmental emissions factor table (in this case table ENVCO2). The tax imposed was \$15 per ton of carbon beginning in 1993 and increasing 10% per year thereafter.

Tax effects are behavioral effects. Under perfect "rationality" people will implement conservation, switch fuels, or adopt other means to readjust their behavior to reflect the higher costs of fossil fuels. In reality, there is a great deal of inertia associated with such change. Higher carbon taxes then would be predicted by MARKAL are likely to be needed to induce change in a reasonable time. Once the system readjusts, only a tax rate sufficient to produce price differentials needed under "rationality" will be needed to maintain the new status quo. It is these long-term carbon tax rates that MARKAL provides. Econometric models are more focused on behavioral effects and can aid in estimating the short-term, transitional shock taxes needed to induce change in the short-run.

The effect of this tax is seen in Figure 49. The \$15 per ton ratcheted tax yields a substantial reduction in emissions, but only approaches a CO₂ emissions stability level. Figure 50 shows the effect of the same tax on the US as a whole. The greater effectiveness of the tax in the U.S. illustrates that CO₂ reductions are harder to achieve and more expensive to achieve in New York State than in other parts of the U.S.

Figure 49. Total New York State energy system CO₂ emissions from \$15 per ton carbon tax, escalating at 10% per year, compared to emissions from unbounded reference case and constrained cases of the Conventional Technology Scenario.

Figure 50. Total United States energy system CO₂ emissions from \$15 per ton carbon tax, escalating at 10% per year, compared to emissions from unbounded and constrained cases.

DISCUSSION AND CONCLUSIONS

NYMARKAL is a model of the New York State energy system. It includes numerous options for fuel switching, improved efficiency of supply-side and demand-side technologies, end-use conservation, increased use of renewable energy, reforestation, and pollution taxes such as a carbon tax. NYMARKAL represents the New York State energy system as a set of typical technologies for generating, converting, and using energy as it evolves over a 45-year period. In a variety of scenarios, the model chooses from a menu of several hundred candidate technologies to select the set that meets projected energy demands, environmental restrictions, and other constraints at least cost. NYMARKAL was applied here in demonstration analyses to explore strategies to reduce CO₂ emissions. The analyses begin with the same economic forecast as used in the State Energy Plan and the same initial conditions. However, it takes a different approach to analysis. The energy plan forecasts of fuel and technology trends are based on projections of current trends, modified by environmental regulations and behavioral factors. MARKAL results are based more rigidly on least-cost decision-making. By lifting some of the assumptions about behavior and current societal trends, MARKAL is freed to seek potentially better futures. This is especially appropriate when looking 20 to 40 years into the future, an important time-frame for considerations of greenhouse gas emissions. MARKAL can be made to match projections of current trends, but doing that would decrease its real power. Some of the important lessons from a MARKAL analysis can be gained by comparing MARKAL scenarios with trend projections.

Climate change is a global issue. It is being addressed in international, national, and state forums. New York may, on its own, decide to take action to reduce CO₂ emissions. New York may also be required to take action based on national legislation or international agreements entered into by the United States. It is important to understand the costs and other implications for the State and how New York compares with the rest of the U.S. We have constructed and run a MARKAL model of the U.S. and use it to provide a comparison. It is more difficult and more expensive to reduce carbon emissions in New York State than in the United States as a whole. This can be illustrated by three different comparisons between the two studies:

- Greater emission reductions were feasible in the US than in New York. The maximum CO₂ emissions reduction target achieved (and sustained) in the constrained analyses presented here was 20% below 1988 levels. That target was achieved only by making available a wide range of technological options including reforestation, end-use conservation, nuclear, and imported hydropower. Our MARKAL analyses of the U.S. achieved 20% CO₂ reduction in 2010, increasing toward 50% reduction in 2050 without adding reforestation or other means of carbon sequestration.
- The average cost of achieving stated emissions reduction targets was lower in the U.S. than in New York. The estimated average cost of carbon removal in New York State in this analysis from the unconstrained case to the stability case ranges from \$14/ton carbon to \$22/ton carbon, depending on the scenario. The average cost of further carbon removal to the 10% level ranged from \$48/ton carbon to \$72/ton carbon. In the two scenarios in which 20% CO₂ reductions could be achieved, the average cost of the additional increment ranged from \$94/ton carbon to \$150/ton carbon. In contrast, our analysis of the U.S. as a whole indicated that CO₂ emissions stability could be achieved at an average cost of \$3.50/ton carbon and the additional increment from stability to 20% CO₂ emissions reduction was only \$11/ton carbon.
- CO₂ reductions resulting from the same level carbon tax were greater in the U.S. than in New York. The same carbon tax level (\$15/ton carbon increasing at 10%/year) that results in a 20% reduction in CO₂ emissions nation-wide falls short of stabilizing CO₂ emissions in New York State.

The implication is that, were a common carbon tax instituted, it would have less effect in New York and most carbon emissions reduction would take place elsewhere in the country where it is more cost-effective. Alternatively, were all states required to reduce CO₂ emission an equal percentage (say by 20%), the cost per unit emissions reduction to New York would be much greater than in the rest of the country. If as a nation we wish to reduce carbon emissions, the most cost-effective approach would be to aim at greater emissions reduction outside of New York.

What makes reducing CO₂ emissions in New York more difficult and more expensive? Studies around the world have found that reducing CO₂ emissions invariably translates into reducing coal use. Coal provides a substantial fraction of primary energy in the United States and therefore the country as a whole has the capability of significant reductions in CO₂ emissions with the impact largely confined to this single sector. The US also has a bigger and more diverse arsenal of alternative technologies and resources than

does New York. For example, geothermal and solar energy are more abundant in other parts of the country.

What do the MARKAL results so far say about *how* CO₂ emissions can be reduced in New York State? What must go, what new technologies or resources should come to the fore? We examined end-use conservation, increased efficiency in use of fossil fuels, fuel switching among fossil fuels (e.g., oil or coal to natural gas), nuclear power, hydroelectric power, other non-carbon energy sources, and sequestering carbon in trees. These are each discussed below.

Advocates of conservation and renewables often argue that these are "no regret" options, that is, even if CO₂ reductions were to prove unnecessary, investment in conservation and renewables will have been money well spent. MARKAL analyses examine this issue in the following way: technologies that are indeed "no regret" will be selected in the cases with no CO₂ constraints. Our NYMARKAL and USMARKAL models eliminate the institutional barriers that impede introduction of these technologies in the real world. Our findings are that conservation indeed enters the energy system rapidly even in the absence of CO₂ constraints. Use of renewable energy also increases, but in New York, its growth rate is not outstanding. Without CO₂ constraints it grows at about the same rate as oil or natural gas. Much of the renewable energy is hydroelectric. Under CO₂ constraint, MARKAL invests in more conservation and renewables. From an economic viewpoint, this additional investment is not "no regret" but is cost-effective only under CO₂ constraints.

In the Conventional Technology Scenario, NYMARKAL increases conservation at 4.9%/year without constraint, increasing to 6.2%/year with CO₂ constraints. In the Enhanced Conservation Scenario, annual average increases in conservation in unconstrained and constrained cases are 5.4%/year and 6.6%/year respectively. The additional conservation technologies available in the Enhanced Conservation Scenario are sufficient to allow MARKAL to achieve the 20% CO₂ reduction target. The rate of increase of conservation in New York is higher in both cases than in the US as a whole, although the relative change due to CO₂ constraint is lower (see Table 11).

The reverse is true for renewables, for which the rate of increase is lower in New York than in the US, although the change upon introducing CO₂ constraints is greater. In the New York Additional Quebec Hydropower Scenario, the unconstrained case includes only slightly higher growth in renewables, but with CO₂ constraint, the annual average increase in renewables increases to 3.8%/year.

Table 11. Comparison of average annual growth rate for conservation and renewables between U.S. and New York State (Conventional Technologies Scenario) for unconstrained and constrained CO₂ emissions.

	Unconstrained	Constrained
New York		
Conservation	4.9	6.2
Renewables	0.8	1.4
United States		
Conservation	3.0	4.7
Renewables	3.4	4.0

One conservation technology of especial note is improved lighting systems in commercial buildings. This has been targeted by utilities as a prime candidate for reducing electrical load. NYMARKAL, however, selects this technology only when the system is highly stressed, i.e., in the 20% CO₂ removal case for conservation and the stability case for the No New Nuclear Scenario. The reduced costs shown in Figure 51 tell the story. Reduced costs are slightly higher for service buildings and miscellaneous

buildings, where the technology was never selected. In the later periods, reduced costs of lighting technologies in all three types of buildings are close; a small difference in the cost estimates of this technology, well within the range of uncertainty expected when projecting costs 20 years in the future, would be sufficient to alter the decision to use this technology and the amount it is used. Perhaps more important, it is surprising that commercial lighting technologies did not come out more favorably in the results. Because of the importance of this technology to demand-side management plans, analysis of a more detailed breakdown of lighting technologies is warranted before drawing any conclusions.

Increased efficiency in fossil fuel use is available to the model on the supply and the demand side. The model includes several new, higher efficiency coal-fired power plants and new, higher efficiency, residential, commercial, and industrial furnaces for gas, oil, and coal. Without CO₂ constraints, a variety of more efficient coal electric power devices are brought into the system. As CO₂ emission constraints increase, only the most efficient technologies are included.

Figure 51. Reduced costs of improved commercial lighting.

As expected, CO₂ constraints result in substantial decreases in the use of coal (85% in the Conventional Technology Scenario). Oil use also decreases, with the size of the decrease growing over time. In some sectors (e.g., single family space heating), oil disappears entirely. Use of gas as a fuel for electric power generation does not change, but some of the decreases in oil and coal use for direct combustion by end-users is displaced by gas. Overall, gas use increases. The increase bulges to 35-40% over the unconstrained case in the mid-years after the CO₂ reduction target date (2013-2018) and then narrows (8% in 2028). Total fuel switching among fossil fuels is the same as the increase in gas use. In the Conventional Technology Scenario during the peak period (2013), this is 316 TBtu/year, about 10% of all fossil energy and 6% of total primary energy.

Nuclear and Quebec hydropower were the two primary non-carbon fuels that could fill the gap left by reductions in coal and oil to meet CO₂ emissions constraints. Substantial reductions in CO₂ emissions could not be sustained without nuclear or large future imports of Quebec hydropower. In no scenario were we able to achieve and sustain even 10% reduction in CO₂ emissions without additional nuclear power. Even with 15 GW electrical capacity available from Quebec in the No New Nuclear - Hydro Quebec Scenario, only a stable CO₂ target could be achieved. If the State wants or needs to do more than stabilize CO₂ emissions, and wants to avoid adding new nuclear capacity, other options must be explored.

Renewable technologies, other than hydroelectricity generated in New York State and Quebec, are municipal solid waste, wind turbines, solar thermal power, photovoltaics, biomass, and biogas. The upper bounds we placed on the application of these technologies

in New York total ?? This is only [fraction] of hydroelectric potential, so the the potential contribution of technologies is limited. Nonetheless, under CO₂ emissions constraints, all of these other renewable energy sources reach their upper bounds. Figures 50 and 51 show the reduced costs of centralized and local renewable technologies for the highest CO₂ constraint in each scenario. These suggest that, among these non-hydropower renewable technologies, local and central wind, photovoltaics and solar steam electric have the most consistent and sustained growth, coupled with consistently high reduced costs (indicating a high marginal value to the model). Considering the potential value of these technologies, future analyses should investigate opportunities to raise those upper bounds, allowing more renewable energy into the system. Their maximum use, however, is limited.

Simply keeping track of emissions of other pollutants in NYMARKAL provides the opportunity to assess the effect of CO₂ constraints on sulfur dioxide, nitrogen oxides, and particulate pollution emissions (e.g., Figures 33-35). The dramatic reductions, especially in SO₂ and particles, illustrate the massive effect that CO₂ constraints can have on the energy system. A 10% reduction in the level of CO₂ emissions can result in a reduction of other pollutants beyond what has been possible through existing clean air legislation. There are two sides to this result. First, CO₂ constraints can yield substantial collateral benefits in reducing emissions of other pollutants. As with energy conservation conservation, CO₂ constraints tend to push in the direction of more general environmental quality improvement. On the other side, however, it must be remembered that greater air quality improvements have not been made to date largely because of the large costs involved. The fact that they occur automatically as the result of meeting CO₂ emission reduction targets does not not make these costs any less burdensome to society.

How much of a reduction in New York State CO₂ emissions is technologically feasible? The demand for energy services in New York State is projected to grow. Without an unlimited supply of energy, at some point this increasing demand must exceed supply, resulting in a technically infeasible situation. When CO₂ emissions restrictions are added, the system becomes further constrained and the point of infeasibility comes closer in time to the present. The question of technological feasibility then is not if a reduction is infeasible, but at what point in the future will a given level of CO₂ emissions reduction become infeasible? The State Energy Office's usual planning horizon is about 20 years. That puts the point at which carbon emission controls are imposed in this study near the edge of the planning horizon, yet it appears that maintaining CO₂ emission goals beyond initial target dates may be harder than meeting initial targets. Therefore, this study looked two decades further into the future, to 2028. Beyond the third or fourth decade of the next century, social and technological changes beyond our vision can be expected to intervene. New technologies or resources may emerge, technologies may advance beyond expectation, or population shifts, lifestyles or technological changes may result in lower demands for energy services. Global climate change is a problem that requires us to consider consequences much further into future, at least to 2100, but we cannot expect to make detailed projections that far ahead. We can and do need to consider detailed technological options over a 40-50 year future, however, and that is the task on which NYMARKAL focuses.

NYMARKAL helps to provide insight. Sometimes this confirms conventional wisdom but other times it points out overlooked possibilities and fills knowledge gaps. One can gain insight by reading about the results of model runs, but the model can be used to

Figure 51. Activity and reduced cost of central renewable technologies under CO₂ constraint.

Figure 50. Activity and reduced cost of central renewable technologies under CO₂ constraint.

greater advantage. Energy system planning involves an interaction among complex technological, economic, environmental, social, and political considerations. It is through interaction among people from those areas that real advances can be made. NYMARKAL can provide a common framework of discussion for such interaction.

REFERENCES

Beller, M. (ed). 1975. Sourcebook for Energy Analysis (BNL 50843), Brookhaven National Laboratory, Upton, NY 11973.

Butcher, S.S. and M.J. Ellenbecker. 1982. Particulate emission factors for small wood and coal stoves, JAPCA 32: 380-384.

DeLuchi, M.A., D. Sperling and R.A. Johnston. 1987. A Comparative Analysis of Future Transportation Fuels (UCB-ITS-RR-87-13). Institute of Transportation Studies, University of California, Berkeley, CA.

DOE. 1980a. Technology Characterizations Environmental Information Handbook (DOE/EV-0072). U.S. Department of Energy, Washington, D.C.

DOE. 1980b. Environmental Data, Energy Technology Characteristics, Coal (DOE/EV-0061/3). U.S. Department of Energy, Washington, D.C.

DOE. 1981. Energy Technologies and the Environment (DOE/EP-0026). U.S. Department of Energy, Washington, D.C.

DOE. 1983. Energy Technology Characterizations Handbook: Environmental Pollution and Control Factors (DOE/EP-0093). U.S. Department of Energy, Washington, D.C.

DOE. 1988. Energy Technologies & the Environment (DOE/EH-0077). U.S. Department of Energy, Washington, D.C.

Drouin, R. 1990. Notes pour l'allocution devant le Club d'Electricit du Quebec.

Giesen, G., D. Wilde, G. Wolfrum. 1989. MARKAL Report writer, Version 2.11, Documentation for Users. Forschungszentrum Julich GmbH (KFA), Julich, Germany.

Fishbone, L.G. and Abilock, H. 1981. MARKAL, a linear-programming model for energy systems analysis: technical description of the BNL version, *Energy Research* 5: 353-375.

Fishbone, L.G., Giesen, G., Goldstein, G., Hymmen, H.A., Stocks, K.J., Vos, H., Wilde, D., Zolcher, R., Balzer, C. and Abilock, H. 1983. User's guide for MARKAL (BNL/KFA version 2.0), A multi-period, linear-programming model for energy systems analysis (BNL 51701), Brookhaven National Laboratory, Upton, N.Y.

Giesen, G., Wilde, D. and Wolfrum, G. 1989. MARKAL, a linear-programming model for energy systems analysis, report writer, version 2.11, documentation for users, Forschungszentrum Julich GmbH, Julich, Germany.

Goldstein, G. 1991. PC-MARKAL and the MARKAL Users Support System (MUSS) (BNL 46319), Brookhaven National Laboratory, Upton, N.Y.

Jorgenson, D.W. and Wilcoxon, P.J. 1989. Environmental regulation and U.S. economic growth (Discussion paper 1458), Harvard Institute of Economic Research, Cambridge, MA.

Manne, A.S., Condap, R., and Preckel, P. 1981. ETA-MACRO: a user's guide, (EPRI EA-1724), Electric Power Research Institute, Palo Alto, CA.

Manne, A.S., Beltramo, M.A., Rutherford, F.F., Svoronos, A.N., and T.F. Wilson. 1983. ETA-MACRO: A progress report (EPRI EA-3170), Electric Power Research Institute, Palo Alto, CA.

Mortimer, N. 1991. Nuclear power and global warming, *Energy Policy* 19:76.

Moskowitz, P.D. and L.D. Hamilton. 1988. Energy and complex industrial systems, environmental emissions data reporting and acquisition, Annex III in Emissions, Environmental Transport, and Dose-Response Models: Guidelines for Case Studies (WHO/PEP/88.13), World Health Organization, Geneva.

NYSEO. 1991a. Draft New York State Energy Plan. Prepared jointly by New York State Energy Office, Department of Public Service, Department of Environmental Conservation, Albany, NY.

NYSEO. 1991b. Analysis of Carbon Reduction in New York State. New York State Energy Office, Albany, NY.

Perry, A.M., R.M. Rotty and D.B. Reister. 1977. Net energy from nuclear power, in *Nuclear Power and its Fuel Cycle*, Vol I. International Atomic Energy Agency, Vienna, pp. 709-721.

Sanghi, A.K. and K.S. Michael. 1991. Carbon sequestering through reforestation: cost and potential for New York. Presented at the 84th Annual Meeting, Air & Waste Management Association, Vancouver, British Columbia.

Thérien, N. 1990. Impacts cumulatifs-enjeu "Qualite de l'air", Etude des enjeux environnementaux associes a l'effet de serre suite a la creation de reservoirs hydroelectriques. Rapport final presente a la Vice-presidence Environnement d'Hydro-Quebec.

University of Oklahoma. 1975. Energy Alternatives: A Comparative Analysis. Science and Public Policy Program, University of Oklahoma, Norman, OK.

APPENDIX I. LISTING AND DESCRIPTION OF NYMARKAL OUTPUT FILES.

The convention we adopted for output files was a four digit alphanumeric code identifying the scenario (e.g., TREE for the reforestation scenario), followed by a fifth digit to identify different versions of the scenario, if any. Finally, the level of CO₂ reduction associated with the case was designated as "0" for stability, "10" for a 10% reduction from 1988 levels by 2008, "20" for a 20% reduction from 1988 levels by 2008, etc. File listings follow:

BNYS1	Reference case; Conventional Technology Scenario
BNYS10	Conventional Technology Scenario, CO ₂ stability
BNYS110	Conventional Technology Scenario, 10% reduction in CO ₂
TREE1	Reforestation Scenario, CO ₂ unbounded
TREE10	Reforestation Scenario, CO ₂ stability
TREE110	Reforestation Scenario, 10% reduction in CO ₂
TREE120	Reforestation Scenario, 20% reduction in CO ₂
CONS1	Enhanced Building Conservation Scenario, CO ₂ unbounded
CONS10	Enhanced Building Conservation Scenario,, CO ₂ stability
CONS110	Enhanced Building Conservation Scenario, 10% reduction in CO ₂
CONS120	Enhanced Building Conservation Scenario, 20% reduction in CO ₂
QUEB1	Increased Hydroelectric Imports Scenario, CO ₂ unbounded
QUEB10	Increased Hydroelectric Imports Scenario, CO ₂ stability
QUEB110	Increased Hydroelectric Imports Scenario, 10% reduction in CO ₂
NNQB1	Increased Hydroelectric Imports and No New Nuclear Power Scenario,, no CO ₂ constraint.
NNQB10	Increased Hydroelectric Imports and No New Nuclear Power Scenario,, CO ₂ stability.
TAXC1	Carbon Tax Case. No direct constraints on CO ₂ used with this scenario

APPENDIX II. EMISSIONS OF OTHER GREENHOUSE GASES

Other greenhouse gases include methane (CH₄), nitrous oxide (N₂O), tropospheric ozone (O₃), and chlorofluorocarbons (CFCs). In addition, carbon monoxide (CO), non-methane hydrocarbons, and nitrogen dioxide (NO₂), while not greenhouse gases themselves, contribute to atmospheric chemistry reactions that increase the amount of methane and ozone in the atmosphere. Non-methane hydrocarbons and nitrogen dioxide are the key ozone precursors, while carbon monoxide competes with methane for oxygen; as the amount of CO in the atmosphere increases, the amount of methane removed from the atmosphere through oxidation declines (Ciborowski, 1989).

Here we deal only with direct emissions of greenhouse gases, thus focusing on methane, nitrous oxide and CFCs. It now appears that CFCs have both warming and cooling effects, so role as important greenhouse gases is in question. Moreover, efforts are underway to increase the speed of elimination of the use of CFCs. The contribution of new emissions of CFCs to global warming in comparison to CO₂ and methane emissions produced over the 45 year study period of NYMARKAL will probably be small. Emissions and equivalent greenhouse gas effect of these gases are given in Table II-1.

Table II-1. Emissions of greenhouse gases in New York State.			
Greenhouse Gas	CO ₂ Equivalence	Emission Ktons/y	CO ₂ Equiv. Emission
Carbon Dioxide	1	232,000.	232,000.
Methane	21	2,081.	47,701.
N ₂ O	290	74.3	21,547.
CFCs	1500-7300	31.	?
Others			47,647.*
*Based on NY share of US GHG emissions. Table adopted from NY State Energy Office (1991).			

The emission estimates of methane and nitrous oxides in Table II-1 are subject to considerable uncertainty. Based on CO₂ equivalence of these estimates, however, CO₂ contributes 64% of the warming potential of greenhouse gas emissions in New York State. This assumes CFCs make no contribution. Were CFCs included, the CO₂ contribution would be 48%.

Emissions of greenhouse gases other than CO₂ are important for two reasons: First, they provide a perspective on the extent of the greenhouse problem that is addressed by the current analysis of CO₂ emissions (50-64%). Second, they assist in decisions on what new emission sources are important to include in NYMARKAL. Emission rates

of methane and N_2O are more variable and more uncertain than emission rates of CO_2 . None-the-less, it is useful to include current estimates of these emissions to allow the analysis to address a larger share of the problem.

Sources of methane in New York State include enteric fermentation, wetlands, biomass burning, termites, landfills, oceans, freshwater bodies, saltwater bodies, and the natural gas transmission and distribution system. The latter is the key domestic energy source of methane for consideration for inclusion in NYMARKAL. Emissions from landfills are also of possible interest, since NYMARKAL now includes methane from landfills as an energy resource. The more that resource is used, the lower the direct emission of methane to the atmosphere.

Coal mines are another source of methane. Adding methane emissions to coal imports and imports of coal-fired electricity is a high priority, as is adding methane emissions associated with production and transport of imported natural gas.

Sources of N_2O in New York State include fossil fuel combustion, biomass burning, soil emissions, and lightning. All but the latter are energy systems emissions that can be added to NYMARKAL.

Reference

Ciborowski, P. 1989. Sources, sinks, trends, and opportunities, Chapter 14 in D.E. Abrahamson (ed), *The Challenge of Global Warming*, Island Press, Washington, D.C., pp. 213-230.

APPENDIX III. DOCUMENTATION OF NYMARKAL DEMAND CATEGORIES AND PROJECTION DATA

Demand Categories

The demand categories in MARKAL are energy demands associated with a specific economic activity or entity. Table III-1 lists the demand categories defined in NY MARKAL.

Industrial The classification of industrial demand categories for NY MARKAL posed some difficulties because most of the existing consumption data are reported in terms of Standard Industrial Classification (SIC) group, not by specific enduse based on which linkage can be established with the specific demand technologies that satisfy these demands. In this study, we have defined "process heat" to be the demand category that uses all the fossil fuels consumed in the industrial sector. The electricity demand was broken down into two demand categories: "motor driving" and "lighting & other uses". In addition, a fourth demand category was created to include industrial use of energy resources as feedstocks and non-energy applications, although there is no demand data available in these activities.

Residential. The demand categories defined in NY MARKAL were aggregated from the enduse demands by housing type reported in the NY REEPS model. "Multiple family" in MARKAL was formed by combining three housing types defined in REEPS: Two to four units, five plus units, and mobile homes.

In addition, dishwashers, refrigerators, freezers, and other appliances listed in REEPS were aggregated into a single category: "Miscellaneous appliances". These aggregations were made in order to keep the size of NY MARKAL and the computer run time to achieve the optimal solution at a manageable level. The values of the energy and economic parameters associated with these newly defined demand categories in MARKAL were calculated as the weighted averages of the corresponding values of their components defined in REEPS. Other major demand categories brought into MARKAL from the residential model include space heating, water heating, and air conditioning.

Table III-1. NYMARKAL Demand Categories.

I1	Industrial Process Heat
I2	Electric Motor Drive
I3	Lighting & Misc Electric
N1	Petrochemical Feedstocks & Nonenergy
R0	Single Family Space Heating
R1	Single Family Water Heating
R2	Single Family Air Conditioning
R3	Single Family Cooking
R4	Single Family Miscellaneous Appliances
R5	Multiple Family Space Heating
R6	Multiple Family Water Heating
R7	Multiple Family Air Conditioning
R8	Multiple Family Cooking
R9	Multiple Family Miscellaneous Appliances
RA	Office Building Space Heating
RB	Office Building Water Heating
RC	Office Bldg Air Conditioning & Ventilation
RD	Office Building Lighting & Appliances
RE	Service Building Space Heating
RF	Service Building Water Heating
RG	Service Building Air Conditioning & Ventilation
RH	Service Building Lighting & Appliances
RI	Miscellaneous Space Heating
RJ	Miscellaneous Buildings Water Heating
RK	Miscellaneous Buildings Air Conditioning & Ventilation
RL	Miscellaneous Buildings Lighting & Appliances
RX	Commercial Buildings Miscellaneous Use
T1	Automobile
T2	Light Truck
T3	Bus
T4	Subway & Urban Rail
T5	Intercity Rail - Freight
T7	Air
T8	Vessel
T9	Misc Transport
TH	Heavy Truck

Commercial. In defining the demand categories in the commercial sector, the ten building types classified in the NY CEDMS model were aggregated into three groups as shown in Table III-2.

Table III-2. Mapping from CEDMS to NYMARKAL Building Types.	
MARKAL	NY CEDMS
Office	Office
Service	Restaurant
	Retail
	Grocery
	Health
	Hotel
Miscellaneous	Warehouse
	School
	College
	Miscellaneous

The enduse demands in CEDMS were also aggregated into four categories: Space heat, water heat, air conditioning & ventilation, and lighting & miscellaneous appliances. This was achieved by combining lighting, refrigeration, cooking, and miscellaneous equipment defined in CEDMS into a single enduse demand: "Lighting and miscellaneous appliances". Similar to the residential sector, the values of the energy and economic parameters for the newly defined demand categories were calculated as the weighted averages of the corresponding values of their components listed in CEDMS.

Transportation. The transportation demand categories defined in NY MARKAL were based on the modal classification of the NYSDOT Energy Demand Model. One adjustment made was the aggregation of "light", "medium", and "light-heavy" trucks classified in the latter into a single mode of "light truck" in MARKAL.

Demand Projections

The projections of future end-use demands in MARKAL were made in the End-use Demand

(EUD) Tables developed for the demand categories. An EUD table contains the following parameters:

- **Basis, B(T):** The underlying projection (economic, demographic, or energy) based on which future energy enduse demands are determined. T stands for the time periods (1 to 9) in the planning horizon..
- **Saturation, S(T):** The fraction of the potential demand for a particular demand category actually being fulfilled at a given time period.
- **Base Year Energy Consumption, DE(1):** The energy consumption (by demand technologies) in a specific demand category in the base year.

- Enduse Demand, EUD(T): The amount of useful energy that would be required in a specific demand category exclusive of the efficiencies of individual demand technologies.
- Unit Enduse Demand, EUD: Enduse demand divided by the basis.

In projecting future enduse demands, the enduse demand in the base year ($T=1$, or 1988) was first calculated as the sum of the products of the base year energy consumption of each demand technology and its efficiency. This total was then divided by the product of the basis and saturation ($B(1) \times S(1)$) in the base year to obtain the unit enduse demand. Future enduse demands are projected by multiplying the unit enduse demand to the basis in each future time period t , taking into account changes in the saturation rates if assumed ($EUD \times B(t) \times S(t)$). It should be emphasized here that the enduse demand represents the useful energy (i.e. after device efficiency) required to maintain the activity in a demand category. Actual fuel demands (including electricity and conservation) to satisfy these enduse demands are determined by the activity level of the demand devices obtained in MARKAL's optimal solution.

In this study, a single projection for each demand category was made on various growth assumptions reported in the 1989 SEO Energy Demand Forecast Assessment. They are shown in Tables A6 (the "DM" tables of the NY MARKAL input files). The projected enduse demands (in BBTu) are displayed in the "DEMAND" row under each demand category. It should be emphasized that these projections are not intended to predict what will occur in each sector in the future but to provide a reference point based on which energy system impacts under various energy and environmental policies can be evaluated. The specific assumptions made and the basis for projections in each demand category are described in the sections which follow.

Industrial. The base year industrial consumption pattern, DE(1), was established by allocating all current fossil fuel consumption to process heat. Electricity consumption was broken down by motor driving, lighting and other uses according to NYSERDA distribution. The bases for projection used in the EUD tables are individual energy growth indexes projected in the 1989 SEO Reference II Scenario. The allocation of all fossil fuels to process heat is certainly open to refutation as these fuels are also being used for other purposes (e.g. diesel fuel for mechanical drive). Clearly, a more comprehensive and desegregated (by enduse) demand pattern of industries within New York State will have to be established for studies in which the primary focus is on industrial energy impact. This effort, however, is not within the scope of this study.

Residential. The base year energy consumption by households was established based on data compiled in the NY REEPS. The bases for projecting enduse demands by demand category are household forecasts (single family, two to four units, five plus units, and mobile homes) reported in the 1989 SEO Reference II Scenario. As

described earlier, the multiple units and mobile homes defined in REEPS were combined into a single category of "multiple family" in MARKAL.

Commercial. The commercial energy consumption pattern in the base year was established from data compiled in the NY CEDMS Model. The base year commercial floorspace by building type were projected into the future based on the annual growth rates assumed in the 1989 SEO Reference II Scenario. These projected floorspace (by the ten building types defined in CEDMS) were aggregated into three categories, providing the bases for commercial enduse demand projections in office, service establishments, and miscellaneous buildings.

Transportation. The base year transportation energy consumption by mode were based on data published by NYSDOT. The bases for projecting enduse demands by passenger modes are the projected modal activities in terms of vehicle miles traveled (VMT). For freight modes, these bases are measured in terms of ton miles (TM).

APPENDIX IV. ENVIRONMENTAL EMISSIONS COEFFICIENTS

The following tables provide the environmental emissions by technology for NO_x, total particles (TP), SO₂ (SO_x), as well as carbon monoxide (CO) and volatile organic carbon (VC), which were not included in NYMARKAL. Coefficients are given in the units used in the original source (referenced in the assumptions column) and in kg/mmBtu, the form they were entered in NYMARKAL. Source references are given below. Following the general emissions coefficient tables is a table showing the method of estimating emissions from the current automobile fleet.

References

AFSEF. 1990. AIRS Facility Subsystem Emission Factors, US Environmental Protection Agency, National Air Data Branch. Electronic database.

Butcher, S.S. and M.J. Ellenbecker. 1982. Particulate emission factors for small wood and coal stoves, *J. Air Pollution Control Assoc.* 32: 380-384.

Beller, M. (ed) 1975. Sourcebook for Energy Assessment (BNL 50483). Brookhaven National Laboratory, Upton, NY 11973.

DeLuchi, M.A., D. Sperling, and R.A. Johnston. 1987. A Comparative Analysis of Future Transportation Fuels (UCB ITS-RR-87-13. Institute of Transportation Studies, University of California, Berkeley.

DOE/EH-0077. 1988. Energy Technologies and the Environment. US Department of Energy.

DOE/EV-0061/3. 1980. Environmental Data, Energy Technology Characterizations: Coal. U.S. Department of Energy, Washington, D.C.

DOE/EV-0072. 1980. Technology Characterizations, Environmental Information Handbook. U.S. Department of Energy, Washington, D.C.

DOE/EP-0026. 1981. Energy Technologies and the Environment. U.S. Department of Energy, Washington, D.C.

DOE/EP-0093. 1983. Energy Technology Characterizations Handbook: Environmental Pollution and Control Factors. U.S. Department of Energy, Washington, D.C.

Energy Alternatives: A Comparative Analysis. 1975. Science and Public Policy Program, Univ of Oklahoma, Norman.

-72-

New York State Emissions 04-Jun-91

TECHNOLOGY	NOx lb/yr	NOx lb/mmBtu	TP lb/yr	TP lb/mmBtu	SOx lb/yr	SOx lb/mmBtu	CO lb/mmBtu	VC lb/yr	VC lb/mmBtu	ASSURATIONS
R5E IF SH NEW GAS DEVICE										
R5F IF SH RETROFIT OIL BURNER	217	0.196819	54.1	0.0490887	114	0.103398	0.0654854	54	0.048978	Same as R52
R5G IF SH NEW & IMPROVED OIL BURNER	217	0.196819	54.1	0.0490887	114	0.103398	0.0654854	54	0.048978	Same as R52
R5H IF SH SOLAR WITH OIL BACKUP										
R5I IF SH NEW OIL DEVICE										
R5J IF SH NEW IMPROVED ELECTRIC HEATER										
R5K IF SH NEW IMPROVED ELECTRIC HEATER										
R5L IF SH SOLAR WITH ELECTRIC BACKUP										
R5M IF SH NEW & IMPROVED HEAT PUMP										
R5N IF SH SOLAR WITH HEAT PUMP BACKUP										
R5P IF SH CONSERVATION LEVEL I										
R5Q IF SH CONSERVATION LEVEL II										
R5R IF SH CONSERVATION LEVEL III										
R5S IF SH HEAT DISTRICT HEAT DOWNGR										
R5T IF SH HEAT DISTRICT HEAT DOWNGR										
R5U IF SH HEAT DISTRICT HEAT DOWNGR										
R5V IF SH HEAT DISTRICT HEAT DOWNGR										
R5W IF SH HEAT DISTRICT HEAT DOWNGR										
R5X IF SH HEAT DISTRICT HEAT DOWNGR										
R5Y IF SH HEAT DISTRICT HEAT DOWNGR										
R5Z IF SH HEAT DISTRICT HEAT DOWNGR										
R6A IF WATER HEAT OIL	24.2	0.0219494	9.2	0.0083444	0.276	0.000750332	0.00877976	9.2	0.0083444	Same as R60
R6B IF WATER HEAT OIL	43.2	0.0391824	36	0.032852	113	0.102491	0.016326	36	0.032852	Same as R62
R6C IF WATER HEAT OIL										
R6D IF SOLAR WATER HEAT WITH GAS BACKUP										
R6E IF SOLAR WATER HEAT WITH OIL BACKUP										
R6F IF SH FROM SOLAR SH - GAS BACKUP										
R6G IF SOLAR WATER HEAT WITH ELECTRIC BACKUP										
R6H IF SH FROM SOLAR SH - OIL BACKUP										
R6I IF SH FROM SOLAR SH - ELECTRIC BACKUP										
R6J IF SH FROM SOLAR SH - HEAT PUMP BACKUP										
R6K IF WATER HEAT DISTRICT HEAT DOWNGR										
R6L IF WATER HEAT DISTRICT HEAT DOWNGR										
R6M IF WATER HEAT DISTRICT HEAT DOWNGR										
R6N IF WATER HEAT DISTRICT HEAT DOWNGR										
R6O IF WATER HEAT DISTRICT HEAT DOWNGR										
R6P IF WATER HEAT DISTRICT HEAT DOWNGR										
R6Q IF WATER HEAT DISTRICT HEAT DOWNGR										
R6R IF WATER HEAT DISTRICT HEAT DOWNGR										
R6S IF WATER HEAT DISTRICT HEAT DOWNGR										
R6T IF WATER HEAT DISTRICT HEAT DOWNGR										
R6U IF WATER HEAT DISTRICT HEAT DOWNGR										
R6V IF WATER HEAT DISTRICT HEAT DOWNGR										
R6W IF WATER HEAT DISTRICT HEAT DOWNGR										
R6X IF WATER HEAT DISTRICT HEAT DOWNGR										
R6Y IF WATER HEAT DISTRICT HEAT DOWNGR										
R6Z IF WATER HEAT DISTRICT HEAT DOWNGR										
R7A IF AIR CONDITIONING CENTRAL										
R7B IF AIR CONDITIONING CENTRAL										
R7C IF AIR CONDITIONING CENTRAL										
R7D IF AIR CONDITIONING CENTRAL										
R7E IF AIR CONDITIONING CENTRAL										
R7F IF AIR CONDITIONING CENTRAL										
R7G IF AIR CONDITIONING CENTRAL										
R7H IF AIR CONDITIONING CENTRAL										
R7I IF AIR CONDITIONING CENTRAL										
R7J IF AIR CONDITIONING CENTRAL										
R7K IF AIR CONDITIONING CENTRAL										
R7L IF AIR CONDITIONING CENTRAL										
R7M IF AIR CONDITIONING CENTRAL										
R7N IF AIR CONDITIONING CENTRAL										
R7O IF AIR CONDITIONING CENTRAL										
R7P IF AIR CONDITIONING CENTRAL										
R7Q IF AIR CONDITIONING CENTRAL										
R7R IF AIR CONDITIONING CENTRAL										
R7S IF AIR CONDITIONING CENTRAL										
R7T IF AIR CONDITIONING CENTRAL										
R7U IF AIR CONDITIONING CENTRAL										
R7V IF AIR CONDITIONING CENTRAL										
R7W IF AIR CONDITIONING CENTRAL										
R7X IF AIR CONDITIONING CENTRAL										
R7Y IF AIR CONDITIONING CENTRAL										
R7Z IF AIR CONDITIONING CENTRAL										
R8A IF COOKING GAS										
R8B IF COOKING GAS										
R8C IF COOKING GAS										
R8D IF COOKING GAS										
R8E IF COOKING GAS										
R8F IF COOKING GAS										
R8G IF COOKING GAS										
R8H IF COOKING GAS										
R8I IF COOKING GAS										
R8J IF COOKING GAS										
R8K IF COOKING GAS										
R8L IF COOKING GAS										
R8M IF COOKING GAS										
R8N IF COOKING GAS										
R8O IF COOKING GAS										
R8P IF COOKING GAS										
R8Q IF COOKING GAS										
R8R IF COOKING GAS										
R8S IF COOKING GAS										
R8T IF COOKING GAS										
R8U IF COOKING GAS										
R8V IF COOKING GAS										
R8W IF COOKING GAS										
R8X IF COOKING GAS										
R8Y IF COOKING GAS										
R8Z IF COOKING GAS										
R9A IF MISC APPLIANCE GAS										
R9B IF MISC APPLIANCE GAS										
R9C IF MISC APPLIANCE GAS										
R9D IF MISC APPLIANCE GAS										
R9E IF MISC APPLIANCE GAS										
R9F IF MISC APPLIANCE GAS										
R9G IF MISC APPLIANCE GAS										
R9H IF MISC APPLIANCE GAS										
R9I IF MISC APPLIANCE GAS										
R9J IF MISC APPLIANCE GAS										
R9K IF MISC APPLIANCE GAS										
R9L IF MISC APPLIANCE GAS										
R9M IF MISC APPLIANCE GAS										
R9N IF MISC APPLIANCE GAS										
R9O IF MISC APPLIANCE GAS										
R9P IF MISC APPLIANCE GAS										
R9Q IF MISC APPLIANCE GAS										
R9R IF MISC APPLIANCE GAS										
R9S IF MISC APPLIANCE GAS										
R9T IF MISC APPLIANCE GAS										
R9U IF MISC APPLIANCE GAS										
R9V IF MISC APPLIANCE GAS										
R9W IF MISC APPLIANCE GAS										
R9X IF MISC APPLIANCE GAS										
R9Y IF MISC APPLIANCE GAS										
R9Z IF MISC APPLIANCE GAS										
R0A IF MISC APPLIANCE GAS										
R0B IF MISC APPLIANCE GAS										
R0C IF MISC APPLIANCE GAS										
R0D IF MISC APPLIANCE GAS										
R0E IF MISC APPLIANCE GAS										
R0F IF MISC APPLIANCE GAS										
R0G IF MISC APPLIANCE GAS										
R0H IF MISC APPLIANCE GAS										
R0I IF MISC APPLIANCE GAS										
R0J IF MISC APPLIANCE GAS										
R0K IF MISC APPLIANCE GAS										
R0L IF MISC APPLIANCE GAS										
R0M IF MISC APPLIANCE GAS										
R0N IF MISC APPLIANCE GAS										
R0O IF MISC APPLIANCE GAS										
R0P IF MISC APPLIANCE GAS										
R0Q IF MISC APPLIANCE GAS										
R0R IF MISC APPLIANCE GAS										
R0S IF MISC APPLIANCE GAS										
R0T IF MISC APPLIANCE GAS										
R0U IF MISC APPLIANCE GAS										
R0V IF MISC APPLIANCE GAS										
R0W IF MISC APPLIANCE GAS										
R0X IF MISC APPLIANCE GAS										
R0Y IF MISC APPLIANCE GAS										
R0Z IF MISC APPLIANCE GAS										
R1A IF MISC APPLIANCE GAS										
R1B IF MISC APPLIANCE GAS										
R1C IF MISC APPLIANCE GAS										
R1D IF MISC APPLIANCE GAS										
R1E IF MISC APPLIANCE GAS										
R1F IF MISC APPLIANCE GAS										
R1G IF MISC APPLIANCE GAS										
R1H IF MISC APPLIANCE GAS										
R1I IF MISC APPLIANCE GAS										
R1J IF MISC APPLIANCE GAS										
R1K IF MISC APPLIANCE GAS										
R1L IF MISC APPLIANCE GAS										
R1M IF MISC APPLIANCE GAS										
R1N IF MISC APPLIANCE GAS										
R1O IF MISC APPLIANCE GAS										
R1P IF MISC APPLIANCE GAS										
R1Q IF MISC APPLIANCE GAS										
R1R IF MISC APPLIANCE GAS										
R1S IF MISC APPLIANCE GAS										
R1T IF MISC APPLIANCE GAS										
R1U IF MISC APPLIANCE GAS										
R1V IF MISC APPLIANCE GAS										
R1W IF MISC APPLIANCE GAS										
R1X IF MISC APPLIANCE GAS										
R1Y IF MISC APPLIANCE GAS										
R1Z IF MISC APPLIANCE GAS										
R2A IF MISC APPLIANCE GAS										
R2B IF MISC APPLIANCE GAS										
R2C IF MISC APPLIANCE GAS										
R2D IF MISC APPLIANCE GAS										
R2E IF MISC APPLIANCE GAS										
R2F IF MISC APPLIANCE GAS										
R2G IF MISC APPLIANCE GAS										
R2H IF MISC APPLIANCE GAS										
R2I IF MISC APPLIANCE GAS										
R2J IF MISC APPLIANCE GAS										
R2K IF MISC APPLIANCE GAS										
R2L IF MISC APPLIANCE GAS										
R2M IF MISC APPLIANCE GAS										
R2N IF MISC APPLIANCE GAS										
R2O IF MISC APPLIANCE GAS										
R2P IF MISC APPLIANCE GAS										
R2Q IF MISC APPLIANCE GAS										
R2R IF MISC APPLIANCE GAS										

New York State Emissions 04-Jun-81

UNIT/CO2	NOX lb/yr	NOX lb/1000Btu	TP lb/yr	TP lb/1000Btu	SOX lb/yr	SOX lb/1000Btu	CO lb/yr	CO lb/1000Btu	VC lb/yr	VC lb/1000Btu	ASL/PTONS
R22 OTFC BLD SH GAS	48.8	0.0442816	9.21	0.00835347	0.284	0.000257588	9.72	0.00881604	9.2	0.00834444	Surrogate commercial
R23 OTFC BLD SH DIESEL	217	0.198819	54.1	0.0490887	114	0.103398	72.2	0.0654854	54	0.048978	Surrogate commercial 0.218X 50P
R24 OTFC BLD SH RESIDUAL DL	200	0.1814	76.8	0.0896576	341	0.309287	13.4	0.0121538	76.8	0.0896576	Surrogate industrial 0.85X S
R25 OTFC BLD SH ELECTRIC - IMPROVED DT.											
R26 OTFC BLD SH GAS - IMPROVED DT.											
R27 OTFC BLD SH DIESEL - IMPROVED DT.											
R28 OTFC BLD SH RES. DL - IMPROVED DT.											
R29 OTFC BLD SH CONSERVATION LEVEL 1											
R30 OTFC BLD SH SOLAR											
R31 OTFC BLD SH DISTRICT HEAT DOWNGRADE											
R32 OTFC BLD SH CONSERVATION											
R33 OTFC BLD WH GAS	48.8	0.0442816	9.21	0.00835347	0.284	0.000257588	9.72	0.00881604	9.2	0.00834444	Surrogate commercial
R34 OTFC BLD WH DIESEL	217	0.198819	54.1	0.0490887	114	0.103398	72.2	0.0654854	54	0.048978	Surrogate commercial 0.218X 50P
R35 OTFC BLD WH RESIDUAL DL	200	0.1814	76.8	0.0896576	341	0.309287	13.4	0.0121538	76.8	0.0896576	Surrogate industrial 0.85X S
R36 SERVICE BLD SH GAS											
R37 SERVICE BLD SH DIESEL											
R38 SERVICE BLD SH RESIDUAL DL											
R39 SERVICE BLD SH ELECTRIC - IMPROVED DT.											
R40 SERVICE BLD SH GAS - IMPROVED DT.											
R41 SERVICE BLD SH DIESEL - IMPROVED DT.											
R42 SERVICE BLD SH RES. DL - IMPROVED DT.											
R43 SERVICE BLD SH CONSERVATION LEVEL 1											
R44 SERVICE BLD SH SOLAR											
R45 SERVICE BLD SH DISTRICT HEAT DOWNGRADE											

New York State Emissions 04-Jun-91

	TECHNOLOGY	NOX lb/yr	NOX kg/mwh	TP lb/yr	TP kg/mwh	SO ₂ lb/yr	SO ₂ kg/mwh	CO lb/yr	CO kg/mwh	VC lb/yr	VC kg/mwh	VC ASSEMBLINGS
R0	SERVICE BLDG SH COORDINATION											
R1	SERVICE BLDG WH ELECTRIC	48.8	0.0442616	9.21	0.00833347	0.284	0.000257388	9.72	0.00818604	9.2	0.0083444	Saratoga commercial
R2	SERVICE BLDG WH GAS	217	0.198819	54.1	0.0490887	114	0.103398	72.2	0.0654854	54	0.048978	Saratoga commercial
R3	SERVICE BLDG WH OIL											
R4	SERVICE BLDG WH SOLAR											
R5	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R6	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R7	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R8	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R9	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R10	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R11	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R12	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R13	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R14	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R15	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R16	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R17	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R18	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R19	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R20	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R21	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R22	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R23	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R24	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R25	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R26	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R27	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R28	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R29	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R30	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R31	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R32	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R33	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R34	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R35	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R36	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R37	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R38	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R39	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R40	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R41	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R42	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R43	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R44	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R45	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R46	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R47	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R48	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R49	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R50	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R51	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R52	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R53	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R54	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R55	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R56	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R57	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R58	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R59	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R60	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R61	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R62	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R63	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R64	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R65	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R66	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R67	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R68	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R69	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R70	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R71	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R72	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R73	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R74	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R75	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R76	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R77	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R78	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R79	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R80	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R81	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R82	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R83	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R84	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R85	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R86	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R87	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R88	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R89	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R90	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R91	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R92	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R93	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R94	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R95	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R96	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R97	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R98	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R99	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											
R100	SERVICE BLDG WH SOLAR COINTEGRATED WITH SH											

New York State Emissions 04-Jun-91

[illegible]

New York State Elections 04-Jun-91

[illegible]

New York State Emissions 04-Jun-81

TECHNOLOGY	NOX kg/yr	NOX kg/ton	TP kg/yr	TP kg/ton	SO ₂ kg/yr	SO ₂ kg/ton	CO kg/yr	CO kg/ton	VC kg/yr	VC kg/ton	ASSUMPTIONS
E33 LIQUID METAL REACTORS											
E34 NUCLEAR FUEL REACTORS											
E35 WASTE OIL REACTORS											
E36 WASTE OIL REACTORS											
E37 WASTE OIL REACTORS											
E38 WASTE OIL REACTORS											
E39 WASTE OIL REACTORS											
E40 WASTE OIL REACTORS											
E41 WASTE OIL REACTORS											
E42 WASTE OIL REACTORS											
E43 WASTE OIL REACTORS											
E44 WASTE OIL REACTORS											
E45 WASTE OIL REACTORS											
E46 WASTE OIL REACTORS											
E47 WASTE OIL REACTORS											
E48 WASTE OIL REACTORS											
E49 WASTE OIL REACTORS											
E50 WASTE OIL REACTORS											
E51 WASTE OIL REACTORS											
E52 WASTE OIL REACTORS											
E53 WASTE OIL REACTORS											
E54 WASTE OIL REACTORS											
E55 WASTE OIL REACTORS											
E56 WASTE OIL REACTORS											
E57 WASTE OIL REACTORS											
E58 WASTE OIL REACTORS											
E59 WASTE OIL REACTORS											
E60 WASTE OIL REACTORS											
E61 WASTE OIL REACTORS											
E62 WASTE OIL REACTORS											
E63 WASTE OIL REACTORS											
E64 WASTE OIL REACTORS											
E65 WASTE OIL REACTORS											
E66 WASTE OIL REACTORS											
E67 WASTE OIL REACTORS											
E68 WASTE OIL REACTORS											
E69 WASTE OIL REACTORS											
E70 WASTE OIL REACTORS											
E71 WASTE OIL REACTORS											
E72 WASTE OIL REACTORS											
E73 WASTE OIL REACTORS											
E74 WASTE OIL REACTORS											
E75 WASTE OIL REACTORS											
E76 WASTE OIL REACTORS											
E77 WASTE OIL REACTORS											
E78 WASTE OIL REACTORS											
E79 WASTE OIL REACTORS											
E80 WASTE OIL REACTORS											
E81 WASTE OIL REACTORS											
E82 WASTE OIL REACTORS											
E83 WASTE OIL REACTORS											
E84 WASTE OIL REACTORS											
E85 WASTE OIL REACTORS											
E86 WASTE OIL REACTORS											
E87 WASTE OIL REACTORS											
E88 WASTE OIL REACTORS											
E89 WASTE OIL REACTORS											
E90 WASTE OIL REACTORS											
E91 WASTE OIL REACTORS											
E92 WASTE OIL REACTORS											
E93 WASTE OIL REACTORS											
E94 WASTE OIL REACTORS											
E95 WASTE OIL REACTORS											
E96 WASTE OIL REACTORS											
E97 WASTE OIL REACTORS											
E98 WASTE OIL REACTORS											
E99 WASTE OIL REACTORS											
E100 WASTE OIL REACTORS											

07-Feb-92

New York State Automobile Emissions - "existing fleet"																
Model Year	1990				1993				1998				2003			
	VMT	HC	CO	NOx	VMT	HC	CO	NOx	VMT	HC	CO	NOx	VMT	HC	CO	NOx
<= 1980	1.53E 10	22994345	2.3E 08	30659126	6.24E 09	9367500	93675000	12490000	0	0	0	0	0	0	0	0
1981	3.29E 09	1350224	11196977	3293228	2.04E 09	834591.1	6920999	2035588	0	0	0	0	0	0	0	0
1982	3.59E 09	1472556	12211443	3591601	2.4E 09	984521	8164320	2401271	0	0	0	0	0	0	0	0
1983	4.39E 09	1800873	14934067	4392373	3.06E 09	1252579	10387245	3055072	4.72E 08	193609.6	1605543	472218.6	0	0	0	0
1984	6.66E 09	2731376	22650433	6661892	4.5E 09	1844639	15297010	4499121	1.39E 09	568473.8	4714173	1386521	0	0	0	0
1985	7.34E 09	3010482	24964976	7342640	5.15E 09	2112863	17521304	5153325	2.13E 09	875193	7257698	2134617	0	0	0	0
1986	8.01E 09	3284695	27238930	8011450	6.04E 09	2477465	20544836	6042599	2.94E 09	1205194	9994290	2939497	0	0	0	0
1987	9.26E 09	3795529	31475122	9257389	7.08E 09	2903280	24075983	7081171	3.62E 09	1483253	12300149	3617691	0	0	0	0
1988	9.82E 09	4026762	33392659	9821370	7.13E 09	2924660	24253278	7133317	3.91E 09	1603277	13295464	3910431	6.04E 08	247816.4	2055063.1975	604430.4
1989	9.38E 09	3845462	31889196	9379175	7.29E 09	2989531	24791233	7291539	4.08E 09	1674137	13883090	4083262	1.26E 09	515929.1	4278436.618	1258364
1990	7.54E 09	3093372	25652354	7544810	6.1E 09	2499607	20728445	6096602	3.56E 09	1461038	12115926	3563508	1.48E 09	605193.2	5018675.2956	1476081
	8.46E 10	51405675	4.66E 08	99955055	5.7E 10	30191238	2.66E 08	63279604	2.21E 10	9064176	75166334	22107745	3.34E 09	1368939	11352175.111	3338875
kg/VMT		0.00041	0.0034	0.001		0.00041	0.0034	0.001		0.00041	0.0034	0.001		0.00041	0.0034	0.001
kg/mmBtu		0.0971	0.88	0.189		0.0846	0.747	0.177		0.066	0.54	0.16		0.066	0.54	0.16

APPENDIX V. DOCUMENTATION OF TECHNOLOGY DATABASE

Data Structure And Sources

The structure of NY MARKAL data simulates the flow of energy in various forms (energy carriers) from their sources of supply through intermediate steps of transformation, transportation, and transmission, to the demand devices which satisfy the enduse demand in each demand category. The enduse demands which drive the system are calculated based on current energy consumption pattern, utilization efficiencies, current and projected economic bases associated with the enduses. The intermediate steps include electricity generation (centralized and decentralized), resource and fuel processing, energy storage, and various energy transportation and transmission networks. The sources of supply include imports, in-state mining, and renewable energy resources. Parallel to the energy flow, a set of environmental emission coefficients accounting the amount of carbon dioxide, sulfur oxides, nitrogen oxides, and particles released per unit flow of energy is also defined for each technology in the database.

In addition to the references cited earlier in this report, other primary sources used completing the NY MARKAL database are Draft New York State Energy Plan (NYSEO, 1989), New York State Energy Office Residential End-Use Energy Planning System (REEPS), New York State Energy Office Commercial Energy Demand Modeling Service (CEDMS), New York State Econometric Industrial Energy Demand Model (EIEDM), Annual Energy Review published by the New York State Energy Office (NYSEO, 1990), the New York State Department of Transportation Demand Model (NYSDOT, 1988) capacity planning and operating statistics from the New York Power Pool (NYPP 1990a, 1990b, 1990c), Technical Assessment Guide of Electric Power Research Institute (EPRI, 1987), technology assessments by the U.S. Department of Energy (DOE 1991c), the New York State Energy Advisory Service to Industry Program (EASI, 1989), The New York State Energy Research and Development Authority Electricity Conservation Study (NYSERDA, 1986), the U.S. MARKAL Database (U.S. MARKAL, 1991).

Despite the vast amount of information provided in these sources, arbitrary assumptions had to be made in cases in which the required data or projections were not readily available. This is particularly true during the development of NY MARKAL input data for the time periods beyond the terminal year (2010) in the current State Energy Plan. For the purpose of demonstrating the capability and use of MARKAL, however, the base case and the few scenarios established in this study were shown to be responsive for analyzing the impact of energy and environmental policies and issues of interest within the State, notwithstanding the inherent uncertainties in long run projections and the dubious quality of a small fraction of the input data.

In the following sections, a brief discussion on the data characterization, data sources, and key assumptions made in completing the input data files for each MARKAL classes is presented. Because of the exceedingly large volume of information involved, however, specific values contained in these files are not included in this report, for which the users may conveniently inquire from NY MARKAL input tables through MUSS.

Energy Resource

In NY MARKAL, the energy resources cover all fossil fuel imports from out of state, the natural gas produced within the state, and net electricity imports from Pennsylvania and Quebec, Canada. Table V-1 (Class SRCENCP in NY MARKAL) lists the base case supply sources which contribute or have the potential to contribute to the New York State energy system. For natural gas, total potential supply includes projected supply (pipeline and non-pipeline sources) to local distribution companies, new gas supplies from proposed projects, from indigenous mining, and purchases of enduse customers. For periods beyond 2010, this total and its price components were linearly extrapolated to 2023 (the terminal year in NY MARKAL) using their average growth rates between 1990 and 2010 projected in the 1989 SEO forecast.

For refined oil products, coal, and nuclear fuel, their future supplies to the State were assumed to be unlimited within the NY MARKAL planning horizon. The Import costs of refined oil products were extrapolated from the reference forecast of the 1989 SEO. The import prices of coal were based on its projected costs to electric utilities. The prices of nuclear fuel reflect the cost increases in fuel processing and distribution in the national market. Future wood supplies and costs in the State were kept at their current consumption and price levels.

Electricity imports from Quebec, Canada were projected based on the renewal of the current diversity contract (800 MW) and the approval of the 1000 MW firm capacity contract. Future imports from Pennsylvania were kept at the current level.

Conversion Technologies

In MARKAL, conversion technologies are defined as those which produce electricity or district heat or both. Table V-2 (Class ELE in NY MARKAL) lists existing and new electric generation technologies defined in the base case. Each technology is characterized by a set of technical parameters which include fuel type(s), availability factor, heat rate, and the useful life time. The key financial factors associated with each technology are investment cost per unit capacity, operating and maintenance cost (fixed and variable). For existing power plants and conversion facilities, data on these parameters were obtained from actual operating statistics compiled by New York Power Pool and the Energy Information Administration of

evaluations. Conservation supply schedules for various commercial buildings by enduse were constructed based on NYSERDA study and data collected under EASI Program.

In the transportation sector, the base year energy consumption patterns and the characteristics of the current fleet in each mode were derived base on NY DOT historical data. The new demand devices include more efficient vehicles and vehicles using alternative fuels that have potential to satisfy future New York State transportation needs. The technical and economic data for these options were derived from DOE transportation studies and policies.

Energy Conservation Data from EASI

We obtained data from NYSEO that was collected in the Energy Advisory Service to Industry (EASI) program between June 1987 and April 1990 on potential energy savings from conservation measures.

Preparation Of EASI Data For NYMARKAL. The EASI data were segregated into industry (SIC 2,3) and commerce (SIC 5, 6, 7, 8). Within these two sectors, the data were separated into those energy conservation measures (ECM) that save electricity and those that save other fuels. Within electricity-saving ECMs, those that affect electric motor use were separated from those that do not. All cogeneration ECMs were removed from this database since MARKAL treats cogeneration separately.

Five or six percent of the data had a zero entry in either the investment cost or energy savings category. All these were eliminated from the database. In some cases, the cost may indeed have been zero (for example, turning down thermostats). In other cases, a cost may be estimated from other applications of the same ECM. The database may therefore be further fine-tuned by screening these other ECMs that were omitted here. No estimate is included of the effect of these ECMs on operations or maintenance costs.

Scaling up to New York State. EASI was a sample of a subset of the New York industrial and commercial sectors. It was important to understand to what fraction of the commercial and industrial energy demands the EASI data were applicable. Review of the latest Census of Manufactures showed that establishments with over 500 employees accounted for only 1% of manufacturing establishments in New York State. Categories in the Census of Manufacturers did not have a 400 employee cutoff to match the EASI criteria. Since the percentage of large establishments was very low, even though their percentage share of the total industrial energy use would be higher by an unknown amount, it was decided to scale up the EASI data to the entire state. In part this can be justified on the basis that at least some of the conservation measures in the EASI data are applicable to large as well as small industries. Table V-4 shows the scaling factor to be used in the column, "Factor, Total/EASI."

Results. The energy conservation supply curves for the EASI sample are shown in Figures V-1 through V-8, as indicated in Table V-4. In all cases, the X-axis shows energy savings in 10^9 Btu. The Y-axis shows initial investment in thousands of dollars.

The precise coordinates of the end-point can be read from Table V-4 in the columns labeled Energy Savings and \$ Investment. Figures 1 and 5, "Except Electricity," were scaled up by the total fuel use outside the electrical sector estimated for 1988 in the New York State Annual Energy Review, 1970-1988, pp. 22 and 24, shown as Total Purchased Fuels in Table V-5. Table V-5 also compares the data from three sources. For total electricity, Figures V-2 and V-6, the coordinates were scaled up according to total industrial or commercial electricity consumption in the seven private NYS utilities, averaged for 1988 and 1989. This calculation is shown in Table V-6. (New York Power Authority electricity, delivered principally to large industrial and municipal customers, is not included in these figures.) With the electrical sector separated into segments with and without electric motors, total electrical use must be similarly divided. In Table V-4, "Total Sample Energy" shows the energy use by establishments in which the individual ECMs were recommended. Inasmuch as the same establishment may have an electric motor ECM and one that does not affect electric motors, the sum of Total Sample Energy for Electricity (except motors) and Electric Motors is greater than Total Sample Energy for Electricity alone.

Reference:

US Department of Commerce, Bureau of the Census. 1990. 1987 Census of Manufacturers, Geographic Area Series, New York. U.S. Government Printing Office, Washington, D.C.

US Department of Commerce, Bureau of the Census. 1983. 1982 Census of Manufacturers, Fuels and Electric Energy Consumed, MC82-S-4 (part 2). U.S. Government Printing Office, Washington, D.C.

US Department of Energy, Energy Information Agency. State Energy Data Report, Consumption Estimates, 1960-1988, EIA 0214(88).

Table V-1. Energy Resources in Markal (MARKAL CLASS SRCENCP)

IMPDSH1	RESIDUAL OIL IMPORTS
IMPDSL1	DIESEL FUEL IMPORTS
IMPELC1	ELECTRICITY IMPORTS FROM PA
IMPELC2	ELECTRICITY IMPORTS FROM QUEBEC
IMPGSL1	GASOLINE IMPORTS
IMPHCO1	LOW SULFUR COAL (.5%) IMPORTS
IMPHCO2	MEDIUM SULFUR COAL (1.5%) IMPORTS
IMPHCO3	HIGH SULFUR COAL (2.5%) IMPORTS
IMPJTF1	JET FUEL IMPORTS
IMPKER1	KEROSENE IMPORTS
IMPLPG1	LPG IMPORTS
IMPLWR1	LWR STANDARD FUEL IMPORTS
IMPNGA1	GAS SUPPLY TO BROOKLYN UNION
IMPNGA2	GAS SUPPLY TO CENTRAL HUDSON
IMPNGA3	GAS SUPPLY TO COLUMBIA
IMPNGA4	GAS SUPPLY TO CON EDISON
IMPNGA5	GAS SUPPLY TO CORNING
IMPNGA6	GAS SUPPLY TO NATIONAL FUEL
IMPNGA7	GAS SUPPLY TO LILCO
IMPNGA8	GAS SUPPLY TO NYSE&G
IMPNGA9	GAS SUPPLY TO NIAGARA MOHAWK
IMPNGAA	GAS SUPPLY TO ROCHESTER G&E
IMPNGAB	GAS SUPPLY TO ORANGE & ROCKLAND
IMPNGAD	NEW GAS SUPPLIES - PROPOSED PROJECTS
IMPNGAE	MISC GAS SUPPLIES
IMPPAP1	PROPANE IMPORTS
MINNGA1	NEW YORK INDIGENOUS GAS SUPPLY
RNWBIT1	NEW YORK INDIGEOUS WOOD SOURCES
RNWBIT2	INDUSTRIAL WOODFUEL-WASTES ETC.
RNWHBC1	HERBACEOUS ENERGY CROPS
RNWMCA1	MICROALGAE DIESEL EQUIVALENT
RNWMSW1	MUNICIPAL SOLID WASTE

Table V-2. Electrical Technologies (MARKAL CLASS ELE)

E01	COAL STEAM ELECTRIC - 1940'S
E02	COAL STEAM ELECTRIC - 1950'S
E03	COAL STEAM ELECTRIC - 1960'S
E04	COAL STEAM ELECTRIC - 1970'S

Table V-2, Continued

E05	COAL STEAM ELECTRIC - 1980'S
E06	OIL STEAM ELECTRIC - 1930'S & 1940'S
E07	OIL STEAM ELECTRIC - 1950'S
E08	OIL STEAM ELECTRIC - 1960'S
E09	OIL STEAM ELECTRIC - 1970'S
E0A	OIL STEAM ELECTRIC - 1980'S
E0B	GAS STEAM ELECTRIC - 1940'S & 1950'S
E0C	OIL COMBUSTION TURBINES- 1960'S
E0D	OIL COMBUSTION TURBINES- 1970'S
E0E	OIL COMBUSTION TURBINES- 1980'S
E0F	GAS COMBUSTION TURBINES- 1960'S & 1970'S
E0G	CONVENTIONAL HYDRO ELECTRIC
E0H	EXISTING NUCLEAR POWER PLANTS
E0I	EXISTING IC GENERATORS
E0J	EXISTING MSW GENERATORS - NON-UTILITY
E0K	EXISTING BIOGAS GENERATORS - NON-UTILITY
E0L	DIESEL CO-GENERATORS - NON-UTILITY
E0M	GAS CO-GENERATORS - NON-UTILITY
E0N	EXISTING HYDRO - NON-UTILITY
E0P	STEAM TURBINE, MULTIPLE FUEL, 1950'S
E0Q	STEAM TURBINE, MULTIPLE FUEL, 1960'S
E0R	STEAM TURBINE, MULTIPLE FUEL, 1970'S
E0S	COMBUSTION TURBINE, MULTIPLE FUEL, 1970
E11	COAL COMBINED CYCLE
E12	ATMOSPHERIC FLUIDIZED BED
E13	PRESSURIZED FLUIDIZED BED
E14	COAL CO-GENERATORS - NON-UTILITY
E16	INTEGRATED GASIFICATION COMBINED CYCLE
E21	NATURAL GAS COMBINED CYCLE
E22	STEAM INJECTION GAS TURBINE
E31	ADVANCED LIGHT WATER REACTORS
E32	HIGH TEMPERATURE REACTORS
E33	LIQUID METAL REACTORS
E34	INTEGRAL FAST REACTORS
E41	BIOMASS STEAM ELECTRIC
E42	SOLAR STEAM ELECTRIC
E44	CENTRAL WIND ELECTRIC
E45	LOCAL WIND ELE W/OUT BACKUP
E46	CENTRAL PHOTOVOLTAIC
E48	LOCAL WIND ELECTRIC
E4A	LOCAL PHOTOVOLTAIC - RESIDENTIAL

Table V-2. Continued

E4J	RETROFIT SO2 SCRUBBER COAL PLANT
E4K	REPOWERED EXISTING COAL PLANT
E51	GAS FUEL CELLS
E52	METHANOL FUEL CELLS
E53	MOLTEN CARBONATE FUEL CELLS
E61	CARBON STEAM ELECTRIC
E96	METHANOL COMBUSTION TURBINE ELECTRIC

Table V-3. Demand Devices (MARKAL CLASS DMD)

I11	GAS BURNER
I12	DIESEL FUEL BURNER
I13	RESIDUAL OIL BURNER
I14	COAL BURNER
I15	LPG BURNER
I16	KEROSENE BURNER
I17	BIOMASS BURNER
I1A	SOLAR HEAT WITH GAS BURNER BACKUP
I1B	SOLAR HEAT WITH DIESEL BURNER BACKUP
I1C	SOLAR HEAT WITH RESID OIL BURNER BACKUP
I1D	SOLAR HEAT WITH COAL BURNER BACKUP
I1E	IMPROVED GAS BURNER
I1F	IMPROVED DIESEL FUEL BURNER
I1G	IMPROVED RESIDUAL OIL BURNER
I1H	IMPROVED COAL BURNER
I1I	CONSERVATION I:INDUSTRIAL PROCESS HEAT
I1J	CONSERVATION II:INDUSTRIAL PROCESS HEAT
I1K	CONSERVATION III:INDUSTRIAL PROCESS HEAT
I1L	COGENERATION TO PROCESS HEAT
I1M	DISTRICT HEAT EXCHANGER TO PROCESS HEAT
I21	ELECTRIC MOTOR
I2A	CONSERVATION I:INDUST. ELECTRIC MOTORS
I2B	CONSERVATION II:INDUST. ELECTRIC MOTORS
I2C	CONSERVATION III:INDUST. ELECTRIC MOTORS
I31	LIGHTING & MISC TOOLS
I3A	CONSERVATION I:INDUST. LIGHTING & MISC
I3B	CONSERVATION II:INDUST. LIGHTING & MISC
I3C	CONSERVATION III:INDUST. LIGHTING & MISC
N11	GAS FEEDSTOCK
N12	DIESEL FEEDSTOCK

Table V-3, Continued.

N13	RESIDUAL OIL FEEDSTOCK
N14	COAL FEEDSTOCK
R00	SF SPACE HEAT GAS CENTRAL
R01	SF SPACE HEAT GAS NONCENTRAL
R02	SF SPACE HEAT OIL CENTRAL
R03	SF SPACE HEAT OIL NONCENTRAL
R04	SF SPACE HEAT ELECTRIC CENTRAL
R05	SF SPACE HEAT ELECTRIC NONCENTRAL
R06	SF SPACE HEAT HEAT PUMP
R07	SF SPACE HEAT COAL STOVE
R08	SF SPACE HEAT WOOD STOVE
R09	SF SPACE HEAT LPG BURNER
R0A	SF SH RETROFIT GAS BURNER
R0B	SF SH NEW & IMPROVED GAS BURNER
R0D	SF SH SOLAR WITH GAS BACKUP
R0E	SF SH NEW GAS DEVICE
R0F	SF SH RETROFIT OIL BURNER
R0G	SF SH NEW & IMPROVED OIL BURNER
R0H	SF SH SOLAR WITH OIL BACKUP
R0L	SF SH SOLAR WITH ELECTRIC BACKUP
R0M	SF SH NEW & IMPROVED HEAT PUMP
R0P	SF SH CONSERVATION LEVEL I
R0Q	SF SH CONSERVATION LEVEL II
R0R	SF SH CONSERVATION LEVEL III
R11	SF WATER HEAT GAS
R12	SF WATER HEAT OIL
R13	SF WATER HEAT ELECTRIC
R1A	SF SOLAR WATER HEAT WITH GAS BACKUP
R1C	SF SOLAR WATER HEAT WITH OIL BACKUP
R1D	SF WH FROM SOLAR SH - GAS BACKUP
R1E	SF SOLAR WATER HEAT WITH ELECTRIC BACKUP
R1H	SF WH FROM SOLAR SH - OIL BACKUP
R1L	SF WH FROM SOLAR SH - ELECTRIC BACKUP
R21	SF AIR CONDITIONING CENTRAL
R22	SF AIR CONDITIONING HEAT PUMP
R23	SF AIR CONDITIONING ROOM
R2A	SF AC CENTRAL - NEW & IMPROVED
R2B	SF AC HEAT PUMP - NEW & IMPROVED
R2C	SF AC ROOM - NEW & IMPROVED
R2P	SF AC CONSERVATION LEVEL I
R2Q	SF AC CONSERVATION LEVEL II

Table V-3. Continued.

R2R	SF AC CONSERVATION LEVEL III
R31	SF COOKING ELECTRIC
R33	SF COOKING PROPANE
R41	SF MISC APPLIANCE ELECTRIC
R42	SF MISC APPLIANCE GAS
R4A	SF MISC APPLIANCE ELECTRIC - IMPROVED
R50	MF SPACE HEAT GAS CENTRAL
R51	MF SPACE HEAT GAS NONCENTRAL
R52	MF SPACE HEAT OIL CENTRAL
R53	MF SPACE HEAT OIL NONCENTRAL
R54	MF SPACE HEAT ELECTRIC CENTRAL
R55	MF SPACE HEAT ELECTRIC NONCENTRAL
R56	MF SPACE HEAT HEAT PUMP
R57	MF SPACE HEAT LPG BURNER
R58	MF SPACE HEAT KEROSENE BURNER
R5A	MF SH RETROFIT GAS BURNER
R5B	MF SH NEW & IMPROVED GAS BURNER
R5D	MF SH SOLAR WITH GAS BACKUP
R5E	MF SH NEW GAS DEVICE
R5F	MF SH RETROFIT OIL BURNER
R5G	MF SH NEW & IMPROVED OIL BURNER
R5H	MF SH SOLAR WITH OIL BACKUP
R5L	MF SH SOLAR WITH ELECTRIC BACKUP
R5M	MF SH NEW & IMPROVED HEAT PUMP
R5P	MF SH CONSERVATION LEVEL I
R5Q	MF SH CONSERVATION LEVEL II
R5R	MF SH CONSERVATION LEVEL III
R5S	MF SPACE HEAT DISTRICT HEAT EXCHANGER
R5T	MF SPACE HEAT COGENERATION
R61	MF WATER HEAT GAS
R62	MF WATER HEAT OIL
R63	MF WATER HEAT ELECTRIC
R6A	MF SOLAR WATER HEAT WITH GAS BACKUP
R6C	MF SOLAR WATER HEAT WITH OIL BACKUP
R6D	MF WH FROM SOLAR SH - GAS BACKUP
R6E	MF SOLAR WATER HEAT WITH ELECTRIC BACKUP
R6H	MF WH FROM SOLAR SH - OIL BACKUP
R6L	MF WH FROM SOLAR SH - ELECTRIC BACKUP
R6S	MF WATER HEAT DISTRICT HEAT EXCHANGER
R71	MF AIR CONDITIONING CENTRAL
R72	MF AIR CONDITIONING HEAT PUMP

Table V-3. Continued.

R73	MF AIR CONDITIONING ROOM
R7A	MF AC CENTRAL - NEW & IMPROVED
R7B	MF AC HEAT PUMP - NEW & IMPROVED
R7C	MF AC ROOM - NEW & IMPROVED
R7P	MF AC CONSERVATION LEVEL I
R7Q	MF AC CONSERVATION LEVEL II
R7R	MF AC CONSERVATION LEVEL III
R81	MF COOKING GAS
R82	MF COOKING ELECTRIC
R83	MF COOKING PROPANE
R91	MF MISC APPLIANCE ELECTRIC
R92	MF MISC APPLIANCE GAS
R9A	MF MISC APPLIANCE ELECTRIC - IMPROVED
RA1	OFFICE BLDG SH ELECTRIC
RA2	OFFICE BLDG SH GAS
RA3	OFFICE BLDG SH DIESEL
RA4	OFFICE BLDG SH RESIDUAL OIL
RAB	OFFICE BLDG SH GAS - IMPROVED EFF.
RAC	OFFICE BLDG SH DIESEL - IMPROVED EFF.
RA	OFFICE BLDG SH RES. OIL - IMPROVED EFF.
D	
RAE	OFFICE BLDG SH CONSERVATION LEVEL I
RAF	OFFICE BLDG SH CONSERVATION LEVEL II
RAG	OFFICE BLDG SH SOLAR
RA	OFFICE BLDG SH DISTRICT HEAT EXCHANGER
H	
RAI	OFFICE BLDG SH COGENERATION
RB1	OFFICE BLDG WH ELECTRIC
RB2	OFFICE BLDG WH GAS
RB3	OFFICE BLDG WH OIL
RBA	OFFICE BLDG WH CONSERVATION LEVEL I
RBB	OFFICE BLDG WH SOLAR
RBG	OFFICE BLDG WH SOLAR COMBINED WITH SH
RC1	OFFICE BLDG AC & VENT ELECTRIC
RC2	OFFICE BLDG AC & VENT GAS
RCA	OFFICE BLDG AC HIGH EFF. GAS ABSORPTION
RCB	OFFICE BLDG AC DISTRICT HEAT ABSORPTION
RCE	OFFICE BLDG AC CONSERVATION LEVEL I
RCF	OFFICE BLDG AC CONSERVATION LEVEL II
RD1	OFFICE BLDG LIGHT & APPLIANCES ELECTRIC
RD2	OFFICE BLDG LIGHT & APPLIANCES GAS

Table V-3. Continued.

RD	OFFICE BLDG L & A CONSERVATION
A	
RDB	OFFICE BLDG IMPROVED LIGHTING SYSTEM
RE1	SERVICE BLDG SH ELECTRIC
RE2	SERVICE BLDG SH GAS
RE3	SERVICE BLDG SH DIESEL
RE4	SERVICE BLDG SH RESIDUAL OIL
REB	SERVICE BLDG SH GAS - IMPROVED EFF.
REC	SERVICE BLDG SH DIESEL - IMPROVED EFF.
RED	SERVICE BLDG SH RES. OIL - IMPROVED EFF.
REE	SERVICE BLDG SH CONSERVATION LEVEL I
REF	SERVICE BLDG SH CONSERVATION LEVEL II
REG	SERVICE BLDG SH SOLAR
REH	SERVICE BLDG SH DISTRICT HEAT EXCHANGER
REI	SERVICE BLDG SH COGENERATION
RF1	SERVICE BLDG WH ELECTRIC
RF2	SERVICE BLDG WH GAS
RF3	SERVICE BLDG WH OIL
RFA	SERVICE BLDG WH CONSERVATION LEVEL I
RFB	SERVICE BLDG WH SOLAR
RFG	SERVICE BLDG WH SOLAR COMBINED WITH SH
RG1	SERVICE BLDG A/C & VENT ELECTRIC
RG2	SERVICE BLDG A/C & VENT GAS
RGA	SERVICE BLDG AC HIGH EFF. GAS ABSORPTION
RGB	SERVICE BLDG AC DISTRICT HEAT ABSORPTION
RGE	SERVICE BLDG AC CONSERVATION LEVEL I
RGF	SERVICE BLDG AC CONSERVATION LEVEL II
RH1	SERVICE BLDG LIGHT & APPLIANCES ELECTRIC
RH2	SERVICE BLDG LIGHT & APPLIANCES GAS
RH	SERVICE BLDG L & A CONSERVATION
A	
RHB	SERVICE BLDG IMPROVED LIGHTING SYSTEM
RI1	MISC BLDG SH ELECTRIC
RI2	MISC BLDG SH GAS
RI3	MISC BLDG SH DIESEL
RI4	MISC BLDG SH RESIDUAL OIL
RIB	MISC BLDG SH GAS - IMPROVED EFF.
RIC	MISC BLDG SH DIESEL - IMPROVED EFF.
RID	MISC BLDG SH RES. OIL - IMPROVED EFF.
RIE	MISC BLDG SH CONSERVATION LEVEL I
RIF	MISC BLDG SH CONSERVATION LEVEL II

Table V-3. Continued.

RIG	MISC BLDG SH SOLAR
RIH	MISC BLDG SH DISTRICT HEAT EXCHANGER
RII	MISC BLDG SH COGENERATION
RJ1	MISC BLDG WH ELECTRIC
RJ2	MISC BLDG WH GAS
RJ3	MISC BLDG WH OIL
RJA	MISC BLDG WH CONSERVATION LEVEL I
RJB	MISC BLDG WH SOLAR
RJG	MISC BLDG WH SOLAR COMBINED WITH SH
RK1	MISC BLDG A/C & VENT ELECTRIC
RK2	MISC BLDG A/C & VENT GAS
RKA	MISC BLDG AC HIGH EFF. GAS ABSORPTION
RKB	MISC BLDG AC DISTRICT HEAT ABSORPTION
RKE	MISC BLDG AC CONSERVATION LEVEL I
RKF	MISC BLDG AC CONSERVATION LEVEL II
RL1	MISC BLDG LIGHT & APPLIANCES ELECTRIC
RL2	MISC BLDG LIGHT & APPLIANCES GAS
RLA	MISC BLDG L & A CONSERVATION
RLB	MISC BLDG IMPROVED LIGHTING SYSTEM
RX1	COMMERCIAL BLDGS MISC USE COAL & OTHER
T11	AUTOMOBILE - GASOLINE, EXISTING FLEET
T12	AUTOMOBILE - DIESEL, EXISTING FLEET
T13	AUTOMOBILE - ELECTRIC
T14	AUTOMOBILE - METHANOL
T15	AUTOMOBILE - HYDROGEN
T16	AUTOMOBILE - COMPRESSED NATURAL GAS
T17	AUTOMOBILE - 10% MPG IMPROVEMENT
T18	AUTOMOBILE - 20% MPG IMPROVEMENT
T19	AUTOMOBILE - 40% MPG IMPROVEMENT
T1A	AUTOMOBILE - DIESEL 10% MPG IMPROVEMENT
T1B	AUTOMOBILE - DIESEL 20% MPG IMPROVEMENT
T21	LIGHT TRUCK - GASOLINE, EXISTING FLEET
T22	LIGH TRUCK - DIESEL
T23	LIGHT TRUCK - HYDROGEN
T24	LIGHT TRUCK - METHANOL
T25	LIGHT TRUCK - COMPRESSED NATURAL GAS
T26	LIGHT TRUCK- GASOLINE, 10% MPG IMPROVEMT
T27	LIGHT TRUCK- GASOLINE, 20% MPG IMPROVEMT
T31	BUS - GASOLINE, EXISTING FLEET
T32	BUS - DIESEL, EXISTING FLEET
T33	BUS - HYDROGEN

Table V-3. Continued.

T34	BUS - METHANOL
T35	BUS - COMPRESSED NATURAL GAS
T36	BUS - GASOLINE 10% MPG IMPROVEMENT
T37	BUS - GASOLINE 20% MPG IMPROVEMENT
T38	BUS - DIESEL 10% MPG IMPROVEMENT
T39	BUS - DIESEL 20% MPG IMPROVEMENT
T41	SUBWAY & URBAN RAIL - ELECTRIC
T42	URBAN RAIL - DIESEL
T51	INTERCITY RAIL - PASSENGER, ELECTRIC
T52	INTERCITY RAIL - PASSENGER, DIESEL
T61	INTERCITY RAIL - FREIGHT, ELECTRIC
T62	INTERCITY RAIL - FREIGHT, DIESEL
T71	AIR - JET FUEL
T72	AIR - GASOLINE
T73	AIR - HYDROGEN
T81	VESSEL - GASOLINE
T82	VESSEL - DIESEL
T83	VESSEL - RESIDUAL OIL
T91	MISC TRANSPORT - GASOLINE
T92	MISC TRANSPORT - DIESEL
T93	MISC TRANSPORT - ELECTRIC
T94	MISC TRANSPORT - LPG
TH1	HEAVY TRUCK - DIESEL, EXISTING FLEET
TH2	HEAVY TRUCK - HYDROGEN
TH3	HEAVY TRUCK - METHANOL
TH4	HEAVY TRUCK - COMPRESSED NATURAL GAS
TH5	HEAVY TRUCK - DIESEL, 10% MPG IMPROVEMENT
TH6	HEAVY TRUCK - DIESEL, 20% MPG IMPROVEMENT

Table V-4. Summary of EASI Sample.

Figure	INDUSTRY (SIC 2,3)	Number of ECMs	EASI SAMPLE			1988/1989			Factor Total/EASI
			Energy Savings TStu	\$ Investment (millions)	Total Sample Energy - TStu	TStu Consumed	Total Sectoral Energy TStu Fuel Input		
1	Except Electricity	2229	2.563	9.776	14.235	224.90	224.90	15.80	
2	Electricity	4653	1.249	13.404	23.597	132.88	453.52	19.22	
3	Electricity (exc. motors)	4187	1.025	10.379	22.382	126.04	430.17	19.22	
4	Electric motors	466	0.225	3.025	7.225	40.69	138.87	19.22	
COMMENCE (SIC 5, 6, 7, 8)									
5	Except Electricity	1245	0.673	8.267	2.839	369.10	369.10	130.01	
6	Electricity	3034	0.746	9.090	8.378	169.20	577.48	68.93	
7	Electricity (exc. motors)	2888	0.720	8.606	8.169	166.99	569.94	68.93	
8	Electric Motors	146	0.026	0.483	1.506	30.42	103.82	68.94	

Notes: Except for electricity, total 1988/89 energy is from NYS Annual Energy Review, 1970-1988, for 1988, p. 22,24.
Electricity is from NYSEO and Moody's Public Utility Manual, average 1988/89, as shown in Table 3.
"Total Sample Energy" is the energy use by establishments where ECI has been recommended.

Table V-5. Industrial Energy Consumption, New York State, 1981 and 1988.

		1981		1988	
		Census of Mfgs (1982) pp. 4-62, -63	DOE/EIA-0214(88) (1988) p. 222	DOE/EIA-0214(88) (1988) p. 222	NYS Annual Energy 1970-1988 p. 24
Coal	Tbtu Mtons	2331.1	138.7 5420 w/lignite	91.4 3527	83.3 3387
Natural Gas	Tbtu BCF	119.3	124.2 122	94.3 92	90.2 87.5
Distillate Oil	Tbtu Mbbbl	3030.7	35.7 6129	21.6 3705	23.8 4086
Residual Oil	Tbtu Mbbbl	8497.9	50.2 7987	22.7 3607	22.5 3581
Kerosene	Tbtu Mbbbl		2.3 405	2.3 412	2.3 413
LPG	Tbtu Mbbbl MM lb	84.9	7.4 1917	2.8 758	2.8 718
Total Purchased Fuels	Tbtu	330.2	479.4	354.5	224.9
Electricity Consumption	Tbtu GWh	29367.1	110 32240	102.9 30155	95.9 28105
Electrical System Losses	Tbtu GWh		262.2 76837	232.3 68097	
Electricity Generation	Tbtu GWh		372.2 109077	335.2 98252	
Total Purchased Fuels and Electric Energy	Tbtu	430.4	591.8	459.8	320.8

Sources: State Energy Data Report, Consumption Estimates, 1960-1988, DOE/EIA-0214(88)
NYS Annual Energy Review: Energy Consumption, Supply and Price Statistics, 1970-1988
1982 Census of Manufactures, Fuels and Electric Energy Consumed, MC82-S-4 (Part 2) (June 1983)

Table V-6. New York State Industrial and Commercial Electricity Use.

	1981 Industrial (SIC 2, 3)	1988 C&I	1988 Indust'ial (SIC 5, 6, 7, 8)	1989 C&I	1989 Indust'ial	1989 Comm'l	Avg '88-'89
Con Edison	1,560,827	23,946,874	1,383,812	22,563,062	24,709,177	1,335,588	23,373,589
LILCO	1,318,726	8,566,000	1,534,960	7,031,040	8,636,000	1,346,125	7,289,875
Niagara Mohawk Moody's	11,136,029	22,927,000	11,582,520	11,745,000	12,004,609	11,432,000	
NYSEG Moody's	2,760,953	6,228,000	3,088,295	3,159,000	3,136,670	3,181,000	
Rochester G&E Moody's	1,651,263	3,661,579	1,868,711	1,869,417	1,905,761	1,832,521	
Orange & Rockland	511,108	2,343,000	563,717	1,779,283	2,410,000	582,883	1,827,117
Central Hudson	1,182,478	3,054,000	1,681,523	1,372,477	3,205,000	1,778,860	1,426,140
Total Indl (NYSEO) mwh	20,121,384						38,933,940
Total Commercial mwh		38,476,955			39,390,925		132.88
			48,789,024		50,362,242		49,575,633
							169.20

Notes: Industrial electricity sales are from Vaciana James, NYSEO, except as indicated as Moody's Public Utility Manual (1990). Industrial and commercial electricity sales are reported separately in Moody's for 3 utilities; industrial checks closely with SEO. For other utilities, commercial is calculated by subtracting industrial from total industrial and commercial. Averages were calculated for 1988-89, a period central to E&I data collection.

Figure V-1
Cumulative Energy Conservation Supply Curve
SIC 2,3 Except Electricity (edited)

Figure V-2
Cumulative Energy Conservation Supply Curve
Industry (SIC 2,3) All Electric (no cog)

Figure V-3
 Cumulative SIC 2 & 3, Electricity Only
 No Motors or cogeneration (edited)

Figure V-4
 Cumulative SIC 2 & 3, Electricity Only
 Electric Motors Only (edited)

Figure V-5
Cumulative Wholesale & Retail Trade, FIRE, Service
SIC 5,6,7,8 COMMERCIAL (except electric)

Figure V-6
Cumulative Wholesale & Retail Trade, FIRE, Service
SIC 5,6,7,8 COMMERCIAL (electricity only)

Figure V-7
Cumulative Electricity Conservation Supply Curve
Comm'l (SIC 5,6,7,8) Ex. motors & cogen.

Figure V-8
Cumulative Electricity Conservation Supply Curve
Comm'l (SIC 5,6,7,8) Elec. Motors Only

END

**DATE
FILMED**

5 / 13 / 92