AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

|

READINESS THROUGH RESEARCH

**COMBUSTION CHARACTERISTICS OF
HYDRORETORTED ALABAMA OIL SHALE**

by

**Michael J. Roberts
David M. Rue
Francis S. Lau**

**Paper Presented at the
1992 EASTERN OIL SHALE SYMPOSIUM
Lexington, Kentucky**

November 17-20, 1992

INSTITUTE OF GAS TECHNOLOGY

3424 South State Street Chicago, Illinois 60616

IGT

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

870

COMBUSTION CHARACTERISTICS OF HYDRORETORTED ALABAMA OIL SHALE

M. J. Roberts, D. M. Rue, and F. S. Lau

Institute of Gas Technology
3424 South State Street
Chicago, Illinois 60616

Abstract

Pressurized fluidized-bed hydroretorting of beneficiated Eastern U.S. oil shale leaves sufficient carbon (15 to 27 wt%) in the retorted shale to warrant utilization of that calorific value by combustion. A sample of hydroretorted shale from a bench-scale unit test (oil yield was 233% of Fischer Assay) was used as a feedstock for combustion tests using air. The tests were conducted at 815° to 1080°C, 0.1 to 7 MPa and residence times from 1 to 30 minutes in a thermobalance unit and a continuous (0.5 kg/h) fluidized-bed laboratory-scale unit. Thermobalance tests indicate that combustion of the shale begins at 260° to 315°C depending on the oxygen partial pressure used. Carbon conversions up to 100% with greater than 99.5% recovery of the gross calorific value of the shale were achieved.

Introduction

Results of oil shale retorting approaches for Eastern U.S. oil shale during the last decade have clearly demonstrated that the highest possible oil yields are achieved by retorting in the presence of hydrogen at elevated pressure.^{1,2}

Research work conducted by the Institute of Gas Technology (IGT) has indicated that hydroretorting of beneficiated shale significantly improves the overall economics of producing oil. Process economics can be significantly improved by hydroretorting small particles and developing advanced beneficiation technology for oil shale. Efforts to improve economics of hydroretorting have led to the development of a second-generation process, the pressurized fluidized-bed hydroretorting (PFH) process at IGT.

Components of the first PFH design (PFH-I) are shown in Figure 1. In this process, hydrogen is produced by steam reforming of methane. A non-conventional hydrogen generation method is used in a new PFH-II design presently being developed. Information on PFH processing of raw and beneficiated shales is available in previous publications.^{3,4} Beneficiated shale residue from both processes contains carbon which can be utilized to improve the PFH energy efficiency. Combustion results relating to the PFH-I process are presented.

Equipment and Test Procedure

The combustion characteristics of hydroretorted beneficiated Alabama shale were determined in a series of thermogravimetric analysis (TGA) tests. Tests were conducted in an existing high-pressure, high-temperature thermobalance unit. The unit, shown schematically in Figure 2, senses and records the instantaneous weight of a sample undergoing reaction at temperatures and pressures up to 1093°C (2000°F) and 7.0 MPa (1000 psig).

The thermobalance reactor is constructed from Type 316 stainless steel pipe positioned inside a pressure shell. Furnace elements are placed inside the pressure shell (and outside the reactor tube). The pressure shell is filled with nitrogen and maintained at the same pressure as the reactor using a differential pressure controller. The feed gas flow is controlled with a mass flow controller. The exit gas system contains a back-pressure controller, a dry test meter for measuring total gas flow, a liquid knockout trap, and a gas sampling loop.

In a typical thermobalance test, a weighed, representative 1 to 2 gram sample of hydroretorted shale is held in a stainless steel screen basket suspended from a force transducer by a stainless steel wire. The basket is pretreated at test conditions to prevent weight changes of the basket during the test. Thus, the transducer senses only changes in the

Figure 1. MAJOR COMPONENTS OF PFH-I PROCESS CONCEPT

B86040313

Figure 2. SCHEMATIC DIAGRAM OF THERMOBALANCE UNIT

weight of the sample in the basket. Both isothermal and non-isothermal tests are conducted in the unit. The sample basket is lowered into and raised out of the heated zone as required.

Laboratory-scale combustion tests were conducted in a 5.08-cm (2-inch) diameter fluidized-bed reactor. A schematic diagram of the unit configuration is shown in Figure 3. All vessels and lines are 316 stainless steel, and glass bombs are used to collect gas samples. A two-zone electric furnace is used to heat the reactor. All exit gas is metered, passed through a sodium hydroxide scrubber, and then vented.

Continuous operation is achieved by using a calibrated feed screw to transfer shale from the feed hopper to the reactor. Shale is fed to the bottom of the reactor and discharged from the reactor through an overflow tube. Unsteady-state and steady-state receivers are used to collect the discharged residue shale. The feed gas is preheated with an electric furnace and fed through a sintered metal plate into the reactor. An internal sintered metal filter at the top of the reactor prevents the carry-over of shale fines into the exit gas line.

Steady-state flow, temperature, and pressure conditions are readily established. However, steady-state operation is not initiated until after a time period equivalent to three bed turnovers to ensure solids have the proper time/temperature history.

Discussion

A total of seventeen thermobalance tests were conducted to determine combustion characteristics of hydroretorted, beneficiated Alabama shale. The first three tests were non-isothermal and involved heating a shale sample to 982°C (1800°F) in air at 0.2, 1.5, and 7.0 MPa (15, 200, and 1000 psig). Eleven isothermal tests were conducted using a 20-minute residence time; three other isothermal tests were conducted using 1, 2, and 5-minute residence times. Isothermal test conditions ranged from 816° to 1093°C (1500° to 2000°F) at pressures of 0.2 to 7.0 MPa (15 to 1000 psig).

The hydroretorted shale used in the thermobalance tests was generated in a laboratory-scale continuous PFH test at 482°C (900°F) and 4.2 MPa (600 psig). The hydroretorted shale was screened to -841 + 420 micron and riffled to produce the TGA

feed shale. Analyses of the raw and hydroretorted Alabama shales are presented in Table 1. The sample weight totals more than 100 percent because metals in the shale mineral matter are oxidized during the analysis.

The carbon, sulfur, and nitrogen conversions achieved during the PFH test used to generate the hydroretorted shale were 67, 44, and 55 percent, respectively. The hydroretorted shale sample contained a total of 24.2 weight percent carbon, hydrogen, sulfur, and nitrogen. The shale gross calorific value was reduced from 14.8 to 7.1 MJ/Kg during PFH processing, which represents 32 percent of the original shale heat content.

A summary of the operating conditions and elemental conversions for the combustion characterization tests is presented in Table 2. Conversions are not presented for Test 31-T-12 because at 1093°C (2000°F), the shale sample sintered and could not be separated from the basket after the test.

Non-isothermal TGA tests were conducted in air at pressures of 0.2, 1.5, and 7.0 MPa (15, 200, and 1000 psig). The corresponding oxygen partial pressures were 0.04, 0.32, and 1.5 MPa. Slow heating of the hydroretorted shale in air produces a large weight loss peak between 249° and 349°C (480° and 660°F). This is probably due to the onset of a self-sustained combustion reaction, which was not indicated by thermocouple readings. As the oxygen partial pressure increased, the combustion initiation temperature decreased. Results presented in Table 3 suggest that shale combustion can be initiated at temperatures as low as 250°C (482°F).

The thirteen isothermal thermobalance tests in which the shale did not sinter were conducted at temperatures of 816° to 982°C (1500° to 1800°F) and pressures of 0.2 to 7.0 MPa (15 to 1000 psig). Weight loss was high for all samples at this range of combustion conditions.

Carbon conversion increased from 57.3 percent at 1 minute to 63.9 percent at 2 minutes and to nearly 100 percent for tests at 5 minutes. Detailed evaluations of carbon conversion rates at combustion temperatures above 816°C (1500°F) will require thermogravimetric testing at residence times of less than 5 minutes. Shale residence times in the continuous unit tests were too long to accurately measure the effects of temperature and pressure on

A8908260

Figure 3. SCHEMATIC DIAGRAM OF THE LAB-SCALE THERMOBALANCE REACTOR

Table 1. ANALYSES OF RAW AND HYDRORETORTED
BENEFICIATED ALABAMA SHALE*

Sample Test Unit	Beneficiated --	Thermobalance	Beneficiated and Hydroretorted Lab-Scale Continuous
Moisture, wt %	1.5	0.00	0.00
Ultimate, wt % (dry)			
Ash	53.7	79.1	81.1
Carbon	31.9	15.4	12.9
Hydrogen	3.2	0.8	0.8
Sulfur	9.2	7.5	7.3
Nitrogen	0.8	0.5	0.4
Gross Calorific Value,			
Btu/lb	6354	3060	2690
MJ/kg	14.8	7.1	6.3

* Ultimate analyses of shale samples may exceed 100% due to oxidation of mineral matter.

Table 2. COMBUSTION CHARACTERIZATION TEST CONDITIONS AND RESULTS

Test No.	<u>31-T-1</u>	<u>31-T-2</u>	<u>31-T-3</u>	<u>31-T-4</u>	<u>31-T-5</u>	<u>31-T-6</u>
Operating Conditions						
Temperature, °C	----- 982 -----			----- 927 -----		
Pressure, MPa	0.2	1.5	7.0	0.2	1.5	7.0
Res. Time, * min	----- 20 -----			----- 20 -----		
Heating Mode	----- Non-Isothermal -----			----- Isothermal -----		
Component Conversion, %						
Carbon	99.8	99.6	99.9	99.7	99.7	99.7
Hydrogen	92.3	94.3	95.2	97.1	97.1	97.1
Sulfur	97.7	98.4	96.1	98.5	94.8	82.9
Nitrogen	83.0	100.0	98.5	95.5	98.5	96.8
Total Weight Loss, %	21.3	21.6	20.9	20.9	20.9	19.4

* At maximum temperature.

Table 2, Cont. COMBUSTION CHARACTERIZATION TEST CONDITONS AND RESULTS

Test No.	<u>31-T-7</u>	<u>31-T-8</u>	<u>31-T-9</u>	<u>31-T-10</u>	<u>31-T-11</u>
Operating Conditions					
Temperature, °C	816	982	927	816	982
Pressure, MPa	1.5	1.5	4.2	1.5	7.0
Res. Time, * min	----- 20 -----				
Heating Mode	----- Isothermal -----				
Component Conversion, %					
Carbon	100.0	100.0	100.0	100.0	99.8
Hydrogen	98.1	98.0	98.1	98.0	97.0
Sulfur	93.0	95.8	86.6	94.2	79.5
Nitrogen	100.0	100.0	100.0	98.4	96.8
Total Weight Loss, %	21.3	19.2	21.0	17.7	19.0
Test No.	<u>31-T-16</u>	<u>31-T-16</u>	<u>31-T-15</u>	<u>31-T-14</u>	<u>31-T-17</u>
Operating Conditions					
Temperature, °C	----- 927 -----				
Pressure, MPa	----- 7.0 -----				4.2
Res. Time, * min	1	2	5	20	20
Heating Mode	----- Isothermal -----				
Component Conversion, %					
Carbon	57.3	63.9	100.0	99.6	100.0
Hydrogen	91.5	89.2	97.1	95.2	99.0
Sulfur	38.3	34.9	86.8	93.5	94.8
Nitrogen	82.9	86.2	100.0	100.0	100.0
Total Weight Loss, %	12.7	11.7	20.1	21.0	21.0

* At maximum temperature.

Table 3. EFFECT OF OXYGEN PARTIAL PRESSURE ON COMBUSTION INITIATION TEMPERATURES (Non-Isothermal Tests)

<u>Test No.</u>	<u>O₂ Partial Pressure, MPa</u>	<u>Combustion Initiation Temperature, °C</u>
31-T-1	0.04	295-370
31-T-2	0.32	250-300
31-T-3	1.5	260-275

carbon, but carbon conversions exceeded 99 percent over the temperature and pressure ranges studied.

Results of residence time tests at 927°C (1700°F) showed that the rate of sulfur conversion was slower than the rate of carbon conversion during shale combustion. Sulfur conversion increases with increasing temperature. The apparent decrease in sulfur conversion with increasing pressure for thermobalance tests may be caused by shale sintering in the thermobalance.

Weight loss versus time traces for thermobalance tests conducted at 816°, 927°, and 982°C (1500°, 1700°, and 1800°F) and a pressure of 1.5 MPa (200 psig) are presented in Figure 4. Weight loss rate increases with increasing temperature. The time required to complete 95 percent of the total weight loss decreases with increasing temperature from about 6 minutes at 816°C (1500°F) to 4 minutes at 927°C (1700°F) and 3 minutes at 982°C (1800°F). The decrease in total weight loss as temperature is increased from 927° to 982°C (1700° to 1800°F) appears to be comprised of an increase in organic matter conversion and a larger decrease in weight as a result of inorganic reactions.

The rate of weight loss also increases with increasing oxygen pressure, but the effect of pressure is smaller than the effect of temperature. At 927°C (1700°F), the weight loss after 20 minutes was 21 percent at pressures from 0.2 to 7.0 MPa. However, 86 percent of the total weight loss is achieved in 2 minutes at 7.0 MPa, but only 81 percent of the weight loss occurs in 2 minutes at 0.2 MPa.

Total weight changes in the thermobalance combustion tests were not consistent with the elemental conversions. At a pressure of 1.5 MPa (200 psig), conversions of the organic part of the shale (carbon, hydrogen, and sulfur) increased with increasing temperature. However, the total weight loss decreased with increasing temperature from 21.3 percent at 816°C (1500°F) to 20.9 percent at 927°C (1700°F) and to 19.2 percent at 982°C (1800°F). These results indicate the mineral matter in the shale gains weight during combustion and that the mineral matter weight gain increases with increasing temperature.

Sintering was observed in the isothermal tests conducted at severe conditions. At 927°C (1700°F), part of the samples combusted at 4.2 and 7.0 MPa (600 and 1000 psig) was sintered. At higher temperatures of 982° and 1093°C (1800° and

2000°F) and a pressure of 1.5 MPa (200 psig), more of the sample sintered. The residue from Test 31-T-12 at 1093°C was entirely sintered and could not be separated from the basket after the test.

Ash fusion temperatures of combusted shale in reducing and oxidizing atmospheres are shown in Table 4. The initial deformation temperature (oxidizing atmosphere) of combusted shale was found to be 1288°C (2350°F). Combustion temperatures used in the thermobalance tests were below this temperature.

Six fluidized-bed combustion tests were conducted. The feed for the shale combustion tests was hydrotreated shale product from a bench-scale PFH test. For the first combustion test, the shale was sized to -420 + 177 micron; for the other five tests, the shale was sized to -595 + 177 micron. The wider size consist was used in the later tests so that a sufficient quantity of feed material would be available. The -177 micron fraction of the shale was removed to minimize fines-handling problems. Physical and chemical analyses of the feed and residue shale samples from the combustion tests are shown in Table 5.

Combustion tests were conducted at temperatures of 816° to 927°C (1500° to 1700°F) and pressures of 0.4 to 1.5 MPa (50 to 200 psig). Shale residence times ranged from 14 to 50 minutes, and the bed height-to-diameter ratio was about 2. The feed gas superficial velocity was 0.18 to 0.37 m/s (0.6 and 1.2 ft/s), which provided from 80 to 200 percent excess air to the reactor. Shale feed rates were 400 to 700 grams per hour. Operating conditions and results of the combustion tests are summarized in Table 6.

The superficial velocities were greater than complete fluidization for the largest particles to prevent sintering of the shale during combustion. At lower velocities, the kinetic energy of the particles in the bed was insufficient to prevent sintering. In initial tests with gas velocities below 0.18 m/s (0.6 ft/s), shale sintering occurred at combustion temperatures as low as 650°C (1200°F). Sintering, however, is avoided when the bed is well-fluidized. Combustion tests were conducted without sintering at 927°C (1700°F).

The fluidization velocities needed to avoid sintering did not produce any significant attrition of the shale particles. In Test 32-C-1, the feed shale contained 24.8 percent -250 micron material; the combusted shale residue contained 22.4 percent -250

Figure 4. EFFECT OF TEMPERATURE ON SHALE WEIGHT LOSS

Table 4. COMBUSTED HYDRORETORTED BENEFICIATED ALABAMA
SHALE ASH FUSION TEMPERATURES

	Ash Fusion Temperature, °C	
	Reducing	Oxidizing
Initial Deformation	1107	1288
Softening	1174	1354
Hemispherical	1238	1399
Fluid	1302	1443

micron material. The feed for the other five tests contained 9 percent -250 micron material; the -250 micron fraction of steady-state residue solids from these tests ranged from 8.1 to 17.9 weight percent. The increase in the -250 micron fraction of the combusted shale observed in tests 32-C-7 and 32-C-8 may have been due, in part, to higher gas flow, which caused more mixing and solid/solid contact in the bed. It was also observed that the residue shale particles were smoother and more spherical in shape than the feed. The scrubbing action of the fluidized bed apparently eroded small surface irregularities from the particles, but did not cause significant particle breakage.

The color of the solids was affected by combustion reactions. The hydroretorted beneficiated shale was black, which reflected the high level of carbon still present. After combustion, the shale had a light, reddish-brown color. The lighter the color, the lower was the carbon content of the combusted shale. The color of the combusted shale may reflect the presence of iron oxide. Elemental analyses of raw, beneficiated shale has shown iron concentrations in the range of 3 to 5 weight percent.

High carbon and sulfur conversions were achieved in all combustion tests; measured gas-phase products were carbon dioxide and sulfur dioxide (SO₂) exclusively. Carbon conversions ranged from 93 to 100 percent. Sulfur conversions ranged from 84 to 97 percent. The elemental conversions from these tests were consistent with those from thermobalance combustion characterization tests. Carbon conversion increased with increasing temperature, pressure, and residence time. The differences, however, were small. The carbon conversion achieved in test 32-C-1 (conducted at 816°C and 0.4 MPa [1500°F and 50 psig]) was 93 percent; all other tests had carbon conversions of 97 to 100 percent. At 871°C and 0.4 MPa (1600°F and 50 psig), a 14-minute residence time yielded a carbon conversion of

98.5 percent. Tests conducted in a thermobalance indicated that 5 minutes should provide adequate solids residence time for high carbon conversions.

Sulfur conversions were lower than carbon conversions. Increases in sulfur conversion were achieved with increases in temperature and residence time, but increasing the pressure did not change the sulfur conversion.

Essentially all of the converted sulfur formed SO₂. Sulfur balances based on the SO₂ concentration were poor. Spot gas sample SO₂ concentrations varied by more than 50 percent. Nonuniform SO₂ production and/or interaction of SO₂ with steel vessels and tubing may account, in part, for the poor sulfur recovery in most tests.

The carbonyl sulfide (COS) content in the product gas from all tests was below the gas chromatography detection limit of 10 ppm. Therefore, less than 0.1 percent of the shale sulfur was converted to COS during combustion. The concentration of NO_x compounds was not measured in these combustion tests. However, based on shale nitrogen conversion during the tests, the maximum possible NO_x concentration in the fluidized-bed product gas would have been less than 15 ppm. Product gas compositions were determined in the combustion tests by averaging the compositions of several spot gas samples.

Conclusions

At temperatures of 816° to 982°C and air pressures of 0.2 to 7.0 MPa, rapid and complete combustion of hydroretorted, beneficiated shale is achieved. Carbon conversions increase from greater than 50 percent in 1 minute to almost 100 percent in 5 minutes. Sulfur oxidation, which is slower than carbon combustion, increases with increasing temperature. Shale mineral matter is not completely

Table 5. CHEMICAL AND PHYSICAL ANALYSES OF FEED AND RESIDUE
SOLID SAMPLES FROM COMBUSTION TESTS*

Test No.	32-C-1	32-C-1	32-C-3 through 32-C-8	32-C-3	32-C-4	32-C-6	32-C-7	32-C-8
Sample	Feed	Residue	Feed	Residue	Residue	Residue	Residue	Residue
Ultimate, wt % dry								
Ash	81.1	96.9	81.1	98.6	97.4	98.8	96.3	99.0
Carbon	12.9	1.1	12.9	0.5	0.1	0.2	0.2	0.0
Hydrogen	0.8	0.0	0.8	0.0	0.0	0.0	0.0	0.0
Sulfur	7.3	1.2	7.3	0.3	1.0	0.4	1.4	0.3
Nitrogen	0.4	0.1	0.4	0.0	0.0	0.0	0.0	0.0
Oxygen (HTW)	2.4	0.4	2.4	0.7	0.4	0.5	0.6	0.3
Bulk Density, g/mL	0.57	0.59	0.57	0.59	0.52	0.59	0.53	0.60
Sieve Analysis (wt %), micron								
+595	0.8	1.8	9.4	4.2	12.2	1.4	4.2	3.9
-595+420	5.2	1.3	49.8	61.5	56.8	49.5	50.9	35.4
-420+250	69.2	74.5	31.7	26.2	21.9	38.6	28.5	42.8
-250+210	13.6	10.6	5.1	5.1	6.3	5.0	9.3	8.3
-210+177	7.0	6.9	2.6	0.9	0.7	2.1	2.0	4.7
-177+Pan	<u>4.2</u>	<u>4.9</u>	<u>1.4</u>	<u>2.1</u>	<u>2.1</u>	<u>3.4</u>	<u>5.1</u>	<u>4.9</u>
Total	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
Gross Calorific Value, MJ/kg	6.3	NA	6.3	<0.02	<0.02	<0.02	<0.02	<0.02

* Ultimate analyses of shale samples may exceed 100% due to oxidation of mineral matter.

Table 6. OPERATING CONDITIONS AND RESULTS
FROM SHALE COMBUSTION TESTS

Test No.	<u>32-C-1</u>	<u>32-C-3</u>	<u>32-C-4</u>	<u>32-C-6</u>	<u>32-C-7</u>	<u>32-C-8</u>
Temperature, °C	829	916	821	882	810	921
Pressure, MPa	0.49	0.43	0.81	0.45	1.47	0.79
Shale Res. Time, min	23	33	31	14	50	33
Bed Height/Diameter Ratio	-----2.2-----					
Steady-State Time, min	60	60	60	55	38	55
Shale Feed Rate, g/h	569	404	391	718	382	476
Gas Feed Rate, SCM/h	1.57	1.53	2.80	2.60	4.36	3.11
Gas Superficial Velocity, m/s	0.19	0.23	0.23	0.37	0.18	0.26
Excess Air, %	80	156	162	144	299	306
Component Conversions, wt %						
Carbon	93.0	97.1	99.5	98.5	99.0	100.0
Sulfur	85.9	96.3	88.3	96.1	83.6	96.8
Nitrogen	78.1	100.0	100.0	100.0	100.0	100.0
Oxygen (HTW)	84.6	77.0	84.7	82.8	78.2	88.3
Calorific Value Reduction, %	NA	>99.5	>99.5	>99.5	>99.5	>99.5
Product Gas Composition, mol %						
O ₂	9.9	10.1	4.6	9.7	6.9	11.7
N ₂	79.2	81.2	91.1	80.7	90.6	82.9
CO ₂	7.6	7.6	4.0	8.3	2.5	4.8
SO ₂	<u>3.3</u>	<u>1.1</u>	<u>0.3</u>	<u>1.3</u>	<u>0.0</u>	<u>0.6</u>
Total	100.0	100.0	100.0	100.0	100.0	100.0
Recovered Carbon, % of Feed						
CO ₂	73.1	98.8	101.1	99.9	98.4	105.0
Liquids	NA	0.02	0.03	0.03	0.04	0.02
Sulfur Recovered in Product Gas as SO ₂ , % of feed sulfur	148.8	66.3	40.2	73.6	2.0	58.8

inert at combustion conditions. Oxidation of mineral matter produces a weight gain which increases with increasing temperature and pressure. Partial sintering occurs during fixed-bed combustion of hydrotortorted shale at 927°C, and sintering becomes more severe as the temperature and pressure are increased.

Fluidized-bed combustion of hydrotortorted, beneficiated shale is a practical method of improving the energy efficiency of the PFH process. Successful operation in a laboratory-scale reactor has shown sintering can be avoided by keeping the superficial velocity above the fluidization velocity of the largest particles in the bed. No significant particle attrition results from fluidized-bed combustion of hydrotortorted shale.

After hydrotortorting at 510°C and 7.0 MPa (950°F and 1000 psig) in a bench-scale PFH unit, the residue shale contained 12.9 percent carbon and 7.3 percent sulfur and had a gross calorific value of 6.3 MJ/kg (2690 Btu/lb). Combustion reduced the calorific value of this hydrotortorted shale by an average of more than 99.5 percent during the five laboratory-scale continuous tests. The high calorific value recovery at all combustion conditions studied prevented determination of the effects of operating conditions on conversion.

Acknowledgements

The authors wish to acknowledge the U.S. Department of Energy (Laramie Project Office of the Morgantown Energy Technology Center) for support of this work. ✓

References

1. Punwani, D.V., "Energy From Eastern Oil Shales: An Overview of Research Status," Proc. 12th Energy Tech. Conf. and Expos., Washington, D.C., March 24-26, 1985.
2. Roberts, M.J., Punwani, D.V., Hu, W.C.S. and Rex, R.C., "Effects of Temperature and Pressure on Hydrotortorting Yields of Three Eastern Oil Shales," A.I.Ch.E. Natl. Mtg., Miami, Florida, 1986.
3. Roberts, M.J., Rue, D.M. and Lau, F.S., "Pressurized Fluidized-Bed Hydrotortorting of Six Eastern Shales in Batch and Continuous Laboratory-Scale Reactors," Fuel, 71(3), 335-41, 1992.
4. Roberts, M.J., Rue, D.M. and Lau, F.S., "Pressurized Fluidized-Bed Hydrotortorting of Raw and Beneficiated Eastern Oil Shales," Proc. 1991 Eastern Oil Shale Symp., Institute for Mining and Minerals Research, Lexington, Kentucky, 1992.

DATE

FILMED

10 / 4 / 94

END