NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

DIRECT CONVERSION OF LIGHT HYDROCARBON
GASES TO LIQUID FUEL

Report No. 11

Quarterly Technical Status Report
for
Third Quarter F.Y. 1990

Project Manager: R. D. Kaplan

Principal Investigator: M. J. Foral

Work performed under Contract No. DE-AC22-89PC89866

For

U. S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania

By

Amoco Oil Company
Research & Development Department
Post Office Box 3011
Naperville, IL 60566

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

yes

1001709

MAY 07 1992

2

FINAL QUARTERLY PROGRESS REPORT SUBMITTED TO:

1. George Cinquegrane (2 copies)
Contracting Officer's Representative
U.S. DOE/PETC
P.O. Box 10940
Pittsburgh, PA 15236
2. Dona G. Sheehan
Contract Specialist
U.S. DOE/PETC
P.O. Box 10940
Pittsburgh, PA 15236
3. Robert M. Hamilton
FE-231, E-155/GTN
U.S. Department of Energy
Washington, DC 20545
4. Gilbert V. McGurl
Program Manager
U.S. DOE/PETC, MS 922-H
P.O. Box 10940
Pittsburgh, PA 15236

ADDITIONAL CIRCULATION FOR DRAFT REPORTS TO:

Amoco Corporation
Suite 600
305 East Shuman Boulevard
Naperville, IL 60563-8408
J. A. Mahoney

Amoco Oil Company
P.O. Box 3011
Naperville, IL 50566
R. D. Kaplan, H-4
M. J. Foral, H-4
A. R. LaPuma, H-4
D. W. Washecheck, H-2
D. B. Lerman, H-1
E. G. Wollaston, H-3
A. S. Couper, H-1

TABLE OF CONTENTS

	<u>Page</u>
EXECUTIVE SUMMARY	7
BACKGROUND	8
PROGRAM OBJECTIVES	9
PROJECT DESCRIPTION	9
RESULTS AND DISCUSSION	10
Task 2: Modification of Existing Pilot Plant	10
Task 3.2: Process Variable Experiments.....	11
CONCLUSIONS	17
ACKNOWLEDGEMENT	17

LIST OF FIGURES

- FIGURE 1 Effect of Ethane Concentration on Hydrocarbon Conversion
- FIGURE 2 Effect of Ethane Concentration on Methane Conversion
- FIGURE 3 Effect of Ethane Concentration on Methanol Selectivity
- FIGURE 4 Effect of Ethane Concentration on Methanol Yield
- FIGURE 5 Effect of Oxygen Concentration on Product Yield
- FIGURE 6 Effect of Oxygen Concentration on Methane Conversion
- FIGURE 7 Effect of Oxygen Concentration on Hydrocarbon Conversion

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process or service by trade name, mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

TECHNICAL STATUS

This technical status report is being transmitted in advance of DOE review, and no further dissemination or publication will be made of this report without prior approval of the DOE Project/Program Manager.

EXECUTIVE SUMMARY

Amoco Oil Company, under a contract with the United States Department of Energy, is investigating the direct conversion of light hydrocarbon gases to liquid fuels via partial oxidation. This report describes work completed in the second quarter of the two-year project. Task 1 of the work, preparation of the Project Management Plan, was completed in the first quarter. Work continued and progress was made on two other tasks during this quarter:

Task 2. Modification of an existing Amoco pilot plant to handle the conditions of this project. Construction has progressed on a new reactor for Task 3.5 (Effect of Reactor Geometry). It will be installed as soon as construction is completed and the reactor is pressure tested. Installation should take place during the first week of August.

Task 3.2. Process variable (e.g. temperature, pressure, residence time) studies to determine optimal partial oxidation conditions. Thirty-eight runs were made on the pilot plant to study the effects of oxygen concentration, higher carbon number hydrocarbons (ethane), temperature, pressure, and residence time on methanol production. Higher levels of ethane in the methane feed increase per-pass methanol yield, but decrease overall methane conversion. It appears that the ethane in the feed reacts preferentially, leaving less oxygen to react with the less-reactive methane. This could have a significant impact on process economics. Lower oxygen levels lead to increased methanol selectivity, but also to much lower methane conversion. Once again, the higher carbon number hydrocarbons in the feed appear to react preferentially with the limited available oxygen, leaving little to react with methane. Lower oxygen levels also decrease total hydrocarbon conversion slightly, while methanol yield is maximized at oxygen concentrations below 5 vol%.

The project continues to proceed on schedule. Work in the next quarter will concentrate on the effect of reactor geometry (Task 3.5). The new reactor will be installed along with new internals to determine reactor geometry effects.

BACKGROUND

Fischer-Tropsch synthesis, gasification processes like Lurgi dry bottom gas, direct coal liquefaction, and remote natural gas all represent sources of substantial quantities of light hydrocarbon gases. Methane is the major and most stable component of all these gases. Steam reforming methane to produce synthesis gas is capital-intensive because it is highly endothermic and requires severe reaction conditions. A process for direct conversion of light gases, especially methane, to methanol, gasoline, or other liquid fuels could be far superior.

Steam reforming is the first stage in traditional commercial methods for the production of liquid fuels. This first step produces synthesis gas:

The synthesis gas is then converted into methanol via a catalytic process.

Reaction 1 produces more hydrogen than required by reaction 2. The excess can either be utilized elsewhere in the case of a domestic refinery or, in the case of a remote operation, is lost. A third step could be the catalytic condensation of methanol to gasoline.

A more efficient route of converting light hydrocarbons would be to directly form methanol by partial oxidation.

Such a process could substantially reduce capital and energy requirements for methanol production. The methanol could be used as a fuel or a fuel blending component, as in the case of M80 fuels (80% methanol, 20% gasoline), or else converted into gasoline through well-known processes, such as MTG. A plant based on Reactions 1 and 2 followed by methanol condensation to gasoline has been built and is operating in New Zealand. However, the process is uneconomical if it were not for the New Zealand Government support. If a process for the direct conversion of light hydrocarbons to methanol is feasible, thereby eliminating the process steps shown by Reactions 1 and 2, then a gas-to-gasoline process could become economically viable.

A proposed process for converting light hydrocarbon gases directly to hydrocarbon liquids, e.g., methanol or formaldehyde, is not new. In 1932 Newitt and Haffner reported the formation of methanol, along with smaller amounts of formaldehyde and formic acid, in the high-pressure oxidation of methane.⁽¹⁾ The reaction was carried out in a static system at 360-393°C and 50-150 atm. The maximum methanol selectivity was ca. 22%; however, CH₄ conversion was only a few percent. More recently, Gesser, Hunter and co-workers have reported methanol selectivities up to 89% and yields of around 7%.⁽²⁾ However, other workers have in general been unable to reproduce these results.

- (1) D. M. Newitt, A. L. Haffner, Proc. R. Soc. London, Ser. A, 134, p. 591
- (2) H. D. Gesser, N. R. Hunter, Chem. Rev., 85(4), p. 235 (1985);
H. D. Gesser, U. S. Patent 4,618,732, issued 10/21/86.

PROGRAM OBJECTIVES

The objective of this program is to investigate the direct conversion of light gaseous hydrocarbons, such as those produced during Fischer-Tropsch synthesis or as a product of gasification, to liquid transportation fuels via a partial oxidation process. The process will be tested in an existing pilot plant to obtain credible mass balances. Specific objectives to be met include determination of optimal process conditions, investigation of various processing options (e.g. feed injection, product quench, and recycle systems), and evaluation of an enhanced yield thermal/catalytic system. Economic evaluation of the various options will be performed as experimental data become available.

PROJECT DESCRIPTION

The project is of two years' duration and contains three major tasks. The third task (Pilot Plant Experiments) contains seven subtasks, corresponding to the project objectives outlined above. The tasks and subtasks foreseen when the project began are described below.

Task 1.--Project Management Plan: A plan will be prepared describing the work to be done, milestones, and manpower requirements and costs.

Task 2.--Pilot Plant Modification: An existing pilot plant dedicated to investigation of light hydrocarbon conversion will be modified to provide it with the capability to handle the processes and conditions of this program. These modifications will include construction of a new reactor, construction and installation of reactant injection and product quench systems, and, possibly, addition of a product recycle loop to the unit.

Task 3.1.--Comparison of Preliminary Data With Los Alamos Model: We will determine if the kinetic model developed by Los Alamos National Laboratory can be used to guide our experimental effort. Results from this task will be carefully analyzed and will determine the direction of the subsequent experimental program. This is a major decision point in the project.

Task 3.2.--Pressure/Temperature/Reaction Time Effects: The methane conversion data base will be extended over the following range of conditions:

Temperature:	600 to 1100 F
Pressure:	200 to 1300 psig
Reaction Time:	3 to 90 seconds

These experiments will be guided by the results of Task 3.1 to those process regimes which appear most promising.

Task 3.3--Study of Different Injection Systems: Different schemes for introducing and mixing reactants before or within the reactor will be evaluated theoretically and/or experimentally. The goal will be to maximize methanol yield.

Task 3.4--Study of Different Quench Systems: The efficacy of different product cooling techniques will be investigated to determine the effect of quenching on product composition and methanol yield. Both gas and liquid quench options will be investigated.

Task 3.5--Effect of Reactor Geometry: The effect of reactor geometry, particularly aspect (i.e. length/diameter) ratio, will be investigated to determine mass transfer and mixing effects on product composition and methanol yield.

Task 3.6--Effect of Reactor Recycle: The effect of recycling unreacted hydrocarbons to the reactor inlet will be evaluated first by appropriately blending the feed stream to simulate reactor recycle. If these results are promising relative to methanol production, a recycle compressor and recycle line will be added to the pilot plant for more detailed tests.

Task 3.7--Enhanced-Yield Catalyst Study: An attempt will be made to develop a combined thermal/catalytic process in which byproduct carbon monoxide and hydrogen from the thermal process is converted to methanol over a heterogeneous catalyst. Such a combined process may provide higher methanol yields than the thermal process alone.

Reporting will be done periodically throughout the duration of the project according to DOE guidelines.

RESULTS AND DISCUSSION

During this quarter, pilot plant runs (Task 3.2) demonstrated that the concentrations of ethane and oxygen in the reactor feed can significantly affect hydrocarbon conversion and methanol yield. Ethane (and other higher carbon number hydrocarbons) appear to react preferentially with oxygen, effectively decreasing methane conversion. Higher oxygen concentrations increase conversion, but at the expense of lower methanol selectivity. Construction of the new reactor for Task 3.5 is nearing completion and will be installed during the next quarter.

Task 2: Pilot Plant Modification

Materials for the new reactor (Task 3.5; Effect of Reactor Geometry) have arrived and the reactor is currently under construction. It will be installed on the unit as soon as it is completed and pressure tested. On-site safety concerns have once again been raised with regard to the proposed oxygen compressor. New site guidelines were just issued, specifying monel as the material of choice for the conditions of interest (1500 psig pure oxygen).

The compressor system we had selected is principally stainless steel. Further discussions will be held with site safety personnel to resolve this situation.

Task 3.2: Process Variable Studies:

A total of 38 mass-balanced pilot plant runs were completed this quarter, concluding work on Task 3.2 (Process Variable Studies). The effects of temperature, pressure, residence time, oxygen concentrations, and ethane concentration were investigated in this Task. Data analyses are complete for the effects of oxygen and ethane concentration, and these results are covered in this report. The effects of temperature, pressure and residence time will be covered fully in the next report.

Effect of ethane concentration:

Runs were made in which a pure methane feed was spiked with various levels of ethane, from 0 to 4.8 vol%. Other parameters were held constant at $T=800$ F; $P=1300$ psig and hydrocarbon/oxygen=10. Figures 1-4 present the trends in hydrocarbon and methane conversion, and methanol selectivity and yield. Figure 1 shows that hydrocarbon conversion (that % of the incoming carbon atoms that are converted to oxygen-containing products) increases linearly with increasing ethane content of the feed. This increase occurs because the ethane reacts more readily with oxygen than the methane. Ethane conversion in the reactor was 40%, independent of ethane concentration. Hydrocarbon conversion with natural gas feed falls on the same line as conversion with ethane-spiked methane feeds (Figure 1).

Methane conversion decreases with increasing ethane concentration (see Figure 2). This is expected, since the more reactive ethane would preferentially consume the oxygen, leaving less to react with methane. Figure 2 also shows that natural gas feeds give lower methane conversions than feeds with equivalent amounts of ethane. This is probably due to the even higher reactivity of propane and butanes which are present in the natural gas (1.5 vol%).

The fact that methane conversion is lower in the presence of higher carbon number hydrocarbons (such as ethane) could have a significant impact on the economics of this process. Since a lower per-pass methane conversion translates to a larger recycle loop for the process (and therefore higher equipment cost), any effect that lowers the methane conversion significantly will probably be detrimental to process economics. We would expect this effect to be less significant at higher oxygen feed levels since more oxygen would be available to react with methane. Runs related to the effect of oxygen level are presented later in this report.

Methanol selectivity is only a mild function of ethane concentration, as shown in Figure 3. It appears that there is a minimum in the selectivity at around 2% ethane, but this minimum is quite broad. The surprising aspect of this plot is that the selectivity stays relatively constant, even at ethane concentrations of up to 5 vol%. At this ethane level, nearly 40% of the carbon in the products comes from ethane conversion. Since the selectivity

Figure 1

Effect of Ethane Level on Hydrocarbon Conversion

P=1300 psig/ T=800 F / Res. Time=35 sec.

Hydrocarbon Conversion (%)

Figure 2 Effect of Ethane Level on CH₄ Conversion

P=1300 psig/ T=800 F / Res. Time=35 sec.

CH₄ Conversion (%)

Figure 3

Effect of Ethane Level on MeOH Selectivity
P=1300 psig/ T=800 F/ Res. Time=35 sec.

Figure 4

Effect of Ethane Level on MeOH Yield
P=1300 psig/ T=800 F/ Res. Time=35 sec.

does not change much over this range of ethane concentrations, it appears that the partial oxidation of ethane takes place with a selectivity pattern similar to that of methane. This result is supported by the early work of Wiezevich and Frohlich (Ind. Engr. Chem., 26(3), pp. 267-276, 1934) who found that carbon-carbon bond scission is an important step in the partial oxidation of higher hydrocarbons. One possible explanation is that both methane and ethane oxidation have the same rate-limiting step (and therefore a common reaction intermediate).

Methanol yield increases steadily with increasing ethane concentration (Figure 4), since hydrocarbon conversion increases and selectivity remains roughly constant.

Effect of oxygen concentration:

A series of runs was made in which oxygen concentration varied between 1.5 and 12.5 vol% of the total feed. Other parameters were held constant at T=800 F, P=1300 psig and Residence Time=35 seconds. Figures 5-7 show the effect of oxygen concentration on product yield, methane conversion, and hydrocarbon conversion, respectively.

Methanol yield generally decreases with increasing oxygen concentration, while the yield of carbon oxides (CO and CO₂) increases (Figure 5). This is consistent with the mechanism proposed by workers at Los Alamos (I. Tepermeister and J. Smith, Report LA-11396-MS; MIT-LANL-3, August 1987) in which a methoxy radical (CH_3O) can combine with either gas-phase oxygen (to form carbon oxides), or gas phase methane (to form methanol). Higher oxygen concentrations promote the carbon oxide formation branch at the expense of the methanol formation branch. An increase in methanol selectivity with decreasing oxygen level has also been reported by Gesser et al. (Ind. Eng. Chem. Res., 27, 256-264, 1988).

Figure 5 indicates that the increase in methanol yield with decreasing oxygen concentration is not necessarily monotonic. Methanol yield increases slightly (from 4.3 to 5.0 mol%) with decreasing oxygen concentration between 12.5 and 5 vol% oxygen. At lower oxygen levels (i.e. between 1.5 and 5.0 vol%), the data are more scattered and more difficult to interpret. It appears that at these low oxygen concentrations, methanol yield either remains constant at around 5.0 mol%, or it increases slightly. In either case, it is clear that methanol yield is maximized at oxygen concentrations below 5.0 vol%.

As expected, methane conversion increases steadily with increasing oxygen concentration (Figure 6). At higher oxygen concentrations, more oxygen is left after reaction with higher hydrocarbons to react with methane.

Hydrocarbon conversion increases with increasing oxygen concentration, as shown in Figure 7. Oxygen level affects hydrocarbon conversion less than it affects methane conversion: even at 1.5 vol% oxygen, hydrocarbon conversion is over 10 mol% whereas methane conversion is nearly zero. Less oxidized products are formed at lower oxygen concentrations, allowing better utilization of the oxygen and therefore higher hydrocarbon conversion.

Figure 5

Product Yields as Function of Oxygen Level

T=800 F; P=1300 psig; Res. Time=35 sec.

Figure 6

Effect of Oxygen Level on Methane Conversion

T=800 F; P=1300 psig; Res. Time=35 sec

Figure 7

Effect of Oxygen Level on Hydrocarbon Conversion

T=800 F; P=1300 psig; Res. Time=35 sec

Hydrocarbon Conversion (%)

CONCLUSIONS

The above results indicate that the level of C_2+ hydrocarbons in the feed significantly influences per-pass conversion and yield, but not methanol selectivity. This demonstrates the importance of using the proper feed in these pilot plant studies, specifically one containing higher hydrocarbons since any commercial operation will undoubtedly have higher hydrocarbons in the feed. For this reason, all subsequent pilot plant runs will be made with a natural gas feed.

The oxygen studies indicate that lower oxygen concentrations give higher methanol selectivity, while the yield (the product of methanol selectivity and hydrocarbon conversion) is maximized below 5 vol% oxygen. This suggests that, based on methanol yield, lower oxygen concentrations are desirable. However, at these low oxygen levels methane conversion is almost zero; nearly all of the products result from conversion of C_2+ species in the natural gas. Since the extent of methane conversion significantly impacts the economics of the process, higher oxygen concentrations are preferred. Subsequent runs will therefore use 9% oxygen as the base concentration, since methane conversion is significant (nearly 5%) at this concentration and methanol yield is 4.5 mol%, only 0.5 mol% lower than the observed maximum.

ACKNOWLEDGEMENT

This work was supported by the United States Department of Energy under Contract DE-AC22-89PC89556.

NOTICE

This report was prepared by the organization(s) named below as an account of work sponsored by the United States Department of Energy (DOE). Neither DOE, members of DOE, the organization(s) named below, nor any person acting on behalf of any of them: (a) makes any warranty, express or implied, with respect to the use of any information, apparatus, method, or process disclosed in this report or that such use may not infringe privately owned rights; or (b) assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this report.

Prepared by
Amoco Oil Company (Amoco Corporation)
Naperville, Illinois

/MJF/RDK/jmb/doe9027

END

**DATE
FILMED**

8 / 19 / 92