DOE/PC/89866--T5

DE92 015592

DIRECT CONVERSION OF LIGHT HYDROCARBON
GASES TO LIQUID FUEL

Report No. 19

Quarterly Technical Status Report
for
First Quarter F.Y. 1991

Project Manager: R. D. Kaplan

Principal Investigator: M. J. Foral

Work performed under Contract No. DE-AC22-89PC89866

For

U. S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania

By

Amoco Oil Company
Research & Development Department
Post Office Box 3011
Naperville, IL 60566

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

JUN 17 1991

MAY 07 1982

2

FINAL QUARTERLY PROGRESS REPORT SUBMITTED TO:

1. George Cinquegrane (2 copies)
Contracting Officer's Representative
U.S. DOE/PETC
P.O. Box 10940
Pittsburgh, PA 15236
2. Dona G. Sheehan
Contract Specialist
U.S. DOE/PETC
P.O. Box 10940
Pittsburgh, PA 15236
3. Robert M. Hamilton
FE-231, E-155/GTN
U.S. Department of Energy
Washington, DC 20545
4. Gilbert V. McGurl
Program Manager
U.S. DOE/PETC, MS 922-H
P.O. Box 10940
Pittsburgh, PA 15236

ADDITIONAL CIRCULATION FOR DRAFT REPORTS TO:

Amoco Corporation
Suite 600
305 East Shuman Boulevard
Naperville, IL 60563-8408
T. H. Fleisch

Amoco Oil Company
P.O. Box 3011
Naperville, IL 50566
R. D. Kaplan, H-4
M. J. Foral, H-4
A. R. LaPuma, H-4
D. W. Washecheck, H-2
D. B. Lerman, H-1
E. G. Wollaston, H-3
A. S. Couper, H-1
J. A. Mahoney, F-7

TABLE OF CONTENTS

	<u>Page</u>
EXECUTIVE SUMMARY	7
BACKGROUND	8
PROGRAM OBJECTIVES	9
PROJECT DESCRIPTION	9
RESULTS AND DISCUSSION	10
Task 3.5: Reactor Geometry Effects.....	10
Effect of Temperature.....	11
Effect of Oxygen Concentration.....	11
Task 3.3: Effect of Feed Injection Systems	12
CONCLUSIONS	12
ACKNOWLEDGEMENT	12

LIST OF FIGURES

- FIGURE 1 Effect of Reactor Diameter on Methanol Selectivity: Temperature Trends
- FIGURE 2 Effect of Reactor Diameter on Methanol Yield: Temperature Trends
- FIGURE 3 Effect of Reactor Diameter on Methanol Selectivity: Oxygen Concentration Trends
- FIGURE 4 Effect of Reactor Diameter on Methane Conversion: Oxygen Concentration Trends
- FIGURE 5 Effect of Reactor Diameter on Hydrocarbon Conversion: Oxygen Concentration Trends
- FIGURE 6 Effect of Reactor Diameter on Methanol Yield: Oxygen Concentration Trends

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process or service by trade name, mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

TECHNICAL STATUS

This technical status report is being transmitted in advance of DOE review, and no further dissemination or publication will be made of this report without prior approval of the DOE Project/Program Manager.

EXECUTIVE SUMMARY

Amoco Oil Company, under a contract with the United States Department of Energy, is investigating the direct conversion of light hydrocarbon gases to liquid fuels via partial oxidation. This report describes work completed in the fifth quarter of the two-year project. Work continued and progress was made on two other tasks during this quarter:

Task 3.3 (Studies of different reactant gas mixing and injection systems): Three different mixing systems have been designed and constructed. Two consist of different sizes of commercial in-line static mixers, and one consists of two partially-closed needle valves in series. This latter configuration is similar in principle to that used by Prof. Gesser at the University of Manitoba. Prof. Gesser has reported exceptionally high methanol selectivities and yields with this system. The feed section of the pilot plant has been modified to allow rapid switching between these different mixer configurations. Experiments are currently underway to study the effects of feed mixing on methane conversion and methanol selectivity.

Task 3.5 (Studies to determine the effect of reactor geometry): Three sizes of reactor have been studied, differing in diameter but not in length. In this way the effects of reactor surface-to-volume ratio on methanol selectivity and yield have been assessed. The higher surface-to-volume ratio (small diameter) reactor is much more sensitive to high reaction temperatures, showing a steep decrease in methanol selectivity with temperatures above 900°F. The larger diameter reactors showed a much more moderate decrease in methanol selectivity with higher temperatures. These results can be explained by increased high-temperature decomposition of methanol on the reactor walls in the high surface-to-volume (small diameter) reactor. It also appears that there is an interaction between reactor diameter (surface-to-volume ratio) and oxygen concentration effects. The smaller diameter reactors showed a monotonic increase in methanol selectivity with decreasing oxygen concentration between 12.5 vol% to 1.0 vol%, while the large diameter reactor exhibited a maximum in methanol selectivity at around 4-6 vol% oxygen. The reason for this behavior is not known, but may involve third-body (wall) stabilization of methanol-forming intermediates at lower oxygen concentrations.

Because of previous operability problems with the pilot plant the project remains about 3-4 weeks behind schedule. The total cost of the project through December 1990 was \$371M; this is \$172M below the budget plan of \$543M. About \$35M of this difference is due to being behind schedule, the remainder (about \$137M) is the true under-run. In the next quarter we will continue studying the effect of feed mixing (Task 3.3). Work will also begin on the effects of product quench (Task 3.4) and product recycle (Task 3.6).

BACKGROUND

Fischer-Tropsch synthesis, gasification processes like Lurgi dry bottom gas, direct coal liquefaction, and remote natural gas all represent sources of substantial quantities of light hydrocarbon gases. Methane is the major and most stable component of all these gases. Steam reforming methane to produce synthesis gas is capital-intensive because it is highly endothermic and requires severe reaction conditions. A process for direct conversion of light gases, especially methane, to methanol, gasoline, or other liquid fuels could be far superior.

Steam reforming is the first stage in traditional commercial methods for the production of liquid fuels. This first step produces syntheses gas:

The synthesis gas is then converted into methanol via a catalytic process.

Reaction 1 produces more hydrogen than required by reaction 2. The excess can either be utilized elsewhere in the case of a domestic refinery or, in the case of a remote operation, is lost. A third step could be the catalytic condensation of methanol to gasoline.

A more efficient route of converting light hydrocarbons would be to directly form methanol by partial oxidation.

Such a process could substantially reduce capital and energy requirements for methanol production. The methanol could be used as a fuel or a fuel blending component, as in the case of M80 fuels (80% methanol, 20% gasoline), or else converted into gasoline through well-known processes, such as MTG. A plant based on Reactions 1 and 2 followed by methanol condensation to gasoline has been built and is operating in New Zealand. However, the process is uneconomical if it were not for the New Zealand Government support. If a process for the direct conversion of light hydrocarbons to methanol is feasible, thereby eliminating the process steps shown by Reactions 1 and 2, then a gas-to-gasoline process could become economically viable.

A proposed process for converting light hydrocarbon gases directly to hydrocarbon liquids, e.g., methanol or formaldehyde, is not new. In 1932 Newitt and Haffner reported the formation of methanol, along with smaller amounts of formaldehyde and formic acid, in the high-pressure oxidation of methane.⁽¹⁾ The reaction was carried out in a static system at 360–393°C and 50–150 atm. The maximum methanol selectivity was ca. 22%; however, CH₄ conversion was only a few percent. More recently, Gesser, Hunter and co-workers have reported methanol selectivities up to 89% and yields of around 7%.⁽²⁾ However, other workers have in general been unable to reproduce these results.

- (1) D. M. Newitt, A. E. Haffner, Proc. R. Soc. London, Ser. A, 134, p. 591
- (2) H. D. Gesser, N. R. Hunter, Chem. Rev., 15(4), p. 235 (1985); H. D. Gesser, U. S. Patent 4,618,732, issued 10/21/86.

PROGRAM OBJECTIVES

The objective of this program is to investigate the direct conversion of light gaseous hydrocarbons, such as those produced during Fischer-Tropsch synthesis or as a product of gasification, to liquid transportation fuels via a partial oxidation process. The process will be tested in an existing pilot plant to obtain credible mass balances. Specific objectives to be met include determination of optimal process conditions, investigation of various processing options (e.g. feed injection, product quench, and recycle systems), and evaluation of an enhanced yield thermal/catalytic system. Economic evaluation of the various options will be performed as experimental data become available.

PROJECT DESCRIPTION

The project is of two years' duration and contains three major tasks. The third task (Pilot Plant Experiments) contains seven subtasks, corresponding to the project objectives outlined above. The tasks and subtasks foreseen when the project began are described below.

Task 1.—Project Management Plan: A plan will be prepared describing the work to be done, milestones, and manpower requirements and costs.

Task 2.—Pilot Plant Modification: An existing pilot plant dedicated to investigation of light hydrocarbon conversion will be modified to provide it with the capability to handle the processes and conditions of this program. These modifications will include construction of a new reactor, construction and installation of reactant injection and product quench systems, and, possibly, addition of a product recycle loop to the unit.

Task 3.1.—Comparison of Preliminary Data With Los Alamos Model: We will determine if the kinetic model developed by Los Alamos National Laboratory can be used to guide our experimental effort. Results from this task will be carefully analyzed and will determine the direction of the subsequent experimental program. This is a major decision point in the project.

Task 3.2.—Pressure/Temperature/Reaction Time Effects: The methane conversion data base will be extended over the following range of conditions:

Temperature:	600 to 1100°F
Pressure:	200 to 1300 psig
Reaction Time:	3 to 90 seconds

These experiments will be guided by the results of Task 3.1 to those process regimes which appear most promising.

Task 3.3.—Study of Different Injection Systems: Different schemes for introducing and mixing reactants before or within the reactor will be evaluated theoretically and/or experimentally. The goal will be to maximize methanol yield.

Task 3.4.—Study of Different Quench Systems: The efficacy of different product cooling techniques will be investigated to determine the effect of quenching on product composition and methanol yield. Both gas and liquid quench options will be investigated.

Task 3.5.—Effect of Reactor Geometry: The effect of reactor geometry, particularly aspect (i.e. length/diameter) ratio, will be investigated to determine mass transfer and mixing effects on product composition and methanol yield.

Task 3.6.—Effect of Reactor Recycle: The effect of recycling unreacted hydrocarbons to the reactor inlet will be evaluated first by appropriately blending the feed stream to simulate reactor recycle. If these results are promising relative to methanol production, a recycle compressor and recycle line will be added to the pilot plant for more detailed tests.

Task 3.7.—Enhanced-Yield Catalyst Study: An attempt will be made to develop a combined thermal/catalytic process in which byproduct carbon monoxide and hydrogen from the thermal process is converted to methanol over a heterogeneous catalyst. Such a combined process may provide higher methanol yields than the thermal process alone.

Reporting will be done periodically throughout the duration of the project according to DOE guidelines.

RESULTS AND DISCUSSION

During this quarter, pilot plant runs (Task 3.5) demonstrated that reactor geometry can have an effect on methanol yield and selectivity in this system. Experiments using reactors of different length-to-diameter ratios have shown that wall effects may be significant, even when using a supposedly inert quartz liner. Maximum methanol yields were not greatly affected by reactor geometry and fell in the range of 4-5 mol%. However, the oxygen concentration at which the maximum occurred was sensitive to reactor length-to-diameter ratio. The larger diameter reactor gave the maximum yield at intermediate oxygen concentrations (around 8 vol%), while the smaller diameter reactors gave maximum yields at low oxygen concentrations (1-3 vol%). These effects are discussed in detail below.

Task 3.5: Effect of Reactor Geometry:

During this quarter, experiments were made to explore the effects of different reactor diameters and surface-to-volume ratios on methanol yield and selectivity. Different size quartz reactor liners were used in these studies: a "large" 31 mm diameter tube, a "medium" 19 mm diameter tube, and a "small" 10.5 mm diameter tube. All reactor configurations utilized the same 13-inch

long, 3-zone electric furnace. With each size of reactor, the effects of temperature and oxygen concentration were investigated. These two parameters were chosen for study because they were seen to have the largest effect on methanol yield and selectivity in process variable (Task 3.2) experiments. For each size reactor temperatures were varied between 700°F and 1,100°F and oxygen concentrations, between 1.0 vol% and 12.5 vol%. Pressures between 1100 and 1300 psig were used in all runs because methanol yield is maximized at these pressures. Because of plant size considerations, the use of different reactor diameters precluded operating at constant residence time between reactor sizes. For the small, medium and large diameter reactors the residence times were around 16, 30, and 55 seconds, respectively. Previous process variable studies showed that methanol yield and selectivity were maximized within this residence time range and did not vary significantly.

Temperature Effects

Experiments were made to test the effect of reactor temperature with each reactor size and results are presented in Figures 1 and 2.

The most noticeable trend in these figures is that the small diameter reactor appears to be much more sensitive to high temperatures ($T > 900^\circ\text{F}$) than the medium or large diameter reactors. Figure 1 shows that with the small reactor methanol selectivity dropped from 26% to only 7% as temperature increased from 900 to 1100°F. With the medium and large diameter reactors methanol selectivity decreased to only 20% from 27% over the same temperature range. Hydrocarbon conversion was not affected by reactor diameter, so the change in methanol selectivity is reflected in the methanol yield trends (Figure 2). This effect is probably due to increased decomposition of methanol on the walls of the reactor at higher temperatures. The smaller diameter reactor has a higher surface to volume ratio and therefore is more sensitive to these wall effects.

Oxygen Concentration Effects

The results of varying oxygen concentration are presented in Figures 3-6.

The most significant difference between the various sized reactors is in methanol selectivity (Figure 3). With both the "medium" and "small" diameter tubes, selectivity to methanol increased monotonically with decreasing oxygen concentration. With the "large" tube, however, there is a clear maximum in methanol selectivity at around 4-6 vol% oxygen. Preliminary analysis indicates that in the large tube more formaldehyde is produced at lower oxygen concentrations than at higher oxygen concentrations. These trends are currently being compared to data from the small and medium tube runs. It is possible that formaldehyde decomposition on the walls is more significant in the small and medium diameter tubes. Another possibility is that wall interactions in some way stabilize methanol-forming intermediates at low oxygen concentrations, leading to higher methanol selectivities in the smaller diameter reactors.

In all three reactors, both methane and overall hydrocarbon conversions increase with increasing oxygen concentration, as shown in Figures 4 and 5

Figure 1

Effect of Reactor Diameter on MeOH Selectivity
Temperature Trends; P=1100-1300 psig; HC/O₂=10

Methanol Selectivity (%)

Figure 2

Effect of Reactor Diameter on Methanol Yield
Temperature Trends; P=1100-1300 psig; HC/O₂=10

Methanol Yield (%)

Figure 3

Effect of Reactor Diameter on MeOH Selectivity
Trend with O₂ Concentration; T=850F; P=1300 psig

Methanol Selectivity (%)

Figure 4

Effect of Reactor Diameter on CH₄ Conversion
Trend with O₂ Concentration; T=850F; P=1300 psig

Methane Conversion (%)

Figure 5

Effect of Reactor Diameter on HC Conversion
Trend with O₂ Concentration; T=850F; P=1300 psig

Hydrocarbon Conversion (%)

Figure 6

Effect of Reactor Diameter on Methanol Yield
Trend with O₂ Concentration; T=850F; P=1300 psig

Methanol Yield (%)

respectively. The small differences in conversion between reactors suggested by the lines on these plots are not considered to be significant. Because the methanol selectivity in the large diameter reactor exhibits a maximum while hydrocarbon conversion changes monotonically, the methanol yield in the large reactor exhibits a maximum. Figure 6 shows that this maximum occurs around 8 vol% oxygen and is slightly lower than the maximum yield with the medium tube but slightly higher than the maximum yield with the small tube. Maximum methanol yield was between 4-5 mol% regardless of reactor diameter.

These results are interesting and require some further analysis. They may help explain some inconsistencies apparent in the methane partial oxidation literature. Most workers report a monotonic increase in methanol selectivity with decreasing oxygen, but some have observed a maximum selectivity occurring around 4-8 vol% oxygen. It is possible that wall effects and/or wall reactivity could play a role in explaining these discrepancies.

Task 3.3: Feed Injection Effects

The first investigations to be made under this task will study the effects of feed mixing on methanol selectivity and methane conversion. The feed inlet section of the plant has been re-designed to allow rapid switching between one of four mixing systems. These consist of two sizes of commercial in-line static mixers, a series of two partially-closed needle valves, and a packed bed mixer composed of a $\frac{1}{2}$ -inch diameter tube filled with $\frac{1}{8}$ -inch ceramic balls. Experiments are currently underway with the commercial static mixers and the needle valves. Results will be presented in subsequent reports.

CONCLUSIONS

The above results indicate that reactor geometry (in particular reactor surface-to-volume ratio) can have a significant effect on this system. The higher surface-to-volume ratio (small diameter) reactor was much more sensitive to high reaction temperatures, showing a steep decrease in methanol selectivity with temperatures above 900°F. The larger diameter reactors showed a much more moderate decrease in methanol selectivity with higher temperatures. These results can be explained by increased high-temperature decomposition of methanol on the reactor walls in the high surface-to-volume (small diameter) reactor. In addition, it appears that there is an interaction between reactor diameter (surface-to-volume ratio) and oxygen concentration effects. The smaller diameter reactors showed a monotonic increase in methanol selectivity with decreasing oxygen concentration between 12.5 and 1.0 vol%, while the large diameter reactor exhibited a maximum in methanol selectivity at around 8 vol% oxygen. The reason for this behavior is not known, but may involve third-body (wall) stabilization of methanol-forming intermediates at lower oxygen concentrations.

ACKNOWLEDGEMENT

This work was supported by the United States Department of Energy under Contract DE-AC22-89PC89866.

NOTICE

This report was prepared by the organization(s) named below as an account of work sponsored by the United States Department of Energy (DOE). Neither DOE, members of DOE, the organization(s) named below, nor any person acting on behalf of any of them: (a) makes any warranty, express or implied, with respect to the use of any information, apparatus, method, or process disclosed in this report or that such use may not infringe privately owned rights; or (b) assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this report.

Prepared by
Amoco Oil Company (Amoco Corporation)
Naperville, Illinois

/MJF/jmb/9103

**DATE
FILMED**

8 / 18 / 92