AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

**FOURTH QUARTER 1993
AND 1993 SUMMARY**

**F- AND H-AREA SEWAGE
SLUDGE APPLICATION SITES
GROUNDWATER MONITORING REPORT (U)**

PUBLICATION DATE: APRIL 1994

Authorized Derivative Classifier:

UNCLASSIFIED
Does Not Contain Unclassified
Controlled Nuclear Information

WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER SITE
AIKEN, SC 29808

Prepared for the U.S. Department of Energy under Control Contract No. DE-AC09-89SR18025

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ce

DISCLAIMER

This report was prepared by Westinghouse Savannah River Company (WSRC) for the United States Department of Energy under Contract No. DE-AC09-89SR18035 and is an account of work performed under that contract. Reference herein to any specific commercial product, process, or service by trademark, name, manufacturer, or otherwise does not necessarily constitute or imply endorsement, recommendation, or favoring of same by WSRC or by the United States Government or any agency thereof. The views and opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Abstract

Samples from the four wells at the F-Area Sewage Sludge Application Site (FSS wells) and the three wells at the H-Area Sewage Sludge Application Site (HSS wells) are analyzed quarterly for constituents as required by South Carolina Department of Health and Environmental Control Construction Permit 12,076 and, as requested, for other constituents as part of the Savannah River Site (SRS) Groundwater Monitoring Program. Annual analyses for other constituents, primarily metals, also are required by the permit.

No constituent exceeded either the final Primary Drinking Water Standards or the SRS Flag 2 criteria during fourth quarter 1993. Iron, lead, and manganese were the only permit-required analytes that exceeded standards at the F- and H-Area Sewage Sludge Application Sites in 1993. Tritium, aluminum, and other constituents not included in the permit have exceeded standards at this site previously, but only sporadically. These constituents were not analyzed fourth quarter 1993.

THIS PAGE LEFT BLANK INTENTIONALLY.

Contents

	Page
Abstract	iii
List of Figures	vi
List of Tables	vii
Executive Summary	1
Introduction	3
Discussion	4
Groundwater Monitoring Data	4
Analytical Results Exceeding Standards	5
Water Elevations and Groundwater Flow Directions	6
Conclusions	7
1993 Summary	8
References Cited	9
Errata	10
Appendix A – Final Primary Drinking Water Standards	A-1
Appendix B – Flagging Criteria	B-1
Appendix C – Figures	C-1
Appendix D – Groundwater Monitoring Results Tables	D-1
Appendix E – Data Quality/Useability Assessment	E-1

List of Figures

	Page
1. Location of the F- and H-Area Sewage Sludge Application Sites at the Savannah River Site	C-2
2. Location of the F- and H-Area Sewage Sludge Application Sites within the General Separations Area	C-3
3. Groundwater Monitoring Well Locations and Piezometric Surface of the Water Table at the F-Area Sewage Sludge Application Site	C-4
4. Groundwater Monitoring Well Locations and Piezometric Surface of the Water Table at the H-Area Sewage Sludge Application Site	C-5

List of Tables

	Page
1. Maximum Levels of Constituents Exceeding the Final Primary Drinking Water Standards at the F-Area Sewage Sludge Application Site	D-5
2. Maximum Levels of Constituents Exceeding Other Flag 2 Criteria at the F-Area Sewage Sludge Application Site	D-5
3. Maximum Levels of Constituents Exceeding the Final Primary Drinking Water Standards at the H-Area Sewage Sludge Application Site	D-6
4. Maximum Levels of Constituents Exceeding Other Flag 2 Criteria at the H-Area Sewage Sludge Application Site	D-6
5. Groundwater Monitoring Results for Individual Wells at the F-Area Sewage Sludge Application Site	D-7
6. Groundwater Monitoring Results for Individual Wells at the H-Area Sewage Sludge Application Site	D-12

THIS PAGE LEFT BLANK INTENTIONALLY.

Executive Summary

During fourth quarter 1993, samples from the four monitoring wells at the F-Area Sewage Sludge Application Site (FSS series) and the three monitoring wells at the H-Area Sewage Sludge Application Site (HSS series) were analyzed for constituents required by Construction Permit 12,076, issued by the South Carolina Department of Health and Environmental Control. These samples were also analyzed for other constituents as part of the Savannah River Site (SRS) Groundwater Monitoring Program. This report describes the monitoring results that exceeded final Primary Drinking Water Standards (PDWS) or SRS flagging criteria.

During fourth quarter 1993, no constituent exceeded the final PDWS or the Flag 2 criteria in any FSS or HSS well. Lead and tritium have historically exceeded PDWS and aluminum, iron, and manganese have historically exceeded the SRS Flag 2 criteria in FSS or HSS wells. These constituents, however, were not analyzed fourth quarter 1993, consistent with permit requirements.

During fourth quarter 1993, groundwater flow beneath the F-Area Sewage Sludge Application Site was toward the south-southwest, and flow beneath the H-Area Sewage Sludge Application Site was toward the southwest (universal transverse Mercator coordinates). These flow directions are consistent with previous quarters.

THIS PAGE LEFT BLANK INTENTIONALLY.

Introduction

The F-Area Sewage Sludge Application Site covers approximately 8 acres south of Road E in the southeastern portion of F Area (Figures 1 and 2, Appendix C). The H-Area Sewage Sludge Application Site includes approximately 13 acres south of Road E in the southeastern portion of H Area (Figures 1 and 2, Appendix C). These sites were permitted to receive sludge from Savannah River Site (SRS) sanitary waste water treatment plants in accordance with Construction Permit 12,076, issued by the South Carolina Department of Health and Environmental Control (SCDHEC) April 21, 1986. Sewage sludge was disposed of at the F-Area site from 1987 until third quarter 1990. Sludge was disposed of intermittently at the H-Area site from November 1990 through second quarter 1992.

In 1988, SRS determined that new wells were required at the F- and H-Area sites to assess the effects on groundwater of sewage sludge application to these sites. After receiving approval from SCDHEC, SRS installed four new wells at the F-Area site and three new wells at the H-Area site. These wells, designated FSS 1D, 2D, 3D, and 4D and HSS 1D, 2D, and 3D, were first sampled during fourth quarter 1988. All wells monitor the water table.

Currently, the SRS Environmental Protection Department/Environmental Monitoring Section (EPD/EMS) samples these wells each quarter, and the SRS Environmental Restoration Department reports the results of this sampling to SCDHEC as required by Special Condition 4 of Construction Permit 12,076.

On November 3, 1993, SRS received SCDHEC approval of the closure plans for the F- and H-Area Sewage Sludge Application Sites. One of the contingencies of the approval was that "wells for the F-Area sanitary sludge site . . . are to be left intact and operational with quarterly sampling for radionuclides The sampling of these wells with reference to sludge parameters can be terminated at this time" Radionuclide sampling was made a requirement because the sludge site is located near the Old Burial Ground (letter, L. E. Arrington, SCDHEC, to W. D. Dunaway, WSRC, November 3, 1993, with attachment of SCDHEC memorandum, B. D. Crawford to L. E. Arrington, October 26, 1993).

Beginning in 1994, the FSS well series will be sampled for radionuclides and reported in the groundwater monitoring reports for the Mixed Waste Management Facility, which includes monitoring results for the Old Burial Ground.

Discussion

Groundwater Monitoring Data

The EPD/EMS sampling procedure (EPD/EMS, 1992) requires evacuation of a minimum of two well volumes and stabilization of pH, specific conductance, and turbidity prior to sample collection. Stability is established when a minimum of three successive measurements of each of these parameters, taken within a given time period, are within a specified tolerance range.

If a well pumps dry before two well volumes are purged or before stabilization is achieved, it must be revisited within 24 hours for the data to be considered from a single sampling event. On the second visit within 24 hours, samples are taken without further purging or stability measurements; thus, these samples may not be representative of groundwater quality.

Tables 5 and 6 (Appendix D) list the number of well volumes purged from each FSS and HSS well, respectively, during each quarter of 1993 and provides sampling codes (I, P, X, etc. as defined in the Appendix D front matter) that describe incomplete or unsuccessful sampling events. Wells FSS 1D, 2D, 3D, and 4D and HSS 1D and 3D went dry during purging; all recovered sufficiently to be sampled within 24 hours. Most of these wells consistently have failed to meet the purging and stabilization criteria. At present, all FSS and HSS wells have single-speed centrifugal pumps.

Samples from the monitoring wells at the F- and H-Area Sewage Sludge Application Sites are analyzed for the following parameters as required by SCDHEC Construction Permit 12,076:

- Quarterly analyses for specific conductance and pH (laboratory measurements)
- Quarterly analyses for water quality indicators: chloride, nitrate, nitrite, sodium, and total dissolved solids
- Annual analyses for cadmium, calcium, copper, iron, lead, magnesium, manganese, nickel, potassium, and total phosphates (as phosphorus)

The FSS and HSS wells may also receive additional analyses as part of the SRS Groundwater Monitoring Program.

Monitoring results that equaled or exceeded the Safe Drinking Water Act final Primary Drinking Water Standards (PDWS) or drinking water screening levels, as established by the U.S. Environmental Protection Agency (EPA) (Appendix A); the South Carolina final PDWS for lead (Appendix A); or SRS flagging criteria that are based on final and proposed PDWS, Secondary Drinking Water Standards, or method detection limits (Appendix B) are described

in this report. Constituent levels that equaled or exceeded final PDWS or SRS Flag 2 criteria are described as *elevated* or as *exceeding* or *above* standards.

The final PDWS for individual analytes given in Appendix A may not always match the SRS flagging criteria in Appendix B. The final PDWS are used as guidelines in this compliance report to meet regulatory requirements; the flagging criteria are used by EPD/EMS to identify relative levels of constituents in the groundwater and as guides for scheduling groundwater sampling.

Analytical Results Exceeding Standards

Table 1 (Appendix D) summarizes constituents that exceeded the final PDWS (see Appendix A) during all four quarters of 1993 for the F-Area Sewage Sludge Application Site. Table 3 (Appendix D) summarizes constituents above the final PDWS for the H-Area Sewage Sludge Application Site for the year. During the fourth quarter 1993, no constituent exceeded the final PDWS at either the F- or H-Area Sewage Sludge Application Site.

Tables 2 and 4 (Appendix D) summarize constituents exceeding other Flag 2 criteria (see Appendix B) during fourth quarter 1993 for the F- and H-Area Sewage Sludge Application Sites, respectively. No constituent exceeded the Flag 2 criteria in either the FSS or the HSS wells during fourth quarter 1993.

Tables 5 and 6 (Appendix D) present the results for all analyzed constituents for the entire year 1993 and identify the results that received modifiers (which help define laboratory accuracy and precision) or that exceeded standards or the EPA-approved holding times during fourth quarter 1993.

Presently, SRS sets no flagging criteria for alkalinity. In the FSS wells during fourth quarter 1993, alkalinity ranged up to 32 mg/L in well FSS 1D (Table 5, Appendix D). In the HSS wells during fourth quarter 1993, alkalinity reached a maximum of 1 mg/L in wells HSS 1D and 2D (Table 6, Appendix D).

Result values for earlier quarters presented in this report may differ from the values for those same quarters presented in previous reports because some re-analyses may have occurred after the quarterly reports were printed. Also, samples for field data are collected once each quarter but samples for analytical data may be collected more than once each quarter. Thus, because the results tables present the highest analytical result for the quarter, the reported analytical result may be from a sample collected on a different date from the date the field data sample was collected.

In addition to the results tables, Appendix D provides definitions of the abbreviations and the modifiers used in the results tables as well as descriptions of holding times, data rounding, and data qualification practices. Appendix E provides a general assessment of the quality and useability of the data.

Water Elevations and Groundwater Flow Directions

Water-table elevations during fourth quarter 1993 at the F-Area Sewage Sludge Application Site indicate that the groundwater flow direction was toward the south-southwest (universal transverse Mercator coordinates [UTM]), discharging into Fourmile Branch (Figure 3, Appendix C). Historically, groundwater flow direction at this site has been consistently south to southwest.

The nearly linear orientation of the wells at the H-Area Sewage Sludge Application Site and the fact that wells HSS 1D and 2D are screened well below the water table make the determination of groundwater flow direction at this site difficult. Available data, including water-level elevations from the three HSS wells, indicate that groundwater flow was generally southwest during fourth quarter 1993 (UTM coordinates) (Figure 4, Appendix C). Groundwater flow direction at this site has been consistently south to southwest in previous quarters.

Conclusions

- During fourth quarter 1993, no constituent exceeded the final PDWS or the SRS Flag 2 criteria in any FSS or HSS well.
- Groundwater flow beneath the F- and H-Area Sewage Sludge Application Sites was toward the south-southwest and southwest (UTM coordinates), respectively. Historically, groundwater flow directions at the sites generally have been south to southwest.
- Alkalinity ranged up to 32 mg/L in the FSS well series and up to 1 mg/L in the HSS well series during fourth quarter 1993.
- The wells that pumped dry during purging in fourth quarter 1993, FSS 1D, 2D, 3D, and 4D and HSS 1D and 3D, may not have yielded representative groundwater samples.

1993 Summary

- As in previous years, tritium exceeded the final PDWS in downgradient wells FSS 2D and 3D during each quarter this constituent was analyzed. Maximum tritium activity during 1993 occurred in well FSS 2D during first quarter at $8.5\text{E}+01$ pCi/mL.
- Elevated concentrations of lead occurred sporadically during the year in FSS and HSS wells. Lead was elevated in upgradient well FSS 1D and downgradient well FSS 3D during first and third quarters 1993 and in downgradient well HSS 1D during third quarter 1993.
- Generally, a constituent in a downgradient well but not in an upgradient well, such as the elevated lead in downgradient well HSS 1D, is considered a product of the waste management unit.
- The source of the elevated tritium activities in the downgradient FSS wells has not been determined. Historical records for the F- and H-Area Sewage Sludge Application Sites indicate that no radionuclides were disposed of in the immediate area. However, the FSS wells are adjacent to the Old Burial Ground which has elevated tritium activities.
- Presently, SRS sets no flagging criteria for alkalinity. In the FSS wells during 1993, alkalinity ranged up to 67 mg/L in well FSS 2D during first quarter (Table 5, Appendix D). In the HSS wells during 1993, alkalinity ranged as high as 5 mg/L in well HSS 1D during first quarter (Table 6, Appendix D).
- Groundwater flow beneath the F- and H-Area Sewage Sludge Application Sites was generally to the southwest during previous years.

References Cited

EPD/EMS (Environmental Protection Department/Environmental Monitoring Section), 1992. **Hydrogeologic Data Collection Procedures and Specifications: Sampling Groundwater Monitoring Wells.** Manual 3Q5, Chapter 15, Rev. 1. Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

Errata

- Some results for earlier quarters of 1993 that are presented in this report may differ from the results presented in the earlier reports. These differences arise because reanalyses may be performed by the laboratories after reports have been printed.

First Quarter 1993:

- No errata have been reported.

Second Quarter 1993:

- No errata have been reported.

Third Quarter 1993:

- No errata have been reported.

Appendix A – Final Primary Drinking Water Standards

Final Primary Drinking Water Standards

Analyte	Unit	Level	Status	Source
Antimony	µg/L	6	Final	EPA, 1992b
Arsenic	µg/L	50	Final	EPA, 1992a
Asbestos	fibers/L	7,000,000	Final	EPA, 1992a
Barium	µg/L	2,000	Final	EPA, 1992a
Benzene	µg/L	5	Final	EPA, 1992a
Benzo[a]pyrene	µg/L	0.2	Final	EPA, 1992b
Beryllium	µg/L	4	Final	EPA, 1992b
Bis(2-ethylhexyl) phthalate	µg/L	6	Final	EPA, 1992b
Bromodichloromethane	µg/L	100 ^a	Final	EPA, 1992a
Bromoform	µg/L	100 ^a	Final	EPA, 1992a
2-sec-Butyl-4,6-dinitrophenol	µg/L	7	Final	EPA, 1992b
Cadmium	µg/L	5	Final	EPA, 1992a
Carbon tetrachloride	µg/L	5	Final	EPA, 1992a
Chlordane	µg/L	2	Final	EPA, 1992a
Chlorobenzene	µg/L	100	Final	EPA, 1992a
Chloroethene (Vinyl chloride)	µg/L	2	Final	EPA, 1992a
Chloroform	µg/L	100 ^a	Final	EPA, 1992a
Chromium	µg/L	100	Final	EPA, 1992a
Copper	µg/L	1,300	Final	EPA, 1992a
Cyanide	µg/L	200	Final	EPA, 1992b
Dibromochloromethane	µg/L	100 ^a	Final	EPA, 1992a
Dibromochloropropane	µg/L	0.2	Final	EPA, 1992a
1,2-Dibromoethane (Ethylene dibromide)	µg/L	0.05	Final	EPA, 1992a
1,2-Dichlorobenzene	µg/L	600	Final	EPA, 1992a
1,4-Dichlorobenzene	µg/L	75	Final	EPA, 1992a
1,2-Dichloroethane	µg/L	5	Final	EPA, 1992a
1,1-Dichloroethene	µg/L	7	Final	EPA, 1992a
1,2-Dichloroethene	µg/L	50	Final	EPA, 1992b
cis-1,2-Dichloroethene	µg/L	70	Final	EPA, 1992a
trans-1,2-Dichloroethene	µg/L	100	Final	EPA, 1992a
Dichloromethane (Methylene chloride)	µg/L	5	Final	EPA, 1992b
2,4-Dichlorophenoxyacetic acid	µg/L	70	Final	EPA, 1992a
1,2-Dichloropropane	µg/L	5	Final	EPA, 1992a
Endrin	µg/L	2	Final	EPA, 1992b
Ethylbenzene	µg/L	700	Final	EPA, 1992a
Fluoride	µg/L	4,000	Final	EPA, 1992a
Gross alpha ^b	pCi/L	1.5E+01	Final	EPA, 1992a
Heptachlor	µg/L	0.4	Final	EPA, 1992a
Heptachlor epoxide	µg/L	0.2	Final	EPA, 1992a
Hexachlorobenzene	µg/L	1	Final	EPA, 1992b
Hexachlorocyclopentadiene	µg/L	50	Final	EPA, 1992b
Lead	µg/L	50	Final	SCDHEC, 1981
Lindane	µg/L	0.2	Final	EPA, 1992a
Mercury	µg/L	2	Final	EPA, 1992a
Methoxychlor	µg/L	40	Final	EPA, 1992a
Nickel	µg/L	100	Final	EPA, 1992b
Nitrate as nitrogen	µg/L	10,000	Final	EPA, 1992a
Nitrate-nitrite as nitrogen	µg/L	10,000	Final	EPA, 1992a
Nitrite as nitrogen	µg/L	1,000	Final	EPA, 1992a
Nonvolatile beta ^c	pCi/L	5E+01	Final	EPA, 1977
PCBs ^d	µg/L	0.5	Final	EPA, 1992a
Pentachlorophenol	µg/L	1	Final	EPA, 1992a
Selenium	µg/L	50	Final	EPA, 1992a

Analyte	Unit	Level	Status	Source
Strontium-89/90 ^a	pCi/L	8E + 00	Final	EPA, 1992a
Strontium-90	pCi/L	8E + 00	Final	EPA, 1992a
Styrene	μg/L	100	Final	EPA, 1992a
2,3,7,8-TCDD	μg/L	0.00003	Final	EPA, 1992b
Tetrachloroethylene	μg/L	5	Final	EPA, 1992a
Thallium	μg/L	2	Final	EPA, 1992b
Toluene	μg/L	1,000	Final	EPA, 1992a
Total trihalomethanes	μg/L	100	Final	EPA, 1992a
Toxaphene	μg/L	3	Final	EPA, 1992a
2,4,5-TP (Silvex)	μg/L	50	Final	EPA, 1992a
1,2,4-Trichlorobenzene	μg/L	70	Final	EPA, 1992b
1,1,1-Trichloroethane	μg/L	200	Final	EPA, 1992a
1,1,2-Trichloroethane	μg/L	5	Final	EPA, 1992b
Trichloroethylene	μg/L	5	Final	EPA, 1992a
Tritium	pCi/mL	2E + 01	Final	EPA, 1992a
Xylenes	μg/L	10,000	Final	EPA, 1992a

- ^a This value is the drinking water standard for total trihalomethanes (the sum of bromoform, bromodichloromethane, chloroform, and dibromochloromethane).
- ^b The standard given is for gross alpha including radium-226 but excluding radon and uranium.
- ^c This is the screening level above which providers of public drinking water should perform analyses for specific man-made radionuclides. The standard for the total dose equivalent from all such radionuclides is 4 mrem per year.
- ^d Analyses were conducted in 1993 for the following: PCB 1016, PCB 1221, PCB 1232, PCB 1242, PCB 1248, PCB 1254, and PCB 1260.
- ^e For double radionuclide analyses where each separate radionuclide has its own standard, the more stringent standard is used.

References

- EPA (U.S. Environmental Protection Agency), 1977. **National Interim Primary Drinking Water Regulations**, EPA-570/9-76-003. Washington, DC.
- EPA (U.S. Environmental Protection Agency), 1992a. **National Primary Drinking Water Regulations, Code of Federal Regulations**, Title 40, Part 141, pp. 589-729. Washington, DC.
- EPA (U.S. Environmental Protection Agency), 1992b. **National Primary Drinking Water Regulations—Synthetic Organic Chemicals and Inorganic Chemicals; National Primary Drinking Water Regulations Implementation**. **Federal Register**, July 17, 1992, pp. 31776-31849. Washington, DC.
- SCDHEC (South Carolina Department of Health and Environmental Control), 1981. **State Primary Drinking Water Regulations**, R.61-58.5. Columbia, SC.

THIS PAGE LEFT BLANK INTENTIONALLY.

Appendix B – Flagging Criteria

Flagging Criteria

The Savannah River Site Environmental Protection Department/Environmental Monitoring Section (EPD/EMS) flagging criteria are as follows:

- Flag 2 criteria for constituents equal the Safe Drinking Water Act (SDWA) final Primary Drinking Water Standard (PDWS), the SDWA proposed PDWS, or the SDWA Secondary Drinking Water Standard (SDWS). If a constituent does not have a drinking water standard, the Flag 2 criterion equals 10 times the method detection limit (MDL) calculated as the 90th percentile detection limit obtained recently by one of the primary analytical laboratories.
- Flag 1 criteria for constituents equal one-half of the final PDWS, one-half the proposed PDWS, or one-half the SDWS. If a constituent does not have a drinking water standard, the Flag 1 criterion equals 5 times the MDL calculated as the 90th percentile detection limit obtained recently by one of the primary analytical laboratories.
- Flag 0 criteria are assigned to constituent levels below Flag 1 criteria, constituent levels below the sample detection limits, or constituents having no flagging criteria.

The following parameters are not assigned flagging criteria: alkalinity, calcium, color, corrosivity, Eh, magnesium, odor, potassium, silica, sodium, total dissolved solids, total phosphates (as P), total phosphorus, and turbidity. In addition, common laboratory contaminants and cleaners including some phthalates, ketones, and toluene are not assigned flagging criteria.

Analyte	Unit	Flag 1	Flag 2	Source ^a
Acenaphthene	µg/L	50	100	EPA Method 8270
Acenaphthylene	µg/L	50	100	EPA Method 8270
Acetone	µg/L	500	1,000	EPA Method 8240
Acetonitrile (Methyl cyanide)	µg/L	500	1,000	EPA Method 8240
Acetophenone	µg/L	50	100	EPA Method 8270
2-Acetylaminofluorene	µg/L	50	100	EPA Method 8270
Acrolein	µg/L	100	200	EPA Method 8240
Acrylonitrile	µg/L	100	200	EPA Method 8240
Actinium-228	pCi/L	1.64E+03	3.27E+03	Proposed PDWS (EPA, 1991)
Aldrin	µg/L	0.25	0.5	EPA Method 8080
Alkalinity (as CaCO ₃)		No flag	No flag	Set by EPD/EMS
Allyl chloride	µg/L	250	500	EPA Method 8240
Aluminum	µg/L	25	50	SDWS (EPA, 1992c)
Americium-241	pCi/L	3.17E+00	6.34E+00	Proposed PDWS (EPA, 1991)
Americium-243	pCi/L	3.19E+00	6.37E+00	Proposed PDWS (EPA, 1991)
4-Aminobiphenyl	µg/L	50	100	EPA Method 8270
Ammonia	µg/L	500	1,000	APHA Method 417B
Ammonia nitrogen	µg/L	500	1,000	EPA Method 350.1
Aniline	µg/L	50	100	EPA Method 8270
Anthracene	µg/L	50	100	EPA Method 8270
Antimony	µg/L	3	6	Final PDWS (EPA, 1992b)
Antimony-125	pCi/L	1.5E+02	3E+02	Final PDWS (EPA, 1977)
Aramite	µg/L	50	100	EPA Method 8270
Arsenic	µg/L	25	50	Final PDWS (EPA, 1992a)

Analyte	Unit	Flag 1	Flag 2	Source ^a
Asbestos	Fibers/L	3,500,000	7,000,000	Final PDWS (EPA, 1992a)
Azobenzene	µg/L	50	100	EPA Method 825
Barium	µg/L	1,000	2,000	Final PDWS (EPA, 1992a)
Barium-140	pCi/L	4.5E+01	9E+01	Final PDWS (EPA, 1977)
Benzene	µg/L	2.5	5	Final PDWS (EPA, 1992a)
alpha-Benzene hexachloride	µg/L	0.25	0.5	EPA Method 8080
beta-Benzene hexachloride	µg/L	0.25	0.5	EPA Method 8080
delta-Benzene hexachloride	µg/L	0.25	0.5	EPA Method 8080
Benzidine	µg/L	250	500	EPA Method 8270
Benzo[a]anthracene	µg/L	0.05	0.1	Proposed PDWS (EPA, 1990)
Benzo[b]fluoranthene	µg/L	0.1	0.2	Proposed PDWS (EPA, 1990)
Benzo[k]fluoranthene	µg/L	0.1	0.2	Proposed PDWS (EPA, 1990)
Benzoic acid	µg/L	250	500	EPA Method 8270
Benzo[g,h,i]perylene	µg/L	50	100	EPA Method 8270
Benzo[a]pyrene	µg/L	0.1	0.2	Final PDWS (EPA, 1992b)
1,4-Benzoquinone	µg/L	50	100	EPA Method 8270
Benzyl alcohol	µg/L	50	100	EPA Method 8270
Beryllium	µg/L	2	4	Final PDWS (EPA, 1992b)
Beryllium-7	pCi/L	3E+03	6E+03	Final PDWS (EPA, 1977)
Bis(2-chloroethoxy) methane	µg/L	50	100	EPA Method 8270
Bis(2-chloroethyl) ether	µg/L	50	100	EPA Method 8270
Bis(2-chloroisopropyl) ether	µg/L	50	100	EPA Method 8270
Bis(chloromethyl) ether	µg/L	50	100	EPA Method 8270
Bis(2-ethylhexyl) phthalate	µg/L	3	6	Final PDWS (EPA, 1992b)
Bromide	µg/L	5,000	10,000	EPA Method 300.0
Bromodichloromethane	µg/L	50	100	Final PDWS (EPA, 1992a)
Bromoform	µg/L	50	100	Final PDWS (EPA, 1992a)
Bromomethane (Methyl bromide)	µg/L	5	10	EPA Method 8240
4-Bromophenyl phenyl ether	µg/L	50	100	EPA Method 8270
2-sec-Butyl-4,6-dinitrophenol	µg/L	3.5	7	Final PDWS (EPA, 1992b)
Butylbenzyl phthalate		No flag	No flag	Set by EPD/EMS
Cadmium	µg/L	2.5	5	Final PDWS (EPA, 1992a)
Calcium		No flag	No flag	Set by EPD/EMS
Carbon disulfide	µg/L	5	10	EPA Method 8240
Carbon tetrachloride	µg/L	2.5	5	Final PDWS (EPA, 1992a)
Carbon-14	pCi/L	1E+03	2E+03	Final PDWS (EPA, 1977)
Carbonate		No flag	No flag	Set by EPD/EMS
Cerium-141	pCi/L	1.5E+02	3E+02	Final PDWS (EPA, 1977)
Cerium-144	pCi/L	1.31E+02	2.61E+02	Proposed PDWS (EPA, 1991)
Cesium-134 ^b	pCi/L	4.07E+01	8.13E+01	Proposed PDWS (EPA, 1991)
Cesium-137	pCi/L	1E+02	2E+02	Final PDWS (EPA, 1977)
Chlordane	µg/L	1	2	Final PDWS (EPA, 1992a)
Chloride	µg/L	125,000	250,000	SDWS (EPA, 1992c)
4-Chloroaniline	µg/L	50	100	EPA Method 8270
Chlorobenzene	µg/L	50	100	Final PDWS (EPA, 1992a)
Chlorobenzilate	µg/L	50	100	EPA Method 8270
Chloroethane	µg/L	5	10	EPA Method 8240
Chloroethene (Vinyl chloride)	µg/L	1	2	Final PDWS (EPA, 1992a)
Chloroethyl vinyl ether	µg/L	5	10	EPA Method 8240
2-Chloroethyl vinyl ether	µg/L	5	10	EPA Method 8240
Chloroform	µg/L	50	100	Final PDWS (EPA, 1992a)
4-Chloro-m-cresol	µg/L	50	100	EPA Method 8270
Chloromethane (Methyl chloride)	µg/L	5	10	EPA Method 8240
2-Chloronaphthalene	µg/L	50	100	EPA Method 8240
2-Chlorophenol	µg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source ^a
4-Chlorophenyl phenyl ether	µg/L	50	100	EPA Method 8270
Chloroprene	µg/L	1,000	2,000	EPA Method 8240
Chromium	µg/L	50	100	Final PDWS (EPA, 1992a)
Chromium-51	pCi/L	3E+03	6E+03	Final PDWS (EPA, 1977)
Chrysene	µg/L	0.1	0.2	Proposed PDWS (EPA, 1990)
Cobalt	µg/L	20	40	EPA Method 6010
Cobalt-57	pCi/L	5E+02	1E+03	Final PDWS (EPA, 1977)
Cobalt-58	pCi/L	4.5E+03	9E+03	Final PDWS (EPA, 1977)
Cobalt-60	pCi/L	5E+01	1E+02	Final PDWS (EPA, 1977)
Color		No flag	No flag	Set by EPD/EMS
Copper	µg/L	650	1,300	Final PDWS (EPA, 1992a)
Corrosivity		No flag	No flag	Set by EPD/EMS
m-Cresol (3-Methylphenol)	µg/L	50	100	EPA Method 8270
o-Cresol (2-Methylphenol)	µg/L	50	100	EPA Method 8270
p-Cresol (4-Methylphenol)	µg/L	50	100	EPA Method 8270
Curium-242	pCi/L	6.65E+01	1.33E+02	Proposed PDWS (EPA, 1991)
Curium-243	pCi/L	4.15E+00	8.3E+00	Proposed PDWS (EPA, 1991)
Curium-243/244 ^c	pCi/L	4.15E+00	8.3E+00	Proposed PDWS (EPA, 1991)
Curium-244	pCi/L	4.92E+00	9.84E+00	Proposed PDWS (EPA, 1991)
Curium-245/246 ^c	pCi/L	3.12E+00	6.23E+00	Proposed PDWS (EPA, 1991)
Curium-246	pCi/L	3.14E+00	6.27E+00	Proposed PDWS (EPA, 1991)
Cyanide	µg/L	100	200	Final PDWS (EPA, 1992b)
p,p'-DDD	µg/L	0.5	1	EPA Method 8080
p,p'-DDE	µg/L	0.5	1	EPA Method 8080
p,p'-DDT	µg/L	0.5	1	EPA Method 8080
Di-n-butyl phthalate		No flag	No flag	Set by EPD/EMS
Di-n-octyl phthalate		No flag	No flag	Set by EPD/EMS
Diallate	µg/L	50	100	EPA Method 8270
Dibenz[a,h]anthracene	µg/L	0.15	0.3	Proposed PDWS (EPA, 1990)
Dibenzofuran	µg/L	50	100	EPA Method 8270
Dibromochloromethane	µg/L	50	100	Final PDWS (EPA, 1992a)
1,2-Dibromo-3-chloropropane	µg/L	0.1	0.2	Final PDWS (EPA, 1992a)
1,2-Dibromoethane (Ethylene dibromide)	µg/L	0.025	0.05	Final PDWS (EPA, 1992a)
Dibromomethane (Methylene bromide)	µg/L	5	10	EPA Method 8240
1,2-Dichlorobenzene	µg/L	300	600	Final PDWS (EPA, 1992a)
1,3-Dichlorobenzene	µg/L	50	100	EPA Method 8270
1,4-Dichlorobenzene	µg/L	37.5	75	Final PDWS (EPA, 1992a)
3,3'-Dichlorobenzidine	µg/L	50	100	EPA Method 8270
trans-1,4-Dichloro-2-butene	µg/L	150	300	EPA Method 8240
Dichlorodifluoromethane	µg/L	5	10	EPA Method 8240
1,1-Dichloroethane	µg/L	5	10	EPA Method 8240
1,2-Dichloroethane	µg/L	2.5	5	Final PDWS (EPA, 1992a)
1,1-Dichloroethene	µg/L	3.5	7	Final PDWS (EPA, 1992a)
1,2-Dichloroethene	µg/L	25	50	Final PDWS (EPA, 1992b)
cis-1,2-Dichloroethene	µg/L	35	70	Final PDWS (EPA, 1992a)
trans-1,2-Dichloroethene	µg/L	50	100	Final PDWS (EPA, 1992a)
Dichloromethane (Methylene chloride)	µg/L	2.5	5	Final PDWS (EPA, 1992b)
2,4-Dichlorophenol	µg/L	50	100	EPA Method 8270
2,6-Dichlorophenol	µg/L	50	100	EPA Method 8270
2,4-Dichlorophenoxyacetic acid	µg/L	35	70	Final PDWS (EPA, 1992a)
1,2-Dichloropropane	µg/L	2.5	5	Final PDWS (EPA, 1992a)
cis-1,3-Dichloropropene	µg/L	5	10	EPA Method 8240

Analyte	Unit	Flag 1	Flag 2	Source ^a
trans-1,3-Dichloropropene	µg/L	5	10	EPA Method 8240
Dieldrin	µg/L	2.5	5	EPA Method 8080
Diethyl phthalate		No flag	No flag	Set by EPD/EMS
Dimethoate	µg/L	50	100	EPA Method 8270
p-Dimethylaminoazobenzene	µg/L	50	100	EPA Method 8270
p-(Dimethylamino)ethylbenzene	µg/L	50	100	EPA Method 8270
7,12-Dimethylbenz[a]anthracene	µg/L	50	100	EPA Method 8270
3,3'-Dimethylbenzidine	µg/L	50	100	EPA Method 8270
a,a-Dimethylphenethylamine	µg/L	50	100	EPA Method 8270
2,4-Dimethyl phenol	µg/L	50	100	EPA Method 8270
Dimethyl phthalate		No flag	No flag	Set by EPD/EMS
1,3-Dinitrobenzene	µg/L	50	100	EPA Method 8270
2,4-Dinitrophenol	µg/L	250	500	EPA Method 8270
2,4-Dinitrotoluene	µg/L	50	100	EPA Method 8270
2,6-Dinitrotoluene	µg/L	50	100	EPA Method 8270
1,4-Dioxane	µg/L	50	100	EPA Method 8270
Diphenylamine	µg/L	50	100	EPA Method 8270
1,2-Diphenylhydrazine	µg/L	50	100	EPA Method 8270
Dissolved organic carbon	µg/L	5,000	10,000	EPA Method 9060
Disulfoton	µg/L	50	100	EPA Method 8270
Eh		No flag	No flag	Set by EPD/EMS
alpha-Endosulfan	µg/L	50	100	EPA Method 8270
beta-Endosulfan	µg/L	50	100	EPA Method 8270
Endosulfan I	µg/L	0.5	1	EPA Method 8080
Endosulfan II	µg/L	0.5	1	EPA Method 8080
Endosulfan sulfate	µg/L	0.5	1	EPA Method 8080
Endrin	µg/L	1	2	Final PDWS (EPA, 1992b)
Endrin aldehyde	µg/L	0.5	1	EPA Method 8080
Endrin ketone		No flag	No flag	Set by EPD/EMS
Ethylbenzene	µg/L	350	700	Final PDWS (EPA, 1992a)
Ethyl methacrylate	µg/L	50	100	EPA Method 8270
Ethyl methanesulfonate	µg/L	50	100	EPA Method 8270
Europium-152	pCi/L	3E+01	6E+01	Final PDWS (EPA, 1977)
Europium-154	pCi/L	1E+02	2E+02	Final PDWS (EPA, 1977)
Europium-155	pCi/L	3E+02	6E+02	Final PDWS (EPA, 1977)
Famphur	µg/L	50	100	EPA Method 8270
Fluoranthene	µg/L	30	100	EPA Method 8270
Fluorene	µg/L	50	100	EPA Method 8270
Fluoride	µg/L	2,000	4,000	Final PDWS (EPA, 1992a)
Gross alpha	pCi/L	7.5E+00	1.5E+01	Final PDWS (EPA, 1992a)
Heptachlor	µg/L	0.2	0.4	Final PDWS (EPA, 1992a)
Heptachlor epoxide	µg/L	0.1	0.2	Final PDWS (EPA, 1992a)
Heptachlorodibenzo-p-dioxin isomers	µg/L	0.00325	0.0065	EPA Method 8280
1,2,3,4,6,7,8-HPCDD	µg/L	0.00325	0.0065	EPA Method 8280
Heptachlorodibenzo-p-furan isomers	µg/L	0.00225	0.0045	EPA Method 8280
1,2,3,4,6,7,8-HPCDF	µg/L	0.00225	0.0045	EPA Method 8280
Hexachlorobenzene	µg/L	0.5	1	Final PDWS (EPA, 1992b)
Hexachlorobutadiene	µg/L	50	100	EPA Method 8270
Hexachlorocyclopentadiene	µg/L	25	50	Final PDWS (EPA, 1992b)
Hexachlorodibenzo-p-dioxin isomers	µg/L	0.00225	0.0045	EPA Method 8280
1,2,3,4,7,8-HXCDD	µg/L	0.00225	0.0045	EPA Method 8280
Hexachlorodibenzo-p-furan isomers	µg/L	0.002	0.004	EPA Method 8280
1,2,3,4,7,8-HXCDF	µg/L	0.002	0.004	EPA Method 8280

Analyte	Unit	Flag 1	Flag 2	Source ^a
Hexachloroethane	µg/L	50	100	EPA Method 8270
Hexachlorophene	µg/L	250	500	EPA Method 8270
Hexachloropropene	µg/L	50	100	EPA Method 8270
2-Hexanone	µg/L	50	100	EPA Method 8240
Indeno[1,2,3-c,d]pyrene	µg/L	50	100	EPA Method 8270
Iodine	µg/L	250	500	APHA Method 415A
Iodine-129	pCi/L	5E-01	1E+00	Final PDWS (EPA, 1977)
Iodine-131	pCi/L	1.5E+00	3E+00	Final PDWS (EPA, 1977)
Iodomethane (Methyl iodide)	µg/L	75	150	EPA Method 8240
Iron	µg/L	150	300	SDWS (EPA, 1992c)
Iron-55	pCi/L	1E+03	2E+03	Final PDWS (EPA, 1977)
Iron-59	pCi/L	1E+02	2E+02	Final PDWS (EPA, 1977)
Isobutyl alcohol	µg/L	500	1,000	EPA Method 8240
Isodrin	µg/L	50	100	EPA Method 8270
Isophorone	µg/L	50	100	EPA Method 8270
Isosafrole	µg/L	50	100	EPA Method 8270
Kepone	µg/L	50	100	EPA Method 8270
Lanthanum-140	pCi/L	3E+01	6E+01	Final PDWS (EPA, 1977)
Lead	µg/L	7.5	15	Final PDWS (EPA, 1992a)
Lindane	µg/L	0.1	0.2	Final PDWS (EPA, 1992a)
Lithium	µg/L	25	50	EPA Method 6010
Magnesium		No flag	No flag	Set by EPD/EMS
Manganese	µg/L	25	50	SDWS (EPA, 1992c)
Manganese-54	pCi/L	1.5E+02	3E+02	Final PDWS (EPA, 1977)
Mercury	µg/L	1	2	Final PDWS (EPA, 1992a)
Methacrylonitrile	µg/L	250	500	EPA Method 8240
Methapyrilene	µg/L	50	100	EPA Method 8270
Methoxychlor	µg/L	20	40	Final PDWS (EPA, 1992a)
3-Methylcholanthrene	µg/L	50	100	EPA Method 8270
2-Methyl-4,6-dinitrophenol	µg/L	250	500	EPA Method 8270
Methyl ethyl ketone		No flag	No flag	Set by EPD/EMS
Methyl isobutyl ketone		No flag	No flag	Set by EPD/EMS
Methyl methacrylate	µg/L	50	100	EPA Method 8270
Methyl methanesulfonate	µg/L	50	100	EPA Method 8270
2-Methylnaphthalene	µg/L	50	100	EPA Method 8270
Molybdenum	µg/L	250	500	EPA Method 6010
Naphthalene	µg/L	50	100	EPA Method 8270
1,4-Naphthoquinone	µg/L	50	100	EPA Method 8270
1-Naphthylamine	µg/L	50	100	EPA Method 8270
2-Naphthylamine	µg/L	50	100	EPA Method 8270
Neptunium-237	pCi/L	3.53E+00	7.06E+00	Proposed PDWS (EPA, 1991)
Nickel	µg/L	50	100	Final PDWS (EPA, 1992b)
Nickel-59	pCi/L	1.5E+02	3E+02	Final PDWS (EPA, 1977)
Nickel-63	pCi/L	2.5E+01	5E+01	Final PDWS (EPA, 1977)
Niobium-95	pCi/L	1.5E+02	3E+02	Final PDWS (EPA, 1977)
Nitrate as nitrogen	µg/L	5,000	10,000	Final PDWS (EPA, 1992a)
Nitrate-nitrite as nitrogen	µg/L	5,000	10,000	Final PDWS (EPA, 1992a)
Nitrite as nitrogen	µg/L	500	1,000	Final PDWS (EPA, 1992a)
2-Nitroaniline	µg/L	50	100	EPA Method 8270
3-Nitroaniline	µg/L	50	100	EPA Method 8270
4-Nitroaniline	µg/L	50	100	EPA Method 8270
Nitrobenzene	µg/L	50	100	EPA Method 8270
Nitrogen by Kjeldahl method	µg/L	500	1,000	EPA Method 351.2
2-Nitrophenol	µg/L	50	100	EPA Method 8270
4-Nitrophenol	µg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source ^a
4-Nitroquinoline-1-oxide	μg/L	50	100	EPA Method 8270
N-Nitrosodi-n-butylamine	μg/L	50	100	EPA Method 8270
N-Nitrosodiethylamine	μg/L	50	100	EPA Method 8270
N-Nitrosodimethylamine	μg/L	50	100	EPA Method 8270
N-Nitrosodiphenylamine	μg/L	50	100	EPA Method 8270
N-Nitrosodipropylamine	μg/L	50	100	EPA Method 8270
N-Nitrosomethylethylamine	μg/L	50	100	EPA Method 8270
N-Nitrosomorpholine	μg/L	50	100	EPA Method 8270
N-Nitrosopiperidine	μg/L	50	100	EPA Method 8270
N-Nitrosopyrrolidine	μg/L	50	100	EPA Method 8270
5-Nitro-o-toluidine	μg/L	50	100	EPA Method 8270
Nonvolatile beta	pCi/L	2.5E+01	5E+01	Proposed PDWS (EPA, 1986)
Octachlorodibenzo-p-dioxin isomers	μg/L	0.005	0.01	EPA Method 8280
Octachlorodibenzo-p-furan isomers	μg/L	0.005	0.01	EPA Method 8280
Odor		No flag	No flag	Set by EPD/EMS
Oil & Grease	μg/L	5,000	10,000	EPA Method 413.1
Parathion	μg/L	0.25	0.5	EPA Method 8080
Parathion methyl	μg/L	0.25	0.5	EPA Method 8080
PCB 1016	μg/L	0.25	0.5	Final PDWS (EPA, 1992a)
PCB 1221	μg/L	0.25	0.5	Final PDWS (EPA, 1992a)
PCB 1232	μg/L	0.25	0.5	Final PDWS (EPA, 1992a)
PCB 1242	μg/L	0.25	0.5	Final PDWS (EPA, 1992a)
PCB 1248	μg/L	0.25	0.5	Final PDWS (EPA, 1992a)
PCB 1254	μg/L	0.25	0.5	Final PDWS (EPA, 1992a)
PCB 1260	μg/L	0.25	0.5	Final PDWS (EPA, 1992a)
PCB 1262	μg/L	0.25	0.5	Final PDWS (EPA, 1992a)
Pentachlorobenzene	μg/L	50	100	EPA Method 8270
Pentachlorodibenzo-p-dioxin isomers	μg/L	0.00275	0.0055	EPA Method 8280
1,2,3,7,8-PCDD	μg/L	0.00275	0.0055	EPA Method 8280
Pentachlorodibenzo-p-furan isomers	μg/L	0.00275	0.0055	EPA Method 8280
1,2,3,7,8-PCDF	μg/L	0.00275	0.0055	EPA Method 8280
Pentachloroethane	μg/L	50	100	EPA Method 8270
Pentachloronitrobenzene	μg/L	50	100	EPA Method 8270
Pentachlorophenol	μg/L	0.5	1	Final PDWS (EPA, 1992a)
pH	pH	8	10	Set by EPD/EMS
pH	pH	4	3	Set by EPD/EMS
Phenacetin	μg/L	50	100	EPA Method 8270
Phenanthrene	μg/L	50	100	EPA Method 8270
Phenol	μg/L	50	100	EPA Method 8270
Phenols	μg/L	25	50	EPA Method 420.1
p-Phenylenediamine	μg/L	50	100	EPA Method 8270
Phorate	μg/L	0.5	1	EPA Method 8080
2-Picoline	μg/L	50	100	EPA Method 8270
Plutonium-238	pCi/L	3.51E+00	7.02E+00	Proposed PDWS (EPA, 1991)
Plutonium-239	pCi/L	3.11E+01	6.21E+01	Proposed PDWS (EPA, 1991)
Plutonium-239/240 ^c	pCi/L	3.11E+01	6.21E+01	Proposed PDWS (EPA, 1991)
Plutonium-240	pCi/L	3.11E+01	6.22E+01	Proposed PDWS (EPA, 1991)
Plutonium-241	pCi/L	3.13E+01	6.26E+01	Proposed PDWS (EPA, 1991)
Plutonium-242	pCi/L	3.27E+01	6.54E+01	Proposed PDWS (EPA, 1991)
Potassium		No flag	No flag	Set by EPD/EMS
Potassium-40	pCi/L	1.5E+02	3E+02	Proposed PDWS (EPA, 1986)
Pronamid	μg/L	50	100	EPA Method 8270
Propionitrile	μg/L	1,000	2,000	EPA Method 8240
Pyrene	μg/L	50	100	EPA Method 8270
Pyridine	μg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source ^a
Radium (alpha-emitting) ^d	pCi/L	1E+01	2E+01	Proposed PDWS (EPA, 1991)
Radium-226	pCi/L	1E+01	2E+01	Proposed PDWS (EPA, 1991)
Radium-228	pCi/L	1E+01	2E+01	Proposed PDWS (EPA, 1991)
Radon-222	pCi/L	1.5E+02	3E+02	Proposed PDWS (EPA, 1991)
Ruthenium-103	pCi/L	1E+02	2E+02	Final PDWS (EPA, 1977)
Ruthenium-106	pCi/L	1.5E+01	3E+01	Final PDWS (EPA, 1977)
Safrole	µg/L	50	100	EPA Method 8270
Selenium	µg/L	25	50	Final PDWS (EPA, 1992a)
Silica		No flag	No flag	Set by EPD/EMS
Total silica	µg/L	500	1,000	EPA Method 6010
Silver	µg/L	50	100	SDWS (EPA, 1992c)
Sodium		No flag	No flag	Set by EPD/EMS
Sodium-22	pCi/L	2.33E+02	4.66E+02	Proposed PDWS (EPA, 1991)
Specific conductance	µS/cm	250	500	Set by EPD/EMS
Strontium-89	pCi/L	1E+01	2E+01	Final PDWS (EPA, 1977)
Strontium-89/90 ^c	pCi/L	4E+00	8E+00	Final PDWS (EPA, 1992a)
Strontium-90	pCi/L	4E+00	8E+00	Final PDWS (EPA, 1992a)
Styrene	µg/L	50	100	Final PDWS (EPA, 1992a)
Sulfate	µg/L	200,000	400,000	Proposed PDWS (EPA, 1990)
Sulfide	µg/L	5,000	10,000	EPA Method 9030
Sulfotep	µg/L	50	100	EPA Method 8270
Surfactants		No flag	No flag	Set by EPD/EMS
2,3,7,8-TCDD	µg/L	0.000015	0.00003	Final PDWS (EPA, 1992b)
2,3,7,8-TCDF	µg/L	0.002	0.004	EPA Method 8280
Technetium-99	pCi/L	4.5E+02	9E+02	Final PDWS (EPA, 1977)
1,2,4,5-Tetrachlorobenzene	µg/L	50	100	EPA Method 8270
Tetrachlorodibenzo-p-dioxin isomers	µg/L	0.00225	0.0045	EPA Method 8280
Tetrachlorodibenzo-p-furan isomers	µg/L	0.002	0.004	EPA Method 8280
1,1,1,2-Tetrachloroethane	µg/L	5	10	EPA Method 8240
1,1,2,2-Tetrachloroethane	µg/L	5	10	EPA Method 8240
Tetrachloroethylene	µg/L	2.5	5	Final PDWS (EPA, 1992a)
2,3,4,6-Tetrachlorophenol	µg/L	50	100	EPA Method 8270
Tetraethyl dithiopyrophosphate	µg/L	50	100	EPA Method 8270
Thallium	µg/L	1	2	Final PDWS (EPA, 1992b)
Thionazin	µg/L	50	100	EPA Method 8270
Thorium-228	pCi/L	6.25E+01	1.25E+02	Proposed PDWS (EPA, 1991)
Thorium-230	pCi/L	3.96E+01	7.92E+01	Proposed PDWS (EPA, 1991)
Thorium-232	pCi/L	4.4E+01	8.8E+01	Proposed PDWS (EPA, 1991)
Thorium-234	pCi/L	2E+02	4.01E+02	Proposed PDWS (EPA, 1991)
Tin	µg/L	10	20	EPA Method 282.2
Tin-113	pCi/L	1.5E+02	3E+02	Final PDWS (EPA, 1977)
Toluene	µg/L	500	1,000	Final PDWS (EPA, 1992a)
o-Toluidine	µg/L	50	100	EPA Method 8270
Total carbon	µg/L	5,000	10,000	EPA Method 9060
Total dissolved solids		No flag	No flag	Set by EPD/EMS
Total hydrocarbons	µg/L	5,000	10,000	EPA Method 418.1
Total inorganic carbon	µg/L	5,000	10,000	EPA Method 9060
Total organic carbon	µg/L	5,000	10,000	EPA Method 9060
Total organic halogens	µg/L	25	50	EPA Method 9020
Total organic nitrogen	µg/L	500	1,000	APHA Method 420
Total petroleum hydrocarbons	µg/L	5,000	10,000	EPA Method 418.1
Total phosphates (as P)		No flag	No flag	Set by EPD/EMS
Total phosphorus		No flag	No flag	Set by EPD/EMS

Analyte	Unit	Flag 1	Flag 2	Source ^a
Toxaphene	µg/L	1.5	3	Final PDWS (EPA, 1992a)
2,4,5-TP (Silvex)	µg/L	25	50	Final PDWS (EPA, 1992a)
Tributyl phosphate	µg/L	50	100	EPA Method 8270
1,2,4-Trichlorobenzene	µg/L	35	70	Final PDWS (EPA, 1992b)
1,1,1-Trichloroethane	µg/L	100	200	Final PDWS (EPA, 1992a)
1,1,2-Trichloroethane	µg/L	2.5	5	Final PDWS (EPA, 1992b)
Trichloroethylene	µg/L	2.5	5	Final PDWS (EPA, 1992a)
Trichlorofluoromethane	µg/L	5	10	EPA Method 8240
2,4,5-Trichlorophenol	µg/L	50	100	EPA Method 8270
2,4,6-Trichlorophenol	µg/L	50	100	EPA Method 8270
2,4,5-Trichlorophenoxyacetic acid	µg/L	2.5	5	EPA Method 8150
1,2,3-Trichloropropane	µg/L	5	10	EPA Method 8240
O,O,O-Triethyl phosphorothioate	µg/L	50	100	EPA Method 8270
1,3,5-Trinitrobenzene	µg/L	50	100	EPA Method 8270
Tritium	pCi/mL	1E+01	2E+01	Final PDWS (EPA, 1992a)
Turbidity		No flag	No flag	Set by EPD/EMS
Uranium	µg/L	10	20	Proposed PDWS (EPA, 1991)
Uranium alpha activity	pCi/L	1.5E+01	3E+01	Proposed PDWS (EPA, 1991)
Uranium-233/234 ^c	pCi/L	6.9E+00	1.38E+01	Proposed PDWS (EPA, 1991)
Uranium-234	pCi/L	6.95E+00	1.39E+01	Proposed PDWS (EPA, 1991)
Uranium-235	pCi/L	7.25E+00	1.45E+01	Proposed PDWS (EPA, 1991)
Uranium-238	pCi/L	7.3E+00	1.46E+01	Proposed PDWS (EPA, 1991)
Vanadium	µg/L	40	80	EPA Method 6010
Vinyl acetate	µg/L	5	10	EPA Method 8240
Xylenes	µg/L	5,000	10,000	Final PDWS (EPA, 1992a)
Zinc	µg/L	2,500	5,000	SDWS (EPA, 1992c)
Zinc-65	pCi/L	1.5E+02	3E+02	Final PDWS (EPA, 1977)
Zirconium-95	pCi/L	1E+02	2E+02	Final PDWS (EPA, 1977)
Zirconium/Niobium-95 ^d	pCi/L	1E+02	2E+02	Final PDWS (EPA, 1977)

^a References for methods are found in Appendix E; references for dated sources are at the end of this appendix.

^b EPD/EMS set this flagging criterion using the 1991 proposed PDWS because the final PDWS in 1977 may have been in error.

^c When radionuclide analyses are combined, the lower PDWS of the two isotopes is used for flagging.

^d The applied standard is for radium-226.

References

EPA (U.S. Environmental Protection Agency), 1977. **National Interim Primary Drinking Water Regulations**, EPA-570/9-76-003. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1986. *Water Pollution Control; National Primary Drinking Water Regulations, Radionuclides (Proposed)*. **Federal Register**, September 30, 1986, pp. 34836-34862. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990. *National Primary and Secondary Drinking Water Regulations; Synthetic Organic Chemicals and Inorganic Chemicals (Proposed Rule)*. **Federal Register**, July 25, 1990, pp. 30369-30448. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991. *National Primary Drinking Water Regulations; Radionuclides; Proposed Rule*. **Federal Register**, July 18, 1991, pp. 33052-33127. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1992a. *National Primary Drinking Water Regulations, Code of Federal Regulations*, Section 40, Part 141, pp. 589-729. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1992b. *National Primary Drinking Water Regulations—Synthetic Organic Chemical and Inorganic Chemicals; National Primary Drinking Water Regulations Implementation. Federal Register*, July 17, 1992, pp. 31776-31849. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1992c. *National Secondary Drinking Water Regulations, Code of Federal Regulations*, Section 40, Part 143, pp. 772-776. Washington, DC.

Appendix C – Figures

Figure 1. Location of the F- and H-Area Sewage Sludge Application Sites at the Savannah River Site

Figure 2. Location of the F- and H-Area Sewage Sludge Application Sites within the General Separations Area

Figure 3. Groundwater Monitoring Well Locations and Piezometric Surface of the Water Table at the F-Area Sewage Sludge Application Site

Figure 4. Groundwater Monitoring Well Locations and Piezometric Surface of the Water Table at the H-Area Sewage Sludge Application Site

THIS PAGE LEFT BLANK INTENTIONALLY.

Appendix D – Groundwater Monitoring Results Tables

Key to Reading the Tables

The following abbreviations may appear in the data tables:

Constituents

1,2,3,4,6,7,8-HPCDD	1,2,3,4,6,7,8-heptachlorodibenzo-p-dioxin
1,2,3,4,6,7,8-HPCDF	1,2,3,4,6,7,8-heptachlorodibenzo-p-furan
1,2,3,4,7,8-HXCDD	1,2,3,4,7,8-hexachlorodibenzo-p-dioxin
1,2,3,4,7,8-HXCDF	1,2,3,4,7,8-hexachlorodibenzo-p-furan
Lindane	gamma-benzene hexachloride
PCB	polychlorinated biphenyl
1,2,3,7,8-PCDD	1,2,3,7,8-pentachlorodibenzo-p-dioxin
1,2,3,7,8-PCDF	1,2,3,7,8-pentachlorodibenzo-p-furan
Sp. conductance	specific conductance
TCDD	tetrachlorodibenzo-p-dioxin
TCDF	tetrachlorodibenzo-p-furan

Laboratories

CN	Clemson Technical Center, Inc.
EM	Environmental Protection Department/ Environmental Monitoring Section (EPD/EMS) Laboratory
GE and GP	General Engineering Laboratories
SC	Savannah River Technology Center
SP	Spencer Testing Services, Inc.
TM	TMA/Eberline
WA and WS	Roy F. Weston, Inc.

Sampling Codes

B	blank sample was collected
C	well was pumping continuously
D	well was dry
E	equipment blank was collected
I	well went dry during sampling; insufficient water to collect all samples
L	well went dry before sampling began; only depth to water can be determined
P	inaccessibility or mechanical failure prevented sample collection and field analysis of the water
S	no water in standpipe; for water level events only
X	well went dry during purging; samples collected after well recovered

Sampling Methods

B	sample collected using an open bucket bailer
P	sample collected using a bladder pump
S	sample collected using a single-speed centrifugal downhole pump
V	sample collected using a variable-speed pump

Units

E	exponential notation (e.g., $1.1E-09 = 1.1 \times 10^{-9} = 0.0000000011$)
mg/L	milligrams per liter
msl	mean sea level
MSL	million structures per liter
NTU	turbidity unit
pCi/L	picocuries per liter
pCi/mL	picocuries per milliliter
pH	pH unit
$\mu\text{g/L}$	micrograms per liter
$\mu\text{S/cm}$	microsiemens per centimeter

Other

CS	carbon steel
D	primary drinking water standard (PDWS) column in data tables
GP	groundwater protection standard column in data tables
H	holding time column in data tables
Mod	modifier column in data tables
PDWS	primary drinking water standard
PVC	polyvinyl chloride
TOC	top of casing

Holding Times

Standard analytical methods include a limit, called holding time, on the maximum elapsed time between sample collection and extraction or analysis by the laboratory. In the data tables, a large bullet (●) in the *H* (holding time) column indicates that holding time was exceeded. Analyses performed beyond holding time may not yield valid results.

The South Carolina Department of Health and Environmental Control allows only 15 minutes to elapse between sampling and analysis for pH. Thus, only field pH measurements can meet the holding time criterion; laboratory pH analyses always will exceed it.

The laboratory procedure used for the determination of specific conductance allows one day to elapse between sampling and analysis. Thus, laboratory specific conductance measurements may exceed the holding time criterion.

Data Rounding

Constituent results in analytical results tables that appear to equal the final PDWS but are not marked in the *D* (exceeded the final PDWS or screening level) column are below the final PDWS in the database. Values stored in the database contain more significant digits than the reported results. Apparent discrepancies in the tables are due to the rounding of reported results.

Data Qualification

The contract laboratories continually assess their own accuracy and precision according to U.S. Environmental Protection Agency (EPA) guidelines. They submit sample- or batch-specific quality assurance/quality control information either at the same time as analytical results or in a quarterly summary. Properly defined and used result modifiers (also referred to as qualifiers) can be a key component in assessing data useability. Result modifiers designed by Environmental Protection Department/Environmental Monitoring Section and provided to the primary laboratories are defined below. These modifiers appear in the data tables under the column "Mod." The lettered modifiers are based on EPA's STORET codes.

<u>Result modifier</u>	<u>Definition</u>
(Blank)	Data are not qualified. Number should be interpreted exactly as reported.
A	Value reported is the mean of two or more determinations.
J	Value is estimated because quantitation in the sample or in associated quality control samples did not meet specifications.
L	Value is off-scale high. The actual value is not known but is known to be greater than the value shown.
M	Presence of the analyte is verified but not quantified.
R	Result was rejected because performance requirements in the sample analysis or associated quality control analyses were not met.
T	Analyte was not detected; if present, it was below the criteria for detection.
V	Analyte was detected in an associated method blank.
Y	Result was obtained from an unpreserved or improperly preserved sample. Data may not be accurate.
1	Result may be an underestimation of the true value due to analytical bias.
2	Result may be an overestimation of the true value due to analytical bias.
3	The associated result may be of poor precision (high variability) due to analytical bias.
4	Result is associated with QA results indicating matrix interference.
6	The associated result is from a reanalysis performed out of holding time due to problems with an earlier analysis.

Table 1. Maximum Levels of Constituents Exceeding the Final Primary Drinking Water Standards at the F-Area Sewage Sludge Application Site

<u>Well</u>	<u>Constituent</u>	<u>Unit</u>	<u>1Q93</u>	<u>2Q93</u>	<u>3Q93</u>	<u>4Q93</u>	<u>Mod</u>
FSS 1D	Lead	µg/L	83	NA ^a	58	NA	
FSS 2D	Tritium	pCi/mL	8.5E+01	NA	7.7E+01	NA	
FSS 3D	Lead	µg/L	327	NA	329	NA	
	Tritium	pCi/mL	4.5E+01	NA	4.3E+01	NA	

^a NA = not analyzed.

Table 2. Maximum Levels of Constituents Exceeding Other Flag 2 Criteria at the F-Area Sewage Sludge Application Site

<u>Well</u>	<u>Constituent</u>	<u>Unit</u>	<u>4Q93</u>	<u>Mod</u>
N ^a	None	N	N	N

^a N = not applicable.

Notes: These results do not include field data.

Flags are established by EPD/EMS and are based on PDWS, Secondary Drinking Water Standards, or method detection limits (see Appendix B).

Table 3. Maximum Levels of Constituents Exceeding the Final Primary Drinking Water Standards at the H-Area Sewage Sludge Application Site

<u>Well</u>	<u>Constituent</u>	<u>Unit</u>	<u>1Q93</u>	<u>2Q93</u>	<u>3Q93</u>	<u>4Q93</u>	<u>Mod</u>
HSS 1D	Lead	µg/L	- ^a	NA ^b	74	NA	

^a - = analyzed but not above final PDWS.

^b NA = not analyzed.

Table 4. Maximum Levels of Constituents Exceeding Other Flag 2 Criteria at the H-Area Sewage Sludge Application Site

<u>Well</u>	<u>Constituent</u>	<u>Unit</u>	<u>4Q93</u>	<u>Mod</u>
N ^a	None	N	N	N

^a N = not applicable.

Notes: These results do not include field data.

Flags are established by EPD/EMS and are based on PDWS, Secondary Drinking Water Standards, or method detection limits (see Appendix B).

Table 5. Groundwater Monitoring Results for Individual Wells at the F-Area Sewage Sludge Application Site

WELL FSS 1D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N75257.6	33.280181 °N	229.9-209.9 ft msl	266 ft msl	4" PVC	S	Water table
E53897.6	81.671063 °W					

SAMPLE DATE	02/19/93	05/13/93	07/02/93	10/24/93
-------------	----------	----------	----------	----------

FIELD DATA

Analyte	1Q93	2Q93	3Q93	4Q93	Unit
Water elevation	225.6	227.1	226.3	224.5	ft msl
Depth to water	40.4	38.9	39.7	41.5	ft
pH	6.1	5.9	5.8	6.0	pH
Sp. conductance	74	88	102	84	µS/cm
Water temperature	19.0	20.0	20.8	19.3	°C
Alkalinity as CaCO ₃	25	25	28	32	mg/L
Turbidity	129	75	40	110	NTU
Volume purged	0.9	0.6	0.7	1.0	Well vol.
Sampling code	X	X	X	X	

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Aluminum, total recoverable	2,690		1,390			µg/L		
		Arsenic, total recoverable	< 2.0					µg/L		
		Barium, total recoverable	14					µg/L		
		Cadmium, total recoverable	2.6		< 2.0			µg/L		
		Calcium, total recoverable	13,100					µg/L		
		Carbon tetrachloride		< 1.0				µg/L		
		Chloride	3,710	3,440	2,010	3,000		µg/L	WA	0
		Chloroform		< 1.0				µg/L		
		Chromium, total recoverable	18					µg/L		
		Copper, total recoverable	434					µg/L		
		2,4-Dichlorophenoxyacetic acid	< 1.1					µg/L		
		Endrin	< 0.11					µg/L		
		Fluoride	< 100					µg/L		
		Gross alpha	2.2E + 00					pCi/L		
		Iron, total recoverable	4,120		848			µg/L		
		Lead, total recoverable	83		58			µg/L		
		Lindane	< 0.053					µg/L		
		Lithium, total recoverable			5.3			µg/L		
		Magnesium, total recoverable	420					µg/L		
		Manganese, total recoverable	73		39			µg/L		
		Mercury, total recoverable	< 0.20		< 0.20			µg/L		
		Methoxychlor	< 0.53					µg/L		
		Nickel, total recoverable	24					µg/L		
		Nitrate as nitrogen	113	342	229	365		µg/L	WA	0
		Nitrite as nitrogen	29	< 10	68	< 10		µg/L	WA	0
		Nonvolatile beta	4.4E + 00					pCi/L		
		pH	6.7	6.2	6.3	6.2	J	pH	WA	0
		Phenols	< 5.0					µg/L		
		Potassium, total recoverable	< 500					µg/L		
		Radium-226	2.6E-01					pCi/L		
		Radium-228	1.0E + 00					pCi/L		
		Selenium, total recoverable	< 2.0					µg/L		
		Silica, total recoverable	6,470					µg/L		
		Silver, total recoverable	< 2.0					µg/L		
		Sodium, total recoverable	2,060	3,170	2,390	2,550	V	µg/L	WA	0
		Specific conductance	90	94	95	84		µS/cm	WA	0
		Sulfate	1,640					µg/L		
		Tetrachloroethylene		< 1.0				µg/L		
		Total dissolved solids	71,000	60,000	92,000	78,000		µg/L	WA	0
		Total organic carbon	< 1,000					µg/L		

Note: Flagging levels, modifiers, and laboratories are for fourth quarter 1993 data only. See Appendix B for flagging criteria.

● = exceeded holding time for fourth quarter 1993.

■ = exceeded screening level or final primary drinking water standard for fourth quarter 1993.

Well FSS 1D continued

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Total organic halogens	6.8					µg/L		
		Total phosphates (as P)	193					µg/L		
		Toxaphene	<1.1					µg/L		
		2,4,6-TP (Silvex)	<0.53					µg/L		
		1,1,1-Trichloroethane		<1.0				µg/L		
		Trichloroethylene		<1.0				µg/L		
		Tritium	1.1E+01		1.2E+01			pCi/mL		

WELL FSS 2D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N75103.5 E53918.9	33.279855 °N 81.670708 °W	224.4-204.4 ft msl	261.6 ft msl	4" PVC	S	Water table

SAMPLE DATE 02/19/93 05/13/93 07/02/93 10/24/93

FIELD DATA

Analyte	1Q93	2Q93	3Q93	4Q93	Unit
Water elevation	225.1	226.8	225.7	223.8	ft msl
Depth to water	36.5	34.9	35.9	37.8	ft
pH	7.6	7.0	6.1	5.5	pH
Sp. conductance	184	186	143	66	µS/cm
Water temperature	18.9	19.6	20.8	19.4	°C
Alkalinity as CaCO ₃	67	51	26	9	mg/L
Turbidity	98	51	45	76	NTU
Volume purged	1.0	1.1	1.1	0.9	Well vol.
Sampling code	X	X	X	X	

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Aluminum, total recoverable	518		400			µg/L		
		Arsenic, total recoverable	<2.0					µg/L		
		Barium, total recoverable	55					µg/L		
		Cadmium, total recoverable	<2.0		<2.0			µg/L		
		Calcium, total recoverable	17,300					µg/L		
		Carbon tetrachloride		<1.0				µg/L		
		Chloride	3,900	4,310	3,900	3,040		µg/L	WA	0
		Chloroform		<1.0				µg/L		
		Chromium, total recoverable	<4.0					µg/L		
		Copper, total recoverable	4.7					µg/L		
		2,4-Dichlorophenoxyacetic acid	<1.1					µg/L		
		Endrin	<0.11					µg/L		
		Fluoride	<100					µg/L		
		Gross alpha	1.7E+00					pCi/L		
		Iron, total recoverable	1,650		1,340			µg/L		
		Lead, total recoverable	7.1		4.8			µg/L		
		Lindane	<0.058					µg/L		
		Lithium, total recoverable			8.2			µg/L		
		Magnesium, total recoverable	520					µg/L		
		Manganese, total recoverable	31		48			µg/L		
		Mercury, total recoverable	<0.20		<0.20			µg/L		
		Methoxychlor	<0.58					µg/L		
		Nickel, total recoverable	<4.0					µg/L		
		Nitrate as nitrogen	499	492	652	605		µg/L	WA	0
		Nitrite as nitrogen	17	<10	<10	<10		µg/L	WA	0
		Nonvolatile beta	5.8E+00					pCi/L		
		pH	7.2	6.9	6.5	5.6	J	pH	WA	0
		Phenols	<5.0					µg/L		

Note: Flagging levels, modifiers, and laboratories are for fourth quarter 1993 data only. See Appendix B for flagging criteria.

● = exceeded holding time for fourth quarter 1993.

■ = exceeded screening level or final primary drinking water standard for fourth quarter 1993.

Well FSS 2D continued

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Potassium, total recoverable	795					µg/L		
		Radium-226	1.5E+00					pCi/L		
		Radium-228	1.8E+00					pCi/L		
		Selenium, total recoverable	< 2.0					µg/L		
		Silica, total recoverable	3,610					µg/L		
		Silver, total recoverable	< 2.0					µg/L		
		Sodium, total recoverable	3,640	4,240	4,480	4,630	V	µg/L	WA	0
		Specific conductance	144	185	125	55		µS/cm	WA	0
		Sulfate	11,600					µg/L		
		Tetrachloroethylene		< 1.0				µg/L		
		Total dissolved solids	3,000	123,000	87,000	6,000		µg/L	WA	0
		Total organic carbon	< 1,000					µg/L		
		Total organic halogens	< 5.0					µg/L		
		Total phosphates (as P)	97					µg/L		
		Toxaphene	< 1.1					µg/L		
		2,4,5-TP (Silvex)	< 0.58					µg/L		
		1,1,1-Trichloroethane		< 1.0				µg/L		
		Trichloroethylene		< 1.0				µg/L		
		Tritium	8.6E+01		7.7E+01			pCi/mL		

WELL FSS 3D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N74960.5	33.278933 °N	225.8-205.8 ft msl	258.2 ft msl	4" PVC	S	Water table
E53548.0	81.671406 °W					

SAMPLE DATE 02/19/93 05/13/93 07/02/93 10/24/93

FIELD DATA

Analyte	1Q93	2Q93	3Q93	4Q93	Unit
Water elevation	222.9	224.4	223.5	221.5	ft msl
Depth to water	35.3	33.8	34.8	36.7	ft
pH	5.4	4.9	4.7	5.0	pH
Sp. conductance	55	67	78	67	µS/cm
Water temperature	18.4	19.7	20.1	19.5	°C
Alkalinity as CaCO ₃	1	0	1	1	mg/L
Turbidity	17	5	20	9	NTU
Volume purged	0.9	0.8	0.8	1.0	Well vol.
Sampling code	X	X	X	X	

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Aluminum, total recoverable	584		949			µg/L		
		Arsenic, total recoverable	< 2.0					µg/L		
		Barium, total recoverable	17					µg/L		
		Cadmium, total recoverable	< 2.0		< 2.0			µg/L		
		Calcium, total recoverable	719					µg/L		
		Carbon tetrachloride		< 1.0				µg/L		
		Chloride	3,990	3,880	3,280	3,600		µg/L	WA	0
		Chloroform		< 1.0				µg/L		
		Chromium, total recoverable	4.5					µg/L		
		Copper, total recoverable	140					µg/L		
		2,4-Dichlorophenoxyacetic acid	< 1.1					µg/L		
		Endrin	< 0.11					µg/L		
		Fluoride	< 100					µg/L		
		Gross alpha	2.6E+00					pCi/L		
		Iron, total recoverable	961		1,630			µg/L		
		Lead, total recoverable	327		329			µg/L		

Note: Flagging levels, modifiers, and laboratories are for fourth quarter 1993 data only. See Appendix B for flagging criteria.

● = exceeded holding time for fourth quarter 1993.

■ = exceeded screening level or final primary drinking water standard for fourth quarter 1993.

Well FSS 3D continued

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Lindane	<0.058					µg/L		
		Lithium, total recoverable			<5.0			µg/L		
		Magnesium, total recoverable	545					µg/L		
		Manganese, total recoverable	54		93			µg/L		
		Mercury, total recoverable	<0.20		<0.20			µg/L		
		Methoxychlor	<0.58					µg/L		
		Nickel, total recoverable	4.7					µg/L		
		Nitrate as nitrogen	519	642	672	740		µg/L	WA	0
		Nitrite as nitrogen	17	<10	<10	<10		µg/L	WA	0
		Nonvolatile beta	1.5E+00					pCi/L		
•		pH	5.6	6.3	5.3	5.2	J	pH	WA	0
		Phenols	<5.0					µg/L		
		Potassium, total recoverable	700					µg/L		
		Radium-226	8.0E-01					pCi/L		
		Radium-228	0.0E-01					pCi/L		
		Selenium, total recoverable	<2.0					µg/L		
		Silica, total recoverable	4,500					µg/L		
		Silver, total recoverable	<2.0					µg/L		
		Sodium, total recoverable	3,850	4,890	5,780	6,460	V	µg/L	WA	0
		Specific conductance	43	62	56	53		µS/cm	WA	0
		Sulfate	9,740					µg/L		
		Tetrachloroethylene		<1.0				µg/L		
		Total dissolved solids	6,000	67,000	59,000	43,000		µg/L	WA	0
		Total organic carbon	<1,000					µg/L		
		Total organic halogens	<5.0					µg/L		
		Total phosphates (as P)	<50					µg/L		
		Toxaphene	<1.1					µg/L		
		2,4,5-TP (Silvex)	<0.58					µg/L		
		1,1,1-Trichloroethane		<1.0				µg/L		
		Trichloroethylene		<1.0				µg/L		
		Tritium	4.5E+01		4.3E+01			pCi/mL		

WELL FSS 4D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N75537.8 E52876.1	33.279114 °N 81.674297 °W	222.6-202.6 ft msl	291.8 ft msl	4" PVC	S	Water table

SAMPLE DATE 02/19/93 05/13/93 07/02/93 10/24/93

FIELD DATA

Analyte	1Q93	2Q93	3Q93	4Q93	Unit
Water elevation	220.8	222.3	222.0	220.9	ft msl
Depth to water	71.0	69.5	69.8	70.9	ft
pH	5.1	4.9	4.8	4.9	pH
Sp. conductance	47	51	51	48	µS/cm
Water temperature	17.3	19.7	20.7	19.5	°C
Alkalinity as CaCO ₃	0	0	0	0	mg/L
Turbidity	30	38	18	24	NTU
Volume purged	1.2	1.1	1.1	1.1	Well vol.
Sampling code	X	X	X	X	

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Aluminum, total recoverable	231		254			µg/L		
		Arsenic, total recoverable	<2.0					µg/L		
		Barium, total recoverable	7.8					µg/L		
		Cadmium, total recoverable	<2.0		<2.0			µg/L		

Note: Flagging levels, modifiers, and laboratories are for fourth quarter 1993 data only. See Appendix B for flagging criteria.

• = exceeded holding time for fourth quarter 1993.

■ = exceeded screening level or final primary drinking water standard for fourth quarter 1993.

Well FSS 4D continued

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Calcium, total recoverable	879					µg/L		
		Chloride	4,780	4,040	3,270	4,710		µg/L	WA	0
		Chromium, total recoverable	<4.0					µg/L		
		Copper, total recoverable	<4.0					µg/L		
		2,4-Dichlorophenoxyacetic acid	<1.1					µg/L		
		Endrin	<0.12					µg/L		
		Fluoride	<100					µg/L		
		Gross alpha	1.7E+00					pCi/L		
		Iron, total recoverable	534		402			µg/L		
		Lead, total recoverable	4.5		<3.0			µg/L		
		Lindane	<0.058					µg/L		
		Lithium, total recoverable			<5.0			µg/L		
		Magnesium, total recoverable	462					µg/L		
		Manganese, total recoverable	15		23			µg/L		
		Mercury, total recoverable	<0.20		<0.20			µg/L		
		Methoxychlor	<0.58					µg/L		
		Nickel, total recoverable	<4.0					µg/L		
		Nitrate as nitrogen	1,880	2,020	1,930	3,100		µg/L	WA	0
		Nitrite as nitrogen	<10	<10	<10	<10		µg/L	WA	0
		Nonvolatile beta	1.6E+00					pCi/L		
•		pH	5.1	5.4	5.0	5.1	J	pH	WA	0
		Phenols	7.9					µg/L		
		Potassium, total recoverable	<500					µg/L		
		Radium-226	<2.3E-01					pCi/L		
		Radium-228	9.0E-01					pCi/L		
		Selenium, total recoverable	<2.0					µg/L		
		Silica, total recoverable	5,120					µg/L		
		Silver, total recoverable	<2.0					µg/L		
		Sodium, total recoverable	2,790	3,390	3,730	4,310	V	µg/L	WA	0
		Specific conductance	48	47	25	39		µS/cm	WA	0
		Sulfate	<1,000					µg/L		
		Total dissolved solids	30,000	43,000	94,000	48,000		µg/L	WA	0
		Total organic carbon	<1,000					µg/L		
		Total organic halogens	<5.0					µg/L		
		Total phosphates (as P)	145					µg/L		
		Toxaphene	<1.2					µg/L		
		2,4,5-TP (Silvex)	<0.56					µg/L		
		Tritium	5.7E+00		5.5E+00			pCi/mL		

Note: Flagging levels, modifiers, and laboratories are for fourth quarter 1993 data only. See Appendix B for flagging criteria.

• = exceeded holding time for fourth quarter 1993.

■ = exceeded screening level or final primary drinking water standard for fourth quarter 1993.

Table 6. Groundwater Monitoring Results for Individual Wells at the H-Area Sewage Sludge Application Site

WELL HSS 1D

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Pump</u>	<u>Screen Zone</u>
N87610.3	33.280828 °N	256.5-236.5 ft msl	310.1 ft msl	4" PVC	S	Water table
E64875.6	81.627829 °W					

SAMPLE DATE	02/19/93	05/16/93	07/02/93	10/24/93
-------------	----------	----------	----------	----------

FIELD DATA

Analyte	1Q93	2Q93	3Q93	4Q93	Unit
Water elevation	274.3	276.1	272.0	287.5	ft msl
Depth to water	35.8	35.0	38.1	42.6	ft
pH	6.2	5.5	5.2	5.3	pH
Sp. conductance	35	36	30	26	µS/cm
Water temperature	16.8	21.5	19.2	18.5	°C
Alkalinity as CaCO ₃	5	4	1	1	mg/L
Turbidity	2	2	71	5	NTU
Volume purged	0.9	0.9	0.9	1.1	Well vol.
Sampling code	X	X	X	X	

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Aluminum, total recoverable	44		694			µg/L		
		Arsenic, total recoverable	< 2.0					µg/L		
		Barium, total recoverable	47					µg/L		
		Cadmium, total recoverable	< 2.0					µg/L		
		Calcium, total recoverable	2,630					µg/L		
		Chloride	1,750	2,310	1,590	1,890		µg/L	WA	0
		Chromium, total recoverable	< 4.0					µg/L		
		Copper, total recoverable	33					µg/L		
		2,4-Dichlorophenoxyacetic acid	< 1.1					µg/L		
		Endrin	< 0.11					µg/L		
		Fluoride	< 100					µg/L		
		Gross alpha	7.0E-01					pCi/L		
		Iron, total recoverable	62		854			µg/L		
		Lead, total recoverable	4.7		74			µg/L		
		Lindane	< 0.056					µg/L		
		Magnesium, total recoverable	502					µg/L		
		Manganese, total recoverable	5.4					µg/L		
		Mercury, total recoverable	< 0.20					µg/L		
		Methoxychlor	< 0.56					µg/L		
		Nickel, total recoverable	6.2					µg/L		
		Nitrate as nitrogen	774	1,090	1,140	1,570		µg/L	WA	0
		Nitrite as nitrogen	21	< 10	< 10	< 10		µg/L	WA	0
		Nonvolatile beta	2.4E+00					pCi/L		
		pH	5.8	5.6	5.6	5.4	J	pH	WA	0
		Phenols	< 5.0					µg/L		
		Potassium, total recoverable	1,510					µg/L		
		Radium-226	< 2.9E-01					pCi/L		
		Radium-228	4.0E-01					pCi/L		
		Selenium, total recoverable	< 2.0					µg/L		
		Silica, total recoverable	10,100					µg/L		
		Silver, total recoverable	< 2.0					µg/L		
		Sodium, total recoverable	1,700	1,650	1,600	1,620	V	µg/L	WA	0
		Specific conductance	33	28	24	22		µS/cm	WA	0
		Sulfate	< 1,000					µg/L		
		Total dissolved solids	24,000	36,000	62,000	36,000		µg/L	WA	0
		Total organic carbon	< 1,000					µg/L		
		Total organic halogens	< 5.0					µg/L		
		Total phosphates (as P)	< 50					µg/L		
		Toxaphene	< 1.1					µg/L		
		2,4,5-TP (Silvex)	< 0.56					µg/L		
		Tritium	< 5.0E-01					pCi/mL		

Note: Flagging levels, modifiers, and laboratories are for fourth quarter 1993 data only. See Appendix B for flagging criteria.

• = exceeded holding time for fourth quarter 1993.

■ = exceeded screening level or final primary drinking water standard for fourth quarter 1993.

WELL HSS 2D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N67355.9 E64785.9	33.280445 °N 81.627045 °W	254.5-234.5 ft msl	304.4 ft msl	4" PVC	S	Water table

SAMPLE DATE	02/19/93	05/16/93	07/01/93	10/24/93
-------------	----------	----------	----------	----------

FIELD DATA

Analyte	1Q93	2Q93	3Q93	4Q93	Unit
Water elevation	273.2	274.1	270.9	266.5	ft msl
Depth to water	31.2	30.3	33.5	37.9	ft
pH	5.5	4.9	5.0	4.9	pH
Sp. conductance	27	28	32	27	µS/cm
Water temperature	18.0	19.2	19.0	18.7	°C
Alkalinity as CaCO ₃	1	1	1	1	mg/L
Turbidity	1	1	0	1	NTU
Volume purged	4.1	3.4	3.8	3.1	Well vol.
Sampling code					

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Aluminum, total recoverable	28		43			µg/L		
		Arsenic, total recoverable	< 2.0					µg/L		
		Barium, total recoverable	26					µg/L		
		Cadmium, total recoverable	< 2.0					µg/L		
		Calcium, total recoverable	948					µg/L		
		Chloride	2,400	2,540	2,120	2,090		µg/L	WA	0
		Chromium, total recoverable	< 4.0					µg/L		
		Copper, total recoverable	< 4.0					µg/L		
		2,4-Dichlorophenoxyacetic acid	< 0.30					µg/L		
		Endrin	< 0.0060					µg/L		
		Fluoride	< 100					µg/L		
		Gross alpha	1.1E+00					pCi/L		
		Iron, total recoverable	36		9.9			µg/L		
		Lead, total recoverable	< 3.0		3.4			µg/L		
		Lindane	< 0.0050					µg/L		
		Magnesium, total recoverable	505					µg/L		
		Manganese, total recoverable	8.3					µg/L		
		Mercury, total recoverable	< 0.20					µg/L		
		Methoxychlor	< 0.50					µg/L		
		Nickel, total recoverable	4.3					µg/L		
		Nitrate as nitrogen	1,040	1,270	1,120	1,540		µg/L	WA	0
		Nitrate-nitrite as nitrogen	1,100		1,190			µg/L		
		Nitrite as nitrogen	< 10	< 10	< 10	< 10		µg/L	WA	0
		Nonvolatile beta	2.5E+00					pCi/L		
•		pH	5.6	5.1	6.1	5.4	J	pH	WA	0
		Phenols	< 5.0					µg/L		
		Potassium, total recoverable	1,380					µg/L		
		Radium-226	< 2.5E-01					pCi/L		
		Radium-228	2.9E+00					pCi/L		
		Radium, total alpha-emitting	1.7E+00					pCi/L		
		Selenium, total recoverable	< 2.0					µg/L		
		Silica, total recoverable	21,700					µg/L		
		Silver, total recoverable	< 2.0					µg/L		
		Sodium, total recoverable	2,010	2,000	1,810	1,810	V	µg/L	WA	0

Note: Flagging levels, modifiers, and laboratories are for fourth quarter 1993 data only. See Appendix B for flagging criteria.

• = exceeded holding time for fourth quarter 1993.

■ = exceeded screening level or final primary drinking water standard for fourth quarter 1993.

Well HSS 2D continued

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Specific conductance	29	28	25	23		µS/cm	WA	0
		Sulfate	<1,000					µg/L		
		Total dissolved solids	39,000	72,000	65,000	55,000		µg/L	WA	0
		Total organic carbon	1,240					µg/L		
		Total organic halogens	<5.0					µg/L		
		Total phosphates (as P)	<50					µg/L		
		Toxaphene	<0.24					µg/L		
		2,4,6-TP (Silvex)	<0.090					µg/L		
		Tritium	3.1E+00					pCi/mL		

WELL HSS 3D

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Pump	Screen Zone
N68257.5 E64709.5	33.282315 °N 81.628996 °W	282.6-282.6 ft msl	309.8 ft msl	4" PVC	S	Water table

SAMPLE DATE 02/19/93 05/16/93 07/02/93 10/24/93

FIELD DATA

Analyte	1Q93	2Q93	3Q93	4Q93	Unit
Water elevation	286.9	287.7	285.3	281.2	ft msl
Depth to water	22.9	22.1	24.5	28.6	ft
pH	4.8	4.5	4.3	4.5	pH
Sp. conductance	28	33	32	30	µS/cm
Water temperature	17.3	22.1	19.8	19.3	°C
Alkalinity as CaCO ₃	0	0	0	0	mg/L
Turbidity	51	38	57	114	NTU
Volume purged	1.4	1.5	1.3	1.3	Well vol.
Sampling code	X	X	X	X	

ANALYTICAL DATA

H	D	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Aluminum, total recoverable	162		173			µg/L		
		Arsenic, total recoverable	<2.0					µg/L		
		Barium, total recoverable	5.8					µg/L		
		Cadmium, total recoverable	<2.0					µg/L		
		Calcium, total recoverable	166					µg/L		
		Chloride	3,540	3,430	2,480	4,320		µg/L	WA	0
		Chromium, total recoverable	<4.0					µg/L		
		Copper, total recoverable	9.6					µg/L		
		2,4-Dichlorophenoxyacetic acid	<1.1					µg/L		
		Endrin	<0.11					µg/L		
		Fluoride	<100					µg/L		
		Gross alpha	1.0E+00					pCi/L		
		Iron, total recoverable	950		558			µg/L		
		Lead, total recoverable	12		10			µg/L		
		Lindane	<0.056					µg/L		
		Magnesium, total recoverable	149					µg/L		
		Manganese, total recoverable	4.5					µg/L		
		Mercury, total recoverable	<0.20					µg/L		
		Methoxychlor	<0.56					µg/L		
		Nickel, total recoverable	<4.0					µg/L		
		Nitrate as nitrogen	715	1,050	962	1,500		µg/L	WA	0
		Nitrite as nitrogen	<10	<10	20	<10		µg/L	WA	0
		Nonvolatile beta	3.3E+00					pCi/L		
		pH	4.7	4.6	4.7	4.8	J	pH	WA	0
		Phenols	<5.0					µg/L		
		Potassium, total recoverable	<500					µg/L		

Note: Flagging levels, modifiers, and laboratories are for fourth quarter 1993 data only. See Appendix B for flagging criteria.

● = exceeded holding time for fourth quarter 1993.

■ = exceeded screening level or final primary drinking water standard for fourth quarter 1993.

Well H88 3D continued

ANALYTICAL DATA

H	Q	Analyte	1Q93	2Q93	3Q93	4Q93	Mod	Unit	Lab	Flag
		Radium-226	2.4E-01					pCi/L		
		Radium-228	1.5E+00					pCi/L		
		Selenium, total recoverable	<2.0					µg/L		
		Silica, total recoverable	3.150					µg/L		
		Silver, total recoverable	<2.0					µg/L		
		Sodium, total recoverable	1,820	2,020	2,750	2,750	V	µg/L	WA	0
		Specific conductance	25	27	25	28		µS/cm	WA	0
		Sulfate	<1,000					µg/L		
		Total dissolved solids	14,000	23,000	54,000	42,000		µg/L	WA	0
		Total organic carbon	<1,000					µg/L		
		Total organic halogens	<5.0					µg/L		
		Total phosphates (as P)	<50					µg/L		
		Toxaphene	<1.1					µg/L		
		2,4,5-TP (Silvex)	<0.57					µg/L		
		Tritium	5.6E+00					pCi/mL		

Note: Flagging levels, modifiers, and laboratories are for fourth quarter 1993 data only. See Appendix B for flagging criteria.

● = exceeded holding time for fourth quarter 1993.

■ = exceeded screening level or final primary drinking water standard for fourth quarter 1993.

THIS PAGE LEFT BLANK INTENTIONALLY.

Appendix E – Data Quality/Useability Assessment

Data Quality/Useability Assessment

Quality assurance/quality control (QA/QC) procedures relating to accuracy and precision of analyses performed on groundwater samples are followed in the field and laboratory and are reviewed prior to publication of results. The Environmental Protection Department/Environmental Monitoring Section's (EPD/EMS) review of the volume of analytical data acquired each quarter and presented in various reports is an ongoing process; its review of the QA/QC data cannot be completed in time to meet the deadlines for the reports required by the Resource Conservation and Recovery Act and associated regulations. Other site and regulatory personnel can obtain further information on the data quality and useability in a variety of ways, including those described below.

Data Qualification

The contract laboratories continually assess their own accuracy and precision according to U.S. Environmental Protection Agency (EPA) guidelines. They submit sample- or batch-specific QA/QC information either at the same time as analytical results or in a quarterly summary. Properly defined and used result modifiers (also referred to as qualifiers) can be a key component in assessing data useability. Result modifiers designed by EPD/EMS and used by the primary laboratories are presented in Appendix D.

Assessment of Accuracy of the Data

Accuracy, or the nearness of the reported result to the true concentration of a constituent in a sample, can be assessed in several ways.

A laboratory's general accuracy can be judged by analysis of results obtained from known samples. The non-radionuclide contract laboratories analyze commercial reference samples every quarter at EPD/EMS' request. The results of these analyses are presented in the EPD/EMS quarterly report, *The Savannah River Site's Groundwater Monitoring Program*. The primary laboratories also seek or maintain state certification by participating periodically in performance studies; reference samples and analysis of results are provided by EPA. Results of these studies also are published in the EPD/EMS quarterly reports.

Analysis of blanks provides a tool for assessing the accuracy of both sampling and laboratory analysis. Results for all field blanks for the quarter can be found in the EPD/EMS quarterly reports. Any field or laboratory blanks that exceeded established minimums are identified in the same reports, in tables associating them with groundwater samples analyzed in the same batches.

Surrogates, organic compounds similar in chemical behavior to the compounds of interest but not normally found in environmental samples, are used to monitor the effect of the matrix on the accuracy of analyses for organic parameters. For example, for analyses of volatile organics by EPA Method 8240, three surrogate compounds are added to all samples

and blanks in each analytical batch. In analyses of semivolatile organics, three to four acid compounds and three to four base/neutral compounds are used. Other surrogates are used in pesticides analyses. Percent recoveries for surrogate analyses are calculated by laboratory personnel, reported to EPD/EMS, reviewed, and entered into the database, but they are not published. If recoveries are not within specified limits, the laboratory is expected to re-run the samples or attach result qualifiers to the data identifying the anomalous results.

Sample-specific accuracy for both organic and inorganic parameters can be assessed by examination of matrix spike/matrix spike duplicate results. A sample is analyzed unspiked to determine a baseline set of values. A second portion of sample is spiked with known concentrations of compounds appropriate to the analyses being performed, typically 5 volatile organic compounds for volatile organics analyses, 11 semivolatile compounds for semivolatiles, 6 pesticide compounds for pesticides, all metals for metals analyses, and a known quantity of cyanide for cyanide analysis. The percentage of the spike compound that is recovered (i.e., measured in excess of the value obtained for the unspiked sample) is a direct measure of analytical accuracy. EPA requires matrix spike/matrix spike duplicates to be run at least once per 20 samples of similar matrix.

Matrix spike/matrix spike duplicate results are reported to EPD/EMS but are not published. For organic compounds, according to EPA guidelines, no action is taken on the basis of matrix spike/matrix spike duplicate data alone (i.e., no result modifiers are assigned solely on the basis of matrix spike results); however, the results can indicate if a lab is having a systematic problem in the analysis of one or more analytes.

In the case of inorganic compounds, such as metals, the matrix spike sample analysis provides information about the effect of each sample matrix on the digestion and measurement methodology. Data qualifiers can be assigned on the basis of the percentage of spike recovery and are reported in the published results tables.

Assessment of Precision

Precision of the analyses, or agreement of a set of replicate results among themselves, is assessed through the use of duplicates (laboratory-initiated) and blind replicates (provided by EPD/EMS). The results of duplicate and replicate analyses are presented in the results tables of the first, second, and third quarter reports. Duplicate and replicate results are not presented in fourth quarter reports; the results tables present instead only the highest result for each analyte for each quarter of the year.

The laboratories assess precision by calculating the relative percent difference, or RPD, for each pair of laboratory-initiated duplicate results. During 1992, at least one of the contract laboratories used a data qualifier (J3) to modify metals analyses when the RPD for laboratory duplicates was greater than 20%.

Additional statistical comparisons of laboratory duplicate and blind replicate results, both intra- and interlaboratory, are presented in the EPD/EMS quarterly reports. The calculation used for these reports is the MRD, or mean relative difference, which is similar to EPA's RPD except that the MRD provides a single value for all of the analyses of a particular com-

pound, either inter- or intralaboratory, during one quarter. Because detection limits may vary among samples, the MRD requires calculation of a reference detection limit, which is the detection limit at the 90th percentile of the array of limits in the population of all replicate and duplicate analyses for a given analyte during a particular quarter. The MRD is not method-specific.

Method-Specific Accuracy and Precision

The contract laboratories' EPA-approved laboratory procedures include QA/QC requirements as an integral part of the methods. Thus, knowledge of the method used in obtaining data is an important component of determining data useability. EPA has conducted extensive research and development on the methods approved for the analysis of water and waste water; information on the accuracy and precision of the method is available from EPA publications, as is full information on required QA/QC procedures. A listing of the methods used by the primary laboratories during first quarter 1992 is given below along with the source for the method description. Many, if not all, of these sources include presentations of representative accuracy and precision results.

<u>Method</u>	<u>Used to Analyze</u>	<u>Source</u>
EPA120.1	Specific conductance	EPA EMSL 1983
EPA150.1	pH	EPA EMSL 1983
EPA160.1	Filterable residue (total dissolved solids)	EPA EMSL 1983
EPA160.2	Nonfilterable residue	EPA EMSL 1983
EPA180.1	Turbidity	EPA EMSL 1983
EPA200.7	Trace elements	EPA EMSL 1983
EPA206.2	Arsenic	EPA EMSL 1983
EPA208.2	Barium	EPA EMSL 1983
EPA239.2	Lead	EPA EMSL 1983
EPA245.1	Mercury	EPA EMSL 1983
EPA270.2	Selenium	EPA EMSL 1983
EPA279.2	Thallium	EPA EMSL 1983
EPA300.0	Inorganics, non-metallics	EPA EMSL 1991
EPA310.1	Alkalinity	EPA EMSL 1983
EPA325.2	Chloride	EPA EMSL 1983
EPA335.3	Cyanide	EPA EMSL 1983
EPA340.2	Fluoride	EPA EMSL 1983
EPA353.1	Nitrogen, nitrate-nitrite	EPA EMSL 1983
EPA353.2	Nitrogen, nitrate, nitrite, or combined	EPA EMSL 1983
EPA353.3	Nitrogen, nitrate-nitrite, or nitrite only	EPA EMSL 1983
EPA354.1	Nitrogen, nitrite	EPA EMSL 1983
EPA365.1	Phosphorus, all forms (reported as total phosphates)	EPA EMSL 1983
EPA365.2	Phosphorus, all forms (reported as total phosphates)	EPA EMSL 1983
EPA375.4	Sulfate, turbidimetric	EPA EMSL 1983
EPA376.2	Sulfide	EPA EMSL 1983
APHA403	Alkalinity	APHA 1985
EPA413.1	Oil & grease	EPA EMSL 1983
APHA415A	Iodine	APHA 1985
EPA415.1	Total organic carbon	EPA EMSL 1983
EPA418.1	Petroleum hydrocarbons	EPA EMSL 1983
EPA420.1	Phenolics	EPA EMSL 1983
EPA420.2	Phenolics	EPA EMSL 1983
APHA705	Total alpha-emitting radium	APHA 1985

<u>Method</u>	<u>Used to Analyze</u>	<u>Source</u>
ASTMD3869C	Iodide	ASTM 1992
APHA5320	Dissolved organic halogen	APHA 1989
EPA6010	Metals	EPA 1986
EPA7041	Antimony	EPA 1986
EPA7060	Arsenic	EPA 1986
EPA7421	Lead	EPA 1986
EPA7470	Mercury	EPA 1986
EPA7740	Selenium	EPA 1986
EPA7841	Thallium	EPA 1986
EPA8010	Halogenated volatile organics	EPA 1986
EPA8020	Aromatic volatile organics	EPA 1986
EPA8080	Organochlorine pesticides and PCBs	EPA 1986
EPA8140	Organophosphorus pesticides	EPA 1986
EPA8150	Chlorinated herbicides	EPA 1986
EPA8240	GCMS VOA	EPA 1986
EPA8270	GCMS semivolatiles	EPA 1986
EPA8280	Dioxins and furans	EPA 1986
EPA9012	Total cyanide	EPA 1986
EPA9020	Total organic halides	EPA 1986
EPA9030	Sulfides	EPA 1986

An example of the available method-specific QA/QC information is that for the analysis of metals by EPA Method 6010/200.7 (EPA, 1986/EPA EMSL, 1983). The primary laboratories, General Engineering Laboratories (GE) and Roy F. Weston, Inc. (Weston), use this inductively coupled plasma (ICP) atomic emission spectrometric method.

The following precision and accuracy data are based on the experience of seven laboratories that applied the ICP technique to acid-distilled water matrices that had been dosed with various metal concentrates. (Note: not all seven laboratories analyzed all 14 elements.) The references give results for samples having three concentration ranges; the results here are for samples having the lowest values, similar to actual groundwater results for SRS.

ICP Precision and Accuracy Data

<u>Element</u>	<u>True value ($\mu\text{g/L}$)</u>	<u>Mean reported value ($\mu\text{g/L}$)</u>	<u>Mean percent RSD^a</u>
Aluminum	60	62	33
Arsenic	22	19	23
Beryllium	20	20	9.8
Cadmium	2.5	2.9	16
Chromium	10	10	18
Cobalt	20	20	4.1
Copper	11	11	40
Iron	20	19	15
Lead	24	30	32
Manganese	15	15	6.7
Nickel	30	28	11
Selenium	6	8.5	42

Element	True value ($\mu\text{g/L}$)	Mean reported value ($\mu\text{g/L}$)	Mean percent RSD ^a
Vanadium	70	69	2.9
Zinc	16	19	45

Note: In EPA (1986), the column heading is Mean Standard Deviation (%).

^a Relative standard deviation.

As another example, EPA Method 601/8010 (EPA, 1991/EPA, 1986) is used by both GE and Weston for analyses of halogenated volatile organics. In the presentation of the method in both references, the following table gives method-specific accuracy and precision as functions of concentration. Contract laboratories are expected to achieve or at least approach these limits.

Accuracy and Precision as Functions of Concentration for EPA Method 601/8010

Parameter	Accuracy as recovery, X'^a ($\mu\text{g/L}$)	Single analyst precision ($\mu\text{g/L}$) ^b	Overall precision ($\mu\text{g/L}$) ^c
Bromodichloromethane	$1.12C - 1.02^d$	$0.11\bar{X} + 0.04^e$	$0.20\bar{X} + 1.00$
Bromoform	$0.96C - 2.05$	$0.12\bar{X} + 0.58$	$0.21\bar{X} + 2.41$
Bromomethane	$0.76C - 1.27$	$0.28\bar{X} + 0.27$	$0.36\bar{X} + 0.94$
Carbon tetrachloride	$0.98C - 1.04$	$0.15\bar{X} + 0.38$	$0.20\bar{X} + 0.39$
Chlorobenzene	$1.00C - 1.23$	$0.15\bar{X} - 0.02$	$0.18\bar{X} + 1.21$
Chloroethane	$0.99C - 1.53$	$0.14\bar{X} - 0.13$	$0.17\bar{X} + 0.63$
2-Chloroethyl vinyl ether ^f	$1.00C$	$0.20\bar{X}$	$0.35\bar{X}$
Chloroform	$0.93C - 0.39$	$0.13\bar{X} + 0.15$	$0.19\bar{X} - 0.02$
Chloromethane	$0.77C + 0.18$	$0.28\bar{X} - 0.31$	$0.52\bar{X} + 1.31$
Dibromochloromethane	$0.94C + 2.72$	$0.11\bar{X} + 1.10$	$0.24\bar{X} + 1.68$
1,2-Dichlorobenzene	$0.93C + 1.70$	$0.20\bar{X} + 0.97$	$0.13\bar{X} + 6.13$
1,3-Dichlorobenzene	$0.95C + 0.43$	$0.14\bar{X} + 2.33$	$0.26\bar{X} + 2.34$
1,4-Dichlorobenzene	$0.93C - 0.09$	$0.15\bar{X} + 0.29$	$0.20\bar{X} + 0.41$
1,1-Dichloroethane	$0.95C - 1.08$	$0.09\bar{X} + 0.17$	$0.14\bar{X} + 0.94$
1,2-Dichloroethane	$1.04C - 1.06$	$0.11\bar{X} + 0.70$	$0.15\bar{X} + 0.94$
1,1-Dichloroethene	$0.98C - 0.87$	$0.21\bar{X} - 0.23$	$0.29\bar{X} - 0.40$
trans-1,2-Dichloroethene	$0.97C - 0.16$	$0.11\bar{X} + 1.46$	$0.17\bar{X} + 1.46$
1,2-Dichloropropane ^f	$1.00C$	$0.13\bar{X}$	$0.23\bar{X}$
cis-1,3-Dichloropropene ^f	$1.00C$	$0.18\bar{X}$	$0.32\bar{X}$
trans-1,3-Dichloropropene ^f	$1.00C$	$0.18\bar{X}$	$0.32\bar{X}$
Dichloromethane (Methylene chloride)	$0.91C - 0.93$	$0.11\bar{X} + 0.33$	$0.21\bar{X} + 1.43$
1,1,2,2-Tetrachlorethane	$0.95C + 0.19$	$0.14\bar{X} + 2.41$	$0.23\bar{X} + 2.79$
Tetrachloroethylene	$0.94C + 0.06$	$0.14\bar{X} + 0.38$	$0.18\bar{X} + 2.21$
1,1,1-Trichloroethane	$0.90C - 0.16$	$0.15\bar{X} + 0.04$	$0.20\bar{X} + 0.37$
1,1,2-Trichloroethane	$0.86C + 0.30$	$0.13\bar{X} - 0.14$	$0.19\bar{X} + 0.67$
Trichloroethylene	$0.87C + 0.48$	$0.13\bar{X} - 0.03$	$0.23\bar{X} + 0.30$
Trichlorofluoromethane	$0.89C - 0.07$	$0.15\bar{X} + 0.67$	$0.26\bar{X} + 0.91$
Vinyl chloride	$0.97C - 0.36$	$0.13\bar{X} + 0.65$	$0.27\bar{X} + 0.40$

^a X' = expected recovery for one or more measurements of a sample containing a concentration of C , in $\mu\text{g/L}$.

- b Expected single analyst standard deviation of measurements.
- c Expected interlaboratory standard deviation of measurements.
- d C = true value for the concentration, in $\mu\text{g/L}$.
- e $\bar{X}$ = average recovery found for measurements of samples containing a concentration of C , in $\mu\text{g/L}$.
- f Estimates based on performance in a single laboratory.

References

APHA (American Public Health Association), 1985. **Standard Methods for the Examination of Water and Wastewater**, 16th edition. Washington, DC.

APHA (American Public Health Association), 1989. **Standard Methods for the Examination of Water and Wastewater**, 17th edition. Washington, DC.

ASTM (American Society for Testing and Materials), 1992. **1992 Annual Book of ASTM Standards**, Volume 11.02, Water (II). Philadelphia, PA.

EPA (U.S. Environmental Protection Agency), 1986. **Test Methods for Evaluating Solid Waste (SW-846)**, Volumes IA-IC. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1987. **Data Quality Objectives for Remedial Response Activities**. PB88-131870; EPA/540/G-87/003. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1988a. **Contract Laboratory Program Statement of Work for Inorganics Analysis, Multi-Media, Multi-Concentration**. SOW No. 788. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1988b. **Contract Laboratory Program Statement of Work for Organics Analysis, Multi-Media, Multi-Concentration**. SOW No. 288. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990. **Guidance for Data Useability in Risk Assessment**. Interim Final. EPA/540/G-90/008. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991. *Guidelines Establishing Test Procedures for the Analysis of Pollutants, Code of Federal Regulations*, Title 40, Part 136, Appendix A. Revised July 1, 1991. Washington, DC.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1979. **Handbook for Analytical Quality Control in Water and Wastewater Laboratories**. PB-297 451; EPA-600/4-79-019. Cincinnati, OH.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1983. **Methods for Chemical Analysis of Water and Wastes**. Revised March 1983. Cincinnati, OH.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1991. Test Method, The Determination of Inorganic Anions in Water by Ion Chromatography – Method 300.0. Revised August 1991. Cincinnati, OH.

DATE

FILMED

7/12/94

END