2

**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

EGG-FSP-10262
July 1992

INVESTIGATION OF COMPONENT FAILURE RATES FOR
PULSED VERSUS STEADY STATE TOKAMAK OPERATION

L. C. Cadwallader

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

Received by OSTI

Aug 2 1992

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This document contains new concepts or the author(s) interpretation of new calculations and/or measurements; accordingly, EG&G Idaho, Inc. is required by the United States Government to include the following disclaimer:

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

EGG-FSP--10262

DE92 019758

INVESTIGATION OF COMPONENT FAILURE RATES FOR
PULSED VERSUS STEADY STATE TOKAMAK OPERATION

L. C. Cadwallader

July 1992

Idaho National Engineering Laboratory
EG&G Idaho, Inc., P. O. Box 1625
Idaho Falls, ID 83415-3523

Prepared for the
U.S. Department of Energy
Idaho Operations Office
Under DOE Contract No. DE-AC07-76ID01570

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

This report presents component failure rate data sources applicable to magnetic fusion systems, and defines multiplicative factors to adjust these data for specific use on magnetic fusion experiment designs. The multipliers address both long pulse and steady state tokamak operation. Thermal fatigue and radiation damage are among the leading reasons for large multiplier values in pulsed operation applications. Field failure rate values for graphite protective tiles are presented, and beryllium tile failure rates in laboratory testing are also given. All of these data can be used for reliability studies, safety analyses, design tradeoff studies, and risk assessments.

SUMMARY

This report describes the magnitudes of multipliers that should be applied to component failure rates for high power pulsed and steady state tokamak experiments. The candidate reactor designs used as the basis for estimating these failure rate multipliers are the pulsed operation International Thermonuclear Experimental Reactor (ITER) design and steady state operation designs from the Advanced Reactor Innovations and Evaluation Study (ARIES). From this initial effort, our goal is to accumulate operating experience data from tokamaks and other areas of scientific research to make better estimates of component failure rates for future fusion experiments and reactors. Figure S-1 depicts the goal of this task.

When no fusion data are available and there are no specific fusion component failure rate scaling studies already performed, this report gives guidance when applying failure rate data from other industries to fusion experiments. Sources of data are given, and modification factors are discussed. These modification factors, or multipliers, are often used in reliability engineering when analysts are applying data from known to unknown systems. Fractional multipliers are used when components are derated, that is, when components are purposely used at capacities below their full design parameter values. An example of derating is life extension derived for a cryogenic refrigerator when it is operated at part load rather than full load. Fusion component failure rate multipliers are almost always greater than one, because the tokamak environment is typically more harsh than most other industrial and scientific research applications.

Other issues of engineering concern are the divertor and first wall lifetimes, because of detrimental effects of wall erosion, plasma disruption forces, and the downtime associated with replacing protective materials; and magnet reliability, because of the several year change out time if one fails. These are concerns for both steady state and pulsed machines.

Figure S-1. Collections of Component Failure Rate Data for Fusion Use.

Table 2 on pages 11 and 12 in the text gives the suggested multipliers for several major tokamak components and systems. The pulsed operation condition will cause more equipment wear and thermal fatigue; therefore, there will be shorter component lives in plasma facing components (PFCs), magnets, and electrical systems. These systems are also the most concern for steady state tokamaks, but of lesser magnitude. Other systems, most notably the toroidal and poloidal field magnet coils, have lesser magnitude failure rate multipliers but are still strong concerns due to the significant downtime for replacement.

Appendix A gives failure rates for graphite and beryllium tiles, based on existing tokamak experiences and laboratory tests. The graphite tile cracking failure rates are on the order of $1\text{E}-05$ to $1\text{E}-06$ per graphite tile per pulse. A Tore Supra paper on wall protection suggested that their design called for actively cooled graphite tiles that could operate over 10,000 pulses, or a overall failure rate of $1\text{E}-04/\text{tile-pulse}$. Therefore, these results are better than the life predictions made by the Tore Supra operations staff. Carbon fiber composite tile usage in the Tokamak Fusion Test Reactor (TFTR) shows that this material performs better than graphite, by over an order of magnitude reduction in failure rate values. Both Joint European Torus (JET) and TFTR personnel endorse CFC tile reliability over that of graphite.

Beryllium tiles have inherent properties that differ from graphite tiles, and laboratory tests currently show failure rates on the order of $1\text{E}-04/\text{tile-pulse}$ for tile melting, although the laboratory conditions were more harsh than expected reactor conditions. The JET beryllium tile experience shows that the failure rate might be lower than the laboratory-derived value. Unfortunately, there is no data readily available at this time for plasma spray coating failure rate calculations.

The suggested failure rate multipliers are tentative values that will need reevaluation as the ITER design progresses. Design options for the divertor, first wall, magnets, and vacuum vessel need more study to provide good predictions of reliability.

CONTENTS

ABSTRACT	ii
SUMMARY	iii
1. INTRODUCTION	1
2. RELIABILITY PREDICTION TECHNIQUES	3
3. FAILURE RATE MULTIPLIERS	10
4. REFERENCES	23
APPENDIX A. FIRST WALL AND DIVERTOR TILE FAILURE RATE CALCULATIONS	A-1

INVESTIGATION OF COMPONENT FAILURE RATES FOR PULSED VERSUS STEADY STATE TOKAMAK OPERATION

1. INTRODUCTION

Reliability of in-vessel tokamak components will be an area of concern when significant neutron activation occurs on future machines and remote maintenance is required. Our best source of information on these reliability issues comes from the current generation of fusion experiments and from materials testing. Some of these machine operations data are not well documented, and fission reactor component failure rate data are instead used for fusion components. This report gives some insights into component failure rates for both pulsed and steady state fusion machines, to support designers in making choices for in-vessel components and other tokamak systems. These failure rates can be important to support both design regulation, such as a probabilistic Safety Analysis Report, the accident analysis section of an Environmental Impact Statement, and a Probabilistic Risk Assessment. Certainly, failure rates can also support tokamak availability studies. For example, the International Thermonuclear Experimental Reactor (ITER) Conceptual Design Activity (CDA) has set an annual availability goal of 25%, and this value must be verified in the next design phase. The final reason for seeking fusion component failure rates is that simple reliability analyses serve as a design check for the tokamak systems. For expensive projects, such as ITER, design checks are important to mission success. Component failure rates must be as accurate as possible when used for any of these reasons.

The current practice in component failure rate data for fusion is to apply fission reactor data tempered with engineering judgement. In a few cases, fusion component laboratory testing results are also used. Many assumptions are inferred when using fission reactor data on fusion components: similar design standards, materials, operating conditions, operating environments, comparable maintenance frequency and effectiveness, and others. There are positive reasons to use fission data banks: statistically significant data sets (more than 1000 reactor-years of data), accessibility, and easy interpretation. In fact, the chemical process industry and the cryogenics industry advocate using these data for

their own needs.^{1,2,3}

Using fission component failure rates on fusion components is not always accurate. Fusion components are usually very specialized and generally closer in technology to particle accelerators than to fission reactors. Consider a tritium handling system. Data from the Tritium Systems Test Assembly (TSTA) at Los Alamos National Laboratory, which handles up to 130 grams of tritium for simulated fusion fuel reprocessing, is prototypical of the ITER fuel cleanup loop. These data are much more applicable to ITER than data from fission reactor tritium handling. Using fission component failure rates on TSTA components is not usually very accurate. Consider a simple component such as piping. TSTA piping is usually 6.4-mm stainless steel with an outer jacket of polyvinylchloride pipe. Fission reactor data dwells on single walled process piping, generally 50 mm in diameter and larger. TSTA stainless steel piping is most similar to fission reactor instrumentation tap piping than to mild steel reactor coolant piping, but there is little fission data available on instrumentation piping reliability. The more similar the material, usage, environment, and maintenance, the better the application of other industry's failure rate data to fusion components.

In this report, I discuss current failure rate practices, application to fusion components, and how some component and/or system failure rates might vary for pulsing and steady state tokamak operation. Machines like ITER will behave differently than other proposed devices, such as those suggested in the Advanced Reactor Innovations and Evaluation Study (ARIES). ITER will pulse for several hundred or a thousand seconds and then cool for perhaps a similar amount of time, then pulse again. The ARIES designs run continuously, perhaps for thousands of hours between shutdowns.

The next section presents some reliability prediction information, followed by suggested data sources and multipliers to apply to failure rates from those sources. Each fusion component multiplier is explained. This report also gives some failure rates for graphite and beryllium tile plasma facing components (PFCs), since tile lifetime is an important safety and operational reliability issue for ITER and future machines.

2. RELIABILITY PREDICTION TECHNIQUES

Generally, component failure rates are reported as constant failure probabilities per operating hour, with associated error bounds. For example, a continuously operating electric motor might have a failure rate of $1\text{E-}05/\text{operating hour}$. Sometimes rates are given as failure probabilities per demand to function, such as a valve having a failure rate of $1\text{E-}04/\text{demand to close}$. System failure modeling typically uses both types of failure rates. An example of a dual failure mode component is a standby unit, such as a second coolant pump. The operating pump requires an hourly failure rate, and the standby pump must be modeled as failing to start on demand and failing to continue to run, given a successful start demand. Applying these data to new systems requires analysis of the new system, its environment, and its components.

Reliability prediction is a means to analyze an engineering system during the design phase, or in the operational phase before a significant amount of time has accumulated. Prediction is based on generic failure rates for components and the use of multipliers to modify the component failure rates to make them applicable to different component uses. Reliability prediction is important to analysis of new designs. A good example of prediction is the Thomas method⁴ for piping failure rate estimation, where a set of specific multipliers are applied to a generic piping failure rate. The Thomas method multipliers are tailored to reflect the specific piping application, such as age, number of welds, etc. Prediction is also practiced in military equipment design.^{5,6}

Reliability prediction involves engineering judgement. The following formula is often used in component reliability prediction work:⁷

$$\text{Applicable Failure Rate} = (\text{Generic Failure Rate})(K1)(K2)(K3)(K4)(K5)(K6)$$

where the generic, unmodified failure rate can be found in a handbook or compilation of reliability data. This failure rate is considered to be unstressed by special factors, that is, it is operating well within its design parameters and the failures are from causes inherent in operating such a piece of equipment. The K factors are described below.

K1 is an applied stress factor, such as electrical voltage or thermal stresses, that push the design envelope.

K2 is the ratio of minor, or tolerable failures, to catastrophic failures (This factor could be 1.0, depending on the failure mode of interest. For example, only about 10% of pipe failures are ruptures, and the rest of the failures are various sizes of leaks. When weighting a generic pipe failure rate for pipe ruptures, we would use $K2 = 0.10$.)

K3 is the environmental stress factor, accounting for high humidity, irradiation, dirt, high temperature, or other location-related features.

K4 is the maintenance factor, which accounts for good or bad maintenance.

K5 is the system complexity factor, since complex systems tend to fail more frequently than simple systems.

K6 is the cycling effects factor, primarily used for electronic equipment, such as a factor of $(1+8N)$, where N is the number of on-off cycles per operating hour. K6 alters the hourly failure rate to account for high numbers of cycles.

These factors must all be addressed to find a reasonable failure rate for a given component. Sometimes, this task is simple because the component cited in the handbook or data source is quite similar to the new component in design and usage, so the component failure rate value applies directly to the new usage. Other times, K factors must be evaluated for a new application and values must be assigned to these multipliers. Usually, K factors will vary from values of perhaps 0.1 to 3, but this is highly dependent on the type of component, the source of the generic data, and the category of the K factor. Much larger K factor values, 10 and higher, are often found. Choosing appropriate data sources and assigning K factors are where engineering judgement becomes very important for reliability work. I note that there are often dissenting views published, especially in the IEEE Transactions on Reliability, on using this method. Nonetheless, it is still used because of the lack of any better approach to systems that do not have any field experience data as a referent.^{8,9} I have collected and evaluated some multipliers from the reliability literature to set fusion component reliability bounds for these six listed K-factor multipliers.

Most of the published values relate to the K3 environment stress factor, such as high temperature or high radiation environments. Table 1

TABLE 1. ENVIRONMENTAL K3 FACTORS FOR SEVERAL TYPES OF EQUIPMENT

Type of equipment	Average Environmental K3 Factors	
	High temperature	High radiation
<u>Selected nuclear industry values:¹⁰</u>		
Circuit breakers and relays	1.8	2.1
Motors and generators	5.2	1.0
Electric heaters	1.8	1.0
Transformers	1.6	1.2
Valve operators or actuators	1.6	1.4
Instruments, controls, and sensors	2.0	1.1
Electrical conductors	2.5	2.6
Average electrical component factor	2.4	1.5
<u>Selected aerospace industry values:¹¹</u>		
Electrical connectors	2.3	
Electrical relays	12	
Electrical switches	2	
Liquid level sensors	4	
Pressure switches	1	
Pressure transducers	2.5	
Temperature transducers	25	
Average electrical component factor	7	
Quick disconnects	3	
Mechanical filters	5	
Pumps	1.5	
Check valves, shutoff valves	1	
Solenoid valves	2	
Vent and relief valves	15	
Pressure regulators	3	
Average mechanical component factor	5	
Notes: High temperature typically meant at or below 100° C		
High radiation usually meant radiation exposure above background radiation levels		
Aerospace factors did not include high radiation environments		

gives the averages of these multipliers for several kinds of components. From the table, we see that for typical nuclear industry electrical components, the average multipliers are 2.4 for high temperature and 1.5 for high radiation environments. From the aerospace industry, the high temperature multipliers are more aggressive, with electrical components at an average value of 7 and mechanical components at an average value of 5. The spacecraft data also considered high vibration and high pressure, but did not consider high radiation. This is probably because most manned spacecraft missions are too short in duration for irradiation effects to become significant. The multipliers from Table 1 are used as guidance to give an overall environmental K3 factor for application to generic failure rates. Other K factor values are discussed below.

K1. I assume that K1, the applied stress factor, is 1.0 for most fusion components, since they must be robustly designed to meet these stresses. Fusion components are typically designed to be as robust as possible, and often do not have specifically planned service lives. Occasionally, I will use a K1 factor, but it is often set to 1.0.

K2. The K2 factor is often used to show the percentages of the severity of the failure cause to the failure rate. As discussed, piping failures can be various sizes of leaks, or catastrophic ruptures. A K2 factor for ruptures might be 0.1 of the overall piping failure rate. Since we are mainly concerned with the catastrophic failures that can damage the fusion machine or injure people, we will specifically dwell on the component failure modes that precipitate such catastrophic failures. Therefore, I have set the K2 factor to 1.0.

K3. The environment factor is perhaps the most widely used factor. It can be used equally well on equipment that operates per request (demand) or on equipment operating on an hourly basis. Table 1 gave the averaged values for this factor.

K4. The maintenance factor, K4, will require future judgement as to the tradeoffs between hands-on and remote maintenance. Remote maintenance loses many of the less tangible benefits of hands-on maintenance, such as tactile sensation for testing smoothness or cleanliness of mating surfaces

or seals, sense of smell to assist in preventive or corrective maintenance diagnosis, reliance on television cameras versus eyesight, lesser dexterity of manipulators versus hands, etc. Many factors must be accounted for to accurately assign a K4 value to fusion applications. For this discussion, I suggest using an optimistic K4 factor of 1.5 (I expect that this factor can easily increase as more study of remote maintenance reliability is performed).

K5. The system complexity factor, K5, is most often used for complicated electronic equipment (radar units, satellite link navigation systems, and other electronic systems). Most of the fusion components discussed here are not as complex as radar systems or other military electronic equipment, so I choose to set the K5 factor to 1.0 as well.

K6. The K6 factor, to account for on-off cycling effects, is difficult to predict for fusion components. This factor is usually applied to component failure rates as a degradation factor that reduces the hourly service life to account for numerous on-off cycles. K6 is only used on hourly failure rates to account for cycling effects. Reference 6 gives guidance for setting K6 cycling factors to a variety of electrical equipment, but most of our discussion will dwell on cycling effects on mechanical components. We know that frequent equipment cycling can be detrimental to its longevity, by thermal cyclic fatigue, wear, and other causes. However, equipment built for on-off cycling is already treated with 'failure to start on demand' as well as 'failure to continue to run' failure rates. Of course, the K3 environment factor, such as high temperature or high radiation, still applies to such equipment. Nonetheless, greatly increasing the cycling frequency (cycles/hour) will cause increased degradation, even in components built for cyclic operation. This effect is seen for both mechanical¹² and electrical components.⁶

Guidance from reference 6 shows that for only a few cycles/hour, many cyclic electrical components (relays, circuit breakers, connectors) have a K6 factor of 1.0. This value infers that infrequent or routine cycling is not a degradation to equipment items built for cyclic duty. Reference 6 suggests calculating an electrical equipment K6 multiplier by using (cycles/hour)/10. This formula shows that as the cycling frequency

increases, components begin to lose the ability to cope with the increased demand. Electrical components begin building up residual heat from imperfect current contact points, lubricants may be affected by the warmth so that metal-to-metal wear accelerates, electrical insulation warms and can become pliable, self-induced mechanical shocks and vibration in the component can begin to cause it to lose its proper adjustment, etc. Generalizing to a tokamak experiment, the infrequent pulses allow cool down of the armor tiles on interior walls, as well as the support systems. Magnet coils and magnet power supplies cool down, vacuum pumps remove the impurities created during the pulse, diagnostic probes cool down, etc. The choice is to run constantly at a high temperature or to run infrequently at very elevated temperatures, with long cooldowns. Frequent pulsing does not allow the cool down periods, and seems to be most detrimental to metals.¹³ For future tokamak components that are pulsed frequently, perhaps 12 times per hour, I assign a K6 factor of 3 to apply to component failure rates derived from existing tokamak experiments. I based this value on information from references 6 and 12. For pulses of longer duration, so that there are only perhaps 2 or 3 pulses per hour, the K6 factor could be 1.5 or simply 1.0.

Overall K factor. The individual K factor multipliers can be combined into a single multiplier to apply to a given component failure rate. When no fusion-specific data or other highly applicable data exists, I suggest using a half order of magnitude (a factor of roughly 3) as an overall K factor on fission reactor equipment failure rates when applying them to existing fusion components. I suggest the value of 3 because of several influences, which I explain below.

Many fusion components do not have the large safety factors (and cost increases) that fission components are required to have from design standards (i.e., the "N-stamp" of the American Society of Mechanical Engineers or the "Class 1E" of the Institute of Electrical and Electronics Engineers), and there is a concern that remote maintenance may not be as successful as the hands-on maintenance routinely employed at fission reactors. The overall K factor comes from a K3 factor of 2 (based on Table 1) for components close to the edge of the design envelope and small K4 factor of 1.5 to treat remote maintenance concerns. Combining these

numbers gives a factor of 3 for the overall K factor when applying fission reactor component failure rate data to present day fusion components. Any additional changes in the operating environment must also be considered by augmenting the K3 factor.

Generally, using fission failure rate data for fusion components must be done to get any meaningful fusion safety results.¹⁴ For conservatism, analysts will sometimes round up the fission-based failure rates to the next highest order of magnitude. This practice generally compliments my suggestion of using a multiplier of 3 on fission failure rate data. Then, the fission failure rate should be a conservative upper bound to the fusion component, so that uncertainty analyses and rework to treat small design changes are not necessary in early design stages. Another conservatism that analysts sometimes use to obtain a failure probability is multiplying the failure rate by 10,000 hours per year rather than the actual 8,760 hours per year or less (if the component is not in continuous operation).

Reliability analysts are accustomed to working with failure data that predicts failure rate behavior to within an order of magnitude,^{15,16} therefore, order-of-magnitude estimates and roundoff to half orders of magnitude are quite common practices for risk assessment. However, when failure rate information is well known, analysts will take advantage of precise estimates.

The next section gives suggested generic data sources to use for a variety of fusion components, and presents several guidelines for either specific or overall K factor multipliers to use on those generic failure rate data sets.

3. FAILURE RATE MULTIPLIERS

Current information on component failure rates comes mainly from the nuclear fission industry. Data handbooks such as references 10, 17 and 18 are often used for fusion components. Besides those data usage assumptions already mentioned, analysts accept several more assumptions when using these data. Since the same industrial base will manufacture the fusion components, any manufacturing errors will be inherent in all of the components.¹⁹ Another is that designers, using appropriate technology and good design techniques, will achieve performance results similar to those from the original component application.²⁰

Consideration of the data source system to fusion system comparison must be performed as part of this K factor assessment. Fission reactors typically operate in steady state, perhaps thousands of hours at a time, with short startup and cooldown times (perhaps a half-day each). Fission reactors can have high availabilities, on the order of 60-75% or higher. Current tokamak reactor experiments have low availabilities, probably around 10% operating time per calendar year. Such low availabilities are the nature of fusion experiment programs - downtime between pulses for machine cooling and data review; downtime for cleaning the vacuum vessel interior; and extended downtime to make system modifications, change parameters of tests, install new diagnostic devices, etc. Nonetheless, some tokamak system components are run very frequently, perhaps most of the year, such as those in the support systems - electric power, cryogenic cooling systems, vacuum pumping systems, and building ventilation to cool electrical components. Those systems operate quite like fission power plant systems. Other fusion systems, such as magnet power supplies, are pulsed perhaps several hundred times a month, for several seconds at each pulse.

Table 2 gives suggestions for fission and other data sources that most closely align to fusion systems. Table 2 gives the K factor multipliers I suggest for failure rate application to both pulsed and steady state fusion systems. The closer a component's K factor is to 1.0, the generally lower the component's failure rate. Consequently, system reliability should be better with overall K factors closer to 1.0.

TABLE 2. SUGGESTED FAILURE RATE DATA SOURCES AND K FACTOR MULTIPLIERS FOR PULSED AND STEADY STATE FUSION SYSTEMS

<u>Fusion Component or Fusion System of Interest</u>	<u>Source and Reference Numbers of Data Sources for Fusion Applications</u>	<u>Suggested Overall or Specific K Factor Multiplier for ITER Pulsed Operations</u>	<u>Suggested Overall or Specific K Factor Multiplier for Steady State Operations</u>
Toroidal magnets	fusion experiences [21]	K1 = 3	1
Poloidal magnets	fusion experiences [21]	3	3
Electric power system	industry usage [22]	100	3
Vacuum System	note a	3, if using turbo pumps 1, if using cryopumps	1
Vacuum Vessel	note a	10	3
First Wall Tiles	fusion experiences, Appendix A	K1 = 3	K1 = 1
Divertor	fusion experiences, Appendix A	10	3
Heat Transfer System	fission experiences, [10,17,18] (water) [23] (liquid metal) [24] (gas)	3	3

Note a: I am compiling vacuum system component reliability information from accelerators and fusion experiments. I should publish it later this year.

TABLE 2. SUGGESTED FAILURE RATE DATA SOURCES AND K FACTOR MULTIPLIERS FOR PULSED AND STEADY STATE FUSION SYSTEMS
(continued)

<u>Fusion Component or Fusion System of Interest</u>	<u>Source and Reference Numbers of Data Sources for Fusion Applications</u>	<u>Suggested Overall or Specific K Factor Multiplier for ITER Pulsed Operations</u>	<u>Suggested Overall or Specific K Factor Multiplier for Steady State Operations</u>
Cryoplant	particle accelerator and industry usage, [25]	1	1
Plasma Fueling System	fission and fusion, [18,26,27], note b	1	1
Plasma heating systems (NBI, ICRH, ECRH, etc.)	fusion experiences, particle accelerator experiences, [28,29]	1	1

Note b: Tritium storage is included here. There are the two cited reports and more under way, taken from operating experiences at the Tritium Systems Test Assembly at Los Alamos

There are several other ways to achieve low component failure rates. One method of keeping the component failure rates low is to make the component's operating environment as benign as possible. Another is to operate the component well within its design safety and planned operations factors (the 'derating' mentioned earlier). In established views on fusion technology, the steady state operations method of few demands and very long run times is less stressful to components than frequent pulses and the alternating stresses they place on the tokamak. This viewpoint is shown in Table 2 by comparing the K factor multipliers in the ITER and ARIES columns, and it is also illustrated in Figure 1. The ratio of the K factors in the ARIES column to those in the ITER column provides a qualitative measure of the benefit gained in system and component reliability of steady state versus pulsed reactor configurations.

On the following pages, I explain my rationale for selecting each of these K factor multipliers, either specific or overall values, for the various fusion components cited in this table. The K factors depend on the data source and the expected usage and environment for the ITER and ARIES components. In general, extrapolating data from existing tokamak experiment equipment to ITER equipment typically should require a failure rate increase of between 3 and 10. This range of factors comes from the expected higher radiation levels (a factor of 1.5), higher temperatures (a factor of 1 to 5, see Table 1), and the remote maintenance issue (a factor of 1.5). Note that for components that have only per demand failure rates, only K3 environmental factors are employed in Table 2.

Toroidal Magnets. The toroidal field (TF) magnets serve to provide plasma confinement. These magnets are conceptualized to have a 'demand counter' for their useful life; that is, the more cycles on and off, the quicker they wear out.³⁰ Fusion magnets are constructed to give as reliable a life as possible, since replacing a magnet coil is costly and time consuming.

While a pulsed tokamak configuration does not mean that the magnets will ramp up and down on a routine basis, pulsed systems will probably have more disruptions. Existing tokamaks experience between 10% and 20% disruptions from all pulses.^{31,32} Such high numbers of disruptions

Figure 1. Qualitative comparison of pulsed versus steady state fusion reactor operation.

will lead to more need for vacuum vessel impurity cleaning due to disruption-induced wall material erosion and possible probe material disintegration. That is, disruptions will poison the vacuum vessel and will require frequent glow discharge cleaning. The magnets must be turned off for the cleaning to be effective. This requirement means that the magnet will have to be cycled on and off more often than for steady state systems. There will also be induced loads from disruption forces, both mechanical and electromagnetic. I suggest a multiplier of 3 to account for increased K1 stress effects (fluctuating voltages, mechanical loads, and heating). Steady state TF magnet systems should operate as reliably as present superconducting TF magnet systems.

Poloidal Magnets. The poloidal field (PF) magnets are slowly and continuously ramping up and down in current to perform their function of plasma shaping. Any tokamak configuration will require these magnets to continually be changing their field strength to accommodate variations in the plasma profile. Long pulse times for ITER will place greater demands on most of these magnets, especially the plasma vertical equilibrium coils, so that they have to ramp up and down many times, perhaps thousands of times per burn for the vertical positioning coils, in time spans of several hundred or a thousand seconds. Such a high number of demands, coupled with the use of superconducting coils in ITER and future machines, indicates that a K factor should be applied to these coils. I apply an overall K factor multiplier of 3 to both the steady state and pulsed systems, since their function and usage is roughly the same for each configuration. Concerns about radiation heating and damage (1.5), mechanical and electromagnetic forces (1.5), and thermal effects (1.5) combine to give a value of roughly 3. In the past, most PF magnets have been resistive copper coils rather than superconducting magnets. Extrapolations from resistive magnet performance to superconducting magnet performance are probably not very precise, and should be done very cautiously.

Electric Power System. The electric power systems to run the plasma heating systems and magnets continue to grow in size. Cycling electric equipment for extended time periods, such as the runs associated with ITER, will lead to degraded performance. If ITER cycled as much as 12-15

times an hour over periods of several days or a week, exercised electric components such as relays, switches, and circuit breakers should be multiplied by factors as low as 2 and up to as high as 150 (the 150 applies if a circuit breaker is used as a switch), according to reference 6. A multiplier of 100 is therefore reasonable to apply to industrial equipment that might be utilized for fusion applications. Such equipment is often designed for continuous-usage electrical distribution systems, not cyclic power routing operations, therefore, such a high K factor is reasonable even if the cycle frequency is less than 12/hour. When TF magnets and heating are operated continuously, rounding the electrical system failure rate up to the next order of magnitude (usually about a factor of 3 or so) should be conservative.

Vacuum System. The vacuum system must maintain the vacuum vessel at very low pressures to keep unwanted particles and gases out of the plasma. The vacuum system is usually located away from the torus, perhaps on the floor beneath the torus, so radiation and thermal stresses are not significant problems. One of the main concerns for vacuum pumps is system impurities. When the pulsed tokamak system is loaded down with large batches of impurities, such as wall erosion particles, I assume that there is more tendency for wear and abrasion in the turbomolecular vacuum pumps. Wear and abrasion for these components is not a severe problem, so I have assigned a multiplier of 3 to apply to current failure rate information on fusion vacuum equipment. If cryogenic vacuum pumps are used, there is no change from current fusion vacuum pump failure rate information. Steady state applications will have continuous small amounts of wall erosion products, in volumes similar to those routinely handled in existing machines. Therefore, I assume the turbomolecular pump units can tolerate steady state operation easily, and steady state machine operations values are not changed from existing system's field experience failure rates.

Vacuum Vessel. The vacuum vessel serves as the primary confinement barrier for the fusion plasma. The vessel must have structural strength, ability to withstand bakeout heat for cleaning, have many penetrations to allow diagnostics access, and withstand potential hydrogen explosions. The most severe off-normal event other than an explosion is a major plasma

disruption. Pulsed machines will have more plasma disruptions, because disruptions are much more likely to occur during the frequent pulse terminations. Current generation machines show rather high plasma disruption rates, perhaps 10% to 20% of all pulses end in some form of disruption, as previously stated. Major, severe disruptions are those of concern here, because these generate high energy runaway electrons that damage the vessel, the disruption heat energy is deposited on the walls, and generated eddy current forces place large mechanical stresses on the vessel. While all disruptions may be thought of as severe, extremely severe disruptions might occur at a rate of perhaps only 1% of all disruptions. I suggest a K1 factor of 3 increase for the thermal shocks and an additional factor of 3 to account for the large, meganewton-range mechanical forces from eddy currents when extrapolating existing fusion vessel failure rates to higher powered machines. Vessel thermal fatigue and irradiation life should be included in design criteria, as they already are for existing vacuum vessels and fission reactor pressure vessels. High power pulsed machines, like ITER, should have an overall K factor of 10 for use on the vacuum vessel failure rate from existing fusion experiment machines. The high value of 10 accounts for the harsh thermal and mechanical shocks that disruptions can produce.

A steady state tokamak will not experience as many disruptions, but those it does have are more likely to be severe, since the power level can be high. I suggest an overall K factor of 3 to account for disruption effects in future steady state machines.

First Wall Tiles. The first wall (FW) armor tile failure rates from published information on existing tokamaks are presented in Appendix A. While this information is the best presently available, we cannot be sure that these failure rates are indicative of future generation machine performance. One factor in this tile failure rate calculation is that tile misalignments can provide 'leading edges', that is, an edge of a tile protruding above the nominal plasma facing surface of the graphite tile. These tile edges take much more thermal abuse, which leads to cracking and spalling. In general, pulsed machine first wall tiles have thermal fatigue, erosion, and heat removal concerns. Laboratory experiments with graphite tiles brazed to cooling tubes have shown that braze reliability

is essential for adequate heat conduction. Braze voids lead to heat buildup and tile fracture.³³ High heat load cycling in a radiation field is among the harshest of possible environments, and also considering that plasma disruptions generate high energy runaway electrons indicates that it is prudent to increase the tile failure rate from presently known values when extrapolating to future pulsed machines.

Present graphite tile failure rates from Appendix A are on the order of $1\text{E-}06$ to $1\text{E-}05$ /tile-pulse for normal operations, and we see that there is an increase of roughly a factor of 3 to 4 for disruption conditions (the inverse of the disruption percentage) in some of the existing tokamaks. That factor of 3 to 4 increase is based on the assumption that disruptions are the worst condition experienced and are the true cause of tile degradation. For higher power levels, higher average heat loading levels, higher thermal fatigue, and more frequent pulsing, the K1 plasma disruption factor of 3 is used as an overall K factor multiplier for tiles. Steady state machines must deal with more severe surface erosion problems balanced with tile heat conduction depth to provide a reasonably long-lived tile. The heat load and thermal fatigue issues will be reduced from those in pulsed operations; therefore, the steady state tile failure rate should be comparable to existing tile failure rates. We note that Buende³⁴ states that thermal fatigue could be life limiting for first wall materials, and that derating the component (intentional operation at reduced capacity) because of decreased heat loads in steady state operation would be extremely beneficial in reducing the failure rate. Component derating is well known to electronics reliability engineers to enhance component life.⁹ Mechanical systems also experience the effects of reductions in operations. For example, a cryogenic refrigerator operated at 40% capacity has been seen to operate more than twice as long between failures or major maintenance sessions than similar units operated at higher capacities.³⁵ Mechanical derating of the tiles (reduced heat load and stresses) should also provide for longer life, so the steady state operation overall K factor should be unity. Carbon fiber composite (CFC) tiles are more robust than graphite tiles, with failure rates at least an order of magnitude lower than graphite tiles. For conservatism, I suggest using the graphite tile K factors on CFC tiles until more information about their durability is collected.

While CFC tiles withstand the tokamak environment better than graphite, there is still the problem of poisoning the plasma with carbon atoms eroded from the tile surface. Therefore, beryllium tiles are suggested as a possible replacement for graphite tiles. Beryllium metal has a low melting point (by fusion standards), and can be brittle when irradiated.³⁶ There are some data available on beryllium tile operating experiences from the Joint European Torus (JET), and from laboratory testing. These are given in Appendix A with the graphite tile failure rates. A current point estimate failure rate for melting is $1\text{E-}04/\text{tile-pulse}$. Beryllium brazing to copper cooling tubes should be easier than for graphite, because beryllium and copper have more similar thermal expansion characteristics than graphite and copper, but most of the other concerns are the same - heat load, thermal cycling, erosion, disruption forces, and runaway electrons. No overall K factor is assigned to beryllium tile failure rates for future pulsed or steady state tokamaks. More information is needed before such a factor can be selected.

Divertor. The divertor is probably the most sensitive component inside the tokamak. It must accept high particle and heat loads in normal operation, as well as increased loads in plasma disruptions. Divertor design is at a point of producing workable solutions rather than optimal designs. More materials research is needed to develop a robust divertor design. A graphite tile divertor failure rate from the Japan Torus-60 (JT-60) is given in Appendix A. The point estimate values are $3\text{E-}05/\text{tile-pulse}$ and $8\text{E-}05/\text{tile-disruption}$. These failure rates are expected to increase for future pulsed machines as the fusion power (heat loading) increases, and more energetic disruptions and runaway electrons are encountered. Sweeping the plasma across the divertor surface might offset some of these detriments, but this is not clear. Therefore, I suggest increasing the overall FW K factor multiplier of 3 by another factor of 3 to give a factor of roughly 10 for a graphite divertor material in a high power pulsed tokamak. The extra factor of 3 comes from the more aggressive environmental challenges that divertor must face compared to the first wall tiles. The steady state machine divertor environment should be less harsh, so I suggest using the same multipliers from the pulsed machine first wall discussion above on the steady state

machine divertor tiles. Even in the generally more benign steady state machine, the divertor will take a great deal of punishment.

Other divertor design options, such as liquid metal falls or gas streams, need further study before even crude reliability estimates can be made or K factor multipliers can be chosen.

Heat Transfer System. Heat transfer systems using water, helium, and liquid sodium have all been characterized for reliability in fission reactor applications. These data can be applied to fusion heat transfer systems. As fusion experiments increase in power, cooling systems will have to operate continuously in a high heat and irradiation environment, precisely the environment that they operate in for fission systems. Since both future pulsed and steady state machines will likely have their cooling systems operating continuously, these data should be able to apply directly to fusion systems (if similar materials are used in construction). For example, piping of different materials can behave differently under irradiation. Mild steel pipe whose interior is clad with stainless steel, such as is used in fission reactors, will behave differently than a fusion reactor's stainless steel pipe. However, outside of materials concerns, the only major difference between the fission and fusion systems are maintenance effectiveness and design standards. The K4 factor of 1.5 is used here to account for the remote maintenance issue. If pulsed systems experience large bursts of high energy (14 MeV and below rather than fission's 2 MeV) neutrons, the high radiation K3 factor of about 1.5 should also be applied, giving a new overall K factor of roughly 3. If we assume that fusion design standards will be as robust as fission design standards are, then they are comparable, and the overall K factor for pulsed systems remains at 3.0. Steady state systems will operate like the pulsed tokamak cooling systems, and the overall K factor should be the same.

Cryoplant. The cryoplant is one of the facility support systems that remains on-line almost continuously because of long downtimes associated with warmup and cooldown (on the order of several days to a week duration). Failure rates from particle accelerator and other cryoplants have been collected for use, and these values should not need modification

to apply to fusion facilities because they are very similar in design, application, and service life.

Plasma Fueling System. Plasma fueling needs for pulsed and steady state machines are similar. Fueling means, either beam injection or gas puffing, are usually cyclic rather than constant processes. There might be a slight disadvantage to pulsed operation because the downtimes between pulses might force interruptions in the cycling rate of the fueling system. This is probably a minor concern. I do not suggest using any failure rate multipliers on present fusion experiment fueling systems to apply their failure rates to next generation experiments. If there are increased duty factors (such as increasing to 25% or higher availability), they will be accounted for in the increased system failure probabilities.

Plasma Heating Systems. Pulsed devices like ITER will require high energy systems, in the range of dozens of megawatts of input power. System on-off cycling will degrade these components, just like the magnets. Because existing machines use their beam heating a great deal, it is possible that the usage is already very similar to that planned for future experiments. Therefore, I suggest using a multiplier of 1 on the present failure rate values for pulsed systems, and the same factor for steady state systems. The steady state systems will be few and not continuously demanded for the ignited, steady burn plasma. Their usage, or duty factor, will be less than present generation systems, and the decreased duty factor should be accounted for when failure rates and operation times are used to generate failure probabilities for fault tree quantification. There may be a small negative influence of high heat loads on the antennas to contend with, but this problem should be surmountable.

Other Systems. There are other systems that must also be treated for next generation machines. Two of these systems are computer controls and the variety of plasma diagnostics. There is enough knowledge of computer hardware and software reliability to provide a good basis for estimates of future machine performance, when they are needed. On the other hand, plasma diagnostic devices are numerous and their reliability will require much attention during the ITER Engineering Design Activity.

These suggested multipliers are tentative values, chosen on the basis of the best information available. These values will need reevaluation as more information is found and as the ITER design progresses.

4. REFERENCES

1. H. R. Greenberg and J. J. Cramer, Risk Assessment and Risk Management for the Chemical Process Industry, Van Nostrand Reinhold, New York, 1991, pages 224-225.
2. F. P. Lees, Loss Prevention in the Process Industries, Butterworths, London, 1980, Volume 2, Appendix 9, Failure and Event Data.
3. A. Santay, safety analyst at Air Products and Chemicals, private communication, April 22, 1991.
4. H. M. Thomas, "Pipe and Pressure Vessel Failure Probability," Reliability Engineering, 2, 1981, pages 83-124.
5. Military Standard, Reliability Modeling and Prediction, MIL-STD-756B, US Department of Defense, November 18, 1981.
6. Military Handbook, Reliability Prediction of Electronic Equipment, MIL-HDBK-217E, US Department of Defense, October 27, 1986.
7. W. H. Von Alven (editor), Reliability Engineering, Prentice-Hall, Englewood Cliffs, NJ, 1964, pages 311-318.
8. D. J. Klinger et al., AT&T Reliability Manual, Van Nostrand Reinhold, New York, 1990, chapter 4.
9. N. B. Fuqua, Reliability Engineering for Electronic Design, Marcel Dekker, Inc., New York, 1987, part 2, 4.
10. IEEE Guide To The Collection And Presentation Of Electrical, Electronic, Sensing Component, And Mechanical Equipment Reliability Data For Nuclear-Power Generating Stations, Standard 500-1984, Institute of Electrical and Electronics Engineers, December 1983.
11. Saturn Component Failure Rates and Failure Rate Modifiers, NASA Technical Memorandum, NASA TM X-64619, Quality and Reliability Assurance Laboratory, Marshall Space Flight Center, 1971.
12. H. P. Bloch and F. K. Geitner, An Introduction to Machinery Reliability Assessment, Van Nostrand Reinhold, New York, 1990, ch. 5.
13. R. J. LeClaire et al., "Aspects of Long Pulse Commercial Tokamak Reactor Design," Proceedings of the Tenth Symposium on Fusion Engineering, Philadelphia, PA, December 5-9, 1983, pages 249-253.
14. H. Schnauder and A. Wickenhauser, "Potential Influence of Reliability Analysis on Component Design in Fusion Reactors," Nuclear Engineering and Design, 100, 1987, pages 489-500.
15. E. J. Henley and H. Kumamoto, Reliability Engineering and Risk Assessment, Prentice-Hall, Inc., Englewood Cliffs, NJ, 1981, page 277.
16. N. H. Roberts et al., Fault Tree Handbook, NUREG-0492, U. S. Nuclear Regulatory Commission, January 1981, page XI-10.

17. Guidelines for Process Equipment Reliability Data, Center for Chemical Process Safety, American Institute of Chemical Engineers, 1989.
18. Component Reliability Data for Use in Probabilistic Safety Assessment, IAEA TECDOC-478, International Atomic Energy Agency, October 1988.
19. G. Ollivier and R. Buende, "Reliability and Availability Analysis During the Design of an Innovative Component of a Thermonuclear Plant," presented at the 7th International Conference on Reliability and Maintainability, Brest, France, 1990.
20. H. L. Thaggert and I. M. Jacobs, "Component Failure Rates Applicable to LMFBRS as Derived from LER Data," Nuclear Safety, 24, November-December 1983, pages 801-809.
21. L. C. Cadwallader, Magnet Operating Experience Review for Fusion Applications, EGG-FSP-9977, EG&G Idaho, Inc., November 1991.
22. "Report on Reliability Survey of Industrial Plants, Part 1: Reliability of Electrical Equipment," IEEE Transactions on Industry Applications, IA-10, March/April 1974, pages 213-235.
23. Failure Data Handbook for Nuclear Power Facilities, LMEC-Memo-69-7, Liquid Metal Engineering Center, August 1969. Note: The Centralized Reliability Data Organization at Oak Ridge National Laboratory holds more recent data for a larger, international group of liquid metal fission reactors.
24. G. W. Hannaman, GCR (Gas Cooled Reactor) Reliability Data Bank Status Report, GA-A14839, General Atomic Company, July 1978. Note: Some additional work has recently been done for the New Production Reactor project in the US. When this work becomes available, it will likely supercede Hannaman's early work on the Peach Bottom and Fort St. Vrain gas cooled fission reactor power plants.
25. L. C. Cadwallader, Cryogenic System Operating Experience Review for Fusion Applications, EGG-FSP-10048, EG&G Idaho, Inc., January 1992.
26. L. C. Cadwallader and M. A. Stolpe Gavett, Tritium Waste Treatment System Component Failure Data Analysis from June 18, 1984 to December 31, 1989, EGG-FSP-8973, rev. 1, also LANL-LA-UR 90-2993, EG&G Idaho, Inc., November 1990.
27. L. C. Cadwallader et al., Tritium Room Air Monitor Component Failure Data Analysis From January 1, 1984 to December 31, 1990, EGG-FSP-9450, EG&G Idaho, Inc., May 1991.
28. S. Papastergiou, "Reliability Analysis of the JET Neutral Injection Beamlines," Proceedings of the Thirteenth Symposium on Fusion Engineering, 2-6 October 1989, Knoxville, TN, pages 416-419.
29. C. D. Challis et al., "Reliability Study of the JET Neutral Injection System," Proceedings of the 14th IEEE Symposium on Fusion Engineering, IEEE 91CH3035-3, September 30 - October 3, 1991, San Diego, CA, pages 62-65.

30. J. R. Miller, ITER magnet designer, conversation at the first Workshop on Reliability and Availability for ITER Magnetics Systems, April 23-24, 1991, Cambridge, Massachusetts.
31. D. K. Owens and M. A. Ulrickson, "Plasma-Wall Interaction: Recent TFTR Results and Implications on Design and Construction of Limiters," Fusion Technology 1986, Proceedings of the Fourteenth Symposium on Fusion Technology, Avignon, France, September 8-12, 1986, pages 61-72.
32. A. Tanga and M. F. Johnson, Statistical Analysis of JET Disruptions, JET-R(91)08, July 1991.
33. C. D. Croessmann and J. B. Whitley, "High Heat Flux Testing of Plasma Facing Materials for Tore Supra," Fusion Technology 1988, Proceedings of the 15th Symposium on Fusion Technology, Utrecht, The Netherlands, 19-23 September 1988, pages 796-802.
34. R. Buende, "Pulsed Versus Steady-State Reactor Operation in View of Safety and Economy," presented at the Seminar on Safety, Environmental Impact, and Economic Prospects of Nuclear Fusion, Erice, Sicily, August 1989.
35. J. Porter, "Cryogenic System for a Superconducting Spectrometer," IEEE Transactions on Nuclear Science, NS-30, August 1983, pages 2909-10.
36. J. M. Beeston et al., "Mechanical Testing of Irradiated Beryllium," presented at the Fifth International Conference on Fusion Reactor Materials, Clearwater, Florida, November 1991, also submitted to Journal of Nuclear Materials.

APPENDIX A

FIRST WALL AND DIVERTOR TILE FAILURE RATE CALCULATIONS

APPENDIX A

FIRST WALL AND DIVERTOR TILE FAILURE RATE CALCULATIONS

The literature has provided enough information to calculate overall failure rates for graphite tiles used in several existing fusion experiments. Joint European Torus (JET), Japan Torus-60 (JT-60), Tokamak Fusion Test Reactor (TFTR), and Tore Supra graphite tile failure rates are given here. I have not found sufficient published information from other machines to perform these graphite tile failure rate calculations. Beryllium tile tests and JET beryllium experience are used to quantify those tile failure rates. There are some assumptions included with these failure rates, and these assumptions will be discussed with the calculations. Overall, the point estimate calculation of number of tile failures divided by the total number of tiles in use and number of pulses (or disruptions) performed in a given time period was used for the failure rate calculation. Variances in the numbers of tiles and the numbers of pulses led to the large uncertainty values I have suggested.

Joint European Torus

JET installed 960 graphite tiles on the inboard walls of the vacuum vessel in January 1985. The tiles are bolted to inconel back plates. Over the next six months, about 1500 successful tokamak pulses were performed, some up to 4.5 MA plasma current. There were also about 350 disruptions in that time period, for 1850 pulses.^{A-1,A-2} Initial inspections after the run showed that three first wall (FW) tiles had minor cracks, either from rough handling on installation or, more likely, from plasma interactions. While these small cracks in the JET tiles are not thought to be debilitating,^{A-3} the presence of cracks can decrease the life of the tiles.^{A-4} Huguet, et al.^{A-2} did note that one of the graphite limiter blocks did have a 25-mm long, 2-mm deep crack in it.

JET has 4 limiters with 8 graphite blocks in each limiter, for a total of 32 limiter blocks. The point estimate failure rates and their assumptions are given below:

Inboard wall tile failure rate	$(3)/(960 \times 1850) = 2\text{E-}06/\text{tile-pulse}$
(predominately cracking)	$(3)/(960 \times 350) = 9\text{E-}06/\text{tile-disruption}$
Limiter tile failure rate	$(1)/(32 \times 1850) = 2\text{E-}05/\text{tile-pulse}$
(cracking failure mode)	$(1)/(32 \times 350) = 9\text{E-}05/\text{tile-disruption}$

The per pulse failure rates assume that the actual pulses are the life limiting factor for the tile failures. Slow acting phenomena, such as crack growth, thermal fatigue, and erosion are contributors for this failure rate. The per disruption failure rates assume that the plasma disruption conditions are the worst environment for the tiles. Runaway electrons, high heat loads and particle fluxes, and eddy current mechanical loads would be the causes of tile failures from disruptions. These assumptions are the same for all of the graphite tile failure rates presented here. More study must be done to know which of these effects are truly the life limiting factors for the tiles.

Due to uncertainties in the numbers of pulses and disruptions used to generate these failure rates, I suggest an error factor of 10 be applied to these estimated values. This means that the upper bound failure rate is an order of magnitude larger than the given point estimates.

Japan Torus-60

JT-60 installed about 13,000 tiles in May 1987.^{A-5} The divertor had about 6000 tiles, and the first wall and limiter had the remaining 7000 tiles. These graphite tiles are bolted to stainless steel support plates. Over the first 1600 pulses with graphite, there were about 500 disruptions. The divertor tiles had 236 faults, mostly cracks. The limiter and FW tiles had 38 faults of graphite tile cracking, spalling and breaking.^{A-6} Heat loads were about 4 MW/m^2 for the limiter and wall, and 10 MW/m^2 for the divertor tiles over 5 to 10 second pulses. The point estimate failure rates are:

Divertor tile failure rate:	$(236)/(6000 \times 1600) = 3\text{E-}05/\text{tile-pulse}$
(predominately cracking)	$(236)/(6000 \times 500) = 8\text{E-}05/\text{tile-disruption}$

Limiter/FW tile failure rate: $(38)/(7000 \times 1600) = 3\text{E-}06/\text{tile-pulse}$
(predominately cracking) $(38)/(7000 \times 500) = 1\text{E-}05/\text{tile-disruption}$

In addition, there were 4 first wall tiles that suffered runaway electron damage by hole boring that displaced the graphite. The failure rate for that failure mode is:

Limiter/FW tile failure rate: $(4)/(7000 \times 500) = 1\text{E-}06/\text{tile-disruption}$
(runaway electron damage)

Due to the variability of the numbers of tiles, i.e. J-60 publications refer to 'tile units' (a tile unit varies from 2 to 10 individual graphite tiles), used to generate these failure rates, I suggest an error factor of 10 be applied to these estimated values.

Tore Supra

The Tore Supra tokamak began its operating life in April 1988 with graphite tiles in place. The tiles are subjected to a continuous 1 MW/m^2 heat load, with pulses lasting from 10 to 30 seconds. There are 7500 graphite tiles on the inner first wall, brazed to square stainless steel water cooling tubes. The damage seen over the first several years is 90 tiles ruptured due to oxidized braze joints, 10 tiles ruptured due to disruptions and runaway electrons, and 75 tiles damaged during mounting (about half of these 75 tiles were damaged by heat from subsequent welding operations adjacent to their locations).^{A-7, A-8} Tore Supra conducted about 5900 pulses over the 1988 to 1990 time frame.^{A-9} The tile failure rate is:

Inner FW tile failure rate: $(90+10)/(7500 \times 5900) = 2\text{E-}06/\text{tile-pulse}$
(all failure modes)

Unfortunately, I have not found enough articles about Tore Supra's disruption history in the literature to provide a good estimate of the number of disruptions to use in further failure rate calculations. The 75 tiles damaged during mounting were not included in the failure rate calculation. Since 1% of the tiles failed, I assumed that there were

pre-operational checks to fix the mounting damage problems. Since the number of pulses I used here may be from a longer time period than that of the reported tile faults, an error factor of 10 or more should be applied to the point estimate tile failure rate.

It is interesting to note that Tore Supra had high heat flux tests performed on their prototype tiles at Sandia National Lab.^{A-10} The tiles that failed after 1000 cycles under a 1.8 MW/m^2 electron beam were extrapolated to have a lifetime of 10,000 cycles at the design heat flux of 1 MW/m^2 . A tile lifetime of 10,000 cycles is a point estimate failure rate of $1\text{E-}04/\text{tile-pulse}$, which is at least an order of magnitude higher than the values I have found here. Current results of tile performance should be pleasing to operations personnel at Tore Supra.

Tokamak Fusion Test Reactor

TFTR mechanically installed 1900 graphite tiles onto inconel backing plates for the bumper limiter in the 1985 time frame. The bumper limiter serves as the inner first wall for TFTR. The inconel plates are cooled by cooling tubes of inconel, brazed to the opposite side of the plate surfaces.^{A-11} Over the time span of 1986 and 1987, the bumper limiter was exposed to 10,000 plasma discharges at up to 20 MW of neutral beam injection and 1000 plasma disruptions. The bumper limiter did not receive much damage in this operating period. In 1987, inspection revealed that some of the inconel guard pieces located on the upper and lower ends of the bumper limiter were melted.^{A-12} Overall, only 6 tiles were reported to be broken from the initial high power neutral beam injection runs. Another 100 tiles were reported to have some surface damage of spallation or cracking, but apparently this was minor damage and did not greatly interfere with tile performance.^{A-13}

Assuming that the high power neutral beam tests were conducted in the 1986-1987 time frame, this gives a bumper limiter (inner first wall) graphite tile breakage failure rate of:

Limiter/FW tile failure rate:	(6)/(10000x1900)	= $3\text{E-}07/\text{tile-pulse}$
(tile breaking)	(6)/(1000x1900)	= $3\text{E-}06/\text{tile-disruption}$

Limiter/FW tile failure rate: $(100)/(10000 \times 1900) = 5\text{E-}06/\text{tile-pulse}$
(predominately cracking) $(100)/(1000 \times 1900) = 5\text{E-}05/\text{tile-disruption}$

Graphite Tile Failure Rate Comparisons

The graphite tile failure rates are generally better than predicted, however, there are some concerns about the causes of tile failures. Dietz et al.^{A-13} discuss tile alignment as a failure cause. The idea, shared by R. Nygren at Sandia National Laboratories,^{A-14} is that the number of tile failures would be much lower if the tiles were aligned to reduce any tile edges protruding up towards the plasma. The early work discussed tile height tolerances of ± 2 mm, but the more recent work by Dietz et al. discusses tolerances of less than ± 0.5 mm being sought by the major tokamaks. It is quite possible that these graphite tile failure rates are more a measure of the number of tiles protruding toward the plasma than random failure rates of the tiles themselves, since the leading edges would see a much more harsh heat loading environment than the tiles are designed for. Nonetheless, it is operating experience from the existing tokamaks, and alignment problems will probably also be seen in future, larger machines. These data can be valuable to predict future graphite tile performance.

Table A-1 shows the failure rates from the various tokamak machines. These failure rates are typically the cracking failure mode, but should be considered as the rates for 'all modes of failure' in lieu of any other data or information. The agreement between failure rates is surprisingly good, considering the variety in each design, the different graphite suppliers, varying heat loads, variety of heat removal systems, and different machine operating times. Note that Tore Supra tiles must be considered separately, since these tiles are actively cooled rather than passively cooled. However, there is the previously stated concern that we are seeing more a measure of tile alignment problems than random tile failures. There is also a concern that the first operating time periods reported on in the literature are not long enough to produce steady state failure rate values for the tiles. These failure rates might still be in the early life region, where tile imperfections cause cracks, and bolting-induced stresses are being relieved.

TABLE A-1. SUMMARY OF POINT ESTIMATE FAILURE RATES FOR GRAPHITE TILES
FROM EXISTING TOKAMAK EXPERIMENTS

<u>Parameter of Comparison</u>	<u>JET</u>	<u>JT-60</u>	<u>TFTR</u>
Tile cracking values for normal plasma operations, per tile-pulse:			
Inner FW tile fail rate	2E-06	3E-06	5E-06
Limiter tile fail rate	2E-05	3E-06	5E-06
Divertor tile fail rate	n/a	3E-05	n/a

Tile cracking values for disruption conditions, per tile-disruption:			
Inner FW tile fail rate	9E-06	1E-05	5E-05
Limiter tile fail rate	9E-05	1E-05	5E-05
Divertor tile fail rate	n/a	8E-05	n/a

Note: JET heat loading is less than 5 MW/m^2 for the FW and limiter,
with pulses of typically 10 s.

JT-60 heat loading is 4 MW/m^2 for the FW/limiter, and 10 MW/m^2
for the divertor, with pulses of 5 to 10 s.

TFTR heat loading is 1.5 MW/m^2 for the bumper limiter, with
pulses of typically 3 - 5 s.

Normal operation rates assume cyclic operation wears tiles, and
disruption-based rates assume only disruptions cause degradation

Note: The JT-60 Limiter and FW tile failure rate for runaway electron
damage is $1\text{E-06/tile-disruption}$

The TFTR broken tile failure rate is 3E-07/tile-pulse and
 $3\text{E-06/tile-disruption}$

Further inspection results from JET, performed in 1986,^{A-15} discussed that there was more minor tile damage, such as heat scorching and small cracks, mechanical stress induced cracking from loads caused by tile mounting pins bending, and runaway electron impacts. Most of the damage seemed to be concentrated at the mid-plane inner wall and octant joint areas. Unfortunately, there was not enough information to calculate new tile failure rates. JET also began using carbon fiber composites (CFCs) rather than fine grain graphite tiles at that time. CFCs appear to handle the tokamak environment much better than graphite blocks. Deitz et al.^{A-13} give uniformly good reports on CFC reliability and survivability as PFCs. A preliminary CFC tile failure rate calculation for TFTR tiles is presented on the following page.

While I have concerns about the time frame for the tile inspections, these values are still the best graphite tile failure rates presently available, and should serve as order of magnitude indicators for any future graphite tile usage.

The TFTR and Tore Supra tile failure rates are the most closely comparable because the cooling method is similar in nature. The Tore Supra heat loading is 1 MW/m^2 for the inboard FW, with pulses of 5 - 10 s. These conditions are close to TFTR's, which has a 1.5 MW/m^2 heat loading and nominal 5-second pulses. The Tore Supra failure rate of $2\text{E-}06/\text{tile-pulse}$ and the TFTR failure rate of $5\text{E-}06/\text{tile-pulse}$ are within a half order of magnitude of each other. Such information is important to future machines, such as Princeton's proposed Tokamak Physics Experiment.

I noted that from their descriptions, care was taken by each of the tile installation teams, including tile non-destructive evaluations to eliminate flawed tiles, thorough cleaning and visual inspection, and careful tile attachment. We see that bolting is much simpler than brazing, since Tore Supra had 1 to 1.5% of the tile brazes fail during installation. There are difficulties with tile brazing, since the majority of the Tore Supra tile faults were due to oxidized brazes.

Tokamak Fusion Test Reactor Carbon Fiber Composite Tiles

TFTR began using carbon fiber composites (CFCs) in 1989. The bumper limiter had 770 graphite tiles replaced with carefully aligned, similar size CFC tiles. CFCs were chosen because there was an expectation that they could better withstand disruption damage, the CFCs could withstand a larger fatigue loading and suffer less spallation damage, and they could accept a higher heat load than fine grain graphite. The TFTR experience with CFCs shows that these tiles have proven the initial speculations that they would be able to better withstand the tokamak environment. The limiter CFC tiles have withstood about 20,000 pulses (7,000 high power neutral beam shots and 13,000 lower power ohmically heated shots) without failure. There has been some surface erosion due to carbon evaporation from high temperatures, but the tiles are still intact enough to continue operations without any thought of replacement. Ulrickson et al.^{A-16} noted that there had been some record severity TFTR plasma disruptions in the two years of CFC tile usage, but the tiles were not damaged.

Conservatively assuming one failure in the 2 year time period, the CFC tile failure rate is:

Limiter CFC tile failure rate: $(1)/(20000 \times 770) = 7\text{E-}08/\text{tile-pulse}$
(for all failure modes)

Considering that there might be as much as 20% disruptions in TFTR operation, then the number of disruptions would be about 4,000. The failure rate per disruptions would be:

Limiter CFC tile failure rate: $(1)/(4000 \times 770) = 3\text{E-}07/\text{tile-disruption}$
(for all failure modes)

I suggest using an error factor of 10 on these failure rates because of the uncertainty in the number of tiles, number of pulses, and number of disruptions. We note that compared to Table A-1, these conservative CFC tile failure rates are typically one order of magnitude lower, if not closer to two orders of magnitude lower than graphite tile failure rates. Overall, CFCs do appear to be more reliable than graphite. Both JET and TFTR personnel endorse CFC tile usage.^{A-13, A-16}

Joint European Torus Beryllium Tiles

JET installed a set of 1,716 beryllium (type S65b) belt limiter tiles in the 1989 shutdown.^{A-17,A-18} Recent information on the success of these tiles gives some values of tile damage. A few tiles were damaged due to highly localized edge loading that resulted from misalignment between the plasma and the limiter (similar to graphite tile problems). These tiles were installed to tolerances of better than 0.5 mm, but apparently, induced forces moved some tiles outward into the plasma by up to 2 mm. About 5% (86 tiles) of the plasma facing area of the entire belt limiter was melted, probably from disruption loads and misalignment edge loads, and another 10-15% (215) showed some damage from localized, abnormal edge loads. None of the beryllium tiles showed deep fissures or cracking, and none of the tiles showed gross mechanical or structural failure. There was also a clear relation of increased wall damage at the degraded toroidal field coil's location.

JET ran about 1300 pulses in 1987, with a typical disruption percentage of about 20%.^{A-1} Assuming a similar number of pulses and disruptions in 1989 gives the following failure rates:

Limiter Be tile failure rate: $(86)/(1716 \times 1300) = 4\text{E-}05/\text{tile-pulse}$
(tile melting failure mode) $(86)/(1716 \times 260) = 2\text{E-}04/\text{tile-disruption}$

Because of the large number of assumptions made for this failure rate, I suggest an error factor of 30 be applied to these values. Tile testing at Sandia National Laboratories^{A-19} showed tile degradation in the form of growing cracks after ten thousand 0.3-s pulses at 25 MW/m². Because the cracks were beginning to link up to form deep, continuous cracks at 10,000 cycles, I choose this cracking as a failure because linked cracks quickly lead to tile structural failure. These data give a point estimate laboratory failure rate of 1E-04/tile-pulse. The actual JET tiles saw an average of less than 2 MW/m² during pulses, and there was usually a thirty minute cooldown time between shots.

The beryllium tile failure rates from JET are not very precise, due to the uncertainty in the actual number of failed tiles and the number of actual pulses and disruptions in 1989. Until more information and operating experience is available for beryllium tiles, I suggest using the laboratory failure rate of $1\text{E-}04/\text{tile-pulse}$, with an error factor of 3. The laboratory failure rate should be very conservative, since the heat loading and pulse repetition rate were both much higher than those seen in tokamak operations, for most pulse and plasma disruption conditions. Even with these conservatisms, the laboratory failure rate value is within a half order of magnitude of the presently calculated JET tile failure rate.

Currently, there is not enough information published on beryllium sprays and/or coatings to make any quantitative assessments as to their reliability. JET experience has been positive, but more study is needed to assess spalling, flaking, melting, and other potential failure modes.

APPENDIX A. REFERENCES

- A-1. B. J. Green et al., "Machine Utilisation and Operation Experience with JET from 1983," Fusion Technology 1988, Proceedings of the 15th Symposium on Fusion Technology, Utrecht, The Netherlands, 19-23 September 1988, pages 1633-1637.
- A-2. M. Huguet et al., "Limiters and First Wall on JET," Proceedings of the 11th Symposium on Fusion Engineering, Austin, TX, November 18-22, 1985, pages 1238-1248.
- A-3. K. J. Deitz et al., "Wall Protection in JET," in: H. Knoepfel, editor, Tokamak Startup, Problems and Scenarios Related to the Transient Phases of a Thermonuclear Fusion Reactor, Plenum Press, New York, 1986, pages 317-323.
- A-4. J. Ohmori et al., "Mechanical Behavior of Graphite First Wall During Disruptions," Fusion Engineering and Design, 9, 1989, pages 207-211.
- A-5. H. Takatsu et al., "Design, Fabrication and Initial Operation of the JT-60 Graphite First Walls," Proceedings of the 12th Symposium on Fusion Engineering, Monterey, CA, October 12-16, 1987, pages 151-154.
- A-6. H. Takatsu et al., "Operation Experiences of the JT-60 First Walls During High-Power Additional Heating Experiments," Fusion Engineering and Design, 9, 1989, pages 3-8.
- A-7. M. Lipa et al., "Brazed Graphite for Actively Cooled Plasma-Facing Components in Tore Supra - Description, Tests, and Performance," Fusion Technology, 19, July 1991, pages 2041-2048.
- A-8. A. Grosman et al., "Tore Supra First-Wall Description and Behavior During the Initial Plasma Experiments," Journal of Nuclear Materials, 162-164, 1989, pages 162-171.
- A-9. A. Grosman et al., "Plasma Edge Control in Tore Supra," Plasma Physics and Controlled Fusion, 32, 1990, pages 1011-1027, and K. J. Dietz et al., "Experience with high heat flux components in large tokamaks," Fusion Engineering and Design, 16, 1991.
- A-10. P. Chappuis et al., "Tore Supra Graphite Inner First Wall," Fusion Technology 1988, Proceedings of the 15th Symposium on Fusion Technology, Utrecht, The Netherlands, 19-23 September 1988, pages 884-888.
- A-11. R. C. Hemlich et al., "TFTR Bumper Limiter and Final Protective Plate Engineering, Fabrication and Assembly," Proceedings of the 11th Symposium on Fusion Engineering, November 18-22, 1985, Austin, Texas, pages 910-912.

- A-12. H. F. Dylla et al., "Material Behavior and Materials Problems in TFTR," Journal of Nuclear Materials, 155-157, 1988, pages 15-26.
- A-13. K. J. Dietz et al., "Experience with high heat flux components in large tokamaks," Fusion Engineering and Design, 16, 1991, pages 229-251.
- A-14. R. E. Nygren, Sandia National Laboratories, private communication, April 9, 1992.
- A-15. M. A. Pick et al., "Experience with Graphite in JET," Proceedings of the 12th Symposium on Fusion Engineering, Monterey, CA, October 12-16, 1987, pages 137-140.
- A-16. M. Ulrickson et al., "Experience with Carbon Fiber Composite Limiter Tiles on TFTR," Fusion Technology, 21, May 1992, pages 1817-1822.
- A-17. G. Celentano et al., "The JET Belt Limiter," Fusion Technology 1986, Proceedings of the Fourteenth Symposium on Fusion Technology, Avignon, France, September 8-12, 1986, pages 581-587.
- A-18. E. Deksnis et al., "Damage to JET beryllium tiles," Journal of Nuclear Materials, 176&177, 1990, pages 583-587.
- A-19. R. D. Watson and J. B. Whitley, "Thermal Fatigue Tests of a Prototype Beryllium Limiter for JET," Nuclear Engineering and Design/Fusion, 4, 1986, pages 49-60.

Distribution

J. Anderson, LANL
J. Bartlit, LANL
C. Baker, ORNL
A. Boschi, ENEA
R. Bünde, IPP
G. Cambi, ENEA
R. Carlson, LANL
R. Conn, UCLA
I. Cook, Culham
J. Doggett, LLNL
V. Chuyanov, Kurchatov
J. Doggett, LLNL
C. Flanagan, ORNL
W. Gauster, SNLA
B. Green, JET
W. Gulden, IPP
R. Hancox, Culham
S. Ho, UCB
J. Holdren, UCB
M. Kazimi, MIT
B. Kolbasov, Kurchatov
J. Levine, PPPL
R. Mattas, ANL
D. Montgomery, MIT
R. Nygren, SNLA
R. Parker, MIT
G. Pearson, UKAEA
P. Petersen, GA
S. Piet, EG&G Idaho
D. Post, PPPL
J. Raeder, IPP
G. Saji, JAERI
K. Schultz, GA
Y. Seki, JAERI
L. Topilski, Kurchatov
R. Watson, SNLA
C. Wong, GA
M. Wykes, JET

END

**DATE
FILMED
9/28/92**