FIELD-FLOW FRACTIONATION OF CHROMOSOMES

Final Technical Report

for Period July 1, 1989 - January 31, 1993

J. Calvin Giddings

University of Utah
Salt Lake City, Utah 84112

April 1993

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

THE U.S. DEPARTMENT OF ENERGY
AGREEMENT No. DE-FG02-89ER60851

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

FINAL TECHNICAL REPORT

Abstract

The first main topic of this project involved the preparation, fractionation by sedimentation/steric FFF, and modeling of metaphase chromosomes. After numerous unsuccessful attempts to prepare chromosomes, we finally implemented a procedure (in collaboration with Los Alamos National Laboratory) to prepare metaphase chromosomes from Chinese hamster cells. Extensive experimentation was necessary to identify a suitable FFF channel surface to minimize chromosome adsorption and a carrier liquid to stabilize and disperse the chromosomes. Under suitable operating conditions, the Chinese hamster chromosomes were purified from cell debris and partially fractionated. The purified, pre-enriched chromosomes that can be prepared by sedimentation/steric FFF or produced continuously by continuous SPLITT fractionation provide an enriched feed material for subsequent flow cytometry.

In the second project component, flow FFF permitted successful separations of (1) single- from double-stranded circular DNA, (2) double-stranded circular DNAs of various sizes, and (3) linear double-stranded DNA fragments of various lengths. Diffusion coefficients extracted from retention data agreed well with literature data as well as predictions of major polymer theories. The capacity of FFF separations was evaluated to examine potential applications to long DNA chains.

The goals of the project evolved during the period of funding, July 1989-January 1993; the organization of the final report reflects that evolution. The original intent of the work was to employ the field-flow fractionation (FFF) family of techniques to separate chromosomes. In the final year of the project, use of a related technique, continuous SPLITT fractionation (CSF), was initiated. The first section of the report describes the preparation, fractionation, and modeling of chromosomes. The importance of isolating DNA fragments for genome work and the obvious suitability of the FFF techniques for DNA fractionation led to expansion of the project to include characterization of linear and circular DNAs by FFF. These results comprise the second section of the report.

I. Chromosome Preparation, Fractionation, and Modeling

The chromosome work may be roughly divided into: (1) chromosome preparation, (2) optimization of FFF instrumentation and procedures, and (3) chromosome modeling for increased understanding of fractionation behavior.

Chromosome Preparation

Sedimentation and flow FFF have been used in the steric/hyperlayer mode to separate spherical particles in the 0.5-50 μm size range that differ in diameter by less than 20%. Therefore, we anticipated good resolution for metaphase chromosomes, which are elongated bodies ranging up to 10-12 μm in length, based on differences in chromosome length. We expected near complete resolution for simple sets of chromosomes; therefore, our goal was isolation of metaphase chromosomes from the cells of organisms having low chromosome numbers. In our attempt to prepare metaphase chromosomes from such

species as drosophila, onion, and human blood cells, we availed ourselves of voluminous advice from experts as well as guidance from literature procedures. The preparations proved to be unexpectedly challenging, possibly due to problems of experience and equipment. Although great effort was expended, we were not successful.

Success in chromosome preparation eventually came as the result of collaboration with the Biomedical Sciences Division of Lawrence Livermore National Laboratory and the Life Sciences Division of Los Alamos National Laboratory. In particular, Dr. Scott Cram and his group (Los Alamos National Laboratory) provided a procedure for isolation of chromosomes from the Chinese hamster. One of our students received on-site instruction in the procedure. A brief summary of this procedure, which has provided the bulk of our chromosomes samples, follows: Chinese hamster cells (cell line Don from ATCC) were grown in McCoy's medium 5A supplemented with 10% fetal calf serum in a 37°C, 5% CO₂ incubator. The cells were metaphase arrested by adding colcemid to the culture medium to a final concentration of 0.1 µg/mL and incubating for 4 hrs. The cells were then swollen in a hypotonic solution containing 40 mM KCl for 10 to 20 min. Metaphase chromosomes were released from swollen cells by shearing with a syringe needle in isolation solution.

Los Alamos has also directly provided us with additional chromosome preparations.

Optimization of FFF Instrumentation and Procedures

The chromosome sizes led us to expect the steric mode operation of FFF, i.e., the mode in which the larger particles elute earlier. Both the sedimentation and flow subtechniques were applied with roughly comparable results. A typical sedimentation system, for example, included an FFF channel 86.5 cm in length, 2 cm in breadth, and either 0.0127 or 0.0254 cm in thickness. Newly constructed channels were characterized with polystyrene latex spheres having diameters similar to the chromosomes. Selection of an appropriate material for the channel accumulation wall required considerable experimentation. Hastelloy-C, the usual material, was unsuitable because of substantial chromosome adsorption. A polyimide coating reduced adsorption as did polyethylene and polypropylene in the presence of Pluronic F108 and Triton X-100 surfactants. Polymethylmethacrylate (PMMA) proved to be the best material to avoid chromosome adsorption.

Extensive experimentation was also required for identification of an appropriate carrier liquid for the chromosome separation which both stabilizes and disperses the chromosomes. The best carrier identified thus far contains KCl and propidium iodide as stabilizers and a nonionic surfactant such as Triton X-100 or Pluronic F108 as the dispersing agent.

A sedimentation FFF fractogram of Chinese hamster chromosomes prepared under the optimized conditions identified to date is shown in Figure 1. The void peak consists of impurities in the samples including DNA and cell debris. Fluorescence micrographs of the numbered peak fractions are shown in Figure 2. The micrographs confirm the steric mode elution order as well as some degree of size differentiation. While a complete separation was not achieved, the partial differentiation combined with removal of interfering impurities constitutes important progress. Specifically, the purified, partially-fractionated chromosome preparations should provide a much improved feed material for subsequent flow cytometry, greatly improving the efficiency of the latter.

Figure 1. A fractogram of Chinese Hamster chromosomes. Channel surface: PMMA. Carrier: 20 mM KCl, 30 μ g/mL propidium iodide, 0.5% Triton x-100. Field strength: 60 g. Flowrate: 1.30 mL/min.

fraction #7

fraction #10

fraction #16

fraction #22

Figure 2. Microscopic photographs of fractions collected as shown in Fig. 1.

Recognition of the importance of the pre-enriched feed material encouraged us to apply continuous SPLITT fractionation (CSF) to the chromosome separation. The separation in CSF, as in FFF, is based on sample components reaching different flow streamlines under the influence of an external field. However, the CSF separation occurs as the streamlines are physically separated at the cell outlet. Such a system is ideally suited to continuous, preparative operation to produce the enriched chromosome material. The efficacy of gravitational CSF of Chinese hamster chromosomes has been confirmed by fluorescence microscopy.

II. DNA Separation

In recognition of the importance of isolating DNA fragments for genome work, we expanded the project to include FFF of DNA. We have addressed the following objectives in an extensive study which has been written up for publication:

"Separation and Measurement of Diffusion Coefficients of Linear and Circular DNAs by Flow Field-Flow Fractionation," M.-K. Liu and J. C. Giddings, *Macromolecules*, in press.

A preprint accompanies this report. The objectives also provide the structure of the summary presented here: (1) Expand FFF applicability to more diverse forms of DNA. (2) Obtain diffusion coefficients for DNA from flow FFF retention measurements. (3) Determine the capacity of FFF for preparative separations. (4) Compare data and FFF theory. (5) Examine potential application to very long DNA chains.

Diverse Forms of DNA

Only a few applications of FFF to DNA have been reported previously. We have enlarged the scope with primarily lower molecular weight ($<10^7$ daltons) DNAs which are separated by virtue of the balance between external driving forces and diffusion, i.e., well-characterized normal mode FFF. Successful flow FFF experiments included: separation of single- from double-stranded circular DNA, separation of double-stranded circular DNAs of different sizes, and separation of linear double-stranded DNA fragments of different lengths. The predicted tradeoff between resolution and separation speed is illustrated by the experiments. Although considerable study of a stopless flow procedure using a frit for sample introduction was conducted, the reported experiments used the traditional triangular channel inlet and the stopflow procedure to allow sample relaxation. The traditional procedure produced narrower peaks.

Diffusion Coefficients

Normal mode flow FFF retention data can readily be used to calculate diffusion coefficients D , friction coefficients f and the hydrodynamic diameter d of DNA in solution. An extensive literature search was undertaken to expand the empirical base of D values for comparison with flow FFF values. In addition, D values derived from theories of wormlike polymer chain structure have been tabulated. DNA species of increasing molecular weight may be progressively described as rod-shaped (Tirado-Garcia de la Torre theory), wormlike chains (Yamakawa-Fujii theory) and random coil chains (Kirkwood-Riseman theory). The theoretical treatment based on radius of gyration and diffusivity (Mandelkern-Flory) was also considered. Agreement between theoretical values and FFF-derived D value agree well over substantial molecular weight ranges.

Preparative Capacity - Overloading

Because flow FFF is an elution technique, it can be easily used in a preparative capacity to obtain purified DNA components. Determinations have been made of the amount of material that can be separated in a single run before "overloading" effects, peak shifts, broadening, and distortions, lead to peak overlap and a loss of purity. For long chain polymers, "overloading" effects are expected to increase with molecular weight because of increasing entanglement of longer chains. The expected trend was observed with both linear and circular DNAs and found to be more severe with the linear chains. In addition, higher sample loads shifted higher molecular weight peaks toward lower retention times, an effect that probably originates in the mutual repulsion of the negatively charged DNA molecules.

DNA Behavior in Flow FFF systems - Theory and Experiment

A more thorough understanding of the steric transition point and lift force effects were deemed necessary to facilitate attempts to separate longer (molecular weight $>10^7$) DNA chains. For a given set of flow conditions, the steric transition point (the point of reversal in FFF elution order) was found to correspond to a DNA molecular weight of 5 to 6 million daltons. Attempts to predict the steric inversion from theories based on radius of gyration and diffusivity gave reasonable agreement with experimental data, with a discrepancy attributable to a lift force effect. Calculations of the lift force effect postulating an entropic lift phenomenon were not more successful in reproducing observed retention data than calculations considering the lift force as being of hydrodynamic origin.

Application of FFF to Long DNA Chains

In addition to the transition to the steric mechanism of FFF, long chain DNAs present formidable experimental challenges which we have begun to address. An attempt was made to reduce shear degradation of long chain DNAs by using FFF channels with a split-inlet or frit for sample introduction instead of the conventional triangular (high shear) configuration. The split-inlet and the frit inlet sample introductions also bypass the need for stopflow relaxation during which the high sample concentration near the accumulation wall may contribute to overloading. Experimental data showed that overloading was indeed the major obstacle to separation of long DNA chains. Even with the experimental modification of a frit outlet to enrich the sample at the outlet, overloading occurred before sample detectability was achieved. The final approach, designed to overcome chain entanglement as well as shear degradation, was to condense DNA into small compact particles prior to separation. Although condensed particles were successfully prepared, as evidenced by electron microscopy, the concentrations were too low to yield a detectable signal.

Reprint removed

END

**DATE
FILMED**

7 / 15 / 93