Report No. DOE/

ROCK MATRIX AND FRACTURE ANALYSIS OF FLOW IN
WESTERN TIGHT GAS SANDS

DOE/MC/21179--T5

DE92 017655

Quarterly Technical Progress Report
January-March, 1985N.R. Morrow
K.R. Brower
J.S. WardNew Mexico Petroleum Recovery Research Center
New Mexico Institute of Mining and Technology
Socorro, New Mexico

Contributors:

Shirleen Bretz
Vijaya Dandge
Mary Graham
Ingrid Klich

DEB 7/28/82

PRRC Report 85-13

Prepared for the Department of Energy
Under Contract No. DE-AC21-84MC21179

MASTER

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Task 1. Advanced Core Analysis

Advanced core analysis includes measurements on the matrix properties of the rock. Matrix properties are important even in fractured wells since it is these properties which determine the rate of gas flow into the fractures.

Cores are being tested from the fluvial, coastal, and paludal zones of the Mesaverde. At least two cores from each of these zones from all three wells will be analyzed. Properties measured include permeability as a function of confining pressure over the range of 500 to 5000 psi. A minimum of two Klinkenberg permeabilities are being determined from at least five data points. Interpretation includes estimates of pore size from gas slippage. Water adsorption and desorption isotherms will be determined for selected samples with data points being obtained at the following relative humidities: 0, 20, 40, 60, 75, 90, 92, 95 and 98.

Porosity measurements from both thin section examination and volumetric measurements are being made. These results will be compared with the porosities of the cored intervals determined from logs.

Progress

Core samples received to date are listed in Table 1. This table also provides a summary of the analyses performed to date on these samples.

Surface area measurements: Surface areas are being measured using a Quantachrome Monosorb unit on new samples as they are received. In addition, comparisons have been made between the surface areas of whole and crushed samples from the same whole core (Table 2). The crushed samples tend to give somewhat higher surface areas than uncrushed samples, but this is not always the case. Variations within a single whole core may account for some of the differences observed as shown by the two uncrushed samples of MWX3 67-35. Results for a single sample are repeatable to within $\pm 0.3 \text{ m}^2/\text{gm}$ or better.

Clay analysis: Fluvial zone samples including MWX1 10-13, MWX1 22-20, MWX2 17-22, MWX2 47-34, MWX3 58-14, and MWX3 60-19 have been ground

and slides of oriented clay mineral aggregates prepared. These will be used for x-ray analysis to determine which clay minerals are present in these samples.

Impregnation of Low Permeability Sandstones: Significant discrepancies have been noted in porosity measurements. In our experience visible porosities from thin section are almost always lower than those measured by routine core analyses.¹ This probably results from inadequate resin impregnation techniques employed by commercial petrographic labs.

Sandstones from the Multiwell drill holes commonly range from 2-90 microdarcies permeability. We have found that some standard impregnation procedures result in resin penetration for only a minute distance (sometimes less than 1 mm) down from the surface of such low permeability rocks. Thus, thin sections cut at slightly deeper levels may not represent a completely impregnated section.

An impregnation procedure is now being used which to date has given complete penetration by "Scotchcast" resin for samples having permeability as low as 15 microdarcies. Surface penetration depths of 2-3 mm are attainable for samples in the 2-15 microdarcy range and this should be adequate for thin sectioning. The procedure involves injection of a dyed resin into core samples under high pressure. Use of "Scotchcast" resin also requires that the system be kept at 95°C to reduce the resin viscosity to 100 centipoise. However this involves a compromise because increased temperature which increases the rate of setting of the resin and thus reduces the time available for penetration.

Individual specimens are evaluated simultaneously along with the resin in a vacuum oven. The sample is then immersed into the resin and a pressure of 1000 psi is applied for 1 to 1.5 hours. Helium is used as the pressurizing gas because of its low solubility in the resin. The temperature is raised to 120°C for 2-4 hours to allow the resin to cure thoroughly. After cooling to room temperature, the sample is ground and polished and then sent to a commercial laboratory for thin sectioning.

This procedure should also give more consistent results for preparation of etched pore casts since the resin penetrates much deeper beneath the surface than previously.

Task 2. Flow Along and Across Fractures

Sometimes production from low permeability gas sands is much higher than could be expected from the properties of the rock matrix as determined by core analysis. The presence of natural fractures is often cited as a key factor in gas production for both fractured and unfractured wells. Vertical fractures have been found in some of the cores recovered in the Multiwell project. The cores show that by far the majority of fractures become filled with calcite cement.

As part of this project, flow measurements are being made along and across selected fractured samples as a function of overburden pressure for a minimum of five core samples. Comparative measurements will be made on unfractured neighboring zones of a given whole core sample. Permeability measurements will be made at a minimum of four levels of water saturation for each of at least six samples to assess the effect of water content on permeabilities in fractured systems. The effects of chemical treatments on mineralized fractures will be studied to assess whether such treatments lead to permeability enhancement or formation damage.

Progress

Core samples containing calcite filled fractures have recently been obtained. Planned tests on these samples are listed in Table 3.

Cores containing fractures were not available from several zones of interest. However, some observations on gas flow at high water saturations suggest that low permeability sandstone may contain preferential flow paths other than fractures. Preliminary observations have been made on a whole core. A narrow hole was drilled to approximately the center of a whole core sample (about 4 1/2" diameter by 3" long) and a piece of stainless steel tubing was cemented into the hole. The core was submerged in water and nitrogen was injected through the stainless steel tube at a pressure of about 30 to 60 psi. Gas bubbles evolved primarily at freshly cut surfaces but not at surfaces exposed to drilling mud. Distribution and size of the bubbles was very inhomogeneous; a few points on the surface continually produced bubbles of much larger size than did the remainder of the surface. With time, additional points of gas production appeared and flow rates, as indicated by bubble size, increased at some points. From this qualitative experiment it appears that preferential gas flow paths exist even in the absence of visible fractures.

A more quantitative measurement of preferential flow has also been tested. Helium is used as the flowing gas and production at different points of the outflow face of a small core sample is monitored by means of a thermal conductivity detector. By minimizing the size of the sampling tube and mounting it on an x-y positioning stage, the relative amounts of helium emerging from the core face can be mapped. Preliminary results using a 0.1 mm stainless steel capillary sensing tube confirm that gas is steadily produced in a few preferential streams.

Task 3. Chemical Alteration

Chemical alteration of various mineralogical components and resultant effects on permeability will be investigated. Experiments will include the use of various reagents, including weak acids (e.g. acetic acid), strong acids (e.g. HClO_4), alkali, and chelating agents (e.g. EDTA). The objective of this work is to determine which features of pore structure determine flow properties and also to explore new possibilities for chemical stimulation of low permeability gas sands.

Progress

A summary of work carried out so far on the effects of chemical treatments is presented in Table 4.

Currently, the fine structure of low permeability gas sands is being investigated through study of the effect of firing on surface areas and adsorption. Table 5 contains comparisons between several samples from the MWX2 48-9 whole core. Samples were fired for 2 or more hours each at temperatures of 500°, 600°, 700°, 800°, 900°, and 1000°C. Surface area measured by N_2 adsorption is highest for the core fired at 600°C; it then decreases steadily. Accompanying changes in other core properties such as permeability and clay content are also being investigated.

Task 4. Effect of Water on Gas Production

Water is known to modify greatly the flow of gas in tight sand and is a key factor in gas production. Permeability to gas will be measured at various levels of water saturation established by equilibration of core samples in humidity chambers. Electrical resistivity at various levels of water saturations and confining pressures will also be measured. Special attention will be given to water distribution within the rock pore space. Circumstances under which water can act to inhibit gas production and the pressure differences necessary to overcome capillary seals formed by water will also be investigated. Capillary pressure measurements will be made using a high-speed centrifuge.

Progress

Relative permeability measurements: Last quarter, relative permeabilities to gas in the presence of a partial water saturation were reported for four Multiwell samples (MWX3 66-17, MWX3 64-29, MWX3 67-16, and MWX3 67-35).² Two levels of confining pressure (500 and 5000 psi) and several water saturations (0, 15, 30, 45 and 60 percent) were used in the measurements for each of these samples.

Comparison of these results with those reported previously in the literature³⁻⁷ requires abstraction of results reported graphically either as permeability or relative permeability on either linear or logarithmic scales. This has been accomplished and the results are shown in Figure 1. Open symbols are those obtained at low confining pressures (500 psi and below); filled symbols show data where confining pressures were in the range of those expected under in situ conditions. Both our data and those in the literature showed lower relative permeabilities generally for measurements under higher confining pressures. A reasonable estimate of the relative permeability to gas at high confining pressures is provided by the form of Corey relationship⁸ used by Sampath and Keighin⁶ shown in Figure 1 as a solid line. Suggested means of estimating relative permeability to water are also indicated. Detailed discussion is provided in a recently prepared SPE Preprint (13882).⁹

Capillary pressure measurements: Extensive high-speed centrifuge and desorption data are presented in preprint SPE 13882, to be presented May 21 at the 1985 SPE/DOE Low Permeability Symposium. Detailed comparisons of replicate centrifuge experiments and data analysis methods are included in this paper.

REFERENCES

1. Morrow, N.R., Brower, K.R. and Kilmer, N.H., "Relationship of Pore Structure to Fluid Behavior in Low Permeability Gas Sands," Final Report, DOE/BC/10216-13 (DE84012721), U.S. Department of Energy, Bartlesville, Sept. 1984.
2. Morrow, N.R., Brower, K.R., Kilmer, N.H. and Ward J.S., "Rock Matrix and Fracture Analysis of Flow in Western Tight Gas Sands," Quarterly Technical Progress Report for DE-AC21-84MC21179, Sept. to Dec. 1984.
3. Byrnes, A.P., Sampath, K. and Randolph, P.L., "Effect of Pressure and Water Saturation on Permeability of Western Tight Sandstones," paper presented at 1979 DOE Symposium on Enhanced Oil & Gas Recovery and Improved Drilling Technology, Tulsa, Aug. 22-24.
4. Thomas, R.D. and Ward, D.C., "Effect of Overburden Pressure and Water Saturation on Gas Permeability of Tight Sandstone Cores," J. Pet. Tech. (Feb. 1972), 120.
5. Walls, J.D., Nur, A.M. and Bourbie, T., "Effects of Pressure and Partial Water Saturation on Gas Permeability in Tight Sands: Experimental Results," J. Pet. Tech. (April 1982), 930.
6. Sampath, K. and Keighin, C.W., "Factors Affecting Gas Slippage in Tight Sandstones of Cretaceous Age in the Uinta Basin," J. Pet. Tech. (Nov. 1982), 2715.
7. Walls, J.D., "Measurement of Fluid Salinity Effects on Tight Gas Sands With a Computer Controlled Permeameter," paper SPE 11092 presented at the 1982 Annual Fall Technical Conference and Exhibition, New Orleans, Sept. 26-29.
8. Corey, A.T., "The Interrelation Between Gas and Oil Relative Permeabilities," Prod. Monthly (Nov. 1954), 38.
9. Ward, J.S. and Morrow, N.R., "Capillary Pressures and Gas Relative Permeabilities of Low Permeability Sandstone," paper SPE/DOE 13882 presented at 1985 SPE/DOE Low Permeability Symposium, Denver, May 20-22.

Table 1
MULTI-WELL SAMPLES

Well	ID	Depth (ft)	Geologic Zone	Gas Permeability	Relative Permeability	Adsorption- Desorption	Surface Area	Clay Analysis	Pore Cast	Electrical Resistivity	Thin Section
NWX-1	3-11	4319.4-4320.4	PAR						x		
NWX-1	3-21	4308.3-4309.1	PAR						x		
NWX-1	8-16	4548.4-4548.9	FM						x		
NWX-1	10-13	4699.7-4700.5	FM	x		in progress	x	in progress	x		
NWX-1	13-15	4851.0-4851.5	FM								
NWX-1	22-20	5357.2-5357.7	FP	x		in progress	x	in progress	x		
NWX-1	29-24	5725.7-5726.6	FP						x		
NWX-2	17-22	4937.0-4937.8	FM	x		in progress	x	in progress	x		
NWX-2	47-34	4195.5-4916.6	FM	x		in progress	x	in progress	x		
NWX-1	14-24A	4917.9-4918.2	FM						x		
NWX-1	14-24B	4918.2-4918.9	FM						x		
NWX-3	58-14	4918.1-4918.7	FM	x		in progress	x	in progress			
NWX-3	60-19	5726.3-5726.8	FP	x		in progress	x	in progress			
NWX-3	63-16	5832.1-5832.6	FP								
NWX-3	64-29	6464.5-6465.0	CO	x	x	x	x				
NWX-3	66-17	6893.4-6893.8	PAL	x	x	x	x				
NWX-3	67-16	7096.1-7096.7	PAL	x	x	x	x				
NWX-3	67-35	7134.2-7134.6	PAL	x	x	x	x				
NWX-3	68-15	7551.2-7551.7	SH								
NWX-1	3-25	4330.7-4331.6	PAR	x		x	x				
NWX-1		6402.1-6402.7	CO								
NWX-1		6435.3-5436.1	CO								
NWX-1		6502.7-6503.2	CO								
NWX-1		6536.5-6537.1	CO								
NWX-2		6432.6-6433.2	CO								
NWX-2		6452.5-6453.0	CO								
NWX-2		6471.5-6472.3	CO								
NWX-2		6507.4-6508.0	CO								
NWX-2		6537.0-6537.9	CO								
NWX-2		7119.4-7120.3	PAL								
NWX-2		7139.2-7139.9	PAL								
NWX-2		7278.9-7279.7	PAL								
NWX-3		6445.0-6445.8	CO								
NWX-3		6461.1-6461.8	CO								

KEY TO GEOLOGIC ZONE: CO = Coastal FM = Fluvial (Meander belts) FP = Fluvial (Point bars) PAR = Paralic
SH = Shoreline/Marine

Table 2
Surface Area Measurements

<u>Sample Designation</u>	<u>BET Surface Area (m²/g)</u>	
	<u>Uncrushed</u>	<u>Crushed</u>
MWX1 42-25		1.96
MWX2 51-19		2.38 ± 0.26
MWX3 64-29	3.21	4.35
MWX3 66-17	1.69	2.50 ± 0.13
MWX3 67-16	3.33	3.50
MWX3 67-35	Sample 1 3.35	3.02
	Sample 2 1.66 ± 0.18	
MWX1 3-25	1.11	1.04

Table 3 MULTI-WELL FRACTURED SAMPLES

Well	ID	Depth (ft)	Geologic Zone	Gas Permeability				Relative Permeability				Surface Area			
				V*	V	H*	H	V*	V	H*	H	V*	V	H*	H
MWX-1	13-18	4846.5-4847.0	FM	x	x	x	x	x	x			x	x	x	x
MWX-1	16-11	5034.8-5035.2	FM												
MWX-1	21-4A	5271.6-5272.0	FP	x	x										
MWX-1	29-31	5730.9-5731.2	FP	x	x							x	x	x	x
MWX-1	29-7B	5733.2-5733.6	FP	x	x	x	x					x	x	x	x
MWX-1	34-10	6002.3-6002.5	CO	x	x	x	x								
MWX-1	38-27	6192.6-6193.0	CO												
MWX-1		5735.8-5736.0	FP												
MWX-2		5764.0	FP												
MWX-3		6459.2-6460.0	CO												
MWX-3		6511.9-6512.4	CO												

Key to Geologic Zone: CO = Coastal
FM = Fluvial (meander belts)
FP = Fluvial (point bars)

V* = vertical; cored along the fracture
V = vertical; without the fracture
H* = horizontal; cored across the fracture
H = horizontal; without the fracture

Table 4 MULTI-WELL FRACTURED SAMPLES
(ACID TREATED)

Well	ID	Depth (ft)	Geologic Zone	Gas Permeability				Relative Permeability				Surface Area			
				V*	V	H*	H	V*	V	H*	H	V*	V	H*	H
MWX-1	13-18	4846.5-4847.0	FM	x								x			
MWX-1	16-11	5034.8-5035.2	FM												
MWX-1	21-4A	5271.6-5272.0	FP												
MWX-1	29-31	5730.9-5731.2	FP												
MWX-1	29-7B	5733.2-5733.6	FP												
MWX-1	34-10	6002.3-6002.5	CO												
MWX-1	38-27	6192.6-6193.0	CO												
MWX-1		5735.8-5736.0	FP												
MWX-2		5764.0	FP												
MWX-3		6459.2-6460.0	CO												
MWX-3		6511.9-6512.4	CO												

Key to Geologic Zone: CO = Coastal

FM = Fluvial (meander belts)

FP = Fluvial (point bars)

V* = vertical; cored along the fracture

V = vertical; without the fracture

H* = horizontal; cored across the fracture

H = horizontal; without the fracture

Table 5

BET Surface Areas for MWX2 48-9

<u>Treatment</u>	<u>Surface Area (m²/g)</u>
none	1.61
500°C	2.85
600°C	3.37
700°C	2.57
800°C	1.62
900°C	0.91
1000°C	0.17

COLLECTED RELATIVE PERMEABILITIES

Figure 1. Gas relative permeability results for tight sandstones and example of estimated relative permeability for the wetting phase.

**DATE
FILMED
8/26/92**