THE DEVELOPMENT OF AN INTEGRATED MULTISTAGE FLUID BED RETORTING PROCESS

Technical Report for the Period

January 1, 1992 - March 31, 1992

By

S. Carter
J. Stehn
A. Vego
D. Taulbee

May 1992

Work Performed Under
Cooperative Agreement No:
DE-FC21-90MC27286

For

U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center

By

University of Kentucky
Center for Applied Energy Research
Lexington, Kentucky

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

APR 06 1992

ABSTRACT

This report summarizes the progress made on the development of an integrated multistage fluidized bed retorting process (KENTORT II) during the period of January 1, 1992 through March 31, 1992 under Cooperative Agreement No. DE-FC21-90MC27286 with the Morgantown Energy Technology Center, U.S. Department of Energy. The KENTORT II process includes integral fluidized bed zones for pyrolysis, gasification, and combustion of the oil shale. The purpose of this program is to design and test the KENTORT II process at the 50-lb/hr scale.

The design of the 50-lb/hr KENTORT II retort was completed and fabrication is ready to begin. Data from the cold-flow model of the system and operating experience from the 5-lb/hr unit were used as the basis for the design. In another aspect of the program, a study of the cracking and coking kinetics of shale oil vapors was continued. A mathematical model was implemented to characterize the important mass transfer effects of the system. This model will be eventually broadened to become a general fluidized bed coking model. In addition, experiments were performed to examine the effects of surface area, initial carbon content and steam treatment on coking activity. From the data that has been collected to-date, it appears that the coking activity of the tested substrates can be explained in terms of porosity (surface area and pore volume) and the initial carbon content of the solid.

ACKNOWLEDGMENT

The work described herein was performed at the University of Kentucky Center for Applied Energy Research under Cooperative Agreement DE-FC21-90MC27286 with the Laramie Project Office of the Morgantown Energy Technology Center (METC), U.S. Department of Energy.

TABLE OF CONTENTS

LIST OF FIGURES	v
LIST OF TABLES	v
INTRODUCTION AND BACKGROUND	1
OBJECTIVES	3
DESIGN OF 50-LB/HR KENTORT II RETORT	4
Process Overview	4
Reactor Design	6
Reactor Material Selection	6
Seals Between Reactor Sections	6
Reactor Assembly	8
Pyrolyzer Design	10
Gasifier Design	10
Cooling Zone Design	11
Combustor Design	11
Summary	16
CRACKING AND COKING KINETICS	17
Approach	17
Introduction	17
Model Development	18
Parameter Estimation	20
Nomenclature	23
Experimental	25
Apparatus	25
Procedure	27
Materials	27
Results and Discussion	30
Numerical Modeling	30
Experimental Results	35
Conclusions	37
REFERENCES	39

LIST OF FIGURES

Figure 1.	Schematic diagram of the 50-lb/hr KENTORT II process.	5
Figure 2.	Spring energized c-ring.	7
Figure 3.	Gas distributor mount.	8
Figure 4.	Assembly view of KENTORT II reactor.	9
Figure 5.	Pyrolyzer.	12
Figure 6.	Gasifier.	13
Figure 7.	Cooling zone.	14
Figure 8.	Combustor.	15
Figure 9.	Schematic diagram of the fluidized bed coking and cracking kinetics apparatus.	26
Figure 10.	Base case numerical solution of model. Temperature, 873K; Fluidizing gas, nitrogen; Bed height, 7.6 cm; no chemical reaction. Units are dimensionless except for time.	31
Figure 11.	Numerical solution to model with $d_p=0.12$ cm.	32
Figure 12.	Numerical solution to model under base case conditions with chemical reaction.	34
Figure 13.	Carbon deposition onto low-carbon content substrates as a function of meso- and macro-surface area. 10 minutes solid residence time; 12 g/minute raw shale feedrate; 75 g charge of substrate.	36
Figure 14.	The effect of initial carbon content of the substrate on subsequent carbon deposition.	37
Figure 15.	Effects of steam on the coking activity of combusted oil shale.	38

LIST OF TABLES

Table 1.	Ultimate Analyses (As-Received Basis) of the Raw Oil Shale and Coking Substrates (wt%).	28
Table 2.	Surface Area (m^2/g) and Pore Volume (cm^3/g) of Coking Substrates as Determined by Hg Porosimetry (macro and meso).	29

INTRODUCTION AND BACKGROUND

It is now well accepted that fluidized bed pyrolysis of oil shale at near-zero hydrogen partial pressure will generate higher than Fischer assay oil yields. This enhancement varies according to shale type, but for most shales of the world it can be significant, and the oil shales contained in the U.S. are not exceptions. It has been shown that fluidized bed pyrolysis of eastern and western U.S. oil shales can enhance oil yields by 50%^{1, 2, 3, 4, 5} and 10%^{6, 7} above Fischer assay, respectively. In addition, fluidized bed technology offers the advantages of rapid pyrolysis kinetics (short solid residence time), total use of mined shale, and thermal efficiency. The Center for Applied Energy Research (CAER) has developed a commercial retorting concept, KENTORT II, which is based on fluidized bed technology. This process has been successfully demonstrated in a 3-inch diameter, 5-lb/hr system at the CAER using eastern U.S. oil shale.⁸ The objective of the current program is to scale the KENTORT II process to a 6-inch diameter, 50-lb/hr reactor.

Approximately 40% of the original carbon remains in the spent shale following fluidized bed pyrolysis of Eastern shale. This is more carbon than is required to provide process heat, and an intermediate gasification stage was included in the KENTORT II design to utilize this excess carbon for synthesis gas production. The gasification section is also important because it permits steam/iron sulfide reactions to go nearly to completion. These reactions remove the majority of the sulfur from the shale in the case of eastern shale because approximately 90% of its sulfur is present as iron sulfides. The removal of sulfur from the shale as H_2S prior to combustion creates a relatively concentrated stream of H_2S which is easier to scrub than a dilute stream of SO_2 from combustion. The H_2S serves as feedstock for elemental sulfur production which improves process economics because of the by-product credit. For shales which do not contain large amounts of residual carbon and/or iron sulfides following pyrolysis, the gasification step is not plausible.

Following gasification, the remaining carbon in the shale is combusted to provide process heat. The heat of combustion is transferred to the gasification and pyrolysis zones via recirculation of the processed shale because sufficient heat cannot be transferred using gases alone. Following combustion, essentially all of the carbon and sulfur in the shale have been removed. This has important environmental implications because the potential for acid drainage by the disposed spent shale is significantly reduced when the sulfur content is low.^{9, 10}

Operation of the KENTORT II process was shown to be viable at the 5-lb/hr scale during the previous cooperative agreement, but because of the small size of the unit, questions relative to scale-up remain. A critical issue is the effect that scale-up will have on the physical operation of the multi-stage fluidized bed system. To reduce the risks of scale-up, a cold-flow model of the unit was built and tested. The important features of the components of the successfully operated cold-flow model were then

incorporated into the designs of the reactor vessels which were completed this quarter. Another consideration is the effect of scale-up on the magnitude of solid-recycle induced cracking and coking losses in the pyrolysis zone. A study of the kinetics of cracking and coking over various process solids was continued, and the development of a fluidized bed coking model was initiated this quarter.

OBJECTIVES

The primary objective of this program is to perform the research necessary to design, construct and test the KENTORT II process at the 50-lb/hr scale. The tasks for the program are listed below:

Task 1 - Design and Construction of the KENTORT II Prototype Unit

- 1.1 - Cold-Flow Modeling of the Reactor
- 1.2 - Mini-Plant Investigation of Solids Recycle (Cracking and Coking Kinetics)
- 1.3 - Final Design and Construction of the KENTORT II Prototype Unit

Task 2 - Operation of the Prototype Unit

- 2.1 - Reactor and System Shakedown
- 2.2 - Prototype Operational Runs

Task 3 - Shale Acquisition and Product/By-Product Characterization

- 3.1 - Collection and Characterization of the Oil Shale Feedstock
- 3.2 - Characterization of the KENTORT II Materials and Products for Utilization and Environmental Characteristics
 - 3.2.1- Characterization of KENTORT II Products for Asphalt Application
 - 3.2.2- Characterization of Nitrogen and Mineralogic Transformations in the KENTORT II Process
- 3.3 - Economic Evaluations

Efforts were directed toward subtasks 1.2 and 1.3 during this reporting period. The objective of subtask 1.2 is to gain a better understanding of the kinetics of cracking and coking of shale oil vapor over recycled shale in the KENTORT II process. With this knowledge, the design and operation of the solid-recycle loop to the pyrolyzer may be adjusted to minimize oil losses. With the results from subtasks 1.1 and 1.2 available, it is the objective of subtask 1.3 is to complete the design of the 50-lb/hr retort.

DESIGN OF 50-LB/HR KENTORT II RETORT

Process Overview

The KENTORT II process is a fully integrated four-stage fluidized bed oil shale retort. The pyrolysis, gasification and cooling zones are aligned vertically and share a common fluidizing gas. The combustion zone is adjacent to the gasification section and a separate gas stream (air) is used for fluidization (see Figure 1). All beds are designed to operate in the bubbling mode, and cold-flow studies have shown that a gas velocity of about 3 ft/s provides proper fluidization for an 8 x 60 mesh particle size range.¹¹

Raw shale at a rate of 50-lb/hr is fed over-bed to the pyrolysis zone which is the uppermost bed of the reactor. The fluidizing medium is a mixture of steam and product gases from the gasification stage below. Heat is provided to the pyrolysis section by a combination of fluidizing gas and recirculating solids from the gasification zone which are injected directly into the bed. Some initial segregation of the raw shale and hot, recycled shale is beneficial in order to reduce high temperature secondary reactions. The pyrolysis zone is baffled to narrow the particle residence time distribution. The design conditions for the pyrolyzer are: temperature, 500-550°C; raw shale feedrate, 50 lb/hr; mean shale residence time, 3 minutes; bed depth, 12 inches; maximum solid recirculation rate, 200 lb/hr.

Shale from the pyrolysis zone is transferred to the gasifier section via a downcomer. The bed depth in the gasification zone is designed to be adjustable between 15-30 inches so that solid residence time may be adjusted from 30 to 60 minutes. The design temperature range for the gasification zone is from 750 to 850°C. Hot solids from the combustor enter the lower part of the bed at a rate of up to 500 lb/hr to heat the gasification zone. Steam from the cooling section below is used as the fluidizing medium.

A downcomer transfers shale from the gasification zone to the cooling zone which also serves to preheat the steam that fluidizes the gasification bed. The cooling zone is the primary exit point for solids from the reactor. An overflow outlet in the wall of the vessel creates a 15-inch deep bed.

The combustor provides all the heat required for the pyrolysis and gasification sections of the KENTORT II process. The gasification and the combustion zones are closely aligned to facilitate the transfer of solids. To minimize mixing of the gas streams, however, the pressure between the two vessels is balanced. The bed depth in the combustor is determined by the height of an overflow standpipe. The design bed depth is 12 inches, although this can be adjusted from 6 to 24 inches if necessary. The combustor is fueled primarily by carbon-containing shale which is recycled from the gasification section via a pneumatic lift pipe. Fines recovered by the pyrolysis cyclone are fed into the combustion bed to provide additional fuel. Air is used for fluidization in the combustor.

Figure 1. Schematic diagram of the 50-lb/hr KENTORT II process.

Reactor Design

During 1991, a full-scale cold-flow model of the 50-lb/hr reactor was built and tested. It was demonstrated that the operation of the unit was stable for three selected particle size distributions (8 x 20, 20 x 60, and 8 x 60 mesh) at a design throughput rate of 50 lb/hr. The positions and nozzle geometries of the inlet and outlet ports and the sizing of downcomers were taken from the cold-flow study for use in the design of the retort. Translation of the cold-flow design to the high-temperature conditions of the retort required additional information, especially for the selection of materials of construction. The combination of elevated temperatures and corrosive atmospheres made the choices of construction materials challenging.

Reactor Material Selection. Previous experience⁸ with the 5-lb/hr retort demonstrated the inherent material problems associated with the combination of high temperatures and corrosive gases that characterize the different zones of the KENTORT II process. Rapid scaling and spalling was observed for type 304 SS that was exposed to the fluidized bed region of the gasification section. By aluminizing the base metal of the 5-lb/hr retort, however, it was shown that corrosion could be effectively reduced to acceptable levels. Aluminizing is a process where aluminum diffuses at high temperature into the surface of a base metal for a minimum depth of 100 microns producing an aluminum-rich alloy on the surface.

Because of the success of the aluminized metal at the 5-lb/hr scale, this measure of corrosion protection was adopted for the 50-lb/hr retort. The base metal used for some of the internals of the 5-lb/hr reactor, however, displayed evidence of high-temperature failure, so heat-resistant base metals were a requirement for critical areas of the reactor. Commonly used high-temperature alloys such as Inconel and Hastelloy were rejected because of possible difficulties during fabrication. Furthermore, high-nickel alloys do not necessarily provide protection against the type of sulfidation that has been evident in the 5-lb/hr reactor, so the additional expense for these types of materials would be wasted. Other alloys such as cast stainless steels were also considered. While the cast stainless steels are relatively inexpensive, have very high tensile strength and creep resistance at elevated temperatures, the fracture toughness is poor. The alloy which appears to most closely meet all of our requirements, however, is TP 316H stainless steel. This alloy is covered under ASTM A312 as a modification of grade TP 316 and is intended for high temperature service.¹² This material will be used for the shell of the reactor vessel.

Seals Between Reactor Sections. The sections of the KENTORT II unit are separated by gas distributors which are sandwiched between standard ANSI 150-lb flanges. The selection of the type of device to seal the sections of the reactor is, again, made difficult by the high-temperature, corrosive conditions of the KENTORT II system. A test rig which was made from two 3-inch 150-lb flanges was utilized for evaluating different sealing devices. Ceramic fiber sheets and ropes were tested and were found not

to provide a quality gas-tight seal. A ceramic based gasket forming compound was tested and was found to be woefully inadequate for sealing large flanges. A gasket made from Grafoil, a flexible graphite material, was also tested. Grafoil is rated for temperatures up to 3000°C, but only under neutral atmospheres. When exposed to air at temperatures above 525°C on the outer surface of the gasket, the graphite material burned and disintegrated. While Grafoil may be unsuitable for the highest temperature flanges, it will be appropriate for the less severe areas of the reactor such as the thermowell ports.

NASA Lewis Research Center provided four custom-made metallic o-rings for testing purposes. The o-rings were fabricated from 5/16-inch stainless steel tubing which was joined at the ends with an electron beam weld. To accommodate the metallic o-ring, the sealing surface of the test rig was smoothed to a roughness of 32 micro-inches. Subsequent tests showed that the o-rings did seal properly, but they required heavy torquing and were not reusable after being thermally cycled.

Two spring energized metallic c-rings (see Figure 2) were obtained for testing purposes. The c-rings consist of a limiting plate and a spring-energized seal. The limiting plate, made from a 300 series stainless steel, centers the seal between the mating flanges and eliminates the need for a groove in the flange. The seal consists of an Inconel X-750 spring inside a c-shaped Inconel X-750 jacket, which is nickel coated. The nickel coating has dual functions: it penetrates the imperfections of the mating surfaces to improve sealing capability and increases the corrosion resistance. Tests conducted with the prototypes showed that the c-rings provided a quality seal, and are reusable after thermal cycling. The c-rings were, therefore, selected for use in the 50-lb/hr retort.

Figure 2. Spring energized c-ring.

Since the c-rings cannot be aluminized, protection against corrosion was an important consideration. If the seal is directly exposed to the shale particles, especially in the gasification zone, the potential for corrosion is increased. By using an extension ring to mount the gas distributor above the c-ring (see Figure 3), the seal becomes isolated from the solids. Since the c-ring is at the bottom of the fluidized bed, the concentration of corrosive gases is low and sulfidation is not expected to be a problem.

Reactor Assembly. Figure 4 shows an assembly view of the main body of the KENTORT II system. The gasification and combustion sections are each mounted at the same level above the floor (10 feet) so that thermal expansion will have a minimal effect on the connecting pipes between the sections. Expansion joints are still required, however, for connection to downstream equipment and connections between sections. The scaffold which supports the reactor system is constructed of eight 4 x 4-inch, 22 feet-long columns which are tied together with channel-type bars.

The main reactor sections are sealed with the aforementioned spring energized c-rings. The inlet and outlet ports for the solid recirculation loops which link the pyrolysis, gasification, and combustion zones will also be sealed with c-rings because of the high temperatures. Temperature and pressure ports are located at 6-inch intervals within each fluidized bed and at 1 foot intervals in the freeboard areas. These ports consist of 1/2-inch schedule 40 pipe with 150-lb flanges. The temperature of these flanges will be below 525°C, so Grafoil gaskets can be used. All ports extend approximately 5 inches

Figure 3. Gas distributor mount.

Figure 4. Assembly view of KENTORT II reactor.

from the vessel wall so that a 4-inch layer of insulation can be installed without restricting access to the ports. High-temperature electrical heating elements will be placed beneath the layer of insulation surrounding the pyrolysis, gasification, and combustion zones to compensate for heat loss and to aid the preheating of the system.

Pyrolyzer Design. The pyrolysis section is 6-feet tall and consists of 6-inch schedule 40 pipe. A modified 8-inch 150-lb flange for mating with the gasifier is connected to the bottom of the pipe (see Figure 5). A 46-inch tall baffle splits the pyrolysis zone into two equally sized beds to narrow the residence time distribution of the solids. Raw shale is introduced above the bed through an angled 1-inch pipe on one side of the baffle, and shale exits the zone through a downcomer, which is attached to the distributor, on the other side of the baffle. There are 12 ports along the vertical axis (6 on each side of the baffle) which will accommodate a combined thermowell and pressure tap assembly.

The recirculation inlet to the pyrolysis zone is a 1-inch pipe (Fig. 5, section A-A), which is connected directly to the lift pipe from the gasifier. It is placed 3.5 inches above the gas distributor. This position was successfully tested on the cold-flow model and is incorporated into the final design.

The fluidizing gas and product vapors leave the pyrolysis zone through a 2-inch pipe at the top of the vessel (Fig. 5, section A-A) and enter a cyclone that will separate the fines from the gas stream. These fines are fed directly into the combustor by a rotary valve.

Gasifier Design. The gasification zone is 6-feet high and is constructed of 8-inch schedule 40 pipe with 150-lb flanges at each end. The gasification zone has a larger diameter than the pyrolyzer for two reasons. First, a longer solids residence time is required for gasification, so it was desirable to increase the diameter to reduce the L/D ratio of the bed. Second, a larger diameter was required to keep the gas velocity in the gasification zone similar to the pyrolysis and cooling zones. Since the pyrolysis, gasification and cooling zones share a common fluidizing gas, the density and velocity (if the vessel diameter is constant) of the fluidizing gas vary according to the temperatures of the zones.

A 1.5-inch inlet for the recirculation port from the combustor, is placed 15 inches above the distributor and cut at a 60° angle (see Figure 6, section A-A). This was observed from cold-flow studies¹¹ to be the most favorable arrangement to permit the free-flow of solids into the gasification zone. A 1-inch schedule 40 pipe, placed in the freeboard region, is available for feeding raw shale during start-up and during periods of upset when the dipleg of the downcomer which feeds the gasifier becomes uncovered. Six 1/2-inch ports on each side of the baffle are available for temperature and pressure readings.

A 46-inch tall baffle is located 2 inches above the gas distributor to provide staging for the particles to narrow the residence time distribution. Three brackets attached 21 inches from the top on the gasifier are used to mount the unit to the scaffold.

Cooling Zone Design. Because the cooling zone is designed to operate between 350-500°C, a slightly smaller inside diameter is required compared to the pyrolyzer, so a 6-inch schedule 80 pipe has been specified as the vessel shell. A concentric reducer is used to ensure a smooth transition between this zone and the gasification zone (see Figure 7). The reducer eliminates any dead space around the edges of the gasifier distributor. A 1-inch pipe is used as the outlet port for the spent shale (Fig. 7, section A-A). This pipe, which also controls the bed height, is mounted at a 30 degree angle from the vessel wall. The cooling zone is 3-feet tall and the bed height is 15 inches.

A 7-inch long plenum chamber made from 6-inch schedule 40 pipe and a 6-inch 150-lb flange serves as the base for the cooling zone. The steam used for fluidization will be introduced through a vertical 2-inch pipe attached to the bottom of the unit.

Combustor Design. The combustor consists of 6-inch schedule 40 pipe, and has been slightly modified from the cold-flow design. The height has been increased from 4.5 feet on the cold-flow model to 6 feet on the hot unit. This change was introduced so that CO would have the opportunity to completely combust in the taller freeboard section of the unit. High CO levels were recorded in the 5-lb/hr unit because of a very short freeboard section in the combustion zone. Additionally, a taller freeboard should reduce entrainment of non-fine particles.

Pyrolyzed fines from the cyclone are fed into a pipe that extends through the port at the top of the combustor and into the bed (see Figures 1 and 8). By injecting the fines directly into the bed, the entrainment of the fines will be delayed and afforded an opportunity for combustion prior to exiting the combustor. Gases and entrained solids exit the combustor through a horizontal 1.5-inch pipe at the top which is connected to a cyclone for fines removal. The inlet port for solid recirculation from the gasification zone is a 1.5-inch pipe, placed 3.5 inches above the distributor.

A 7-inch long plenum chamber with a 2-inch inlet port for the fluidizing gas and a 2-inch outlet port for the recirculation loop to the gasifier serves as the combustor base. The standpipe which controls the depth of the combustion bed extends through the gas distributor and through the outlet port at the bottom of the plenum chamber. This configuration makes it easy to adjust the standpipe height and thereby allow for a study of the mean solid residence time. Three brackets attached to the plenum mount the combustor to the scaffold.

NOTE: CAP REMOVED TO SHOW
BAFFLE ORIENTATION.

SECTION A-A

SECTION B-B

SECTION C-C

Figure 5. Pyrolyzer.

Figure 8. Combustor.

The combustor is covered with 4 inches of high temperature insulation, but no electrical heating elements will be used. Instead, a propane burner will be used to preheat the fluidizing air during start-up and during steady state operation if necessary.

Summary

During the preceding quarter, the design of the KENTORT II reactor was completed and blueprints for manufacturing were developed. Construction materials were selected, and pipes and flanges for fabrication of the main body of the unit were procured. A spring energized metallic c-ring was tested and was found to perform adequately as a seal for the different sections of the unit. Fabrication of the KENTORT II unit is scheduled to begin next quarter. The supporting scaffold was designed, the materials were procured, and the structure is now ready for installation.

CRACKING AND COKING KINETICS

Approach

The objective of this task is to further our understanding of the chemistry and kinetics associated with solids-recycle retorting. A valved fluidized bed, designed to permit rapid exposure and isolation of fluidized solids to shale oil vapors, was utilized for this study. This technique allows a wide range of solid-recycle ratios to be simulated and permits the accurate control of the exposure time and temperature of the solids. The kinetics of coke deposition are determined by ultimate analysis of the solids before and after vapor contact. In addition, total carbon, nitrogen, and sulfur evolution are monitored in real-time with a mass spectrometer. Gasified and combusted shales are the primary substrates of interest, but other materials such as naturally occurring minerals have been tested. Once the kinetics portion of the study is completed, the reactor will be operated in a manner to simulate continuous solid-recycle conditions in order to collect sufficient products to conduct complete material balances and oil analyses.

Introduction

In oil shale processes where the pyrolysis zone is heated by recirculating solids, adsorption of oil vapor and subsequent coking and cracking onto these solids can lead to significant oil yield reduction. It has been shown that the type of solid heat carrier can have a large effect on the magnitude of oil loss.^{13, 14, 15, 16} Our interest in this area has been primarily focused on the coke inducing tendencies of materials used for heat transfer in the KENTORT II process. Since shale is recirculated among pyrolysis, gasification, and combustion zones to transfer heat in the KENTORT II process, the solids that are recycled to the pyrolysis zone from the gasification zone are composed of a mixture of shale particles which have been gasified and combusted to various degrees. By determining the coking kinetics of these materials and their deactivation with time, oil coking can be predicted as a function of solid recycle rate and temperature. In doing so, operating regimes may be identified which limit oil loss, or conversely, coking and cracking conditions may be chosen which improve oil quality by selective removal of undesirable components.

We have previously reported that the rate of carbon deposition is largely influenced by the type of processing that the oil shale has been exposed to. From this early work it appeared that pore volume and the initial carbon content of the shale affected the coking properties the most.¹⁷ The greater the porosity and the lower the carbon content, the greater the rate of carbon deposition that was observed. The coking activities of the three main categories of shales were ranked as: combusted > gasified > pyrolyzed. For these materials, the initial carbon content was the most influential coking indicator since the porosity characteristics were not dissimilar. Additional experiments were performed this quarter to strengthen the argument for coking deactivation by carbon coverage and to aid in separating the effects of pore volume and surface area on

carbon deposition. To evaluate the effects of porosity in terms of diffusional limitations and to characterize the transient mass transfer behavior in the experimental setup, an isothermal fluidized bed model was developed this quarter which represents the beginnings of an overall, fluidized bed coking model.

An area that has not been addressed is the state of the mineral matter and its effect on the coke producing tendency of the solids. Steam and oxygen at high temperature have the potential to alter the surface characteristics of minerals, and experiments were performed this quarter to investigate any possible mineralogical effects on carbon deposition.

Model Development

Due to the complexity that is to be eventually added to the coking model, the simplest possible fluidized bed model which captures the essence of the mechanisms of a fluidized bed was chosen. The bed is assumed to consist of a bubble phase and an emulsion phase, and the bubbles are considered to be spherical and of constant size. The coking reaction (nth order) only takes place within the pores of the particles which are considered to be spherical. Only a first-order reaction was chosen for the present study because the intent of the model at this time is to identify the important mass transport parameters of the system. Certainly, a chemical reaction term that considers deactivation will eventually be added. Simple binary counter diffusion is assumed within the particles. The problem is considered to be unsteady state and the concentration profile within the particles is coupled with the emulsion phase in the fluidized bed. A FORTRAN subroutine in the NAG library (D03PFG) was used to solve the system of parabolic partial differential equations.

A general two-phase fluidized bed model assuming first order, solid-catalyzed kinetics for the emulsion phase is given by Yates¹⁸ as:

$$E_e \frac{\partial^2 C_e}{\partial z^2} - U_e \frac{\partial C_e}{\partial z} - K_{be}(C_e - C_b) - k_e C_e - \frac{\partial C_e}{\partial t} \quad (1)$$

This equation is basically the convective-diffusion equation with chemical reaction. In addition, the third term in Eq. 1 represents the mass transfer rate between the emulsion and bubble phases. A similar equation describes the bubble phase, but in this case it is assumed that no chemical reaction takes place:

$$E_b \frac{\partial^2 C_b}{\partial z^2} - U_b \frac{\partial C_b}{\partial z} - K_{be}(C_b - C_e) - \frac{\partial C_b}{\partial t} \quad (2)$$

For the purposes of the present study, however, Eq. 1 is not sufficient to explicitly describe reactions within a porous particle. By changing the reaction term to a mass transfer term from the emulsion phase to the particle, Eq. 1 becomes:

$$E_e \frac{\partial^2 C_e}{\partial z^2} - U_e \frac{\partial C_e}{\partial z} - K_{be}(C_e - C_b) - \frac{1 - \epsilon_{mf}}{\epsilon_{mf}} k_p a (C_e - C_r(R)) - \frac{\partial C_e}{\partial t} \quad (3)$$

where $C_r(R)$ is the vapor concentration in the particle at the surface.

To account for the coking reaction which is assumed to take place only within the particle, the unsteady state diffusion equation for a sphere is needed. By adding an nth-order chemical reaction term this equation becomes:

$$D_{eff} \left(\frac{\partial^2 C_r}{\partial r^2} + \frac{2}{r} \frac{\partial C_r}{\partial r} \right) - S_p \rho_p k_r C_r^n - \theta \frac{\partial C_r}{\partial t} \quad (4)$$

Equation 4 prescribes binary counter diffusion and no convective mass flux, which are assumptions that must eventually be shown to be proper.

Equations 2 and 3 can be solved as a coupled set of equations either analytically, if enough terms are neglected, or numerically. A means of coupling Eq. 4 to Eqs. 2 and 3 is needed, however. By utilizing continuity at the particle surface, the following boundary condition for Eq. 4 is obtained:¹⁹

$$D_{eff} \left(\frac{\partial C_r}{\partial r} \right)_R = k_p (C_e - C_r(R)) \quad (5)$$

The problem can then be completely characterized with the addition of standard boundary conditions. At the center of the particle the usual boundary condition is applied to Eq. 4:

$$\frac{\partial C_r}{\partial r} = 0 \quad \text{at } r=0 \quad (6)$$

For the emulsion and bubble phases the following boundary conditions are assumed:

$$C_e = C_b = C_{in} \quad \text{at } z=0 \quad (7)$$

$$\frac{\partial C_e}{\partial z} - \frac{\partial C_b}{\partial z} = 0 \quad \text{at } z=L \quad (8)$$

While Eqs. 2-4 contain 2 space variables, the problem is not strictly two dimensional. Since the solids in a fluidized bed are well-mixed, the time-averaged concentration of oil vapor in the emulsion phase that the particle contacts is not a function of axial position. It is suggested, therefore, that C_e in Eq. 5 can be replaced by $C_{e,avg}$ which is the average concentration in the axial direction and is only a function of time. Equation 5 is then written as:

$$D_{eff} \left(\frac{\partial C_r}{\partial r} \right)_R = k_p (C_{e,avg} - C_r(R)) \quad (9)$$

Similarly, $C_r(R)$ is not a function of axial position and is also only a function of time. Therefore, the parameters coupling Eqs. 3, 4, and 9 are only functions of time and a simultaneous solution of Eqs. 2-4 in 2 space variables is not required.

Parameter Estimation. The difficulty in dealing with a fluidized bed reactor is made worse by the situation that the physical properties of the oil vapor must also be empirically estimated. The oil vapor was considered to have a molecular weight of 400 and a critical temperature of 823 K. A heavy oil was assumed because it is generally believed that the heaviest oil fractions participate to the greatest extent in the coking reactions.

The molecular diffusivity of oil vapor in the fluidizing gas (steam or nitrogen) was determined by the Lennard-Jones relationship: ²⁰

$$D_{12} = \frac{0.001858 T^{3/2} [(M_1 + M_2)/M_1 M_2]^{1/2}}{P \sigma_{12}^2 \Omega_D} \quad (10)$$

The Lennard-Jones force constants, ϵ and σ , were estimated for the oil vapor by the relationships:

$$\frac{\kappa T}{\epsilon} - 1.30 \frac{T}{T_c} \quad (11)$$

$$\sigma = 1.18 V_b^{1/3} \quad (12)$$

Tabulated values of ϵ and σ were obtained for nitrogen and steam.²⁰ A geometric mean was used to determine ϵ_{12} and an arithmetic mean for σ_{12} . Once these values were obtained, the collision integral, Ω_D , was determined from published values.²¹ To aid computation, smooth curves were fitted to the collision integral data as a function of $\kappa T / \epsilon_{12}$. Since diffusion in this case occurs in porous solids, an effective molecular diffusivity was defined by:²⁰

$$D_{12,eff} = \frac{D_{12}\theta}{\tau} \quad (13)$$

Knudsen diffusion prevails under conditions where pore-wall collisions are more frequent than molecular collisions. Since gas has low density at high temperatures, the possibility for significant Knudsen diffusion exists. The Knudsen diffusivity, D_K , was determined by the relationship:

$$D_K = 9700 r_e \sqrt{T/M} \quad (14)$$

The mean pore radius was defined by:

$$r_e = \frac{2\theta}{S_p \rho_p} \quad (15)$$

Similar to Eq. 13, the porosity and tortuosity of the solid was accounted for by the relation:

$$D_{K,eff} = \frac{D_K\theta}{\tau} \quad (16)$$

Finally, the overall effective diffusivity, D_{eff} , was determined as the combination of molecular diffusion and Knudsen diffusion by the relation:

$$\frac{1}{D_{eff}} = \frac{1}{D_{K,eff}} + \frac{1}{D_{12,eff}} \quad (17)$$

The remaining parameters that need to be estimated are all fluidized bed parameters. The determination of the minimum fluidization velocity, U_{mf} , is important because it specifies the velocity of gas passing through the emulsion phase. The following relations (Eqs. 18-20), presented by Yates,¹⁸ were used to determine U_{mf} :

$$Re_{mf} = [(33.7)^2 + 0.0408 Ga]^{1/2} - 33.7 \quad (18)$$

$$\text{where } Re_{mf} = \frac{U_{mf} d_p \rho_s}{\mu} \quad (19)$$

$$\text{and } Ga = \frac{d_p^3 \rho_s (\rho_s - \rho_g) g}{\mu^2} \quad (20)$$

Based on the model of Davidson and Harrison the average bubble velocity was determined by the relationship as presented by Yates:¹⁸

$$U_b = (U_o - U_{mf}) + 0.711 (g d_b)^{1/2} \quad (21)$$

This relationship assumes that the bubble diameter, d_b , is known, and for the purposes of this work, a value of 1 cm was assumed.

While the model used in this work assumes only bubble and emulsion phases to exist, the exchange coefficient, K_{bc} , was determined by including the cloud phase as an intermediate resistance in series as suggested by Kunii and Levenspiel.²² The bubble-to-cloud coefficient is given by:

$$K_{bc} = 4.5 \left(\frac{U_{mf}}{d_b} \right) + 5.85 \left(\frac{D^{1/2} g^{1/4}}{d_b^{5/4}} \right) \quad (22)$$

The cloud-to-emulsion coefficient was determined by:

$$K_{ce} = 6.78 \left(\frac{\epsilon_{mf} D_e U_b}{d_b^3} \right)^{1/2} \quad (23)$$

The bubble-to-emulsion coefficient is then derived by:

$$\frac{1}{K_{be}} = \frac{1}{K_{bc}} + \frac{1}{K_{ce}} \quad (24)$$

Using the emulsion phase gas velocity, the mass transfer coefficient to the particle, k_p , is determined by the relationship:

$$Sh = 2.0 + 0.6 Sc^{1/3} Re_m^{1/2}$$

where $Sc = \frac{\mu}{\rho_g D_{12}}$

and $Sh = \frac{k_p d_p Y}{\mu}$ (25)

The activation energy used for the coking rate constant was taken from Wallman et al.²³ ($E_o = 38293$ cal/mol) and the frequency factor was adjusted to agree with the conversion observed from the experiments.

Nomenclature

- A = preexponential factor for 1st-order coking reaction, s^{-1}
 C_b = concentration of oil vapor in bubble phase, mol/cm^3
 C_e = concentration of oil vapor in emulsion phase, mol/cm^3
 $C_{e,avg}$ = average conc. of oil. vapor in emulsion phase, mol/cm^3
 C_{in} = inlet oil vapor concentration, mol/cm^3
 C_r = concentration of oil vapor in particle phase, mol/cm^3
 $C_r(R)$ = conc. of oil vapor at particle surface, mol/cm^3
 d_p = particle diameter, cm
 D_{12} = molecular diffusivity of oil in fluidizing gas, cm^2/s
 $D_{12,eff}$ = effective mol. diff. of oil in fluidizing gas, cm^2/s
 D_{eff} = effective diffusivity of oil vapor in particle, cm^2/s
 D_K = Knudsen diffusivity, cm^2/s
 $D_{K,eff}$ = effective Knudsen diffusivity, cm^2/s
 E_b = axial diffusion coefficient in bubble phase, cm^2/s
 E_e = axial diffusion coefficient in emulsion phase, cm^2/s
 E_o = activation energy of coking reaction, cal/mol
 g = gravitational constant, 980.665 cm/s²
 k_e = first order chemical reaction constant in emulsion, s^{-1}
 k_p = mass transfer coef. between emulsion and part. surf., s^{-1}
 k_r = n-th order reaction constant in particle.
 $(cm^3)^n/(cm^2)(mol)^{n-1}s$
 K_{bc} = bubble-cloud mass transfer interchange coefficient, s^{-1}

K_{be} = bubble-emulsion mass transfer interchange coefficient, s^{-1}
 K_{ce} = cloud-emulsion mass transfer interchange coefficient, s^{-1}
 L = axial length of fluidized bed, cm
 M_1 = molecular weight, amu
 n = order of coking reaction
 r = radial position in particle, cm
 r_e = mean effective radius of pore in solid particle, cm
 P = pressure, atm
 R = radius of particle, cm
 R = gas constant, $82.057 \text{ atm}\cdot\text{cm}^3/\text{mol}\cdot\text{K}$, $1.9872 \text{ cal/mol}\cdot\text{K}$
 Re_{mf} = particle Reynolds number at minimum fluidizing velocity
 S_p = surface area of particle, cm^2/g
 t = time, s
 T = temperature, K
 T_c = critical temperature, K
 U_b = velocity of emulsion gas, cm/s
 U_e = velocity of bubble gas, cm/s
 U_{mf} = minimum superficial fluidization velocity, cm/s
 U_o = superficial gas velocity, cm/s
 V_b = molar volume of oil at normal boiling temperature, cm^3/mol
 Y = logarithmic mean of nondiffusing component
 z = axial position in fluidized bed, cm

Greek Letters

ϵ = Lennard-Jones force constant
 ϵ_{mf} = void fraction in the emulsion phase
 θ = void fraction within particle
 κ = Boltzmann Constant, $1.3805\text{e-}16 \text{ erg/K}$
 μ = gas viscosity, $\text{g/cm}\cdot\text{s}$
 ρ_g = density of gas, g/cm^3
 ρ_p = density of particle, g/cm^3
 σ = Lennard-Jones force constant
 τ = tortuosity of the porous solid
 Ω = Lennard-Jones collision integral

Subscripts

1 = oil vapor
 2 = fluidizing medium (steam or nitrogen)

Experimental

Apparatus. A detailed description of the apparatus and method development was reported in the latest annual report, but an abbreviated summary will be included here for the reader's convenience.¹⁷ The apparatus consists of two vertically aligned fluidized beds (7.6-cm internal diameter) which share a common fluidizing medium and which are heated externally by two dual-zone (each zone independently controlled) electrical resistance furnaces (see Figure 9). The fluidizing gas is preheated in a separate furnace and introduced into the plenum chamber beneath the lower fluidized bed. Raw oil shale is metered by a nitrogen-purged screwfeeder into the lower fluidized bed operating at 803 K. The level of solids in the bed is held constant by a standpipe through which the pyrolyzed oil shale is removed from the reactor. The lower fluidized bed contains a baffle to narrow the residence time distribution of the solids.

In the upper portion of the apparatus, a vertical baffle divides the pipe into two unequal sections; one covers 73% of the cross sectional area and the other 27%. The larger section contains a fluidized bed of solids, and the smaller section provides a bypass-path for the fluidizing stream. The temperature of the upper fluidized bed is controlled independently from the pyrolysis bed. A semi-butterfly valve beneath the baffled section is used to select which of the routes the upward flowing vapors and gases will follow. A gas injection port is located on each side of the baffle so that gas-flow is maintained within each side of the reactor regardless of the butterfly valve position. A purge gas (He or Ar) is introduced into the seal assembly of the semi-butterfly valve to both inhibit coke formation and serve as a tracer gas. This tracer gas facilitates mass spectrometer analyses by correcting for pressure surges, changing flowrates, and instrumental fluctuations.

In the kinetic mode of operation, a port nearly flush with the distributor plate is used to drain the solids, and purge gas is flowed upward through the tube to prevent solids from exiting the bed prematurely. Processed solids are collected in a flask that has been evacuated and filled with an inert gas to prevent oxidation of the hot substrate.

The gas stream leaving the upper portion of the reactor is sampled at approximately 773 K at the outlet of the second cyclone and drawn through a combustion tube. Oxygen is metered into the heated tube downstream of the sampling location, and to ensure thorough combustion, the majority of the tube is filled with a Pt/Al₂O₃ catalyst. The combustion gases are then routed directly to the inlet of a VG model EGA 300MM quadrupole mass spectrometer (QMS) operating in the multiple ion monitoring (MIM) mode. This mode permits the monitoring of up to 16 masses at a rapid rate (approx. 1.5 s per scan). The masses that were selected for continuous monitoring in this study include 4 or 40 (He or Ar tracer); 12 (carbon-to confirm mass 44 intensity); 18 (H₂O); 28 (fluidization N₂); 32 (excess O₂ from the combustion tube); 44 (CO₂); 46 (NO₂); 64 (SO₂); and 42 (HC-to ensure adequate combustor performance).

Figure 9. Schematic diagram of the fluidized bed coking and cracking kinetics apparatus.

Procedure. Described in the following is the procedure used for the kinetic mode of operation utilizing the products of oil shale pyrolysis as reactants. Following system heat-up, raw shale is metered into the pyrolysis bed with the semi-butterfly valve positioned so that the pyrolysis products bypass the upper fluidized bed (i.e. the valve is in the "bypass" position). Once conditions have reached steady state, the QMS is used to scan from 1 to 82 amu to ensure that combustion of the pyrolysis products is complete. When proper combustor operation is confirmed, the QMS is put into MIM mode and scans 9 selected masses (see previous section) to ensure that steady operation has been achieved.

Once steady state operation has been attained, a weighed aliquot of substrate is loaded into the upper fluidized bed and allowed to reach thermal steady state. After conditions have again stabilized, QMS data collection is initiated. After at least 100 scans of the 9 selected masses have been collected, the semi-butterfly valve is rotated so that the upper bed of solids is fluidized by the gases and vapors from the lower bed (i.e. "fluidize" position). When the selected time interval has elapsed (5 to 15 minutes is typical), the valve is returned to the bypass position and the bed of solids is immediately drained from the bed by halting the flow of purge gas to the drain pipe. Ten minutes are allowed for solids to completely drain from the reactor; most exit within one to two minutes. The solid receiver flask is removed and replaced with an empty one, which is then evacuated and purged with nitrogen before the procedure is repeated.

The batch of processed solids is weighed, and ultimate analyses are performed on each sample by standard methods. For consistency, this will be the measure of carbon deposition used throughout the remainder of the report. Surface area and pore volume measurements by Hg porosimetry and N₂ adsorption are performed on selected solid specimens.

Materials. The master sample of oil shale utilized in this study was from the Cleveland Member of the Ohio Shale from northeastern Kentucky, USA (see raw shale analysis in Table 1). The shale was prepared to a size distribution of $-841\mu\text{m} + 250\mu\text{m}$. This shale sample was used both for the production of shale oil vapors in the apparatus and as the starting material for the generation of pyrolyzed, gasified, and combusted shales, respectively. The production of the processed shales was performed at atmospheric pressure in a 7.6-cm diameter fluidized bed reactor under conditions similar to those that occur during normal operation of the KENTORT II process. The pyrolyzed shale was produced at 803K with nitrogen as the fluidizing gas; the gasified shale was produced at 1073K using steam; the combusted shale was generated in air at 973K. In addition, portions of the pyrolyzed and gasified shales were low-temperature ashed to remove carbon without affecting the mineral matrix. Finally, a sample of the combusted shale was steam treated at 730°C in the fluidized bed reactor. Ultimate analyses of these materials are given in Table 1.

Table 1. Ultimate Analyses (As-Received Basis) of the Raw Oil Shale and Coking Substrates (wt%).

	C	H	N	S	Ash
Raw Shale	16.0	1.9	0.8	1.9	74.1
Pyrolyzed Shale	9.6	0.7	0.7	1.2	84.8
Pyrolyzed-LTA	6.5	0.5	0.6	1.3	88.5
Gasified Shale	7.3	0.2	0.6	0.4	91.0
Gasified-LTA	3.3	0.1	0.5	0.4	95.4
Combusted Shale	1.4	0.2	0.6	0.2	97.0
Combusted-Steamed	1.2	0.1	0.5	0.1	97.8
Kaolin-Fine	<0.1	1.6	0.6	<0.1	85.0
Kaolin-Coarse	<0.1	1.4	0.5	<0.1	86.3
Huron Shale (illite)	0.2	0.6	0.6	1.4	92.9
Illite-Heat Treated	<0.1	<0.1	0.5	<0.1	99.1
Ottawa Sand (quartz)	<0.1	<0.1	0.3	<0.1	99.6

The mineralogy of Devonian oil shales is reasonably consistent. The silicate fraction of the shale is composed primarily of illite, which constitutes about 2/3 of the minerals, followed by quartz (~20%) and the clay minerals, chlorite (~10%) and kaolinite (~5%).^{24, 25} Therefore, naturally occurring kaolinite, illite, and quartz samples were also tested as coking substrates. Pure chlorite is not amenable to fluidized bed processing and was not tested. Two kaolin samples (fine- and coarse-grained) were taken from a commercial mine in Georgia, USA and a low-carbon shale (high illite content) from the Huron Member of the Ohio Shale in Rowan Co., KY, USA were dried and prepared to a size distribution of -841 μ m +250 μ m. The quartz sample was unmodified Ottawa sand (-841 μ m +600 μ m). A portion of the low-carbon shale ('illite') was heat treated to 600°C in air. The surface area and porosity characteristics of all the coking substrates are listed in Table 2.

Table 2. Surface Area (m^2/g) and Pore Volume (cm^3/g) of Coking Substrates as Determined by Hg Porosimetry (macro and meso).

Pore Diameter	Surface Area (Pore Volume)		
	> 50 nm macro	2-50 nm meso	Total
Pyrolyzed Shale	2.1 (0.125)	11.3 (0.030)	13.4 (0.155)
Pyrolyzed-LTA	2.4 (0.147)	7.3 (0.025)	9.69 (0.173)
Gasified Shale	2.5 (0.164)	9.2 (0.024)	11.6 (0.188)
Gasified-LTA			
Combusted Shale	3.6 (0.230)	9.1 (0.031)	12.7 (0.261)
Combusted-Steamed	4.0 (0.252)	6.2 (0.026)	10.3 (0.279)
Kaolinite-Fine	8.3 (0.190)	13.9 (0.106)	21.7 (0.296)
Kaolinite-Coarse	6.8 (0.346)	3.7 (0.022)	10.5 (0.368)
Illite	1.0 (0.044)	8.1 (0.030)	9.1 (0.074)
Illite-Heat Treated	1.8 (0.080)	7.6 (0.023)	9.3 (0.103)
Ottawa Sand	0.0 (0.000)	1.0 (0.001)	1.0 (0.001)

Results and Discussion

Numerical Modeling. To facilitate numerical solution to the problem, the variables were non-dimensionalized as follows:

$$\begin{aligned} C_e^* &= \frac{C_e}{C_{in}} ; & C_b^* &= \frac{C_b}{C_{in}} ; & C_r^* &= \frac{C_r}{C_{in}} \\ Z^* &= \frac{z}{L} ; & R^* &= \frac{r}{R} \end{aligned} \quad (26)$$

The following initial conditions were used throughout the work:

$$C_e^* = 0 ; C_b^* = 1 ; C_r^* = 0 \quad \text{at} \quad t = 0 \quad (27)$$

The base case for the numerical solution to the model included no chemical reaction, nitrogen as the fluidizing gas and a temperature of 873 K. A mesh size of 41 was used for both the r - and z -directions. The same mass flowrate of fluidizing gas was used throughout the study. Axial dispersion coefficients, $E_e = E_b = 1 \text{ cm}^2/\text{s}$, were used and are low enough to be considered nearly plug flow, but large enough to perhaps dampen wiggles in the numerical solution. While many have assumed either plug flow or backmixed flow for the bubble and emulsion phases, it is more realistic to consider that flow only approaches one of these ideal cases.

Figure 10 shows that steady state conditions are achieved for each of the 3 phases within 1 second for the base case conditions. The solution is smooth for all of the "surfaces" with the exception of some wiggles which develop in the bubble phase solution at $Z^* = 0.8$ which are artifacts of the numerical solution due to the convection term. The wiggles disappear, however, at times greater than $t = 0.6 \text{ s}$. Using a coarser mesh of 21 grid points the wiggles were much more pronounced. The concentration in the bubble phase displays a minimum at approximately 0.2 s. This sort of behavior is expected because the bubble phase "feeds" the emulsion and particle phases until the initial vapor concentration is achieved. A very small concentration gradient is evident across the particle which is not completely surprising since a relatively small particle size is tested, $d_p = 0.08 \text{ cm}$. The concentration of the emulsion phase follows closely the concentration in the particle which indicates that resistance into the emulsion phase is an influential parameter.

Lowering the temperature by 100 K to 773 K only reduced the effective diffusivity from $0.008 \text{ cm}^2/\text{s}$ to $0.007 \text{ cm}^2/\text{s}$. The data at 773 K is nearly indistinguishable from that at 873 K. Increasing the particle diameter to $d_p = 0.12 \text{ cm}$, however, significantly changed the transient response of the system (Figure 11). The system achieved steady state more quickly than for the small particle, which was somewhat surprising. None of the mass

Figure 10. Base case numerical solution of model. Temperature, 873K; Fluidizing gas, nitrogen; Bed height, 7.6 cm; no chemical reaction. Units are dimensionless except for time.

$L = 7.6 \text{ cm}$

Temperature = 873 K

Fluidizing Gas = Nitrogen

Figure 11. Numerical solution to model with $d_p = 0.12 \text{ cm}$.

transfer coefficients changed significantly with increased particle size, but the minimum fluidization velocity increased substantially. The velocity of gas through the emulsion phase, therefore, increased and the velocity of bubble gas decreased because the overall superficial velocity was held constant. This created greater mass transfer from the bubble phase to the emulsion phase and greatly increased the temporal response of the system. A more intuitive effect of particle size can be also observed, however. The concentration gradient across the particle radius is much steeper, at least initially, compared to the small particle size simulation. Due to the larger gradient for the emulsion phase, an imprint of the bubble phase response is observable.

The effect of chemical reaction on the transient response of the system is similar to that without reaction except that lower concentrations are reached at steady state (Figure 12). In addition, it appears that steady state is reached more slowly. The frequency factor was adjusted so that the conversion approximately matched the experimental results. Therefore, no conclusions should be drawn concerning the closeness of fit to experimental results. A simple first order chemical reaction was used, and this was sufficient for the purposes of this work. Since it was the objective to study the transient response of the system due to mass transfer, complicated chemical reaction deactivation models were not attempted. This is, however, the objective of future work with this model. Chemical reaction created a steeper concentration gradient within the particle, so diffusional effects cannot be neglected even for the small particle size. In the case of no reaction the wiggles in the bubble phase solution disappeared at steady state, but with chemical reaction present the wiggles survive.

Results from a test case utilizing steam as the fluidizing gas are basically indistinguishable from the base case results, so no other test cases were attempted for steam.

Comparisons of the computer model to the experimental results are difficult because a proper expression for the rate and deactivation of the coking reactions was not utilized. An important conclusion which may be made, however, is that the unsteady state experimental results cannot be attributed to mass transfer effects. A typical experiment reaches an apparent steady state within minutes rather than a second. The deactivation of the solid particles is the only explanation for the temporal response of the experiments.

Figure 12. Numerical solution to model under base case conditions with chemical reaction.

Experimental Results. Results from numerical modeling of mass transfer phenomena indicated that pore diffusion may not be as important as we had originally thought. The testing of a coarse-grained sample of kaolinite this quarter provided valuable insights into separating the effects of pore volume and surface area. While the chemical compositions of the fine- and coarse-grained kaolins are essentially identical, the porosity and surface areas are very different. We consider only meso- and macro-pores as being important to the carbon deposition process because the molecules most likely responsible for the majority of the coking are too large to fit into micro-pores (<2 nm dia.). Therefore, the porosity measurements reported here do not include micro-pore volume or surface area. The fine-grained kaolinite has twice the surface area but only 80% of the pore volume of the coarse-grained material. The fine-grained kaolinite consistently displayed greater carbon deposition compared to the coarse-grained which suggests that surface area played a more significant role than pore volume. This result urged us to more closely evaluate surface area as a coking indicator.

When considering only substrates that have a 'low' initial carbon content, an increase in carbon deposition as a function of surface area is observed (Figure 13). Low-carbon substrates are distinguished from high-carbon substrates because it appears that carbon coverage hinders additional carbon deposition. The amount of carbon deposition for the lowest surface area materials, illite and heat-treated illite, in Figure 13 is somewhat lower than the other substrates because the pore volumes are approximately 50% of the other materials. The surface area relationship in Figure 13 also holds for the gasified and pyrolyzed shale samples which had been subjected to a low-temperature ash (LTA) procedure. The total carbon content for these samples was high, 3.26 and 6.47 wt%, respectively, but it appears that the carbon coverage which is most significant to the carbon deposition process was removed by LTA. The LTA samples, therefore, performed like materials which contained essentially no carbon.

The initial carbon content of the substrate strongly affects the amount of carbon deposition (see Figure 14). Only combusted, gasified, and pyrolyzed shales were considered in this plot so that pore structure and surface area were as similar as possible. The LTA samples, especially the pyrolyzed shale, do not strictly adhere to this relationship which, again, indicates that the total carbon content is not always indicative of the nature of the carbon coverage experienced by the shale oil vapors in the pores of the solids.

To this point, no mention has been made of the activity of the bare mineral surface itself. Among the various un-pretreated substrates, no differences in coking activity were discernable when surface area, carbon content, and pore volume were accounted for. Several different pretreatment procedures were undertaken this quarter to determine whether a difference in chemical activity of the substrate could affect the rate of carbon deposition. Acid-washed and base-washed samples of combusted and gasified shales displayed the same rate of carbon deposition as the un-pretreated parent materials. The value of this test is uncertain, however, because only a low concentration

Figure 13. Carbon deposition onto low-carbon content substrates as a function of meso- and macro-surface area. 10 minutes solid residence time; 12 g/minute raw shale feedrate; 75 g charge of substrate.

of acid or base could be used in the washing procedure without destroying the physical integrity of the substrates. A portion of the illite sample was heat-treated in air at 600°C to investigate the effect of oxygen on the mineral matrix without the presence of carbon. The heat-treatment did not significantly change the porosity characteristics of the substrate and the carbon uptake was essentially the same as the un-pretreated illite.

Steam has long been regarded as a coke reducing agent during the processing of hydrocarbons. Rubel et al.²⁶ have indicated that steam treatment of combusted shale lowers its coking activity, but it is unclear what role steam played to produce this result. We wanted to investigate the effects of steam as a pretreating agent and as an inhibitor during exposure of shale oil vapors to the substrate. One method of pretreating with steam was to blend steam (30% by volume) with N₂ during the preheating period. No significant effects were observed, however, and a more severe pretreatment method was later utilized to more thoroughly evaluate the effects of steam pretreatment. Here, a portion of the combusted shale sample was processed in the fluidized bed reactor at 700°C with steam used for fluidization. It was determined that a slight reduction in

coking activity was achieved from this steam treatment, but as discussed previously this appears to be attributable to a reduction in surface area (see Figures 13 and 15). In another series of runs, steam was used for fluidization to search for any effects during oil vapor exposure, but no effects were discernable (Figure 15).

Conclusions

In short, from a preliminary evaluation of the data, it appears that the only effective pretreatment method for reducing the coking activity of the shale is to reduce the surface area and porosity of the substrate. Basically, substrate reactivity is mainly governed by the surface area of the mineral matrix and the extent of carbon coverage on the accessible pores. The results of the mathematical model of the experimental system indicated that diffusion limitations were not as pronounced as we had originally thought, but are still significant, especially at larger particle sizes. The transient nature of the experiments cannot be attributed to mass transfer effects.

Figure 14. The effect of initial carbon content of the substrate on subsequent carbon deposition.

Figure 15. Effects of steam on the coking activity of combusted oil shale.

REFERENCES

1. Rubel, A.M., M.J. Margolis, J.K. Haley, and B.H. Davis, *1983 Eastern Oil Shale Symposium Proceedings*, 1983, IMMR83/089, University of Kentucky, Lexington, Ky.
2. Margolis, M.J., *1981 Eastern Oil Shale Symposium Proceedings*, 1981, University of Kentucky, IMMR82/066, Lexington, KY.
3. Richardson, J.H., E.B. Huss, L.L. Ott, J.E. Clarkson, M.O. Bishop, L.J. Gregory, and C.J. Morris, Lawrence Livermore National Laboratory, UCID-19548, 1982.
4. Ahmed, M.M., D.W. Parker, and D.H. Archer, *1982 Eastern Oil Shale Symposium Proceedings*, 1982, University of Kentucky, IMMR82/075, Lexington, KY.
5. Rubel, A.M. and S.D. Carter, *Preprints Div. Pet. Chem.*, ACS, 1984, 29, 202-208 (1).
6. Wallman, P.H., Tamm, P.W., and Spars, B.G., *ACS Symp. Ser. 163*, 1981, 93.
7. Bissel E.R., Burnham, A.K., and Braun, R.L., *I and EC Proc. Des. Dev.*, 1985, 24, 381.
8. Carter, S.D., Rubel, A.M., Robl, T.L., and Taulbee, D.N., 'The Development of the KENTORT II Process for Eastern U.S. Oil Shale,' 1990, Final Report for work performed under Contract No.: DE-FC21-86LC11086, DOE/LC/11086-2860.
9. Carter, S.D. and D.N. Taulbee, *Fuel Processing Technology*, 1985, 11, 251-272.
10. Robl, T.L., K. Cisler, G. Thomas, and D.W. Koppenaal, *1985 Eastern Oil Shale Symposium Proceedings*, 1985, University of Kentucky, KCERL/85-147, Lexington, Ky.
11. Vego, A., Carter, S.D., Stehn, J.L., and Neathery, J.K., *1991 Eastern Oil Shale Symposium Proceedings*, 1991, University of Kentucky, in press, Lexington, KY.
12. Annual Book of ASTM Standards, 'Steel - Piping, Tubing, Fittings, A 312/A312M - 89a, 1.2, Volume 01.01, 1990.
13. Coburn, T.T., *Proc. 1988 Eastern Oil Shale Symp.*, 1989, University of Kentucky, p. 325.
14. Dung, N.V., Wall, G.C. and Kastl, G., *Fuel*, 1987, 66, 372.
15. Wall, G.C. and Udaja, P., *Fuel*, 1988, 67, 1340.
16. Udaja, P., Duffy, G.J., and Chensee, M.D., *Fuel*, 1990, 69, 1150.
17. Carter, S.D., Vego, A., Taulbee, D.N., and Stehn, J.L., *The Development of an Integrated Multistage Fluid Bed Retorting Process*, Annual Technical Report for the

Period: Sept. 28, 1990 - Sept. 30, 1991, January 1992, Cooperative Agreement No. DE-FC21-90MC27286.

18. Yates, J.G., *Fundamentals of Fluidized-bed Chemical Processes*, 1983, Butterworths, London.
19. Yang, R.T., *Gas Separation by Adsorption Processes*, 1987, Butterworths, Boston.
20. Satterfield, C.N., *Mass Transfer in Heterogeneous Catalysis*, 1970, MIT Press, Cambridge, Mass.
21. Hirschfelder, J.O., Curtiss, C.F., and Bird, R.B., *Molecular Theory of Gases and Liquids*, 1954, Wiley, New York.
22. Kunii, D., and Levenspiel, O., *Fluidization Engineering*, 1969, Wiley, New York.
23. Wallman, P.H., Singleton, M.F., and Taylor, R.W., *Proc. 23rd Oil Shale Symposium*, 1990, Colorado School of Mines, Boulder, CO.
24. Robl, T.L., Rubel, A.M., and Barnhisel, R.I., *Proc. 1989 Eastern Oil Shale Symposium*, 1990, University of Kentucky, IMMR88-101, 212-218.
25. Hosterman, J.W. and Whitlow, S.I., U.S. Geol. Sur., 1981, Open File Rep. No. 81-585, 178 p.
26. Rubel, A.M., Rimmer, S.M., Keogh, R., Robl, T.L., Carter, S.D., and Derbyshire, F.J., *Fuel*, 1991, 70, 1352.

END

**DATE
FILMED**

9 / 8 / 92