AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

3-D Turbulent Particle Dispersion Submodel Development

Quarterly Progress Report #3

4Q/91

covering the period of 15 October 1991 to 15 January 1992

DE-FG22-90PC 90094

to the Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, PA

Project Manager: James Hickerson

from the Department of Chemical Engineering
University of Utah
Salt Lake City, UT 84112

Graduate Students: S. Jain & S. Kumar

Phillip J. Smith
principal investigator

RECEIVED
USDOE/PETC

92 JUL 23 AM 10:37

ACQUISITION & ASSISTANCE DIV.

44-3711

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

yes

Table of Contents

1.0	Overview of Project	2
2.0	Dilute Particle Phase Dispersion Model Development.....	2
2.1	The 3D STP Submodel	2
2.2	Solution Algorithm	3
2.3	Current Status	4
3.0	Dense-Phase Dispersion Submodel	4
3.1	Review of Theory Development.....	4
3.2	Solution Technique	6
3.3	Current State of Development	6
4.0	Conclusion	7
5.0	References.....	7

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

1.0 Overview of Project

Many practical combustion processes which use solid particles, liquid droplets, or slurries as fuels introduce these fuels into turbulent environments. Examples include spray combustion, pulverized coal and coal slurry combustion, fluidized beds, sorbent injection, and hazardous waste incineration. The interactions of the condensed phases with turbulent environment have not been well described. Such a description is complicated by the difficulty of describing turbulence in general, even in the absence of particles or droplets. But the complications in describing the dispersion and reaction of the condensed phases in turbulent environments do not stem entirely or even primarily from the uncertainties in the description of the turbulence. Even when the turbulence characteristics are known, computational methods for coupling the dynamics of the particulate phase with the continuous phase have not been well established. Several new theoretical descriptions of the turbulent dispersion of particles and droplets have been proposed over the last five years. It is the purpose of this project to explore the potential of two of these theories for coupling with the other aspects of three-dimensional, reacting, turbulent, particle-laden systems to provide computational simulations that could be useful for addressing industrial problems.

We are exploring two quite different approaches, each with their own set of advantages and disadvantages. Each approach is discussed separately in this report. The discussions include a brief summary of the theory and solution algorithm being used followed by a statement of status and plans.

2.0 Dilute Particle Phase Dispersion Model Development

The first approach is to use pure Lagrangian methods to describe the particulate phase. Lagrangian methods have been used because of their advantage in accounting for time-temperature histories of the reacting particles. Particles arriving at any given spatial position in a system may have very different histories in these methods. There are significant disadvantages however in pure Monte Carlo Lagrangian methods because they require tracking the history of such a large number of particles in order to achieve numerically accurate and stable solutions. This is particularly true if the simulation is to be performed for physi-

cally large systems and for systems that are reacting (i.e. utility boilers). We have developed a technique for computationally tracking clouds of particles, rather than individual particles, which includes not only the mean position but the turbulent dispersion of the cloud about the mean position. The method also couples the reaction of these particles with the continuous phase. This submodel is referred to as the stochastic transport of particles (STP).

2.1 The 3D STP Submodel

The STP model is coupled to the Eulerian continuous phase (most often a gas) calculations by additive source terms in the transport equations. These terms account for mass, momentum and energy transfer between the phases. The calculation of the cloud dispersion allows these source terms to be distributed spatially throughout the Eulerian mesh. The contribution of particles with a specific residence time to the Eulerian particle source term in a given computational cell is evaluated by integrating the product of the instantaneous values of the particle number flow-rate, $\dot{q}$, particle reaction rate, r_p^m , and a weighting term based on the pdf between the limits of cell boundaries. Thus, the total source term for an Eulerian cell is given by,

$$S_{p,ijk}^* = \int_{-\infty}^{\infty} \int_{V(ijk)} \dot{q}_p^* W(x_i, t) dV dt \quad (\text{EQ 1})$$

where ijk represent the coordinates of the Eulerian cell, the time integral is with respect to residence time and $\int_{V(ijk)} dV$ represents a volume integral between the boundaries of the Eulerian cell with coordinates ijk . That is, in the Cartesian coordinate system

$$\int_{V(ijk)} f(x_i, t) dV = \int_{x_{1,lb}}^{x_{1,ub}} \int_{x_{2,lb}}^{x_{2,ub}} \int_{x_{3,lb}}^{x_{3,ub}} f(x_i, t) dx_1 dx_2 dx_3 \quad (\text{EQ 2})$$

where lb and ub represent the lower and upper bounds of the cell, respectively. Table 1 defines the specific variables for which these source terms are calculated.

Table 1 Variable Substitutions to compute source terms

Source Term	ϕ	Description
S_p^m	m	total mass from condensed phase
S_p^u	u	axial momentum
S_p^v	v	radial momentum
S_p^w	w	tangential momentum
S_p^f	f	vapor evolved from liquid phase
S_p^η	η	mass evolved from solid phase
S_p^h	h	enthalpy exchanged with condensed phase
where	$S_p^m = S_p^f + S_p^\eta$	

The term $W(x_i, t)$ is a weight function defined in terms of the probability density function (pdf) for particle position, $P(x_i, t)$.

$$W(x_i, t) = \frac{P(x_i, t)}{\int_{V(\min - \max)} P(x_i, t) dV}, \quad (\text{EQ 3})$$

The pdf's for particle position are assumed to be multivariate Gaussian or normal pdf's. These are completely described by their means, μ_i , and variances, σ_i , and are of the form

$$P(x_i, t) = \frac{1}{(8\pi)^{3/2} \prod_{i=1}^3 \sigma_i} e^{-s^2/2} \quad (\text{EQ 4})$$

$$s = s(x_i, t) = \sum_{i=1}^3 \left(\frac{x_i - \mu_i}{\sigma_i} \right)^2. \quad (\text{EQ 5})$$

The expected mean particle position is given by

$$\langle x_i(t) \rangle = \int_0^t \langle V_i(t_1) \rangle dt_1 + \langle x_i(0) \rangle = \mu_i \quad (\text{EQ 6})$$

$$\frac{d\langle V_i \rangle}{dt} = \beta (\langle U_i \rangle - \langle V_i \rangle) + g_i \quad (\text{EQ 7})$$

where $\langle U \rangle$ and $\langle V \rangle$ are the ensemble averaged gas and particle phase velocities respectively. β is calculated from Stoke's law as

$$\beta = \frac{3\pi d_p \mu_g}{m_p}. \quad (\text{EQ 8})$$

The covariance matrix for a stationary field is written in terms of the particle velocity correlation function $R_{ij}^p(t_1, t_2)$ as

$$\sigma_{ij}(t) = 2 \int_0^t (t - \tau) R_{ij}^p(\tau) d\tau \quad (\text{EQ 9})$$

$$R_{ij}^p(t_1, t_2) = \langle v_i(t_1) v_j(t_2) \rangle. \quad (\text{EQ 10})$$

2.2 Solution Algorithm

The 3D STP algorithm has been developed to allow parallel processing of the particle and continuous (gas) phase calculations, resulting in improved memory and run time efficiency.

After initialization, finite difference forms of the transport equations for the gas phase are solved for each variable independently in an iterative fashion (microiterations). A single overall iteration in which new estimates of each of the variables in the Table I are generated (macroiteration). During these macroiterations, the particle source terms are not changed. After the Eulerian equations are converged for a given set of particle source terms, the particle portion of the model is activated. New source terms are produced from the particle portion of the code. One cycle, in which the gas phase is converged and the particle portion of the code calculates new source terms is called a particle iteration. In parallel processing the particle and gas phase calculations are done simultaneously and exchange of information takes place through direct data transfer.

Particles clouds are initiated from several (typically about ten) starting locations in the reactor. In addition, heteroge-

neity of inlet particle-laden streams is accounted for by tracking separate clouds for several (typically about fifteen) different particle types. These are used primarily to simulate the range of particle sizes fed to the coal reactor. Having selected a starting location and initial particle size for a cloud, the equations describing the development of the pdf for particle location are solved as a function of residence time. In addition to the pdf for particle position, the particle temperature, composition, size and density are predicted as functions of time. The particle properties are then used to calculate source terms for the gas phase calculations.

The Lagrangian nature of this particle model allows considerable detail in describing the rates of reaction and heat transfer between the gases and the condensed phases. Condensed phases ranging from liquids to slurries can be modelled. Specific modelled transfer rates include vaporization, devolatilization, heterogeneous reaction, and heat transfer. This formulation allows the simulation to calculate local characteristics in a large variety of reacting and nonreacting flows. These include nonreacting turbulent flows both with and without entrained particles, gaseous diffusion flames, coal combustion and gasification, fuel oil combustion, coal slurry combustion, and spray drying.

2.3 Current Status

Computer code has been developed to predict particle trajectories using the 3DSTP algorithm. Fig. 1 shows preliminary results from calculations for a test case of non-reacting flow through a box. Currently the particle portion of the code is being run as a stand-alone program. The gas phase variables are read from the restart file written out by gas phase calculations.

Incorporation of the particle calculations into the three-dimensional combustion code and debugging of the developed code will continue over the next quarter. Evaluation of the code will proceed from that point according to the tasks outlined previously.

3.0 Dense-Phase Dispersion Submodel

The second approach to describing the turbulent transport of particles is to use a pure Eulerian description. In this

section the progress is described in the development of a dense-phase particle dispersion submodel which can be used to predict the flow behavior of multiphase mixtures for potentially all void fractions but particularly in situations where the mixture is more dense. The work done focuses primarily on the development of a computer model which can couple the important processes to predict steady-state enclosed flow patterns of gas-solid mixtures in an arbitrary three-dimensional geometry.

3.1 Review of Theory Development

The main thrust of this effort is to develop a code applicable to industrial scale particle-laden combustors over a wide range of loadings including circulating fluidized bed combustors. The solid fractions in these more dense situations are typically in the range of 0.3 - 0.6, in which case a Lagrangian approach which is based on the assumption of non-interacting particles starts to break down. The Eulerian description considers the mixture to be comprised of mutually interpenetrating phases. In what follows, we describe the theory for a two-phase (gas-solid) mixture with uniform monodisperse particles. Extensions to multiple sizes are described in a later section.

The basic governing equations for either phase can be written as follows:

Continuity:

$$(\nabla \cdot \rho v) = S^m \quad (\text{EQ 11})$$

Momentum:

$$\rho \frac{Dv}{Dt} = -(\nabla \cdot \sigma) + \rho f \quad (\text{EQ 12})$$

where ρ is the bulk density of the phase concerned, i.e. the actual density of the phase at that point times the volume fraction of that phase at that point, σ is the stress tensor, S^m is the mass source to the phase concerned from the other phase, f is the external force acting on the phase, given by

$$f = \rho g + S'' \quad (\text{EQ 13})$$

where g is the acceleration due to gravity, and S'' is the momentum source added to the phase under consideration

Figure 1: Preliminary results obtained from the 3DSTP code for a test case of particle laden, non-reacting flow through a box. Mean trajectories of particles starting from 10 different locations are shown. Notice the symmetrical particle trajectories predicted for this simple test case.

due to momentum exchange with the other phase, i.e. the drag.

In addition, we need a constitutive equation to describe the stress-strain relationship, and an equation of state for each phase. The gas phase is a continuum in the usual sense, and the forms of constitutive equations for such a phase are rather well-established. However, the particle phase constitutes a distributed continuum. The forms of constitutive equations for such continua are not universal and have to be determined for each individual situation separately. For this purpose we turn to the theory of rapid granular flows.

Other approaches have been reviewed (see Smith (1991)); however, we have settled on the kinetic model of Jenkins and Savage (1983). This approach and related kinetic theories had the advantage of being the most fundamental in

their incorporation of the microstructure of the particle flow, while still preserving simplicity in the resulting constitutive equations. Their constitutive relations are given below:

$$\sigma = \frac{\pi^{1/2} \kappa T^{1/2}}{d} I - \left(\frac{1}{5}\right) \kappa (2 + \alpha) [(trD) I + 2D] \quad (\text{EQ 14})$$

$$\kappa = 2\rho v g_0(v) d (1 + e) \left(\frac{T}{\pi}\right) \quad (\text{EQ 15})$$

$$\left(\frac{3}{2}\right) \rho \frac{DT}{Dt} = -(\nabla \cdot q) - tr(\sigma \nabla v) - \gamma \quad (\text{EQ 16})$$

$$q = -\kappa \nabla T \quad (\text{EQ 17})$$

$$\gamma = \frac{\kappa(1-e)}{2d^2} \left[12T - (3\pi + 4\alpha) d \left(\frac{T}{\pi}\right) (trD) \right] \quad (\text{EQ 18})$$

where T is defined as the "granular temperature", and is actually the ensemble average of the square of the fluctuating velocity of individual particles:

$$T = \frac{1}{3} \langle C^2 \rangle, \quad (\text{EQ 19})$$

d is the diameter of the particles (assumed spherical and uniform), e is the coefficient of restitution for collisions between particles, v is the ensemble-averaged local solid fraction in the mixture, γ is defined as the dissipation due to "viscous" drag, i.e. the energy dissipation due to collisions, q is the flux of T (the "diffusive flux" of the granular "temperature"), κ is the "thermal conductivity" of the granular material in rapid shear flow, α is a constant, tr denotes the trace of a matrix, D is the rate of deformation tensor, I is the identity tensor, and $g_0(v)$ is a function of the solid fraction v which may be of the form (see Smith, 1991):

$$g_0(v) = \frac{1}{1-v} + \frac{3v}{2(1-v)^2} + \frac{v^2}{2(1-v)^3}. \quad (\text{EQ 20})$$

One can see from inspection of (EQ 14) that the form of this constitutive equation is very reminiscent of that of a Newtonian fluid. In fact, if we define a particle pressure:

$$p_e = \frac{\pi^{1/2} \kappa T^{1/2}}{d} = 2 \left(\frac{T}{\pi} \right)^{1/2} T \rho g_0(v) v (1+e), \quad (\text{EQ 21})$$

and a particle viscosity:

$$\mu_e = \left(\frac{2}{5} \right) \kappa (2+\alpha) = \left(\frac{4}{5} \right) \rho v g_0(v) d (1+e) (2+\alpha) \left(\frac{T}{\pi} \right) \quad (\text{EQ 22})$$

then the resulting equations of motion (EQ 12) become identical to the Newtonian case, with the one difference that in rapid granular flow, the pressure and viscosity are functions of the granular temperature, which varies much more rapidly than the thermodynamic temperature in the flow field. It can be seen that the balance equation for the "granular temperature" is similar to the equation of change of the turbulent kinetic energy of a turbulent Newtonian fluid.

The gas is assumed to be a Newtonian fluid and a $k-\epsilon$ model is used to account for the turbulence. The coupling between the two phases is principally through the inter-

phase drag, though any other minor contributions can be easily added if necessary. The drag can be expressed as a linear function of the difference in velocities of the two phases. For example, the contribution to the source term of the equation of motion of the i^{th} equation from the j^{th} phase can be written as:

$$S_{ij}^u = \beta (v_j - v_i), \quad (\text{EQ 23})$$

where β is the inverse of the Stokesian relaxation time.

3.2 Solution Technique

The governing equations shown above ((EQ 12), (EQ 13) and (EQ 16)) are first discretized using a combination of finite-difference and finite-volume techniques in such a manner as to obtain the resulting finite-difference equations in a semi-implicit form. These are then solved implicitly for the velocities and other such primitive variables, using one of the variants of the SIMPLE (Semi-Implicit Method for Pressure-Linked Equations) (see Smith, 1990) algorithm. The calculations are done iteratively, and within each cycle of iteration, both gas and particle values are updated successively. Since, as has been mentioned, the gas and particle phase equations have the same form, we use the same routines for each phase.

3.3 Current State of Development

At present, coding of the dense phase dispersion submodel is nearing completion. We expect to have test results and to be able to test the validity of the code by comparison with experimental data in the next few months. For the purposes of comparison we plan to use data obtained by Ai (1990) at the University of Illinois at Urbana-Champaign. Currently the code is capable of handling both continuous and semibatch operation (i.e. with respect to the particle phase), multiple inlets and outlets, and permits specification of inlet profiles for gas and particle velocities, solid fractions, and granular temperatures.

We have also extended the theory to mixtures of several particle phases, wherein each particle "phase" may have a different density, coefficient of restitution, and particle size. This is being done by adding to each particle phase equation, in addition to the gas interphase drag, a drag term analogous to (EQ 23) which results from interparticle interactions. The form of the exchange coefficient between

Conclusion

the particles is currently based on a Stokesian hypothesis, but can be modified easily to suit any other form.

Department of Energy, Pittsburgh Energy Technology Center, Pittsburgh, PA (1991).

The code also currently allows for reaction in the gas phase. We plan to extend the code to allow heterogeneous reactions. This would involve having to incorporate an energy equation for each particle phase.

Evaluation of the code will initially be done by comparison with the data of Ai (1990), who has measured detailed solid velocities and solid fractions in a 2-dimensional atmospheric laboratory scale fluidized bed with monodisperse particles. Although the data is for a two-dimensional case, we feel that it will be a valuable tool to test the 3-D code due to the high accuracy of the data.

4.0 Conclusion

Two algorithms have been developed for computing the turbulent dispersion of particles. One, a pure Lagrangian algorithm has the advantage of tracking more accurate time temperature histories for clouds of homogeneous particles and seems most applicable to dilute mixtures. The other, a pure Eulerian approach, more readily allows for the local effects of the other phases including particle-particle interactions. This approach seems most applicable to denser systems. Issues of computational efficiency and model accuracy are being explored. These computational models will be helpful in describing turbulent multiphase systems of industrial significance.

5.0 References

1. Ai, Y.H., *Solids Velocity and Pressure Fluctuation Measurements in Air Fluidized Beds*, M.S. Thesis, Department of Mechanical Engineering, University of Illinois at Urbana-Champaign (December 1990).
2. Jenkins, J.T., and Savage, S.B., "A theory for the rapid flow of identical, smooth, nearly elastic spherical particles," *J. Fluid. Mech.*, **130**, 187(1983).
3. Smith, P.J., *User's Manual for 3D Combustion Code*, Internal Document, Department of Chemical Engineering, University of Utah (1990).
4. Smith, P.J., *3-D Turbulent Particle Dispersion Submodel Development (Quarterly Progress Report #1)*,

**DATE
FILMED**

9/29/94

END