1 of 1

DOE/PC/79650--6

DE-AC22-87PC79650-6

CWS-FIRED RESIDENTIAL WARM-AIR HEATING SYSTEM

Quarterly Report for the Period November 1, 1987 - January 31, 1988

By
J. Balsavich, F.E. Becker and L.A. Smolensky

March 1988

Work Performed Under Contract No. DE-AC22-87PC79650

Tecogen Inc.
A Subsidiary of Thermo Electron Corporation
Waltham, Massachusetts

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PATENT STATUS

This technical report is being transmitted in advance of DOE patent clearance and no further dissemination or publication shall be made of the report without prior approval of the DOE Patent Counsel.

TECHNICAL STATUS

This technical report is being transmitted in advance of DOE review and no further dissemination or publication shall be made of the report without prior approval of the DOE Project/Program Manager.

TE4415-40-88

DE-AC22-87PC79650-6

CWS-FIRED RESIDENTIAL
WARM-AIR HEATING SYSTEM

Quarterly Report for the Period
November 1, 1987 - January 31, 1988

By
J. Balsavich, F.E. Becker and L.A. Smolensky

Work Performed Under Contract No. DE-AC22-87PC79650

TABLE OF CONTENTS

<u>Chapter</u>		<u>Page</u>
1	INTRODUCTION AND SUMMARY	1
2	WORK PERFORMED DURING THE FOURTH QUARTER..	3
	2.1 PERISTALTIC PUMP	3
	2.2 Y-JET ATOMIZER	9
	2.3 TEST RESULTS	12
	2.4 NEW COMBUSTOR DESIGN	20
3	SUMMARY STATUS ASSESSMENT AND FORECAST	23

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
2.1	Assembling Instrumentation for Horizontal Flow Train	4
2.2	Laboratory Facility	5
2.3	Peristaltic CWS Pump	6
2.4	Peristaltic Pump Performance	8
2.5	Y-Jet Atomizer	10
2.6	Y-Jet Atomizer Inserted in Precombustor	11
2.7	Schematic of Laboratory Facility	14
2.8	"Flame" and Precombustor Temperature vs Time	17
2.9	Effect of Excess Air on Heat Exchanger Number of Transfer Units	18
2.10	Effect of Excess Air on Effectiveness	19
2.11	Effect of Excess Air on Stack Losses	21
3.1	Status Chart	24

LIST OF TABLES

<u>Table</u>		<u>Page</u>
2.1	TYPICAL TEST - MEASURED SYSTEM PERFORMANCE	15

1. INTRODUCTION AND SUMMARY

The objective of the Coal/Water Slurry (CWS) Fired Warm-Air Heating System program is the development of a reliable, efficient, compact and safe CWS-burning residential furnace. This report summarizes results of the fourth quarter of the first phase of the program effort carried out by Tecogen Inc.

During the first phase of the program, Tecogen is developing several key components of the furnace. These components may be grouped into three general areas:

- Components directly related to combustion processes (i.e., combustion chamber, burner, and atomizer)
- A heat exchanger that transfers sensible heat from the flue gases to a circulating water loop
- A gas cleanup system

During the fourth quarter, work continued on Task 1.170, Testing and Development of Initial Prototype Components. It was found from this testing that the entire furnace system, including the combustor, peristaltic pump, Y-jet atomizer, and heat exchanger performed reliably. In particular, the combustor, which is best denoted as an Inertial Reactor with Internal Separation (IRIS) because it uses radial forces to detain particles, achieved a carbon conversion efficiency of over 96 percent.

2. WORK PERFORMED DURING THE FOURTH QUARTER

During this quarter, work has continued on Task 1.70, Testing and Development of Initial Prototype Components. During this period, the system components have been reconfigured from the original horizontal flow train shown in Figure 2.1 to the verticle configuration shown in Figure 2.2. This configuration allows testing of both the combustor and the heat exchanger in the vertical mode. Although the particular configuration shown in Figure 2.2 may not be used in subsequent designs, a verticle combustor and heat exchanger will be made an integral part of the final design in an effort to minimize floor space.

Testing of the entire system continued this quarter. The main focus of this work was concentrated on the IRIS combustor and its required support subsystems. These subsystems include the fuel delivery system, including the peristaltic pump and the slurry atomizer.

2.1 PERISTALTIC PUMP

The most important part of the fuel delivery system is the pump. Traditionally, progressive cavity pumps are the most commonly used type of pump for CWS. These pumps work quite well, but they are too expensive to be used in residential-sized systems. A more cost-effective alternative to the progressive cavity pump is the peristaltic pump.

The pump used in this work (shown in Figure 2.3) is a peristaltic pump, which consists of compressible tubing confined within a fixed pump head. In the pump head, several rollers, which are connected to the motor shaft, rotate over the fixed tubing. The pump is equipped with a variable-speed drive to control the slurry flow rate. As the first roller passes over the tubing, it is squeezed essentially flat. As the tubing recovers its original round shape, it

Figure 2.1 Assembling Instrumentation for Horizontal Flow Train

Figure 2.2 Laboratory Facility

113-288

Figure 2.3 Peristaltic CWS Pump

draws in CWS from the storage tank. As the first roller continues over the tube, a second roller closes off the inlet to the pump and thereby traps a fixed volume of slurry within the pump head. As the pump continues to rotate, this fixed volume of slurry is forced out of the pump.

The peristaltic pump, because of its principle of operation, has several features that make it desirable for this application. First, none of the mechanical parts of the pump come in contact with the slurry, which is abrasive in nature. Thus any wear problems associated with the pump are minimized. Second, the pump does not allow back flow, which eliminates the need for a check valve in the fuel delivery line. Third, due to its positive displacement nature, the pump capacity is extremely insensitive to applied back pressure. For this reason, by calibrating the pump as a function of rotational speed, it can be used to measure the amount of slurry being burned. Finally, peristaltic pumps are fairly inexpensive and the only major maintenance they require is the periodic replacement of the pump head tubing.

A disadvantage of this type of pump is that it tends to introduce pulsations into the fuel delivery lines caused by the use of compressible tubing. This was particularly evident when the pump was used with the Y-jet atomizer. We found that these pulsations could be greatly reduced by using flexible tubing only in the pump head itself. By having inflexible tubing right after the pump head inlet and outlet, the fuel delivery system capacity was greatly reduced and flow fluctuations significantly diminished.

Figure 2.4 shows a comparison of peristaltic pump performance, in terms of capacity versus rotational speed, using CWS, No. 2 heating oil, and water. As shown in the figure, the flow rate of water and oil increase linearly with increasing roller speed. However, the same behavior is not true for CWS. For slurry, as the roller speed

Figure 2.4 Peristaltic Pump Performance

is increased, pump capacity tends to reach a maximum fixed flow rate. for a given pump head, and does not increase with increasing speed. This is due to the non-Newtonian behavior of the CWS. Although the peristaltic pump behaves like a positive displacement pump in the pump head itself, the amount of fluid it can pump depends on the amount of fluid it can draw into the fixed volume established by the moving rollers. As the pump speed is increased, the CWS that we are using exhibits a shear thickening behavior. Thus, the resistance to flow in the pump inlet line increases, which tends to reduce the pump's filling efficiency and places a limit on how much the pump can pass regardless of the rotational speed. In referring to Figure 2.4, it must be pointed out that the y-axis in the figure is the percent of the maximum flow rate of the liquid being pumped. Due to the sensitivity of the pump's filling efficiency to viscosity, for a given pump head and rotational speed, the less viscous water and oil have higher actual flow rates than the same pump passing CWS.

2.2 Y-JET ATOMIZER

System testing this quarter used a Y-jet atomizer to atomize the slurry and introduce it tangentially into the precombustor portion of the IRIS combustor. A photograph of the atomizer is shown in Figure 2.5, and Figure 2.6 is a photograph of the atomizer inserted into the combustor. This particular atomizer consists of a Y-shaped tube, 3/8-inch o.d. with a 0.035-inch wall in which slurry is pumped into one branch of the Y, and compressed air enters the outer branch. The mixture then enters a tube 1/4-inch o.d. with a 0.029-inch wall which is surrounded by another 3/8-inch tube. Compressed air is introduced into the annular space between these two tubes to aid in atomization and to help cool the inner tube containing the slurry, since the atomizer tip is inside the precombustion chamber of the IRIS. Under normal operating conditions, compressed air at 5 psi is required in the Y branch of the atomizer,

111-288

Figure 2.5 Y-Jet CWS Atomizer

Figure 2.6 Y-Jet Atomizer Inserted into Precombustor

and air at 20 psi is required in the annular cooling portion. The amount of air required by the atomizer is typically a small fraction of the total air required for combustion - in most cases less than 10 percent.

The type of Y-jet atomizer used in this work has several attractive features. The relatively large opening at the atomizer discharge greatly reduces the chance of clogging the unit. Also, this type of atomizer is very inexpensive. A problem that it does have, however, is that it is not capable of providing very fine atomization; however, this does not pose a problem for the IRIS combustor. The principle of operation of the IRIS combustor is to selectively detain larger particles in a hot precombustor chamber by the use of centrifugal force. This greatly increases particle residence time in the hottest part of the furnace. As the particles burn in the precombustor, they eventually become small enough so that the centrifugal forces in the precombustor can no longer detain them. Once this occurs, the particles fall into the main combustion chamber where they burn even further. With this type of operation, the IRIS combustor can obtain good carbon conversion efficiencies with the relatively coarse atomization provided by the Y-jet atomizer.

2.3 TEST RESULTS

In testing the furnace system this quarter, particular emphasis was placed on the IRIS combustor. During this testing period, the Y-jet atomizer was used exclusively to atomize the CWS fuel. The slurry that was burned was provided by Energy International, Inc. This particular slurry was 64.84 percent coal by weight, and had a heating value of 9762 Btu/lb of slurry. The type of coal used was deep-cleaned Upper Elkhorn #3 seam and had the following properties:

Weight % Ash (dry):	1.35%
Weight % Sulfur (dry):	0.58%
Heating Value (dry):	15,056 Btu/lb

Due to the low amount of ash in the coal, and to the low firing rate of the residential-sized furnace, typically 10 lb/hr of slurry, the system had to be run for periods of three to four hours to obtain reasonable amounts of ash for chemical analysis. The ash that was collected for chemical analysis was obtained from two different locations. Referring to Figure 2.7 (a schematic diagram of the vertical configuration test system) ash was collected in the ash collection transition box directly below the IRIS combustor, and in the ash collection system box directly below the heat exchanger. The reason for collecting ash samples at these two different locations is that the combustor ash collection box remains hot throughout a particular test. Particles that are separated out in this box are still able to burn. However, the smaller particles that are able to escape the transition box and pass through the heat exchanger are quickly extinguished by the cold walls. Thus, the amount of combustible matter remaining in the ash at this location is preserved. The analysis of ash at this location provides a conservative indication of the IRIS's combustion efficiency. The distribution of the amount of ash collected in each location has been found to be dependent on various parameters such as excess air and wall temperature; however, a breakdown of one-third collected in the combustor transition box and two-thirds collected in the ash collection system seems to be the norm.

Table 2.1 shows the results of a typical test in terms of measured system performance. Combustion efficiencies were determined by chemical analysis of the ash samples by a commercial laboratory.

The IRIS combustor was constructed of stainless steel, for initial testing purposes, so that modifications could be easily made. Typically, stainless steels are rated for 1650°F for continuous use in an oxidizing environment. We recognized that this would limit the allowable operating wall temperature; however, we chose to operate the system with elevated temperatures, around 1850°F, in the prototype

Figure 2.7 Schematic of Laboratory Facility

TABLE 2.1
TYPICAL TEST
MEASURED SYSTEM PERFORMANCE

Input Rate:	100,000 Btu/hr
Precombustor Wall Temperature:	1850°F
Excess Air:	110%
Combustion Efficiency: (Based on ash collected in the ash collection box below the heat exchanger)	96.6%
Combustion Efficiency: (Based on ash collected in the transition box below the combustor)	99.9%

combustor to achieve good combustion. These temperatures tend to limit the life of the prototype unit; however, they would not pose a problem for the next generation combustor which will incorporate refractory material to allow higher temperatures and to achieve a higher degree of carbon burnout.

Although high wall temperatures are desirable for good combustion efficiencies, they are not needed for ignition of the atomized CWS. Figure 2.8 shows a temperature history of the precombustor wall and flame temperature. The flame temperature on the figure is denoted in quotation marks, since this temperature is not compensated for radiation effects. Referring to the figure, at about 40 minutes into the test, the Y-jet atomizer was removed and the system was allowed to cool down slightly. Five minutes later, the atomizer was reinstalled in the prechamber of the combustor, and the slurry ignited with the wall temperature at only 1365°F.

It is interesting to note that to maintain even the elevated temperatures encountered during this testing, a large amount of excess air was required. For the present stainless-steel combustor, to maintain a wall temperature of 1850°F, the system had to be operated with 110 percent excess air. This is required to lower the flame temperature and keep the combustor walls from melting. Although this large amount of excess air does not appear to be detrimental to the performance of the IRIS combustors, in terms of overall furnace performance it is not desirable. Excess air tends to reduce the performance of the heat exchanger. For the shell-and-tube heat exchanger currently being tested, excess air can greatly reduce the number of transfer units (Ntu) of the heat exchanger. Figure 2.9 shows that operating the system with 110 percent excess air reduces the heat exchanger Ntu by 34 percent compared with the design condition of 0 percent excess air. The effect of this reduction of Ntu on heat exchanger effectiveness is shown in Figure 2.10, where a 10-point

Figure 2.8 "Flame" and Precombustor Temperature as a Function of Time

Figure 2.9 Effect of Excess Air on Heat Exchanger Number of Transfer Units

Figure 2.10 Effect of Excess Air on Heat Exchanger Effectiveness

drop in effectiveness from design conditions is realized by operating with 110 percent excess air. This decrease in heat exchanger effectiveness with increasing excess air increases the stack losses. Figure 2.11 shows a plot of stack heat losses including sensible and latent, as a function of excess air. Referring to the figure, operating this system with 110 percent excess air increases the stack losses from the design point 17 to 27 percent. In order to recover this additional 10 percent of the heat input, the heat exchanger would have to be substantially increased in size.

2.4 NEW COMBUSTOR DESIGN

The present stainless-steel combustor has demonstrated that the IRIS concept can burn coarsely atomized CWS with fairly high combustion efficiencies; however, it must be operated at lower wall temperatures which places a limit on attempts to improve combustion efficiency any further. Also, the large amount of excess air required to limit the wall temperature has an adverse effect on the heat recovery performance of the entire furnace. For these reasons, a new IRIS combustor has been designed. The new combustor is modular in design which allows the volume of both the precombustor and main combustion chambers to be varied. Also, provisions have been made to facilitate the changing of the combustion chamber liners. It is planned to test both silicon carbide and high-temperature metals such as Hastelloy alloy 188, in an effort to operate with between 20 and 30 percent excess air, and to operate with wall temperatures in excess of 2200°F. This should effect an increase in both combustion and overall system heat recovery efficiencies.

Figure 2.11 Effect of Excess Air on Stack Losses

3. SUMMARY STATUS ASSESSMENT AND FORECAST

Figure 3.1 illustrates the progress to date: the program is on schedule. Work is proceeding on the only remaining major task, Task 1.70, Testing and Development of Initial Prototype Components, and will continue until the end of this phase of the program.

The results of testing during this quarter have shown that the IRIS combustor is capable of operating with coarsely atomized slurry provided by the Y-jet atomizer. Measured combustion efficiencies, by chemical analysis of ash samples, has shown that the IRIS combustor is capable of combustion efficiencies of over 96 percent using this coarsely atomized slurry, with wall temperatures of only 1850°F.

Since tests have shown that the system does work with CWS, testing will continue on improving combustion and overall system efficiency. The procurement of materials and the construction of the next generation of the IRIS combustor will begin during the next quarter. Also, tests on the existing combustor will include turndown and various startup scenarios.

Figure 3.1 Status Chart

**DATE
FILMED**

8 / 19 / 93

END