Studies of Granular Flow Down An Inclined Chute*Quarterly Technical Progress Report**Year Two, Quarter Two: March 13, 1992 to 12 June, 1992*

DOE/PC/90182--T5

DE92 018871

Contract Number: DE-AC22-91PC90182**Contract Duration:** 12/13/90 to 12/12/94**Contractor:** University of Florida**Principal Investigator:** Daniel M. Hanes**DOE Project Manager:** William Peters

Received USF

AUG 06 1992

US/DOE patent clearance in not required prior to the publication of this document.**Progress Report:**

A preliminary series of experiments were run in order to examine the effects sidewalls have on the steady-state mass flow rate of granular material in a rectangular, inclined chute. These experiments also serve to assess the problems associated with the initial operation of the granular flow apparatus.

Presumably, the friction between the sidewalls and the flowing material will slow the flow rate of that material. The relative effect of the sidewalls should decrease with increasing width for a given flow entrance condition. For instance, when the width of the chute is at a minimum (one grain diameter), the sidewalls will have a maximum frictional effect. And as the width approaches infinity, the sidewalls will have a minimum frictional effect. It is desired to know at what chute widths the sidewall effects will reasonably approach this minimum, if this condition can even be approached with the existing apparatus.

The relationship between chute width and flow rate will be important to know during more involved experiments which will follow this initial investigation. These experiments will include the measurement of localized grain density, local velocity and individual grain dynamics (rotation and translation) and collisions.

The secondary objective, to observe and correct problems with the system, is a more general and qualitative goal. This is the first time this system has been run and there are bound to be many faults inherent to it. This report will attempt to point out and, where possible, offer solutions to these problems.

The granular material used in the experiments described in this report are technical quality glass spheres, three millimeters in diameter. These beads are

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

11/14/27 1992

produced by Cataphote, Inc. Cataphote lists the tolerances for the 3mm spheres at ± 0.2 mm. The average mass of a single bead was measured to be 0.034 g which gives an average measured specific gravity of the glass at 2.42 g/cm³.

The region within which the properties of this granular material will be studied is a rectangular aluminum chute with clear lexan sidewalls. The interior of the chute is twelve feet long, eighteen inches tall, and the width is adjustable from zero to ten inches in one inch increments. A drawing of the chute appears in Figure 3.1. The 3/4 inch channel design of the chute floor was designed to deflect less than 1/100 inch for all twelve feet of the chute (14 seconds) when supported horizontally by its ends. The floor of the chute is designed to be covered with interchangeable Plexiglass inserts, allowing different floor- roughness conditions to be studied.

The angular range which the chute is to be operable in was specified as 0° to 35°. Additionally, the chute had to be adjustable to within the 1/100 inch tolerance at any angle. After many different design ideas, a final design was agreed upon, as shown in Figure 3.2. This design dictated that the chute be supported at six points and pivot at the top (entrance) in a single plane. The lower four supports consist of square telescoping tubing to allow for the various angles. At the base of each of these adjustable legs is a worm gear screwjack. One turn of the shaft on these jacks extends the leg 1/40 inch. At the two top pivot points there are adjustable wedge jacks. These six jacks (one for each support point) allow the chute to have the micro-adjustability required. There are ten pivot points, each physically achieved by a pillow block bearing.

The driving force for the granular flow in the experimental region is gravity. The vehicle which re-circulates this flow is an eighteen inch Corra-Trough® belt conveyor manufactured by Buck-El, Inc. A drawing of this conveyor is shown in Figure 3.3. Entrance and exit chambers were designed to route the flow between the chute and the conveyor. Both devices had to be flexible because the position of the chute relative to the conveyor changes each time the angle of the chute is changed. Photos of the entrance and exit chambers appear in Figures 3.4 and 3.5, respectively. A six-inch rubber iris valve controls the main flow between the top hopper and the entrance chamber.

Finally, to control the entering flow more accurately, an adjustable gate apparatus was constructed. This mechanism, shown in Figure 3.6 positioned at the top of the chute, is adjustable for any width and can be positioned anywhere along the length of the chute. The aluminum plate which forms the gate itself is what allows the adjustability as it is completely interchangeable, permitting an almost infinite number of entrance conditions to be created.

The granular flow system has basically four variables: iris aperture, r_i , chute width, w , entrance gate height, h , and chute angle, α . For these experiments the iris aperture will be held constant (closed when setting up chute, fully open when taking experiments) as will the chute angle. The only variables, then, are chute width and gate height. The quantity which these variables presumably affect is mass flow rate.

The first step in setting up the chute is angle adjustment. It was decided that the experiment be run at approximately 25° because this angle produces fairly chaotic flow conditions, as opposed to sliding flow conditions. The chute is supported by a movable hoist and the pins are removed from the four telescopic leg supports. Pivoting about the two top support points, the chute is lowered to the proper angle. The angle is read by an Inogon inclinometer, which uses a vernier scale and two diffraction grating discs and is accurate to 0.2° . The pins are replaced and the hoist removed when the angle is close to 25° . A somewhat iterative process is performed whereby an angle reading is taken at different points on the chute floor and the six legs of the chute are adjusted until the angle is the same at all points. When the chute was finally set the angle, α , was read at 24.8° . This is the angle at which all measurements will be taken.

To vary the chute width, Plexiglass inserts were milled to within .01 inch for four different widths: 4, 6, 8, and 10 inches. These inserts comprise three four-foot sections for each width. To set the width, the chute's removable wall is loosened to allow the floor inserts to fit between the walls. Next, the sliding wall is pressed against the inserts and the bolts tightened. The entrance chamber opening is then lined up with the centerline of the chute.

The gate of Figure 3.6 is positioned approximately eight inches from the top of the chute. This gate, when opened, provides a rectangular section through which the granular material enters. The area of this section is simply the width times the height of the gate, $A = w \cdot h$. In order to provide consistent entrance conditions for each experiment, enough material must be in the system such that just upstream of the entrance gate the glass beads are stagnant, forming a reservoir analogous to "head" in a fluid flow situation. Figure 4.1 is a picture of the head formed when the gate is closed and the iris valve opened. In this way, material begins with effectively zero velocity and accelerates only as it passes through the rectangular entrance section. The height of the entrance gate is set with the help of an aluminum gage milled from .25 inch to 1.50 inch in .25 inch increments.

Thus there are four different widths and six different entrance heights which can define a single run of the chute system. Additionally, the flow can be run without the gate restricting the flow, when the gate is wide open, for each chute width. The idea behind these experiments is that friction within the chute itself will serve as a restriction to the flow. If there is enough material in the system then the open flow rate for each successive chute width should be proportionally greater than the previous one. The experiments now add up to a total of twenty-eight different chute configurations which may be run at this angle.

Since the main purpose of this experiment is to measure mass flow rate under each of these conditions, a method to do this had to be devised. An instantaneous mass flow rate measurement would be ideal for future experiments. Several ideas were proposed to accomplish this task but each of them would initially require a standard in order to be calibrated. The standard which was constructed is simply a beam-balance linked to a timer, as shown in Figure 4.2. This method produces a time-averaged mass flow rate which is acceptable for the present experiments since the flow is essentially steady-state.

To take a measurement, the first step (after setting the height and width) is to turn on the conveyor and open the iris valve. Waiting approximately one minute will allow the flow to reach steady-state. Meanwhile, the timer is reset, a catch bucket is placed on the balance and the counter weight is set to a mass, m_1 , high enough to offset the weight of the bucket. Next, the flow is diverted from the bottom hopper of the conveyor into the catch bucket. As the mass in the bucket surpasses m_1 the arm of the balance trips a switch which starts the timer. Now, enough additional weight, m_2 (≈ 30 lb for small h and ≈ 80 lb for large h), is added to the counter balance arm. When the mass in the bucket reaches m_2 the switch is tripped again and the timer stopped. If t is denoted as the time that appears on the timer, then the mass flow rate is given by $(m_2 - m_1)/t$.

For each chute configuration three mass flow measurements are to be taken, giving a total of eighty-four measurements. The average mass flow rate for each restricted chute configuration (when the flow is stagnant behind the gate) are given in Table 5.1. These data appear graphically in Figure 5.1. All mass flow rates referred to in this section are average mass flow rates unless otherwise stated.

Only 5 data points appear for the 8.00 inch width and only 4 appear for the 10.00 inch width. This is due to the material free-flowing (the gate having no influence) at gate heights of 1.50 inch and 1.00 inch and greater for the 8.00 inch and 10.00 inch widths, respectively.

As expected, the mass flow rate increases as either the gate height or chute width is increased. Upon closer examination, however, it is also noted that for a given gate height, increases more than proportionally for each successively greater chute width. For example, given a gate height of 0.75 inches, the mass flow rate is 1.62 lb/s when the chute is 4.00 inches wide. When the chute width (and hence the entrance area) is increased by 50% to 6.00 inches, the mass flow rate increases by 52% to a value of 2.46 lb/s. Likewise, when the width is increased from 4.00 to 8.00 inches (100%) at $h = 0.75$ inch, the mass flow rate increases by 102%.

This trend is followed for all restricted configurations when either the gate height is greater than 0.50 inch or the chute width is greater than 6.00 inch. In other words, the only time the data does not follow this pattern is when the width is increased from 4.00 to 6.00 inches at gate heights of 0.25 and 0.50 inch.

Another way to present the data is in terms of chute width, w , versus mass flow rate per unit entrance area, $/A$, for constant values of gate height. The curves of Figure 5.2a display this relationship. These lines are relatively flat for increasing chute width and become closer together as gate height increases. A more revealing display of the same data is shown in Figure 5.2b, which is simply a transposition of Figure 5.2a. In this figure lines of constant chute width are plotted for varying gate height. For each chute width the curves are practically the same. The implications of these two figures will be discussed in the next section.

Figure 5.3 shows the measured mass flow rate values when the gate was opened and the material allowed to free-flow. The only thing restricting the flow during these trials was the open iris valve (which is the smallest cross

sectional area the material passes through). These data do not seem to follow any particular pattern and there are probably many factors which influence these numbers.

In terms of qualitative observations there were many minor difficulties associated with construction and operation of the chute apparatus. The vast majority of these were solved prior to taking the data involved with this report. However, there remain six main points which, while probably not affecting the data herein, should nevertheless be discussed. In no particular order these include problems related to the entrance and exit chambers, static electricity build-up, the mating of floor insert sections, the loss of material during conveyor operation, and general corruption of the granular material.

First, conditions at the flow entrance were less than ideal. The idea was that behind the gate opening the flow would be essentially stagnant, thereby providing consistent entrance conditions for each measurement. This situation was realized for the smaller gate heights. However, when the flow rate was more extreme, at greater entrance gate heights, the material behind the gate tended to be more excited. The term "head" was introduced earlier to describe the height of the build-up of material behind the gate. In the less intense flow situations this head remains constant but during greater flow volumes becomes more unstable.

At the other end of the chute is the exit chamber, which routes the flow into the bottom hopper. This device is adequately sized; that is, it does not restrict the flow under any of the tested chute conditions. Because of the steep angle that the back makes with the chute floor (see Figure 3.5), however, some very minor reflection of individual beads back into the chute (on the order of 1 per second) was seen to occur.

Thirdly, the problem of static electricity build-up within the material and on the walls of the chute must be addressed. This phenomenon seemed to occur randomly and probably depended a great deal on the daily air quality in the laboratory. Some days there would be no notice of any static and other days one would receive a slight shock from the walls of the chute when adjustments were made. The 16th of April was an especially good day for static. No quantitative measurements were taken, but the presence of this static electric charge did not seem to restrict or alter the flow in any way.

As mentioned before, the floor of the chute is made of three four-foot Plexiglass sections, a different set for each width setting. Where the ends of these sections come together two seams are formed, one about a third of the way down the chute and another two thirds down. If the edge of one section was just a fraction of an inch higher than the section upstream of it then a very strong effect was produced. The beads striking this imperfection in the floor bottom were deflected fairly violently upward, forming a "rooster tail" pattern. To correct for this a spacer in the form of a strip of paper was placed under the upstream section's edge, insuring that section would be higher. This, while still an imperfection, affected the flow in what was considered a negligible way.

One major problem observed is that of spillage. While the manufacturer of the conveyor, Buck-EI, designed it to have no losses, this was far from the case. The actual losses, most of which fell through the spaces between the belt and the bottom hopper, were measured to be approximately 60 lb/hr. The

losses were virtually nil from the experimental chute section itself, however. Measures taken to prevent spillage mostly consisted of cardboard guards positioned around high loss areas. To keep the losses from significantly affecting the volume of material, spilled material was recovered and returned to the flow following each series of experiments.

Finally, the issue of general pollution of the granular material must be covered. With fresh beads in circulation, the material becomes dirty after running the system for only a few minutes. The corruption falls into two categories: particles whose sizes are on the same order of magnitude as the beads and particles which are several orders of magnitude smaller than the beads. The first category is mainly composed of small rubber pieces, but also includes some metal chips presumably left from the manufacturing of either the conveyor or the chute. The second category consists of dust particles from the air as well as rust particles (probably from the bottom hopper, which was never painted). Build-up of dirt particles was found both within the volume of circulating material and on the walls and floor of the chute. The inside of the chute was wiped out following each set of experiments to minimize effects this dirt might have.

There are several conclusions which can be drawn and recommendations which can be made from the data and observations of the previous section. However, the most significant and unanticipated finding is this:

While the sidewalls do have a slight effect on flow rate, a much greater effect is due to the entrance conditions, specifically the height of the entrance gate. This implies that future experiments may be run for any of the widths tested herein (4.00, 6.00, 8.00 and 10.00 inch) at this angle (24.8°) without the sidewalls having a significantly different effect (i.e. the sidewalls have approximately the same relative effect when the chute width is 4.00 inch as they do when the chute is 10.00 inch wide).

Figure 5.1 and Table 5.1 imply a relationship between the sidewalls and the flow rate. The disproportional increase in flow for a given gate height from one width to a greater width indicates that the sidewalls have a greater effect on flow when the chute width is smaller. This tends to support the theory that as chute width approaches infinity a minimum sidewall effect is reached.

The next two figures, 5.2a and b, expose a different relationship: that the restrictive gate has more of an effect on flow than chute width. Consider the theoretical situation where the edges of the entrance region do not affect the flow at all. In this case the flow rate would only depend on the size of the opening. Therefore, the flow rate per unit area, $/A$, would be constant for any entrance size and both Figures 5.2a and 5.2b would be horizontal lines. Figure 5.2a shows that for changing chute width the flow per unit area, while it is increasing (except for the two instances mentioned earlier), it is doing so only slightly; the lines are essentially flat. This is not the case for increasing gate height. The curves of Figure 5.2b are far from flat; they are closer to exponential curves. If it were possible to continue increasing the gate height and still maintain a head behind the gate, these curves would probably flatten out as well.

The differences in flow per unit area readings for the smaller gate heights (0.25 and 0.50 inch) are slight enough to be attributed to experimental error.

This could explain the fact that the flow rate per unit area is less at $w = 6.00$ inch than it is at $w = 4.00$ inch for these two gate heights (see Figure 5.2a). The difference in flow per unit area readings for increasing width are more evident for the higher values of gate height. This is most likely indicative that the sidewalls have a greater effect when the gate height is greater; this is logical since at greater gate heights there is more exposed sidewall at the entrance. For instance, when $w = 6.00$ inch and $h = 0.25$ inch only 0.50 inch of the entrance perimeter is sidewall (4.0 %), while at $h = 1.50$ inch, 3.00 inches of this perimeter is sidewall (20.0 %). This is evidenced by Figure 5.2b, where the lines of constant chute width start out close together and spread apart as the gate height increases.

Since the results displayed in Figure 5.3 arise from conditions of open flow, they are not included with and cannot be compared to the restricted flow results. The values of measured for open flow do not seem to follow any trend. The reasons for the values obtained are unknown. Without having a fixed entrance condition to go by, and without taking other measurements within the circulation system, conclusions are difficult to draw from this data. These values probably depend on many factors including total volume of material in the system, radius of the iris aperture, r_i (which is difficult to measure), effects of the entrance chamber (since the material is no longer stagnant in this region), and others.

One theory which may explain the sudden rise in the curve of Figure 5.3 and the subsequent negative slope can be presented. It must be stressed that this theory is based on only four data points and cannot be taken as truth until many more experiments are taken. The theory is this: If the same amount of material is entering the chute over a period of time, then the wider chute width will actually produce a lower mass flow rate than a more narrow chute. This is contrary to initial intuition, perhaps, but it makes sense when the frictional contact area is considered. At a narrow chute width, the vertical flow depth is greater and the perimeter (and therefore the area) of contact between the granular material and the chute walls and floor is smaller. As the chute width is increased, so is the contact perimeter and hence the friction is greater (i.e. more beads touch the walls and floor), producing a smaller flow rate. In the case of Figure 5.3, the decrease in flow rate might be explained by this theory. The first requirement of this theory is met, that is the amount of material entering the chute is the same. This is because the opening of the entrance chamber is six inches wide allowing the entire flow to enter the chute whenever the width of the chute is six or more inches. The low value of the first data point in Figure 5.3 could then be accounted for by the fact that the chute width is only 4.00 inches wide at this point, thereby restricting the entering flow.

The first qualitative observation presented in the results section was the problem of material activity behind the entrance gate, where a standing volume of material is supposed to exist. Particularly, the problem of varying head at high flow rates should be addressed. This is caused by most of the material being in circulation (in the chute or on the conveyor), rather than building up in the upper hopper. As the mass flow rates did not exceed the maximum ability of the conveyor, none of the material accumulated in the lower hopper. This dilemma could probably be eliminated simply by adding more material to the system.

One recommendation is that the concept of "head" as it applies to this granular flow system should be studied more closely. It is not known how or if the level of head built up behind the gate affects the flow. If the height of the stagnant reservoir could be held at different values while flow rate measurements were taken, a relationship between head and flow rate could be established.

The exit chamber was fashioned in such a way (rather a short distance from end of chute to back wall of chamber) in order to permit the flow to still be routed into the lower hopper at large values of α . The resulting steep angle of the chamber back caused small numbers of beads to be reflected back into the flow. While this has no effect on steady-state average mass flow values, it may have some effect on future experiments. The solution to this can take two forms. Either a shock absorbing surface can be fixed to the back of the exit chamber or a new chamber can be constructed which is designed in such a way that colliding beads are not reflected back into the chute, but rather into the hopper. The former of these two solutions is certainly the simplest.

The build-up of static electricity, although seemingly not strong enough to restrict flow of the 3 mm beads, could become a major problem in the future as the introduction of sensitive electronic devices occur. The elimination of this static electricity should not be very difficult, however. It would seem that the simple grounding of the chute and conveyor apparatus would serve to dissipate any charge build-up.

There are two solutions to the "rooster tail" problem which may be implemented. This problem, which also does not affect average steady-state flow conditions at this angle, will become more important when other measurements within the chute region are to be taken. The best solution would be to acquire long enough sheets of Plexiglass from which to cut floor inserts to cover the chute from top to bottom. If twelve-foot sheets of Plexiglass can not be obtained, the second solution is to precisely machine holes in the ends of the existing inserts. Joining pegs can be placed in these holes and the seam can be sanded smooth to insure no edge will form for the beads to collide with.

The problem of spillage from the conveyor belt is more of an inconvenience than a real problem. The rate of spillage is not great enough to affect average flow rates or any foreseeable future experiments, since none of the losses appear to come from the chute itself. The only solution, barring purchase of a new conveying system, is to meticulously locate areas where leakage occurs and take measures to eliminate that leakage.

Corruption of the granular material by foreign particles may also become a serious problem as more and more sensitive measurements of the flow are taken. There are two problems to overcome. The first is the cleaning of the existing material and the second is the elimination of further pollution. Most of the dirt particles seem to originate within the system, including the rubber, metal and rust particles. It may be that now that the system has been run for a significant period of time all of the loose particles have been absorbed by the granular material and no additional garbage is being introduced. It could also be that the system is continually producing new garbage. The actual case is most likely somewhere in between these two extremes. The amount of dirt

permitted in the system must be defined before cleaning measures are undertaken.

This project, although having undergone many delays, has been rather productive overall. It was determined that, for this angle, the difference in sidewall effects between the minimum chute width (4.00 inch) and maximum chute width (10.00 inch) is minimal. A significant effect on flow rate is seen, however, in relation to entrance gate height. Now that these relationships have been quantified, the data can be referenced when experiments are performed under similar circumstances. It should be stressed that these relationships are valid only for this angle ($\alpha = 24.8^\circ$). The data is very well suited to dimensionless analysis, however, and relationships could probably be developed to cover the entire range of variables, following many more experiments at different angles. Also, it should be pointed out that a more accurate appraisal of sidewall effects could be carried out by measuring the velocity profile across the width of the flow, once the ability to do so is established. Hopefully the recommendations for solutions to the six quantitative observations will be helpful for performing future experiments.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Table 5.1. Average mass flow rate, $\dot{m}$, for varying values of chute width, w , and gate height, h .

$h(\text{in})$	$w(\text{in})$	4.00	6.00	8.00	10.00
0.25		0.19	0.27	0.38	0.49
0.50		0.84	1.22	1.68	2.27
0.75		1.62	2.46	3.26	4.39
1.00		2.50	3.88	5.22	6.72
1.25		3.49	5.42	7.42	-
1.50		4.61	7.12	-	-

Figure 3.1. Dimensions of experimental chute.

Figure 3.2. Drawing of chute and adjustable, supporting framework.

Figure 3.4. Entrance chamber.

Figure 3.5. Exit chamber.

Figure 3.6. Photograph of entrance gate apparatus affixed to top of chute.

Figure 4.1. Photograph of "head" which forms behind the closed entrance gate.

Figure 4.2. Beam balance and timer used to measure mass flow rate.

Figure 5.1. Gate height, h , vs. mass flow rate, $\dot{m}$, for constant values of chute width, w .

Figure 5.2a. Chute width, w , vs. mass flow per unit area, $\dot{m}/A$, for constant values of gate height, h .

Figure 5.2b. Gate height, h , versus mass flow per unit area, $\dot{m}/A$, for constant values of chute width, w .

Figure 5.3. Chute width, w , vs. mass flow rate, $\dot{m}$, for open flow (unrestricted) conditions.

END

**DATE
FILMED**

10 / 6 / 92