Low Severity Coal Liquefaction Promoted by Cyclic Olefins

Dt. FG22-91PC 91.281

**Quarterly Report
October to December 1992**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**Christine W. Curtis
Chemical Engineering Department
Auburn University, AL 36849**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

for

Acknowledgment

Researchers contributing to this report are: Dr. Lynn M. Perry, Shou-Ta Chen, and An Ping Huang. The technical assistance of Frank Bowers and Joe Aderholdt is gratefully acknowledged.

Table of Contents

Introduction	1
Part I. Low Severity Coal Liquefaction Using Hexahydroanthracene	2
Objective	2
Experimental	3
Results & Discussion	5
Thermal & Catalytic Low-Severity Liquefaction Reactions with Hexahydroanthracene	5
Parametric Evaluation	9
Summary	18
Future Work	18
References	18
Part II. Infrared Studies of Cyclic Olefins	19
Introduction	19
Objective	19
Progress	19
Future Work	25
Experimental	27
Materials	27
Experimental Procedures	29
References	29

LOW SEVERITY COAL LIQUEFACTION PROMOTED BY CYCLIC OLEFINS

INTRODUCTION

Low severity coal liquefaction promoted by cyclic olefins offers a means of liquefying coal at low severity conditions. Lower temperature, 350°C, and lower hydrogen pressure, 500 psi, have been used to perform liquefaction reactions. The presence of the cyclic olefin, hexahydroanthracene, made a substantial difference in the conversion of Illinois No. 6 coal at these low severity conditions. The Research performed this quarter was a parametric evaluation of the effect of different parameters on the coal conversion and product distribution from coal. The effect of the parameters on product distribution from hexahydroanthracene was also determined. The work planned for next quarter includes combining the most effective parametric conditions for the low severity reactions and determining their effect. The initial reactions will be performed with Illinois No. 6 coal. The best parametric combination will be tried with other coals such as the bituminous coal, Pittsburgh No. 8, and the subbituminous coal, Wyodak.

The second part of the research performed this quarter involved performing Fourier transform infrared (FTIR) spectroscopy using cyclic olefins. The objective of this study was to determine the feasibility of using FTIR and a heated cell to determine the reaction pathway that occurs in the hydrogen donation reactions from cyclic olefins. The progress made to date includes evaluating the FTIR spectra of cyclic olefins and their expected reaction products. This work is included in this progress report. The research planned next quarter is to begin using the high-temperature cell to assess the difficulties involved as well as to determine the products produced from the cyclic olefins as the temperature is raised in a nitrogen atmosphere.

PART I

LOW SEVERITY COAL LIQUEFACTION USING HEXAHYDROANTHRACENE

Low severity coal liquefaction allows for solubilization of coal with reduced gas make. These lower severity conditions may result in some selective bond rupture. However, usually at low severity conditions, the amount of coal solubilization is much lower than what is normally obtained at higher severity conditions. Promotion of coal solubilization through hydrogen transfer using highly active and effective hydrogen donors is the objective of this study.

The highly effective donors being tested are cyclic olefins. Representative cyclic olefins are isotetralin, which is 1,4,5,8-tetrahydronaphthalene, and 1,4,5,8,9,10-hexahydroanthracene. These compounds are hydroaromatics without aromatic rings and have been shown to be highly effective donors (Bedell and Curtis, 1991). Some recent studies have compared the ability of isotetralin to release hydrogen at 380°C in both nitrogen and hydrogen atmospheres to that of tetralin. Likewise, at 380°C the ability of hexahydroanthracene to release hydrogen in nitrogen and hydrogen atmospheres was compared to that of dihydroanthracene. At equivalent reaction conditions and in the presence of anthracene as a hydrogen acceptor, isotetralin released more than 200 times as much hydrogen as tetralin and hexahydroanthracene released 18 to 25 times as much hydrogen as dihydroanthracene (Wang, 1992).

Objective

The objective of the research performed during this quarter was to determine the effect of reaction parameters on low severity coal liquefaction with hexahydroanthracene present. The reactions were performed at 350°C using a hydrogen pressure of 500 or 1000 psig and a reaction time of 30 or 60 min. The reactions were performed with hexahydroanthracene at 0.5 or 1.0

wt % donable hydrogen (0.61 or 1.22 g). The reactions were performed both thermally and catalytically. The catalysts used were Molyvan L without sulfur, Molyvan 822 with sulfur, and molybdenum naphthenate with sulfur. Molyvan L is a sulfurized oxymolybdenum dithiocarbamate and Molyvan 822 is a molybdenum dithiocarbamate.

Experimental

Thermal and catalytic reactions of Illinois No. 6 coal were performed at low severity conditions using ~ 50 cm³ stainless steel tubular microreactors. The first set of reactions that were performed were at 350°C with hexahydroanthracene added at a 0.5 wt % donable hydrogen level. The reaction time was 30 min and the hydrogen pressure introduced at ambient temperature was 500 psig (which equalled 0.16 g of H₂). The reactors were agitated vertically at 450 cpm. The solvent used in the experiment was hexadecane. The coal loading was 2.0 g; the total liquid charge was 4 g with 0.61 g of the liquid being hexahydroanthracene. For the parametric evaluation, the pressure was raised to 1000 psig and the hexahydroanthracene was increased to 1.22 g. In addition, the reaction time was increased to 60 min and the catalyst loading was increased to 1000 ppm.

The liquid products from the experiments were analyzed in terms of a product distribution of gas, oil (hexane solubles), asphaltenes (hexane insolubles, toluene solubles); preasphaltenes (toluene insolubles, THF solubles); and insoluble organic matter (IOM)(THF insolubles that are catalyst- and ash-free). The procedure for performing the product separation undertook the following steps: (1) liquefaction products were removed from the stainless steel tubular microreactor with hexane and decanted into a 250 ml beaker; (2) the beaker was then filled with approximately 150 ml of hexane; (3) the solution was sonicated using a Branson 350 sonifier for

approximately 4 min; (4) the solution was then poured into 250 ml centrifugal bottle and centrifuged for about 10 min; (5) the liquids were then decanted into a 500 ml flat-bottom flask; (6) the solution was then rotovaporated and heated while a nitrogen purge was used to promote the evaporation of the liquid; and (7) after rotovaporation, the oil left in the round-bottom flask was dried in the hood for 1 day and weighed. The same procedure was used for obtaining asphaltenes, preasphaltenes and IOM. After rotovaporation, each of these three materials were dried in a hood for 1 day and then weighed.

The reaction products from hexahydroanthracene were analyzed on a Varian 3700 gas chromatograph equipped with a Supelco DB-5 column, splitless injector and flame ionization detector. Quantitative analysis of the products were achieved using the internal standard method with p-xylene as the internal standard.

The catalyst precursors used were Molyvan L, Molyvan 822, and molybdenum naphthenate (Mo naphthenate) for the first set of experiments. All of the catalysts were introduced at a level of 500 ppm of Mo on a basis of total feed. Molyvan 822 and molybdenum naphthenate were reacted in the presence of sulfur where sulfur was added at a 3:1 sulfur to molybdenum stoichiometric ratio. Molyvan L was reacted in the absence of sulfur. For the parametric evaluation, the catalyst used was Mo naphthenate at a loading level of 1000 ppm.

The following term, percent hydrogenation (% HYD), is defined to assist in comparing the results from a number of different reactions. Percent hydrogenation is the number of moles of hydrogen required to produce the liquid reaction products as a percentage of the moles of hydrogen required to achieve the most hydrogenated product. For hexahydroanthracene, the most hydrogenated product was considered to be perhydroanthracene.

Results and Discussion

Thermal and Catalytic Low-Severity Liquefaction Reactions with Hexahydroanthracene

As was discussed in the previous quarterly report, the product distributions previously obtained for the low severity coal liquefaction reactions with hexahydroanthracene (HHA) were suspect. In order to check the product distributions and the coal conversion previously obtained (Table 1), the low severity coal liquefaction reactions with HHA were performed again. The results from the newly performed liquefaction reactions are given in Table 2.

The coal conversion for the catalytic reactions were somewhat higher in the repeated experiments compared to the first set. The coal conversion changed most radically for the thermal reaction. The coal conversion increased from 34.3% (Table 1) to 40.7% (Table 2).

The normalized product distributions present the data so that they can be compared readily. In the new data (Table 2), the amount of oil was usually less than that observed in the previously obtained data. It is interesting to note that although the thermal and catalytic coal conversions with HHA were very similar in the new data (Table 2), the amount of oil for the thermal reaction was ~55% which was lower than the catalytic reactions. All of the catalytic reactions yielded oil amounts that ranged from 61.4 to 64.1% (Table 2). The data given in Table 2 is taken as the baseline data for the parametric evaluation since all of the product distributions for the parametric evaluation were performed in the same manner.

The product distributions obtained from gas chromatographic analysis of the hexane soluble oils yielded the products formed during the reaction from HHA. These products are presented in Table 3. In the newly performed reactions, consistently more HHA remained after reaction, more anthracene (ANT) and octahydroanthracene (OHA) were formed and less

Table 1. Product Distribution for Thermal and Catalytic Reactions of Illinois No. 6 Coal with Hexahydroanthracene at 350°C (Previous Data)^a

Product Distribution (weight in grams)	Catalyst			
	None	Molyvan L ^b	Molyvan 822 ^c	Mo Naphthenate ^c
Gas	0.155 ± 0.007	0.160 ± 0.000	0.165 ± 0.007	0.160 ± 0.000
Oil	3.643 ± 0.184	3.557 ± 0.021	3.463 ± 0.025	3.239 ± 0.067
Asphaltenes	0.087 ± 0.003	0.081 ± 0.006	0.113 ± 0.037	0.063 ± 0.001
Preasphaltenes	0.847 ± 0.114	1.074 ± 0.014	0.559 ± 0.018	0.818 ± 0.038
IOM ^d	1.024 ± 0.023	0.903 ± 0.002	0.963 ± 0.021	0.916 ± 0.015
Coal Conversion, %	34.3 ± 1.5	42.0 ± 0.1	38.2 ± 1.4	41.1 ± 1.0
Recovery, %	96.7 ± 1.5	98.4 ± 0.5	90.8 ± 2.0	89.0 ± 1.5
Product Distribution Normalized (weight percent)				
Gas	2.60 ± 0.18	2.73 ± 0.01	2.83 ± 0.07	2.72 ± 0.08
Oil	64.51 ± 3.24	62.25 ± 0.27	69.09 ± 0.47	66.70 ± 0.65
Asphaltenes	1.46 ± 0.01	1.37 ± 0.10	1.94 ± 0.61	1.07 ± 0.05
Preasphaltenes	14.24 ± 2.25	18.29 ± 0.23	9.61 ± 0.49	13.91 ± 0.21
IOM	17.19 ± 0.80	15.36 ± 0.05	16.53 ± 0.67	15.60 ± 0.73

^a Reaction Conditions: 500 psig H₂ at ambient temperature, 30 min reaction time, 2 g of Illinois No. 6 coal, 0.61 g of HHA; 4.0 g total liquid charge with hexadecane as solvent, 500 ppm of Mo on a feed basis when catalyst is present.

^b Without sulfur.

^c With sulfur.

^d IOM: Insoluble organic matter which is ash free.

Table 2. Product Distribution for Thermal and Catalytic Reactions of Illinois No. 6 Coal with Hexahydroanthracene at 350°C (New Data)^a

Product Distribution (weight in grams)	Catalyst			
	None	Molyvan L ^b	Molyvan 822 ^c	Mo Naphthenate ^c
Gas	0.145±0.007	0.145±0.007	0.140±0.014	0.170±0.014
Oil	3.093±0.087	3.544±0.007	3.291±0.018	3.378±0.007
Asphaltenes	0.130±0.019	0.120±0.008	0.133±0.013	0.126±0.008
Preasphaltenes	1.463±0.056	1.072±0.024	1.052±0.041	0.965±0.233
IOM ^d	0.927±0.033	0.881±0.039	0.945±0.034	0.843±0.013
Coal Conversion, %	40.7±2.1	43.4±2.6	39.2±2.2	45.8±0.8
Recovery, %	97.9±0.3	98.1±0.4	94.7±0.1	92.8±2.7
Product Distribution Normalized (weight percent)				
Gas	2.47±0.12	2.46±0.06	2.38±0.24	2.91±0.16
Oil	54.67±1.25	61.99±0.90	61.41±0.09	64.11±3.29
Asphaltenes	2.22±0.32	2.03±0.18	2.26±0.21	2.16±0.21
Preasphaltenes	24.88±0.91	18.14±0.01	17.89±0.69	16.43±3.51
IOM	15.76±0.54	15.38±1.03	16.06±0.57	14.39±0.17

^a Reaction Conditions: 500 psig H₂ at ambient temperature, 30 min reaction time, 2 g of Illinois No. 6 coal, 0.61 g of HHA; 4.0 g total liquid charge with hexadecane as solvent, 500 ppm of Mo on a feed basis when catalyst is present.

^b Without sulfur.

^c With sulfur.

^d IOM: Insoluble organic matter which is ash free.

**Table 3. Product Distribution from Hexahydroanthracene in Reaction
with Illinois No. 6 Coal**

Reaction Conditions				Product Distribution, wt %			
Catalyst	Level (ppm)	Temperature (°C)	Pressure (psi)	ANT	DHA	HHA	OHA
None	0	350a	500	11.16±1.39	34.65±0.58	44.64±0.88	9.55±0.26
	0	350b	500	17.18±1.53	23.06±0.95	51.44±0.57	8.32±0.85
Molyvan L without Sulfur	500	350a	500	8.13±1.95	42.00±1.93	40.60±1.50	9.27±0.89
	500	350b	500	12.99±2.09	34.31±1.08	41.33±0.99	11.37±1.07
Molyvan 822 with Sulfur	500	350a	500	8.30±0.57	39.80±0.52	42.96±0.73	8.94±0.33
	500	350b	500	11.22±1.09	32.30±1.59	46.04±1.60	10.44±0.79
Mo Naph with Sulfur	500	350a	500	10.20±2.37	35.44±0.83	43.80±2.70	10.56±1.37
	500	350b	500	13.89±0.98	26.15±0.69	50.37±0.25	9.59±1.24

a: old data b: new data

Reaction Conditions: 500 psig H₂ at ambient temperature, 30 min reaction time, 2 g Illinois No. 6 coal, 0.61 g HHA, 4.0 g total liquid charge with hexadecane as solvent, 500 ppm of Mo on feed basis when catalyst was present.

ANT = anthracene, DHA = dihydroanthracene, HHA = hexahydroanthracene, OHA = octahydroanthracene, Naph = Naphthenate, HYD = hydrogenation

dihydroanthracene (DHA) was produced compared to the previous reactions. It is interesting to note that more ANT was formed in the thermal reaction than in any of the catalytic reactions which indicates that the catalyst promoted hydrogenation of HHA. For all the reactions, the net amount of hydrogen transferred was greater than that accepted by the HHA. A negative percent hydrogenation was obtained in both thermal and catalytic reactors (Table 4).

Parametric Evaluation

A parametric evaluation of the factors that influence low severity coal liquefaction was performed. The parameters that were examined were hydrogen pressure, catalyst loading, reaction time, and hydrogen donor level. Two systems were chosen for the evaluation: thermal reaction system with Illinois No. 6 coal and hexahydroanthracene and catalytic reaction system with Illinois No. 6 coal, hexahydroanthracene, Mo naphthenate and excess sulfur.

The hydrogen pressure was increased from 500 psi to 1000 psi in both the thermal and catalytic reactions with Mo naphthenate. A comparison of the results is given in Table 5. Coal conversion was higher at the lower hydrogen pressure for both the thermal (40.7%) and catalytic (45.8%) reaction. When the hydrogen pressure was increased, the coal conversion became the same ~38.9% for both the thermal and catalytic reactions. With the higher hydrogen pressure, the amount of oil produced in the reaction also became lower. The increased hydrogen pressure may have influenced the hydrogen transfer from HHA to the coal.

The effect of catalyst loading was also determined by increasing the catalyst loading from 500 to 1000 ppm of active Mo on a per feed basis (Table 6). The amount of coal conversion increased with the catalyst loading yielding 40.7% coal conversion with no catalyst, 45% with 500 ppm of Mo naphthenate, and 50.1% with 1000 ppm of Mo naphthenate. The primary change

Table 4. Percent Hydrogenation of Hexahydroanthracene Products in Low Severity Reactors with Illinois No. 6 Coal

Reaction Conditions		Percent Hydrogenation*
Catalyst	Temperature (°C)	
None	350a	-13.32
	350b	-12.76
Molyvan L without Sulfur	350a	-14.16
	350b	-13.74
Molyvan 822 with Sulfur	350a	-13.65
	350b	-12.55
Mo Naph with Sulfur	350a	-12.99
	350b	-12.05

a: old data b: new data

* Negative sign indicates dehydrogenation.

Table 5. Effect of Hydrogen Pressure on the Product Distributions of Thermal and Catalytic Reactions of Illinois No. 6 Coal with Hexahydroanthracene at 350°C^a

Product Distribution (weight in grams)	Hydrogen Pressure (500 psi)		Hydrogen Pressure (1000 psi)	
	No Catalyst	Mo Naphthenate ^b	No Catalyst	Mo Naphthenate ^c
Gas	0.145±0.007	0.170±0.014	0.310±0.014	0.034±0.014
Oil	3.093±0.087	3.378±0.007	2.594±0.009	2.949±0.128
Asphaltenes	0.130±0.019	0.126±0.008	0.113±0.008	0.106±0.012
Preasphaltenes	1.463±0.056	0.965±0.233	1.349±0.041	1.449±0.055
IOM ^c	0.927±0.033	0.843±0.013	0.551±0.056	0.951±0.036
Coal Conversion, %	40.7±2.1	45.8±0.8	38.9±3.5	38.8±2.3
Recovery, %	97.9±2.1	92.8±2.7	88.3±1.8	96.0±0.5
Product Distribution Normalized (weight percent)				
Gas	2.47±0.12	2.91±0.16	5.12±0.22	5.62±0.23
Oil	54.67±1.25	64.11±3.29	55.07±1.85	52.92±1.56
Asphaltenes	2.22±0.32	2.16±0.21	1.86±0.12	1.76±0.21
Preasphaltenes	24.88±0.91	16.43±3.51	22.25±0.62	23.97±0.95
IOM	15.76±0.54	14.39±0.17	15.70±0.88	15.73±0.63

^a Reaction Conditions: 500 and 1000 psig H₂ at ambient temperature, 30 min reaction time, 2 g of Illinois No. 6 coal, 0.61 g of HHA; 4.0 g total liquid charge with hexadecane as solvent, 500 ppm of Mo on a feed basis when catalyst is present.

^b With sulfur.

^c IOM: Insoluble organic matter which is ash free.

Table 6. Effect of Catalyst Loading on the Product Distributions of Thermal and Catalytic Reactions of Illinois No. 6 Coal with Hexahydroanthracene at 350°C

Product Distribution (weight in grams)	No Catalyst	Mo Naphthenate ^a 500 ppm Mo	Mo Naphthenate ^a 1000 ppm Mo
Gas	0.145 ± 0.007	0.170 ± 0.014	0.170 ± 0.014
Oil	3.093 ± 0.087	3.378 ± 0.007	3.114 ± 0.067
Asphaltenes	0.130 ± 0.019	0.126 ± 0.008	0.166 ± 0.057
Preasphaltenes	1.463 ± 0.056	0.965 ± 0.233	1.421 ± 0.167
IOM ^c	0.927 ± 0.033	0.843 ± 0.013	0.776 ± 0.040
Coal Conversion, %	40.7 ± 2.1	45.8 ± 0.8	50.1 ± 2.6
Recovery, %	97.9 ± 2.1	92.8 ± 2.7	96.3 ± 3.3
Product Distribution Normalized (weight percent)			
Gas	2.47 ± 0.12	2.91 ± 0.16	2.88 ± 0.21
Oil	54.67 ± 1.25	64.11 ± 3.29	57.16 ± 2.71
Asphaltenes	2.22 ± 0.32	2.16 ± 0.21	2.81 ± 0.93
Preasphaltenes	24.88 ± 0.91	16.43 ± 3.51	24.04 ± 3.05
IOM	15.76 ± 0.54	14.39 ± 0.17	13.11 ± 0.80

^a Reaction Conditions: 500 psig H₂ at ambient temperature, 30 min reaction time, 2 g of Illinois No. 6 coal, 0.61 g of HHA; 4.0 g total liquid charge with hexadecane as solvent, 500 and 1000 ppm of Mo on a feed basis when catalyst is present.

^b Without sulfur.

^c With sulfur.

^d IOM: Insoluble organic matter which is ash free.

in the product distribution between the 500 and 1000 ppm catalysts was the amount of pre-asphaltenes produced. More coal was converted to preasphaltenes at 1000 ppm but less to oil compared to the 500 ppm loading. Some retrogressive reactions of oil may have also occurred.

Reaction time was increased from 30 to 60 min (Table 7). In both the thermal and catalytic reactions, the amount of coal conversion increased with the increased reaction time. The amount of preasphaltenes in both the thermal and catalytic reactions increased substantially with longer reaction time. This increase was at the expense of the oil content as well as from an increase in coal conversion.

An increase in the hydrogen donor level from 0.5 weight percent donable hydrogen to 1.0 weight percent donable hydrogen (Table 8) resulted in a small increase in the coal conversion for both the thermal and the catalytic reactions. In both the thermal and catalytic reactions, the amount of oil produced also increased and the amount of preasphaltenes decreased. Hence, the presence of the increased hydrogen donor enabled the product slate to be maintained; degradation of the oil fraction did not occur.

The product distributions produced from HHA in the parametric reactions are presented in Table 9. The effect of increased residence time was to increase the amount of anthracene produced in both the thermal and catalytic reactions. The effect of the increased hydrogen donor content was to increase the amount of OHA produced. In all of the reactions the HHA underwent dehydrogenation resulting in hydrogen being donated by HHA to the coal system (Table 10).

Table 7. Effect of Reaction Time on the Product Distributions of Thermal and Catalytic Reactions of Illinois No. 6 Coal with Hexahydroanthracene at 350°C

Product Distribution (weight in grams)	Reaction Time 30 Minutes		Reaction Time 60 Minutes	
	No Catalyst	Mo Naphthenate ^b	No Catalyst	Mo Naphthenate ^c
Gas	0.145±0.007	0.170±0.014	0.145±0.007	0.160±0.000
Oil	3.093±0.087	3.378±0.007	2.796±0.045	2.252±0.169
Asphaltenes	0.130±0.019	0.126±0.008	0.115±0.021	0.143±0.002
Preasphaltenes	1.463±0.056	1.965±0.233	1.874±0.034	2.350±0.008
IOM ^c	0.927±0.033	0.843±0.013	0.841±0.004	0.775±0.046
Coal Conversion, %	40.7±2.1	45.8±0.8	46.1±0.5	50.2±3.1
Recovery, %	97.9±2.1	92.8±2.7	97.5±0.9	96.8±2.1
Product Distribution Normalized (weight percent)				
Gas	2.47±0.12	2.91±0.16	2.49±0.14	2.72±0.00
Oil	54.67±1.25	64.11±3.29	48.89±0.42	41.67±0.05
Asphaltenes	2.22±0.32	2.16±0.21	1.98±0.34	2.44±0.03
Preasphaltenes	24.88±0.91	16.43±3.51	32.19±0.36	39.98±0.12
IOM	15.76±0.54	14.39±0.17	14.45±0.06	13.19±0.81

^a Reaction Conditions: 500 psig H₂ at ambient temperature, 30 and 60 min reaction time, 2 g of Illinois No. 6 coal, 0.61 g of HHA; 4.0 g total liquid charge with hexadecane as solvent, 500 ppm of Mo on a feed basis when catalyst is present.

^b With sulfur.

^c IOM: Insoluble organic matter which is ash free.

Table 8. Effect of Hydrogen Donor Level on Product Distributions of Thermal and Catalytic Reactions of Illinois No. 6 Coal with Hexahydroanthracene at 350°C

Product Distribution (weight in grams)	Weight of HHA (0.61 g)		Weight of HHA (1.22 g)	
	No Catalyst	Mo Naphthenate ^b	No Catalyst	Mo Naphthenate ^c
Gas	0.145±0.007	0.170±0.014	0.135±0.007	0.155±0.007
Oil	3.093±0.087	3.378±0.007	3.368±0.037	3.436±0.030
Asphaltenes	0.130±0.019	0.126±0.008	0.145±0.002	0.121±0.007
Preasphaltenes	1.463±0.056	1.965±0.233	1.234±0.071	1.871±0.100
IOM ^c	0.927±0.033	0.843±0.013	0.868±0.006	0.837±0.025
Coal Conversion, %	40.7±2.1	45.8±0.8	44.3±0.32	46.3±1.6
Recovery, %	97.9±2.1	92.8±2.7	97.1±0.4	92.6±0.8
Product Distribution Normalized (weight percent)				
Gas	2.47±0.12	2.91±0.16	2.29±0.09	2.64±0.12
Oil	54.67±1.25	64.11±3.29	59.72±0.93	66.25±1.32
Asphaltenes	2.22±0.32	2.16±0.21	2.45±0.01	2.05±0.12
Preasphaltenes	24.88±0.91	16.43±3.51	20.86±0.92	14.82±1.73
IOM	15.76±0.54	14.39±0.17	14.68±0.10	14.24±0.40

^a Reaction Conditions: 500 and 1000 psig H₂ at ambient temperature, 30 min reaction time, 2 g of Illinois No. 6 coal, 0.61 g and 1.22 g of HHA; 4.0 total liquid charge with hexadecane as solvent, 500 ppm of Mo on a feed basis when catalyst is present.

^b With sulfur.

^c IOM: Insoluble organic matter which is ash free.

Table 9. Product Distribution from Hexahydroanthracene in Parametric Evaluation Reactions with Illinois No. 6 Coal at 350°C

Catalyst Type	Level (ppm)	Time (min)	Pressure (psi)	Weight of HHA (g)	Product Distribution (wt %)			
					ANT*	DHA	HHA	OHA
Effect of Pressure								
None	0	30	1000	0.61	19.72±0.62	20.75±0.93	48.84±0.33	10.69±0.68
Mo Naph*	500	30	1000	0.61	14.06±0.99	27.46±2.59	47.99±2.19	10.49±0.87
Effect of Catalyst Loading								
Mo Naph	1000	30	500	0.61	14.54±0.61	25.36±0.78	50.57±0.38	9.53±0.16
Effect of Reaction Time								
None	0	60	500	0.61	29.09±2.55	17.89±1.70	44.34±1.39	8.68±0.85
Mo Naph	500	60	500	0.61	17.90±0.71	22.57±0.94	50.06±0.28	9.47±0.41
Effect of Increased Hydrogen Donor Content								
None	0	30	500	1.22	13.41±1.42	27.93±0.53	45.11±1.71	13.55±0.80
Mo Naph	500	30	500	1.22	11.25±0.61	32.42±2.02	43.96±1.45	12.37±0.07

* With sulfur.

^b ANT = Anthracene, DHA = Dihydroanthracene, HHA = Hexahydroanthracene, OHA = Octahydroanthracene, Naph = Naphthalene, HYD = Hydrogenation

**Table 10. Percent Hydrogenation of the Hexahydroanthracene Products
in the Parametric Evaluation Reactions**

Catalyst Type	Level (ppm)	Time (min)	Pressure (psi)	Weight of HHA (g)	Percent Hydrogenation (%)
Effect of Pressure					
None	0	30	1000	0.61	-12.85
Mo Naph ^a	500	30	1000	0.61	-12.37
Effect of Catalyst Loading					
Mo Naph ^a	1000	30	500	0.61	-12.12
Effect of Reaction Time					
None	0	60	500	0.61	-16.34
Mo Naph ^a	500	60	500	0.61	-12.77
Effect of Increased Hydrogen Donor Content					
None	0	30	500	1.22	-11.79
Mo Naph ^a	500	30	500	1.22	-12.32

^a With sulfur.

Summary

Hexahydroanthracene added to low severity coal liquefaction reactions increased the amount of coal conversion compared to thermal and catalytic reactions without hexahydroanthracene. Evaluation of the effect of various reaction parameters showed that catalyst loading and increased reaction time were both beneficial for coal conversion. A doubled hydrogen donor content increased coal conversion slightly but was able to maintain the product slate and increase the amount of oil produced. By contrast, increased reaction time resulted in a degradation of the product slate.

Future Work

The future work includes performing a series of parametric evaluation reactions in which a combination of reaction parameters are used. The combination which produces the most coal conversion and maintains the best product slate under low severity conditions for Illinois No. 6 will be performed using other coals like Pittsburgh No. 8 and Wyodak.

References

- Wang, S.L. Master's Thesis, Auburn University, 1992.
- Curtis, C.W. "Low Severity Coal Liquefaction Promoted by Cyclic Olefins," Quarterly Report, January-March 1992.
- Bedell, M.W. and Curtis, C.W. *Energy and Fuels*, 5, 469, 1991.

PART II

INFRARED STUDIES OF CYCLIC OLEFINS

Introduction

Cyclic olefins have been shown to be very reactive for releasing their hydrogen under thermal and catalytic conditions (Bedell and Curtis, 1991). The released hydrogen is then available for donation to coal (Bedell and Curtis, 1993) and to resins (Owens, 1991). The thermal activity of these cyclic olefins is under investigation by infrared spectroscopy. The types of products that can be produced from cyclic olefins were examined. If these reaction products can be observed separately by FTIR from the cyclic olefins, then the appearance of reaction products can be observed in the heated IR cell. The work performed this quarter identified the FTIR of the products from cyclic olefins and also began evaluating fluorolube as a high-temperature solvent for the cyclic olefins. The work on fluorolube will be continued next quarter. The high-temperature cell will be setup and tested.

Objective

To determine the feasibility of using FTIR and a heated cell to observe and evaluate the extent of hydrogen donation by cyclic olefins to acceptor compounds representative of those found in coal.

Progress

In order to use FTIR as a tool for investigating hydrogen donation one must be able to observe spectroscopically the release of hydrogen from a donor compound. To achieve this goal, the research is designed to proceed in several systematic steps.

A model compound system must be chosen. Two groups of model compounds, naphthalene series and anthracene series, were chosen for analysis and are presented in Lists 1 and 2 given in the Experimental Section. List 1 contains the naphthalene series consisting of naphthalene, isotetralin, and seven hydroaromatic analogues. List 2 presents the anthracene series consisting of anthracene, hexahydroanthracene, and three hydroaromatic analogues. All sources of the model compounds and available physical constants are recorded on List 1 and 2. Specific gravities were required to prepare the wt:wt percent solutions. Boiling and melting points are necessary for the heated investigations.

FTIR spectra of each model compound is required to determine major absorption bands. The naphthalene and anthracene series of compounds were analyzed as 1% (wt:wt) solutions in carbon tetrachloride and carbon disulfide on List 3, respectively. Solution spectra are relatively easy to acquire and the feasibility of determining unique absorption bands or differences between an individual model compound and the products after heating can be determined.

Unique absorption bands for each model compound need to be determined. The principal absorption bands for the naphthalene/carbon tetrachloride series, naphthalene and its hydrogenated analogues, for the wavelength region 3200 to 2500 cm^{-1} are tabulated in Table 11. Unique absorption bands for individual model compounds can be determined from this table. For example, if one was able to dehydrogenate tetralin, the FTIR spectrum could show bands at 2820 cm^{-1} and/or bands at 2832 cm^{-1} which would indicate the dehydrogenated tetralin products of 1,4-dihydronaphthalene and 1,2-dihydronaphthalene, respectively. Alternatively, neither of these product bands would be available and all bands between 2935 cm^{-1} and 2500 cm^{-1}

List 1. RESEARCH CHEMICALS: NAPHTHALENE SERIES

Compound (PTIR)	St.	M. Wt.	Source	Purity	bp-mp (°C)	S.G.	Jar-Total Mass (g)
Naphthalene	S	128.17	Aldrich 18,450-0	99 + %	bp 217 mp 80	***	2-20
Tetralin 1,2,3,4-Tetrahydro- naphthalene	L	132.21	Aldrich 10,241-5	99%	bp 207	0.973	1-100
1,4-dihydro- naphthalene	L	130.19	Wiley Organics 1168.83 Lot 5962 Lot 4749 Lot 8393 Lot 5963	 92% 90% 69% 14%	 *** *** *** ***	 *** *** *** ***	 1-2 1-2 1-2 1-2
1,2-Dihydro- naphthalene	L	130.19	Aldrich D10,593-7 Wiley Organics 1168,70-1	75% 95%	bp 89 16mm	0.997	1-25 3-1.5
1,4,5,8-Tetrahydro- naphthalene (Isotetralin)	S	132.21	Ken Olson Wiley Organics	97% 88%	mp 52	***	1-15 1-10
1,2,3,4,5,8-Hexa- hydronaphthalene	L	134.23	Wiley Organics 3395.05	98%	***	***	2-10
1,2,3,4,5,6,7,8- Octa- hydronaphthalene (9,10-Octalin)	L	136.24	Aldrich 34,765-5	99%	bp 194	0.914	1-5
Trans-decahydro- naphthalene (Trans-decalin)	L	138.25	Aldrich 11,047-7	99%	bp 185 756mm	0.870	1-50
Cis-decahydro- naphthalene (Cis-decalin)	L	138.25	Aldrich 11,046-9	99%	bp 193	0.897	1-50

List 2. RESEARCH CHEMICALS: ANTHRACENE SERIES

Compound	State	M. Wt.	Source	Purity	bp-mp (°C)	Jar-Total Mass (g)
Anthracene	S	178.23	Aldrich 14,106-2	99%	bp 340 mp 216	2-20
1,4,5,8,9,10 Hexa- hydroanthracene	S	184.28	Aldrich 20,774-8 Janssen 19.653.59	97% 99%	*** mp 147	3-35 1-5
9,10 Dihydroanthracene	S	180.25	Aldrich 12,617-9 Chem.Ser. F1012	97% 98%	bp 312 mp 108	1-3 3-3
1,2,3,4,5,6,7,8 Octa- hydroanthracene	S	***	Alfred Bader	***	***	1-0.5
Perhydro- anthracene	L	***	Ruth Owens #308	***	***	1-1

List 3. MISCELLANEOUS CHEMICALS

Compound	State	M.Wt.	Source	Purity	bp mp (°C)	Amount	S.G.
CCl ₄	L	153.82	Fisher C199-1	Spectranal.	76.7	500 ml	1.585
Hexadecane	L	226.45	Aldrich H670-3	99%	bp 287 mp 18	100 ml	0.773
CS ₂	L	76.14	Fisher C-573	Certified Spectranal.	bp 46 mp -112	500 ml	1.627
Fluorolube	grease	***	Fisher F-16	***	(°F) 0-350	***	***

Table 11. FTIR ABSORPTION WAVELENGTHS FOR NAPHTHALENE ANALOGS/CCI,

Compound/(Purity)	Wavelengths (cm ⁻¹) 3200-2700												
Naphthalene (99)	3092	3068	3053	3035	3021	2982	2964	2933	****	****	****	****	****
1,2-Dihydronaphthalene (75) (95)	3093	3069	3058	3036	3019	****	****	<u>2934</u>	****	2886	****	2854	****
	3093	3069	3058	3036	3019	****	****	****	****	2886	****	2864	****
	3093	3069	3058	3036	3019	****	****	****	****	2886	****	2864	****
1,4-Dihydronaphthalene (92N) (90) (69N) (69)	3077	3062	****	3030	3019	2981	****	****	****	2883	2866	****	****
	3077	3065	****	3034	3019	2984	****	****	****	2886	2871	****	****
	3094	3070	3057	<u>3032</u>	<u>3017</u>	****	****	<u>2932</u>	****	<u>2883</u>	****	<u>2859</u>	****
	****	3069	3059	3035	<u>3018</u>	****	****	2935	****	2886	****	2862	****
	****	3069	3059	3035	<u>3018</u>	****	****	2935	****	2886	****	2862	****
1,4-Tetrahydronaphthalene (99)	3075	3061	****	3042	3018	****	****	<u>2931</u>	2898	2885	****	2860	2841
Isotetralin (97) (88)	****	3067	****	<u>3030</u>	****	2975	****	2924	****	****	<u>2875</u>	****	<u>2848</u>
	****	3066	****	<u>3031</u>	****	2975	2958	2926	****	****	<u>2875</u>	****	<u>2849</u>
Hexahydronaphthalene (98)	****	****	****	3029	****	2973	****	<u>2928</u>	<u>2905</u>	<u>2884</u>	<u>2873</u>	<u>2859</u>	****
Octahydronaphthalene (99)	****	****	****	****	****	****	****	<u>2928</u>	****	<u>2886</u>	<u>2866</u>	<u>2858</u>	****
Cis-Decalin (99)	****	****	****	****	****	****	****	<u>2925</u>	****	****	****	<u>2860</u>	****
Trans-Decalin (99)	****	****	****	****	****	****	****	<u>2920</u>	****	****	****	<u>2851</u>	****
Hexadecane (99)	****	****	****	****	****	****	****	<u>2957</u>	<u>2926</u>	****	<u>2872</u>	<u>2854</u>	****

Italic = > Shoulder or Trace Amount Bold Print = > 0.050 - 0.099 Absorbance
Normal Print = > 0.02 - 0.049 Absorbance Bold/Underline = > ≥ 0.100 Absorbance

could be missing, leading to the result that the tetralin was completely dehydrogenated to produce naphthalene. Tabulation of absorbance bands in other wavelength regions is currently in progress in order to provide a full scope of our capabilities. Subtracted spectra will be used to confirm all results. All work will be repeated on the anthracene/carbon disulfide series of model compounds.

A solvent or diluent which would withstand heating and not possess absorbance bands in the wavelength regions of the model compounds is needed for the investigations. The thermal properties, melting point of 0 to 350°F of fluorolube, List 3, suggest this diluent might be appropriate for the heated cell investigations. Hexadecane was also analyzed for adsorption as a possible solvent for the model compound investigations. The major disadvantage of hexadecane is the strong absorbance bands observed between 2957 and 2926 cm^{-1} and between 2872 and 2854 cm^{-1} . Although most of the naphthalene model compounds show absorbencies in these wavelength regions, it does not mean this solvent is precluded as a diluent for the heated investigations. The naphthalene model compounds do appear to present additional absorbance bands outside of these wavelength regions as can be seen in Table 11. The band widths of the hexadecane absorbances needs to be considered carefully. More opportunity for use of this solvent may be available once the wavelength regions from 2700 cm^{-1} to 600 cm^{-1} have been tabulated.

It must be determined whether or not the unique absorbance bands obtained in carbon tetrachloride or carbon disulfide are maintained in the diluents, fluorolube or hexadecane. Preliminary work has been done using fluorolube as the diluent for the cycloolefins and their corresponding aromatic and hydroaromatic analogues. The work has not

been completed nor tabulated. But, preliminary results look promising. Figure 1 shows the spectra of 1% mixtures of isotetralin, 1,2-dihydronaphthalene, and 1,4-dihydronaphthalene in fluorolube. Isotetralin is closest to the x-axis while 1,4-dihydronaphthalene is farthest. From these spectra, it appears that it would be possible to observe the formation of 1,2-dihydronaphthalene as a result of dehydrogenation of isotetralin. The formation of 1,4-dihydronaphthalene does not appear possible in this wavelength region. A closer look at the remaining wavelength regions is required before looking at another diluent. We will need to perform subtraction of the various spectra for confirmation of unique absorbances for these models.

Future Work

The principal absorbance wavelengths of all model compounds from both the naphthalene and anthracene series in the respective solvents will be tabulated. These tabulations will serve as a library to explain results obtained in high temperature and eventually high pressure investigations involving coal. Heating experiments on hexadecane and fluorolube will be performed to determine the thermal effects on the background absorbance spectrum. Once it has been determined that the diluent is satisfactory, a significantly saturated model compound such as isotetralin or hexahydronaphthalene, will be mixed with the diluent, heated, and examined by FTIR for hydrogen release. Several time periods will be examined. Once it has been determined that hydrogen release can be observed using FTIR analysis, an acceptor model compound will be chosen in order to monitor hydrogen transfer by the same method. The ultimate goal will be the design and implementation of heated experiments to measure hydrogen

Figure 1. FTIR Spectra of Isotetralin, 1,2-Dihydronaphthalene and 1,4-Dihydronaphthalene in Fluorolube.

transfer from cyclic olefins to coal. In the event the proposed procedures fail, exploratory work on thin films using the naphthalene series of model compounds will be performed to determine if it will be feasible to observe dehydrogenation and/or hydrogen transfer by FTIR. An appropriate literature search will be performed.

Experimental

Materials

The naphthalene series (List 1) of chemical compounds consisted of the following 9 chemical compounds:

naphthalene	NAP
1,2-dihydronaphthalene	1,2 DHN
1,4-dihydronaphthalene	1,4 DHN
1,2,3,4-tetrahydronaphthalene or tetralin	TET
1,4,5,8-tetrahydronaphthalene or isotetralin	ISO
1,2,3,4,5,8-hexahydronaphthalene	HHN
1,2,3,4,5,6,7,8-octahydronaphthalene	OHN
trans-decahydronaphthalene or trans-decalin	T-DEC
cis-decahydronaphthalene or cis-decalin	C-DEC

Naphthalene, tetralin, 1,2-dihydronaphthalene, octahydronaphthalene, cis-decalin, and trans-decalin were purchased from Aldrich Chemical Company and used as received. These compounds were all 99% purity or better. Hexahydronaphthalene (98% purity), isotetralin (88%

purity), 1,2-dihydronaphthalene (95% purity), and 1,4-dihydronaphthalene (90% purity) were purchased from Wiley Organics and used as received. Isotetralin (97% purity) was also prepared in house and used in these investigations.

The anthracene series (List 2) of chemical compounds consisted of the following 5 chemical compounds:

anthracene	ANT
1,4,5,8,9,10-hexahydroanthracene	HHA
9,10-dihydroanthracene	9,10 DHA
1,2,3,4,5,6,7,8-octahydroanthracene	OHA
perhydroanthracene	PHA

Anthracene (99% purity) and 9,10-dihydroanthracene were purchased from Aldrich Chemical Company and used as received. Hexahydroanthracene (99% purity) was purchased from Janssen Chemical Company and used as received. Octahydroanthracene was purchased from Alfred Bader and perhydroanthracene was prepared in house. Purity was not available for these two compounds. Both compounds were used without further purification.

Spectranalyzed carbon tetrachloride and carbon disulfide (List 3), purchased from Fisher Scientific and used as received, were employed as the solvents for the naphthalene and anthracene series of compounds, respectively. Infrared absorbance bands are presented in List 4. Fluorolube (List 3) was purchased from Fisher Scientific and used as received.

Experimental Procedures

Naphthalene and all naphthalene analogues were prepared, in volumetric flasks, as 1% solutions (wt:wt) in carbon tetrachloride for FTIR analysis. Anthracene and all anthracene analogues were prepared, in volumetric flasks, as 1% solutions (wt:wt) in carbon disulfide for FTIR analysis. Additionally, all compounds of the naphthalene series were prepared as 1% mixtures (wt:wt) in fluorolube to prepare thin films for FTIR analysis. All analytes were corrected for impurities to make 1% solutions. All samples were analyzed on sodium chloride windows, 0.1 mm teflon spacer, with a Nicolet 5XSC FTIR spectrometer, 16 scans, using a nitrogen purge. Replicate analyses were performed on most analytes.

References

- Bedell, M.W. and Curtis, C.W. *Energy and Fuels*, 5, 469, 1991.
- Bedell, M.W. and Curtis, C. W. *Energy and Fuels*, in press, 1993.
- Owens, R.M., Master's Thesis, Auburn University, 1991.
- Wang, S.L., Master's Thesis, Auburn University, 1992.

List 4. IR ABSORBANCE BANDS FOR SOLVENTS*

Solvent	Spacer Width (mm)	Absorption Bands (cm ⁻¹)
Carbon Tetrachloride (CCl ₄)	0.1	2200-2140 1595-1460
	1.0	2340-2100 1640-1385 875-845
Carbon Disulfide (CS ₂)	0.1	820-720
	1.0	1610-1500 1270-1200 1020-960 860-400

* Willard, Hobart H., Merritt, Jr., Lynne L., Dean, John A., Settle, Jr., Frank A., "Instrumental Methods of Analysis, Seventh Edition", Wadsworth Publishing Co., Belmont CA, 1988, p. 308.

Absorption bands for 0.1 mm spacer confirmed by experiments.

List 5. INFRARED-TRANSMITTING MATERIALS*

Window Composition	Wavelength Range (cm ⁻¹)
Sodium Chloride (NaCl)	40,000-590
Potassium Bromide (KBr)	40,000-400

* Willard, Hobart H., Merritt, Jr., Lynne L., Dean, John A., Settle, Jr., Frank A., "Instrumental Methods of Analysis, Seventh Edition", Wadsworth Publishing Co., Belmont CA, 1988, p. 306.

Wavelength range confirmed by experiments.

Figure 2. FTIR Spectra with Absorbance Wavelengths of Isotetralin, 1,2-Dihydronaphthalene, and 1,4-Dihydronaphthalene in Fluorolube.

END

**DATE
FILMED**

7 / 13 / 93