DOE/PC/90537-T2

SEQUENTIAL LOW-TEMPERATURE DEPOLYMERIZATION
AND LIQUEFACTION OF U. S. COALS

na

Progress Report no. 2

(covering the period January 1 - March 31, 1987)

Joseph S. Shabtai and Wendell H. Wiser
(801-581-5161) (801-581-8602)

Principal Investigators

Department of Fuels Engineering

University of Utah

Salt Lake City, UT 84112

Prepared for the United States Department of Energy

under Grant no. DE-FG-22-86PC90537

April, 1987

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

ds

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

1

DISCLAIMER

This report was prepared with the support of the U. S. Department of Energy, Grant No. DE-FG-22-86PC90537. However, any opinions, findings, conclusions, or recommendations expressed herein are those of the authors and do not necessarily reflect the views of the DOE.

PERSONNEL

Junior research personnel participating in this project during the reporting period were:

Mr. T. Skulthai, Graduate student

Mrs. Y. Zhang, Graduate student

OBJECTIVES AND SCOPE OF THE RESEARCH PROJECT

One of the main objectives of this project is to investigate the low-temperature ($\leq 290^{\circ}\text{C}$) depolymerization-liquefaction reactions of representative U. S. coals using a 3-step procedure recently developed in our Laboratory. The procedure involves subjecting the coal first to two consecutive depolymerization steps in which different types of intercluster linkages are subjected to preferential cleavage. The depolymerized products obtained have low molecular weights and consist predominantly of monocluster compounds. In the third step of the procedure these simplified depolymerization products are subjected to hydroprocessing and attendant exhaustive hydrodeoxygenation to yield light liquid hydrocarbon mixtures as main products. It is planned under the research program to adapt and optimize the above indicated procedure for U. S. coals of different rank, and to examine the feasibility of the new processing concept for conversion of these coals into light liquid hydrocarbon fuels.

A second major objective of the research program is to subject the low-temperature depolymerization products (obtained by the first two consecutive steps) to exhaustive structural analysis for the purpose of deriving average structural models for the coals under investigation. Such models are expected to be useful as fingerprints for identification and differentiation of various representative U. S. coals.

PROJECT STATUS

During the period January 1 - March 31, 1987 period, covered by the present report, systematic studies on the low-temperature depolymerization and liquefaction of a Wyodak (Wyoming) coal were performed, and parallel studies of a coal from Elkhorn (Kentucky) were continued. Following is a description

of results obtained.

RESULTS

A. Depolymerization - Liquefaction of a Wyodak (Wyoming) Coal

The Wyodak, Wyoming coal sample, referred below as W(W) coal, was characterized by the following ultimate analysis (MAF basis), in wt %: (C, 76.03; H, 5.35; N, 1.37; Cl, 0.02; S, 0.60; O (diff.), 16.63. H/C atomic ratio = 0.84; ash content (dry basis), 8.9 %. The sample showed a calorific value of 11,926 BTU/lb (dry basis).

The W(W) coal was subjected to the previously developed stepwise depolymerization-liquefaction procedure summarized in Figure 1 [for details see J. Shabtai, T. Skulthai and I. Saito, Am. Chem. Soc. Div. Fuel Chem. Prepr., 31 (4), 15-23 (1986)]. The procedure consists essentially of the following sequential steps: (1) intercalation of the coal sample with catalytic amounts (5 - 20 %) of FeCl_3 , followed by mild hydrotreatment (HT) of the coal- FeCl_3 intercalate; (2) base-catalyzed depolymerization (BCD) of the product from step 1, under super-critical conditions; and (3) hydroprocessing (HPR) of the depolymerized product from the two preceding steps, using a sulfided 6Co8Mo catalyst.

The depolymerization behavior of the W(W) coal was previously studied using ZnCl_2 as catalyst in the mild hydrotreatment (HT) step (J. Shabtai, I. Saito and T. Skulthai, Proc. 1985 Internat. Confer. on Coal Science, Sydney, Australia, Pergamon Press, Sydney, 1985, pp. 223-226). In the present systematic study the depolymerization-liquefaction of the W(W) coal was examined using FeCl_3 as catalyst in the HT step. FeCl_3 possesses somewhat lower hydrogenolysis activity compared to ZnCl_2 . However, it was recently found in this Laboratory that FeCl_3 has several important advantages as

^aHT = hydrotreatment (250 - 290°C; H₂ pressure, 1000 - 1500 psig)

^bBCD = base-catalyzed depolymerization (250 - 290°C; initial N₂ pressure, 1000 psig)

^cHPR = hydroprocessing (350 - 370°C; H₂ pressure, 2700 psig)

Figure 1. Low-temperature Coal Depolymerization-Liquefaction Procedure.

catalyst in comparison with ZnCl_2 .., i.e., higher C-C hydrogenolysis selectivity, lower corrossivity, and essentially quantitative recoverability at the end of the HT step of the coal depolymerization procedure (Figure 1). It was therefore important to optimize the latter procedure for a representative subbituminous U. S. coal e.g., W(W) coal, using FeCl_3 as catalyst in the mild hydrotreatment (HT) step.

Mild Hydrotreatment (HT) Step

It was found in a series of experiments that impregnation of the W(W) coal with FeCl_3 concentrations in the range of 7.5 - 20.0 wt % is sufficient to produce a low yield (7-10 wt %) of THF-soluble products in the HT step at a temperature of 275°C. Such a low yield was found to be suitable for obtaining a maximal overall yield in the sequential depolymerization procedure (see below).

Base-Catalyzed Depolymerization (BCD) Step

Table 1 and Figure 2 show the effect of the reaction temperature used in the mild HT step upon the yield of THF-soluble products in the subsequent BCD step, which was performed at a mild temperature of 250°C for the purpose of better comparison at moderate overall W(W) coal conversions. As seen, the yield of THF-solubles from hydrotreatment (HT) of a W(W) coal- 20 % FeCl_3 intercalate increases with increase in HT temperature (from 3.1 % at 225°C to 12.3 % at 290°C). However, a maximal yield (38.3 %) in the subsequent BCD step (performed at 250°C for all runs) was obtained in expt. 3, in which the HT step temperature was 275°C; increase in HT temperature to 290°C results in a marked decrease in THF-solubles in the BCD step. Likewise, the total yield of THF-solubles from the combined HT plus BCD steps (Table 1) reaches a maximum (48.0 wt %) when the HT temperature is 275°C. On the basis of these results a HT temperature of 275°C was used in all subsequent experiments

Table 1

Effect of Temperature Used in the HT Step upon the
Yield of THF-Soluble Products in the Subsequent BCD step

Expt. no.	1	2	3	4
<u>HT Step^a</u>				
HT temperature, °C	225	250	275	290
Yield of THF solubles, % by wt.	3.1	6.8	9.7	12.3
<u>BCD Step^b</u>				
BCD temperature, °C	250	250	250	250
Yield of THF solubles,	21.8	35.0	38.3	21.4
Total Yield ^c	24.9	41.8	48.0	43.7

^aThe hydrotreatment (HT) step in all runs was performed using W(W) coal-20 % FeCl₃ intercalate as feed; H₂ pressure, 1500 psig; reaction time, 2 hr.

^bThe base-catalyzed depolymerization (BCD) step was performed using as feed the hydrotreated Wyodak coal derived from the HT step; H₂ pressure, 1000 psig; depolymerizing agent, 10 % NaOH in ethanol; reaction time, 1 hr.

^cTotal yield of THF-soluble products from the combined HT plus BCD steps, calculated on the original dry coal (including ash).

Figure 2. Effect of temperature used in the HT step upon the yield of THF-soluble products in the subsequent BCD step at 250°C (feed, W(W) coal - 20 % FeCl intercalate).

concerned with the dependence of depolymerization yields upon BCD conditions.

Table 2 summarizes the effect of temperature in the BCD step (in the range of 225°-275°C) upon the yield and distribution of THF-soluble products obtained from W(W) coal by the combined HT plus BCD steps. As seen from experiments 5-7, the total yield of THF-solubles increases markedly with increase in BCD temperatures (from 43.8 % at 225°C to 81.2 % at 275°C). The yield increases further if methanolic KOH solution instead of ethanolic NaOH solution is used as base catalyst in the BCD step (compare expt. 8 with expt. 7). Application of the BCD step alone, without first subjecting the coal to HT (expt. 9) results in a markedly lower solubilization yield.

Table 2 shows also the distribution of the total THF-soluble products from W(W) coal into oils, asphaltenes, and asphaltols, as a function of the BCD temperature. As seen, the proportion of the asphaltol fraction decreases, while that the oil fraction increases with increase in BCD temperature from 225°C to 275°C (see expts. 5-7). The highest yield of oils (61.5 wt %) is obtained with 10 % methanolic KOH as base catalyst (expt. 8). Products obtained from W(W) coal by BCD alone consist mostly (77.1 wt %) of asphaltols (expt. 9). This clearly indicates the major importance of the HT step in the sequential HT-BCD coal treatment. Most of the data in Table 2 are plotted in Figure 3.

Hydroprocessing (HPR) Step

Depolymerized products from the sequential HT-BCD treatment of W(W) coal were subjected to hydroprocessing (HPR) with a sulfided 6Co8Mo/ γ -Al₂O₃ catalyst, using a 300 ml stirred autoclave and mesitylene as a solvent. HPR experiments were performed at 370°C, a hydrogen pressure of 2700 psig, and reaction times of 4-8 hr. In most experiments the reaction time was 8 hr, as a fresh portion of the sulfided catalyst and 0.06 wt % of CS₂ were introduced

Table 2

Effect of BCD Temperature on the Yield and Distribution
of THF-soluble Products from Combined HT-BCD Treatment^{a,b}

Experiment no. ^b	5	6	7	8 ^c	9 ^d
BCD temperature, °C	225	250	275	275	275
Yield of THF-solubles, % by wt.	43.8	65.5	81.2	85.5	69.7
Distribution of THF-solubles, % by wt. ^e					
Oils ^f	32.2	38.5	55.8	61.5	20.3
Asphaltenes ^g	1.7	7.7	7.9	3.8	2.6
Asphalts ^h	65.0	53.8	36.3	34.7	77.1

^aMild hydrotreatment (HT) of W(W) coal-20 % FeCl₃ intercalates (prior to BCD) was performed at 275°C, 1500 psig hydrogen pressure, and 3 hr reaction time.

^bIn each BCD run was used about 3 g of hydrotreated (HT) coal and 45 ml of 10 % ethanolic NaOH solution; reaction time, 1.5 hr.

^cIn this run the depolymerizing agent in the BCD step was a 10 % methanolic solution of KOH.

^dThis run involved BCD only (without preceding HT).

^ewt. % of total THF-soluble product.

^fCyclohexane-solubles.

^gBenzene solubles-cyclohexane insolubles.

^hTHF-solubles-benzene insolubles.

Figure 3. Change in composition of THF-soluble products from HT-BCD of W(W) coal, as a function of BCD temperature.

in the autoclave after a period of 4 hr.

Table 3 summarizes the yields and distribution of products from two comparative HPR experiments, i.e., (a) expt. 11, performed directly on the THF pre-extracted W(W) coal without preliminary depolymerization by the HT-BCD procedure; and (b) expt. 12, performed with the depolymerized W(W) coal as feed, viz., after preliminary HT-BCD treatment of the coal. As seen, the total product yield and the yield of liquids from HPR of the non-depolymerized coal (expt. 11) are drastically lower compared to those obtained with the depolymerized W(W) coal as feed (expt. 12). Furthermore, the product from expt. 12 consists almost entirely (96.3 wt %) of liquids, whereas the product from expt. 11 consists mostly of solid components. The total yield in expt. 12 is essentially quantitative if the hydrodeoxygenative removal of oxygen from the depolymerized W(W) coal feed (oxygen content, 11.8 %) is taken into account.

Table 4 summarizes the elemental compositions of the depolymerized W(W) coal and of the product obtained from it by hydroprocessing (HPR). As seen HPR results in the formation of a hydrocarbon product with considerably increased C and H contents and sharply reduced O and N contents as compared with those of the depolymerized W(W) coal feed.

Table 5 summarizes the boiling point distribution of the depolymerized W(W) coal and of the hydroprocessed product derived from it. As seen, the oxygen-rich, depolymerized W(W) coal sample is characterized by relatively low volatility as reflected by a vacuum residue of 32.6 wt %, and a low proportion (8.5 %) of gasoline, kerosene and gas oil fractions. In contrast, the hydroprocessed product contains 98.0 wt % of distillables, including 71.3 wt % of low-boiling fractions (gasoline, kerosene, and gas oil; b.p. up to 325°C).

Table 3
Comparison of Hydroprocessing (HPR)^a of W(W) Coal
with and without Preliminary HT-BCD Depolymerization

Experiment no.	10	11
HT-temperature, °C	-	275
BCD-temperature, °C	-	275
Yield of HPR Products, wt %	27.9	88.5
Distribution, ^d %		
Liquids	19.7	96.3
Gases	8.2	3.2
Solids	72.1	0.5

^aIn each HPR experiment, 4.5 g of feed and 60.0 g of solvent (mesitylene) were used; catalyst: sulfided 6Co8Mo/Y-Al₂O₃; the catalyst/feed ratio was 1:5 by wt, and 0.06 % wt of CS₂ was added after 4 hr reaction time; total time, 8 hr.

^bIn this experiment, the feed consisted of W(W) coal pre-extracted with THF, but without any HT-BCD treatment prior to HPR.

^cIn this experiment, the W(W) coal was subjected to THF pre-extraction, and HT-BCD depolymerization, prior to HPR.

^dDistribution of total product.

Table 4
Elemental Compositions of the Depolymerized W(W) Coal and of the
Hydrocarbon Product Derived from it by Hydroprocessing (HPR)

Element, % by wt.	Depolymerized Coal ^a	Hydroprocessed (HPR) product ^b
Carbon	77.59	87.57
Hydrogen	9.35	11.60
Nitrogen	1.21	0.24
Oxygen (by difference)	11.85	0.59
H/C Atomic Ratio	1.45	1.59

^aThe depolymerized W(W) coal sample was obtained by HT at 275°C, followed by BCD at 275°C.

^bObtained under the hydroprocessing conditions given in Table 3, footnote a.

Table 5

Boiling Point Distribution of the Depolymerized W(W) Coal and
of the Hydrocarbon Product Derived from it by Hydroprocessing (HPR)^a

Fraction (b.p., °C), wt %	Depolymerized coal ^b	Hydroprocessed (HPR) ^c product
Gasoline (<200°)	2.6	29.8
Kerosene (200-275°)	2.7	33.2
Gas Oil (275-325°)	3.2	8.3
Heavy Gas Oil (325-400°)	10.9	14.7
Vacuum Gas Oil (400-538°)	44.8	12.0
Total Distillable (<538°)	64.2	98.0
Atmospheric Residue (>350°)	89.8	23.2
Vacuum Residue (>538°)	32.6	2.0

^aBoiling point distributions were determined by simulated distillation.

^bFor preparation details, see Table 2, footnotes a and b.

^cFor HPR conditions, see Table 3, footnote a.

The above results demonstrate the extraordinarily high efficiency of the overall HT-BCD-HPR procedure for converting a typical subbituminous U. S. coal into light hydrocarbon liquids.

B. Depolymerization-Liquefaction of an Elkhorn (Kentucky) Coal

The systematic study of the low-temperature depolymerization-liquefaction of a high-volatile bituminous coal from Elkhorn (Kentucky) is continuing. Optimal conditions for the HT and BCD steps of the procedure with this coal as feed were determined and a detailed study of the HPR step is in progress. A full account of results obtained will be given in Progress Report no. 3.

Parallel to the above studies, work was initiated on the low-temperature depolymerization-liquefaction of a Pittsburgh #8 high volatile bituminous coal, supplied by the premium coal sample program at the Argonne National Laboratory.

END

**DATE
FILMED**

7 / 19 / 93