DOE/NE/ER13641-5

THINNING AND RUPTURE OF A THIN LIQUID
FILM ON A HEATED SURFACE

DOE/ER/13641--5

DE92 019958

Annual Technical Progress Report
for Period November 1, 1991 through October 31, 1992

S. G. Bankoff and S. H. Davis

Northwestern University
Evanston, IL 60208

August 5, 1992

Prepared for
The U.S. Department of Energy
Agreement No. DE-FG02-86-ER13641

DISCLAIMER

MASTER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ph
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

PROGRESS REPORT

The following results on the dynamics and stability of thin films were obtained during the last project period.

Forced Dryout

Tan, Bankoff and Davis (1990) examined a viscous liquid layer on a horizontal plate that is non-uniformly heated. The free surface between the liquid and the passive gas above is dimpled above the temperature maximum due to thermocapillarity. Lubrication theory was used to derive a long-wave evolution equation for the interface shape. A prediction is given for the heat flux needed to rupture the film. Burelbach, Bankoff and Davis (1990) tested the theory experimentally using a silicone oil layer. The theoretical predictions and the experimental observations are in excellent agreement, with the theory yielding a simple criterion for dryout. This is the first direct confirmation known to us of lubrication theory as applied to non-isothermal free-surface problems.

Film Instabilities on a Horizontal Plane

Burelbach, Bankoff and Davis (1988) considered a film on a uniformly-heated horizontal plane subject to gravity, viscous forces, evaporation (condensation), capillarity, thermocapillarity, vapor recoil, and van der Waals attractions. Here thermocapillary, evaporative and rupture instabilities are present. Conditions were obtained for linearized stability and numerical calculations of the nonlinear equation were made showing the dynamical approach to a ruptured state. Reisfeld and Bankoff (1990) extended the analysis to a case where the viscosity depends on temperature and showed by proper rescaling that the evolution equation can be converted to the constant-viscosity case. The result is useful for films of temperature-sensitive liquids.

Film Instabilities on Inclined Planes

Joo, Davis and Bankoff (1991b) considered a film on a uniformly-heated inclined plane. Here now the thermocapillary and evaporative instabilities compete with the surface-wave instabilities driven by the component of gravity along the plane. The two-dimensional long-wave equation combines those of Benney (1966) for the isothermal film and Burelbach, Bankoff and Davis (1988) for the horizontal plane. There is a competition between the surface waves that propagate and steepen with the thermal instabilities that create fingers (depressions) that promote dryout. Numerical solutions of the nonlinear equation indicate that mean flow precludes dryout if the Reynolds number is large enough, while dryout results if the Marangoni number is large enough. All of this applies for two-dimensional disturbances only.

Joo and Davis (1992a) studied an isothermal viscous film on a vertical plane. It was found that all two-dimensional finite amplitude surface waves are unstable to three-dimensional disturbances. By numerically integrating the three-dimensional Benney equation, it was found that the instability occurs for small cross-stream wave numbers whose cut-off value is determined by surface tension. Although the mechanisms are different, the instability has an analogy to the secondary instability of the Tollmien-Schlichting waves in wall-bounded shear flows. The instability process occurs in three steps:

1. primary linear stability,
2. nonlinear equilibration of primary instability into two-dimensional finite-amplitude permanent waves,
3. secondary (three-dimensional) instability of the two-dimensional wave.

In wall-bounded shear flows, there is a threshold amplitude and the secondary instability appears on a (rapid) convective time scale. In the present thin-layer flows, the instability is unconditional (at least for vertical layers),

restricted to long waves, and viscous in nature, as in the primary instability.

Joo, Davis and Bankoff (1992a) developed the long-wave evolution equation, valid for three-dimensional disturbances, that governs both surface-wave and thermocapillary instabilities. This system has the property that by linear theory each instability alone cannot evolve into longitudinal structure. However, through nonlinear interaction and for moderate flow and heat transfer rates, the system conspires to generate longitudinal structures, periodic cross-stream. If these structures lead to dryout, rivulets would thus be created. This work thus demonstrates, for the first time, a mechanism of rivulet formation based solely on instability phenomena in the unbroken film, and hence is independent of wetting conditions. Joo, Davis and Bankoff (1992b,c) found analogous behavior if evaporation replaces thermocapillarity.

Joo and Davis (1992b) discussed for the isothermal film two types of instabilities. There is the three-dimensional breakdown of finite amplitude waves as discussed by Joo and Davis (1992a). These instabilities have the same downstream wave length as the background two-dimensional wave. Further, there is a spatially subharmonic instability that can occur in two dimensions; this is discussed. Finally, simulations of the evolution equation show that chaotic waves can develop from simple initial conditions.

Joo, Davis and Bankoff (1991a) examined in two dimensions the differences in predictions between the Benney equation and the Kuramoto-Sivashinsky equation.

Instrumentation

We have developed conductivity probes for local thin film measurements on an inclined solid surface. Conductivity probes were first used Neal and Bankoff (1963) to measure local void fraction in a study of mercury-nitrogen cocurrent flows. Nassos and Bankoff (1967) adapted these probes to air-water

flows by introducing a Schmitt trigger into the probe circuit. These probes have had very wide application. Kim, Lee and Bankoff (1984) and Kim and Bankoff (1985) used them in studying surface waves in cocurrent, turbulent, steam-water condensing stratified flows. The new feature here is that the local film thickness is obtained by measuring the impedance to ground of a partially-immersed probe. A thin glycerol-water film ($Re = 5-10$) drains uniformly around the outer circumference of an unheated, vertical stainless steel pipe 1.2m long and 5cm in outer diameter. In order to reduce the noise-to-signal ratio, it is necessary to use very fine, unwetted probes. Eight-micron diameter wires proved to be too flexible. With a 25 micron diameter, gold-plated tungsten wire immersed part way into the liquid, the noise-to-signal ratio is about $\pm 20\%$, which is comparable to other methods. The wire is made nonwetting by the application of a very thin carbonized coating, produced by dipping the wire into a heavy oil and then subjecting it to electrical heating in a high vacuum cell. The calibration of the wire signal amplitude at a driver frequency of 400 Hz is performed by immersing the probe in a horizontal liquid layer in a stainless steel dish. Data acquisition, and calculation of correlation functions and power spectra are performed by proprietary software on a PC. Eight probes have been constructed which can be placed at various elevations and circumferential positions. An adjustable wave maker is installed at the top in order to give an initial fundamental frequency. The flow loop and procedures are described in Appendix A. Both subharmonic and superharmonic responses appear as the two-dimensional wave travels downstream. We expect to follow the growth of three-dimensional secondary instabilities. We expect that the apparatus will have been modified to allow the heating of the pipe by condensing steam in the interior. This will allow us to examine thermocapillary effects and evaporation effects on

the development of wave instabilities, and also on the rupture and subsequent evolution of dry patches and rivulets.

Coating Flows

Reisfeld and Bankoff (1992) analyzed the case of a viscous liquid flowing on the surface of a horizontal cylinder which is heated or cooled. Lubrication theory was used to study a thin film subject to gravity, capillary, thermocapillary, and intermolecular forces. For an isothermal film, it was found that various steady-state film profiles can exist, for even very large Bond numbers. These steady-state shapes depend on the fluid properties through the Marangoni number, as well as the thermal conditions at the film free-surface through the Biot number.

Reisfeld, Bankoff and Davis (1991a) studied the spin-coating process for small Peclet numbers. A fixed volume of liquid is placed on a horizontal disk spinning at a constant angular speed. The liquid forms a film that thins continuously due to centrifugal drainage and evaporation, or, for a condensing film, thins to a finite thickness when surface absorption counterbalances drainage. A nonlinear evolution equation describing the shape of the film interface as a function of space and time is derived, and its stability is examined using linear theory. When there is either no mass transfer or there is evaporation from the film surface, infinitesimal disturbances decay for small wave numbers and are transiently stable for larger wavenumbers. The transient stability is a phenomenon in which a disturbance grows for a time and then decays to zero; this has not been reported before for spin coating. When absorption, rather than evaporation, is present at the free surface, the film exhibits three different domains of stability: disturbances of small wavenumbers decay, disturbances of intermediate wavenumbers grow transiently, and those of larger wavenumbers grow exponentially.

Reisfeld, Bankoff and Davis (1991b) next studied the case of spin coating with moderate or large Peclet numbers. Evaporation of solvent from the film increases the fluid viscosity and reduces the radial outflow. Governing equations were developed for the shape of the film interface as a function of space and time, as well as the axisymmetric solvent-concentration distribution, for both unit-order and large Peclet numbers. The numerical solution of these equations elucidates how a spinning film with either a corrugated or a flat free-surface evolves over time in the presence of a time-varying concentration (and hence viscosity) field. A correlation for the final film thickness is deduced from the governing equations in terms of the physical variables of the system the result of which shows good agreement with published experimental results.

Droplet Spreading

Given that we aim to approach dryout, it is of interest to know the effect of heat transfer on the spreading of a liquid. Ehrhard and Davis (1991) considered a liquid drop on a hot plate and found that thermocapillarity hinders spreading when the plate is heated and promotes spreading when the plate is cooled. Thus, there is possible sensitive control of spreading via heat transfer.

Publications on Grant

- Bankoff, S. G. 1990 "Dynamics and stability of thin heated liquid films," Max Jakob Memorial Award Lecture, J. Heat Transfer 112, 538.
- Burelbach, J. P., Bankoff, S. G. and Davis, S. H. 1988 "Nonlinear stability of evaporating/condensing liquid films," J. Fluid Mech. 195, 463.
- Burelbach, J. P., Bankoff, S. G. and Davis, S. H. 1990 "Steady thermocapillary flows of thin liquid layers. II. Experiments," Phys. Fluids A2, 322.
- Ehrhard, P. and Davis, S. H. 1991 "Non-isothermal spreading of liquid drops on horizontal plates," J. Fluid Mech. 229, 365.
- Joo, S. W. and Davis, S. H. 1992a "Instabilities of three-dimensional viscous falling films," J. Fluid Mech. (in press).
- Joo, S. W. and Davis, S. H. 1992b "Irregular waves on viscous falling films," Chem. Eng. Comm. (in press).
- Joo, S. W., Davis, S. H. and Bankoff, S. G. 1991a "On falling-film instabilities and wave breaking," Phys. Fluids A3, 231.
- Joo, S. W., Davis, S. H. and Bankoff, S. G. 1991b "Long-wave instabilities of heated falling films; two-dimensional theory of uniform layers," J. Fluid Mech. 230, 117.
- Joo, S. W., Davis, S. H. and Bankoff, S. G. 1992a "A mechanism for rivulet formation in heated falling films," Applied Mathematics Technical Report No. 9910, Northwestern University (pending publication).
- Joo, S. W., Davis, S. H. and Bankoff, S. G. 1992b "Instabilities in evaporating films," Proc. Intern. Symp. on Instab. in Multiph. Flows, Rouen, France, (eds. G. Gauesbet and A. Berlemont).

- Joo, S. W., Davis, S. H. and Bankoff, S. G. 1992c "Evaporative and thermocapillary instabilities in heated falling films," Proc. Japan-U.S. Symp. on Two-Phase Flow Dynamics, Berkeley, CA and to appear in Nucl. Eng. Design.
- Reisfeld, B. and Bankoff, S. G. 1990 "Nonlinear stability of a heated thin film with variable viscosity," Phys. Fluids A2, 2066.
- Reisfeld, B. and Bankoff, S. G. 1992 "Nonisothermal flow of a liquid film on a horizontal cylinder," J. Fluid Mech. 236, 167.
- Reisfeld, B., Bankoff, S. G. and Davis, S. H. 1991a "The dynamics and stability of thin liquid films during spin coating. Part 1. Films with constant rates of evaporation or absorption," J. Appl. Phys. 70, 5258.
- Reisfeld, B., Bankoff, S. G. and Davis, S. H. 1991b "The dynamics and stability of thin liquid films during spin coating. Part 2. Films with unit-order and large Peclet numbers," J. Appl. Phys. 70, 5267.
- Tan, M. J., Bankoff, S. G. and Davis, S. H. 1990 "Steady thermocapillary flows of thin liquid layers. I. Theory," Phys. Fluids A2, 313.

END

DATE
FILMED

10 / 20 / 92