AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

SUPERCritical WATER OXIDATION TECHNOLOGY FOR DWPF (U)

by J. T. Carter

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

Other Authors:

J. A. Gentilucci
(WSRC)

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This paper was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

REPRODUCTION OF THIS DOCUMENT IS UNLIMITED **MASTER**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER LABORATORY

WSRC-RP-92-252

February 7, 1992

TO: E. W. HOLTZSCHEITER, 773-A

FROM: *J. T. Carter*
J. T. CARTER, J. A. GENTILUCCI

SUPERCRITICAL WATER OXIDATION TECHNOLOGY FOR DWPF (U)

At the request of Mr. H. L. Brandt and others in the Savannah River Field Office High Level Waste Division office, DWPF and SRL personnel have reviewed two potential applications for supercritical water oxidation technology in DWPF.

The first application suggested by Mr. Brandt would replace the current hydrolysis process by destroying the organic fractions of the precipitated cesium / potassium tetraphenylborate slurry. Mr. Jeffrey Bettinger (Stone and Webster Engineering Company) reviewed a conceptual flowsheet for this application on January 7, 1992. SRL, DWPF, and DOE personnel attended this review and after consultation elected to gain additional knowledge about the technology, determine the technical certainties/uncertainties, and review an initial screening test proposal.

This review was held February 4, 1992 at the Modar Development Facilities in Natick, MA. Modar, Inc is one of two companies in the U.S. developing this technology for commercial application. Modar is currently a subcontractor to the DOE Industrial Energy Recovery Division. Attendees included H. L. Brandt of DOE-SR, E. W. Holtzscheiter, and J. T. Carter of SRL, and J. A. Gentilucci of DWPF.

The developers expressed a high degree of confidence the organic portion of the slurries will be destroyed by this technique. The primary concern is the metal salts composition and their melting points. Since the reactor operates at moderately high temperatures some of the metal salts, particularly the borates may become liquid or at least semi-liquid. This represents a major reactor pluggage problem for the pipe reactor. The vessel reactor and filter system (designed to solve the problem) has not been fully demonstrated. The \$30,000 scoping test proposal presented by Modar addresses only this concern.

Additional concerns presented by WSRC included the fate of many components including cesium, plutonium, uranium, and strontium. The molecular structure of the strontium and cesium adsorbed on the sodium titanate is not known nor the phase diagrams available for these components over the range 0-3800 psi and 0-600°C. The

Encl. 2/10/92 J.R. Classif

lack of the basic thermodynamic properties and the inability to predict (via property correlations) these properties [1] would dictate a very elaborate research and development program, since the reactor must operate in a single phase region.

Programs for the development of NaCl/Na₂SO₄ phase diagrams have taken upwards of 10 years. A similar program (although perhaps shorter in duration if the appropriate resources are applied) is anticipated for the multi-component precipitate slurry system. Since an appropriate substitute for plutonium is not available much of this work would have to be completed in the high level caves at SRL.

A second concern expressed by the WSRC personnel involves the remote maintenance and contamination control for the unit. Most of the equipment operates above 3400 psi. This pressure will require a second containment vessel to prevent pressurizing the canyon cells and thereby causing a flow reversal in the event of a catastrophic vessel failure. Remote maintenance of the equipment within the containment vessel becomes impractical if not impossible.

The standard Hanford connectors will also require a major redesign to be functional as a connection device at the higher pressure. The design effects for the remote maintenance and double containment are also anticipated to take several years.

For these reasons WSRC does not recommend proceeding with the development of the supercritical water oxidation technology for this application.

The second application reviewed is that of the liquid benzene destruction. A 1991 Stone and Webster Engineering Company review [2] recommended that the technology be considered for this application, and further more the overall impression of the report is that the technology is sufficiently developed for this application. The developers also expressed a high degree of confidence the organic will be destroyed. Since the benzene has been decontaminated to less than 1000 d/m/ml the secondary containment and remote maintenance concerns are minimized.

Supercritical water oxidation technology was considered by WSRC when the initial selection of the CIF alternative technology was made. The detoxifier was chosen as the first option to be tested since it operated below atmospheric pressure, is commercially available, requires only 40 kw of electric power, has no liquid effluent streams which would need additional treatment and has been demonstrate near DWPF capacities with compounds chemically similar to Benzene.[3]

WSRC is currently running capacity and DRE tests with the detoxifier to confirm the equipment can perform as expected. Should these tests fail a demonstration of supercritical water oxidation technology will be undertaken.

References

1. B. W. Shah, et.al., "Supercritical Water A Medium for Chemistry", Chemical and Engineering News, December 23, 1991.
2. J. M. Cardito to R. K. Hall, "Clean Air Act Appraisal and Supercritical Water Oxidation Review", TLSR-FC-008, May 21, 1991.
3. J. T. Carter, J. Morrison, "CIF Alternative Development" WSRC-TR-90-327, August 1, 1990.

JTC;dhw

**DATE
FILMED**

7 / 27 / 93

END