BNL--52329

DE92 018122

**Integration of Transients in Axisymmetrical
Cavities for Accelerators -
Formulation and Applications to
BNL Photocathode Gun**

Zohreh Parsa
Brookhaven National Laboratory, Upton, NY 11973

Luca Serafini
INFN and University of Milan, Milan, Italy

April 1992

Physics Department/CAP
Brookhaven National Laboratory
Associated Universities, Inc.
Upton, Long Island, New York 11973

Under Contract No. DE-AC02-76CH00016 with the
UNITED STATES DEPARTMENT OF ENERGY

**MASTER
MASTER**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

**Integration of Transients in Axisymmetrical Cavities for Accelerators – Formulation
and Applications to BNL Photocathode Gun**

**Zohreh Parsa
Brookhaven National Laboratory
Upton, New York 11973, USA**

**Luca Serafini
INFN and University of Milan, Milan, Italy**

ABSTRACT

This note provides a sketch of the formalism used for the Integration of Transients in Axisymmetrical Cavities for Accelerators, (ITACA). Application to study the BNL Photocathode Gun via the code ITACA is also included.

I. Introduction

We present an analysis of the BNL photocathode gun [1-3] and illustrate the formulation (Section II) used for the integration of the transients in axisymmetrical cavities for accelerators (ITACA).

We perform a numerical study of the interactions between high charged e-beam and the accelerating environment, where the effects of the e.m. fields produced by such interactions (wake-fields) are taken into account in the context of a self-consistent model which integrates the wave-equations for monopole axisymmetric fields coupled to the Newton-Lorentz equations for the motion via the electromagnetic particle in cell code ITACA [4]. With a new charge and current assignment algorithm, based on Rician distributions, which minimize the unphysical fluctuations in the driving current for the wave-equations, the effects of the e.m. interaction on the beam dynamics properties (emittances, energy spreads, etc.) are described (in Section III) for the BNL photoelectron gun. Additional information is given in References [6-10].

II. Overview of Formalism:

Consider the inhomogenous wave equations in vacuum:

$$\nabla^2 \vec{H} - \frac{1}{c^2} \frac{\partial^2 \vec{H}}{\partial t^2} = - \nabla \times \vec{J} \quad (1)$$

$$\nabla^2 \vec{E} - \frac{1}{c^2} \frac{\partial^2 \vec{E}}{\partial t^2} = \nabla \left(\frac{\rho}{\epsilon_0} \right) + \mu_0 \frac{\partial \vec{J}}{\partial t} \quad (2)$$

assuming that, both the source

$$\vec{J} = \vec{J}(r, z, t), \quad \rho = \rho(r, z, t) \quad (3)$$

and the Electromagnetic (E.M.) fields

$$\vec{E} = \vec{E}(r, z, t), \vec{H} = \vec{H}(r, z, t) \quad (4)$$

are axisymmetrical (i.e., cylindrical on axis beams and monopole fields), then one can verify that the wave equation (1,2), can be divided into two uncoupled sets: The TM-like set: (H_ϕ, E_r, E_z)

$$\begin{cases} \frac{\partial^2 H_\phi}{\partial z^2} + \frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial H_\phi}{\partial r} \right) - \frac{H_\phi}{r^2} - \frac{1}{c^2} \frac{\partial^2 H_\phi}{\partial t^2} = \frac{\partial J_z}{\partial r} - \frac{\partial J_r}{\partial z} \\ \frac{\partial^2 E_r}{\partial z^2} + \frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial E_r}{\partial r} \right) - \frac{E_r}{r^2} - \frac{1}{c^2} \frac{\partial^2 E_r}{\partial t^2} = \frac{1}{\epsilon_0} \frac{\partial \rho}{\partial r} + \mu_0 \frac{\partial J_r}{\partial t} \\ \frac{\partial^2 E_z}{\partial z^2} + \frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial E_z}{\partial r} \right) - \frac{1}{c^2} \frac{\partial^2 E_z}{\partial t^2} = \frac{1}{\epsilon_0} \frac{\partial \rho}{\partial z} + \mu_0 \frac{\partial J_z}{\partial t} \end{cases} \quad (5)$$

and the TE-like set: (E_ϕ, H_r, H_z)

$$\begin{cases} \frac{\partial^2 E_\phi}{\partial z^2} + \frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial E_\phi}{\partial r} \right) - \frac{E_\phi}{r^2} - \frac{1}{c^2} \frac{\partial^2 E_\phi}{\partial t^2} = \mu_0 \frac{\partial J_\phi}{\partial t} \\ \frac{\partial^2 H_r}{\partial z^2} + \frac{\partial^2 H_r}{\partial r^2} - \frac{H_r}{r^2} - \frac{1}{c^2} \frac{\partial^2 H_r}{\partial t^2} = \frac{\partial J_\phi}{\partial z} \\ \frac{\partial^2 H_z}{\partial z^2} + \frac{\partial^2 H_z}{\partial r^2} - \frac{1}{c^2} \frac{\partial^2 H_z}{\partial t^2} = -\frac{1}{r} \frac{\partial(r J_\phi)}{\partial r} \end{cases} \quad (6)$$

The general TM field can be expanded as a sum of infinite TM_{onp} modes of a resonant cavity; and the general TE field can be expanded as a sum of infinite TE_{onp} modes of a resonant cavity where, J_r and J_z are the driving current for the TM field and J_ϕ is the driving current for the TE field.

Thus a charged particle q moving with a velocity

$$\vec{v} = v_r \vec{e}_r + v_z \vec{k} \quad (7)$$

inside: I) a TM field is subject to a force

$$\vec{F} = F_r \vec{e}_r + F_z \vec{k} \quad (8)$$

and gives rise to a current

$$J = J_r \vec{e}_r + J_z \vec{k} \quad (9)$$

II) inside a TE field, is subject to a force

$$\vec{F} = F_\phi \vec{e}_\phi \quad (10)$$

and gives rise to a current

$$\vec{J} = J_r \vec{e}_r + J_\phi \vec{e}_\phi + J_z \vec{k} \quad (11)$$

Then for an initial driving current of the type;

$$\vec{J} = (J_r(r, z, t), J_z(r, z, t)) \quad (12)$$

in presence of a TM-Field, the sub-system of wave equations for the TM Field

$$\nabla^2 \vec{H} - \frac{1}{c^2} \frac{\partial^2 \vec{H}}{\partial t^2} = - \nabla \times \vec{J} \quad (13)$$

plus the Relativistic equations for the charged particles motion in the TM-Field

$$\frac{d\vec{p}}{dt} = q(\vec{E} + \vec{v} \times \vec{B}) \quad (14)$$

where $\vec{v} = (v_r, v_z)$, is a "self-consistent" system of equations.

In this case; the beam-cavity interaction can be completely described, from the point of view of the field propagations, by means of one scalar equation:

$$L\Phi - \frac{1}{c^2} \frac{\partial^2 \Phi}{\partial t^2} = r \frac{\partial J_z}{\partial r} - r \frac{\partial J_r}{\partial z} \quad (15)$$

Figure 1.

$$\Phi = rH_\phi \text{ (pseudo scalar potential)} \quad (16)$$

where $H_\phi = H_\phi(r, z, t)$, $J_r = J_r(r, z, t)$ and $J_z = J_z(r, z, t)$ and

$$L \equiv \frac{\partial^2}{\partial z^2} + \frac{\partial^2}{\partial r^2} - \frac{1}{r} \frac{\partial}{\partial r} \quad (17)$$

which is a typical "hyperbolic" equation; with initial conditions $\phi^0 = \phi(r, z, t = 0)$, $\phi'^0 = \frac{\partial \phi}{\partial t}(r, z, t = 0)$, $J_r^0 = J_r(r, z, t = 0)$ and $J_z^0 = J_z(r, z, t = 0)$, to be solved in a domain Ω , with boundary conditions on the curve Γ ;

$$\begin{cases} \left. \frac{\partial \phi}{\partial \eta} \right|_{\Gamma} = 0 \\ \phi(r = 0) = 0 \end{cases} \quad (18)$$

To solve these equations numerically, we adopt the standard FDM (Finite Difference Method) Technique, which allows to transform the differential problem into an algebraic problem, via the discretization of the operator L and of the functions ϕ , J_r, J_z over a (regular) mesh. Thus

$$L\Phi \rightarrow L_d\Phi_d \quad (19)$$

by expanding the partial derivatives in Taylor series up to the 2nd order around each point $o(r, z)$ of the mesh.

Figure 2.

$$L_d \Phi_d = A \Phi_0 + B(r) \Phi_1 + C(r) \Phi_2 + D \Phi_3 + E \Phi_4 \quad (20)$$

$$A = \frac{2}{\epsilon^2} + \frac{2}{h^2}$$

$$B = \frac{1}{\epsilon^2} - \frac{1}{2\epsilon r}$$

$$C = \frac{1}{\epsilon^2} + \frac{1}{2\epsilon r}$$

$$D = E = \frac{1}{h^2}$$

Applying the same procedure to the inhomogeneous term on the r.h.s. of the wave equation (15), we get:

$$\begin{aligned} r \frac{\partial J_z}{\partial r} - r \frac{\partial J_r}{\partial z} &\Rightarrow a(r) J_{z1} + b(r) J_{z2} + \\ &c(r) J_{r3} + d(r) J_{r4} \\ &\equiv f_d \end{aligned} \quad (21)$$

where,

$$a = -b = \frac{r}{2\epsilon}$$

$$c = -d = -\frac{r}{2h}$$

so that the discretized wave equation becomes:

$$\begin{cases} L_d \Phi_d = -K^2 \Phi_d \\ -L_d \Phi_d + \frac{\partial^2 \Phi_d}{\partial \tau^2} = f_d \\ \tau = ct \end{cases} \quad (22)$$

Since $-L_d$ is definite positive one can show that, if $\phi_d(r, z, t = 0)$ and $f_d(r, z, t)$ are sufficiently regular, the explicit time scheme

$$\frac{\Phi_d^{\tau+\delta\tau} - 2\Phi_d^\tau + \Phi_d^{\tau-\delta\tau}}{\delta\tau^2} - L_d \Phi_d^\tau = f_d^\tau \quad (23)$$

is a 2nd-order approximation (in $\delta\tau$) to the exact solution of the wave-equation.

If the ϕ -values of all the mesh points are given at a time t and at $t_0 - \delta t$, the explicit time scheme, repeatedly applied, allows to compute the field behavior in time, from t_0 till a given integration time $t_{\max}$. The operations involved are simply matrix multiplications.

$$\rightarrow \ell = 1, \dots, i_{\max} \bullet j_{\max}$$

$$\begin{bmatrix} \phi_{\ell}^{\tau+\delta\tau} \end{bmatrix} = \begin{bmatrix} m \\ \downarrow \\ 1 \\ \cdot \\ \cdot \\ \dots B'_j \dots D'E'C' \dots A'_j \dots \\ \dots B'_j \dots D'E'C' \dots A'_j \dots \\ \dots B'_j \dots D'E'C' \dots A'_j \dots \\ \cdot \\ \cdot \\ \cdot \\ \cdot \\ \cdot \end{bmatrix} \begin{bmatrix} \phi_{\ell}^{\tau} \end{bmatrix} - \begin{bmatrix} \phi_{\ell}^{\tau-\delta t} \end{bmatrix} + \delta\tau^2 \begin{bmatrix} f_{\ell}^{\tau} \end{bmatrix} \quad (24)$$

$\delta \tau^2 L_d + 2 \cdot 1$

Diagram illustrating a 2D lattice structure with axes r (vertical) and z (horizontal). The lattice points are labeled with indices i and j . The diagram shows a grid of points with dashed lines connecting them. The vertical axis is labeled r and the horizontal axis is labeled z . Points are labeled $\phi_1, \phi_2, \phi_{imax+1}, \phi_{imax+2}, \phi_{jimax+imax},$ and ϕ_l . A label $\phi_l = \phi_{(j-1)imax+i}$ is shown for a specific point. A label ϕ_l is also shown on the left side of the diagram.

The main disadvantage of a regular mesh is the difficulty to apply the boundary conditions along curved paths in the (r,z) plane.

Figure 3.

How is it possible to retain the 2nd-order approximation in ϵ and h also for the special internal points (O) lying near to the boundary? (For these points not all the four neighbors live inside the cavity, so the standard scheme is not applicable.)

We expand again up to 2nd-order in Taylor series the function $L\Phi$ around the point 0, but we replace the equation for points 1 and 3, which are actually external points,

Figure 4.

With the conditions $\frac{\partial \phi}{\partial n} = 0$ on the two points A and B, which lie on the boundary: the normal direction is specified by the local arc of circle which describes the boundary.

Figure 5.

The wave equation in "0" introduces 4 unknowns ${}^{\tau}\phi_o, {}^o\phi_r'', {}^o\phi_r', {}^o\phi_z''$

$${}^o\phi_r'' + {}^o\phi_z'' - \frac{1}{r} {}^o\phi_r' = \frac{1}{\tau^2} [{}^{\tau}\phi_o + -{}^{\tau}\phi_o - 2{}^o\phi_o] \quad (25a)$$

$$\rightarrow \begin{cases} {}^o\phi_r'' = \frac{\partial^2 \phi}{\partial r^2} \Big|_{(r''=0, t=t_0)} \\ {}^o\phi_z'' = \frac{\partial^2 \phi}{\partial z^2} \Big|_{(r''=0, t=t_0)} \\ {}^o\phi_r' = \frac{\partial \phi}{\partial r} \Big|_{(r''=0, t=t_0)} \end{cases}$$

(For ${}^o\phi_r''$ and ${}^o\phi_z''$; two equations are given at the points 2 and 4).

$${}^o\phi_2 = {}^o\phi_o - \varepsilon {}^o\phi_r' + \frac{\varepsilon^2}{2} {}^o\phi_r'' + \dots \quad (25b)$$

$${}^o\phi_4 = {}^o\phi_o - h {}^o\phi_z' + \frac{h^2}{2} {}^o\phi_z'' + \dots \quad (25c)$$

which introduces another unknown ${}^o\phi_z'$. For ${}^o\phi_r'$ and ${}^o\phi_z'$; writing $\frac{\partial \phi}{\partial n} = 0$ on the basis of the

2nd-order expansion in A and B we obtain equation (25-d and e):

(For point 3:)

$$n_\alpha = \cos \alpha \hat{k} + \sin \alpha \hat{e}_r \Rightarrow$$

$$({}^o\phi_r' + \zeta {}^o\phi_{rz}'') \tan \alpha + {}^o\phi_z' + \zeta {}^o\phi_z'' = 0 \quad (25d)$$

and (for point 1:)

$$n_\beta = \cos\beta \hat{k} + \sin\beta \hat{e}_r \Rightarrow$$

$$({}^o\phi'_r + \rho {}^o\phi''_{rz}) \tan\beta + {}^o\phi'_z + \rho {}^o\phi''_{rz} = 0 \quad (25e)$$

These two equations introduce another new unknown ${}^o\phi''_{rz}$: Thus to derive another equation we write the expansion for the point 7:

$${}^o\phi_7 = {}^o\phi_o - \varepsilon {}^o\phi'_r + \frac{\varepsilon^2}{2} {}^o\phi''_r - h {}^o\phi'_z + \frac{h^2}{2} {}^o\phi''_z + \varepsilon h {}^o\phi''_{rz} \quad (25f)$$

now, solving 6 equations (25a-f), one obtains the following solution for ${}^\tau\phi_o$:

$${}^\tau\phi_o = A {}^o\phi_1 + B {}^o\phi_2 + C {}^o\phi_3 + D {}^o\phi_4 + E {}^o\phi_5 + F {}^o\phi_6 + G {}^o\phi_7 + H {}^o\phi_8 + I {}^o\phi_o + L {}^\tau\phi_o \quad (26)$$

where

$$A = \left(\frac{1+\eta}{2}\right) \left\{ 2 \frac{\tau^2}{\varepsilon^2} \left\{ 1 + \frac{2\rho \tan\beta}{\delta h} \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] \right\} - \frac{\tau^2}{\varepsilon h} \left\{ \frac{2\rho\eta}{h} \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] - \frac{\xi \tan\alpha}{\delta\eta} \frac{\chi}{D^+} \right\} \right\}$$

$$B = \left(\frac{1-\eta}{2}\right) \left\{ 2 \frac{\tau^2}{\varepsilon^2} \left\{ 1 + \frac{2\rho \tan\beta}{\delta h} \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] \right\} - \frac{\tau^2}{\varepsilon h} \left\{ \frac{2\rho\eta}{h} \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] - \frac{\xi \tan\alpha}{\delta\eta} \frac{\chi}{D^+} \right\} \right\}$$

$$C = \left(\frac{1+\delta}{2}\right) \left\{ 2 \left(1 - \frac{\rho\eta}{\varepsilon} \right) \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] - \frac{\chi}{D^+} \delta h \left(1 - \frac{\xi \tan\alpha}{\varepsilon\eta} \right) \right\} \frac{\tau^2}{h^2}$$

$$D = \left(\frac{1-\delta}{2}\right) \left\{ 2 \left(1 - \frac{\rho\eta}{\varepsilon} \right) \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] - \frac{\chi}{D^+} \delta h \left(1 - \frac{\xi \tan\alpha}{\varepsilon\eta} \right) \right\} \frac{\tau^2}{h^2}$$

$$E = \left(\frac{1+\eta}{2}\right) \left(\frac{1+\delta}{2}\right) \cdot \frac{\tau^2}{\varepsilon h} \left\{ \frac{2\rho\eta}{h} \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] - \frac{\xi \tan\alpha}{\delta\eta} \frac{\chi}{D^+} \right\}$$

$$F = \left(\frac{1+\eta}{2}\right) \left(\frac{1-\delta}{2}\right) \cdot \frac{\tau^2}{\varepsilon h} \left\{ \frac{2\rho\eta}{h} \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] - \frac{\xi \tan\alpha}{\delta\eta} \frac{\chi}{D^+} \right\}$$

$$G = \left(\frac{1-\eta}{2}\right) \left(\frac{1-\delta}{2}\right) \cdot \frac{\tau^2}{\varepsilon h} \left\{ \frac{2\rho\eta}{h} \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] - \frac{\xi \tan\alpha}{\delta\eta} \frac{\chi}{D^+} \right\}$$

$$H = \left(\frac{1-\eta}{2}\right) \left(\frac{1+\delta}{2}\right) \cdot \frac{\tau^2}{\varepsilon h} \left\{ \frac{2\rho\eta}{h} \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] - \frac{\xi \tan\alpha}{\delta\eta} \frac{\chi}{D^+} \right\}$$

$$I = 2 - \frac{2\tau^2}{\varepsilon^2} \left\{ 1 + \frac{2\rho \tan\beta}{\delta h} \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] \right\} - \frac{\tau^2}{h^2} \times \\ \times \left\{ 2 \left(1 - \frac{\rho\eta}{\varepsilon} \right) \left[1 - \frac{\chi}{D^+} \left(\xi - \frac{\delta h}{2} \right) \right] - \frac{\chi}{D^+} \delta h \left(1 - \frac{\xi \tan\alpha}{\varepsilon\eta} \right) \right\}$$

$$L = -1$$

$$D^+ = \tan\alpha + \frac{2\tan\beta}{\delta h} \left(\xi - \frac{\delta h}{2} \right) \left(1 - \frac{2\rho\eta}{\varepsilon} \right)$$

$$\chi = \frac{2\tan\beta}{\delta h} \left(1 - \frac{2\rho\eta}{\varepsilon} \right) - \frac{2\eta}{\varepsilon} - \frac{1}{r}$$

and

$$\begin{array}{cc} \rho > 0 & \eta = -1 \\ \leftrightarrow & \leftrightarrow \\ \xi > 0 & \delta = -1 \end{array} \quad \begin{array}{cc} \rho > 0 & \eta = -1 \\ \leftrightarrow & \leftrightarrow \\ \xi < 0 & \delta = 1 \end{array}$$

$$\begin{array}{cc} \rho < 0 & \eta = 1 \\ \leftrightarrow & \leftrightarrow \\ \xi > 0 & \delta = -1 \end{array} \quad \begin{array}{cc} \rho < 0 & \eta = 1 \\ \leftrightarrow & \leftrightarrow \\ \xi < 0 & \delta = 1 \end{array}$$

The current and charge assignment algorithm is based on a Rician distribution:

$$\rho_i(r, r_i, z, z_i) = \frac{q_i}{(2\pi)^{3/2} \sigma_r^2 \sigma_z} e^{-\frac{(z-z_i)^2}{2\sigma_z^2} - \frac{(r-r_i)^2}{2\sigma_r^2}} e^{-X} I_0(X) \quad (27)$$

where q_i, r_i, z_i are the charge and coordinates of the i -th particle; σ_r, σ_z are the gaussian width of the distribution and $X \equiv \frac{r r_i}{\sigma_r^2}$.

The corresponding current densities distributions are:

$$J_{iz}(r, r_i, z, z_i) = \beta_{\parallel i} c \rho(r, r_i, z, z_i) \quad (28)$$

$$J_{ir}(r, r_i, z, z_i) = \beta_{\perp i} c \rho(r, r_i, z, z_i) \frac{I_1(X)}{I_0(X)} \quad (29)$$

with $\beta_{\perp i}$ and $\beta_{\parallel i}$ are the radial and axial components of the i -th particle beta respectively.

$$I_0(X) = \frac{1}{\pi} \int_0^\pi e^{X \cos \theta} d\theta, \quad (30)$$

$$I_1(X) = \frac{1}{\pi} \int_0^\pi e^{X \cos \theta} \cos \theta d\theta, \dots \quad (31)$$

where $I_0(X)$ and $I_1(X)$ are the 0-th order, 1st-order... modified Bessel functions of the first kind.

Thus

$$J_z = \beta_{||}^i \bar{q}_i e^{-(z-z_i)^2/2\sigma_z^2} e^{(-r^2-r_i^2)/2\sigma_r^2} I_0\left(\frac{r r_i}{\sigma_r^2}\right) \quad (32)$$

$$J_r = \beta_{\perp}^i \bar{q}_i e^{-(z-z_i)^2/2\sigma_z^2} e^{(-r^2-r_i^2)/2\sigma_r^2} I_1\left(\frac{r r_i}{\sigma_r^2}\right) \quad (33)$$

$$\bar{q}_i = \frac{q_i c}{(2\pi)^{3/2} \sigma_r^2 \sigma_z^2} \quad (34)$$

These satisfy the continuity equation, guarantees gauge invariance ($\nabla \cdot \vec{E} - \rho/\epsilon = 0$) and minimizes the unphysical fluctuation in the driving current. Figure 6 illustrates plot of J_r vs (r/σ_r) for different values of $\left(\frac{r_i}{\sigma_r}\right)$.

Once the field $\Phi(r, z, t) = r \cdot H_\phi(r, z, t)$ is obtained all over the mesh, via the integration of the wave equation, it is straight forward to compute the electric-field components $\epsilon_r^{ij}(t)$, $\epsilon_z^{ij}(t)$, in each mesh point (i, j) , as functions of time, integrating the $2 \cdot \text{imax} \cdot j$ small one-dimensional equations:

Figure 6.

$$\left\{ \begin{array}{l} \frac{d\epsilon_r^{ij}}{d\tau} = -\frac{1}{r} \frac{\partial \phi^{ij}}{\partial z} - J_r^{ij} \\ \frac{d\epsilon_z^{ij}}{d\tau} = -\frac{1}{r} \frac{\partial \phi^{ij}}{\partial r} - J_z^{ij} \\ \tau = ct, \vec{E} = \frac{\vec{E}}{\sqrt{\mu_0/\epsilon_0}} \\ i = 1, \dots, i_{\max} \\ j = 1, \dots, j_{\max} \end{array} \right.$$

where

$$\epsilon_{r,z}^{ij}(t), \phi^{ij}(t), J_{r,z}^{ij}(t)$$

are the values of the electric field, magnetic field and current densities at each point of a subregion of the mesh which covers a region around the z-axis where the particles are expected to move.

Figure 7.

For large class of particles this saves memory.

For the particle tracking, one must integrate the relativistic equations of the motion, in a TM-like e.m. field:

$$\vec{E} = (E_r(r,z,t), E_z(r,z,t))$$

$$\vec{H} = (H_\phi(r,z,t))$$

$$\frac{d\beta_{\parallel n}}{d\tau} = \frac{\Omega}{\gamma_n} \left[\epsilon_z^n (1 - \beta_{\parallel n}^2) - \epsilon_r^n \beta_{\parallel n} \beta_{\perp n} + H_\phi^n \beta_{\perp n} \right]$$

$$\frac{d\beta_{\perp n}}{d\tau} = \frac{\Omega}{\gamma_n} \left[\epsilon_r^n (1 - \beta_{\perp n}^2) - \epsilon_z^n \beta_{\parallel n} \beta_{\perp n} - H_\phi^n \beta_{\parallel n} \right]$$

$$\frac{dz_n}{d\tau} = \beta_{\parallel n}$$

$$\frac{dr_n}{d\tau} = \beta_{\perp n}$$

$$\tau = ct, n = 1, \dots, N, \Omega = \frac{q\mu}{m_0 c}$$

$$\gamma_n = [1 - \beta_{\parallel n}^2 - \beta_{\perp n}^2]^{-1/2}$$

where $\epsilon_r^n, \epsilon_z^n, H_\phi^n$ are the interpolated values on the mesh at the position (r_n, z_n) . To integrate these N_p (number of macro particles) 1-dim equations, together with the 2imax • jsma11 equations for the electric field, a standard R.-K. procedure can be used, getting a IV-order approximation.

III. BNL Photocathode Gun:

The BNL gun consists of a 1 1/2 cell π -mode cavity with a methal photocathode at the midplane of its first cell. With inner diameter of 83.08 [mm], and total length of 78.75 mm (where the 1st cell length = 2.625 cm, and the 2nd cell length = 5.250 cm, with Radius of aperture of 1 [cm]).

The gun is powered by a (conventional type), SLAC klystron, and is designed to produce a low emittance beam of 4.65 MeV at the exit of the gun, with the 100 MV/m Field on cathode (i.e., an average axial gradient of 66.6 MV/m), cavity shunt impedance of 57 Mohm/m cavity

Q of 11,900, and the stored energy of ~ 4 Joules [J]. Figure 7 shows the schematic plot of the BNL gun. The initial results are obtained by illuminating the cathode with a Nd: YAG laser beam (266 nm), where the photoelectrons are injected to the LINAC via a transport beamline.

Figure 7. Schematic Plot of the BNL Photocathode Gun.

In the following Figures, I-V, (see Figure Captions below), the behaviour of the beam including the self field and wake field effects (at various points along the cavity) are shown, for the standard BNL gun, where the field on the cathode is 100 MV/m, the laser spot size is 3 mm, the laser pulse width is 2 p second, the initial phase is 63° , and the bunch charge is 1 nc.

The injection energy of the photoelectrons is 1.5 eV, a typical value for a Yt cathode, with the rms emittance, of ≈ 3.5 mm-mrad at the cathode. The laser-pulse has been taken to have a Gaussian distribution both in the radial coordinate (between $r = 0$ and $r = 3\sigma_r = 9$ mm) and in the longitudinal direction, where it is described between $-3\sigma_t$ and $3\sigma_t$ from the centroid of the pulse (a total of 12 ps).

The initial phase of 63° (used in this paper) corresponds to the time the head of laser (at $3\sigma_r$ from the centroid) hits the cathode surface. Thus, the injection phase of the centroid of the electron bunch is at $63^\circ + 3\sigma_r$, which is $\approx 68^\circ$.

In Table A, the variation of the results obtained with the change in the injection phase and the cathode material are summarized. For these calculations a mesh with 165,000 points, integration step of .067 mm (≈ 23 RF deg); and 2400 particles with Gaussian widths of 0.3 mm radially and 0.15 mm axially were used for 2 types of cathodes (Yttrium and Cooper). The ND-Yag photon energy was assumed to be 4.6 eV, the work function of Cu 4.6 eV and Yt to be 3.1 eV.

In Table B, the variation in the results obtained with changes in mesh size and number of particles are shown (and are negligible).

Figures I-(4 and 5), show the effect of the cavity surface around the cathode onto the bunch self field, at ($\phi_{out} \approx 83^\circ$).

Figures II – (4,5), show the propagation of the bunch self - field, (at $\phi_{out} \approx 103^\circ$).

Figures III – (4,5), show the effect of wake and the bunch self - field, (at $\phi_{out} \approx 123^\circ$).

Figures IV-1, shows the self-field plot of the bunch (the magnetic component), and

Figures IV-2, shows the self-field plot of the bunch; (the electric component), at output phase of 90 RF deg after the injection (63°), hence at RF phase of 153° .

In Figure (IV-2), the solid- lines, has a long negative tail produced by the interaction between the bunch charge and current with the cathode surface; (i.e., by the image charge and current).

The peak in the radial electric field (dashed lines) is such that the axial position of the peak is decreasing with increasing radius. That is due to the interaction with the cavity surface in the iris region (i.e., due to wake - field effect: in fact this distribution matches the shape of the field lines in the $r \cdot H_\phi = \text{constant}$ plot of previous graph, Figure (IV-1).

Figure V, shows various parameters with changes in the initial phase values, at $\phi_{out} \approx 243^\circ$. Additional analysis of the BNL gun is given elsewhere, see e.g., [1,6-10].

Table A

Cathode	Copper	Copper	Yttrium	Yttrium
Starting energy [eV]	.05	.05	1.5	1.5
Cathode peak field [MV/m]	100	100	100	100
Extract bunch charge [nC]	1.	1.	1.	1.
Laser spot σ_r [mm]	3.	3.	3.	3.
Rms cathode emitt. [m•rad]	$.65 \cdot 10^{-6}$	$.65 \cdot 10^{-6}$	$3.5 \cdot 10^{-6}$	$3.5 \cdot 10^{-6}$
Laser pulse length ($2\sigma_t$) [ps]	4.	4.	4.	4.
Injection phase [deg]	57.	63.	60.	63.
Exit charge [nC]	.89	.89	.89	.89
Exit energy [MeV]	4.18	4.14	4.17	4.14
Rms energy spread [keV]	± 14	± 29.0	± 21.6	± 29.0
Exit radius σ_x [mm]	4.1	4.1	4.1	4.1
Exit divergence $\sigma_{x'}$ [mrad]		26.9	27.8	26.9
Exit rms norm. emitt. [m•rad]	5.0	7.5	6.5	8.
Rms bunch length [mm]	1.15	1.20	1.175	1.20
Peak current [A]	174	166	170	166

Table B

Mesh	330,000	165,000
Particles	6200	2400
Cathode	Copper	Copper
Starting energy [eV]	.05	.05
Cathode peak field [mV/m]	100	100
Extract. bunch charge [nC]	1.	1.
Laser spot σ_r [mm]	3.	3.
Rms cathode emitt. [m•rad]	$.64 \cdot 10^{-6}$	$.65 \cdot 10^{-6}$
Laser pulse length ($2\sigma_t$) [ps]	4.	4.
Injection phase [deg]	60.	60.
Exit charge [nC]	.89	.89
Exit energy [MeV]	4.173	4.170
Rms energy spread [keV]	± 21.4	± 21.6
Exit radius σ_x [mm]	4.1	4.1
Exit divergence $\sigma_{x'}$ [mrad]	27.9	27.8
Exit rms norm. emitt. [m•rad]	5.2	5.5
Rms bunch length [mm]	1.170	1.175
Peak current [A]	168	170

Figure VI, shows plot of the transverse emittance vs z , for the case of copper cathode at $\Phi_0 = 57^\circ$ (first column of Table A).

Conclusion

We discussed the formalism used for integrating the transients in axisymmetrical cavities (Section II), and illustrated some numerical results obtained via program ITACA for the BNL photocathode gun (Section III). The preliminary data measured at ATF gave a much smaller value e.g. for emittance as compared to those obtained with ITACA, although for a more accurate comparison additional measurements are needed. They will be made when more data becomes available. For additional information see references [1-10].

References

1. Z. Parsa, "*Preliminary Emittance Measurements and Calculations of the Laser Excited Beam from the BNL Accelerator Test Facility Radio Frequency Electron Gun*", Proceedings of the BNL Center for Accelerator Physics Meetings, Vol. II, Sec. II, P. 1-54, BNL-52292 (1991), and Ref. therein.
2. K. Batchelor, I. Ben-Zvi, I. Biglio, T.S. Chou, R.C. Fernow, J. Fischer, N. Kurnit, K.T. McDonald, R.B. Palmer, Z. Parsa, G. Pellegrini, J. Sheehan, T. Srinivasan-Rao, S. Ulc, A. Van Steenberg, M. Woodle, "*Operational Status of Brookhaven Accelerator Test Facility*", Proceedings of the 1989 IEEE Particle Accelerator Conf. Chicago, Ill, March 20-23, 1989, #89CH2669-0 (1990), and BNL Report BNL-41797; *ibid.*, Proceedings of the 2nd European Accelerator Conf. Nice, France, June 12-16, 1990, Ed. Frontiers, (1990).
3. P. Russel et al., The Brookhaven Accelerator Test Facility, Proceeds of the Rice Meeting, 1990 of APS Div. of Particle – Fields, Houston, Tx. Jan. 1990, (P. Bonner and H. Miettinen, eds.) World Scientific, Singapore, P. 975, (1990).
4. L. Serafini and C. Pagani, "A Computer Code for the Integration of Transient Equations in Axisymmetrical Cavities", Proc. 1st. EPAC, Rome, Ed World Scientific, p. 866, (1988); L.

- Serafini et al., "Design of the SC Laser Driven Injector for ARES", Proc. 2nd EPAC Nile, Ed. Frontieres, p. 143 (1990), and Numerical Simulations for the ARES SC Injectors, Tep. INFN TC-90/10.
5. M. Zanin, Thesis, University of Milan (1989); A. Pretti, L. Serafini and M. Zanin (to be published).
 6. Z. Parsa, and L. Young, "*On Design and Analysis of High Brightness Electron Source*", Proceedings, of the 2nd European Particle Accelerator Conf., Nice – France, June 12-16, 1990, Nile, Ed., Frontieres, (1990); BNL Report BNL-44365 (1990).
 7. Z. Parsa, and L. Young, "*The BNL Photocathode Gun with the Code PARMELA*", Proceedings of the 13th Int. FEL Conf., Santa Fe, NM., 260-30 Aug., 1991, BNL-46804 (1991).
 8. Z. Parsa, "*Analysis of a High-Brightness Photoelectron Beam with Self-Field and Wake-Field Effects*", *ibid* and BNL-46794 (1991).
 9. Z. Parsa, " *Effects of Variation of the Laser Pulse Width on the Laser Induced Photo-electrons*", *ibid*, and BNL-46795 (1991).
 10. Z. Parsa, "*Interactions Between Charged Particles and RF Space Charge and Wake Fields in an Accelerating Structure*", Proceedings of the Particles and Fields 91 conf. Aug. 18-22, 1991, Vancouver, Canada, (1991).

*An executable version of the program will be available on BNLDAG in [PARSA.ZPACC].

**We (Z.P.) thank Paul Kessler, Tony Natoli and R. Imossi for providing extra disks and computer assistance, and A. Pretti for assisting with the Graphic Processor.

Figure I-1 to 8, at $\phi_{out} = 82.953^\circ$, $\phi_{init} = 63^\circ$

Figure I-1 shows plot of the $r \cdot H_\phi = \text{const}$ lines for 1 nC case, total field.

Figure I-2 shows plot of the lines of self field produced by 1 nC bunch.

Figure I-3 shows plot of R vs R'; the transverse phase space,

Figure I-4 shows plot of H_{ϕ} vs R ,

Figure I-5 shows plot of H_{ϕ} vs z , the effect of cavity surface around the cathode onto the bunch self field.

Figure I-7 shows plot of E_z (solid line) and E_r (dashed lines) vs r .

Figure I-8 shows plot of E_z (solid line) and E_r (dashed lines) vs Z .

Figure II-1 to 8, at $\phi_{out} = 103^\circ$, $\phi_{init} = 63^\circ$.

Figure II-1 shows plot of the $r \cdot H_\phi = \text{const}$ lines for 1 nC case, total field.

Figure II-2 shows plot of R vs R' ; o the transverse phase space. The solid line traces the rms ellipse.

Figure II-3 shows plot of H_{ϕ} vs R ,

Figure II-6 shows plot of J_r (solid lines) and J_z (dashed lines) distributions as functions of z at different radii.

Figure II-7 shows plot of E_z (solid line) and E_r (dashed lines) vs z .

Figure III-1 to 9, at $\phi_{\text{out}} = 123^\circ$, $\phi_{\text{out}} = 63^\circ$.

Figure III-1 shows plot of the $r \cdot H_\phi = \text{const}$ lines for 1 nC case, total field.

Figure III-2 shows plot of R vs R' ; the transverse phase space.

Figure III-3 shows plot of the propagation of the bunch self field produced by the bunch.

Figure III-4 shows plot of H_{ϕ} vs R ,

Figure III-5 shows plot of H_{ϕ} vs z , the effect of wake and the bunch self - field.

Figure III-6 shows plot of J_r (solid lines) and J_z (dashed lines) distributions as functions of z at different radii.

Figure III-7 shows plot of E_z (solid line) and E_r (dashed lines) vs r .

Figure III-8 shows plot of E_z (solid line) and E_r (dashed lines) vs Z .

Figure III-9 shows plot of $\rho - \text{div}E$ vs z and R .

Figure IV-1 shows plot of the magnetic component of the bunch self - field.

Figure IV-2 shows plot of E_z (solid line) and E_r (dashed lines) vs z , the electric component of the bunch self field, at $\phi_{out} = 152.905^\circ$.

Figure V-1 to 8, at $\phi_{\text{out}} = 243.039^\circ$, $\phi_{\text{in}} = 63^\circ$.

Figure V-1 shows plot of the $r \cdot H_\phi = \text{const}$ lines for 1 nC case, total field.

Figure V-2 shows plot of X vs X' ; the transverse phase space.

Figure V-3 shows plot of propagation of the bunch self field produced by the bunch.

Figure V-4 shows plot of J_r (solid lines) and J_z (dashed lines) distributions as functions of z at

Figure V-5 shows plot of Transverse Emittance vs z . Dashed line shows the normalized

emittances $\sqrt{\langle x^2 \rangle \langle p_x^2 \rangle - \langle x p_x \rangle^2} = \epsilon_n$; Solid curve line shows the emittance $\epsilon = \sqrt{\langle x^2 \rangle \langle x'^2 \rangle - \langle x x' \rangle^2}$ and third curve ($\epsilon_n^{\text{central}}$), gives ϵ_n associated to the central slice of the bunch.

Figure V-6 shows plot of length of the bunch and R_{rms} vs z .

Figure V-7 shows plot of Average Kinetic Energy (solid line) and $\Delta\gamma / \langle\gamma\rangle$ (dashed line), vs z .

Figure V-8 shows plot of P_z/mc vs z . The solid line is the rms ellipse.

gives ε_n associated to the central slice of the bunch.

END

**DATE
FILMED
9/01/92**