AN ESTIMATION OF TRITIUM INVENTORY LIMITS FOR THE E-AREA VAULTS (U)

by

A. D. Yu and J. R. Cook

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Received by SSTI

AUG 11 1992

This report was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U.S. Department of Energy. By acceptance of this report, the publisher and/or recipient acknowledges the U.S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this report, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted report.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

**WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER LABORATORY DIVISION**

Keywords: Tritium Vault
Burial Ground Expansion
Modeling

WSRC-TR-91-597-TL

CC: S. A. Lorah, 724-10E
C. W. McVay, 724-10E
L. T. Reid, 705-H
J. M. Wallace, 724-10E
J. R. Shappell, 724-9E
S. T. Wach, 703-H
S. R. Reed, 703-H
A. D. Yu, 773-43A

W. E. Stevens, 773-43A
E. L. Wilhite, 773-43A
N. S. Roddy, 773-43A
B. G. Kitchen, 773-41A
B. D. Helton, 773-41A
W. R. McDonell, 773-42A
J. R. Cook, 773-43A
SRL Records (4)

December 2, 1991

TO: R. W. HARRAL, 773-43A

FROM: W. L. TAMOSAITIS, 773-43A

**AN ESTIMATION OF TRITIUM INVENTORY LIMITS
FOR THE E-AREA VAULTS (U)**

At the request of Waste Management, Interim Waste Technology has conducted a modeling study to estimate the tritium inventory limits for the E-Area vaults. These inventory limits are based on the groundwater impact of the planned waste disposal.

The tritium inventory limit for an Intermediate Level Tritium Vault (ILTV) is estimated to be 400,000 Curies with a 100 year storage period. During this period, it is assumed that the ILTV will be vented, any leachate will be extracted, and its performance will be carefully monitored.

The tritium inventory limits for a Low Activity Waste Vault (LAWV) and an Intermediate Level Non-Tritium Vault (ILNTV) are estimated to be 15,000 and 11,000 Curies, respectively. Venting and leachate extraction were not assumed necessary. These operational alternatives would further enhance the performance of these vaults.

These limits are significantly higher than the forecasted maximum tritium inventories for the vaults. Details of the modeling study are described in the attached report.

**WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER LABORATORY DIVISION**

Keywords: Tritium Vault
Burial Ground Expansion
Modeling

WSRC-TR-91-597

CC: R. W. Harral, 703-H
S. A. Lorah, 724-10E
C. W. McVay, 724-10E
L. T. Reid, 705-H
J. M. Wallace, 724-10E
J. R. Shappell, 724-9E
S. T. Wach, 703-H
S. R. Reed, 703-H

W. L. Tamosaitis, 773-A
E. L. Wilhite, 773-43A
N. S. Roddy, 773-43A
B. G. Kitchen, 773-41A
B. D. Helton, 773-41A
W. R. McDonell, 773-42A

SRL Records (4)

October 28, 1991

TO: W. E. STEVENS, 773-43A

FROM: A. D. YU, 773-43A *ADY*
J. R. COOK, 773-43A *JRC*

**AN ESTIMATION OF TRITIUM INVENTORY LIMITS
FOR THE E-AREA VAULTS (U)**

CONCLUSIONS

The tritium inventory limit for an Intermediate Level Tritium Vault (ILTV) is estimated to be 400,000 Curies with a 100 year storage period. During this period, it is assumed that the ILTV will be vented, any leachate will be extracted, and its performance will be carefully monitored.

The tritium inventory limits for a Low Activity Waste Vault (LAWV) and an Intermediate Level Non-Tritium Vault (ILNTV) are estimated to be 15,000 and 11,000 Curies, respectively. Venting and leachate extraction were not assumed necessary. These operational alternatives would further enhance the performance of these vaults.

These limits are significantly higher than the forecasted maximum tritium inventories for the vaults.

SUMMARY

At the request of Waste Management Technology (WMT), a ground-water modeling study has been conducted to estimate the tritium inventory limits for each of the E-Area vaults. Important modeling assumptions and results are:

	ILTV	ILNTV	LAWV
Tritium Inventory Limit, Curies	400,000	15,000	11,000
Peak Time, Years Groundwater Conc.	153	10	10
Tritium Waste	Yes	No	No
Transport Mechanism	Leaching	Vapor Diffusion	Vapor Diffusion
Cap Efficiency	96.4	96.4	96.4
Venting	Yes	No	No
Leachate Collection	Yes	No	No
100 Year Storage	Yes	No	No

Venting the ILTV is consistent with a previous recommendation by Orebaugh and Wallace¹ based on hydrogen generation. The ILNTV and the LAWV design and operational alternatives are consistent with those used by Cook² to estimate the disposal limits for contaminants other than tritium. The tritium inventory limit for an ILTV is 400,000 Ci which is four times higher than the expected maximum inventory of 100,000 Ci. The tritium inventory limits for an ILNTV and a LAWV are 11,000 and 15,000 Ci which are significantly higher than the estimated maximum inventories of 5,000 and 10,000 Ci, respectively. This means that low activity and intermediate activity non-tritium wastes can be safely stored/disposed in the E-Area vaults even though small quantities of tritium will be present in these wastes.

INTRODUCTION

Approximately 50,000 Curies of tritium waste are generated at SRS annually. Most of the tritium is associated with the spent melt crucibles remaining from the thermal extraction step in the tritium production process. Tritium crucibles and other forms of solid tritium wastes have been traditionally disposed in earthen trenches in the E-Area. Although trench disposal of tritium wastes at SRS has not resulted in any health or environmental problems to onsite or offsite populations, groundwater tritium concentrations exceeding the EPA Drinking Water Standard resulting from low level waste disposal after September, 1988 are an environmental concern as addressed by DOE Orders 5820.2A³ and 5400.4.⁴

Starting in the 1990's, tritium wastes and other forms of low level solid radioactive wastes generated at SRS will be stored or disposed in subgrade concrete vaults now under construction in the E-Area -- a 200 acre site located immediately north of the existing Solid Waste Disposal Facility. Low-level solid radioactive waste at SRS is classified into tritium wastes and non-tritium wastes according to its tritium content. A Waste item such as a tritium crucible or a B-25 box with one milligram (10 Ci) or more tritium recorded on the burial slip is classified as tritium waste. Wastes with only incidental quantities of tritium (zero milligram on the burial slip) are classified as non-tritium wastes. The non-tritium wastes are administratively divided into two categories: the low activity and the intermediate activity. Wastes radiating more than 200 mrem per hour at 5 cm (2 inches) from the surface of an unshielded container are classed as intermediate activity.

Tritium wastes will be consigned to the ILTV. Low activity wastes will be consigned to the LAWV. Intermediate activity wastes will be consigned to the ILNTV.

The E-Area Vaults are designed to meet the performance objectives of DOE Order 5820.2A. The major performance objectives are:

1. less than 25 mrem/yr to any member of the public via all pathways (surface water, groundwater, soil, plants, animals, and air).

2. less than 100 mrem/yr continuous exposure or less than 500 mrem for a single acute exposure to an inadvertent intruder after the loss of active institutional control (100 years).
3. Protect groundwater resources, consistent with Federal, State and local requirements. This is interpreted at SRS as less than 4 mrem/yr for groundwater at the E-Area facility boundary according to EPA⁵ Drinking Water Standards.

The impact of trench disposal of tritium on human health via ten potential pathways was simulated using the PATHRAE model.⁶ Modeling results indicate that the groundwater pathway presents the greatest potential hazards to onsite and offsite populations. The groundwater scenario (Figure 1) starts with water infiltration into the waste, leaching of the contaminants, traveling through the vadose zone, and recharge to the groundwater. It is assumed that at some future time, a person drills a well at a certain distance down gradient from the waste disposal site and uses the well water for his living and farming activities. The most stringent regulatory assumption is that the well is drilled at one meter from a waste vault and the person drinks two liters of the well water every day for 365 days a year.

Most groundwater models will predict the concentrations of a contaminant at the well. The concentration changes with time which is affected by the inventory, amount of infiltration, leach rate, transport properties, retardation, decay, and chemical reactions. Ordinarily, the concentration of a contaminant will go through a peak. The peak concentration is used to calculate the maximum ingestion dose by:

$$D = C \times 730 \times DCF \quad (1)$$

where

D = dose in mrem/yr,

C = concentration in pCi/L,

730 = amount of water ingested in L/yr, and

DCF = dose conversion factor in mrem/pCi.

The regulatory maximum ingestion dose has been 4 mrem/yr. At present, the EPA adopted tritium ingestion dose conversion factor is $6.3\text{E-}08$ mrem/pCi based on ICRP-30 dose methodology.⁷ Substituting these numbers into equation (1), the maximum concentration allowed in the groundwater is approximately 90,000 pCi/L or 90 pCi/mL.

Two groundwater release mechanisms are considered: (1) Leaching, and (2) Vapor phase transport. The leaching mechanism results from water penetration into the vault, contacting the waste where tritium is leached, and water migration through the bottom slab. The vapor phase transport results from diffusion through the waste containment units, into the vault space and then out of the vault walls. Once tritium is out of the vault wall, it is carried by infiltration water through the vadose zone and into the groundwater.

A tritium crucible is sealed with epoxy resin and then placed into a stainless steel overpack with an O-ring seal. The crucibles will be arranged in an upright position into the 142 silos in an ILTV. Wastes in the ILNTV and the LAWV are contained in plastic bags and B-25 Boxes. Vapor phase tritium release from the crucibles is much slower than that from plastic bags. Besides, the ILTV is assumed to be vented for 100 years. Consequently, vapor phase tritium transport will not be a significant groundwater contamination mechanism for the ILTV. On the other hand, because the forecasted tritium inventory for the ILNTV and the LAWV is two orders of magnitude lower than that for the ILTV, groundwater contamination by leaching for the ILNTV and the LAWV will be no problem if the performance assessment for the ILTV shows satisfactory results. As a result, this study models leaching for the ILTV and vapor phase transport for the ILNTV and the LAWV.

From a Waste Management point of view, the groundwater tritium concentrations are affected by the initial inventory, the vault design, and the operational alternatives. These are the major human factors controllable by the SRS Waste Management team to comply with the DOE Orders. The design of the E-Area Vaults⁸ is complete. It has included the recommendations made by WMT and IWT⁹ to vent and drain the ILTV so that hydrogen buildup and bottom water intrusion will not occur. Groundwater contamination is also affected by the effectiveness of the closure cap in reducing infiltration.

The objective of this study is to estimate a tritium inventory limit for the ILTV, the ILNTV, and the LAWV based on a performance analysis of each of the vaults. The limiting mechanism for the ILTV is leaching. The limiting mechanism for the ILNTV and the LAWV is vapor phase transport. This report includes site and waste characterization, model description, model validation, the performance assessment, quality assurance, and results of the investigation.

SITE CHARACTERIZATION

The E-Area vault project^{8,10} (approximately 200 acres) is located immediately north of the present Solid Waste Disposal Facility (Figure 2). Of this area, 100 acres is currently under development for new disposal units.

The topography of the site is gently sloping. The surface materials are made up of sandy clays and clayey sands. The existing vegetation consists primarily of pine trees.

At present, 17 well clusters have been installed in the immediate vicinity of the site. Water level measurements taken in these wells indicate that the water table is at depths ranging from 60 to 40 feet (18 to 12 m) below the ground surface. Water flow in the water table is to the north, towards a major tributary of the Savannah River, Upper Three Runs Creek.

WASTE CHARACTERIZATION

Solid wastes to be disposed at the new E-Area vaults will be divided into four disposal categories: 1) long lived wastes will be consigned to the Long Lived Waste Storage Building. 2) Tritium Wastes will be consigned to the ILTV. 3) Low Activity (non-tritium) Wastes will be consigned to the LAWV. 4) Intermediate Activity (non-tritium) Wastes will be consigned to the ILNTV. Figure 3 shows a flow chart of the waste classification. The tritium wastes consist of the following two primary waste forms:

1. Job control waste, small equipment and process vessels from the tritium recovery process. Job control waste, known as dry active waste in the commercial nuclear industry, consists of rubber gloves and shoe covers, paper wipes, clothes, and PVC/polyethylene bags. This waste will be contained in standard metal boxes.
2. Tritium crucibles and large disassembly and removal (D&R) waste forms. Tritium crucibles are stainless steel furnace crucibles containing the melted lithium-aluminum targets remaining from the tritium recovery process. To prevent spread of contamination at the disposal site, the entire crucible will be sealed in a stainless steel overpack. These vessels will weigh approximately 2,000 pounds and radiate 7-8 R/hr at three feet. The primary gamma emitter from the crucibles is zinc-65. Oversized D&R waste from process maintenance or modifications will be packed in customized containers.

Wastes will be characterized on the package manifest which will accompany the waste shipment to the disposal facility. Information such as weight, volume, Curie content, major isotopes, and the generating facility will be recorded on the manifest and entered into the disposal facility's computerized database.

MODEL DESCRIPTION

The model used for the ILTV (leaching) performance assessment is the PATHRAE-RAD⁶, a performance assessment code for the land disposal of radioactive waste, developed for the EPA by Rogers and Associates (Salt Lake City, Utah). The code can be used to calculate annual radiological doses to workers during disposal operations, to off-site personnel after site closure, and to reclaimers and inadvertent intruders after site closure. The exposure events (pathways) are described in Appendix A.

The model used for the ILNTV and the LAWV (vapor phase transport) performance assessment is the PORFLOW¹¹ code developed by the Analytical and Computational Research Inc (Los Angeles, CA). The code is a 3-dimensional, finite volume simulator that performs heat and mass transfer calculations in saturated and unsaturated zones. Mass transport by diffusion in the ILNTV and the LAWV is modeled.

MODEL VALIDATION

The PATHRAE code was validated against tritium lysimeter data. The PORFLOW model was verified against an analytical solution. Model validation/verification is described below:

History Match of a Tritium Lysimeter Test

A tritium lysimeter test¹² was initiated at the E-Area when three spent melt crucibles were placed in a lysimeter in mid November, 1973. Leachate sample collection began 11 weeks later on February 1, 1974 and continued weekly for more than 10 years.

The rate of tritium release from the lysimeter test was matched by PATHRAE-RAD⁶. By trial and error, a reasonable match of PATHRAE predictions to the field data was obtained using a source term of 400 Curies and a leach rate of 0.3 yr^{-1} (Figure 4). This results in an effective partition coefficient $k_d = 1.45 \text{ cm}^3/\text{g}$ on the waste form (crucibles) which corresponds to a retardation factor of 12.6. The retardation is dependent on the waste form and not on adsorption. The tritium lysimeter test and the history match are described in greater detail in Appendix B.

Verification of the PORFLOW Code

An analytical solution of molecular diffusion was used to verify the PORFLOW model. The problem used for the verification is tritium diffusion in polyethylene bags. The surface area of the bags is $2.67 \times 10^9 \text{ cm}^2$. The volume of the bags is $2.18 \times 10^{10} \text{ cm}^3$. The thickness is 0.03048 cm. The diffusivity is $3.47 \times 10^{-10} \text{ cm}^2/\text{sec}$. These numbers were used for all the bags in a LAWV.

It was also assumed that 1.0 Curie of tritium was in the bags initially and tritium was replenished so that the source term remained at 1.0 Curie. Tritium concentration outside the bags was assumed to be zero all the time. Decay was neglected. Tritium flux in Ci/yr calculated by an analytical solution¹³ is compared to the PORFLOW prediction in Figure 5. The PORFLOW prediction is in good agreement with the analytical solution. Details of the diffusion model verification and LAWV performance prediction are described in Appendix C.

PERFORMANCE ASSESSMENT

The Tritium Pathways

The PATHRAE-RAD code was used to predict the tritium doses resulting from Trench Burial of 100,000 Curies of tritium wastes via the following pathways:

1. Groundwater migration with discharge to a river,
2. Groundwater migration with discharge to a well,
3. Food grown on the waste site,
4. Biointrusion into the waste,
5. Inhalation of radioactive dust onsite, and
6. Inhalation of radioactive particles offsite.

The purpose of this modeling effort was to screen out the pathways with least hazardous potential. Other pathways of surface erosion, bathtub effect, direct gamma exposure and inhalation of radon gas, were not included because they were considered to have minimal impact. Peak doses and peak times are summarized in Table 1. Key input data to PATHRAE are described in Appendix D.

TABLE 1. RESULTS OF TRENCH BURIAL PATHWAY PREDICTIONS

PATHWAY	PEAK DOSE (mrem/yr)	PEAK TIME (year)
Groundwater to river at 750 m	1.1×10^{-3}	29.0
Groundwater to well at 1.0 m	6.5×10^{-4}	5.3
Food grown onsite	0.	
Biointrusion	0.	
Dust inhalation onsite	2.0×10^{-5}	0.
Atmospheric transport offsite	9.4×10^{-2}	0.

Except for groundwater to well at 1.0 m (facility boundary), predicted peak doses for other pathways are all much lower than the 25 mrem/yr requirement. These results indicate that groundwater protection is the primary concern for tritium waste disposal. The following analysis will focus on groundwater ingestion pathway at the one meter well only.

Disposal Scenarios

The rate of tritium release to the groundwater is dependent on the initial inventory, the design of the disposal facility, and the operational alternatives. The inventory used for the ILTV performance assessment is 100,000 Curies. This is approximately two years worth of tritium wastes⁹. Looking from another angle, an ILTV will be used to store 142 tritium crucibles. The tritium inventory for each of the crucibles is 200 to 400 Ci. WMT assumes it to be 500 Ci¹⁴ for conservatism. The forecasted inventory for an ILTV is about 71,000 Ci for the crucibles and 29,000 Ci for the rest of the wastes totaling 100,000 Ci. Three disposal scenarios were modeled:

1. **Trench Burial.** For this scenario, 100,000 Curies of crucibles are buried in an earthen trench. The size of the trench is the same as an ILTV (56.5 ft long, 48.5 ft wide, 28.5 ft deep). There is no closure cap. Annual infiltration is 38 cm.

2. **Perched Water Intrusion.** For this scenario⁹, 100,000 Curies of tritium wastes are assumed to be disposed in a concrete vault. However, it is assumed that perched water intrudes the bottom two feet of the vault annually. Perched water intrusion may result from a poorly designed vault or a poorly placed vault. Perched water may come from either the vertical or the horizontal direction.
3. **100 Year Storage.** For this scenario, the model assumed that 1) 100,000 Curies of tritium wastes are stored in an ILTV. 2) A 96.4% closure cap¹⁵ reduces the infiltration to 1.36 cm/yr. 3) A 100-yr storage period will be implemented. During this period, any leachate will be extracted, the ILTV will be vented, and the performance of the vault will be carefully monitored. 4) After 100 years, the ILTV is no longer in place (i.e., trench burial) but the cap is still in place.

The assumption of complete vault degradation after 100 years is conservative. The purpose of this assumption is to demonstrate that even if it occurred, the operators can still shut down and walk away from the facility after 100 years.

Figure 6 shows the time dependence of predicted doses for the three disposal scenarios. Predicted peak dose for Trench Burial is 65,000 mrem/yr. This means trench disposal of tritium wastes will not meet the 4 mrem/yr Drinking Water Standard. Predicted peak dose for the perched water intrusion is 4,000 mrem/yr. Water intrusion through the cracks in the bottom slab may also result in unsatisfactory vault performance.

Predicted peak dose for the 100 Year Storage is approximately 1 mrem/yr compared to the 4 mrem/yr EPA Drinking Water Standard. This means the inventory limit for an ILTV can be increased to four times the inventory used for the prediction. Therefore, the inventory limit is 400,000 Curies.

Vapor Phase Transport

We have indicated that an ILTV can be used to store 400,000 Curies of tritium wastes. We anticipate leaching in the LAWV and the ILNTV to be no problem because 1) the tritium inventory in a LAWV or an ILNTV is much lower than that of an ILTV, 2) the size of a LAWV (643.3' x 145' x 25') or an ILNTV (189' x 48' x 29') is larger than the ILTV (56' x 48' x 29') which means lower source term concentration, 3) The LAWV and the ILNTV have similar design features as the ILTV.

An operational alternative for the LAWV and the ILNTV is to seal the riser pipes with grout some time after site closure. This alternative will reduce the operating cost. However, it would also cut down the breathing power of the vault. As a result, the tritium in the wastes may migrate to the groundwater by vapor phase diffusion.

The waste forms expected to contain tritium in the LAWV and the ILNTV are mainly job control wastes. Tritium is assumed to be in the form of HTO and contained in polyethylene or PVC bags within a cardboard box and a B-25 Box. HTO would diffuse from the high concentration source (in the bag) through the bag wall into the void space in the vault and then through the vault wall into the soil. HTO in the soil would then be carried by infiltrating water to the groundwater.

Groundwater contamination resulting from wastes disposed in a LAWV through the vapor phase transport is sensitive to (1) the initial inventory, (2) the HTO diffusivity through the bag, (3) the amount of water in the bags, and (4) the vault wall thickness. Water in the bags and the vault wall will lower the HTO vapor pressure¹⁶. The inventory used for the calculation is 1,000 Curies per vault. The diffusivity is estimated to be 3.47×10^{-10} cm²/sec¹⁷⁻¹⁸. The thickness of side walls for a LAWV is two feet. Figure 7 shows the predicted groundwater concentrations at three different water contents.

A potential source for HTO in the job control wastes is reactor moderator water. Tritium concentration in moderator water is about 13 to 15 Ci/L¹⁹. The volume of moderator water containing 1000 Ci of tritium is 67,000 cm³ compared to the LAWV volume of 2.18x10¹⁰ cm³. The weight percent of moderator water in the LAWV is approximately 0.0003. This means we should use the top curve in Figure 7 for inventory limit estimation.

The peak groundwater concentration for the No Water In Bags case in Figure 7 is approximately 6.0 pCi/mL. This was based on a source term of 1,000 Curies of tritium. The tritium inventory limit for a LAWV is the source term resulting in a peak concentration of 90 pCi/mL, which is 15,000 Curies.

The dimensions of ILNTV was used in another PORFLOW input dataset to predict the groundwater impact of vapor phase diffusion. The source term was assumed to be 1,000 Curies of tritium. It was also assumed that there was no water in the bags. Predicted peak concentration was 8.2 pCi/mL. The tritium inventory limit for an ILNTV is approximately 11,000 Curies.

TRITIUM VAULT DESIGN

A schematic of the ILTV is shown in Figure 8. The vault is subdivided into two cells and provides for approximately 1,330 cubic meters of waste storage/disposal capacity. One cell will be operated as an open cell for various waste forms and the other will contain a system of silos each capable of supporting a single crucible contained in an overpack in the upright position.

The cast-in-place concrete will be "Strength Design" with 4,000 psi 90-day strength in accordance with American Concrete Institute specifications. The mix will include Portland cement, blast furnace slag, fly ash, 1.9 cm (3/4 in.) aggregate, and superplasticizer. Control joints will be provided at approximately 8 m (26 ft) intervals. Special measures will be made to reduce concrete cracking which include casting full height of wall in a single lift, cooling concrete to 15°C (60°F) by liquid nitrogen before placement, and applying curing compound to wall surfaces to prevent premature drying.

All interior vault cell walls will be lined with a drainage net comprised of a polystyrene spacer mat (against the concrete wall face) and a woven geotextile fabric. The bottom slab of the ILTV is at least 0.76-m (2.5-ft) thick and will be sloped. Two crushed stone drainage layers separated by a single ply geotextile fabric will fill the bottom 0.36 m (14 in.) of the ILTV. An internal leachate collection system comprised of drainage piping, sumps, and riser pipes will remove excess water from within the tritium vault.

A subdrainage system consisting of a 14-inch crushed stone layer with non-woven geotextile fabric beneath, sloped bottom, and perforated drain pipe will be constructed. This system will prevent bottom water accumulation.

Each cell has a removable raincover with gutters and sloped top to remove excess water during the 20-year operation period. A permanent concrete roof designed to support 2.4 m (8 ft) of earth cover will be constructed during final closure. Concrete crane runways adjacent to the vault sidewalls are designed for the wheel loads imposed by the 75-ton gantry crane.

The tritium crucibles overpacked by stainless steel sleeves will be placed within the silo system. A total of 142 silos will be provided in a single cell. The silos are 20 inches (51 cm) in diameter with upper section enlarged to 0.61 m (24 in) diameter to accommodate a concrete shielding plug.

The disposal site will be covered by a multi-layer cap to reduce water infiltration after closure. Details of the cap design have not been determined, awaiting additional site-specific tests and modeling results.

QUALITY ASSURANCE

The models used for this study have been used extensively by the defense and commercial industries. They have been validated against the site specific data and analytical solutions.

DISCUSSIONS

It has been more than 35 years since the first disposal of tritium waste at the SRS. There is also an active environmental monitoring program for tritium migration. With approximately 3,000,000 Curies of tritium disposed onsite²⁰ so far, there has been no health or environmental safety hazards to onsite workers and offsite populations. This is in good agreement with our performance assessment results of insignificant doses via river, food, dust, and atmospheric pathways.

The tritium lysimeter data was used to calibrate the leach rate and a distribution coefficient of $1.45 \text{ cm}^3/\text{g}$ was obtained. This only applies to the waste form (crucibles) and not to the soil in either the vadose zone or the aquifer. The history match provides a tool for model validation.

Predicted peak groundwater concentration for Trench Burial is 1,000,000 pCi/mL. This is in good agreement with the groundwater monitoring data taken at the Old Burial Ground. Although some of the samples show slightly higher concentrations, this is expected because the monitoring wells are drilled through the waste site and screens are set right at the water table. The model results were computed for a point at the facility boundary and in the shallow aquifer where complete mixing of infiltration water and groundwater was assumed.

There is overwhelming evidence that trench burial of the tritium wastes will not be acceptable. Concrete vaults present a solution that is both technically sound and cost effective. The ILTV will 1) separate waste from soil, 2) prevent a future inadvertent intruder, and 3) facilitate institutional control.

SRS is a humid site. It is necessary to build an engineered cap to reduce infiltration. Additionally, special care must be taken to prevent perched water intrusion in the disposal units. The leachate collection system and the drainage system are designed to serve this purpose. During the 100 year storage period, leachate will be extracted and analyzed. This will give us a very dependable method to monitor the vault performance. With these monitoring data, one can decide if the time for storage could be shortened or should be extended.

The ILTV must be vented because of vapor phase transport. Vapor phase transport for the LAWV and the ILNTV peaks at 10 years. Most of the HTO will be vaporized after the 20-year operational period. Vapor transport mechanism is sensitive to the diffusivity in bags. If the diffusivity is much lower than the 3.47×10^{-10} cm²/sec used in this study, tritium release would be lower and slower. If the diffusivity is much higher, tritium release would be higher and faster. This means most of the tritium would be vaporized in less than 10 years. In either of the above cases, vapor phase transport should not present problems to the groundwater.

RESULTS

1. The impact of tritium disposal on river, food, dust, and atmospheric pathways is insignificant compared to the groundwater pathway at the facility boundary.
2. Trench burial of the tritium wastes is unacceptable. In the 1990's, SRS tritium wastes will be disposed/stored in concrete vaults.
3. Approximately 100,000 Curies of tritium wastes produced in two years will fill one ILTV. Most of the radioactivity comes from spent melt crucibles.
4. The ILTV will be equipped with a leachate collection system and a subdrainage to prevent perched water intrusion. The vault will also be vented and covered with a cap consisting of clay and gravel layers. The tritium crucibles in stainless steel overpack will be arranged in a silo system. There will be a storage period of 100 years.
5. The ILNTV and the LAWV have similar design features as the ILTV to prevent perched water intrusion. They will also be capped. However, they need not be vented after closure.
6. The tritium inventory limits for an ILTV, an ILNTV, and a LAWV are 400,000, 11,000, and 15,000 Curies, respectively.
7. With the above design and operational alternatives, the E-Area Vaults will meet all DOE Order 5820.2A performance objectives.

REFERENCES

1. E. G. Orebaugh and R. M. Wallace, "Quantification of Hazards Associated with the Decay Storage/Disposal of Tritium Crucibles (U)," WSRC-RP-89-1226, October 13, 1989.
2. J. R. Cook, "Interim Disposal Limits for E Area Vaults (U)," WSRC-RP-91-787, August 2, 1991.
3. U.S. Department of Energy, "Radioactive Waste Management," Order DOE 5820.2A, September 26, 1988.
4. U.S. Department of Energy, "Comprehensive Environment Response, Compensation, and Liability Act Requirements," Order DOE 5400.4, October 6, 1989.
5. U.S. Environmental Protection Agency, "National Interim Primary Drinking Water Regulations," EPA-570/9-76-003.
6. G. B. Merrell, V. C. Rogers, and M. K. Bollenbacher, "The PA-THRAE-RAD Performance Assessment Code For The Land Disposal Of Radioactive Wastes," Rogers and Associates Engineering Corporation, Salt Lake City, Utah, August, 1986.
7. International Commission on Radiological Protection (ICRP), "Limits for Intakes of Radionuclides by Workers," ICRP Publication 30, Part 1 (and subsequent parts and supplements), Vol. 2, No. 3/4 through Vol. 8, No. 4, Pergamon Press, New York, 1979-1983.
8. "Project S2889, Burial Ground Expansion, Intermediate Level Tritium Vault, Intermediate Level Non-Tritium Vault, and Long Lived Waste Building, Formal Design Review Board," December 17, 1990.
9. A. D. Yu, J. R. Cook, "Optimization of the Low-Level Tritium Vault Design (U)," WSRC-TR-90-88, February 6, 1990.
10. J. R. Cook, M. W. Grant, and O. A. Towler, "Environmental Information Document, New Low-Level Radioactive Waste Storage/Disposal Facilities at the Savannah River Plant," DPST-85-862, April 1987.

11. Akshai K. Runchal and Budhi Sagar, "PORFLOW, A Model for Fluid Flow, Heat and Mass Transport in Multiphase Fractured or Porous Media," User Manual, Version 2.34, Analytical and Computational Research Inc., June 3, 1991.
12. M. W. Grant and R. H. Hawkins, " Results of the Spent Melt Lysimeter Experiment," DPST-85-384, Sept. 30, 1985.
13. J. R. Cook, "Analysis of Tritium Release from Storage/Disposal Vaults (U)," WSRC-RP-89-918, Sept. 19, 1989.
14. J. M. Wallace, private communication, October, 1991.
15. J. R. Cook, "Performance Assessments of Closure Cap Alternatives at the Savannah River Plant", DP-MS-88-47, presented at the Tenth Annual DOE Low-Level Radioactive Waste Management Conference, Denver, Colorado, August 29 - September 1, 1988.
16. J. H. Horton, J. C. Corey, and R. M. Wallace, "Tritium Loss From Water Exposed to the Atmosphere," Environmental Science and Technology, Vol. 5, No. 4, April 1971, pp. 338-343.
17. H. Miyake, M. Matsuyama, K. Ashida, and K. Watanabe, "Permeation, Diffusion, and Solution of Hydrogen Isotopes, Methane, and Inert Gases in/through Tetrafluoroethylene and Polyethylene," J. Vac. Sci. Technol., July-Sept. 1983, p.1447.
18. M. Naumann, W. Blume, and D. Schneider, "Permeability of Polymer Materials to Compounds Containing Radionuclides," J. of Radiological Chem., Vol. 30 (1967) pp. 489-497.
19. D. P. Lambert, private communication, September, 1991.
20. C. E. Murphy, Jr. et. al., "Tritium in the Savannah River Site Environment (U)," WSRC-RP-90-424-1, May, 1990.

Figure 1

Figure 2
The Location of E-Area Vaults

Figure 3
Flow Chart Showing How Solid Wastes Will Be Classified
At The E-Area Disposal Facilities

Figure 4
A History Match of Tritium Lysimeter Data

G91J023.08

Figure 5

COMPARISON OF PORFLOW TO AN ANALYTICAL SOLUTION
DIFFUSION THROUGH 12-MIL BAGS

Figure 6
Predicted Groundwater Tritium Doses and
Concentrations at the One-Meter Well
(Initial Inventory = 100,000 Ci)

G91J023 06

Figure 7
Groundwater Tritium Concentrations Impacted by Vapor Phase Diffusion
(Initial Inventory = 1,000 Curies)

Figure 8
A Schematic of the Tritium Vault

APPENDIX A

PATHRAE-RAD EXPOSURE EVENTS

The PATHRAE-RAD code allows a wide range of generic and site specific nuclear waste disposal analysis. Up to ten exposure events (pathways) by which radioactivity may reach humans can be considered. These pathway scenarios are:

1. Groundwater migration with discharge to a river. This is an advection pathway. A waste component is leached by percolating precipitation, moves downward through the unsaturated zone, flows to an aquifer and discharges into a river.
2. Groundwater migration with discharge to a well. Same as above, except that the contaminated aquifer water is withdrawn from a well.
3. Surface erosion of the cover material and waste and subsequent contamination of surface water. An erosion rate (m/yr) is specified. Erosion starts with the cover over the disposed waste and then operates on the waste materials. The contaminants are removed to a surface stream where doses are calculated.
4. Saturation of waste and facility overflow (bathtub effect). This pathway calculates the doses when a waste site becomes saturated with water and the contaminated water subsequently overflows the waste trench and enters a stream.
5. Food grown on the waste site. This pathway describes the consumption of food grown on reclaimed farm land and accounts for potential exposure of individuals to waste materials through the human food chain (crops, milk, meat). Excavation of the waste materials is assumed.
6. Biointrusion into the waste. This pathway is similar to the Food pathway described above, but involves the consumption of crops whose roots have penetrated into otherwise undisturbed waste materials.

7. Direct gamma exposure. This exposure pathway calculates the external radiation dose to an individual standing directly over a waste site. The cover material over the waste is allowed to erode at a specified rate so the degree of shielding provided by the cover may decrease in time.
8. Inhalation of radioactive dust on-site. This pathway traces the effects of inhaling contaminated dust that is suspended during the excavation of a basement or well by an intruder some time after site closure.
9. Inhalation of radon gas and radon daughters on-site. This pathway calculates the effects on an intruder of inhaling radon and radon daughters while inside a structure built over the waste.
10. Inhalation of radioactive particulates off-site (from an on-site incinerator, trench fire, or dust resuspension). This pathway uses a Gaussian plume technique to trace the effects of site derived airborne contaminants on a representative off-site population.

APPENDIX B
A LYSIMETER TEST AND ITS HISTORY MATCH

A tritium lysimeter test¹² was initiated at the E-Area when three spent melt crucibles were placed in a lysimeter in mid November, 1973. Leachate sample collection began 11 weeks later on February 1, 1974 and continued weekly for more than 10 years.

Figure B-1 shows the schematic of the tritium lysimeter. The lysimeter tank was buried approximately 10 ft. below grade and was 10 ft. in diameter. The crucibles were 34 inches long, 30 inches OD (the newer crucible design is longer and more narrow) and contained spent Li-Al melts. The tritium content in each of the crucibles was between 100 and 150 Curies. One of the lysimeter lids was intentionally left open to allow fast release of tritium. The top of the crucibles was about 5 ft. below grade.

The bottom of the lysimeter was sloped and filled with a layer of gravel. Leachate collected was pumped to the surface. The volumes of the leachate and tritium concentrations were measured weekly. Table B-1 summarizes the cumulative volume (L) and tritium release (Ci). The tritium release was not corrected for decay.

TABLE B-1. TRITIUM LYSIMETER DATA

YEAR	CUMULATIVE PERCOLATE VOLUME (Liters)	CUMULATIVE TRITIUM RELEASE (Curies)
0	0	0.00
1	2,863	80.38
2	8,851	192.89
3	13,443	237.61
4	18,382	263.47
5	22,833	280.37
6	28,637	293.65
7	33,057	300.87
8	36,563	304.02
9	42,660	315.79
10	47,433	334.90

A total of 47,433 liters of percolate water was collected in 10 years from a surface area of 78.5 ft² (7.3 m²). This corresponded to an average infiltration rate of 0.65 m/yr. Cumulative tritium (HTO) release was 334.9 Ci. Approximately one percent of tritium (HT and HTO vapor) was released to the atmosphere.

The rate of tritium release from the lysimeter test was matched by PATHRAE-RAD. Because the sump was located only 2 ft. under the crucibles, tritium transport through the vadose zone was fast (10 weeks). As a result, the dominant mechanism for tritium release was the leaching process affected by the infiltration rate, inventory, and leach rate. Leach rate is the fraction of the source term leached per year and is a term used by the PATHRAE code.

By trial and error, a reasonable match of PATHRAE predictions to the field data was obtained using a source term of 400 Curies and a leach rate of 0.3 yr⁻¹. The history match is depicted in Figure 4. An equation used to calculate leach rate from a shallow land burial is:

$$L = \frac{V_{in}/\phi}{Y(1+\delta_b K_d/\phi)} \quad (B-1)$$

where

- L = leach rate (0.3 yr⁻¹),
- V_{in} = infiltration rate (0.65 m/yr),
- φ = effective porosity (0.2),
- Y = thickness of waste layer (0.86 m),
- δ_b = bulk density (1.6 g/cm³), and
- K_d = partition coefficient on waste surface (cm³/g).

Substituting the given parameter values into equation (1), we obtain K_d = 1.45 cm³/g. This is the tritium effective partition coefficient on the waste form (crucibles) which results in a retardation factor of 12.6.

Figure B-1
Spent Melt Lysimeter

APPENDIX C

VAPOR PHASE DIFFUSION MODELING

A two-dimensional numerical model was developed to simulate vapor phase diffusion of HTO in a LAWV using the PORFLOW code. The assumptions and input data to the model are described below:

Physical Dimensions

A LAWV is 643.3 ft long, 145 ft wide and 25 ft deep. It is assumed that 15,408 B-25 Boxes (6'x4'x4') are disposed in a LAWV stacking four layers high. A B-25 Box contains 12 cardboard boxes (21"x21"x21"). Each of the cardboard boxes contains one 12-mil polyethylene bag. Thus, there are 184,896 bags in a LAWV.

It is assumed that the bag dimension is 20"x20"x18". The volume of a bag is 7,200 in³ or 1.18x10⁵ cm³. The surface area of a bag is 2,240 in² or 1.445x10⁴ cm². On a per LAWV basis, these are the dimensions of the LAWV and bags:

	<u>LAWV</u>	<u>Bags</u>
Volume (cm ³)	6.6x10 ¹⁰	2.2x10 ¹⁰
Surface Area (cm ²)	2.1x10 ⁸	2.7x10 ⁹

The thickness of the polyethylene bags is 12 mils or 0.03048 cm. The thickness of the vault wall is approximately 61 cm (2 ft).

Initial Inventory

The wastes in a LAWV contains only incidental quantities of tritium. There is no established tritium inventory for this class of wastes. The initial inventory used for the modeling is assumed to be 1,000 Curies per vault. The tritium inventory limit is calculated by:

$$I = I_0 \times \frac{4 \text{ mrem/yr}}{D_0}$$

where

I = Tritium inventory limit in Curies

I_0 = Initial tritium inventory used for the prediction, Ci

D_0 = Predict peak dose in mrem/yr

Because I_0/D_0 is a constant, the tritium inventory limit is independent of the choice of I_0 .

HTO Diffusivities

Naumann, Blume, and Schneider [Ref. 17] measured the diffusivity of HTO in polyethylene (PE) bags to be 32.5×10^{-9} cm²/hr, or 9.14×10^{-12} cm²/sec. A similar measurement by Miyake et. al. [Ref. 16] showed the H₂ diffusivity in PE to be 4.74×10^{-7} cm²/sec.

The above diffusivities are tested for HTO and H₂ in a PE membrane. Previous Gas Generation Test results [Paul Drez, IT Corporation, Albuquerque, NM, WIP:8902-TEST/2] indicated that the diffusion of H₂ in PE waste bags is 1.8×10^{-5} cm²/sec. This two-orders of magnitude increase in diffusivity is attributed to the "twist and tape" procedure used to seal the bags. It was assumed that the "horse tail" provided a convenient path for H₂ diffusion.

The HTO diffusion coefficient in waste bags is obtained by multiplying 3.14×10^{-12} by a factor of $1.8 \times 10^{-5} / 4.74 \times 10^{-7}$. The resulting value is 3.47×10^{-10} cm²/sec. This value is one of the controlling factors for vapor phase diffusion in a LAWV.

HTO diffusion through the cardboard boxes and B-25 boxes used for the waste package is assumed to be very fast. The HTO diffusivity in concrete vaults is approximately 1.0×10^{-3} cm²/sec [Elmer Wilhite, DPST-88-235, 1/18/88].

Retardation By Water

It was assumed that the LAWV was kept at a constant temperature of 25°C. At this temperature, the vapor pressure for water is 23.756 mm Hg or 3.13×10^{-2} atm [CRC Handbook]. The liquid-vapor equilibria of HTO-H₂O system is represented by the Raout's law [Horton, Corey, and Wallace, Ref. 15]:

$$y_i = x_i P_{vpi}$$

where

y_i = mole fraction of component i in the vapor phase
 x_i = mole fraction of component i in the liquid phase
 P_{vpi} = vapor pressure of component i .

The PORFLOW code does not have a vapor-liquid equilibrium correlation. Vapor-liquid equilibrium is approximated by the use of a partition coefficient (K_d). It was assumed that the vapor phase is the mobile phase, with diffusion only. The liquid phase is the immobile phase. The following calculations illustrate how a K_d value is obtained to represent vapor-liquid equilibrium in the concrete walls:

It is assumed that the porosity of the concrete is 0.15, the residual water saturation is 0.1, and the bulk density of concrete is 2.4 g/cm^3 . The air volume in 1 cm^3 of concrete is $0.15 \times 0.9 = 0.135 \text{ cm}^3$, and the volume of the immobile phase is 0.865 cm^3 which has a weight of 2.1 grams.

The partial pressure of H_2O in air is $3.126 \times 10^{-2} \text{ atm}$. At 25°C (298°K), the weight of 0.135 cm^3 water vapor is $3.1 \times 10^{-6} \text{ gram}$. The partition coefficient (K_d) is calculated by:

$$K_d = \frac{0.015/2.1}{3.1 \times 10^{-6}/0.135} = 311 \text{ cm}^3/\text{g}$$

This partition coefficient is used to model the retardation of HTO diffusion in concrete.

The amount of HTO in the vapor phase within the PE bags is also dependent on the water contents. A conservative assumption is that all of the water comes from the reactor moderator water. 1,000 Curies of reactor moderator water occupies only $67,000 \text{ cm}^3$ of volume compared to the LAWV volume of $2.18 \times 10^{10} \text{ cm}^3$, or 0.0003 weight percent. As a result, it was assumed that there was no retardation for HTO in the bags ($K_d = 0$).

Model Description

A 25x5 grid was used to simulate the vapor phase diffusion through the bags and the concrete wall. In the x-axis, nodes 1-8 represented the air space in the bag. Nodes 9-13 represented 0.03048 cm of PE bag wall. Nodes 14-20 represented the vault void space. Nodes 21-25 represented the concrete wall. Because the PE bag wall is discretized at 0.006096 cm per grid, the adjacent air spaces are also discretized with comparable grid sizes to minimize numerical dispersion. The y-axis was discretized so that the areas of the bags and the concrete walls are properly represented.

The initial tritium concentration in the bags is 4.587×10^{-8} Ci/cm³. Boundary conditions of no concentration gradient at the center of the bag and zero tritium concentration at the exterior concrete wall were assumed.

Model Verification

A partial model including X-direction grids 1-13 was used to simulate tritium diffusion through the bags. The tritium content in the bags was assumed to remain at 1 Ci. The tritium concentration at the exterior bag wall was set to zero as a boundary condition. The predicted tritium flux is in good agreement with an analytical solution as shown in Figure 5. The model is therefore verified for the following performance predictions.

Modeling Results

The model was executed with a diminishing source term. Tritium concentration gradient through the vault wall peaked at 0.09 pCi/cm³/cm in about 10 years. The corresponding peak tritium flux is 1.8×10^{12} pCi/yr.

Because tritium concentration peaked at 10 years which is less than the 20 year operation period, the infiltration rate is assumed to be 38 cm/year. The depth of the vadose zone is assumed to be 20 ft (6100 cm). Assuming the soil effective porosity is 0.2, the travel time in the vadose zone is $6100 \times 0.2 / 38 = 32$ years. In this time period, 1.8×10^{12} pCi/yr of tritium decays to 1.4×10^{11} pCi/yr.

Recharge to the aquifer is diluted by groundwater. The groundwater velocity at the E-Area is 3500 cm/yr. Thickness of the shallow aquifer is about 50 ft (1500 cm). The smaller dimension of the LAWV is 145 ft (4420 cm). The peak tritium concentration in the aquifer is $1.4 \times 10^{11} / (3500 \times 1500 \times 4420) = 6.0$ pCi/ml. This is the predicted peak tritium concentration in the shallow aquifer.

APPENDIX D
PATHRAE INPUT DATA

Site specific data used for PATHRAE predictions are:

Length of repository (m)	17.2
Width of repository (m)	14.8
River flow rate (m ³ /yr)	9.1x10 ⁹
Stream flow rate (m ³ /yr)	1.7x10 ⁸
Distance to river (m)	750.
Density of aquifer (kg/m ³)	1600.
Longitudinal dispersivity (m)	38.
Lateral dispersion coefficient	0.
Cover thickness over waste (m)	4.88
Thickness of waste in pits (m)	8.7
Total waste volume (m ³)	2210.
Distance to well	1., 100.
Density of waste (kg/m ³)	1600.
Fraction of food consumed that is grown on site	0.5
Fraction of year spent in direct radiation field	1.
Depth of plant root zone (m)	1.
Areal density of plants (kg/m ²)	1.
Average dust loading in air (kg/m ³)	1.x10 ⁻⁷
Annual adult breathing rate (m ³ /yr)	8000.
Fraction of year exposed to dust	0.25
Canister lifetime (years):	
Trench Burial	0.
Perched Water Intrusion	20.
100 Year Storage	100.

Height of rooms in reclaimer house (cm)	240.
Air change rate in reclaimer house (changes/sec)	0.00056
Thickness of concrete slab floor (cm)	20.
Atmospheric stability class	4
Average wind speed (m/s)	3.
Fraction of time wind blows toward receptor	1.
Receptor distance for atmospheric pathway (m)	500.
Dust resuspension rate for offsite transport (m ³ /s)	1.x10 ⁻⁷
Deposition velocity (m/s)	0.01
Amount of water percolating through waste annually (m)	
Trench Burial	0.38
Perched Water Intrusion	0.12
100 Year Storage	0.0137
Degree of soil saturation	0.426
Residual soil saturation	0.1
Permeability of vertical zone (m/yr)	2.2
Soil number	0.25
Porosity of aquifer	0.20
Porosity of unsaturated zone	0.20
Distance from aquifer to waste (m)	13.
Average vertical groundwater velocity (m/yr)	0.45
Horizontal velocity of aquifer (m/yr)	35.
Length of perforated well casing (m)	10.
Surface erosion rate (m/yr)	2.x10 ⁻⁴
Annual runoff of precipitation (m)	1.0
Leach constant (yr ⁻¹)	
Trench Burial	0.017
Perched Water Intrusion	0.078
100 Year Storage	0.0006

Tritium

Ingestion dose factors (mrem/pCi)	6.3×10^{-8}
Inhalation dose factor (mrem/pCi)	9.5×10^{-8}
Direct gamma dose factor (mrem/pCi)	0.
Aquifer sorption (cm^3/g)	$1. \times 10^{-3}$
Vertical sorption (cm^3/g)	$1. \times 10^{-3}$
Half life (yr)	12.3

Inventory (Ci)

Trench Burial	100000.
Perched Water Intrusion (2 ft of waste)	7000.
100 Year Storage	100000.

END

**DATE
FILMED**

10 / 20 / 92