AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

NEW INFRARED
PHOTON ABSORPTION PROCESSES

Final Technical Progress Report
for Period August 1, 1988 - February 1, 1993

J. E. Bayfield

University of Pittsburgh
Pittsburgh, Pennsylvania 15260

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed or represents that its use would not infringe privately-owned rights.

May 1993

Prepared for

THE U. S. DEPARTMENT OF ENERGY
AGREEMENT NO. FG02-88ER13960

RECEIVED
JUL 02 1993
OSTI

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

The fast ionization of atoms by very short laser pulses, and its possible suppression at extreme pulse intensities, is an active new field of investigation at present. Described is an investigation of whether past techniques for infrared laser multiphoton ionization of excited hydrogen atoms and of one-dimensional microwave ionization of highly excited hydrogen atoms can be combined and extended to address the new issues. Although technically difficult and requiring further improvement of apparatus, intense-field infrared laser experiments on excited hydrogen atoms are possible and can directly test theoretical and numerical results.

I. Motivation for the Research.

We describe an apparatus for the short-pulse one-dimensional laser ionization of excited hydrogen atoms. During the contract period, motivation for this type of experiment has increased, as theoretical and numerical studies have indicated that ionization may be suppressed and atomic states stabilized when the laser pulses are short enough and intense enough (1-4). Many of these studies are based upon one-dimensional theoretical models and/or upon the explicit assumption that the atom is the simplest one, hydrogen. Others of these studies require that the atom have high electronic angular momentum, which is achievable (5,6). However, none of the theoretical and numerical work has been directly tested in the laboratory.

II. Activities over the Entire Grant Period.

Our experimental approach has been to extend our past hydrogen atom beam techniques (7) to produce extremal Stark-state atoms ("one-dimensional" or "stretched" atoms) (8) with the principal quantum number adjustable from 4 to 30. The challenge has been to produce enough of these atoms to make high intensity laser photoionization experiments possible at the low duty

cycles (typically a part per billion light-on time) at which these lasers operate. At the same time, other non-stretched atoms in the atom beam are not to contribute excessive background signals.

We chose an unproven approach, which was to

1) Start with the metastable 2s state hydrogen atoms in our fast atomic beam (9,7), which are relatively copious with percentages of 0.1% to 1% depending on atom beam energy and charge exchange gas type.

2) Rapidly switch on a static electric field of about 80 Volt/cm, to Stark-split the hydrogen atom energy level manifolds, and then quickly induce the 2s to $(n, n1, m) = (n, 0, 0)$ transition with a resonant nanosecond pulse UV dye laser, all within the 100 nsec time interval before static field quenching of the 2s atoms has become too developed.

3) Before the $(n, 0, 0)$ atoms have moved much further through the apparatus, an intense short-pulse carbon dioxide infrared laser system is fired to photoionize these atoms, which is the nonperturbative "multiphoton" process to be studied. Other excited atoms in the beam will also be photoionized, producing a "background" ion signal that must be measured using shots with the dye laser beam off, and then subtracted from the ion signal with the dye laser beam on. The number of these other excited atoms that become involved varies with the infrared laser intensity, but should never exceed the number of 2s atoms.

4) Other sources of "background" ions must be kept weak enough for the desired ion signal due to the intense infrared laser beam to be measured with a reasonable number of laser shots.

5) Since the entire dye laser excitation and infrared laser photoionization must occur within a 100 nsec time interval, jitter in laser pulse timing and static field switching must be kept low enough and/or timing information must be recorded for each laser shot in order to select out good shots.

Our activities have been directed towards demonstrating the feasibility of the above approach, with the hope of then carrying out detailed intense laser field photoionization experiments. we have worked with a total level of funding of \$360,000 for the 4.3 year period, with much of this support going towards equipment essential for the approach, namely

a) a bakeable ultrahigh vacuum chamber for the laser-atom interaction region, containing large static field plates and having appropriate laser beam entrance and exit windows;

b) an excimer-pumped dye laser and the associated optics for exciting the 2s to (n, 0, 0) transition;

c) laser-beam pulse energy meters;

d) a CAMAC data acquisition system controlled by a personal computer;

e) a fast transient digitizer controlled by a second, dedicated computer capable of handling the data throughput. This digitizer is for shot-by-shot acquisition of light pulse timing information;

f) modifications of our carbon dioxide laser oscillator-amplifier system to obtain single-longitudinal mode, 1 Joule pulses of duration less than one nsec.

A schematic diagram of the apparatus is shown in Figure 1. The heart of the experiment is the fast atomic beam apparatus, consisting first of the deuterium ion accelerator, various ion beam steering and focusing electrodes (not shown) and two pairs of electrodes connected to a fast high voltage pulser to gate the deuterium ion beam on for 400 nsec by transverse deflection. Deuterium was chosen rather than hydrogen to get a lower ion velocity, essential for the experiment to follow after the infrared laser system electrical noise had decayed. Deuterons were separated out from molecular ions by Magnet 1 and passed through more ion beam steering electrodes (not shown) on through a differentially pumped charge transfer gas cell region. Searches for diatomic hydrogen ions based on their collisional dissociation in the gas cell region to produce protons demonstrated that the deuteron beam was pure to within a few percent. The beam emerging from the gas cell region was partially deuterons, partially negative ions, and partially neutral deuteron atoms with a distribution of different electronic energy states. The ions were gently deflected off the neutral beam axis by a pair of Ion Removal parallel electrostatic field

Figure 1. Schematic diagram of the experimental apparatus for intense infrared nonperturbative multiphoton ionization of fast excited deuterium atoms.

plates; the ions were stopped by an aperture in front of Magnet 2 and could be monitored by a collection plate in front of that aperture. In the interaction region in front of Magnet 2 there were two large horizontal parallel electrostatic field plates for applying the pulsed Stark field for splitting the energy manifolds. The low voltage pulser connected to the Stark plates produced a field switch-on with a rise time less than five nanoseconds and with no pulse ringing. UV light from the excimer-pumped dye laser was collimated, spatially expanded, split by four two inch beam splitters and gently focused in the vertical direction by cylindrical lenses onto the atom beam axis through two six inch diameter windows on the the interaction region vacuum chamber.

After the dye laser beam pulse excited the atoms initially in the 2s state, the one Joule infrared laser pulse was fired axially along the atomic beam axis through a zinc selenide window on the Magnet 2 vacuum chamber. The IR light incident on the window was sampled by a zinc selenide beam splitter and monitored by IR pulse energy meter 1. Part of the IR light passed through the vacuum system and emerged through a zinc selenide window on the Magnet 1 vacuum chamber to be monitored by IR pulse energy meter 2. Shot-by-shot measurements by the two IR pulse energy meters gave values of the IR laser beam transmission through the apparatus, which for bad shots that were misdirected had low values. The UV dye laser pulse was sampled by a UV photodiode, while the IR laser pulse was sampled by a photon drag detector. The two light pulses could be recorded by the transient digitizer, and shots with bad pulse timing could be rejected. The fast deuterons produced by the IR laser pulse were steered by Magnet 2 into a Johnston MMI electron multiplier which produced a 400 nsec pulse input into the fast charge integrating preamplifier. The output of the preamplifier went to a fast analog to digital converter CAMAC

module; the pulse height distribution for a run of shots was routinely monitored and served to establish that the atom beam steering through the apparatus was proper. Typical ions per laser shot were estimated to be around 20, a value that precluded pulse counting individual ions. Computer 1 controlled the apparatus, including firing the two lasers and the voltage pulsers. Thus ions produced with and without either the dye or IR laser light could be measured in a time-localized sequential manner for precision subtraction of the effects of beam intensity drifts and the like.

III. Evaluation of Progress in the Research.

First a collinear laser/atom beams two-photon dye laser excitation technique was studied and discarded in favor of transverse one-photon excitation, see the top portion of Figure 1. For the selected technique, Doppler broadening of the excitation resonance line was minimized by 4 milliradian collimations of both the atom beam and dye laser beam, and Doppler shifts were minimized by alignment of beams to the same level of precision.

A first non-bakeable vacuum chamber for the laser-atom interaction chamber was built and placed into service. An excessively large background gas atom stripping signal was observed that was ultimately determined to be due to trace amounts of large organic molecules within the chamber. Although the gas pressure of these molecules was not observable on an ionization

vacuum gauge, the large number of atoms per molecule was the cause of the excessive stripping. A second bakeable vacuum chamber was built and placed into service. After bakeout, the stripping was reduced to expected values.

Also studied was the efficiency of removal of ions from the atomic beam, including those ions elastically scattered in the charge exchange gas, see Figure 2. The details of this scattering were unknown for the low ion beam energies required for detection of photoionization signal ions to occur after laser discharge noise had sufficiently decayed. Although argon charge exchange gas produces higher metastable 2s atom beam fractions, the increased elastic scattering forced us to use molecular hydrogen gas instead.

A crucial issue for our experiments has been the size of the infrared photoionization signal for those atoms that initially were in the metastable 2s state, as compared with the size of various sources of background ions. The principal sources of background were a) stripping of atoms by residual gas in the vacuum system, which is the ion current in Figure 2 for hydrogen gas and for ion removal voltage above 130 volts; b) residual ions, which is the additional ion current in Figure 2 for the ion removal voltage lowered to 80 volts; and c) infrared photoionization of excited atoms in the beam with n above 10. We have achieved the regime where the sum of the first two backgrounds equals one half the third background.

An upper bound on the ratio of our expected signal to the third background is the ratio of the

Figure 2. Deuterium ion angular distributions determined by varying the ion removal voltage, without charge exchange gas, with hydrogen gas and with argon gas.

electron capture cross section for production of the metastable 2s state, about 0.08 square Angstroms per molecule for deuterium ions on hydrogen gas at 10 keV (9), to the sum of cross sections for capture into states with n above 10, which is about 0.002 square Angstroms per molecule (10). Thus the bound is about 40.

Figure 3 shows results for the signal to background ratio (called "fractional signal") for two experimental runs made some eight months apart. Plotted is the ratio as a function of dye laser wavelength. Nonzero signals due to the dye laser UV light are seen near the wavelength expected for the resonant transition 2s $\rightarrow$ 11p. The wavelength shift between the two runs could easily be due to long term drift in the dye laser calibration. The width of the resonance is about 0.004 nm or about 8 GHz in frequency units. This compares well with the 6 GHz specification for the bandwidth of the dye laser. However, the size of the fractional signals seen in Figure 3 is about 0.04, disappointingly small. We partially ascribe this small number to the following factors:

- 1) 2s atom quenching in the ion removal electric field: x 2 signal loss
- 2) optical decay of the 11p atoms during the time between dye laser and infrared laser pulses:
x 2 loss
- 3) incomplete overlap of the dye laser light with the 400 nsec slug of 2s atoms: x 4 loss

Figure 3. Signal to background ratios as a function of the dye laser wavelength used to excite metastable 2s deuterium atoms in the fast atomic beam to the 11p state at zero Stark electric field.

4) insufficient dye laser light intensity to saturate the 2s to 11p transition: $\times 3$ loss

5) an unexpectedly large n-greater-than-10 background: $\times 4$ loss in signal to background.

A further factor of five remains unexplained. Factors 1), 3) and 4) above were expected, so we were looking for a fractional signal of about one. Factor 2) played a role because the time jitter of our infrared laser system was comparable to the 250 nsec 11p radiative lifetime. Factor 5) was determined from two ratio measurements, the first the ratio of n-greater-than-ten background to gas stripping background by comparing ADC ion rates with the infrared light on and off, and the second the ratio of atom beam and gas stripping ion intensities using DC Faraday cup techniques. The first ratio was 4 , the second one 5000, and the ratio of these ratios was then 0.0008. This last number was expected to be the ratio of the charge exchange cross sections for electron capture into n greater than ten (10) to that into all states (9), which was estimated to be the smaller value 0.0002.

IV. Future prospects.

Improved laser equipment would remove factors 2), 3) and 4) above, increasing the fractional signal by a factor of 25 to achieve a value of unity. The infrared laser pulse timing needs to be reduced an order of magnitude, the dye laser intensity at the location of the atoms needs to be

increased a factor of three, and the UV optics system needs to provide complete overlap with the atomic beam. This would make detailed studies of the resonance possible, studies that hopefully would reveal the origin of the unexplained factor of five reduction in the fractional signal. Overcoming this last factor would make the originally proposed measurements quite feasible. Detailed studies would require thousands of laser shots (several hours) per data point to get percent-level statistics.

REFERENCES

1. Q. Su, J. H. Eberly and J. Javanainen, Phys. Rev. Lett. 64, 862 (1990)
2. J. Grochmalicki, M. Lowenstein and K. Rzazewski, Phys. Rev. Lett. 66, 1038 (1991).
3. F. Benvenuto, G. Casati and D. L. Shepelyansky, Phys. Rev. A 45, 7670 (1992); Phys. Rev. A, to be published 1993.
4. R. J. Vos and M. Gavrilla, Phys. Rev. Lett. 68, 170 (1992).
5. D. Richards, J. Phys. B 17, 1221 (1984).
6. L. D. Noordan, A. ten Wolde, A. Lagendijk and H. B. van Linden van den Heuvell, Phys. Rev. A 40, 6999 (1989).
7. J. E. Bayfield and D. W. Sokol, Phys. Rev. A 34, 2977 (1986).
8. J. E. Bayfield and L. Pinnaduwege, Phys. Rev. Lett. 54, 313 (1985).
9. J. E. Bayfield, Phys. Rev. 182, 115 (1969).
10. J. E. Bayfield, G. A. Khayrallah and P. M. Koch, Phys. Rev. A 9, 209 (1974).

**DATE
FILMED**

8 / 5 / 93

END