DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DOE/PC/89757--8

DE-AC22-89PC89757-8

DOE/PC/89757--8

THERMODYNAMICS AND SURFACE STRUCTURE OF COALS DE92 040016

Quarterly Report for the Period
July 1, 1991 to September 31, 1991

Amy S. Glass, John W. Larsen, Deanna M. Quay, James E. Roberts, and
Patrick C. Wernett

Department of Chemistry
Lehigh University
Bethlehem, PA 18015

PREPARED FOR THE UNITED STATES DEPARTMENT OF ENERGY
Under Contract DE-AC22-89PC89757

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Thermodynamics and Surface Structure of Argonne Coals

SCOPE AND OBJECTIVES OF WORK

Scope. An understanding of the surface structure and chemistry of coals is necessary for a true understanding and optimization of coal cleaning and other surface interactions. In all chemical reactions of solid coal, the reagent first encounters the coal surface. The extent of surface which is available to a molecule and the interactions which occur during the molecule/surface encounter are critical parameters to understanding the chemistry of the interaction of coals with various solvents. The present studies have been undertaken with the objective of understanding these complex interactions.

Objectives. The present work involves investigations of the surface structure and thermodynamics of coals and treated coals in order to develop a detailed understanding of the coal surface and its transformations and interactions as a result of various chemical treatments. To this end we are using several types of experimental probes:

- 1.) NMR relaxation agents are deposited on coals and the resulting spectra provide information about the structure and chemistry of the atoms at the coal surface.
- 2.) ^{129}Xe NMR is being used as a probe of pore distributions and surface polarity of coals.
- 3.) Classical calorimetric studies and inverse gas chromatography are being used to determine the strengths of interaction between various probe molecules and coals.

Inverse Gas Chromatography

Introduction

We previously reported on our intention to use the technique of inverse gas chromatography (IGC) to determine the nature of the interactions of various molecules with coals. The objective of these studies is to determine the enthalpies of the interactions of various polar and nonpolar molecules with sites in coals such as aromatic and hydroxyl groups. These studies will shed light on the interactions which occur during coal cleaning.

Measurements of the surface areas of coals using different molecules in this lab and by others have found a dependence of the measured surface areas on the size and chemical nature of the probe molecules. The data indicate that diffusion plays a role in determining the surface area which is obtained for a given probe molecule-coal pair. The surface areas have also been found to depend on the concentration of probe molecules in the gas phase and on the time that is allowed for determining the surface area. Such behavior is typical of gas-solid processes that are affected by mass transport.

As a result of these findings, we have begun studies which are aimed at elucidating the effects of diffusion on the interactions of various molecules with coals. These studies involve determinations of diffusion coefficients of various molecules in coals at different temperatures and gas concentrations. Diffusion coefficients are obtained by monitoring the amount of gas taken up versus square root of time at low gas concentrations, i.e., in the

Fickian regime. At higher gas concentrations (above about 10^{-3} Torr at 300K), the dependence of gas uptake on the square root of time is often nonlinear for gas/solid systems, indicating non-Fickian behavior. In this regime, diffusivities are often found to depend on the concentration of the diffusant in the gas phase. The diffusion data obtained from these static measurements will be correlated with data obtained by IGC for the same diffusant/coal systems.

The advantage of using IGC to study the interactions between various molecules and coals is that both chemical and mass transport effects can be determined from a single set of experiments. For a given probe molecule/coal pair, the retention time of a chromatographic peak is characteristic of the chemical interaction and the diffusion time, while the peak width is characteristic of the diffusion time. By performing experiments at different temperatures, gas concentrations, and flow rates, the relative contributions of the two types of mechanisms, diffusion and chemical interaction, can be determined for a given probe molecule/coal pair. Chemical interaction strengths and diffusion behavior will be determined in a given diffusion regime, eg., Fickian or concentration dependent transport.

Experimental

Experiments involve injecting micromolar quantities of probe molecules from a gas manifold at pressures between 1 and 10^{-3} Torr using a gas chromatographic sampling valve with a volume of 15 μ l. The columns are 1/8 inch ss, about 1.5m long, and contain about 3g

of coal of 60/70 Mesh particle size. Control experiments are performed using columns packed with 60/80 Mesh particle size glass beads or Spherocharb, a well-characterized, high surface area carbon adsorbent. Columns are degassed overnight at 130°C before performing each days set of experiments. All liquids are purified by at least 3 freeze-pump-thaw cycles before introducing them as gases into the manifold. Gas pressures are measured using a Hg manometer and a Baritron gauge with a range of 2 to 10^{-4} Torr. He is used as the carrier gas. Both FID and TCD gas detectors are used depending on the probe molecule injected.

Retention volumes are determined at various flow rates from 1-10 ml/min. and at temperatures of 30-130°C. At least three, but usually five or six injections are made for each flow rate and temperature. The retention volumes reported represent the average of all trials for a given set of conditions.

Results and Discussion

Data for different probe molecules on glass beads are presented in Figure 1. The data show the same retention volume independent of the probe molecule used. Retention volumes for the glass bead column were independent of the concentration of probe molecules, carrier flow rate, and column temperature, indicating a lack of interaction of molecules with the glass beads, as expected.

The data for methane on Illinois #6 coal which have been obtained so far are summarized in Figure 2. Retention times for a given temperature and flow rate were found to be independent of methane concentration, indicating that the chemical interaction

between methane and Illinois#6 is not concentration dependent at these methane concentrations. The data of Figure 2 indicate quite different behavior from that of the glass bead column. It is seen that retention volumes varied with flow rate and temperature, indicating that a nonequilibrium process with a significant activation energy characterizes the interaction of methane with Illinois#6 coal. From Fig. 2A it is seen that at a flow rate of 1.9 ml/min., the retention volume of methane on Illinois#6 decreases linearly with temperature, levelling off at about 80°C with a retention volume of about 6.5 ml. As seen from Fig. 2B, at a flow rate of 1.2 ml/min., the retention volume levels off to the same value of about 6.5 ml., but this occurs at the lower temperature of about 70°C. This indicates that the retention volume of 6.5 ml corresponds to that of a noninteracting gas. Experiments with rare gases using the TCD detector are being performed to verify this hypothesis. The data of Fig. 2B differ qualitatively from those of Fig. 2A at temperatures below 70°C. The retention volume increases steeply at temperatures between 60-40°C to a value which is higher than that in Fig. 2B, but then at 30°C the retention volume begins to decrease. At present, we have no explanation for the different types of behavior observed at 1.2 and 1.9 ml/min. flow rates. Experiments are being performed at lower flow rates to further investigate these effects. In addition, we are performing calculations to determine the temperature dependence of the diffusion coefficients.

Conclusions

The experiments using IGC are directed towards understanding the roles played by mass transport and chemical interactions of molecules with coals. IGC is being used to determine the interplay of these two types of interactions for different coals and probe molecules. Planned experiments include studies at a range of flow rates, temperatures, and concentrations for coals of different rank. These experiments will be correlated with data from static gas uptake measurements.

Determination of the Surface Structure of Coals By the Deposition of NMR Relaxation Agents

Present Work:

Our work this month has been determining the effect of added surface dysprosium(III) ions on the NMR spectra of coal. We have also been examining the effect of this relaxation agent on our model system, an aryl sulfonate silica gel.

Background:

To the best of our knowledge, NMR has not previously been applied to surface studies of coal. It is a powerful technique because line positions and intensities are indicative of geometry, bonding hybridization and population of distinct functionalities as well as local environment effects. The NMR spectrum can be influenced by many factors including dipolar through-space coupling between an unpaired electron spin and the spin of the carbon atom. The unpaired electron can act as a relaxation sink, significantly shortening the spin-lattice relaxation time (T_1) of the coupled carbon-13 atom. This shortening of the T_1 can broaden the signal to the point where it disappears into the baseline noise. The effective range of interaction is proportional to the inverse sixth power of the separation of the two spins (r^{-6})¹. In this system, the effective range is a relatively short distance on the order of 1 nanometer. If the paramagnetic centers are deposited on the surface of a sample, an effective range of approximately 1

nanometer would limit the paramagnetic effects to surface functionalities.

NMR relaxation and shift reagents are being deposited on the surface of coals. The dipolar coupling of the unpaired electron spin of the relaxation agent and the carbon atom should significantly shorten the carbon T_1 which should broaden it away. We propose to record the NMR spectrum of a coal before and after deposition and subtract the spectra. The difference spectra will be due to the functionalities within approximately one nanometer of the surface reveal the surface composition of the coal.

Experimental:

In order to observe the effect of paramagnetics on coal, we deposited a known amount of dysprosium nitrate on several samples of Beulah Zap lignite². We chose Beulah Zap lignite primarily because it has a high concentration of oxygen functional groups. We expect the oxygen and carboxylate groups to bind the dysprosium ions. We chose dysprosium because it appears that dysprosium may be a better relaxation agent than copper(II). Work with copper(II) was described in Monthly Report DEAC22-89C89PC89757-16³. When compared to the other lanthanides, dysprosium exhibits the largest downfield shifting behavior⁴. We chose a downfield shifting lanthanide so that the carbonyl peak would not be shifted into the highly congested aromatic region.

We also deposited known concentrations of dysprosium onto an aryl sulfonate ion exchange resin. The aryl sulfonate silica gel serves as a model compound. Samples containing 1, 2, 3, 4, and 8%,

dysprosium on a charge equivalence basis were prepared. We determine the number of dysprosiums with a +3 charge needed to balance the sulfonates with a -1 charge. A 1% coverage charge equivalence is 1% of the amount of dysprosium needed for complete coverage. The coal used is Beulah Zap lignite of the Argonne Premium Coal Sample Program². All NMR spectra were obtained using a General Electric GN-300 NMR spectrometer operating at 75.4 MHz for ¹³C and utilizing a Doty 7mm probe. The samples were examined under Magic Angle Sample Spinning (MASS) conditions⁵. The model compound used was an aryl sulfonate ion exchange resin produced by J.T. Baker, Inc.

The Beulah Zap was treated by mixing with a sodium bicarbonate buffer (pH=9) for one week. It was then dialyzed for 24 hours against deionized water three times. The sample was split, one half was mixed with a dysprosium nitrate solution for one week. Samples containing one dysprosium per 15-20 carboxylic acid functionalities were prepared based on 7 carboxylic acid functionalities per 100 carbon atoms⁶. The other half, our control, was kept in water for one week. The solvent was evaporated from the samples which were then dried in a 110°C oven under vacuum. All manipulations of coal samples were done in a nitrogen environment to minimize oxidation.

The silica gel was prepared by titrating a known quantity of aqueous dysprosium nitrate solution into a slurry of the gel with gentle stirring. The solvent was then evaporated and the samples dried under vacuum at 50°C.

NMR spin-lattice relaxation (T_1) studies³ were then conducted

in order to compare treated and untreated sample T_1 times.

Discussion:

The spin-lattice relaxation time (T_1) studies employed cross-polarization conditions. Cross polarization is a technique commonly employed in solid state NMR involving the transfer of magnetization from the protons to the carbons². Cross polarization is used to improve carbon sensitivity. The technique has been described in an earlier Monthly Report DE-AC22-89PC89757-16. The pulse sequences employed for the relaxation studies referred to in our laboratory as T1CP1H (proton T_1) and T1NOE (carbon-13 T_1) have also been described in Monthly Report DE-AC22-89PC89757-16³.

The coal samples prepared had significantly less dysprosium(III) than those reported in an earlier Monthly Report DE-AC22-89PC89757-18⁷. The samples described in that report had one dysprosium(III) per 0.19 carboxylates and one dysprosium(III) per 1.89 carboxylates. At that loading no signal was observed. This month we prepared samples with much lower dysprosium(III) loadings. Samples with one dysprosium per 19.7 and 16.5 carboxylates were prepared. Signal was observed and carbon and proton T_1 's were determined as described above. The T_1 values are presented in Tables 1 and 2. The errors reported in these tables as well as those in Tables 3 and 4 are the standard deviation in the least squares line fit. Each value represents one measurement. These measurements will be repeated. At the low dysprosium(III) loading of 1 Dy / 238 C atoms, it does not appear to be very effective in decreasing either the carbon or proton T_1 's in the

sample. There is a slight shortening observed at 180 - 204 ppm for both the proton and carbon T_1 's in the other sample with 1 Dy / 282 C atoms. This is the region in which the carboxylates would be observed in both the proton and carbon T_1 spectra since the proton T_1 's are monitored using carbon spectra. This is what would be expected if the dysprosium(III) ions coordinate with the carboxylates. For comparison purposes, Tables 1 and 2 also include data from studies in which copper(II) ions were deposited on the Beulah Zap³. It appears at first that the copper(II) is a better relaxation agent than the dysprosium, but the relative concentrations are very different. The copper concentration is 25-30X higher than the dysprosium concentrations. At dysprosium concentrations similar to that of the copper there was no observable NMR signal⁸. Several possible explanations for the loss of signal were described in Monthly Report DEAC22-89C89PC89757-18⁷.

This quarter we also expanded our study of the effect of the dysprosium(III) ions on our model compound an aryl sulfonate silica gel. A range of dysprosium(III) concentrations from 0-8% based on a charge equivalence basis were evaluated. The carbon and proton T_1 values are presented in Tables 3 and 4. As would be expected the T_1 values decrease with increasing dysprosium(III) concentration. At 4 and 8% the effect seems to level off. A 30% dysprosium(III) loading was also made, but the NMR spectrum had no signal using either cross polarization⁵ or Bloch decay⁸ experiments.

Future Work:

Next month, we plan to vary the procedure in which the Beulah-Zap samples are made. At present we have no proof that the dysprosium(III) ions are staying on the surface of the coal. If they are diffusing into the bulk of the coal instead of remaining on the surface as we have speculated, this might account for the loss of the signal at high dysprosium(III) concentrations. The dysprosium would then be relaxing not just surface functionalities, but also bulk functionalities. We plan to treat a sample as described above with a sodium bicarbonate wash for a week and then apply the dysprosium nitrate solution. We plan to treat another sample by adding the dysprosium nitrate solution to the native coal and shaking for a short period of time (a half hour). The second coal sample will be unswelled by the sodium bicarbonate and since it will have a short reaction time, the dysprosium(III) should remain on the surface. The relaxation times and coal spectra should be different if the dysprosium is located in different regions of the coal.

References

1. Sternlicht, H. J. Chem. Phys. 1965, 42, 2250.
2. Vorres, K. S. Energy and Fuels, 1990, 4, 420-426.
3. Larsen, J. W.; Quay, D. M.; Roberts, J. E.; Wernett, P. C. Thermodynamics and Surface Structures of Coals, Monthly Report, DE-AC22-89PC89757-16, April 1, 1990- May 1, 1990.
4. Horrocks, W. D. Jr.; Sipe, J. P. III J. Am. Chem. Soc. 1971, 93, 6800-6804.
5. Fyfe, C. A. in Solid State NMR for Chemists; C. F. C. Press: Ontario, (1984).
6. Solum, M. S.; Pugmire, R. J.; Grant, D. M. Energy and Fuels, 1989, 3, 187-198.
7. Larsen, J. W.; Glass, A. S.; Quay, D. M.; Roberts, J. E.; Wernett, P. C. Thermodynamics and Surface Structures of Coals, Monthly Report, DE-AC22-89PC89757-18, June 1, 1991- July 1, 1991.
8. Bloch, F. Phys. Rev. 1946, 70, 460.

Table 1
Carbon T1's (SEC) for Buelah Zap Lignite Treated
With Sodium, Copper(II), and Dysprosium(III)

	Na Treated	1 Cu(II)/9.7 C Atoms	Na Treated	1 Dy(III)/ 282 C Atoms	Na Treated	1 Dy(III)/ 238 C Atoms
30 ppm	0.34(0.03)	0.18(0.008)	0.32(0.01)	0.46(0.01)	0.37(0.02)	0.61(0.02)
128 ppm	0.31(0.07)	0.17(0.02)	0.40(0.06)	0.46(0.05)	0.44(0.03)	0.75(0.06)
180 ppm			0.55(0.09)	0.13(0.03)		
199-204 ppm	0.07(0.04)	0.018(0.003)	0.22(0.09)	0.15(0.06)	0.39(0.04)	0.76(0.001)

Table 2
Proton T1's (SEC) for Buelah Zap Lignite Treated
With Sodium, Copper(II), and Dysprosium(III)

	Na Treated	1 Cu(II)/9.7 C Atoms	Na Treated	1 Dy(III)/ 282 C Atoms	Na Treated	1 Dy(III)/ 238 C Atoms
30 ppm	0.021(0.002)	0.009(0.002)	0.065(0.003)	0.038(0.003)	0.031(0.003)	0.033(0.004)
128 ppm	0.016(0.001)	0.005(0.002)	0.028(0.002)	0.023(0.001)	0.014(0.0007)	0.016(0.001)
180 ppm			0.40(0.004)	0.024(0.002)		
199-204 ppm			0.043(0.004)	0.024(0.001)	0.014(0.0005)	0.014(0.001)

Table 3
Carbon T1's (SEC) for Dysprosium(III) Treated
Aryl Sulfonate (% Based on Charge Equivalence)

	Na Treated	1% Dy(III)	2% Dy(III)	3% Dy(III)	4% Dy(III)	8% Dy(III)
13 ppm	2.7(0.8)	0.8(0.3)	0.8(0.4)	0.6(0.3)	0.5(0.2)	0.38(0.10)
27 ppm	1.5(0.3)	0.67(0.08)	0.77(0.08)	0.9(0.3)	0.40(0.07)	0.30(0.06)
127 ppm	0.9(0.6)	0.46(0.01)	0.41(0.01)	0.78(0.01)	0.3(0.2)	0.5(0.2)
180-193 ppm			1.1(0.2)	0.58(0.05)		

Table 4

Proton T1's (SEC) for Dysprosium(III) Treated
Aryl Sulfonate (% Based on Charge Equivalence)

	Na Treated	1% Dy(III)	2% Dy(III)	3% Dy(III)	4% Dy(III)	8% Dy(III)
13 ppm	0.30(0.004)	0.057(0.002)	0.031(0.001)	0.051(0.003)	0.019(0.003)	0.020(0.0006)
27 ppm	0.25(0.006)	0.058(0.002)	0.033(0.0009)	0.062(0.003)	0.017(0.003)	0.023(0.0009)
127 ppm	0.30(0.002)	0.056(0.002)	0.032(0.0009)	0.061(0.002)	0.023(0.001)	0.019(0.0004)
180-193 ppm	0.37(0.007)	0.060(0.002)	0.028(0.001)	0.077(0.01)	0.016(0.002)	0.022(0.002)

END

**DATE
FILMED**

12 / 17 / 92