THERMODYNAMICS AND SURFACE STRUCTURE OF COALS

Quarterly Report for the Period
October 1, 1991 to December 31, 1991

Amy S. Glass, John W. Larsen, Deanna M. Quay, and James E. Roberts

Department of Chemistry
Lehigh University
Bethlehem, PA 18015

PREPARED FOR THE UNITED STATES DEPARTMENT OF ENERGY
Under Contract DE-AC22-89PC89757

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Determination of the Surface Structure of Coals By the Deposition of NMR Relaxation Agents

Present Work:

Our work this month has focused on determining the effects of a new procedure for the deposition of dysprosium(III) ions on the NMR spectra of coal. We have also been trying to determine the concentration and location of the dysprosium ions in the coal using x-ray photoelectron spectroscopy.

Background:

To the best of our knowledge, NMR has not previously been applied to surface studies of coal. It is a powerful technique because line positions and intensities are indicative of geometry, bonding hybridization and population of distinct functionalities as well as local environment effects. The NMR spectrum can be influenced by many factors including dipolar through-space coupling between an unpaired electron spin and the nuclear spin of the carbon atom. The unpaired electron can act as a relaxation sink, significantly shortening the spin-lattice relaxation time (T_1) of the coupled carbon-13 nucleus. This shortening of the T_1 can broaden the signal to the point where it disappears into the baseline noise. The effective range of interaction is proportional

to the inverse sixth power of the separation of the two spins (r^{-6})¹. For many $e^- / {}^{13}\text{C}$ spin pairs, the effective range is a relatively short distance on the order of 1 nanometer. If the paramagnetic centers are deposited on the surface of a sample, an effective range of approximately 1 nanometer would limit the paramagnetic effects to surface functionalities.

NMR relaxation and shift reagents are being deposited on the surface of coals. The dipolar coupling of the unpaired electron spin of the relaxation agent and the carbon atom should significantly shorten the carbon T_1 which should broaden it away. We propose to record the NMR spectrum of a coal before and after deposition and subtract the spectra. The difference spectra will arise from the functionalities within approximately one nanometer of the surface and reveal the surface composition of the coal.

In order to determine the surface concentration of the dysprosium in the coal, we are using x-ray photoelectron spectroscopy (XPS) also known as electron spectroscopy for chemical analysis (ESCA). XPS is a surface technique that can be used for the elucidation of chemical structure. The binding energy for each electron in each element is unique. The measurement of the binding energy in XPS allows the identification of the element and its oxidation state. The relative atomic concentrations of each element can also be determined using XPS spectra².

Experimental:

In order to observe the effect of paramagnetics on coal, we deposited a known amount of dysprosium nitrate on several samples

of Beulah Zap lignite³. We chose Beulah Zap lignite primarily because it has a high concentration of oxygen functional groups. We expect the oxygen and carboxylate groups to bind the dysprosium ions. We chose dysprosium because dysprosium exhibits the largest downfield shifting behavior when compared to other lanthanides⁴. We chose a downfield shifting lanthanide so that the carbonyl peak would not be shifted into the highly congested aromatic region. The coal used is Beulah Zap lignite of the Argonne Premium Coal Sample Program³. All NMR spectra were obtained using a General Electric GN-300 NMR spectrometer operating at 75.4 MHz for ^{13}C and utilizing a Doty 7mm probe. The samples were examined under Magic Angle Sample Spinning (MASS) conditions⁵.

One Beulah Zap sample was treated in the usual manner by mixing with a sodium bicarbonate buffer (pH=9) for one week. It was then dialyzed three times against deionized water for 24 hours each time. The sample was then mixed with a known quantity of dysprosium nitrate solution for one week. The solvent was evaporated and the sample dried to constant weight in a 110^o vacuum oven. Another sample was prepared without the buffer treatment. The Beulah Zap was mixed with a known quantity of dysprosium nitrate solution for a half hour. The solvent was evaporated from the samples which were then dried in a 110^oC oven under vacuum. The sample prepared without buffer is referred to as the "Shake and Bake" sample in some of the spectra and tables. All manipulations of coal samples were done in a nitrogen environment to minimize oxidation.

NMR spin-lattice relaxation (T_1) studies³ were then conducted in order to compare the T_1 times of the samples treated with and without the sodium bicarbonate buffer.

XPS studies were also conducted using a Scienta ESCA 300 spectrometer. Survey and regional spectra were taken of each of the samples described above and an unreacted Beulah Zap sample. The dysprosium treated samples were also sputtered with argon and spectra taken. Dysprosium metal was also surveyed. The dysprosium metal was scraped prior to insertion into the spectrometer and then scraped again inside the sample preparation chamber. Survey and regional spectra were then taken. The dysprosium metal was then exposed to 1×10^{-5} mbar of oxygen for ten minutes and spectra were taken of the oxide.

Discussion:

The spin-lattice relaxation time (T_1) studies employed cross-polarization conditions. Cross polarization is a technique commonly employed in solid state NMR involving the transfer of magnetization from the protons to the carbons⁵. Cross polarization is used to improve carbon sensitivity. The technique has been described in an earlier Monthly Report DE-AC22-89PC89757-16. The pulse sequences employed for the relaxation studies referred to in our laboratory as T1CP1H (proton T_1) and T1NOE (carbon-13 T_1) have also been described in Monthly Report DE-AC22-89PC89757-16⁶.

The coal samples prepared had 0.542 Dy/100 C atoms for the buffer sample and 0.290 Dy/100 C atoms for the other sample. The proton and carbon T_1 values are reported in Tables 1 and 2. The T_1

values for the buffer treated sample are slightly shorter than the other sample. This would be expected since the Dy concentration is slightly higher in the buffer sample. When spectra of each of these samples are processed identically, the signal to noise ratio of the sample treated with just the dysprosium nitrate was almost twice that of the sample treated with the buffer. The spectra are Figures 1 and 2. This indicates that the dysprosium is located in different parts of the coal. The loss of signal in the buffer treated sample indicates that the dysprosium is probably dispersed throughout the coal matrix and is not confined to the surface. This would explain why there was no NMR signal when a high concentration of dysprosium was deposited on the coal as described in Monthly Report DE-AC22-89PC89757-18⁷. If the dysprosium is dispersed throughout the coal, then it could broaden away all the signal. If the dysprosium was on the surface, it should only broaden away surface functionalities.

In order to determine the concentration of the dysprosium on the surface of the coal, we conducted XPS studies. Survey and regional spectra were taken of each of the samples. Figures 3 and 4 are survey spectra that show the comparison between the Beulah Zap out of the bottle and the dysprosium treated samples. Since the dysprosium concentrations are so low, the spectra are very similar. Regional spectra were also taken in order to determine relative concentrations. The samples were then sputtered with argon in order to determine the concentration within the sample. Due to instrumental problems the depth of the sputtering is

unknown. These studies will be repeated. Figures 5 and 6 are the dysprosium 4d region sputtered and unsputtered. The sputtered spectra show significant differences from the unsputtered. The sputtered spectra show the emergence of a doublet. This could be indicative of a difference in the oxidation states between the surface and bulk dysprosium or it could be indicative that there is sputtering damage to the dysprosium. The XPS spectra of dysprosium metal was also taken. Pure oxygen was then added to the spectrometer preparation chamber and the spectrum of the oxidized dysprosium taken. The dysprosium 4d peaks in the coal are similar to those seen in the oxidized spectra. The XPS spectra for the dysprosium metal with and without oxygen are Figures 7 and 8. The area values under the carbon, oxygen and dysprosium peaks for each of the coal spectra are presented in Table 3. The atomic percents for each of these elements are presented in Table 4. The areas are probably a better indicator of relative quantities since the atomic percents are based solely on the three elements. Since coal is a complex substrate and since the sodium bicarbonate treated sample also has an increased concentration of sodium, relationships between the area ratios are probably more meaningful. The sodium Auger peak can be observed in the survey spectrum in Figure 3 at about 500 eV. There is no apparent sodium peak in the other dysprosium treated spectrum (Figure 4). When the carbon/dysprosium area ratios are computed for both the sputtered and unsputtered spectra, the ratios of the two samples are similar. The unsputtered ratios are 100 C:3.1 Dy and 100 C:3.2 Dy for the buffer

treated and no buffer samples respectively. The sputtered ratios are 100 C:5.3 Dy and 100 C:4.7 Dy respectively. This appears to indicate that there is a higher dysprosium concentration below the surface. Since the sputtering efficiency was not determined and since we could not determine whether one element was sputtered preferentially, more work is needed to interpret these values. When these values are compared to those computed from the amount of coal and dysprosium nitrate used to prepare the samples, the surface and sub-surface concentrations of dysprosium appear higher than the values computed for uniform distribution of the dysprosium in the coal, 100 C:0.542 Dy for the buffer and 100 C:0.290 Dy atoms for the "shake and bake" sample. This is encouraging, but due to the instrumental uncertainties described above these experiments need further examination. When the atomic percents of these three elements are compared to each other (Table 4), the relative percents are essentially the same for each sample sputtered and unsputtered. The C: Dy ratio determined from the atomic percents are very different from those determined from the areas. The values 100 C:0.25 Dy and 100 C:0.47 Dy for the unsputtered and sputtered buffer treated samples and the values 100 C:0.25 Dy and 100 C:0.35 Dy for the "shake and bake" sample are closer to the values calculated for a uniform distribution of dysprosium in the coal. This method only takes into account the relative quantities of carbon, oxygen and dysprosium. This is probably an oversimplification of the system since coal is a complex mixture. Since the ratios obtained by area measurements and percents are

very different, additional experiments must be performed to determine which method is the best representation of this system. The ratios calculated are probably useful for comparisons between the buffer and "shake and bake" samples, but interpretation of the ratios in terms of overall concentrations should be reserved until some of the uncertainties are resolved.

Future Work:

Next month we plan to try several other procedures for preparing the coal. Since there were significant differences in the signal to noise ratios between the two procedures used, we plan to react the coal with the dysprosium nitrate for a week without sodium bicarbonate buffer. This should indicate if the increased diffusion of the dysprosium into the coal is a function of the sodium bicarbonate treatment or a function of the length of reaction time. We plan to follow the same procedures discussed earlier, but instead of evaporating the solvent off the coal we will filter it to see how much dysprosium coordinates with the coal, and to determine if the NMR and XPS spectra are different when only dysprosium coordinated to the coal is present. We also plan to run some more XPS experiments on these samples to try to determine the relative concentrations of dysprosium on the surface and in the bulk, and to determine what type of chemistry the dysprosium is undergoing when it is reacted with the coal.

Inverse Gas Chromatographic Studies

Introduction

Our work on the diffusion and thermodynamics of molecules in coals is continuing. Our IGC data for small nonpolar molecules have given us an understanding of the interactions of these types of molecules with coal. The data for these molecules also provide us with a foundation which is necessary for understanding the more complex interactions of large molecules and of polar molecules with coal.

Results and Discussion

Figures 9 through 11 show diffusion and thermodynamic data for three nonpolar molecules in Illinois#6 coal. The data are plotted as a function of molecular diameter. As seen in Figure 9, the diffusion coefficient is dependent on the diameter of the diffusant molecule. This indicates that the diffusion of small nonpolar molecules in coal belongs to the class of diffusion known as "configurational diffusion." For diffusion in pores, Knudsen diffusion gives way to configurational diffusion when the pore diameter is decreased or the molecular size is increased so that the molecular size of the diffusant is no longer negligible compared with the pore diameter (8). In this regime, the diffusion rate is a function of the ratio of the molecular size to the pore diameter. Assuming a constant pore structure and a constant average pore diameter for diffusion in coal under the conditions of our experiments, the effective configurational diffusion

coefficient, D_e , is expected to be a function only of the molecular size. Thus the data in Figure 9 indicate that we are probing a similar pore network with a similar average pore diameter and effective diffusion length at least in the case of the three diffusants Ar, CH_4 , and neo- C_5H_{12} . The behavior illustrated in Figure 9 resembles diffusion behavior seen for nonpolar molecules in polymers (9), as well as behavior seen for nonpolar molecules in molecular sieves (10).

The dependence of diffusion rate on diffusant size in the case of polymers is thought to be the manifestation of an activated process that involves the formation of a hole of the required size in the polymer. Hole formation in the polymer involves movement of polymer chains and requires disruption of interchain forces. In effect, a defect site is created in the polymer and this site is filled by the diffusant molecule.

The dependence of diffusion rate on diffusant size in the case of molecular sieves is thought to be the manifestation of an activated process that involves the "force field" of the pore walls, and is dependent on the proximity of the diffusant to these walls (11).

As seen from Figure 10, the diffusion of these molecules in Illinois#6 coal is an activated process, and the activation energy of diffusion is dependent on the size of the diffusant molecule as well. This behavior is also reminiscent of that found by Berens and Hopfenberg for the diffusion of nonpolar, spherical molecules in polystyrene (9), and of that found by Walker et al. (10).

Figure 11 shows a plot of adsorption enthalpy vs. molecular diameter for the four diffusants. It is seen that molecular size is an indication of the chemical interaction between these molecules and the coal. It is likely that this is a reflection of the dependence of the adsorption enthalpy on molecular polarizability. Such a dependence is typical of the interactions between nonpolar adsorbates and surfaces that contain polar as well as nonpolar functionalities (11). We are determining static molecular polarizabilities for these diffusants in order to quantify the dependence of adsorption enthalpy on polarizability.

It should be noted that the value of the adsorption enthalpy for cyclopropane is unusually high for a nonpolar molecule. It is more similar to adsorption enthalpies reported for polar molecules on graphitic surfaces (12). In addition, its diffusion behavior does not fall on the same straight line in Figs. 9 and 10 as the three other diffusants. An anomalous contribution to the diffusivity and adsorption enthalpy of cyclopropane, due possibly to its nonspherical shape, could account for the poor fit of the behavior of this molecule. More work needs to be done on polar and nonpolar adsorbates to clarify this matter.

Table 5 lists the diffusion and adsorption numbers for the four diffusants. Diffusivities listed were measured at 90°C. Assuming an effective diffusion length of 0.115 mm, based on an average particle diameter of 230 microns, gives the diffusion coefficients listed in column 4. It is seen that an increase of only about 2 Å in molecular diameter results in a decrease of 2

orders of magnitude in the diffusion coefficient. Berens and Hopfenberg observed a decrease in D of about 3 orders of magnitude for an increase in molecular diameter of 1 Å for diffusion in polystyrene at 30°C and for diffusion in poly(methyl methacrylate) at 90°C (9).

Our values of $D_e^{1/2}/r_0$ for CH_4 and Ar agree reasonably well with data from static diffusion measurements on coals of similar rank. Nandi and Walker found values of $D^{1/2}/r_0$ of 0.19 to 0.35 for methane in coals varying from low volatile anthracite to high volatile bituminous at temperatures of 60°C to 230°C (13), similar to our value of 0.29. However, the activation energies of diffusion for CH_4 measured by these authors were 3.9 to 5.4 kcal/mol, in two different coals, significantly higher than our value of 2.6 kcal/mol. Sevenster obtained diffusion coefficients of about 10^{-13} cm²/sec for CH_4 in coal (14). He did not state the effective diffusion length. Sevenster's activation energy for diffusion of CH_4 , about 2.5 kcal/mol at 30°C to 60°C, is very similar to our value of 2.6 kcal/mol at 30°C to 90°C.

Table 6 lists retention volumes and partition ratios for the three diffusants at 90°C. The slopes of the isotherms, v/p , in ml/g*atm, were calculated using the expression

$$v/p = (v_p/RT) * (V_N/W_S)$$

where v_p is the volume occupied by one mole of ideal gas at STP, V_N is the net retention volume in ml, and W_S is the weight of the

coal. This quantity is identical to the corrected retention volume, V_g , which is defined as

$$V_g = (273/T_{col}) * (V_N/W_S)$$

where T_{col} is the temperature of the chromatographic column during the experiment. Values for v/p at 30°C and at 90°C are listed in the last two columns of the table. Anderson et al. found $v/p=0.8$ ml/g*atm for N_2 on low volatile bituminous coal at 0°C and $v/p=0.21$ ml/g*atm for butane at 0°C on the same coal (15). Sutton and Davies found v/p of 3.2 ml/g*atm for CH_4 on a bituminous coal at 35°C (16). These values for the initial slopes of the isotherms of small nonpolar adsorbates are in the same range as our values of 0.6 and 1.3 ml/g*atm for Ar and CH_4 on Illinois#6 coal at 30°C.

Conclusions

As seen from the data presented in this report, we are making progress in our understanding of the interactions between coal and various organic and inorganic molecules. Our data indicate that diffusion plays a significant role in these interactions; the barriers to diffusion are significant. The data provide a picture of the chemical interactions that occur between molecules and coal. The adsorption enthalpy of cyclopropane, 9.9 kcal/mol, is much larger than the values usually found for nonpolar molecules on adsorbents. This may indicate a large dispersion component of the coal surface. Its diffusivity is also anomalous. This may reflect its nonspherical geometry.

We are determining mass transport and adsorption numbers for other nonpolar molecules such as Xe and propane. It is likely that Xe, which is spherical, will fall on the lines in Figures 9 and 10. We intend to measure adsorption of t-butyl-substituted molecules. These molecules will access a similar pore network because of their similar sizes and shapes. Any differences in their adsorption behaviors, therefore, should be ascribable to different types of chemical interactions with coal. Thus it is anticipated that these molecules, including t-butylamine and t-butyl alcohol, will serve as probes of coal surface chemistry. In addition the interactions of highly polarizable molecules, such as benzene, should provide information on the dispersion component of the coal surface.

References

1. Sternlicht, H. J. Chem. Phys. 1965, 42, 2250.
2. Skoog, D. A., and West, D. M. Principles of Instrumental Analysis; Saunders College/Holt, Rinehart and Winston: Philadelphia, (1980), 453-455.
3. Vorres, K. S. Energy and Fuels, 1990, 4, 420-426.
4. Horrocks, W. D. Jr.; Sipe, J. P. III J. Am. Chem. Soc. 1971, 93, 6800-6804.
5. Fyfe, C. A. in Solid State NMR for Chemists; C. F. C. Press: Ontario, (1984).
6. Larsen, J. W.; Quay, D. M.; Roberts, J. E.; Wernett, P. C. Thermodynamics and Surface Structures of Coals, Monthly Report, DE-AC22-89PC89757-16, April 1, 1990- May 1, 1990.

7. Larsen, J. W.; Glass, A. S.; Quay, D. M.; Roberts, J. E.; Wernett, P. C. Thermodynamics and Surface Structures of Coals, Monthly Report, DE-AC22-89PC89757-18, June 1, 1991-July 1, 1991.
8. R. E. Cunningham and R. J. J. Williams, "Diffusion in Gases and Porous Media," Plenum Press, New York, 1980.
9. A. R. Berens and H. B. Hopfenberg, J. Membrane Science 10 (1982) 283-303.
10. P. L. Walker, Jr., L. G. Austin, and S. P. Nandi, In: "Chemistry and Physics of Carbon," vol. 2, P. L. Walker, Jr., ed., Marcel Dekker, New York, 1966, p. 257.
11. A. V. Kiselev and Y. I. Yashin, "Gas-Adsorption Chromatography," Plenum Press, New York, 1969, p. 21.
12. E. M. Arnett, B. J. Hutchinson, and M. H. Healy, J. Am. Chem. Soc. 110 (1988) 5255.
13. S. P. Nandi and P. L. Walker, Jr., Fuel 49 (1970) 309.
14. P. G. Sevenster, Fuel 38 (1959) 403.
15. R. B. Anderson, W. K. Hall, J. A. Lecky, and K. C. Stein, J. Phys. Chem. 60 (1956) 1548.
16. J. B. Sutton and E. C. H. Davies, J. Am. Chem. Soc. 57 (1935) 1785.

List of Figures:

Figure 1: The CP-MASS carbon-13 NMR spectrum for the Beulah Zap sample treated with sodium bicarbonate buffer and dysprosium nitrate solution. The signal to noise ratio is 27:1. 3840 acquisitions.

Figure 2: The CP-MASS carbon-13 NMR spectrum for the Beulah Zap sample treated only with dysprosium nitrate. (Shake and Bake sample). The signal to noise ratio is 47:1. 4224 acquisitions.

Figure 3: XPS survey spectra comparing the Beulah Zap unreacted (out of the bottle) and the Beulah Zap sample treated with the sodium bicarbonate buffer and dysprosium nitrate.

Figure 4: XPS survey spectra comparing the Beulah Zap unreacted (out of the bottle) and the Beulah Zap sample treated only with the dysprosium nitrate (shake and bake).

Figure 5: XPS spectra of the Dy 4d region comparing the sputtered and unsputtered spectra for the Beulah Zap sample treated with the sodium bicarbonate buffer.

Figure 6: XPS spectra of the Dy 4d region comparing the sputtered and unsputtered spectra for the Beulah Zap sample treated only with dysprosium (shake and bake).

Figure 7: XPS spectrum of the Dy 4d region of the scrapped dysprosium metal.

Figure 8: XPS spectrum of the Dy 4d region of the dysprosium metal after exposure to 1×10^{-5} mbar of oxygen for 10 minutes.

Table 1
Proton T1's (Sec) for Beulah Zap Lignite with Dy
Treated With and Without NaHCO3 Buffer

	With Buffer	Without Buffer (Shake & Bake)
30 ppm	0.035(0.004)	0.046(0.003)
128 ppm	0.018(0.001)	0.025(0.001)
142 ppm		0.023(0.001)
205 ppm	0.021(0.001)	0.018(0.001)

Proton T1's determined using TlCplh as described earlier.³ Errors represent the standard deviation in the least squares fit. Each value represents 1 measurement. The "with buffer" sample was prepared with 0.542 Dy / 100 C. The "without buffer" or "shake and bake" sample was prepared with 0.290 Dy / 100 C atoms.

Table 2
Carbon T1's (Sec) for Beulah Zap Lignite with Dy
Treated With and Without NaHCO3 Buffer

	With Buffer	Without Buffer (Shake & Bake)
30 ppm	0.298(0.001)	0.433(0.002)
128 ppm	0.164(0.002)	0.517(0.006)
142 ppm		0.402(0.004)
205 ppm	0.163(0.008)	0.566(0.003)

Carbon T1's determined using T1NOE described earlier.³ Errors represent the standard deviation in the least squares fit. Each value represents one measurement. The "with buffer" sample was prepared with 0.542 Dy / 100 C atoms. The "without buffer" or "shake and bake" sample was prepared with 0.290 Dy / 100 C atoms.

Table 3
Area under XPS Peaks for Carbon, Oxygen and
Dysprosium

	With Buffer	With Buffer	Shake and Bake (W/O)	Shake and Bake (W/O)
	Unspattered	Sputtered	Unspattered	Sputtered
Dy 4d	218	5118	207	341
O 1s 1/2	4242	3996	3535	3208
C 1s 1/2	6974	9730	6392	7195
C/Dy Ratio	100C/3.1Dy	100C/5.3Dy	100C/3.2Dy	100C/4.7Dy

Areas of the peaks were determined by regional scans of each peak taken under identical conditions.

Table 4
Atomic Percents for Carbon, Oxygen and
Dysprosium from XPS

	With Buffer Unspattered	With Buffer Spattered	Shake and Bake (W/O) Unspattered	Shake and Bake (W/O) Spattered
Dy 4d	0.2	0.4	0.2	0.3
O 1s 1/2	20.1	14.5	18.6	15.5
C 1s 1/2	79.7	85.1	81.2	84.1
C/Dy Ratio	100C/0.25Dy	100C/0.47Dy	100C/0.25Dy	100C/0.35Dy

C:/ Dy Ratios are based on the percentages determined by the XPS experiment. Atomic percentages were determined from regional scans of the peaks taken under identical conditions.

Table V. Diffusion and Adsorption Numbers for Ar, CH₄, and Cyclopropane (Diffusion at 90°C)

Diffusant	Molec. Diameter (Å)	$D_e^{1/2}/r_o^+$ (sec ^{-1/2})	D_e^* (cm ² /sec)	E_{act} (kcal/mol)	H (kcal/mol)
Ar	3.4	0.38	1.9×10^{-5}	4.1	-2.65
CH ₄	3.8	0.29	1.1×10^{-5}	5.2	-3.12
Cyclo- C ₃ H ₆	4.5	0.045	2.7×10^{-7}	12.5	-9.86
Neo-C ₅ H ₁₂	5.8	0.058	4.4×10^{-7}	7.9	-8.92

*assumes $r_o = 115 \text{ \AA}$, based on Mesh fraction -60/-70

+Diffusivities determined at 90°C

Table VI. Retention volumes and partition ratios at Infinite Dilution for Ar, CH₄, and cyclopropane at 90°C.

Diffusant	V _g (ml/g)	k	v/p 30°C (ml/g*atm)	v/p 90°C (ml/g*atm)
Ar	0.34	0.91	0.61	0.34
CH ₄	0.57	1.55	1.34	0.57
Neopentane	5.77	20.4	--	5.77
Cyclopropane	10.2	37.3	--	10.2

*Note: V_g corresponds to the slope of the isotherm, also represented by v/p, while k is the amount of solute dissolved in the stationary phase over the amount dissolved in the mobile phase, both at infinite dilution.

Figure 1

DQ032 . 110 DMQ 12DEC91
DQ032 BZ DY #8 NAHCO3 ROTOVAP T1CP1H 5.6KHZ

Figure 2

DQ033 . 110 DMQ 17DEC91
DQ033 T1CP1H BZ DY #8 NO NAHCO3 ROTOVAP 5.6KHZ

Figure 3

90, 1.1 Out of Bottle and with Buffer
 BZDY-1.001 SURVEY LEHIGH 1991-11-19 12:02

Figure 4

90, 1.1 Out of Bottle and Shake and Bake (Roto)
 BZDY-1.001 SURVEY LEHIGH 1991-11-19 12:02

Pass energy
150 eV

Slit width
1.1 mm

Energy step
0.80 eV

Det. height
70 %

Lens mode
TRANSMISSION

X-ray power
2.3 kW

Rec. time
00:16:50

Figure 5

90, 1.1 BZ with NaHCO₃ Buffer Before and After
Sputtering BZDY-3.003 DY4D LEHIGH 1991-11-19 14:

Pass energy

150 eV

Slit width

1.1 mm

Energy step

0.10 eV

Det. height

70 %

Lens mode

TRANSMISSION

X-ray power

2.3 kW

Rec. time

00:07:59

Figure 6

90, 1.1 BZ with Dy - Shake and Bake (Roto) Before and After
Sputtering BZDY-4.002 DY4D LEHIGH 1991-11-19 14:

Figure 7

90, 0.8, scrape, 0 check

DYMET.015 DY4D LEHIGH 1991-12-20 13:11

Binding Energy [eV]

Figure 8

90, 0.8, 02 10 min 1x10⁻⁵mbar ave 1.2
DYMET.017 DY4D LEHIGH 1991-12-20 15:12

Figure 9

WITH ADSORPTION

Diffusion Coefficient vs. Molecular Diameter

Figure 10

Figure 11

Adsorption Enthalpy vs. Molecular Diameter

END

**DATE
FILMED**

12 / 15 / 92