1 of 1

LBL-33289
HIFAN-574

Heavy Ion Fusion Injector Program

S. Yu, S. Eylon, W. W. Chupp, A. Faltens, and T. Fessenden
E. Henestroza, R. Hipple, D. Judd, C. Peters, L. Reginato,
H. Rutkowski, J. Stoker, and D. Vanecek
Accelerator & Fusion Research Division
Lawrence Berkeley Laboratory
University of California
Berkeley, California 94720

J. Barnard, G. Caporaso, Y. J. Chen, F. Deadrick,
A. Friedman, D. Grote, and D. Hewett
Lawrence Livermore Laboratory
7000 East Avenue
P. O. Box 808
Livermore, CA 94550

Submitted to the 1993 Particle Accelerator Conference
Washington, D. C., May 17 - 20, 1993

MASTER

*This work was supported by the Office of Energy Research, Office of Fusion Energy,
U. S. Department of Energy under Contract No. DE-AC03-76SF00098.

ds
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Heavy Ion Fusion Injector Program*

S. Yu, S. Eylon, W.W. Chupp, A. Faltens, T. Fessenden, E. Henestroza, R. Hipple, D. Judd, C. Peters, L. Reginato, H. Rutkowski, J. Stoker, D. Vanecek; LBL
J. Barnard, G. Caporaso, Y.J. Chen, F. Deadrick, A. Friedman, D. Grote, D. Hewett, LLNL
University of California Lawrence Berkeley Laboratory
1 Cyclotron Road, MS 47-112, Berkeley, CA 94720 USA

Abstract

A program is underway to construct a 2 MV, 800 mA, K^+ injector for heavy ion fusion. The Electrostatic Quadrupole (ESQ) injector configuration consists of a zeolite source, a diode of up to 1 MV, together with several electrostatic quadrupole units to simultaneously focus and accelerate the beam to 2 MV. The key issues of source technology, high voltage breakdown, beam aberrations, and transient effects will be discussed. Results from ongoing experiments and simulations will be presented.

I. INTRODUCTION

A new high current ion injector for heavy ion fusion is under construction at Lawrence Berkeley Laboratory. The objective is to build a one-beam version of the 4-beam injector needed for the Induction Linac System Experiments (ILSE). As such, the machine must have high reliability, and the technology must be scalable to the ultimate full-scale fusion driver. The design goals for the K^+ ion beam are driver-scale line charge density ($0.25 \mu C/m A$), driver scale particle energy (2 MV), very low emittance (normalized emittance of less than 1π mm-mr) repetition rate of 1 Hz, and pulse length of 1 μs . While all previous injectors in the Heavy Ion Fusion Accelerator Research (HIFAR) group at LBL have been based on electrostatic aperture column (ESAC) designs, a six-month study at LBL and LLNL from March to September 1992 has led to the choice of the electrostatic quadrupole (ESQ) injector as the most suitable for the long term need of induction linac-based heavy ion fusion research work. The ESQ is a concept which uses a set of electrostatic quadrupoles to simultaneously focus and accelerate an ion beam. The front end of the ESQ is an axisymmetric diode containing a large source (of up to 7" in diameter according to present designs). The concept originated with Abramyan [1] and has been studied extensively by the Magnetic Fusion Energy group at LBL for a number of years [2]. As a high energy, high current injector, the ESQ concept has the distinct advantage of reduced voltage breakdown risks (as compared to ESAC), resulting from the intrinsically lower accelerating gradient and the presence of large transverse fields to sweep out deleterious secondary electrons.

II. INJECTOR DESIGN

A schematic of the one-beam injector is shown in Figure 1. The key components of the injector are a 2 MV MARX generator, a large hot alumino-silicate source (of $\leq 7"$

diameter), a diode column in which the ion beam is accelerated to ~ 1 MV after extraction, and a number of electrostatic quadrupoles to bring the ion beam to 2 MV. Furthermore, external to the accelerating columns, protection devices (metal oxide varistors and guard rings) are built in to prevent irreversible damage in the case of major breakdowns.

Fig. 1. Schematic of the one-beam injector.

The new MARX is a 36-stage pulse-forming network designed to produce a 2 MV pulse with 1 μs rise and 5 μs voltage flat top. This flat top can maintain constant voltage for the 1 - 2 μs long ion pulse during its transit through the length of the injector ($\sim 2 \mu s$ transit time). To minimize beam-induced transients, the electrical system as designed is quite stiff. The total resistance is 5 k Ω .

Source development is reported in a separate paper in this conference [3]. Tests with a small 1" hot alumino-silicate source over the past year has produced very encouraging results. The measured current density of 20 mA/cm², the temperature and emission uniformity, as well as life time have been shown to exceed ILSE requirements under normal operating conditions. A 4" source and a 6" source have been fabricated and initial tests have yielded similar emission characteristics.

The key design constraint for an ESQ injector arises from a distortion of the particle phase space which may lead to an unacceptable increase in beam emittance. This effect arises from a large spread in particle energy with varying radial position when a low energy beam traverses a strong electrostatic quadrupole structure. The phase space distortion resulting from this "energy effect" is further enhanced by the higher order multipole fields intrinsic in an interdigital electrostatic quadrupole structure. Earlier designs with a low energy diode (500 keV) show unacceptable growth in

* Work supported by the Director, Office of Energy Research, Office of Fusion Energy, U.S. Department of Energy under Contract No. DE-AC03-76SF00098.

Figure 5. EGUN output showing the geometry of the axisymmetric injector diode, the beam envelope, and field equipotential surfaces.

The ESQ section consists of 4 quadrupoles with representative parameters given in Table 1. The beam envelopes as calculated by the 3-D particle-in-cell code WARP3D are shown in Figure 6. The normalized emittance at the exit is predicted to be less than 0.7π mm-mrad.

	Unit 1	Unit 2	Unit 3	Unit 4
Length, cm	30	46	46	46
Quad aperture radius, cm	12	10.5	10.5	10.5
Quad voltage, kV	206	259	308	281

Table 1. Parameters of the 4 quadrupole units in the ESQ section.

Figure 6. WARP3D calculations of the beam envelopes in the injector.

III. REFERENCES

- [1] E.A. Abramyan and V.A. Gaponov, *Atomnaya Energiya* **20**, 385 (1966).
- [2] O.A. Anderson et al., *Proceedings of the 1989 Particle Accelerator Conference*, Chicago, March 20-23, 1989.
- [3] S. Eylon et al., *Proceedings of the 1993 Particle Accelerator Conference*, Washington, DC, May 17-20, 1993.
- [4] E. Henestroza et al., *Proceedings of the 1993 Particle Accelerator Conference*, Washington, DC, May 17-20, 1993.

**DATE
FILMED**

10/04/93

END