2
DOE/PC/88818--14

DOE/PC/88818--14

DE92 018088

TI
- 1 1992

**TWO-STAGE, CLOSE COUPLED
CATALYTIC LIQUEFACTION OF COAL**

FOURTEENTH QUARTERLY REPORT FOR THE PERIOD

1 JANUARY 1992 - 31 MARCH 1992

A.G. Comolli
E.S. Johanson
Theo L.K. Lee
G.A. Popper
R.H. Stalzer

WORK PERFORMED UNDER CONTRACT

DE-AC22-88PC-88818

MASTER

**HYDROCARBON RESEARCH, INC.
100 OVERLOOK CENTER, SUITE 400
PRINCETON, NEW JERSEY 08540**

APRIL 1992

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED
JR

**TWO-STAGE, CLOSE COUPLED
CATALYTIC LIQUEFACTION OF COAL**

FOURTEENTH QUARTERLY REPORT FOR THE PERIOD

1 JANUARY 1992 - 31 MARCH 1992

**A.G. Comolli
E.S. Johanson
THEO L.K. Lee
G.A. Popper
R.H. Stalzer**

**WORK PERFORMED UNDER CONTRACT
DE-AC22-88PC-88818**

**HYDROCARBON RESEARCH, INC.
100 OVERLOOK CENTER, SUITE 400
PRINCETON, NEW JERSEY 08540**

APRIL 1992

PRINTED IN THE UNITED STATES OF AMERICA

AVAILABLE FROM:

**National Technical Information Center
U.S. Department of Energy
5285 Port Royal Road
Springfield, Virginia 22161**

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendations, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

TABLE OF CONTENTS

	<u>PAGE</u>
ABSTRACT	1
SUMMARY	2
INTRODUCTION	3
TASK 2 - PROCESS MODELLING	4
TASK 4 - MINI PDU SCALE -UP	6
SCHEDULE	15
APPENDIX	17

PENN STATE LETTER

LIST OF FIGURES AND TABLES

<u>FIGURE</u>	<u>PAGE</u>
1 REVISED CC-CTSL SCHEDULE	16

TABLE

1 PETROGRAPHIC AND REFLECTANCE ANALYSES - RUN 227-63 (CC-6)	5
1 MATERIALS FILTERED IN TWILL SCREEN TESTS	10
2 RESULTS OF TWILL TEST 1	11
3 RESULTS OF TWILL TEST 2	12
4 RESULTS OF TWILL TEST 3	13
5 RESULTS OF TWILL TEST 4	14

ABSTRACT

This quarterly report covers activities of the Two-Stage, Close-Coupled Catalytic Liquefaction of Coal program during the period January 1, - March 31, 1992, at Hydrocarbon Research, Inc. in Lawrenceville and Princeton, New Jersey. This DOE contract period is from October 1, 1988 to September 30, 1992.

The overall purpose of the program is to achieve higher yields of better quality transportation and turbine fuels and to lower the capital and production costs in order to make the products from direct coal liquefaction competitive with other fossil fuel products.

The quarterly report covers work on Laboratory Testing, PDU Activities and Administration.

SUMMARY

The major effort in the 1st quarter of 1992, was in Task 4 "Mini-PDU Studies". The PDU was started-up to demonstrate extinction recycle operations on Black Thunder Mine in the fourth quarter of 1991 coal using a vertical leaf filter. Several obstacles to operation were encountered, including welding, pumping and filtration problems. The filter feed pump could not be repaired after various attempts causing a shut-down of operations.

While repairs were being made to the filter feed pump and filter, several small scale (1 ft²) filtration tests were run to confirm operability of the scaled up 50 ft² filter.

Reflectance measurements on Illinois #6 coal by Penn State were correlated with Bench Scale modelling results.

INTRODUCTION

The studies conducted in this the fourteenth quarterly report of Contract No. DE-AC22-88PC88818, is reported by task and in sequence.

Task 1 is the Management Plan. Task 2 is for Laboratory Studies and includes microautoclave and microreactor work. Task 3 is for Bench-Scale studies. Task 4 is for Mini PDU Scale-up. Task 5 is the Technical Assessment, including Modelling, Design and Economics. Task 6 is Administration.

The contract period was originally October 1, 1988, to September 30, 1991, and has been extended to September 30, 1992.

TASK 2 - PROCESS MODELLING

Samples of the oil-agglomeration cleaned and run-of-mine Illinois No. 6 coal used in Run 227-63(CC-6), and the solids products from the run, were submitted to Penn State for petrographic and reflectance determinations. A copy of their report is appended.

Table 1 is our interpretation of these analyses, in terms of apparent degree of reaction in the Run 227-63(CC-6) operations of the five reflectance cohorts which were reported by Penn State. They present an interesting pattern in that the low reflectance materials, corresponding to vitrinite, were very highly converted (98.0-99.6%). The intermediate reflectance materials, more less liptinite and semi-inertinite, were appreciably converted (80-92.5%), and highest reflectance materials, corresponding in quantity to inertinite, were converted to a degree, about 60%. The pattern of the change in conversion of the various cohorts between Periods 4 and 9 of the run, where the conversion severity was increased by raising the second stage temperature 10°F and lowering ratio of PFL recycle, indicates:

- A) Cohorts up to 1.0% reflectance(vitrinite) are virtually completely convertible;
- B) Cohorts of 1.0 to 2.5% reflectance(liptinite and semi-inertinite) are converted to a degree, which is effected by reaction severity. The increase in conversions of these cohorts with increased reaction severity corresponds closely to first order kinetics, assuming that the cohorts are completely convertible;
- C) Cohorts above 2.5% reflectance (inertinite), while reactive to a degree, contains a component which is apparently unaffected by process severity and is essentially unreactive, amounting to about 2.0% of the cleaned coal and 2.6% of the run-of-mine coal. This proportion of unreactive coal is close to the values, 3-4%, indicated by correlation of the coal conversion data from CTSL operations on Illinois No. 6 coal.

Similar reflectance measurements are to be obtained for Black Thunder Mine coal and its first and second stage products in CTSL operations.

TABLE 1**PETROGRAPHIC AND REFLECTANCE ANALYSES - RUN 227-63(CC-6)****Coal Feeds and Product Solids**

Coal Feed	--- Coal Feeds -----		----- Product Solids -----		
	HRI 5715 Run-of-Mine	HRI 5716 Cleaned	Period 4 --- Cleaned ---	Period 9	Period 12 Run-of-Mine
Petrographic: Macerals					
V% Ash-Free					
Vitrinite	88.7	88.7			
Liptinite	2.0	2.5			
Semi-Inertinite	4.2	3.2			
Inertinite	5.1	5.6			
Reflectance Analysis, V%					
0.00-0.49% Reflectance	27.0	36.5	9.0	3.5	8.5
0.50-0.99% Reflectance	59.0	45.5	4.5	5.0	3.0
1.00-1.99% Reflectance	6.5	8.5	31.0	31.0	32.5
2.00-2.49% Reflectance	2.0	4.0	19.0	14.5	14.0
2.50-5.00% Reflectance	5.5	5.5	36.5	46.0	42.0
Percent of Original Coal					
Total			5.5	4.6	6.3
0.00-0.49% Reflectance			0.50	0.16	0.53
0.50-0.99% Reflectance			0.25	0.23	0.19
1.00-1.99% Reflectance			1.70	1.43	2.05
2.00-2.49% Reflectance			1.04	0.64	0.88
2.50-5.00% Reflectance			2.01	2.11	2.64
Conversion, %					
Total			94.5	95.4	93.7
0.00-0.49% Reflectance			98.6	99.6	98.0
0.50-0.99% Reflectance			99.4	99.5	99.7
1.00-1.99% Reflectance			80.0	92.5	68.5
2.00-2.49% Reflectance			74.0	84.0	56.0
2.50-5.00% Reflectance			63.4	61.6	52.0

Run63petro.tab

TASK 4 - MINI PDU SCALE UP

Filtration Tests Using Bench Unit Filter

Because of the failure to obtain any filter cake in the attempted operation of 75 square foot leaf filter during the Process Development Unit operations of Run 260-03 during November, the filtering effectiveness of the twill screen used in that filter was evaluated using the 13 3/8" diameter horizontal plate filter of the CTSL Bench Unit.

This program consisted of four runs, the first of which filtered a blend of Cellite 560 (Johns Manville) filter aid of 55 microns median particle size and a 550-975°F coal liquefaction distillate, and last three test filtered in various modes the product slurry obtained at the end of Run 260-03, which consisted of partially converted coal solids and the process derived oil at that stage of the run.

These runs demonstrated that the twill screen could give effective clarification of the process derived slurry, but that there was appreciable escape of solids at the beginning of the filtration cycle before effective bridging of the screen holes was achieved, and complete clarification was obtained. Operating options were considered that could accommodate this factor, either allow the unfiltered solids to return to the process, or return the poorly filtered portion directly to the filter feed tank. In either case the escaping solids would be retained as filter cake in the subsequent filtrations. A filter operating cycle appears feasible that will produce a filtrate containing less than 1 W% solids with a practical filtration time.

Filtration Test Feeds

Table 1 summarizes the analyses of the Cellite filter aid and of the PDU slurry, designated L-772, that was used in these tests. The Cellite with a median particle size of 55 microns and less than 10 W% finer than 10 microns, was larger than the apparent particle size of the solids in L-772, which contained over 60 W% material finer than 10 microns. The oil constituent of L-772 was relatively light, containing only 8.3 W% of 975°F+ residuum. The solids content of the filter feed, 16.8 W%, was higher than that expected in equilibrium operations of the PDU, 11.2 W%, and had a relatively low proportion of ash, corresponding to about 76 % conversion of the coal that had been fed to the PDU operation.

Filtration Test Conditions

The filtration quantities used for the tests correspond to the expected amount that would be filtered in the PDU operation on a four hour cycle, namely 12 lbs/square foot of filter area. The filtration test temperature, about 250°F, which is the temperature level generally used in filtrations during Bench Unit operations, to limit problems with open handling of the feed and product materials. The PDU leaf filter will be operated at about 570°F. The pressure of these test filtrations with the L-772 slurry was 110 psig as planned in the PDU operations.

Twill Screen Characteristics

The Twill Screen consists of a warp of pairs of abutting straight wires over which are alternately woven single strands of the wire. The wires are about 0.19 mm in diameter, and the spacing of the warp pairs is about 1.08 mm. The approximate size of the minimum free area for spherical solids passage is about 0.1 mm (100 microns).

Filtration Twill Test 1

Table 2 summarizes the results of Twill Test 1, in which 15 W% cellite in the distillate oil was filtered. The filtration was very rapid, but filter cake was produced, 22.6 W% of the total feed. Allowing for the usual amount of oil retention on filter cakes, the quantity of filter cake corresponds to about 90% retention of the cellite solids.

Filtration Twill Test 2

Table 3 summarizes the results of Twill Test 2, which was a single pass filtration of the L-772 slurry produced during the PDU operations. Here, there was effective, if not complete, filtration of the slurry with a 76.2% of the solids retained as filter cake, and the balance of the solids remaining in the filtrate, which contained 5.5 W% solids. The filtration time was 74 minutes, which considering the relatively low temperature of the filtration test, could be accommodated in four-hour cycle planned for the PDU leaf filter. However, if the solids-containing filtrate were returned to the process, to obtain complete solids removal from the process this additional solids loading would ultimately have to be retained as filter cake. It is estimated that filtration times would be approximately twice as great when complete solids removal is attained after recycling the solids to the process. However, with the filtration in the PDU Leaf Filter at 550°F filtration times would shorten in proportion to the decrease in viscosity.

The filtration times noted above are for a liquid corresponding to the liquid component of the L-772, which is lighter than the prospective liquid that will be filtered during equilibrium operations in the PDU. However, it is planned to operate the leaf filter at about 550°F, which will probably result in a viscosity that is lower than that of the L-772 filtrate at 250°F. The analyses of the L-772 liquid and the liquid feed to the filter in the PDU operations are as follows:

	L-772	PDU FILTER FEED
IBP-450, W%	0.0	0.3
450-550°F, W%	0.0	1.8
550-650°F, W%	20.4	4.9
650-750°F, W%	42.4	19.4
750-850°F, W%	19.9	27.3
850-975°F, W%	9.0	16.6
075°F+, W%	8.3	29.7
Estimated Viscosity, cps		
250°F	3.6	12.2
550°F	0.51	0.94

This analysis indicates that the filtration at 550°F during equilibrium PDU operations should take about one-fourth as long as the Twill Test filtrations. These adjustments project a filtration time for the PDU Leaf Filter of about 40 minutes if the filtrate containing 5.5 W% solids were recycled through the process.

The particle size distribution of the solids remaining in the filtrate was determined as:

Particle Size (US Sieve)

> 105 micron	0.7 W%
74-105 micron	4.0
44-74 micron	3.7
20-44 micron	10.8
10-20 micron	4.3
< 10 micron	76.5

There was some increase in the proportion of -10 micron material from the 62 W% in the filter feed although some of the larger particles were present also.

Filtration Twill Test 3

Table 4 summarizes the results of Twill Test 3, which was a two pass filtration of the L-772 slurry produced during the PDU operations, where the first pass filtrate was returned to filter through the filter cake that was left in place after the first pass. Virtually all of the solids were removed from the final filtrate, which contained about 0.2 W% solids, which represented 99.2% solids removal. The first pass filtration was somewhat more effective, producing a filtrate containing 4.1 W% solids, than the similar filtration of Twill Test 2. However, the filtration time for the first pass test of Twill Test 3 was greater than during Twill Test 2, 113 minutes against 74 minutes. The second pass filtration was even twice as long, at 238 minutes, which is consistent with the fact that in the second pass the filtrate had to pass through almost the entire filter cake, while in the first pass it had to pass through the progressively accumulating filter cake. Nominally, such combined first and second pass filtrations in the PDU Leaf Filter would take about 90 minutes which would possibly present problems in fitting in the four-hour cycle planned which involves washing, drying and recovering the filter cake.

Filtration Twill Test 4

Table 5 summarizes the results of Twill Test 4, which was also a two pass filtration of the L-772 slurry, but using only 25% of the total feed for the first pass filtration. The first pass filtrate was returned to the filter along with the balance of the filter feed through the filter cake that was left in place after the first pass. A high proportion of the solids were removed from the final filtrate, which contained 0.9 W% solids, which represented 96.5% solids removal. The first pass filtration was very rapid, nominally taking only 1 minute, which is consistent with the low amount of cake accumulation in that phase of the test, apparently only about one-tenth of the solids that were contained in the first pass feed. Nevertheless, this "pre-coat" was sufficient to result in the high solids removal in the second pass filtration.

The second pass filtration time, 135 minutes, was higher than the times of the first pass filtrations of either Twill Test 2 or Twill Test 3, but it is consistent with the higher filter cake retention of Twill Test 4. On a correlated basis, the filtration time for Twill Test 4 was intermediate between those of the other two Twill Tests. Adjustment of the results of Twill Test 4 to projected conditions for the PDU Leaf Filter indicates a filtration time of about 50 minutes.

TABLE 1**MATERIALS FILTERED IN TWILL SCREEN TESTS****Cellite 560**

Size	W%	Cumulative
Finer than 4 microns	3.3	3.3
4-8 microns	2.6	5.9
8-16 Microns	6.2	12.1
16-32 microns	19.9	32.0
32-64 microns	35.5	65.5
64-96 microns	26.9	82.4
96-128 microns	13.2	95.6
128-196 microns	4.4	100.0

Dry Bulk Density 16.0 lbs/ft³

Chemical Analysis

SiO ₂	89.6 W%
Al ₂ O ₃	4.0
Na ₂ O + K ₂ O	3.3
Fe ₂ O ₃	1.3
CaO	0.5
Other	1.0

L-772 Slurry From PDU Operations**Solids**

Total, W%	16.8
Ash (SO ₃ -Free), W%	3.8
Unreacted Coal, W%	13.0
Particle Size (US Sieve)	
> 149 micron	0.5
105-149 micron	0.3
74-105 micron	1.5
44-74 micron	3.5
20-44 micron	12.4
10-20 micron	19.5
< 10 micron	62.3

Oil Composition

Gravity, API	16.0
Distillation	
I ₃ P	536
5 V%	591
10 V%	618
20 V%	644
30 V%	666
40 V%	687
50 V%	708
60 V%	730
70 V%	756
80 V%	807
90 V%	938
92 V%	975
975 F+, W%	8.3

Viscosity at 250 F (est) 3.8 cps

TABLE 2

RESULTS OF TWILL TEST 1

Charge, grams	
Cellite 560	700
L-769 500-975 F Distillate	4000
Filtration Conditions	
Temperature, F	245
Pressure, Psig	60
Filtration Time, Minutes	1
Recovery, grams	
Filter Cake	1064
Filtrate	3480
Total	4464
Unaccounted	236

TABLE 3**RESULTS OF TWILL TEST 2**

Charge, grams	
L-772	5417
Filtration Conditions	
Temperature, F	328 (Filter Top Temp.)
Pressure, Psig	110
Filtration Time, Minutes	74
Recovery, grams	
Filtrate	3964
Filter Cake	1357*
Unaccounted	96
Solids Content of Filtrate, W%	5.47
Solids in Charge, Grams	910
Solids in Filtrate, Grams	217
Solids Removal, W%	76.2

* A thin layer of congealed oil remained on cake.

TABLE 4**RESULTS OF TWILL TEST 3****FIRST PASS FILTRATION**

Charge L-772, grams	5350	
Filtration Conditions		
Temperature, F	250	(Filter Top Temp.)
Pressure, Psig	110	
Filtration Time, Minutes	113	
Recovery, grams		
Filtrate	3739	
Filter Cake		(Remained in place)
Filtrate Sample withdrawn	109	
Solids Content of Filtrate, W%	4.14	

SECOND PASS FILTRATION

Charge, grams		
Recharged Filtrate	3625	
Filtration Conditions		
Temperature, F	247	(Filter Top Temp.)
Pressure, Psig	110	
Filtration Time, Minutes	238	
Recovery, grams		
Filtrate	3534	
Filter Cake	1654	
First Filtrate: Sample and Loss	114	
Unaccounted	48	
Solids Content of Filtrate, W%	0.26, 0.10	
Solids Content of Filter Cake, W%	53.30	
Ash In Filter Cake Solids, W%	25.04	

SOLIDS ACCOUNTING

The recovered solids were distributed as follows:

In first pass filtrate sample	4.5 grams
In final filtrate	6.7 grams
In filter cake	881.6 grams
Total	893 grams
Solids in First Pass Feed L-772	893 grams
Solids in total first pass Filtrate	155 grams
Solids retained first pass Filtration	738 grams
Total Filter Cake	882 grams
Solids Removal, First Pass	82.6%
Total Two Passes	99.2%

TABLE 5**RESULTS OF TWILL TEST 4****FIRST PASS FILTRATION**

Charge, grams	
L-772	1428
Filtration Conditions	
Temperature, F	242 (Filter Top Temp.)
Pressure, Psig	110
Filtration Time, Minutes	1
Recovery, grams	
Filtrate	977
Filter Cake	(Remained in place)
Filtrate Sample withdrawn	107
Solids Content of Filtrate, W%	22.59

SECOND PASS FILTRATION

Charge, grams	
Recharged Filtrate	(870)
L-772	(3907)
Total	4777
Filtration Conditions	
Temperature, F	250 (Filter Top Temp.)
Pressure, Psig	110
Filtration Time, Minutes	135
Recovery, grams	
Filtrate	3576
Filter Cake	1545
First Filtrate: Sample	107
Unaccounted	107
Solids Content of Filtrate, W%	10.90
Solids Content of Filter Cake, W%	54.86
Ash, W% of Filter Cake Solids	24.44

SOLIDS ACCOUNTING

In first pass filtrate sample	24 grams
In final filtrate	32 grams
In filter cake	840 grams
Total	904 grams
Solids in First Pass L-772	241 grams
Solids in total first pass Filtrate	221 grams
Solids retained first pass Filtration	20 grams
Solids Removal, first pass	8.3%
Solids Removal, two passes	96.5%

TASK 4 - MINI-PDU SCALE-UP

UNIT OPERATIONS

During the first quarter of 92 the filter feed pump and filter system were undergoing modification and repair with the longest lead item being the retrofit of the pump with a mechanical seal. Major changes to the filter included the following:

1. Addition of a recycle line for filtrate return to the feed tank.
2. Installation of a differential pressure tap across the filter leaves.
3. Installation of gaskets between leaves and the end spool piece to prevent bypassing.
4. Repipe the inlet line to the bottom filter inlet.

SCHEDULE

Following confirmation of proper pump and filter operation in April, a PDU start-up date the week of May 11th is anticipated.

DATE: 3/31/92

[illegible]

APPENDIX

PENNS STATE

Energy and Fuels Research Center

(814) 865-6543
(814) 865-6545

513 Deike Building
The Pennsylvania State University
University Park, PA 16802

Februaury 7, 1991

Mr. Edwin S. Johanson
Hydrocarbon Research, Inc.
P.O. Box 6047
New York & Puritan Avenues
Lawrenceville, NJ 08648

Dear Mr. Johansen,

Attached is a copy of my report on the series of CC-6 coals and residues. This report will be incorporated into our next quarterly report to DOE. If you have any questions concerning the data or interpretation, please do not hesitate to call me.

I have begun working on the coals and residues from runs with Otisca cleaned and uncleaned coals. At this point I do not expect to get interesting results from these materials.

Sincerely,

Alan Davis

AD:ca

cc: G. Mitchell

REPORT ON HRI RUN CC-6
TO DETERMINE EFFECTS OF USING
OIL-AGGLOMERATION CLEANED COALS

Evaluation of the HRI Liquefaction Processing of Oil Agglomerated Cleaned
Illinois #6 Coal

As discussed in the previous quarterly technical progress report, Hydrocarbon Research, Inc. submitted for petrographic evaluation five coal or coal residue samples tested in program Run CC-6, operating identification Run 227-63. The samples were of uncleaned (LO-5466) Illinois #6 feed coal, feed coal cleaned by oil agglomeration (LO-5465), the residue of a CTSL run with uncleaned feed (LO-5464), the residue of a run with oil agglomerated cleaned coal (LO-5462), and the residue of a run under more severe conditions using the same cleaned coal feed. All samples were submitted as oil-free (THF washed) material.

Table I contains the vol. % mineral-free petrographic analyses of the uncleaned and cleaned feed coals. It is apparent that there is negligible difference in the proportions of the three maceral groups between the two feed samples. So, while the oil agglomeration cleaning was successful in reducing the ash from 15.2 to 4.6%, this operation did not produce any selective separation of macerals.

Figs 1-5 are the printouts of 200-point reflectograms generated on the vitrinite + inertinite components of the five samples. These figures should enable any significant trends in the maceral compositions of the coal and residue samples to be detected. The reflectograms of the two feed samples show that the vitrinite of these samples is concentrated at reflectances of 0.4-0.7%. Above this range the reflectances show a wide

spread of readings for the semi-inertinite (intermediate values) and inertinite (higher values) components. The similarity in the reflectograms of the two feed coals mirrors the very similar petrographic compositions of these samples.

For easier comparison of the reflectance distributions, values have been grouped into four reflectance ranges in Table 1. It is obvious that while most of the vitrinite of the feed samples has reflectance values in the two lowest reflectance groups (82-86%), there is little (8.5-11.5%) material with these characteristics remaining in the residues. A small amount of vitrinite has been able to pass unconverted through the reactor. If the run had been entirely successful, none of this material should remain. The reduction in the material reporting to these groups from the residue of run LO-5463 (8.5%) especially in the lowest reflectance group (0-0.49%), indicates that the more severe processing of this run has successfully improved the efficiency of vitrinite conversion. Moreover, the same residue contains the greatest proportion of material in the highest reflectance category (2.50-5.00%). Apparently the residue of the most severe run contains somewhat more condensed material than either of the other residues; this may indicate that not only has the vitrinite undergone more successful hydrogenation, but also that some of the lower reflecting semifusinite may have undergone dissolution.

Table 1. Petrographic and Reflectance Analyses - HRI Run CC-6

	LO-5466	LO-5465	LO-5464	LO-5462	LO-5463
	Feed-Uncleaned	Feed-Cleaned	Run-Uncleaned	Run-Cleaned	Run-Cleaned (Severe)
MACERAL ANALYSIS					
Vitrinite, %	88.7	88.7			
Liptinite, %	2.0	2.5			
Semi-Inertinite, %	4.2	3.2			
Inertinite, %	<u>5.1</u>	<u>5.6</u>			
	100.0	100.0			
REFLECTANCE ANALYSIS					
0.00-0.49%	27.0	36.5	8.5	9.0	3.5
0.50-0.99%	59.0	45.5	3.0	4.5	5.0
1.00-1.99%	6.5	8.5	32.5	31.0	31.0
2.00-2.49%	2.0	4.0	14.0	19.0	14.5
2.50-5.00%	<u>5.5</u>	<u>5.5</u>	<u>42.0</u>	<u>36.5</u>	46.0
	100.0	100.0	100.0	100.0	100.0

Figure 1

REFLECTANCE DISTRIBUTIONS FOR VIT+INERT
LO-5466

Mean Random (polariz) Reflectance:

2	0.30	1.00	**
52	0.40	26.00	*****
57	0.50	48.50	*****
12	0.60	6.00	*****
4	0.70	2.00	****
1	0.80	0.50	*
4	0.90	2.00	****
3	1.00	1.50	***
0	1.10	0.00	
3	1.20	1.50	***
1	1.30	0.50	*
1	1.40	0.50	*
0	1.50	0.00	
3	1.60	1.50	***
2	1.70	1.00	**
0	1.80	0.00	
0	1.90	0.00	
0	2.00	0.00	
0	2.10	0.00	
1	2.20	0.50	*
3	2.30	1.50	***
0	2.40	0.00	
0	2.50	0.00	
1	2.60	0.50	*
0	2.70	0.00	
0	2.80	0.00	
0	2.90	0.00	
0	3.00	0.00	
2	3.10	1.00	**
0	3.20	0.00	
2	3.30	1.00	**
0	3.40	0.00	
4	3.50	2.00	***
0	3.60	0.00	
0	3.70	0.00	
0	3.80	0.00	
0	3.90	0.00	
0	4.00	0.00	
1	4.10	0.50	*
1	4.20	0.50	*

Figure 2

REFLECTANCE DISTRIBUTIONS FOR VIT+INERT

HRI LO-5465

Mean Random (polariz) Reflectance:

2	0.30	1.00	**
71	0.40	35.50	*****
81	0.50	40.50	*****
5	0.60	2.50	*****
2	0.70	1.00	**
1	0.80	0.50	*
2	0.90	1.00	**
5	1.00	2.50	*****
2	1.10	1.00	**
0	1.20	0.00	
3	1.30	1.50	***
1	1.40	0.50	*
1	1.50	0.50	*
1	1.60	0.50	*
1	1.70	0.50	*
2	1.80	1.00	**
1	1.90	0.50	*
1	2.00	0.50	*
3	2.10	1.50	***
1	2.20	0.50	*
2	2.30	1.00	**
1	2.40	0.50	*
1	2.50	0.50	*
0	2.60	0.00	
1	2.70	0.50	*
1	2.80	0.50	*
0	2.90	0.00	
0	3.00	0.00	
0	3.10	0.00	
0	3.20	0.00	
3	3.30	1.50	***
0	3.40	0.00	
0	3.50	0.00	
0	3.60	0.00	
0	3.70	0.00	
0	3.80	0.00	
1	3.90	0.50	*
1	4.00	0.50	*
0	4.10	0.00	
1	4.20	0.50	*
1	4.30	0.50	*
0	4.40	0.00	
0	4.50	0.00	
1	4.60	0.50	*

Figure 3

REFLECTANCE DISTRIBUTIONS FOR VIT+INERT
LO-5464
Mean Random (polariz) Reflectance:

4	0.30	2.00	****
13	0.40	6.50	*****
4	0.50	2.00	****
0	0.60	0.00	
1	0.70	0.50	*
1	0.80	0.50	*
0	0.90	0.00	
3	1.00	1.50	***
3	1.10	1.50	***
5	1.20	2.50	*****
5	1.30	2.50	*****
3	1.40	1.50	***
8	1.50	4.00	*****
9	1.60	4.50	*****
16	1.70	8.00	*****
6	1.80	3.00	*****
7	1.90	3.50	*****
10	2.00	5.00	*****
6	2.10	3.00	*****
7	2.20	3.50	*****
2	2.30	1.00	**
3	2.40	1.50	***
4	2.50	2.00	****
2	2.60	1.00	**
5	2.70	2.50	*****
3	2.80	1.50	***
3	2.90	1.50	***
5	3.00	2.50	*****
5	3.10	2.50	*****
3	3.20	1.50	***
6	3.30	3.00	*****
4	3.40	2.00	****
5	3.50	2.50	*****
2	3.60	1.00	**
3	3.70	1.50	***
3	3.80	1.50	***
3	3.90	1.50	***
5	4.00	2.50	*****
3	4.10	1.50	***
2	4.20	1.00	**
3	4.30	1.50	***
4	4.40	2.00	****
1	4.50	0.50	*
2	4.60	1.00	**
2	4.70	1.00	**
3	4.80	1.50	***
3	4.90	1.50	***

Figure 4

REFLECTANCE DISTRIBUTIONS FOR VIT+INERT
LO-5462

Mean Random (polariz) Reflectance:

1	0.20	0.50	*
6	0.30	3.00	*****
11	0.40	5.50	*****
4	0.50	2.00	****
3	0.60	1.50	***
0	0.70	0.00	
1	0.80	0.50	*
1	0.90	0.50	*
2	1.00	1.00	**
3	1.10	1.50	***
4	1.20	2.00	****
5	1.30	2.50	*****
11	1.40	5.50	*****
8	1.50	4.00	*****
8	1.60	4.00	*****
8	1.70	4.00	*****
7	1.80	3.50	*****
6	1.90	3.00	*****
9	2.00	4.50	*****
11	2.10	5.50	*****
9	2.20	4.50	*****
6	2.30	3.00	*****
3	2.40	1.50	***
4	2.50	2.00	****
5	2.60	2.50	*****
7	2.70	3.50	*****
2	2.80	1.00	**
1	2.90	0.50	*
8	3.00	4.00	*****
4	3.10	2.00	****
7	3.20	3.50	*****
3	3.30	1.50	***
5	3.40	2.50	*****
1	3.50	0.50	*
1	3.60	0.50	*
2	3.70	1.00	**
2	3.80	1.00	**
3	3.90	1.50	***
3	4.00	1.50	***
3	4.10	1.50	***
1	4.20	0.50	*
2	4.30	1.00	**
1	4.40	0.50	*
1	4.50	0.50	*
2	4.60	1.00	**
2	4.70	1.00	**
3	4.80	1.50	***

Figure 5

REFLECTANCE DISTRIBUTIONS FOR VIT+INERT
LO-5463

Mean Random (polariz) Reflectance:

1	0.30	0.50	*
6	0.40	3.00	*****
5	0.50	2.50	*****
4	0.60	2.00	*****
0	0.70	0.00	
1	0.80	0.50	*
0	0.90	0.00	
1	1.00	0.50	*
7	1.10	3.50	*****
1	1.20	0.50	*
6	1.30	3.00	*****
4	1.40	2.00	*****
7	1.50	3.50	*****
8	1.60	4.00	*****
7	1.70	3.50	*****
8	1.80	4.00	*****
13	1.90	6.50	*****
7	2.00	3.50	*****
3	2.10	1.50	***
10	2.20	5.00	*****
4	2.30	2.00	*****
5	2.40	2.50	*****
6	2.50	3.00	*****
5	2.60	2.50	*****
6	2.70	3.00	*****
1	2.80	0.50	*
6	2.90	3.00	*****
7	3.00	3.50	*****
4	3.10	2.00	*****
1	3.20	0.50	*
7	3.30	3.50	*****
6	3.40	3.00	*****
4	3.50	2.00	*****
7	3.60	3.50	*****
4	3.70	2.00	*****
2	3.80	1.00	**
0	3.90	0.00	
4	4.00	2.00	*****
3	4.10	1.50	***
3	4.20	1.50	***
0	4.30	0.00	
3	4.40	1.50	***
4	4.50	2.00	*****
5	4.60	2.50	*****
1	4.70	0.50	*
1	4.80	0.50	*
2	4.90	1.00	**

END

**DATE
FILMED**

9 / 4 / 92