AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

DOE/PC/92109--T5 J-2
2

	DVORSCAK

**DIRECT AROMATIZATION OF METHANE
QUARTERLY TECHNICAL PROGRESS REPORT No. 6**

BD
No Invention
OK to Patc
7-18-94

Prepared for the U.S. Department of Energy Under
Contract No. DE-AC22-92PC92109

by

ALTAMIRA INSTRUMENTS
2090 William Pitt Way
Pittsburgh, PA 15238

Date of Report: May 30, 1994
Date of Contract: September 26, 1992
Anticipated Completion: May 25, 1995
Total Government Award: \$340,930
Program Manager: George Marcelin
COR: Arun C. Bose
Reporting Period: 1-1-94 to 3-31-94

RECEIVED
JUL 24 1994
10:04

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

Executive Summary	i
Objectives	1
Technical Report	1
Introduction	1
Experimental	1
Results and Discussion	2
Current Status	10
Work Planned for Next Quarter	10

LIST OF FIGURES

Figure 1. Effect of ethane flow rate on methane conversion and benzene selectivity for the quenched pyrolysis of methane	6
Figure 2. Effect of quench-water flow rate on conversion, selectivities and yields based on analyzable products	7
Figure 3. Effect of quench-water flow rate on conversion, selectivities and yields based on all products, including "tar"	8
Figure 4. Observed C ₂ -C ₁₀ yields plotted as conversion versus selectivity	9

LIST OF TABLES

Table 1. Summary of qualified runs performed during reporting period	5
--	---

EXECUTIVE SUMMARY

Further experiments have been performed on the quenched pyrolysis of methane. The reaction has been studied in the temperature range of 900 to 1200°C, methane flow rates of 80-1500 Scc/min, and quench water flow rates between 0 and 2000 mL/hour. C₂ -C₁₀ hydrocarbons can be formed in yields as high as 25%, depending on the exact reaction conditions. Heavy products were formed but these were found to diminish under certain quench conditions.

OBJECTIVE

The thermal decomposition of methane shows significant potential as a process for the production of higher unsaturated and aromatic hydrocarbons when the extent of the reaction is limited. Preliminary experiments have shown that cooling the product and reacting gases as the reaction proceeds can significantly reduce or eliminate the formation of solid carbon and heavier ($C_{10}+$) materials. Much work remains in optimizing the quenching process and this is one of the goals of this program. We will also study means to lower the temperature of the reaction as this will result in a more feasible commercial process due to savings realized in energy and material of construction costs. The use of free-radical generators and catalysts will be investigated as a means of lowering the reaction temperature thus allowing faster quenching. It is highly likely that such studies will lead to a successful direct methane to higher hydrocarbon process.

TECHNICAL REPORT

INTRODUCTION

During the sixth quarter we continued the experiments in trying to optimize the quenched pyrolysis reaction. A significant accomplishment during this quarter has been the attainment of benzene yields in the order of 12-15% and $C_2 - C_{10}$ "analyzable" hydrocarbons in the order of 25% during quenched pyrolysis.

EXPERIMENTAL

The quenched pyrolysis of methane has been studied at temperatures between 900 and 1200°C, methane flows of 80-1500 Scc/min, and quench water flows between 0 and 2,000 Scc/hour. The experimental procedure was as follows: The reactor furnace was brought up to the desired temperature while helium flowed through the outer tube of the reactor. Once the desired

temperature was reached, methane flow was started, but bypassing the reactor. At least three analyses of the methane feed were obtained. The methane was then diverted into the reactor and the helium flow cut-off. After five minutes of reaction an effluent sample was taken.

Analysis was performed by on-line gas chromatography using a Varian 3400 GC equipped with an Alumina-GS Microbore capillary column. This arrangement is suitable for resolving all hydrocarbons of interest between methane and naphthalene. Individual components were identified by comparison of retention times with known standards. Peak area was taken to be proportional to the number of carbons in each component times a response factor taken from the literature. The formation of heavy products was calculated by the difference between the products detected in the analysis and the methane conversion.

RESULTS AND DISCUSSION

Difficulties Encountered

We continued to experience problems related to plugging of the outlet lines and GC sampling valves due to condensation of heavy products. However, the frequency of these problems has greatly diminished since we last reported them as a consequence of the modifications that were made relating to heat tracing of the outlet lines (see Quarterly Technical Report No. 5). We have further modified the system by installing a separate temperature control in the separator which is now maintained at a slightly lower temperature than the remaining outlet lines. This hopefully serves to condense some of the heavier materials prior to reaching the analytical lines. No plugging has been experienced since this latest modification was implemented.

Methane Pyrolysis

Table 1 summarizes the results of the qualified runs conducted through the sixth quarter of this project. Under the experimental conditions evaluated thus far, only a narrow

temperature range is suitable for aromatics production. At temperatures less than 1000°C, little conversion is observed, while temperatures much higher than 1200°C results in almost complete conversion of the methane to solids. Thus, most of our work has concentrated in studies at 1100°C.

Runs 50-1, 50-2, 51-1, 52-1, and 52-2 were all performed under similar conditions. Comparison of these results shows good overall reproducibility.

Figure 1 shows the effect of methane flow rate, i.e., residence time, on the conversion of methane and the selectivity to benzene under a constant quench-water flow of 62 and 126 mL/hour. The data point at zero methane flow was obtained from the thermodynamic calculations reported in the Second Quarterly Report. Other plotted results have been reported in previous quarters and thus are not found in Table 1. It can be noted that as residence time increased total methane conversion decreased, while the selectivity for benzene appeared to go through a maximum at a methane flow rate of ca. 500 Scc/min. Interestingly, no significant effect was observed due to this doubling in the quench-water flow rate.

The effect of quench was further studied at 1100°C and a methane flow rate of 500 Scc/min, i.e., near the selectivity maximum noted in Figure 1. Figures 2 and 3 summarize the results of these experiments. Figure 2 details the conversion, selectivity, and yields of analyzable products, i.e., C₂ - C₁₀, for quench-water flow rates between 63 and 372 mL/hr (Run 51). No significant difference in methane conversion or selectivities are observed when only the analyzable products are considered and these are used as the basis for calculating the conversion. However, as shown in Figure 3, total conversion was observed to decrease at higher water flow rates and this decrease was directly associated with the "tar" or heavy products formed. In other words, the yield (conversion x selectivity) of individual products in the C₂ to C₁₀ range did not change appreciably. Thus, it appears that the effect of quenching is minimal at low water

flow rates, while at higher flow rates it serves to reduce the formation of heavy materials without significantly affecting the overall yields of the useful products. At water flow rates of 250 to 372 mL/hour, the yield of "tar" produced is only on the order of 10%, approximately one-third of that produced in the absence of quench. As reported in the Fifth Quarterly Report, extremely high quench-water flow rates (2000 mL/hour) completely inhibits the reaction. This last observation was further confirmed this quarter (Run 46-2).

In all cases the primary product observed was benzene, with smaller amounts of ethylene and acetylene. Preliminary experiments have shown that higher temperatures lead to a decrease in the ethylene yield and an increase in acetylene.

Figure 4 shows some selected results plotted in terms of methane conversion versus selectivity for $C_2 - C_{10}$ products. Also shown for reference are a series of "isoyield" lines. This type of plot has been used extensively in evaluating the results of oxidative coupling processes, where it is normally agreed that a minimum 25% yield of selective products, which has not been achieved, is necessary for commercial application.

In contrast to oxidative coupling, the quenched pyrolysis process has already resulted in yields of useful hydrocarbons above the 25% target. It is hoped that further optimization of the process will increase these yields even further.

Table 1
Summary of qualified experimental runs
performed during reporting period

Run Number	Temp, °C	CH ₄ flow, Scc/min	Water flow, mL/hr	% Conv.	C Selectivities		
					Benzene	C ₂ -C ₁₀	"Tar"
45-1	1100	267	0	47	34	60	40
45-2	1100	360	0	43.2	39	71.5	28.5
45-3	1100	534	0	35.2	47	87.4	13.6
45-4	1100	788	0	31.6	54	92	8
46-2	1100	500	>2000	<4	0	0	0
49-1	1000	500	354	34	39.9	76	24
49-2	1000	500	354	33.5	42.5	82	18
50-1	1100	500	250	35	36	77	23
50-2	1100	500	250	33	32	76	24
51-1	1100	500	250	37	34	71	29
51-2	1100	500	63	58	22	45	55
51-3	1100	500	126	56	23	47	53
51-4	1100	500	372	39	32	69	31
52-1	1100	500	250	38	33	70	30
52-2	1100	500	250	37	34	72	28
53-1	1100	820	186	23	26	73	27
53-2	1100	1000	63	28	23	67	33
57-1	1100	1500	250	13.5	24	83	17

Figure 1. Effect of methane flow rate on methane conversion and benzene selectivity for the quenched pyrolysis of methane.

Figure 2. Effect of quench-water flow rate on conversion, selectivities, and yields, based on analyzable products, for the pyrolysis of methane at 1100°C and a methane flow rate of 500 Scc/min. "X" denotes conversion.

Figure 3. Effect of quench-water flow rate on conversion, selectivities, and yields, based on all products including "tar", for the pyrolysis of methane at 1100°C and a methane flow rate of 500 Scc/min. "X" denotes conversion. Legend as in Figure 2.

Figure 4. Observed C_2 - C_{10} yields during methane pyrolysis plotted as conversion versus selectivity. Dotted lines represent yields as annotated on top of the plot.

Engineering Analysis

Burns and Roe Services Corporation has been interacting with project personnel in order to define target yields necessary for commercial utilization of this process. A preliminary engineering analysis is currently in progress at BRSC and will be reported to DOE as soon as completed.

CURRENT STATUS

The project is proceeding slightly behind schedule due to the number of experimental difficulties with the reactor system and the slow turn-around that we have had with outside repairs. We believe that these difficulties are largely solved and expect to make up the time lost in the next few months.

WORK PLANNED FOR NEXT QUARTER

Next quarter we expect to conclude the experimental work on the gas-phase aromatization of methane by quenched-pyrolysis. We will extend the study to higher temperatures by using inert gas dilution of the feed. We will also begin the effort in assisted pyrolysis by addition of free-radical producers and catalysts.

DATE

FILMED

9 / 26 / 94

END