2
DOE/SF/18440--1

DE92 018747

**A New Diagnostic Technique to Simultaneously Measure the Electron
Temperature, Ionic Charge State, and Plasma Density near the Critical
Surface in Laser-Plasma Interaction Experiments**

**Final Report
DE-FG03-90SF18440**

by

**Katsu Mizuno, and J. S. DeGroot, UC Davis
W. Seka, LLE, and
R. P. Drake, LLNL**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

for

TABLE OF CONTENT

I.	Summaries	3
II.	Experimental Arrangements	4
III.	Measurements of the Ion Acoustic Decay Instabilities with Various Ionic Charge State Z	5
	(A) Second Harmonic Spectrum	
	(B) The IADI Threshold	
	(C) The Stokes Intensity vs Target Material	
	(D) The Spectral Width	
	(E) Measurements of the Ionic Charge State Z	
	(F) Measurements of the Plasma Flow Effects	
IV.	Theoretical Considerations	9
	(A) The IADI Threshold in High Z Plasma	
	(B) The Scaling of the IADI	
V.	References	13
VI.	Figure Captions	15

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

I. Summaries

We have studied the dependence of the second harmonic signature of the ion acoustic decay instability on the target material in laser produced plasmas. Well-defined Stokes peaks were observed. The Stokes peaks were especially sharp for high Z targets. The threshold of the IADI was quite low ($\approx 2 \times 10^{13}$ W/cm²) even in high Z plasma. It increased only weakly with increasing the atomic number. On the other hand, the Stokes intensity decreased strongly with increasing atomic number. Linear theory, combined with the results of hydrodynamic-computer-simulation (LASNEX) calculation, explained our experimental results fairly well.

The effective laser intensity is strongly reduced by the increased collisional-damping of electron plasma wave in high Z plasma, so that the Stokes intensity was reduced strongly. Hence, strong electron heating due to the IADI is less likely in high Z plasma. On the other hand, in the context of the threshold, the collisional damping effect of the electron plasma wave is canceled due to the opposite trend of the damping of the ion acoustic wave which decreases with ZT_e/T_i . The low-threshold, and the sharp and steady spectrum make the IADI a good diagnostic of local plasma conditions near the critical surface for high Z plasma.

The ionic charge state Z is estimated by measuring the ion acoustic wave frequency of the most unstable wave excited by the IADI. For Mo plasma, we had measured value of $Z=30$.

We can also estimate the plasma density of the instability region using Bohm-Gross dispersion relation of the plasma wave. We have obtained plasma density $N_e/N_c = 0.86$.

We have estimated plasma flow effects on the IADI by measuring the angular distribution of the IADI emission. Our results indicate that the flow effect is not important for the IADI in our experiments.

II. Experimental Arrangements

The experiments were conducted using the GDL laser system at the Laboratory for Laser Energetics (LLE), University of Rochester, and the Janus (Phoenix) laser system. Figure 1 shows the schematic of the GDL experiments. Typical parameters are: laser wavelength $\lambda_L = 1.06 \mu\text{m}$, laser pulse length $\tau_L = 0.8 \text{ nsec}$, laser energy $E_L < 100\text{-}200\text{J}$, laser spot diameter $350 \mu\text{m}$, and typical laser intensity $I_L = 10^{12}\text{-}3 \times 10^{14} \text{ W/cm}^2$. The laser light was focused through an $f/3$ lens so as to normally irradiate a planar target while converging. The experiments were performed with various target materials; CH, Al, Cu, Mo, and Au. In all cases, the targets were thick enough (typically $50 \mu\text{m}$ thickness) that no burnthrough was expected.

We monitored the emission spectrum near the second harmonic ($2\omega_0$) of the incident laser, collected at 135° and 180° from the average wavevector of the incident laser and in the plane of the laser electric field. A focusing mirror was used to collect the emission near the second harmonic. The signal was fed into a spectrometer, and the resulting spectrum was streaked using a streak camera (resolution of $1 \text{ \AA}$ and 30 ps typical). The data were recorded on Kodak film, and digitized and processed using computers in LLE, and LLNL. The signal was detected over a small region of the film near the center, so that the nonuniformity of the detector-field is much smaller than the shot-to-shot fluctuation of the signal.

III. Measurements of the Ion Acoustic Decay Instabilities with various Ionic Charge State Z

(A) Second Harmonic Spectrum

We have measured the time-resolved, second-harmonic spectrum of the incident laser light. Figure 2 displays one such spectrum from a MO target at a laser intensity slightly above the threshold of the IADI. The spectral intensity of the second harmonic signal is plotted vs wavelength and time. The narrow, sharply-peaked feature at the left hand side is $2\omega_0$ signal (at twice the laser frequency), which is attributed to the emission from the electron plasma waves excited by resonance absorption. As discussed in our previous paper, we attribute the right hand side peaks to the emission from the electron plasma waves excited by the IADI. A well-defined Stokes structure (1st and 2nd Stokes peaks) is clearly seen. The time sequence of the excitation of the signals is as follows. The $2\omega_0$ signal is excited first; then, after the $2\omega_0$ intensity reaches a certain amplitude (about 100 psec), the 1st Stokes mode is excited; and then, later, a 2nd Stokes mode is excited. Occasionally, we have observed a 3rd Stokes peak, which is barely seen in Fig. 2. No clear anti-Stokes peak is detected in Fig. 2, as usual. The Stokes peak shifts by $\Delta\lambda$ relative to the $2\omega_0$ peak. The shift, $\Delta\lambda$, is proportional to the frequency of the ion-acoustic wave. The measured value of $\Delta\lambda$ agrees very well with the theoretical prediction of the most unstable mode of the IADI.

We have plotted the time-integrated and time-resolved spectra as a parameter of target material in Fig.3 (A), and (B) respectively. Above well-defined threshold laser intensities for the IADI, Stokes sidebands are observed clearly in curves (a), (b), and (c). The shape of the Stokes mode depends strongly on the target material. For a low Z target such as CH, the spectrum is rather broad (curve (a)). The second Stokes mode is barely distinguishable. Clear, sharp, Stokes peaks are observed for higher Z targets such as Mo or Au. The 1st and 2nd Stokes peaks are clearly distinguishable in curve (b). For the highest Z target (Au), no 2nd Stokes peak is observed although the 1st Stokes mode has a well-defined sharp peak (curve (c)). The total area of the Stokes peak in curves (a,b,c) decreases with increasing the Z of target, indicating that the total intensity of the Stokes mode decreases strongly with higher Z.

The trends in the time-resolved spectrum are consistent with those just discussed. Figure 3 (B) shows a series of contour plots for various target materials. The second-harmonic intensities are shown vs. time and wavelength. For the low Z target, the intensity contour of the Stokes mode is broad. For the highest Z target (Au), the contour is very simple, and steady. On the other hand, the contour shape of the $2\omega_0$ signal barely depends on the target material. For all three cases, the intensity contour of the $2\omega_0$ signal is sharp, strong, and steady. The wavelength calibration shot is shown in the left-hand lower corner of the Fig.3 (B) (a). It is shown that the Doppler shift is negligibly small in our experiments.

(B) The IADI Threshold

We have measured the total intensities of the Stokes peak and the $2\omega_0$ peak, by integrating under the peak in each case, for several laser intensities and for various targets including CH, Al, Cu, Mo, and Au. The threshold for the IADI is defined as the laser intensity above which the Stokes mode is observed, and below which no Stokes mode is observed. Figure 4 (A) shows the measured threshold values vs the Atomic number of the target. The solid (empty) circles are experimental results from Janus (GDL) laser system. Both results of the different devices agree within the observed fluctuations. We find that the threshold of the IADI is quite low ($\approx 2 \times 10^{13}$ W/cm²) even for the high Z target, and increases only weakly with increasing the atomic number. The change in the threshold value is less than 50 %, when the atomic number of the plasma varies from 13 (Al) to 79 (Au). This low threshold and the weak Z scaling agree with the simple theory presented later.

The above experiments are made with the laser spot size of 350 μm . No significant change of the threshold value was seen for high Z target, when the laser spot size increased to 600 μm . Because of the large collisional damping of high Z plasma, the collisional threshold dominated the convective effects. On the other hand, the threshold was significantly reduced with larger-spot-size laser irradiations of low Z (CH) targets.

(C) The Stokes Intensity vs Target Material

The Stokes intensity depends strongly on atomic number of the target. The empty circles show the Stokes intensity vs. atomic number in Fig. 4 (B). The total Stokes intensity is measured for each atomic number at the laser intensity of $I_L = 3.6 \times 10^{13}$ W/cm², which

is approximately twice the IADI threshold. The Stokes intensity decreases strongly with increasing atomic number of the target plasma. For comparisons, we have plotted the intensity of $2\omega_0$ signal with empty triangle, which is measured simultaneously with each Stokes signal. The intensity of the $2\omega_0$ signal depends weakly on atomic number since it is not due to an instability. The error bars indicate the observed fluctuations of the intensity from one experiment to the next. Occasionally, the measured intensity varied more than a factor 2. We attribute the observed Z scaling of the Stokes intensity to the decrease of the growth rate. Later, we will show that the growth rate of the IADI decreases with the atomic number.

We see a quite different trend with higher-intensity laser irradiation. Figure 5 shows the intensity ratio of the Stokes signal to the $2\omega_0$ signal as a function of the laser intensity. For a fixed laser intensity slightly above the threshold, the intensity ratio decreases strongly with the atomic number, being consistent with results shown in Fig. 4 (B). However, the Stokes intensity is a weaker function of atomic number of the target plasma with a higher-power laser irradiation of $I_L = 1-2 \times 10^{14} \text{ W/cm}^2$. For the low Z target with a large growth rate, the Stokes peak quickly reaches a large level (curve (a)). After that, it grows weakly with the laser intensity so that the ratio of the Stokes peak to the $2\omega_0$ peak decreases (curve (a)). On the other hand, for the high Z target with a small growth rate, the Stokes peak is weak near the threshold. It continues to grow with laser intensity over the range measured (curve (b)). It is interesting to notice that the measured intensity ratio happened to approach unity and is weakly dependent on the atomic number at the highest intensities used.

(D) The Spectral Width

The spectral broadening of the Stokes mode is also of interest. It will possibly be relevant to the degree of turbulence of the electron plasma wave excited by the IADI. In order to address this, we have made a following definition. Figure 6 shows a typical second harmonic spectrum of a Cu target. We define the peak value of the Stokes mode as I_p and the minimum value between the Stokes mode and $2\omega_0$ as I_m , as shown. We can then quantify the broadness of the Stokes mode using the ratio I_m/I_p . If I_m/I_p is nearly one (or small), the spectrum is almost flat (or sharp). We will use this parameter to discuss the dependence of the spectral broadening on target material.

Figure 6 (B) shows the I_m/I_p vs laser intensity for several target materials. At laser powers slightly above the threshold, the Stokes peak is sharp, so that I_m/I_p is small. The I_m/I_p increases with the laser intensity. For low Z targets, it increases strongly, indicating that the Stokes spectrum is broad. For CH, I_m/I_p can be as high as nearly unity at relatively high intensities ($I_L \approx 1 \times 10^{14} \text{ W/cm}^2$). On the other hand, I_m/I_p increases slowly with laser intensity for the high Z target. A well-defined Stokes peak is still observed with the high Z target at a laser irradiation of 1×10^{14} (I_m/I_p is as low as ~ 0.5 for Mo target). We attribute these differences to differences in growth rate as is discussed in the next section.

(E) Measurements of the ionic charge state Z

The ionic charge state Z is estimated by measuring the ion acoustic wave frequency of the most unstable wave excited by the IADI. The theoretical formula is obtained from the ion acoustic wave dispersion relation and the Landau damping cut off of the electron plasma wave. $Z = (4.4 \times \Omega_i/\omega_{pe})^2 \times M/m - 3T_i/T_e$ For Mo plasma, we have measured value of $Z=30$.

We can also estimate the plasma density of the instability region using Bohm-Gross dispersion relation of the plasma wave. The plasma density is given by $N_e/N_c = 1 - 3(M/m)(\Delta\lambda/\lambda_{2\omega_0})^2/(Z + 3T_i/T_e)$. We have obtained plasma density $N_e/N_c = 0.86$ by substituting the measured $\Delta\lambda$ into the above equation.

(F) Measurements of the plasma flow effects

In order to study the plasma flow effect on the IADI, we monitored the emission spectrum near the second harmonic ($2\omega_0$) of the incident laser, collected at 135° and 180° from the average wavevector of the incident laser and in the plane of the laser electric field. The IADI emissions are measured simultaneously at 135° and 180° . The average $\Delta\lambda$ of 4 shots (laser intensity is between 1.1×10^{13} - 2.6×10^{13}) is $22.9 \text{ \AA}$ for 135° emission, and $23.1 \text{ \AA}$ for 180° emission. The $\Delta\lambda$ barely depends on the emission angle. Therefore, our experimental results indicates that the plasma flow effect is not important for our measurements of the IADI. The spectrum width of the Stokes mode is estimated from the ratio of the minimum and the peak values. The spectrum width of the 135° emission was about 20% wider than that of the 180° emission.

IV. THEORETICAL CONSIDERATIONS

In this section, we present theoretical estimates of the Z scaling of the IADI. The linear theory combined with the results of hydrodynamic-computer-simulation (LASNEX) calculation, explains our experiments fairly well.

(A) The IADI threshold in high Z plasma

We have observed low threshold values even in high Z plasmas. The theoretical threshold value is functions of electron temperature T_e , the normalized temperature ratio ZT_e/T_i , the plasma-density profile, and collisional attenuation of the laser light. We have found that the threshold depends rather weakly on these parameters, because several effects offset one another.

The first step is to estimate the threshold laser intensity at the instability region. The local threshold laser intensity, corresponding to an amplification of noise by e^5 of the IADI is given by,

$$(I_0 \lambda_L^2)_{th} = 1.1 \times 10^{16} T_e (\text{keV}) [(2/kL)(\Gamma_i/\omega_i)^{0.5} + \Gamma_e \Gamma_i / \omega_e \omega_i] \text{ (W/cm}^2 \cdot \mu\text{m}^2) \quad (1),$$

when the laser is normally incident on an inhomogeneous collisional plasma. The parameters Γ_e , Γ_i , C_s , and L are the damping rates of the electron plasma wave and ion acoustic wave, the ion sound speed, and the plasma scale length at the instability region. The first (second) part of Eq. 1 is the contribution from the convective (the collisional and Landau) damping of the electron plasma wave. The wave number of the ion-acoustic wave is k , which is approximately equal to that of the electron plasma wave in our experiments. The wavenumber of the laser light is much smaller than that of the plasma wave (the ratio is about 1/10 for our experimental parameters), so that the dipole approximation is made to obtain the above equation.

We have found that the IADI threshold of the high Z target can be a weak function of T_e and L as is discussed below. Figure 7 shows the IADI threshold intensity I_{th} vs plasma-scale-length L , for several values of T_e . The values I_{th} , L , T_e are those at the instability region. The I_{th} is calculated for the most unstable mode, $k\lambda_{De} = 0.23$. We used following parameters: the average ionic charge state is $Z = 29$ and the temperature ratio is $T_e/T_i = 1.6$ for a Mo plasma, which are obtained from the LASNEX calculation for the

laser intensity $I_L = 1.8 \times 10^{13} \text{ W/cm}^2$. The damping coefficient, Γ_i/kC_s of ion acoustic wave in a collisional plasma is a weak function of the temperature ratio for the high Z plasma. It is obtained from the numerical calculation result (by C. Randall), and is approximately 4.8×10^{-2} . The collisional, Landau, and convective damping are taken into account for the electron-plasma wave.

Fig. 7 indicates that the IADI threshold intensity depends weakly on T_e and L if L is larger than $15\text{-}30 \mu\text{m}$, and T_e is less than $1\text{-}2 \text{ keV}$. In this parameter regime, collisions are the dominant damping mechanism of the electron plasma wave. The collisional threshold decreases proportional inversely to the square root of T_e , as the electron temperature increases. On the other hand the convective threshold increases proportional to T_e . Hence, the net threshold value, with contributions from the dominant collisional and the small convective damping, is almost independent of T_e . The threshold value changed merely 50 % when T_e varied an order of magnitude from 0.2 to 2 eV , if $L > 15\text{-}30 \mu\text{m}$. Therefore, for a reasonably large scale length, the threshold is basically determined by the uniform-plasma, collisional value.

On the other hand, in the small L case ($< 15 \mu\text{m}$), the convective damping is dominant, so that the threshold value increases strongly with the T_e , if the electron temperature is high ($T_e > 1 \text{ keV}$). For the higher electron temperature ($T_e > 2 \text{ keV}$), the convective loss is the dominant damping mechanism of the electron-plasma wave. Our hydrodynamic computer simulation gives $T_e = 0.8 \text{ keV}$ for flux limiter $f = 0.1$, and 1 keV for $f = 0.03$. The plasma scale length at the instability region depends strongly on the flux limiter. Fig. 8 (B) presents L vs. atomic number for $f = 0.1$ (solid circles) and $f = 0.03$ (empty circles). The plasma is steep ($L \approx 10 \mu\text{m}$) due to the ablative steepening for the inhibited heat flow ($f = 0.03$). The L is large ($\approx 40 \mu\text{m}$) for $f = 0.1$. Therefore, the uniform collisional theory applies for $f = 0.1$, and the convective damping becomes important for $f = 0.03$. Remarkably, both these results turn out to be consistent with the data.

The next step is to estimate the laser intensity at the instability region. The laser intensity is significantly modified by the competition of three trends; the collisional attenuation reduces laser intensity, the swelling effect increases it, and the standing-wave effect increases it when the laser reaches the instability region near the critical surface. Figure 8 (A) shows the ratio of the laser intensity I_0 at the instability region with plasma to the laser intensity there without plasma, I_L . The value I_0/I_L decreases with the atomic number because of the collisional attenuation. Its value depends strongly on the flux

limiter especially for a high-Z plasma. With $f = 0.03$, I_0/I_L is as much as five times of the value with $f = 0.1$, in a Mo plasma (Fig. 8 (A)).

The experimental result of Fig. 4(A) is plotted at two points in Fig. 7, using the calculated values of I_0/I_L and L shown in Fig. 8 (A) and (B). We see that the observed threshold is consistent with the prediction of linear theory for either flux limiter. When $f=0.1$ (solid circle), the threshold is dominated by collisions. In contrast, when $f=0.03$ (open circle), the threshold is dominated by convective loss. Notice that the measured low threshold value for the incident laser intensity I_L is thus justified for the both cases of $f = 0.1$ and $f = 0.03$.

(B) The Scaling of the IADI

In this section, we discuss the Z scaling of the IADI assuming the flux limiter is $f = 0.1$ and thus that collisional effects dominate the threshold behaviour, and that simple, homogeneous-plasma theory may describe the essential features of the experiment. In this case, Eq. 1 shows that

$$I_0 \propto (\Gamma_e/\omega_0) \times (\Gamma_i/kC_S) \quad (2).$$

On the other hand, the IADI growth rate, γ , is proportional to I_0 / Γ_e near the threshold ($\Gamma_i \ll \gamma \ll \Gamma_e$).

The threshold and the growth rate depend on the damping coefficients, which depend largely upon T_e . A simple theory gives an approximate electron temperature scaling law, $T_e \sim (Z I_L \tau_L)^{2/5}$ in the free streaming limit, if the plasma scale length in the coronal region scales as $C_S \tau_L$. Hence, the collision frequency scales as,

$$\nu_{ei} \sim n_e Z^{2/5} / (I_L \tau_L)^{3/5} \quad (3)$$

The collision frequency increases weakly with Z, and decreases with I_L , and τ_L .

Eq. 2 shows that the threshold laser intensity at the instability region is determined by the product of the damping rates of the electron plasma wave and the ion acoustic wave. The collisional damping of the epw, and also the attenuation of the laser light increase with Z. On the other hand, the damping of the iaw decreases with $Z T_e / T_i$. In the plasmas studied

here, these opposite trends turn out to cancel each other, producing a weak dependence of the threshold on the target material. The empty circles in Fig. 8 (C) show the threshold (vacuum) laser intensity $I_{L,th}$ (normalized to the value for Mo) as a function of atomic number. The ion-wave damping depends significantly on the temperature ratio T_e/T_i for Al plasma. The lower (upper) empty circle is with $T_e/T_i = 1.65$ ($= 1$). The value $T_e/T_i = 1.65$ is obtained from the LASNEX computer simulation result. The ion damping is a weak function of the temperature ratio for high Z target. The overall threshold value $I_{L,th}$ weakly depends on the atomic number in agreement with the experimental results.

The growth rate, on the other hand, is inversely proportional to Γ_e , and it is independent of ion wave damping if $\gamma > \Gamma_i$. Therefore, the growth rate decreases with Z. The growth rate is written as

$$\gamma \propto (T_e^{1/2} / Z) \times (I_0 / I_L) \times I_L \quad (4)$$

The growth rate is proportional to $(1/Z)$ and the laser attenuation (I_0 / I_L) . Both values decrease with Z, so that the growth rate decreases strongly with atomic number as shown in Fig. 8 (C). The growth rate scales as if the laser intensity is reduced by $(I_0/I_L)/Z$. As a result, the effective laser intensity for a Mo plasma is 20 times smaller than that for a CH plasma.

Hence, it is quite reasonable to observe a weak IADI in high Z plasma. The IADI is excited by a weak effective laser power. The intensity ratio $I_{Stokes} / I_{2\omega_0}$ continues to increase with the laser power as shown by curve (b) in Fig. 5. For low Z plasma, on the other hand, the effective laser intensity is so high that the IADI quickly reaches to a level, and after that the IADI intensity increases slowly. Therefore, $I_{Stokes} / I_{2\omega_0}$ decreases with laser intensity as shown in curve (a) of Fig. 5.

V. References

1. K. Nishikawa, J. Phys. Soc. Jpn. 24, 916; 1152 (1968); W. L. Kruer, The Physics of Laser Plasma Interactions (Addison-Wesley Publishing Company, California, 1988).
2. C. Yamanaka, T. Yamanaka, T. Sasaki, J. Mizui, and H. B. Kang, Phys. Rev. Lett. 32, 1038 (1974).
3. J. L. Bobin, M. Decroisette, B. Meyer, and Y. Vitel, Phys. Rev. Lett. 30, 594 (1973).
4. K. Eidman and R. Sigel, Phys. Rev. Lett. 34, 799 (1975).
5. N. G. Basov, V. Yu. Byvhenkov, O. N. Krolieu, M. V. Osipov, A. A. Rapasov, V. P. Silin, G. V. Shliskov, A. N. Starodub, V. T. Tikhonchuk, and A. S. Shikanov, Sov. Phys. JETP 49, 1059 (1979).
6. Xu Zhizhan, Xu Yuguang, Yin Guangyu, Zhang Yanzhen, Yu Jiajin, and P. H. Y. Lee, J. Appl. Phys. 54, 4902 (1983).
7. Y. Takada, N. Nakano, and H. Kuroda, Phys. Fluids 31, 692 (1988).
8. P. D. Carter, S. M. L. Simm, and T. P. Hughes, Opt. Commun. 27, 423 (1978).
9. K. Tanaka, W. Seka, L. M. Goldman, M. C. Richardson, R. W. Short, J. M. Soures, and E. A. Williams, Phys. Fluids 27, 2187 (1984).
10. J. Briand, L. Berge, A. Gomes, Y. Quemener, C. Arnas, M. Armengaud, J. P. Dinguirard, and D. Pesme, Phys. Fluids B2, 160 (1989).
11. K. Mizuno, P. E. Young, W. Seka, R. Bahr, J. S. DeGroot, R. P. Drake, and K. G. Estabrook, Phys. Rev. Lett. 65, 428 (1990).
12. K. Mizuno, W. Seka, R. Bahr, R. P. Drake, P. E. Young, J. S. DeGroot, and K. Estabrook, in Laser Interaction and Related Plasma Phenomena, edited by Hora and G. H. Miley (Plenum Publishing Corporation, New York, in press).
13. K. Mizuno, P. E. Young, W. Seka, R. Bahr, J. S. DeGroot, R. P. Drake, K. G. Estabrook, and S. HEEETA, International Proceedings Conference on Plasma Science, Buffalo, NY, (IEEE, New York, 1989), p. 85.
14. K. Mizuno, J. S. DeGroot, K. G. Estabrook, Phys. Rev. Lett. 52, 271 (1984); Phys. Fluids 29, 568 (1986).
15. K. Mizuno, J. S. DeGroot, W. Woo, P. W. Rambo, K. G. Estabrook, Phys. Rev. 38, 4333 (1988); P. W. Rambo, W. Woo, J. S. DeGroot, and K. Mizuno, Phys. Fluids 27, 2233 (1984).
16. G. J. Linford, in 1991 Laser Program Annual Report, edited by E. Victor Gerge (Lawrence Livermore National Laboratory, California, 1982), P. 2-110.

17. W. Seka, J. Soures, O. Lewis, J. Bunkenburg, D. Brown, S. Jacobs, G. Mourou, and J. Zimmermann, *Applied Optics* 19, 409 (1980).
18. F. W. Perkins and J. Flick, *Phys. Fluids* 14, 2012 (1971).
19. C. Randall, *Phys. Fluids* 25, 2231 (1982).
20. G. B. Zimmerman and W. L. Kruer, *Comments Plas. Phys. Contr Fusion* 2, 51 (1975).
21. M. D. Rosen, D. W. Phillion, V. C. Rupert, W. C. Mead, W. L. Kruer, J. J. Thomson, H. N. Kornblum, V. W. Slivinsky, G. J. Caporaso, M. J. Boyle, and K. G. Tirsell, *Phys. Fluids* 22, 2020 (1979).

VI. Figure captions

Fig. 1 Experimental Apparatus

Fig. 2 Typical IADI spectrum. The three dimensional (the intensity vs λ and time) plot of the second harmonic signal. Mo target. $I_L = 3 \times 10^{13} \text{ W/cm}^2$.

Fig. 3 The IADI spectrum vs target material.

(A) Time integrated spectrum; (a) CH, (b) Mo, and (c) Au targets. $I_L = 3 \times 10^{13} \text{ W/cm}^2$.

(B) Time resolved contour plot; (a) CH, (b) Mo, and (c) Au targets.

Fig. 4 The threshold of the IADI, and the intensities of the second harmonic spectra for various target material.

(A) The IADI threshold vs. Atomic number of target plasma.

(B) The Stokes intensity (empty circles) and the $2\omega_0$ intensity vs. atomic number.

Fig. 5 The intensity ratio (the Stokes intensity divided by the $2\omega_0$ intensity) as a function of vacuum laser intensity: (curve (a)) CH, and (curve (b)) Au targets.

Fig. 6 Spectrum broadening of the Stokes spectrum for various target material.

(A) The second harmonic spectrum from a Cu target to illustrate the definition of I_m/I_p .

(B) The value of I_m/I_p vs. laser intensity for various target materials, shown with solid circles (CH), empty circles (Al), triangles (Cu), and crosses (Mo)

Fig. 7 The theoretical values of the IADI threshold ($I\lambda_L^2$) vs plasma scale length L as a parameter of the electron temperature, with $T_e = 0.2 \text{ keV}$ (a), 0.5 (b), 1 (c), and 2 (d). The all values are local values estimated at the instability region.

Fig. 8 Theoretical calculations. (A) The calculated laser intensity ratios I_0/I_L for $f=0.1$ (solid circles) and $f=0.03$ (empty circles). The laser intensities are I_0 (with plasma) and I_L (without plasma) at the instability region.

(B) The calculated plasma scale length for $f=0.1$ (solid circles) and $f=0.03$ (empty circles) at the instability region.

(C) The calculated growth rate of the IADI vs atomic number (solid circles). The calculated threshold values (empty circles). These values are normalized by the values of Mo plasma.

Fig. 1

Fig. 2

Fig. 3

Fig. 4

Fig. 5

Fig. 6

Fig. 7

Fig. 8

END

**DATE
FILMED
9/17/92**