AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

**Destruction of LP XM46
Using the Molten Salt Destruction Process**

Ravindra S. Upadhye

and

Bruce E. Watkins

**Lawrence Livermore National Laboratory
P. O. Box 808
Livermore, CA 94550, USA**

EXECUTIVE SUMMARY

The preliminary experimental work done on the destruction of the liquid gun propellant LP XM46 (the new designation for LGP-1846) using the Molten Salt Destruction (MSD) Process at the Lawrence Livermore National Laboratory (LLNL) for the U.S.Army is described in this report.

The current methods of disposal of large quantities of high explosives (HE), propellants and wastes containing energetic materials by open burning or open detonation (OB/OD), or by incineration, are becoming undesirable. LLNL is developing MSD as an alternative to OB/OD and incineration of energetic materials.

A series of 18 continuous experimental runs were made wherein a solution of LP XM46 and water was injected into a bed of molten salt comprising the carbonates of sodium, potassium and lithium, along with air. The purpose of these initial Phase 1 runs was to collect information on the applicability of the Molten Salt Destruction Process for the destruction of LP XM46, identify the key technical uncertainties, and to plan future runs. The tentative results from these experiments, described in detail in the main body of this report, indicate that:

MASTER

- LP XM46 can be safely and completely destroyed in a bed of molten salt at temperatures well below those needed for incineration.

- Under optimum operating conditions, less than 1% of the chemically bound nitrogen in the LP XM46 is converted to NO_x, and less than 1% carbon is converted to CO.

There exist, however, a number of technical uncertainties:

- We need to understand better why nitrates build up in the salt bath, and what we can do to reduce this amount.

- We need to understand the mechanism of LP XM46 oxidation and ways to minimize the formation of CO and NO_x.

In addition, we would like to find out ways by which a more concentrated solution of LP XM46 can be introduced into the reactor, so as to increase the throughputs.

INTRODUCTION

The current methods of disposal of large quantities of high explosives (HE), propellants and wastes containing energetic materials by open burning or open detonation (OB/OD), or by incineration, are becoming undesirable. OB/OD may result in incomplete combustion and may lead to the formation of secondary toxins. Incineration is facing increased opposition because of the possibility of thermal NO_x formation due to high operating temperatures. Also, incineration costs are rising steadily, perhaps due to more stringent controls and permitting delays. Therefore, environmentally acceptable alternatives to incineration and OB/OD will have to be devised to accomplish the task of energetic material waste destruction when effective means of recycling is not feasible.

The Molten Salt Destruction (MSD) Process has been demonstrated for the destruction of HE and HE-containing wastes.^{1,2,3} MSD has been used by Anti-Pollution Systems,⁴ and by Rockwell International,⁵ to destroy hazardous wastes. MSD converts the organic constituents of the waste into non-hazardous substances such as carbon dioxide, nitrogen and water. Any inorganic constituents of the waste, such as binders and metallic particles, are retained in the molten salt. The destruction of energetic material waste is accomplished by introducing it, together with oxidant gases, into a crucible containing a molten salt, such as sodium carbonate, or a suitable mixture of the carbonates, chlorides or sulfates of sodium, potassium, lithium and calcium. (Figure 1 shows the flowsheet of the process; the details of the crucible, the experimental set-up and the injection nozzle are given in Figs. 2, 3 and 4 respectively.) The temperature of the molten salt can be varied between 400° to 900°C. The organic components of the waste react with oxygen to produce carbon dioxide, nitrogen and steam. The inorganic components, in the form of "ash", are captured in the molten salt bed as a result of wetting and dissolution of the ash. Halogenated hydrocarbons in the waste (which may be present as a result of halogenated solvents in the waste, or as a result of certain halogenated binders for the HE) generate acidic gases such as hydrogen chloride during the pyrolysis and combustion processes occurring in the melt. These are scrubbed by the alkaline carbonates, producing steam and the corresponding salt, such as sodium chloride. The off-gases from the process are sent through standard off-gas clean-up processing (such as bag filters or HEPA filters) before being released to the

atmosphere. At the end of the process runs, the salt is separated into carbonates, non-carbonate salts, and ash. The carbonates are recycled to the process, and the stable salts are disposed of appropriately.

LLNL has built a small-scale (nominally 1 kg/hr throughput) unit to test the destruction of energetic materials using the MSD process as described in detail later in this report. The initial unit operated in a pulsed mode, wherein between 10-20 g of the feed was injected into the crucible in a few minutes, followed by several minutes of purging with air. This unit was later modified to accept continuous feed. The experiments described in this report were done in the continuous mode. In addition to LP XM46 (the new designation for LGP 1846), we have destroyed the high explosive HMX (octahydro-1,3,5,7-tetranitro- 1,3,5,7-tetrazocine), RDX (hexahydro-1,3,5-trinitro- 1,3,5-triazine), PETN (2,2-bis[[nitroxy]methyl]-1,3-propanediol dinitrate), ammonium picrate and TATB (2,4,6- trinitro-1,3,5-benzenetriamine) in this unit. Our experiments, described in detail later, demonstrate that energetic materials can be safely and effectively treated by MSD.

Technical Basis

The molten salts are typically mixtures of alkali or alkaline earth carbonates and halides. The salts provide excellent heat transfer and reaction media, catalyze oxidation of organics, and neutralize acid gases such as hydrogen chloride by forming stable salts such as sodium chloride.^{4,6} The relatively high thermal inertia of the melt resists changes in temperature resulting from sudden changes in the feed or heat transfer.

Safety is a major consideration in any process where high explosives or wastes containing high explosives are destroyed. In addition to LP XM46, we have successfully and safely destroyed slurries of 35 weight percent HMX, RDX, PETN and TATB in mineral oil, and 50 weight percent of the above in water. The liquid, in addition to keeping the HE concentration to a safe dilution level, provides a vehicle for handling the HE.

A typical HE, such as HMX, contains sufficient oxygen to propagate a steady back burn without any additional oxygen. To reduce the probability of this, we developed a special nozzle design, shown in Fig. 4. The key features of the nozzle are side injection of the feed

into the crucible, external cooling of the feed, and introduction of a large volume of gas, such as nitrogen or air, as a carrier for the feed. The side injection, coupled with external cooling, keep the feed temperature well below 200°C to minimize spontaneous combustion of the HE. The large volume of inert carrier gas further dilutes the HE, provides a large heat capacity, and keeps the velocity of the feed inside the nozzle relatively high. As a result of all these conditions, the HE decomposes only inside the crucible, and not in the feed nozzle. The high injection velocity also helps maintain a high degree of turbulence and mixing inside the crucible.

Propellants react differently from high explosives when subjected to heat. Therefore, the problem of burn-back may be more severe in some case for propellants than explosives. To avoid the possibility of back-burn, we diluted the propellant with water in the ratio of 2 parts by weight of water per one part by weight of the propellant. This dilution essentially demilitarizes the propellant, and removes it from the category of energetic materials. This diluted mixture can be safely injected into the molten salt bath without any back-propagation.

Experimental Program

The apparatus used for the experiments described below was originally designed and developed to investigate the applicability of the molten salt destruction process to the destruction of HE and HE-containing wastes. The unit was modified to accomodate LP XM46. The main change made was in the feed system, wherein the old nozzle was replaced byv a hypodermic syringe. Figure 3 shows the schematic of the experimental setup used in these experiments.

The crucible (shown in Fig. 2) is made of stainless steel, which is stable in the presence of alkali carbonates. (For wastes of high chlorine content, more corrosion resistant materials, such as specialized Ni-Cr based alloys or ceramics may be necessary). The crucible has the dimensions 5.76" inside diameter, 6.63" outside diameter, and 24" length. It is fitted with a flange on the top and a removable injection nozzle, described earlier, on the side. Thermocouples are placed at various locations, including the crucible, the feed nozzle, and the exhaust gas outlet. The coolant gas flow is controlled so as to maintain the feed nozzle temperature under 150É°C before the initiation of liquid feed. The temperature of the nozzle drops to well below 100°C. Gas sample bottles with manual

and solenoid valves are attached to the exhaust line. The whole assembly is placed inside an explosion-proof cell, designed to withstand an explosion of up to 500 g of TNT. Even though the entire experiment can be performed remotely, 30% aqueous solution of LP XM46 was not considered to be an explosive material, and all the experiments detailed here were conducted as manned operations. The experimental data were continuously logged on a computer.

To start an experiment, a measured amount of salt is introduced into the crucible from the top, and the top flange is secured. The sample bottles are evacuated, and the vacuum valves are closed off. The sample bottles are now ready to accept samples. A solution of LP XM46 and water is made and kept ready to be pumped into the feed tube (see Fig. 3). The nozzle coolant gas is turned on to keep the feed nozzle cool. The heaters are switched on, and data logging is initiated. Once the salt approaches its melting point, the carrier gas in the nozzle is turned on to prevent molten salt from entering the feed nozzle. When the temperature of the melt reaches a desired value (between 500° C to 700°C in our runs), the system is ready for accepting the energetic waste.

The waste to be treated is injected in to the crucible through the side nozzle described earlier. The oxidant gases, if needed, are introduced through the tube near the center of the crucible (No additional oxygen is necessary for LP XM46). The gaseous product of the crucible is sent to the vent as shown in Fig. 3. Gas samples were collected at various intervals after the attainment of a steady state.

A salt sample is withdrawn from the crucible at the end of the final run, and analyzed for traces of the energetic material, such as the constituents of LP XM46. The heaters are then shut off, and the unit is allowed to cool. The entrained gas, the coolant gas and the oxidant gas are continued until the salt freezes, at which time the gas flows are shut off.

Results and Discussion

Gas samples were taken during the experiments, and analyzed using a gas chromatograph and mass spectrometer (GC/MS), as well as an on-line IR sensor for CO for runs 1-6. Table 1 in Appendix 1 shows the details of the runs made with LP XM46 under various operating conditions.

The effect of throughput and temperature on NO_x formation is shown in Fig. 5, which shows that:

- The fraction of the chemically bound nitrogen converted to NO_x (referred to as the NO_x fraction for the remainder of this report) increases with throughput.
- The NO_x fraction appears to go through a maximum. It initially increases with temperature (500°C to 600°C), but decreases later on (from 600°C to 700°C).
- Even under the worst conditions, namely, high throughput and medium temperature, the NO_x fraction is less than 1%.

Figure 6 shows the effect of throughput and temperature on CO formation. The following observations can be made:

- The fraction of carbon in the feed that is converted to CO (referred to as the CO fraction for the remainder of this report) decreases with temperature. It is relatively high at low temperature (about 0.9% at 500°C), decreasing to slightly above 0.1% at 700°C, under high throughputs.
- The effect of throughput on the CO fraction is more pronounced at low temperature than at high temperature. For example, the CO fraction decreases from about 0.9% to 0.2% between low and high throughput at 500°C, whereas a similar change in throughput at 600°C shows a change of 0.36% to 0.17%.
- Runs where the feed-rate was 10 ml/min or less (run numbers 9-17) show relatively high CO fractions. Run numbers 1-6, where higher throughputs were used (18.5 and 37 ml/min) show the CO fraction to be less than 1%. However, the CO analyses in runs 7-18 showed large amount of scatter, and may not be reliable.

The effect of throughput at low throughputs at 650°C on the NOx fraction is shown in figure 7, which indicates that the NOx fraction remains under 1% at all throughputs.

The effect of reducing, neutral and oxidizing conditions under low throughputs at 650°C was examined in runs 7 through 18. Since LP XM46 does not need any external oxygen for complete combustion, the addition of the driver air automatically creates oxidizing conditions (runs 7-8, and 13-18). Replacement of the driver air with nitrogen creates neutral conditions (runs 9 and 10). Reducing conditions were obtained by the addition of a small amount of isopropanol to the LP XM46, and replacing the driver air with nitrogen (runs 11-12). These data are summarized in Fig. 8, where we have plotted the NOx fraction on the Y-axis, and the fraction of the stoichiometric air used on the X-axis. Note that the numbers used for the X-axis are qualitative, in that 0.5, 1.0 and 1.5 are used to represent reducing, neutral and oxidizing conditions, respectively. Figure 8 shows that the NOx fraction shows a slight increase (12% to 16%) from reducing to neutral conditions, followed by a large drop (16% to 1%) from neutral to oxidizing conditions. (The CO analyses for runs 7 through 18 showed large amount of scatter, and were not considered reliable.)

We examined the composition of the salt bath after 2.5 L of diluted LP XM46 had been processed. The concentration of nitrate in the bed was 4.50% and of nitrite 0.42%. Thus, roughly 50% of the nitrate in the LP XM46 remained in the salt bath after the termination of the run. It is not known why that much nitrate should remain in the salt bath. Perhaps nitric displaces carbon dioxide from the bed faster than the oxidation of hydrocarbons and hydroxylamine by nitrate. This would be followed by slow decomposition of nitrate to O₂, NO and sodium hydroxide. Addition of carbon dioxide to the bed should increase the rate of nitrate decomposition and maintain a low, steady state of nitrate in the salt bath.

We also analyzed the water that condensed in the ice trap during runs 1 to 6. These results are presented in Table 2. There was a higher concentration of both sodium and potassium in runs with higher feed rates (runs 2, 4, and 6). This is due to greater entrainment of the molten salt by the higher space velocity in the high feed runs.

At 500°C the ammonia concentration in the condensate varied between 1200 and 1800 ppm, depending on feed rate. As the temperature was increased to 600°C the ammonia dropped in half and then to 30 to 70 ppm at 700°C. It appears that ammonia is incompletely combusted below 600°C, but is nearly completely combusted by 700°.

The pH of the condensate varied greatly from less than 1 to almost 10. The condensate was expected to be slightly acidic due to the presence of dissolved carbon dioxide. This, of course, is moderated by salt entrainment, and subsequent carry over into the condensate vessel.

Conclusions and Future Work

The major conclusions from this work are:

- LP XM46 can be safely and completely destroyed in the molten salt bath.
- Under optimum operating conditions, less than 1% of the chemically bound nitrogen in the LP XM46 is converted to NO_x, and less than 1% carbon is converted to CO.

There exist, however, a number of technical uncertainties:

- We need to understand better why so much nitrate builds up in the salt bath, and what we can do to reduce this amount.
- We need to understand the mechanism of LP XM46 oxidation and ways to minimize the formation of CO and NO_x.

In addition, we would like to find out ways by which a more concentrated solution of LP XM46 can be introduced into the reactor, so as to increase the throughputs.

Acknowledgments: We wish to acknowledge William Brummond, Tim Gates, Ron Kanna, and John Wilder for their contributions to this project. The support from the U.S. Army (ARDEC, Picatinny Arsenal) is gratefully appreciated.

References

1. Upadhye, R.S., et. al., "Destruction of High Explosives and Wastes Containing High Explosives using the Molten Salt Destruction Process", presented at the I&EC Special Symposium, American Chemical Society, Atlanta, Georgia, September 21-23, 1992.
2. Upadhye, R.S., et. al., "Destruction of High Explosives and Wastes Containing High Explosives Using the Molten Salt Destruction Process", paper V-10, presented at the "waste Management of Energetic Materials and Polymers", 23rd International Annual Conference of ICT, Karlsruhe, Germany, June 30 - July 3, 1992.
3. Yossim, S.J., et. al., "Non-polluting Disposal of Explosives and Propellants", U. S. Patent 3,778,320, December 11, 1973.
4. Greenberg, J., "Method of Catalytically Inducing Oxidation of Carbonaceous Materials by the Use of Molten Salts", U.S. Patent 3,647,358, Issued to APS, Inc., 1972.
5. Gay, R.L., et. al., "Destruction of Toxic Wastes Using Molten Salts", presented at the National Meeting of the American Institute of Chemical Engineers, Anaheim, CA, 21 April, 1981.
6. Cooper, J.F., et. al., "Molten Salt Processing of Mixed Wastes with Off-gas Condensation", presented at the 1991 Incineration Conference, Knoxville, TN, 13 May 1991. Also, UCRL-JC-107288, Lawrence Livermore National Laboratory, Livermore, CA, 1991.
7. Henry, R.E., et. al., "Large Scale Vapor Explosions", Proceedings of the Fast Reactor Safety Meeting, April 2-4, 1974, Beverly Hills, CA (NTIS Ref. No. CONF-740401-P2).
8. Gay, R.L., et. al., "Treatment of Propellant and Explosive Wastes using Molten Salt Oxidation", presented at the I&EC Special Symposium, American Chemical Society, Atlanta, Georgia, September 21-23, 1992.

Appendix 1

Results of the Experiments and Data Analysis

The experimental data obtained during the course of this work is summarized in Tables 1 and 2. Table 1 shows the experimental conditions and off-gas analyses. Table 2 shows the composition of the condensate from the cold trap.

Explanation of the terms used in Table 1

Run Number: ID number for the run

Temp, C: Salt temperature, in degrees Celsius

Feed rate: measured feed rate, ml/min

Density: calculated density of the feed solution

Feed rate, g/min: product of volumetric feed rate and density

The next three rows represent calculated values of the concentrations of TEAN, HAN and water in units of g per gram of solution. These values are in turn used to calculate the absolute flow rates of these three components in units of g/min. The next row represents the flow rate of LGP into the molten salt unit, in units of g/min.

Salt inventory: Weight of salt in the crucible, kg

Space velocity: Flow rate of LGP in units of g/hr divided by grams of salt in the vessel

The next row indicates whether the experiments were conducted in (nominal) reducing, neutral or oxidizing conditions. Most experiments are under oxidizing conditions because the driver gas used in the nozzle was air. Runs 9 and 10 are under neutral conditions because the driver gas used was nitrogen. To obtain reducing conditions, such as in runs 11 and 12, small amounts of isopropanol were added to the feed, and nitrogen was used as the driver gas.

The next 10 rows contain the results of gas analyses on the off-gas. They are expressed in volume (or mole) percents. C2, C3 and C4 represent all hydrocarbon compounds with carbon chain lengths of 2, 3 and 4 respectively.

The next two rows represent maximum possible and actual ratios of NO in the off-gas to the total carbon in the off-gas. If ALL the N in the LGP is converted to NO, this ratio will be 2.67. Thus, the ratio of actual to maximum represents the fraction of the chemically bound nitrogen in the LGP that is converted to NO. This ratio is referred to as Nfr_1.

The next row shows the percentage of the carbon in the LGP that is converted to CO.

For run numbers 1 through 6, for which reliable air flow data are available, we performed the NO_x fraction calculations based on the total product gas flow and the composition of the NO in the product gas. Once again, we calculated the NO fraction, referred to as Nfr_2. Finally, the ratio of Nfr_2 to Nfr_1 provides a comparison of the two methods of calculating the NO fraction.

Table 1: Analysis of LP XM46 data

Run Number	1	2	3	4	5	6
Temp, °C	500	500	600	600	700	700
feed rate in ml/min	18.5	37	18.5	37	18.5	37
density, g/ml	1.15	1.15	1.15	1.15	1.15	1.15
feed rate, g/min	21.275	42.55	21.275	42.55	21.275	42.55
g TEAN/g solution	0.07	0.07	0.07	0.07	0.07	0.07
g HAN /g solution	0.22	0.22	0.22	0.22	0.22	0.22
g H2O /g solution	0.71	0.71	0.71	0.71	0.71	0.71
TEAN g/min	1.50	3.01	1.50	3.01	1.50	3.01
HAN g/min	4.77	9.53	4.77	9.53	4.77	9.53
H2O g/min	15.01	30.01	15.01	30.01	15.01	30.01
LP XM46 g/min	7.84	15.68	7.84	15.68	7.84	15.68
g mole/min TEAN	0.0071	0.0142	0.0071	0.0142	0.0071	0.0142
Driver air flow						
SCFH	25	25	25	25	25	25
liter/min	11.8	11.8	11.8	11.8	11.8	11.8
off gas, gmol/min						
from LP XM46	0.3000	0.6001	0.3000	0.6001	0.3000	0.6001
from water	0.8336	1.6673	0.8336	1.6673	0.8336	1.6673
air	0.5268	0.5268	0.5268	0.5268	0.5268	0.5268
total	1.6605	2.7941	1.6605	2.7941	1.6605	2.7941
total, dry	0.6261	0.7254	0.6261	0.7254	0.6261	0.7254
salt inventory, kg	6.40	6.40	6.40	6.40	6.40	6.40
space velocity	0.07	0.15	0.07	0.15	0.07	0.15
g LP XM46/hr/g salt						
% stoich O2 used	>100	>100	>100	>100	>100	>100
Gas Comp (dry basis)						
in vol %						
N2	79.00	80.65	79.31	76.66	77.94	76.28
O2	15.27	12.20	14.49	10.58	13.39	8.58
Ar	0.85	0.87	0.88	0.84	0.88	0.83
CO2	0.93	2.39	3.52	7.71	7.17	12.32
CO	0.01	0.01	0.01	0.01	0.01	0.01
H2	0.20	0.71	0.15	0.47	0.00	0.05
CH4						
C2	0.09	0.79	0.02	0.07	0.00	0.00
C3						
C4						
NO	0.03	0.08	0.07	0.19	0.08	0.19
NO/C						
maximum	2.67	2.67	2.67	2.67	2.67	2.67
actual	0.02	0.02	0.02	0.02	0.01	0.02
%N to NO (Nfr_1)	0.88	0.75	0.69	0.90	0.42	0.58
%C to CO	0.89	0.33	0.36	0.17	0.19	0.11
g moles NOx/min						
max possible	0.11	0.23	0.11	0.23	0.11	0.23
actual	1.63E-4	5.80E-4	4.13E-4	1.37E-4	5.07E-4	1.39E-4
%N to NO (Nfr_2)	0.14	0.26	0.36	0.60	0.45	0.61
Nfr_2/Nfr_1	0.16	0.34	0.53	0.67	1.06	1.05

Table 1 (continued): Analysis of LP XM46 data

Run Number	7	8	9	10	11	12
Temp, °C	650	650	650	650	650	650
feed rate in ml/min	5	5	5	5	5	5
density, g/ml	1.15	1.15	1.15	1.15	1.15	1.15
feed rate, g/min	5.75	5.75	5.75	5.75	5.75	5.75
g TEAN/g solution	0.07	0.07	0.07	0.07	0.07	0.07
g HAN /g solution	0.22	0.22	0.22	0.22	0.22	0.22
g H2O /g solution	0.71	0.71	0.71	0.71	0.71	0.71
TEAN g/min	0.41	0.41	0.41	0.41	0.41	0.41
HAN g/min	1.29	1.29	1.29	1.29	1.29	1.29
H2O g/min	4.06	4.06	4.06	4.06	4.06	4.06
LP XM46 g/min	2.12	2.12	2.12	2.12	2.12	2.12
g mole/min TEAN						
Driver air flow SCFH						
liter/min						
off gas, gmol/min from LP XM46						
from water						
air						
total						
total, dry						
salt inventory, kg	6.40	6.40	6.40	6.40	6.40	6.40
space velocity	0.02	0.02	0.02	0.02	0.02	0.02
g LP XM46/hr/g salt						
% stoich O2 used	>100	>100	100	100	<100	<100
Gas Comp (dry basis) in vol %						
N2	73.78	72.64	85.71	85.73	84.35	84.35
O2	12.20	12.11				
Ar	0.83	0.82				
CO2	13.01	14.37	8.05	7.83	7.85	7.94
CO			1.34	1.34	1.89	1.90
H2			0.63	0.63	1.32	1.24
CH4			0.12	0.12	0.80	0.75
C2			0.09	0.09	0.22	0.23
C3					0.02	0.02
C4					0.01	
NO	0.18	0.10	4.05	4.25	3.52	3.56
NO/C						
maximum	2.67	2.67	2.67	2.67	2.67	2.67
actual	0.01	0.01	0.42	0.45	0.32	0.32
%N to NO (Nfr_1)	0.52	0.26	15.69	16.81	11.90	12.02
%C to CO	0.00	0.00	13.83	14.15	17.05	17.11
g moles NOx/min max possible						
actual						
%N to NO (Nfr_2)						
Nfr_2/Nfr_1						

Table 1 (continued): Analysis of LP XM46 data

Run Number	13	14	15	16	17	18
Temp, °C	650	650	650	650	650	650
feed rate	5	5	10	10	10	10
in ml/min						
density, g/ml	1.15	1.15	1.15	1.15	1.15	1.15
feed rate, g/min	5.75	5.75	11.5	11.5	11.5	11.5
g TEAN/g solution	0.07	0.07	0.07	0.07	0.07	0.07
g HAN /g solution	0.22	0.22	0.22	0.22	0.22	0.22
g H2O /g solution	0.71	0.71	0.71	0.71	0.71	0.71
TEAN g/min	0.41	0.41	0.81	0.81	0.81	0.81
HAN g/min	1.29	1.29	2.58	2.58	2.58	2.58
H2O g/min	4.06	4.06	8.11	8.11	8.11	8.11
LP XM46 g/min	2.12	2.12	4.24	4.24	4.24	4.24
g mole/min TEAN						
Driver air flow						
SCFH						
liter/min						
off gas, gmol/min						
from LP XM46						
from water						
air						
total						
total, dry						
salt inventory, kg	6.40	6.40	6.40	6.40	6.40	6.40
space velocity	0.02	0.02	0.04	0.04	0.04	0.04
g LP XM46/hr/g salt						
% stoich O2 used	>100	>100	>100	>100	>100	>100
Gas Comp (dry basis						
in vol %						
N2	75.23	74.09	72.27	72.68	76.57	77.68
O2	13.10	13.68	7.68	8.01	17.75	18.35
Ar	0.87	0.86	0.81	0.83	0.90	0.92
CO2	10.37	10.92	18.51	17.68	4.38	3.01
CO	0.28	0.37	0.45	0.47	0.35	
H2						
CH4			0.13	0.03		
C2			0.03			
C3						
C4						
NO	0.14	0.07	0.11	0.30	0.04	0.04
NO/C						
maximum	2.67	2.67	2.67	2.67	2.67	2.67
actual	0.01	0.01	0.01	0.02	0.01	0.01
%N to NO (Nfr_1)	0.48	0.24	0.22	0.61	0.28	0.49
%C to CO	2.63	3.28	2.35	2.59	7.40	0.00
g moles NOx/min						
max possible						
actual						
%N to NO (Nfr_2)						
Nfr_2						
Nfr_1						

Table 2: Analyses of the condensate from the cold trap

Condensate values in mg/L

Run Numbers	1	2	3	4	5	6
Nitrite	1074	1516	1776	1789	2425	ND
Nitrate	699	1463	2324	3368	753	7961
Sodium	252	873	361	613	405	709
Potassium	449	1855	702	1258	900	1413
Ammonia	1260	1820	540	800	32	66
pH	9.34	9.79	4.54	9.13	0.91	4.36
Nitrite/Nitrate	1.54	1.04	0.76	0.53	3.22	
Na/K	0.56	0.47	0.51	0.49	0.45	0.50

We are developing a molten salt process for wastes containing energetic materials

Details of the crucible

5.0.0893.2944
19RSU/dem

Figure 2

Molten salt destruction of energetic materials

Figure 3

Details of the injector nozzle

Effect of throughput and temperature on NO_x formation

Figure 5

Effect of throughput and temperature on CO formation

Figure 6

Effect of throughput on NOx at 650 C

Figure 7

Effect of Oxygen on NO_x at 650 C

Figure 8

DATE

FILMED

9/20/94

END