**SELECTED CASE STUDIES OF TECHNOLOGY
TRANSFER FROM MISSION-ORIENTED
APPLIED RESEARCH**

**K. K. Daellenbach
R. L. Watts
J. K. Young
R. B. Abarcar^(a)**

July 1992

**Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Richland, Washington 99352**

**(a) Energetics Inc.,
Columbia, Maryland 11046**

MASTER

ABSTRACT

The U.S. Department of Energy (DOE) Advanced Industrial Concepts Division (AICD) under the Office of Industrial Technologies (OIT) supports interdisciplinary applied research and exploratory development that will expand the knowledge base to enable industry to improve its energy efficiency and its capability to use alternative energy resources. AICD capitalizes on scientific and technical advances from the United States and abroad, applying them to address critical technical needs of American industry. As a result, AICD research and development products are many and varied, and the effective transfer of these products to diverse targeted users requires different strategies as well. This paper describes the products of AICD research, how they are transferred to potential users, and how actual transfer is determined.

SUMMARY

The Advanced Industrial Concepts Division (AICD) of the U.S. Department of Energy (DOE) Office of Industrial Technology (OIT) supports applied research and exploratory development efforts to expand a knowledge base that when effectively transferred to the private sector will allow private industry to improve its ability to conserve energy and use alternative energy resources.

This paper provides an overview of the technology transfer philosophy within AICD. It describes the mechanism of technology transfer and the types of products that AICD successfully develops. The 11 case studies following the Introduction, detail successful technology transfer in each of the AICD Programs (Combustion, Materials, Biocatalysis, and Thermal Sciences) and include two technologies that were developed under the auspices of the Energy Conversion and Utilization Technologies (ECUT) Division, a precursor to the AICD.

ACKNOWLEDGMENTS

The authors gratefully acknowledge the assistance of several people in industry, academia, and at the national laboratories who peer-reviewed sections of this report for technical content and accuracy. These people include: C. A. Amann, General Motors Research Laboratories; J. E. Bailey, California Institute of Technology; D. Chasan, CIBA-GEIGY; L. J. Evans, Lennox Industries, Inc.; P. F. Flynn, Cummins Engine Company, Inc.; J. Greenleaf, Greenleaf Tool Corporation; A. Gross, Enzytech Corporation; N. Hakim, Detroit Diesel Corporation; A. Kilbanov, Massachusetts Institute of Technology; F. A. Nichols, Argonne National Laboratory; B. Olafson, Molecular Simulations, Inc.; R. Palicka, Cercom, Inc.; J. W. Patten, Cummins Engine Company, Inc.; J. M. Perez, U.S. Department of Energy; G. R. Petersen, Jet Propulsion Laboratory; C. D. Scott, Oak Ridge National Laboratory; D. Siebers, Sandia National Laboratories; J. Soderstrom, Oak Ridge National Laboratory; R. Tabaczynski, Ford Motor Company; and D. A. Wagner, General Motors Corporation.

In addition, the authors thank L. M. Buel, M. M. Hale, L.L. Fassbender, R. M. Moreno, and M. L. Ryan for their excellent assistance in preparing this document.

CONTENTS

ABSTRACT	iii
SUMMARY	v
ACKNOWLEDGMENTS	vii
INTRODUCTION	1.1
TECHNOLOGY CASE STUDY 1 - IMPROVED DIESEL ENGINES	2.1
Key Results	2.1
AIC's Role	2.1
Industry's Role	2.2
Benefits of the Improved Diesel Engines	2.3
Future Development	2.3
References	2.4
TECHNOLOGY CASE STUDY 2 - AUTOMOTIVE ENGINE EFFICIENCY IMPROVEMENT	3.1
Key Results	3.1
AIC's Role	3.2
Role of Industry, Universities, and National Laboratories	3.3
Benefits of Automotive Engine Efficiency Improvement	3.4
Future Development	3.5
References	3.5
TECHNOLOGY CASE STUDY 3 - PULSE COMBUSTION	4.1
Key Results	4.1
AIC's Role	4.2
Industry's Role	4.2

Benefits of Pulse Combustion	4.2
Future Development	4.3
References	4.4
TECHNOLOGY CASE STUDY 4 - THIN-FILM OXYGEN UPTAKE TEST FOR ENGINE OIL OXIDATION	5.1
Key Results	5.1
AIC's Role	5.2
Industry's Role	5.2
Benefits and Potential Savings of TFOUTs	5.2
Future Development	5.3
References	5.3
TECHNOLOGY CASE STUDY 5 - NICKEL ALUMINIDE ALLOYS IN TURBOCHARGERS	6.1
Key Results	6.1
AIC's Role	6.1
Industry's Role	6.1
Benefits of Nickel Aluminide Turbochargers	6.1
Future Development	6.2
References	6.2
TECHNOLOGY CASE STUDY 6 - USING 'WHISKERS' TO STRENGTHEN CERAMIC CUTTING TOOL INSERTS	7.1
Key Results	7.1
AIC's Role	7.1
Industry's Role	7.1
Benefits of WRC Inserts	7.2
Future Development	7.2

Bibliography	7.3
TECHNOLOGY CASE STUDY 7 - VAPOR-PHASE LUBRICATION	8.1
Key Results	8.1
AIC's Role	8.1
Industry's Role	8.1
Benefits and Potential Savings of Vapor-Phase Lubrication	8.2
Future Development	8.2
References	8.2
TECHNOLOGY CASE STUDY 8 - TEMPERATURE ABUSE SENSORS	9.1
Key Results	9.1
AIC's Role	9.1
Industry's Role	9.1
Benefits of Temperature Abuse Sensors	9.2
Future Development	9.3
References	9.3
TECHNOLOGY CASE STUDY 9 - USING MOLECULAR MODELING TOOLS TO SOLVE CHEMISTRY PROBLEMS	10.1
Key Results	10.1
AIC's Role	10.1
Industry's Role	10.2
Benefits of Using Molecular Modeling Tools to Solve Chemistry Problems	10.2
Future Development	10.3
References	10.3
TECHNOLOGY CASE STUDY 10 - MARKETS FOR GENETIC ENGINEERING TECHNOLOGIES	11.1

Key Results	11.1
AIC's Role	11.1
Industry's Role	11.2
Benefits of Genetic Engineering Technologies	11.2
Future Development	11.2
References	11.3
TECHNOLOGY CASE STUDY 11 - HIGH-PRODUCTIVITY FLUIDIZED-BED BIOREACTOR	12.1
Key Results	12.1
AIC's Role	12.1
Industry's Role	12.1
Benefits of Fluidized-Bed Bioreactor	12.2
Future	12.2
References	12.3

FIGURES

1.1	The AICD Technology Transfer Strategy	1.2
2.1	Improved Pistons Used in Diesel Engines	2.2
3.1	Fleet Averaged MPG for Automobile Sales	3.2
3.2	Operating Principle of the Four-Stroke-Cycle, Spark-Ignition Engine	3.4
3.3	Operating Principle of the Two-Stroke-Cycle, Spark-Ignition Engine	3.4
4.1	Pulse Combustion Operating Principle	4.1
4.2	Pulse Combustion Energy Savings	4.3
5.1	Schematic Drawing of Oxidation Test Apparatus	5.1
11.1	Potential Markets for Genetic Engineering Tools	11.3

TABLE

1.1	AICD R&D Products and Evidences of Technology Transfer	1.3
-----	--	-----

INTRODUCTION

The Advanced Industrial Concepts Division (AICD) of DOE's Office of Industrial Technologies (OIT) supports applied research and exploratory development efforts that focus on expanding the industrial energy conservation knowledge base. As a result of AICD's efforts, advanced technologies can be more fully developed and commercialized by industry. Within the broader OIT mission, AICD seeks to bridge the research and development (R&D) gap between basic energy research and the engineering development efforts of the more applied OIT programs, as well as those of U.S. private industry. Emerging basic scientific and technical advances in the United States and abroad are exploited by AICD to address specific critical areas that limit industrial energy efficiency and the use of alternative fuels.

AICD supports interdisciplinary R&D of fundamental phenomena under actual industrial operating conditions to assist industry in developing energy-efficient technologies. AICD supports development of R&D tools and carefully selected materials, processes, and technologies to the point at which proof-of-concept is established. From that point, the private sector and/or the OIT end-use programs take the lead in further technology development.

To maximize benefits from its R&D, AICD pursues a technology transfer strategy that ensures prompt and effective dissemination of R&D results to the OIT Programs or directly to the private sector (e.g., potential industrial users). AICD's role in technology transfer goes beyond merely handing off neatly packaged "products" to another organization. Technology transfer is an integral part of AICD's ongoing R&D efforts. It is a process of continuous interaction among researchers in national laboratories, academia, and industry to effectively apply the latest advances in scientific knowledge, methods, and research to use energy more effectively in the industrial sector of the economy.

As stated in the National Energy Strategy⁽¹⁾, "The key to new knowledge and innovation in energy is basic science and research. Of course, there must also be focused R&D - both to advance new technologies and to better understand existing technologies." AICD is forging a strong linkage between the scientific knowledge developed in DOE's Office of Basic Energy Sciences (BES) and the more applied R&D programs funded by OIT.

In the area of technology transfer, the National Energy Strategy sets forth three goals: 1) to increase industry/government collaboration in both R&D and technology commercialization, 2) to increase government participation in the technology transfer process, and 3) to accelerate the technology transfer process to enhance the competitiveness of U.S. industry. AICD is aggressively pursuing all three of these goals.

The technology transfer strategy of AICD is illustrated in Figure 1.1. AICD-funded researchers from national laboratories, academia, and industry interact directly with engineers and scientists funded by various industrial entities to identify critical R&D needs. AICD researchers, in turn, conduct interdisciplinary research to address those R&D needs. They draw on the latest scientific and technical advances to resolve the most critical issues impeding the development of products/processes that improve industrial energy efficiency. AICD research results are disseminated to industrial researchers who use them to further develop and commercialize promising technologies. AICD researchers obtain feedback on: 1) the usefulness of their research results in advancing the technologies, and 2) specific follow-on

Figure 1.1. The AICD Technology Transfer Strategy

research needs. The direct interaction among researchers, technology developers, and technology users promotes widespread use of R&D results and moves concepts forward as quickly as possible through the various developmental stages.

AICD's R&D efforts address specific technology deficiencies that have been identified through close interaction with prospective technology users in the private sector. Products from AICD research include databases; models and other analytical tools; innovative "first-of-a-kind" concepts; knowledge and understanding of mechanisms and phenomena; as well as materials, processes, and technologies arising from the execution of AICD research activities. Just as the technical research results and products differ depending on the needs of the user, the manner by which they are transferred will also vary depending on the mechanisms used by industry to interact with AICD researchers. This flexible technology transfer approach tends to maximize the prospects for the adoption and use of AICD products.

R&D tools developed by AICD include design methods and analytical techniques (including validated predictive computer models), experimental data and correlations, databases, and measurement and diagnostics techniques. These tools may or may not represent commercial products that can be sold to consumers. The new or improved understanding of fundamental concepts embodied in AICD R&D tools must be applied by the private sector or OIT end-use programs that develop industrial technologies. Actual transfer of R&D tools and evidence of their use by others is sometimes difficult to document directly, since the original AICD R&D product is often combined with the knowledge and experience of industrial researchers to develop their commercial products. Types of AICD R&D products and evidence of technology transfer are shown in Table 1.1.

Technical data, information, and knowledge are transferred through publication in technical journals; participation in technology exchange meetings, staff exchanges, workshops, and professional society

Table 1.1. AICD R&D Products and Evidence of Technology Transfer

Types of AICD R&D Products	Evidence of Technology Transfer
R&D Tools Knowledge and understanding of scientific phenomena Experimental data and correlations Design and analytical tools (including experimentally validated computer models)	Industry hires graduate students who did research funded by AICD AICD research results are cited in technical papers written by industrial researchers Industry acquires R&D tools developed by AICD researchers Industry documents use of the tools in the development of a product
Materials, Processes, and Technologies Materials that can be used to fabricate parts and components Lab- and bench-scale processes Prototype technology or pilot plant	Licensing of patented product Processes/prototype scaled-up for industrial markets Commercial products developed Companies formed to commercialize technologies Other clients funding complementary R&D or subsequent phases of AICD R&D

meetings; and other forums for the exchange of scientific information. Direct interaction among researchers and technology users during AICD research projects is the best way to transfer research tools and technical research results. For the purposes of technology transfer tracking, however, successful transfer of R&D products can be deduced from industry's continued interest in cooperative research efforts. It is the prerogative of industry to disclose how AICD research is being applied to develop new products and processes. Several industrial research organizations have written to AICD to express their appreciation for the use of AICD research results. In some cases, they have indicated how the results have been used to develop new products or processes, although such information is often proprietary.

Other types of AICD products include new or improved materials, processing techniques, or laboratory bench-scale processes. In some cases, the product was developed by AICD researchers because it

was needed to conduct AICD research or test innovative concepts from AICD research (e.g., fiber-optic spark plug). In some cases, the improved understanding of fundamental phenomena led directly to the discovery of a new material (e.g., nickel aluminide alloys). In other cases, the technology development was an unforeseen "spin-off" that was not anticipated at the start of the project (e.g., temperature abuse sensors). The resulting product can be patented to protect the rights of the inventor.

Commercialization of the product can be directly pursued by the inventor or developer, or the product can be licensed to others for further development or commercialization. An AICD product may remain as a distinct entity within a larger product or technology that is developed by industry. Since licensing of new technologies for commercial use indicates a substantial commitment by industry to further pursue the technology, evidence of successful technology transfer is explicitly provided by the number of licenses awarded. The formation of new companies and the sales of new products in the marketplace are also indicative of successful technology transfer. In many cases, the new product results in energy savings, although either cost savings or regulatory compliance is usually the driver for the product improvement in the first place.

This report contains 11 case studies of selected technologies resulting from AIC-funded research. The case studies describe the technology or product being introduced into the marketplace, AICD's role in the development of the product, the technology transfer process for deploying the product into the marketplace, industry's role, and the benefits and future of the technology, as well as relevant references. The case studies have been reviewed by AICD Program Managers at both DOE/HQ and the national laboratories, as well as key players involved in the development of the technologies.

The case studies include two technologies that are not currently funded by AICD (Thin-Film Oxygen Uptake Test for Engine Oil Lubrication and Vapor-Phase Lubrication). These case studies were included in the original scope of this tracking effort when it was initiated under the Energy Conversion and Utilization Technologies (ECUT) Division. AICD currently sponsors four of the original ECUT Programs: Combustion, Materials, Biocatalysis, and Thermal Sciences. The Tribology Program was moved to DOE's Office of Transportation Materials (OTM).

REFERENCES

1. U.S. Department of Energy. 1991. *National Energy Strategy, First Edition 1991/1992*. DOE/S-0082P, U.S. Department of Energy, Washington, D.C.

TECHNOLOGY CASE STUDY 1 - IMPROVED DIESEL ENGINES

Key Results

Each day, 46,000 barrels of oil are being saved because of improvements in direct injection engines for heavy-duty diesel trucks. Diesel engines, historically designed for efficiency, had compression ratios $>20:1$. Because the engines were large and heavy, the emphasis in the 1950s and 1960s was on reducing their size and increasing their horsepower output. In the 1970s and 1980s, the oil embargo and increased environmental concerns resulted in a need to further improve truck engine efficiency and to reduce particulate emissions. Because diesel engines were already quite efficient, further improvements required careful optimization of the combustion process.

Using traditional methods to improve the efficiency and environmental acceptability of diesel engines was time-consuming and expensive—design changes were simulated in test engines and then in prototype engines. Until actual engine tests were conducted, the impact of a design change on engine performance could not be evaluated. For example, a change that would reduce the particulate emissions might increase nitrogen oxide emissions. Therefore, new methods that eliminated or reduced expensive and time-consuming engine testing were needed.

AIC's Role

A cooperative program is bringing industry, universities, and national laboratories together in an effort to develop the technology base and design tools needed to improve the efficiency and reduce the emissions of combustion systems. The program was begun by the U.S. Department of Energy (DOE), Energy Conversion and Utilization Technologies (ECUT) Division. Funding for this technology program continues through DOE's Advanced Industrial Concepts Division (AICD). Technical management of the program is centered at the Combustion Research Facility at Sandia National Laboratories, which is sponsored by DOE's Office of Basic Energy Sciences. Industry participates in this program by providing guidance on the research directions and sharing in-house technical expertise, but receives no direct support from DOE. This program is designed to help maintain the U.S. lead in combustion technology and emissions control and serves as a focal point for research and development aimed at:

- improving the understanding of the combustion process
- developing and applying in-situ advanced, laser-based diagnostic tools
- developing and improving computer models of the combustion and gas flow processes.

A Diesel Engine Cooperative Working Group, formed in 1979 as part of ECUT's Combustion Technology Program, guided the development and application of diagnostic tools and computer models to study critical diesel engine combustion processes. In this group, industry researchers from Cummins Engine Company, Navistar (formerly International Harvester), and Exxon collaborated with researchers from Sandia National Laboratories, Los Alamos National Laboratory, Penn State, Yale, Purdue, Southwest Research Institute, United Technologies, and Physical Sciences, Incorporated.

Industry's Role

Combining industry's knowledge and skills with the improved understanding, diagnostic tools, and computer models developed by the ECUT-sponsored cooperative programs has been and will be crucial to improving the diesel engine's efficiency and environmental acceptability. Industry is beginning to use these tools and models to evaluate new engine design concepts before they are introduced into test engines and subsequently into prototype engines. In this way, more concepts can be considered, and improvements can be made more quickly and efficiently.

The Cummins Engine Company has accumulated a great deal of knowledge, skill, and experience to become the world's leading manufacturer (currently >50% of the U.S. market) of diesel engines for heavy trucks. Cummins and other diesel engine manufacturers are applying the tools and models developed by ECUT's Combustion Technology Program to improve present engines and develop advanced diesel engine designs. Specifically, Cummins has:

- used KIVA, a multi-dimensional model that numerically simulates diesel fluid mechanical and combustion processes, to assess combustion chamber shapes and piston designs for next-generation products. This led to moving the piston ring set to within 0.4 inch of the top of the piston from 0.83 inch in 1980 and 1983 pistons (see Figure 2.1). KIVA has also been used in conjunction with engine performance tests to establish relationships between calculated parameters and experimental emissions/performance values. As a result, Cummins has developed a "method" for designing combustion chambers.

Figure 2.1. Improved Pistons Used in Diesel Engines

- developed a better understanding of in-cylinder soot transport. From the experiments performed in an optical access diesel engine at Sandia National Laboratories, Cummins better understands the mechanisms that transport combustion-generated soot into the lubricating oil. By combining the information gained at Sandia with their own in-house data, they were able to develop design guidelines for improved mechanical durability. These guidelines directly influenced Cummins' 1991 products and may influence future products as well.
- continued progress toward understanding nitrogen oxide (NO_x) and soot control in diesels. Through the combination of the DOE-sponsored analytical and experimental research, Cummins continues to evolve their understanding of in-cylinder emissions control. Information gained from this work has been and will continue to be incorporated into the combustion chamber design work at Cummins.
- improved engine breathing and pulse-preserving manifolds and improved the design of turbochargers.

Benefits of the Improved Diesel Engines

Improved diesel engines are saving energy and increasing environmental acceptability. The miles per gallon (mpg) efficiency of heavy diesel trucks has increased dramatically from about 4.5 mpg in 1970 to about 6.3 mpg in 1989 (an overall increase of 40%). According to Cummins, improvements to the engine account for one-fourth (10%) of that increase: 5% comes from improved cycle efficiency and 5% from reducing the cruise rpm from 2100 rpm to 1500 rpm.

In 1987, heavy diesel trucks consumed about 915,000 barrels of fuel per day.⁽¹⁾ An estimated 50% of the trucks consuming this fuel are using improved diesel engines, for a savings of almost 46,000 barrels of fuel per day or nearly \$2 million per day at \$1 per gallon. Improved engines are also reducing the amount of carbon released into the atmosphere by 10 million pounds per day. This assumes that 5.3 pounds of carbon per gallon are not released during the combustion of the fuel because of improved engine efficiency.⁽²⁾

Future Development

The research carried out by the AICD working groups continues to leverage the skills, knowledge, and experience of industry, universities, and national laboratories to develop improved computer models and diagnostic techniques. This research is becoming more and more important because better models are still needed to optimize engine designs, to further reduce the production of harmful emissions, and to integrate new materials, such as ceramics and ordered intermetallics (e.g., nickel aluminides), into engine design for operation at higher temperatures.

Several studies are currently under way. The working group is investigating 1) particulate (soot) formation mechanisms in diesels and the tradeoff with NO_x production, 2) spray mixing and combustion rates, and 3) improved models for diesel combustion processes. Also, research is under way to exploit new experimental techniques for in-situ measurements of spray properties, particulate concentration, flame structure, temperatures, and local fuel-air ratio.

References

1. Davis, S. C., D. B. Shonka, G. J. Anderson-Batiste, and P. S. Hu. 1989. *Transportation Energy Data Book: Edition 10*. ORNL-6565, Oak Ridge National Laboratory, Oak Ridge, Tennessee.
2. Radian Corporation. 1987. "Emissions and Cost Estimates of Globally Significant Anthropogenic Combustion Sources of NO_x, N₂O, CH₄, CO, and CO₂." Prepared for the Environmental Protection Agency by Radian Corporation, Research Triangle Park, Virginia.

TECHNOLOGY CASE STUDY 2 - AUTOMOTIVE ENGINE EFFICIENCY IMPROVEMENT

Key Results

American motorists purchasing new automobiles and light trucks in 1990 received nearly twice as many miles per gallon (mpg) of fuel (compared to automobiles and trucks purchased 20 years earlier) as a result of improved engine performance and reduced vehicle weight. Further fuel-efficiency improvements, however, are needed to decrease our reliance on foreign oil and emissions of harmful pollutants. To meet this challenge, industry, universities, and national laboratories are working together as part of a program sponsored by the U.S. Department of Energy (DOE) to improve advanced engine concepts being developed by industry.

From 1950 to the early 1960s, the primary emphasis in designing automobiles was to meet market interest in spacious cars with large displacement engines for quick acceleration. The Clean Air Act of 1979 mandated stringent limitations on emissions and a phase-out of lead in gasoline that forced manufacturers to put "detuned" engines with lower compression ratios into production. These "tradeoffs" reduced emissions, but also reduced engine performance and fuel efficiency.

The oil embargo of 1973 and the 1975 Corporate Average Fuel Economy (CAFE) standards (regulated by the Department of Transportation's (DOT's) National Highway Traffic Safety Administration⁽¹⁾) created a need to develop more fuel-efficient vehicles. As a result, between 1975 and 1988, passenger automobile mpg improved nearly two-fold from 15.4 to 28.4 mpg (see Figure 3.1).⁽²⁾ Fuel economy improved because of optimizing design changes such as downsizing the vehicle, using lock-up transmissions, extensive redesigning and testing of engine combustion systems, changing to front-wheel drive and radial tires, improving aerodynamics, and improving engine control systems (e.g., electronically controlled fuel injection and spark ignition).

As Figure 3.1 shows, the rapid gains in fuel economy of the late 1970s and 1980s are no longer occurring. Reducing the vehicle weight is an important technique used to improve fuel economy. The average passenger car weight, however, has remained steady at about 3,100 pounds since 1982 (down from 4,058 pounds in 1975).⁽²⁾ Further weight reductions and downsizing may be possible by using lighter-weight materials and designing smaller vehicles. These approaches, however, may encounter consumer resistance because of preference for roomier vehicles and additional costs associated with the use of more expensive materials.

If vehicle designs are to meet improved DOT fuel economy goals, significant automotive engine improvements are required. Nonhomogeneous charge (NHC) engines are currently in the development stage which may be smaller and have potential for greater fuel efficiency. Designing NHC engines is more difficult than designing homogeneous charge (HC) engines because the combustion process is more complex. With NHC engines, nonuniform mixtures of fuel and exhaust products are present in the combustion chamber. Methods for modeling the combustion process may better predict the performance of NHC engines and reduce engine testing, which is time-consuming and expensive.

S9203085.1

Figure 3.1. Fleet Averaged MPG for Automobile Sales

AIC's Role

Improved laser diagnostics and modeling methods using computers were made available during the 1970s by DOE weapons laboratories. These tools were developed to provide a better understanding of nuclear weapons and were made available to industry and academia for use on non-nuclear projects through the DOE's Combustion Technology Program.

In 1978 DOE's Energy Conversion and Utilization Technologies (ECUT) Division established the Combustion Technology Program at the Sandia Combustion Research Facility. The facility's construction was sponsored by DOE's Office of Basic Energy Sciences. The program supports cooperative research by industry, universities, and national laboratories and provides a focal point for:

- improving the understanding of combustion processes
- developing and applying advanced laser-based, in situ diagnostic tools
- developing and improving computer models of combustion and gas flow.

Funding for this technology program area continues through DOE's Advanced Industrial Concepts (AIC) Division.

Role of Industry, Universities, and National Laboratories

Industry, universities, and national laboratories are collaborating to study critical issues relating to direct-injection stratified charge (DISC) engines, dilute homogeneous charge (DHC) engines, heavy-duty diesels, and engine knock. This joint effort is guiding the development and application of diagnostic tools and multidimensional computer models to measure velocity, turbulence, temperature, and air-fuel ratio. Industry participates in the research by helping guide the research activities and sharing in-house research; it receives no direct support from DOE.

DOE's Combustion Technology Program contributed significantly to the industries' use of advanced in situ diagnostic methods to test automotive engines and to design tools that simulate the combustion process in advanced engines on supercomputers. By this process, new design concepts can be evaluated before they are introduced into test engines. Several operating variables can be considered simultaneously, and modifications can be made quickly and efficiently. Several of these proprietary tools owe an intellectual debt to DOE-sponsored models, and in turn, the DOE-sponsored models frequently owe an intellectual debt to industry-sponsored researchers.

Researchers in the DOE Combustion Technology Program have advanced the understanding of the lean fuel mixture limits on combustion, engine knock, and the formation of nitrogen oxides and particulates in advanced engine concepts. Specific improvements to the design process used by industry and facilitated by the DOE Combustion Technology Program are as follows:

- Computer models similar to the DOE-sponsored MAGIC, a two-dimensional model of gas flow, can be used for designing pulse-preserving manifolds and exhaust plumbing for improving engine breathing and performance.
- KIVA, a three-dimensional model that numerically simulates evaporating fuel spray and fluid dynamics on nonuniform mixtures during combustion, can be used for assisting in the design of combustion chambers for advanced engine designs. As a research tool, KIVA has been used to better understand the combustion process of the two-stroke engines. It has also been used by one automotive engine manufacturer to improve the fuel economy of some current/standard designs.
- DOE-sponsored laser diagnostic tools and chemical kinetic models of auto-ignition chemistry help reduce knock and pollution products.
- A fiber-optically instrumented spark plug developed by DOE researchers at Sandia can be used to observe flame growth and propagation in the combustion chamber of production engines. Spark plug placement and orientation can now be studied without modifying the engine's geometry.

An additional benefit is that the collaborative efforts represent a key national resource which provides the nation with cutting-edge capabilities in in situ combustion diagnostics and multidimensional fluid mechanics and chemical kinetic modeling. Finally, university support has provided an important training ground for capable researchers who are accessible to industrial firms upon graduation.

Benefits of Automotive Engine Efficiency Improvement

Advanced engine concepts such as the two-stroke DISC engine may have potential for increased engine efficiency. Compared to the current four-stroke cycle, the two-stroke cycle has twice as many power strokes per unit of engine output (see Figures 3.2 and 3.3). The power output of the two-cycle is somewhat less than the equivalent four-cycle engine; however, the reduced two-cycle engine weight could help achieve higher future fuel-economy goals. In addition, the smaller two-cycle engine would offer lower engine compartment profiles. This would allow for greater stability because of a lower center of mass and higher fuel economy because of lower wind resistance. Two-cycle engines may offer multi-fuel capabilities and operate with increased compression ratios and lean fuel/air mixtures.⁽³⁾

A measure of the potential impact of advanced engine research sponsored by the DOE Combustion Technology Program is that a 1-mpg gain in automobile and light truck fuel economy would translate into a savings of 300,000 barrels per day of imported oil (\$7.5 million per day at \$25 per barrel).⁽⁴⁾

Figure 3.2. Operating Principle of the Four-Stroke-Cycle, Spark-Ignition Engine (Courtesy of Texaco's magazine, *Lubrication*.)

Figure 3.3. Operating Principle of the Two-Stroke-Cycle, Spark-Ignition Engine (Courtesy of Texaco's magazine, *Lubrication*.)

Future Development

Improving automotive gasoline engines continues to be difficult. Improving one parameter, such as emissions, may be at the expense of engine life, fuel economy, or some other important parameter. Industry and DOE-sponsored research aimed at understanding the lubrication and flame chemistry of combustion processes, improving computer models, and developing new diagnostic tools will continue to be essential to improving engine efficiency, operating life, pollution control, and performance in advanced engine concepts.

References

1. 49 CFR 531.5. 1989. National Highway Traffic Safety Administration, "Passenger Average Automobile Fuel Economy Standards." U.S. Code of Federal Regulations.
2. U.S. Department of Transportation. 1990. *National Transportation Strategic Planning Study*. U.S. Department of Transportation, Washington, D.C.
3. Hane, G. J. 1983. *Efficiency Evaluation of the DISC, DHC, and DI Diesel Engines*. PNL-4568, Pacific Northwest Laboratory, Richland, Washington.
4. U.S. Department of Energy, Energy Conversion and Utilization Technologies. 1989. *Combustion Technology Program: A Program Summary Document*. U.S. Department of Energy, Washington, D.C.

TECHNOLOGY CASE STUDY 3 - PULSE COMBUSTION

Key Results

A joint research program between the U.S. Department of Energy's (DOE) Sandia National Laboratories and Lennox Industries, Inc. has contributed to second-generation, pulse-combustion furnace designs that feature quiet operation and compact size over a broad range of frequencies and ratings. Significant additional energy savings will be realized as this technology is applied to new industries and integrated into new pulse-combustion furnace designs.

In pulse combustion, burning occurs in a tube (the combustor) in an oscillatory manner. In a typical practical application, a gas-air mixture is ignited within a combustion chamber at one end of the tube, creating a pressure pulse that closes the air and gas inlet valves and ejects combustion products at the rear end of the tube. The subsequent pressure drop within the combustion chamber reopens the valves and draws in more air and gas, which is ignited by residual hot gas left by the previous ignition.^(1,2) This cycle then repeats itself indefinitely at a frequency varying between 50 and 150 Hz (see Figure 4.1).⁽³⁾

Anticipating increased natural gas prices, Lennox Industries initiated work on applying pulse combustion to space heating in 1975. The American Gas Association, and later the Gas Research Institute, assisted in the technology development for the first pulse-combustion furnaces. Lennox introduced its first pulse-combustion furnace to the market in 1982. Development of second-generation, pulse-combustion technology, however, was slowed down by a lack of effective, inexpensive design and evaluation procedures.^(4,5)

Figure 4.1. Pulse Combustion Operating Principle⁽⁶⁾

AIC's Role

Lennox joined the DOE Combustion Technology Program, a part of the Energy Conversion and Utilization Technologies (ECUT) Division, in 1986. Funding for this technology program area continues through DOE's Advanced Industrial Concepts (AIC) Division. The purpose of this program is to develop a methodology that would allow the design of new pulse-combustion furnaces without resorting to "trial and error," a technique that is expensive, time-consuming, and may not result in the optimal design. The research conducted at Sandia Combustion Research User Facility sought to understand the following:

- internal acoustics, mixing, and combustion, specifically as it relates to noise and NO_x emissions
- effect of reactant physical and chemical properties on injection, mixing, chemical kinetics, and the effects of energy release in an acoustically driven flow
- the fundamental physical mechanisms responsible for the enhancement of heat and mass transfer processes.

Industry's Role

Lennox worked with staff at Sandia to translate this knowledge into practical improvements. The DOE program has shown that the criterion for proper phasing of the combustion and resonant pressure field (Rayleigh criterion) can be modeled as a linear sum of characteristic times. Each of these characteristic times represents the time required to independently mix the fuel and air (species mixing time), the time to mix the reactants with residual hot products (fluid mixing time), and the time required for chemical reactions to occur (chemical kinetics time).^(7,8,9) All these times contribute (to a first order approximation) linearly to a total ignition delay time, which must be phased correctly to satisfy Rayleigh's criterion for stable operation.

Based on these ideas, a Sandia Pulse Combustion Model was developed that relates combustor operating conditions and system geometry to combustor performance.⁽¹⁰⁾ Using the computer model, a second-generation, prototype pulse combustor has been developed that operates at a frequency significantly higher than the current system (80 to 160 Hz).⁽³⁾ The prototype utilizes a novel injection system that allows the fluid dynamic mixing time between the residual hot products and the incoming reactants to be varied continuously for optimal operation. Lennox may incorporate these design features into subsequent products.

Benefits of Pulse Combustion

Conventional gas furnaces send hot combustion products up the flue (typically at temperatures of 350°F to 450°F) due to venting requirements. Higher convective heat transfer rates mean pulse-combustion furnaces can extract more energy from the combustion products by reducing the exhaust gas temperatures by 200°F to 350°F, thus reducing the amount of energy lost up the flue. Heating efficiencies of 97% have been realized by the manufacturers of first-generation, pulse-combustion furnaces compared with 70 to 80% efficiencies for conventional gas furnaces.⁽¹¹⁾

Estimates of energy savings resulting from the use of Lennox high-efficiency, pulse-combustion furnaces from 1981 through 1989 are shown in Figure 4.2.⁽¹²⁾ Based on discussions with furnace dealers, these savings assume that high-efficiency, pulse-combustion furnaces have represented 10 to 25% of total gas furnace sales since 1981. The use of these high-efficiency furnaces represent an annual energy savings of 4.6 trillion Btus or \$32 million (at \$7 per million Btu) in 1989 and cumulative energy savings of about 0.02 quadrillion Btus or \$1.4 billion since 1981.

Similar savings could be realized in markets for furnaces of other sizes and fuel types should second-generation, pulse-combustion technology be exploited by U.S. industry. Second-generation technology has similar efficiencies, but it is quieter and more compact, thereby offering increased consumer satisfaction and product acceptance.

Future Development

Although the gas-fired, pulse-combustion furnace is now a commercial success, research and development is still needed to 1) extend second-generation technology into the marketplace and 2) develop new industrial applications of pulse-combustion technology. Pulse combustion could be used in furnaces that use other fuel types. Pulse combustion also appears to be a viable technology for the destruction of hazardous wastes. A patent has been granted to Sandia for a pulse-combustion drying system. Other promising industrial applications include lime calcining, raw coke oven gas treatment, coal gasification, perlite treatment, and carbon activation.⁽¹³⁾

Figure 4.2. Pulse Combustion Energy Savings

References

1. Keller, J. O., R. S. Gemmen, and P. K. Barr. 1990. "Premixed Combustion in an Oscillating/Resonant Flow Field. Part I: Experimental Investigation." Published in the Proceedings of the American Society of Mechanical Engineers (ASME), Dallas, Texas, November 25-30, 1990, "Thermo-Physical Aspects of Energy Conversion - 1990," AES - Vol. 16. Sponsored by the Advanced Energy Systems Division, ASME.
2. Barr, P. K., and J. O. Keller. 1990. "Premixed Combustion in an Oscillating/Resonant Flow Field. Part II: Modeling the Periodic Reacting Flow." Published in the Proceedings of the American Society of Mechanical Engineers (ASME), Dallas, Texas, November 25-30, 1990, "Thermo-Physical Aspects of Energy Conversion - 1990," AES - Vol. 16. Sponsored by the Advanced Energy Systems Division, ASME.
3. Keller, J. O., P. K. Barr, T. T. Bramlette, L. J. Evens, and R. N. Marchant. 1989. "Pulse Combustion: Demonstration of the Characteristic Mixing Time in a Commercial Burner." *Combust. Sci. and Tech.* 66:127-137.
4. Duffy, G. August 10, 1987. "Lennox Offers New Lifetime Pulse Residential Warranty." *Air Conditioning, Heating, and Refrigeration News*.
5. Brenchley, D. L., and H. J. Bomelburg. 1984. *Pulse Combustion - An Assessment of Opportunities for Increased Efficiency*. PNL-5301, Pacific Northwest Laboratory, Richland, Washington.
6. Corliss, J. M., et al. 1983. *Aerovulved Pulse-Combustion Systems for High Efficiency Commercial/Industrial Boiler*. GRI-80/0182, Gas Research Institute, Chicago, Illinois.
7. Keller, J. O., and C. K. Westbrook. 1986. "Response of a Pulse Combustor to Changes in Fuel Composition." In *Proceedings of the Twenty-first Symposium (International) on Combustion/The Combustion Institute*, pp. 547-555.
8. Keller, J. O., T. T. Bramlette, J. E. Dec, and C. K. Westbrook. 1989. "Pulse Combustion: The Importance of Characteristic Times." *Combustion and Flame* 75:33-44.
9. Keller, J. O., T. T. Bramlette, C. K. Westbrook, and J. E. Dec. 1990. "Pulse Combustion: The Quantification of Characteristic Times." *Combustion and Flame* 79:151-161.
10. Barr, P. K., H. A. Dwyer, and T. T. Bramlette. 1988. "A One-Dimensional Model of a Pulse Combustor." *Combust. Sci. and Tech.* 58:315-336.
11. Product Brochure. 1985. GSR14-861-SCG3 (34G57), Lennox Industries Incorporated, Dallas, Texas.
12. U.S. Department of Commerce. 1988. *Current Industrial Reports: Air Conditioning and Refrigeration Equipment, Including Warm Air Furnaces*. U.S. Department of Commerce, Washington, D.C.

13. *ECUT Program Bulletin*, DOE/ECU-88/5 (PB88-900405) U.S. Department of Energy, Office of Conservation and Renewable Energy, Washington, D.C.

TECHNOLOGY CASE STUDY 4 - THIN-FILM OXYGEN UPTAKE TEST (TFOUT) FOR ENGINE OIL OXIDATION

Key Results

In the past, laboratory tests, followed by fleet field tests, provided the only reliable method of comparing the effectiveness of various lubricant formulations. These tests are expensive and time-consuming. A new inexpensive procedure, perfected with DOE funding, can now dramatically reduce the cost of evaluating lubricant formulations. The Thin-Film Oxygen Uptake Test (TFOUT) is a bench-scale test developed by the National Institute of Standards and Technology (NIST) to screen formulated engine oils, base fluids, and additives. Improved additives, a large factor in increasing the useful life of oils, have extended oil life from 3,000 miles per oil change in 1980 to as much as 7,500 miles per change for some new engines.

TFOUT simulates the conditions at the interface between piston ring zone and cylinder liner. First, measured amounts of test fluids, metal catalysts, fuel, and distilled water are weighed in a glass beaker. This glass beaker is placed in a stainless steel bomb that is equipped with a pressure gauge. The sealed bomb is pressurized with oxygen and placed at a 30-degree angle in an oil bath at 160°C and rotated at 100 rpm (see Figure 5.1).⁽¹⁾ During rotation, the test fluid mixes and a thin film forms on the glass wall of the beaker. The pressure of the container is recorded continuously. A rapid decrease in pressure indicates that the oil has begun to oxidize.

Because TFOUT measures the oxidative stability of the oil, the test is used to correlate oxidation characteristics with viscosity. TFOUT is not a substitute for engine tests, which also measure wear and the volatility and deposit control characteristics of lubricants. The American Society for Testing and

Figure 5.1. Schematic Drawing of Oxidation Test Apparatus
(Reprinted with permission of ASTM)

Materials (ASTM) has adopted the test as a standard test method (ASTM D-4742). TFOUT correlates very well statistically with the viscosity increase measured by the ASTM III D engine dynamometer test, which simulates high-temperature, high-load, highway operating conditions.

AIC's Role

Research leading to the development of TFOUT was initiated as a result of the Used Oil Recycling Act of 1980. This act mandated funding for engine testing of recycled oils. To facilitate public acceptance of recycled oil products, NIST (then the National Bureau of Standards) initiated a program to develop bench-scale test methods.⁽²⁾ Mandated funding for the program stopped in 1982 as a result of changing federal priorities. Funding was provided by DOE's Energy Conversion and Utilization Technologies (ECUT) Division.

In 1983, the ECUT tribology program initiated a joint DOE/NIST program to develop standardized testing procedures for engines. A research bench-scale test to evaluate the oxidative stability of automotive crankcase lubricants was developed in 1985. This test, TFOUT, was accepted as the ASTM standard in 1989. A small company currently manufactures a test kit for use by oil and additive producers all over the world.

Industry's Role

Industry acceptance of TFOUT has been based to a large extent on the need to develop new base oil stocks and additives to formulate fuel-efficient lubricants. As oil is being made from a wide variety of base stocks, the various base stocks require different additive packages. TFOUT provides a fast, effective method for screening new lubricants. For example, before TFOUT was available, Ciba-Geigy could afford to run only about 10 engine tests per year. Now they screen 100 additive compounds per year using TFOUT. Other TFOUT users are Mobil, British Petroleum, Shell, Castrol, Caterpillar Inc., and Cummins Engine Company.⁽³⁾

In addition, research conducted by NIST in support of TFOUT has led to the identification of the beneficial effects of small amounts of sulfur compounds and the detrimental effects of nitrogen compounds in base oils. This research contributed to the development of better lubricants, enabling car manufacturers to extend recommended oil change intervals.

Benefits and Potential Savings of TFOUTs

Because there is a good correlation between bench-scale and actual engine tests for oxidation, TFOUT tests are being used as a pretest by oil- and additive-producing companies. Oils that pass the TFOUT tests are then engine tested.

The use of TFOUTs has reduced both the time and the cost of testing new lubricants. Test results are available in less than 4 hours. About 90% of the development cost for a new lubricant occurs in the testing phase.

Each TFOUT oil-screening, catalyst kit (ASTM D4742 IIID) costs \$230. A new test-stand apparatus will cost between \$10,000 and \$20,000. Major engine-oil tests will cost between \$10,000 and \$15,000. About 500 TFOUT units are expected to be sold annually. Because each unit contains 15 samples, a potential of 7500 TFOUT tests could be conducted each year.^(a) When considering new additive formulas, screening can be accomplished with the TFOUT test at a fraction of the cost required for major engine-oil tests.

Future Development

TFOUT will play an important role in the continued development of standard and advanced engines, both of which are operating at ever higher temperatures. The development of advanced engines could be particularly affected by the lack of lubricant formulations that can withstand high temperatures. The benefits of high-temperature engines cannot be fully realized until tribological losses are minimized.

Current stocks of high-grade, tested oil are being depleted. New formulations are being developed, and used oil is being reconstituted. The oxidative stability of both can be quickly tested with TFOUT. Because of the role it plays in improving engine technology, TFOUT is also being continually improved. A modified thin-film oxygen uptake test (MTFOUT) has been developed for use with oils being tested under a new ASTM engine sequence (III D).⁽⁴⁾

References

1. American Society for Testing and Materials (ASTM). 1990. "Standard Test Method for Oxidation Stability of Gasoline Automotive Engine Oils by Thin-Film Oxygen Uptake (TFOUT)." D4742-88 reprinted from the Annual Book of ASTM Standards, American Society for Testing and Materials, Philadelphia, Pennsylvania.
2. Ku, C. S., and S. M. Hsu. 1984. "A Thin-Film Oxygen Uptake Test for the Evaluation of Automotive Crankcase Lubricants." *Lubrication Engineering* 40(2):75-83.
3. Solar Energy Research Institute (SERI). 1988. *Programs in Energy Conservation: Energy Conversion and Utilization Technologies*. NTIS-PR-360, U.S. Department of Commerce, Springfield, Virginia.
4. Ku, C. S., P. T. Pei, and S. M. Hsu. 1990. "A Modified Thin-Film Oxygen Uptake Test for the Evaluation of Lubricant Stability in ASTM Sequence IIIE Test." SAE Paper No. 902121, Society of Automotive Engineers, Warrendale, Pennsylvania.

(a) Letter of August 2, 1990, from J. M. Perez, Tribology Group, Ceramics Division, National Institute of Standards and Technology, Gaithersburg, Maryland.

TECHNOLOGY CASE STUDY 5 - NICKEL ALUMINIDE ALLOYS IN TURBOCHARGERS

Key Results

Under the sponsorship of the U.S. Department of Energy (DOE), scientists at Oak Ridge National Laboratory (ORNL) have developed a multi-phased nickel aluminide alloy (Ni_3Al) with high specific-fatigue strength (strength per unit weight) that increases with higher temperatures. This intermetallic alloy may be used as a replacement for the standard 713C alloy now used for the turbine rotor of engine turbochargers in heavy-duty diesel trucks. The high specific-fatigue strength at operating temperatures (1450°F) is expected to allow the rotor airfoil designs to approach a more ideal shape. Improved rotor designs are smaller in diameter and lighter in weight and, therefore, have a lower inertia, which leads to increased overall engine efficiency, improved throttle response, and lower exhaust emissions.

AIC's Role

Initially, ORNL discretionary funds were used to investigate intermetallic alloys. A joint program was developed between DOE's Office of Basic Energy Sciences, Office of Fossil Energy, Energy Conversion and Utilization Technologies (ECUT) Division and ORNL, which led to the establishment of an initial technology base for nickel aluminide. The nickel aluminide alloy exhibits high strength and resistance to oxidation at high temperatures. Brittleness appeared to be the alloy's major disadvantage. In FY 1983, researchers at ORNL found that doping the alloy with trace amounts of boron (B) produced adequate ductility and toughness because deformation would now occur in the grains instead of at the grain boundaries. ECUT continued joint sponsorship of work on B-doped Ni_3Al until FY 1987.⁽¹⁾ Funding for this technology program area continues through DOE's Advanced Industrial Concepts (AIC) Division.

Industry's Role

Owners and operators of heavy-duty diesel trucks are primarily interested in increased performance, fuel efficiency, and reliability. Cummins Engine Company, Inc. of Columbus, Indiana, is working with ORNL researchers to take advantage of the nickel aluminide alloy's characteristics by developing new processing and turbine design technologies to produce an improved turbocharger.

Benefits of Nickel Aluminide Turbochargers

Turbocharging doubles the power output of a diesel engine and vastly increases engine efficiency. A turbocharger has two rotors (turbine and compressor) mounted on a common, rotating shaft. Exhaust gas energy powers the turbine which, in turn, drives the compressor to force more air (compared with a normally aspirated engine) into the cylinder combustion chamber. With a greater mass of air in the cylinder, more fuel can be burned, generating a higher power output. The turbocharger is self compensating in that the air supply will track the fuel supply necessary for efficient combustion.

Approximately 30% of the total engine output energy is in the exhaust gas stream which circulates through the turbine. Because the turbocharger handles such a large proportion of energy from the engine, even a small increase in turbocharger efficiency could significantly affect performance and fuel consumption. Reductions in engine cost, weight, and size are possible with the increased power output available from improved turbocharger designs.

Nickel aluminide turbochargers will be able to operate over a wider air-handling range. With improved material properties such as high specific-fatigue strength, the designer can develop more ideal airfoil shapes for the turbine rotor that were previously not possible. Because nickel aluminide is an alloy, it offers some distinct advantages over ceramic technologies. The weldability of this metallic alloy is good, which allows the turbine to be welded directly to the rotating shaft. Investment casting technology allows for near final shape products. Because the alloy is metallic, finish machining is possible. New test methods are not necessary because current fatigue and nondestructive testing (NDT) methods used in the evaluation of conventional turbochargers are adequate to evaluate new designs.

Future Development

Success in the development of the nickel aluminide alloy for use in turbocharger turbine rotors could lead to their application on heavy-duty diesel trucks in the future. The alloy's strength and oxidation resistance at high temperatures is well established. Small weight reductions may also be possible over the conventional nickel-based superalloy.⁽²⁾ This would lead to lower inertia rotors and associated benefits (e.g., faster throttle response and higher efficiencies).

Before nickel aluminide turbines become a commercial reality, however, some processing techniques will have to be improved and made cost-effective. If some secondhand 713C alloy can be used from the current supply stream for nickel aluminide rotors, there could be potential cost savings when full-scale production is achieved. Market figures indicate that for the past 6 years, over 115,000 commercial diesel trucks have been sold annually.⁽³⁾ This represents a large potential market for turbochargers because nearly all diesel trucks have some type of turbocharging system.

Other companies are pursuing improved turbocharger performance by attempting to make them out of ceramic materials. Ceramic turbochargers have potential for significant performance and efficiency improvements. There are, however, significant developmental problems which may prevent commercial application for a number of years.

References

1. Carpenter, J. A., Jr., and J. J. Eberhardt. March-April 1989. ECUT Program Bulletin, DOE/ECU-89/2, PB89-900402, pp. 1T-3T. U.S. Department of Energy, Washington, D.C.
2. Molloy, W. J. October 1990. "Investment-Cast Superalloys, a Good Investment." *Advanced Materials & Processes* 138(4):23-30.
3. "U.S. Factory Sales of Diesel Trucks by Gross Vehicle Weight, Pounds." 1990. Motor Vehicle Manufacturers Association of the U.S. Inc., Detroit, Michigan.

TECHNOLOGY CASE STUDY 6 - USING "WHISKERS" TO STRENGTHEN CERAMIC CUTTING TOOL INSERTS

Key Results

Ceramics combine excellent mechanical properties of high hardness and stiffness with resistance to heat, corrosion, and wear. In addition, ceramics retain high strength properties at high temperatures.

Ceramics can present problems, however, because they are brittle and sensitive to microscopic flaws such as cracks, voids, and impurities. Brittle ceramics are subject to catastrophic failure. As a result, scientists have focused on toughening the ceramics by adding crystal fibers to form a ceramic matrix.

Whisker-reinforced ceramic (WRC) inserts can operate at high speeds in difficult machining applications involving high nickel-based materials such as Inconel. The WRC inserts operate at speeds ten to twenty times higher and last up to seven times longer than inserts made of conventional materials such as carbides. As a result, productivity is higher and machining costs are lower. According to some estimates, WRC inserts save 50% of total machining costs in some applications. An additional advantage is that if WRC inserts fail, the workpiece is not seriously damaged, whereas, tools made of conventional materials may damage the workpiece when they fracture.

AIC's Role

After some initial funding with seed money by Oak Ridge National Laboratory (ORNL), the U.S. Department of Energy (DOE) began funding ceramic research in 1983 because of potential applications to advanced heat engines. Studies conducted by DOE's Basic Energy Sciences Division of Material Sciences at ORNL indicated that ceramics could be strengthened by reinforcing them with long fibers.

Later, through its Energy Conversion and Utilization Technologies (ECUT) Division, DOE funded researchers at ORNL to investigate the possibility of using "whiskers" instead of long fibers to strengthen ceramics. Whiskers are very strong, single-crystal fibers that are typically 0.5 μm in diameter and 40 to 50 μm in length. These fibers are made from SiC , Si_3N_4 , TiC , and TiA . Funding for this technology area continues through DOE's Advanced Industrial Concepts (AIC) Division.

ORNL has successfully developed and patented whisker-reinforced ceramics. In August 1986, the first non-exclusive license was granted to ARCO Chemical Company (now Advanced Composite Materials) of Philadelphia. Nine other companies have since been licensed to use WRCs. Negotiations with four other companies are currently under way. If an end product is to be sold in the United States, a license condition stipulates that it must be manufactured in the United States.

Industry's Role

Currently, inserts for the metals-cutting industry is the primary application for WRCs. The metals-cutting industry is an excellent proving ground for WRC inserts because many of the materials used in

the aerospace and automotive industries are extremely tough. WRC inserts are particularly effective in the high-speed cutting required for high nickel-based alloys such as Inconel, hard-chill case iron, and high-strength steels.

The usefulness of conventional carbide inserts is limited in high-speed cutting operations because of the heat generated. Conventional carbide inserts require coolants to maintain operating temperatures at approximately 800°C. Ideal operating temperatures for some alloys are well above 800°C because at elevated temperatures the metal is in a plastic state and is, therefore, more easily cut. Because ceramic inserts can operate at elevated temperatures, WRC inserts are effective cutting tools for high nickel-based alloys such as Inconel. WRC inserts also have potential for applications in the wood and paper products industry as well as in aluminum can tooling.

Benefits of WRC Inserts

WRC inserts are marketed primarily for their ability to increase productivity of machining operations. Because WRCs can tolerate higher operating temperatures than conventional inserts, machining can take place at higher speeds. For example, by using WRC inserts, a major gas turbine manufacturer reduced a 5-hour machining operation to 20 minutes. The company estimates this one operation will save \$250,000 annually.

Although an WRC insert may cost from three to four times as much as a conventional carbide insert, productivity increases of five to twenty times can result in savings that offset the increased insert cost. Direct energy savings are expected to be minimal because the increase in operating speed results in higher energy use. However, there may be indirect energy savings from reduced heating, ventilating, and air conditioning requirements.

Future Development

The market potential for WRCs is excellent. More research is needed to develop new WRC formulations and new techniques that reduce the cost of production. The cutting tool industry is a \$1-billion-a-year market. WRCs account for about \$10 to \$15 million of that market.

If the cost of materials and fabrication is reduced, the use of WRC inserts could grow rapidly. Reduced production cost will be important to opening up many additional industrial applications. Additional machining applications will also emerge if WRC inserts are developed that do not react chemically with ferrous materials at high operating temperatures.

In addition to the need for cost reduction and the development of new formulations, several other factors have slowed the acceptance of WRC tools:

- Potential users do not understand how much ceramics increase productivity.
- Machining centers frequently cannot operate at the spindle or table speeds ceramics require.

- Machine operators have been taught to avoid operating at speeds that produce red to white hot chips. WRC inserts, however, must operate at these speeds to gain the desired benefits and to avoid premature failure of the tool.

The use of WRC cutting inserts will likely increase as companies develop confidence in the operating conditions required.

Bibliography

Chemical & Engineering News. February 1, 1988. "Ceramic Composites Emerging as Advanced Structural Materials."

Research and Technology Utilization. August 1988. "A Report of the Energy Research Advisory Board to the United States Department of Energy."

International Journal of Refractory & Hard Metals. March 1988. Page 8.

Paulone, S. October 1989. "Living in a New Material World." *Material World*, pp. 51-56.

Cutting Tool Engineering. October 1989. Page 8.

TECHNOLOGY CASE STUDY 7 - VAPOR-PHASE LUBRICATION

Key Results

Liquid lubricants can be used on bearing surfaces at higher-than-normal temperatures for short time periods; however, they tend to deteriorate over time. Sludge and varnish collect, and deposits form and stay in the contact area, clogging the bearing and the recirculation system. Solid lubricants and self-lubricating composites can be used at high temperatures, but they are hard to reapply, less effective than liquid lubricants, and prone to wear and failure.

The principle of vapor-phase lubrication is the use of an oil vapor to deliver sufficient lubricant to form a continuous lubricating film on the critical load-carrying portion of a bearing. Tests show that this thin film of oil can lubricate as effectively as the film resulting from flooding the points of friction with liquid lubricant.

Improved vapor-phase lubrication processes have been developed, with funding from the U.S. Department of Energy (DOE), that can perform successfully for long periods in systems under heavy loads at temperatures ranging from 250°F to over 1000°F. Unlike liquid lubricants, which dilute and wash away, vapor-phase lubricants form a continuous film on the load-bearing surface.⁽¹⁾ The result is a significant reduction in wear and friction.

AIC's Role

High temperature lubrication is also important in several metal-forming operations such as molten steel die casting. Early work at Penn State sponsored by the state of Pennsylvania established vapor-phase lubrication as an effective way to apply continuous lubricating film to a hot metal surface.⁽¹⁾ Tributyl phosphate proved to be an excellent vapor-phase lubricant for molten steel and aluminum die casting.

Research sponsored by DOE's Energy Conversion and Utilization Technologies (ECUT) Division since 1983 at Penn State has expanded the number of lubricants studied for vapor delivery to include essentially all classes of conventional liquid lubricants, including mineral oils, synthetic hydrocarbons, organic acid esters, silicones, polyphenyl ethers, and other phosphate esters.⁽¹⁾ These studies demonstrated the capabilities of vapor-phase lubricants to reduce wear on both steel, ceramic, and mixed steel-on-ceramic surfaces. Today, Penn State researchers continue to play a major role in the demonstration of vapor-phase lubrication. They are working with Martin Marietta to demonstrate the use of vapor-phase lubrication in forging applications.

Industry's Role

Vapor-phase lubrication technology is in the process of being transferred to private industry. Recently, ALCOA investigated vapor-phase lubrication in ceramic processing and in the warm rolling of aluminum. In a low-speed sliding test conducted at ALCOA in Pittsburgh, vapor-phase lubrication

reduced friction by three to four times the coefficient of friction on a non-lubricated surface. Another test using rotating balls ran for 1 hour at a temperature of 1300°F and 300,000-psi stress. The average friction coefficient achieved was 0.06. ALCOA has not yet applied the technology to the warm rolling of aluminum because additional work is needed to uniformly deliver the lubricant to the hot metal surface.

Advanced ceramics components are being tested in equipment for high-temperature applications (up to 1600°F) such as the low-heat rejection, adiabatic diesel engine. The efficient and prolonged operation of such engines depends, in part, on lubrication that provides a uniform film that can withstand heavy loads and high temperatures for long periods. Detroit Diesel has built a prototype low-heat rejection engine, which they have successfully operated at nearly 1000°F using vapor-phase lubrication. Plans include further testing and evaluation of the diesel engine.

Benefits and Potential Savings of Vapor-Phase Lubrication

Industry in the United States may be losing as much as \$100 billion annually through wear and friction, i.e., tribological losses. The cost of these losses is incurred not only in repairing and replacing equipment, but also in production downtime and the necessity of overdesigning systems and components to offset premature failure of equipment. Savings of an estimated \$16 to \$27 billion may be possible through application of technologies designed to reduce tribological losses.⁽²⁾

High-temperature lubrication could also provide significant savings in energy as well as improved pollution control.⁽¹⁾ Application of the technology to vehicles alone could potentially save the United States as much as a million barrels of gasoline per day.⁽³⁾

Future Development

Vapor-delivered lubrication is especially promising for applications in the transportation sector using materials such as ceramics, cermets, and composites; high-temperature advanced diesel engines; aircraft gas turbine engines and large natural gas-fired engines.

Vapor-phase lubrication can be achieved by using the basic formulations of conventional volatile liquid lubricants. It is considered an enabling technology which may lead to new tribological technologies and processes. The demand for vapor-phase lubrication will increase with the emergence of new technologies involving advanced materials and high-temperature operations.

References

1. Klaus, E. E. 1988. "Vapor Delivery--A Technique Designed for High-Temperature Lubrication." *Energy Conversion and Utilization Technologies Program Bulletin*. DOE/ECU-88/3, U.S. Department of Energy, Washington, D.C.
2. Jahanmir, S., N. S. Eiss, L. D. Wedeven, M. B. Peterson, and H. S. Cheng. March 1990. "Tribology and Mechanical Systems." *Mechanical Engineering*, pp. 64-67.

3. Berger, H. June 1990. "Engines of Ceramic, Oiled by Vapor." *Research-Penn State*, 11(2):E4-E5.
Pennsylvania State University, University Park, Pennsylvania.

TECHNOLOGY CASE STUDY 8 - TEMPERATURE ABUSE SENSORS

Key Results

In the past, the use of enzymes as practical catalysts in organic chemistry was hindered by the necessity to carry out enzymatic reactions in water, a poor medium for most industrial chemical processes. However, recent U.S. Department of Energy (DOE)-funded research into enzyme reactions has led to the discovery that several different enzymes can efficiently function in nearly anhydrous (water-free) organic solvents. This emerging field of enzymatic catalysis in nonaqueous media could result in better tasting, nutritional food products and new processes, such as enzyme-based temperature abuse sensors for measuring the freshness and safety of food. Such sensors would allow food inspectors or consumers to examine perishable food for freshness at the point of delivery. In another application, they would help consumers determine when a microwave meal is done.

AIC's Role

The fundamental research to understand the mechanisms for enzyme deactivation at high temperatures was begun at the Massachusetts Institute of Technology (MIT) in the early 1980s under National Science Foundation sponsorship. Research into the concepts of enzyme catalysis in nonaqueous media began in 1985 at MIT, under the DOE Energy Conversion and Utilization Technologies (ECUT) Program.⁽¹⁾ Currently sponsored by the DOE Advanced Industrial Concepts (AIC) Biological and Chemical Technologies Research Program, this work is managed by DOE Headquarters.

In 1987, MIT, realizing the possibility of spin-off applications from DOE-sponsored research, applied for two patents as follows:

- an enzyme-based temperature-abuse sensor based on enzymes that function in an organic liquid (paraffin)
- an enzymatic apparatus for detecting toxic gases or for determining the freshness of food.^(2,3,4)

To capitalize on these and other enzyme-based technologies, the inventor of the biotechnology put together an investment portfolio, found several investors, and formed the company, Enzytech Corporation. Enzytech licensed the enzyme sensor technology from MIT with the intent to commercialize these and other technologies.

Industry's Role

Enzytech conducted a number of market studies for enzyme-related technologies, including several applications of the two MIT enzymatic sensor licenses. Several technologies were determined to be promising. However, applications of the two licenses did not have sufficient market potential to be funded further with the limited resources available. Consequently, Enzytech terminated its licensing agreement with MIT.

Today, Enzytech, located in Cambridge, Massachusetts, is a company organized around several different applications of enzyme technology. The general knowledge base from DOE-sponsored research was instrumental in helping form the new company. The company has coined the term "protein enhancement" to describe its technology, and it seeks to use nonaqueous enzyme technology to "research, develop and commercialize value-added products for the pharmaceutical and food industries."⁽⁵⁾

Benefits of Temperature Abuse Sensors

Before terminating its license with MIT, Enzytech, through a market assessment, determined that the two following types of temperature abuse sensors had significant commercial potential:⁽⁶⁾

- time-temperature indicators (TTIs) - sensors that are designed to monitor the combined time-temperature history of a product by providing an "integrated" response
- "doneness" indicators (DIs) - high-temperature threshold sensors that are used to identify a product that has achieved a specified temperature either instantaneously or for a preset period of time.

Time-temperature indicators could be used by the food industry in conjunction with controlled atmosphere packaging (CAP). CAP uses nitrogen or carbon dioxide inside an oxygen-barrier plastic packing to inhibit bacterial growth and thereby extend the product shelf life of refrigerated appetizers, salads, dinners, and entrees. CAP technology is very attractive to food manufacturers because it allows them to eliminate preservatives, as well as fulfill the ever-increasing demand for convenient, fresh-tasting products.

The need for TTIs arises out of the potential liability and health hazards created by eliminating preservatives in perishable foods. TTIs help ensure that product integrity is maintained during shipping and storage, as well as when the product remains on the refrigerator shelf. TTIs for CAP were not pursued by Enzytech, because several competitors already had alternative TTI products on the market. The most significant problem, however, was that enzyme-based TTIs need to be applied to food packages at temperatures below 34°F (to prevent deterioration of food quality). Investment in technology to print, coat, stamp, or otherwise incorporate wax-based sensors onto packages at these temperatures was not considered feasible.

"Doneness" indicators can be used to help consumers determine when a microwaveable product is sufficiently cooked. Because microwave power levels vary (from 400 to 600 W), it is not unusual for a consumer to over- or undercook a product, even when following the manufacturer's directions. Many of the traditional signs of "doneness" that are apparent in conventional cooking are absent with microwave cooking.

At present, DIs are currently being employed on one line of microwave dinners, at a cost of about 20¢ to 40¢ per unit at the retail level. It is believed that DIs would be widely incorporated into microwave products if the cost of the devices at the retail level could be reduced 2¢ to 4¢ per unit. At present, technology is not available to produce enzyme-based DI sensors encapsulated in wax at this cost.

Future Development

Temperature abuse sensors have been developed to "proof-of-principle," but technical problems and lack of market demand have prevented their implementation. Temperature abuse sensor technology could become a commercial success with the proper financial backing, especially if applications were mandated by the Food and Drug Administration (FDA). Economic incentives would then be sufficient to develop technology to coat, stamp, or otherwise incorporate the devices onto food packages, even at low temperatures.

The flexibility of nonaqueous enzyme technology would allow temperature abuse sensors to be developed with the following features: signal only when the product life is substantially gone, easy end-user interpretation via a descriptive message, no activation of the indicator required, simple construction from food-grade materials, and easy storage before use. To date, no temperature abuse sensors introduced into the marketplace have all of these features.

A lucrative market already exists for DIs if inexpensive enzyme-based sensors could be developed. The microwave food market is expected to experience double-digit growth for the foreseeable future. As of 1990, some 54 million U.S. households had microwave ovens, and sales of microwaveable packaging for prepared foods were forecast to be at about \$340 million by 1991. Some industry sources expect that microwaveable products will become a multibillion dollar industry within the next 10 years.⁽⁶⁾

The CAP industry would benefit from the development of an inexpensive sensor that mimics microbiological activity and hence is a good predictor of product spoilage. In 1990, the domestic CAP market was about \$200 million a year. Worldwide, more than 250 million pounds per year of foodstuffs (red meat, coffee, grated cheese, etc.) were sold in CAP. By the year 2001, this number is expected to increase to 3 billion pounds annually.

References

1. Energy Conversion and Utilization Technologies Division (ECUT). 1989. *Biocatalysis Project Annual Report FY 1988*. DOE/CS-66001-12, Office of Scientific and Technical Information, Oak Ridge, Tennessee.
2. Barzana, E., A. M. Klibanov, and M. Karel. 1989. "A Colorimetric Method for the Enzymatic Analysis of Gases: The Determination of Ethanol and Formaldehyde Vapors Using Solid Alcohol Oxidase." *Analytical Biochemistry* 182:109-115.
3. Dordick, J. S., M. A. Marletta, and A. M. Klibanov. 1987. "Polymerization of Phenols by Peroxidase in Nonaqueous Media." *Biotechnology and Bioengineering* 30:31-36.
4. Boeriu, C. G., J. S. Dordick, and A. M. Klibanov. 1986. "Enzymatic Reactions in Liquid and Solid Paraffins: Application for Enzyme-Based Temperature Abuse Sensors." *Biotechnology* 4:997-999.
5. Enzytech Corporation. Product Information. Enzytech Corporation, Cambridge, Massachusetts.
6. Market Assessment. 1990. Enzytech Corporation, Cambridge, Massachusetts.

TECHNOLOGY CASE STUDY 9 - USING MOLECULAR MODELING TOOLS TO SOLVE CHEMISTRY PROBLEMS

Key Results

To date, the U.S. Government's support of scientific research into molecular modeling software has been instrumental in advancing the technology and its commercial applications to the chemical industry. Computer models can help replace the time-consuming screening techniques that chemists have traditionally used in their search for useful new compounds. Using the interactive simulation capabilities of models, chemists are able to observe detailed, scientifically accurate, molecular structures.⁽¹⁾ In the future, this technology will enable chemists to predict the structure and dynamics of motion as molecules interact, react, and combine. This capability will greatly enhance the ability to develop and produce chemicals to increase U.S. competitiveness in the global chemicals market.

Recent advances in molecular modeling technology are being widely applied in industry to solve complex chemistry problems. Computer software programs that model molecular systems are permitting scientists in the chemical and pharmaceutical industries to simulate and predict biological, chemical, and material properties. This capability has significantly shortened the research and development cycle for new chemical compounds. Other applications of this technology can be found throughout industry, from film processing to automobile manufacturing. Molecular modeling research conducted under the U.S. Department of Energy's (DOE's) Energy Conversion and Utilization Technologies (ECUT) Program has contributed significantly to the rapid advancement of this technology.

AIC's Role

Early research into the concepts that led to the molecular modeling and simulation software tools was sponsored primarily by grants from the National Science Foundation and was conducted by scientists at the California Institute of Technology. In 1980, the DOE, under the ECUT Program, began funding the research that evolved into the present-day molecular modeling technology. This research, known as the Chemical Processes Project, was managed by the Jet Propulsion Laboratory, California Institute of Technology.⁽²⁾

In 1982, the Chemical Processes Project was reorganized and renamed as the Biocatalysis Project to focus on providing an enabling technology base for new industrial bioprocess applications.^(2,3) One of the major areas of research for the Biocatalysis Project was molecular modeling and applied genetics. The objective of this research was to develop and test computer simulation models capable of predicting the activity of enzymes in solution and of enzymes immobilized on supports.^(2,3) Much of the current commercial success that the molecular modeling software industry is experiencing is attributable to the results of this ECUT-funded research. Funding for this technology program area continues through DOE's Advanced Industrial Concepts (AIC) Division.

Industry's Role

Today, companies that developed molecular modeling software in the 1980s are shifting their emphasis from research and development to marketing, and the market for these software tools is rapidly expanding.⁽¹⁾ Molecular modeling tools have a wide variety of engineering and biological applications in industry.

Molecular Simulations, Inc. (MSI) of Sunnyvale, California (formerly BioDesign, Inc.), a privately-held company with close ties to the Biocatalysis Project, is making rapid advancements in the molecular modeling software business. It has become the leading developer and supplier of these software tools that enable scientists and engineers to scientifically simulate biological, chemical, polymer, and material systems.⁽¹⁾

Today, MSI is successfully marketing several software packages. One of these is designed primarily to simulate biological molecules, and its interactive graphical display and analysis capability allows molecular simulations to be done in real time. Parameters can be modified on the basis of trends that develop as the simulation is being carried out.⁽⁴⁾

Pharmaceutical and chemical companies are using this software to design new chemical compounds and to improve on existing designs. A major automobile manufacturing company is using it to look at advanced battery designs for lithium salts in an amorphous polymer. This software package is also finding applications in the film processing, communications, and oil industries as an invaluable molecular modeling tool.

MSI recently began marketing another software package similar in design and capability to the one discussed above but oriented to the needs of polymer scientists.⁽⁵⁾ Using this software tool, scientists and engineers can predict the properties of polymers before they are synthesized. This has potential for the design of a host of new synthetic materials. One company has already used this software tool to develop a new way to make cyclic plastics and is in the process of testing new materials.

MSI has recently released a third molecular modeling software model that incorporates the best features of both the software programs discussed above.⁽⁶⁾ With this model, scientists can more accurately predict and graphically display molecular structures in three dimensions. This software tool combines the empirical properties embodied in force fields with experimental inter-proton distance and angle data obtained from spectroscopy to generate representations of molecules that may not be available in database libraries. It is especially effective in areas such as protein research, where little is known about the molecule's preferred structure.

Benefits of Using Molecular Modeling Tools to Solve Chemistry Problems

The chemical industry comprises a huge market including pharmaceutical, biotechnology, polymers, and material segments. The ability of molecular design software tools to shorten the research and development cycle and the time-consuming screening techniques that chemists have traditionally used in their search for useful new compounds has the potential to result in dramatic labor and capital investment savings in the industry.

Shortening the research and development cycle in chemical production through use of these software tools should result in direct energy savings, because actual production steps and trial-and-error procedures are eliminated. Also, improved product performance could lead to indirect energy savings.

In addition, increased product quality, better drugs, and stronger materials, stem from software scientists' ability to use these computational tools to scientifically design, test, and visually observe new materials prior to formal development.

Future Development

Development and marketing of computer-aided molecular design software tools is an expanding business. With computer hardware costs continuing to fall, and software performance improving, the market for this product is projected to grow at 30% per year for the coming decade. By 1995, development and marketing of molecular design software tools is projected to approach a \$1-billion-per-year business.⁽⁷⁾

Already, MSI states in its marketing literature that it "maintains over 200 perpetual licenses in commercial sites in the U.S. and overseas."⁽⁷⁾ It also maintains over sixty academic accounts in the United States, Europe, and Japan, and lists an impressive collection of well-known companies as its major customers.⁽⁷⁾

Companies such as MSI will continue to improve on the technology, marketing a less-expensive, more user-friendly and technically accurate software tool capable of being run on a greater variety of computational systems. Because computers are an integral part of the modern chemical laboratory, software and hardware design will be an important factor in the future growth of the molecular modeling software industry.

The increasing competition in the pharmaceutical and chemical industries will fuel this growth, primarily in the area of developing catalysts for the production of drugs, specialty chemicals, bulk chemicals, and energy-important fuels.

References

1. "BioDesign's Software Advances Computer-Aided Molecular Design." February 1, 1988. *Chemical & Engineering News* 66:24-25.
2. U.S. Department of Energy. January-December 1986. *Energy Conversion and Utilization Technologies - The 1986 ECUT Program Bulletin Compendium*. DOE/ECU-86/7, National Technical Information Service, Springfield, Virginia.
3. U.S. Department of Energy. March 1988. *Biocatalysis Project Annual Report FY 1987*. Energy Conversion and Utilization Technologies Program, Office of Energy Systems Research, DOE/CS-66001-11, Jet Propulsion Laboratory, California Institute of Technology, Pasadena, California.
4. *BIOGRAF Version 2.2 Features*. 1989. Molecular Simulations, Inc., Sunnyvale, California.

5. ***POLYGRAF - Applications in Polymer Research.*** 1989. Molecular Simulations, Inc., Sunnyvale, California.
6. **"New Software Weds Molecular Modeling, NMR."** March 26, 1990. *Chemical & Engineering News* 68:16.
7. ***Molecular Simulations, Inc., Corporate Profile.*** 1989. Molecular Simulations, Inc., Sunnyvale, California.

TECHNOLOGY CASE STUDY 10 - MARKETS FOR GENETIC ENGINEERING TECHNOLOGIES

Key Results

For the past 150 years, the aerobic fermentation industry has relied on different mechanical designs to improve oxygen transfer to organisms in fermentation because this step is the major rate-limiting problem facing the industry. Overall productivity increases and lower processing costs could be achieved if a new method to simplify the oxygen transfer process was developed. For this process, microorganisms would function at oxygen tensions that are normally fatal or induce undesirable anaerobic growth.

Recent advances in genetic engineering research have led to developing and licensing of two important proprietary technologies with potential commercial applications: a hemoglobin gene that can be cloned into the genetic structure of different organisms and an oxygen switch or gene regulation site that controls the hemoglobin gene (and other genes). Potential commercial markets for microorganisms using these technologies include chemical production, mining, and waste treatment, to name only a few. Research funded by the U.S. Department of Energy's (DOE) Energy Conversion and Utilization Technologies (ECUT) Program has been key in developing these technologies. An independent company, Exogene Corporation, has formed to commercially exploit them.

AIC's Role

The ECUT-funded research that led to the development of the hemoglobin gene and oxygen switch technologies began in 1985 at the California Institute of Technology (Caltech) under the Biocatalysis Project. This project is managed by Caltech's Jet Propulsion Laboratory.

As part of this research, ECUT funded two studies: a 1985 study, "Models and Experimental Probes for Metabolic Engineering Analysis and Synthesis," and a 1988 analysis, "Kinetics of Recombinant Organisms," which has since been terminated. Today at Caltech, the original research is still being funded under a task titled, "Metabolic Engineering."⁽¹⁾ Funding for this technology program area continues through DOE's Advanced Industrial Concepts (AIC) Division.

During the course of this research, the possibility of exploiting the capabilities of the hemoglobin gene in microorganisms such as *E. coli* and yeast was investigated. This research has resulted in patent applications from which two licenses were taken:

- technology for insertion of hemoglobin genes into cells to enhance cell growth under oxygen-limited conditions
- oxygen-sensitive genetic switch to enhance synthesis of cloned proteins (enzymes, analytical reagents, pharmaceuticals).⁽²⁾

Although these technologies have not yet enjoyed industrial practice, the role of the ECUT Program in the growth of this industry has been an important one. For example, the experience and knowledge gained with ECUT-funded research was essential to one company (Exogene) gaining equity financing.

Industry's Role

The Exogene Corporation, Pasadena, California, was founded in 1987 to commercialize the hemoglobin gene and oxygen switch technologies.⁽³⁾ The researchers who developed the concepts at Caltech with ECUT's backing were instrumental in starting the company. Exogene obtained the technologies from Caltech through an exclusive world-wide license.

Exogene is currently conducting laboratory and market research aimed at further developing the technologies for application in chemical and pharmaceutical production, mining, and waste treatment. Through in-house and cooperative research and development activities, Exogene is demonstrating the technologies and exploring their applications to an expanding array of products, cell types, and process configurations. Once demonstrated and proven feasible, Exogene plans to license the technologies to users. Several companies are currently evaluating the technologies for potential commercial use.

Benefits of Genetic Engineering Technologies

In the biochemical engineering and production area, the advancement in hemoglobin technology could affect many processes that use aerobic fermentation. These effects include reduced operating costs for fermenter systems; the ability to use any carbon source more completely, which improves overall productivity; and providing new opportunities for fermentations that might not normally occur. Applications include fermentation for the production of chemicals and fuels and for waste processing. Key benefits to society include lower costs and energy conservation.

Future Development

The commercial future looks promising for these genetic engineering technologies. Three markets (see Figure 11.1) have the highest potential to be penetrated.⁽⁴⁾ The first is biotechnology, which includes the proteins made by genetically engineered bacteria and eukaryotic cells, with a projected annual sales of \$5 billion by 1992. The second market is the pharmaceutical industry (antibiotics, steroids, etc.), with current annual sales in excess of \$2 billion. Annual operating and capital costs exceed \$5 billion for the long-range application of using microorganisms for waste treatment. In addition, specialty chemicals, including amino acids, nucleotides, vitamins, pigments, and flavors, are a multi-billion dollar annual market.

According to SRI International, sales of biotechnology-derived health care products in the United States are projected to reach \$4 billion in 1992 and \$20 billion by the year 2000.

Figure 11.1. Potential Markets for Genetic Engineering Tools

References

1. Energy Conversion and Utilization Technologies Division (ECUT). 1989. *Biocatalysis Project Annual Report FY 1988*. DOE/CS-6600112, Office of Scientific and Technical Information, Oak Ridge, Tennessee.
2. C. Khosla and J. E. Bailey. February 1989. "Heterologous expression of a bacterial hemoglobin improves the growth properties of recombinant *Escherichia coli*." *Nature* 331(6157):633-635.
3. *Exogene Corporation Overview*. 1988. Exogene Corporation, Pasadena, California.
4. *Market Assessment*. July 28, 1990. Exogene Corporation, Pasadena, California.

TECHNOLOGY CASE STUDY 11 - HIGH-PRODUCTIVITY FLUIDIZED-BED BIOREACTOR

Key Results

Beginning in 1985, the U.S. Department of Energy (DOE) sponsored research at Oak Ridge National Laboratory (ORNL) that investigated various bioreactor designs.⁽¹⁾ As a result of this research, a novel fluidized-bed bioreactor (FBR) was developed that contains microorganisms immobilized in a supporting gel bead that constantly interacts with a feed material in a reactor column.

Sugars (e.g., glucose, fructose, sucrose, and the hydrolysates of cellulosic carbohydrate substrate, which include wood and paper products and agricultural waste such as corn stover) can be fermented in a continuous process to produce valuable pharmaceutical and chemical products such as lactic acid and ethanol. The bioreactor's anaerobic breakdown of glucose into ethanol by *Zymomonas mobilis* has a much higher conversion yield (approaching 98% theoretical yield) when compared with batch fermentation processes using yeasts (92%-95% theoretical yields).⁽¹⁾ Ethanol is an important liquid fuel for internal combustion engines and is used to increase octane level and extend gasoline as a base fuel. In addition, nonsterile feeds can be used without detrimental effects. ORNL may license this technology to private industry in the future.

AIC's Role

ORNL's bioreactor engineering research was initiated in 1985 with joint funding from DOE's Office of Basic Energy Sciences, Office of Fossil Energy, and Energy Conversion and Utilization Technologies (ECUT) Division within the Office of Conservation and Renewable Energy. Funding continues through DOE's Advanced Industrial Concepts (AIC) Division. This joint research has led to a bioreactor design that has more than ten times the volumetric productivity of ethanol over conventional batch-processing methods.⁽²⁾ In 1987, the initial studies were expanded to include research into the anaerobic micro-environment of the microorganisms. Maintaining an oxygen-free environment for the organisms is costly under typical operating conditions, yet necessary for fermentation of the substrate feed to occur. Immobilizing the microorganism in a highly porous encapsulating gel bead (up to 5 wt% Kappa-carrageenan) with an oxygen-reducing catalyst created an anaerobic environment which solved this process problem. The encapsulating gel bead also protects the microorganisms from the mechanical stresses in the FBR. In 1988, a patent application was filed for this unique immobilization procedure.

Industry's Role

ORNL is currently involved in proprietary contract negotiations with a private company who may potentially license this technology. The A.E. Staley Co., Decatur, Illinois, an industrial ethanol producer, has assisted this research by providing raw corn dextrose feed material and scientific consultation for the laboratory experiments at ORNL. The National Corn Growers Association has provided some funds to help support research in a butanol fermentation FBR.

Benefits of Fluidized-Bed Bioreactor:

The FBR has important advantages over conventional batch-processing methods. The fluidized-bed allows for excellent mixing of reactor ingredients and interphase mass transfer. The immobilization of the microorganisms increases the biocatalyst concentration manyfold, with equivalent increases in the overall productivity. The immobilization also retains the desired microbes and confers strong resistance to contaminating microorganisms. The bead microenvironment can also be modified to control density and anaerobic conditions. The encapsulated microbes are robust and have been operated in an FBR for over 2 months without physical degradation.

This process can be modified to allow for continuous removal of the fermentation products that inhibit the microbial growth kinetics by adding an extractive phase. Useful products resulting from this fermentation process include ethanol, butanol, citric acid, acetic acid, and lactic acid. An adsorbent introduced into the FBR selectively and effectively removes the organic acid products.⁽³⁾ Recovery of the adsorbed products can be achieved by heating the sorbent in a circulating column⁽⁴⁾ or by extracting the solvent.

Distillation of the fermentation products is energy-intensive and often uses more energy than that captured in the recovered ethanol.⁽⁵⁾ Using a sorbent such as activated carbon/charcoal, a polymeric resin, or hydrous metal oxides for recovery requires only 25% of the energy used for distillation purposes. Activated charcoal is an example of a useful sorbent because of its large specific surface area (800-1200 m²/g), which allows for a high adsorption per unit mass.⁽⁴⁾ Adsorption accomplishes two important tasks: first, it removes the organic acids which are byproducts of fermentation and, second, it controls the pH level of the FBR so it will not be too acidic for fermentation to occur.

Additional savings in energy and raw materials occur because of the approximate 5% increase in theoretical yield with the FBR. The high volumetric productivity of the FBR (compared to conventional batch-processing methods) will allow smaller reactors to be built, thereby reducing capital costs. Cost and energy savings will result because substrates can be used that have not been sterilized. Substrate material, such as corn syrup and stover, are byproducts of farming and are renewable.

Future

The FBR technology competes well with conventional batch-processing technology because the volumetric productivity of the FBR technology is much higher than that of batch processing. FBR technology provides a higher ethanol yield at the same product concentrations. A number of exciting benefits of FBR technology are being simultaneously developed which may, in the future, lead to industrial-scale operations by companies who license the technology from ORNL.

The technical feasibility of the FBR technology has been proven, so larger-scale pilot projects can now be developed and tested. Before the technology can become a commercial success, additional development must occur. In particular, the amount of product captured by the sorbent in the recovery process needs to increase to be able to compete with chemical processing operations.

References

1. Eberhardt, J. J. and L. Keay. January-February 1989. "A Historical Perspective of the ECUT Catalysis/Biocatalysis Program 1980-1989." *ECUT Program Bulletin*. DOE/ECU-89/1, PB89-900401, pp. 1T-11T.
2. Davison, B. H., and C. D. Scott. 1988. "Operability and Feasibility of Ethanol Production by Immobilized *Zymomonas mobilis* in a Fluidized-Bed Bioreactor." *Appl. Biochem. Biotech* 18:(19-34).
3. Davison, B. H., and J. E. Thompson. 1991. "Simultaneous Fermentation and Separation of Lactic Acid in a Biparticle Fluidized Bed Bioreactor." Presented at the Thirteenth Symposium on Biotechnology for Fuels and Chemicals, Colorado Springs, Colorado, May 1991, and submitted to the Proceedings published in *Applied Biochemistry & Biotechnology*.
4. Bradley, K. J., M. K. Hamdy, and R. T. Toledo. 1987. "Physicochemical Factors Affecting Ethanol Adsorption by Activated Carbon." *Biotechnology and Bioengineering* 24:(445-452).
5. Pitt, W. W. Jr., G. L. Haag, and D. D. Lee. 1983. "Recovery of Ethanol from Fermentation Broths Using Selective Sorption-Desorption." *Biotechnology and Bioengineering* 24:(121-131).

DISTRIBUTION

No. of
Copies

No. of
Copies

OFFSITE

- 12 DOE/Office of Scientific and Technical
Information

C. A. Amann
Research Fellow, Executive Department
Director, Engineering Research Council
General Motors Research Laboratories
30500 Mound Road
Warren, MI 48090-9055

J. E. Bailey
Chevron Professor for Chemical
Engineering
California Institute of Technology
Chemical Engineering 210-41
Pasadena, CA 91125

D. Chasan
CIBA-GEIGY
444 Sawmill River Road
Ardsley, NY 10502

H. L. Chum
National Renewable Energy Laboratory
1617 Cole Boulevard
Golden, CO 80401

- 4 Cummins Engine Company, Inc.
P.O. Box 3005
Columbus, IN 47202-3005
ATTN: C.P.J. Ahlers
P. F. Flynn
J. Mully
J. W. Patten

J. M. Davis
Assistant Secretary
Office of Conservation and Renewable
Energy
Forrestal Building
1000 Independence Ave., S.W.
Washington, DC 20585

Department of Energy
785 DOE Place
Idaho Falls, ID 83402
ATTN: L. Keay

- 2 Energetics, Inc.
7164 Gateway Drive
Columbia, MD 21046
ATTN: R. B. Abarcar
P. A. Roth

L. J. Evans
Senior Research Scientist
Lennox Industries, Inc.
P.O. Box 877
1600 Metrocrest Drive
Carrollton, TX 75011-0877

J. Greenleaf
Vice President, New Business
Development
Greenleaf Tool Corporation
1 Greenleaf Drive
Sagertown, PA 16433

A. Gross
Vice President of Research
Enzytech Corporation
64 Sidney Street
Cambridge, MA 02139

N. Hakim
Detroit Diesel Corporation
Mail Stop K-15
1300 W. Outer Drive
Detroit, MI 48239-4001

- 2 Improved Energy Productivity Division
Office of Industrial Technologies
Forrestal Building/CE-231
1000 Independence Ave., S.W.
Washington, DC 20585
ATTN: L. B. Schilling
D. E. Wiley

No. of
Copies

E. E. Klaus
Pennsylvania State University
Department of Chemical Engineering
108 Fenske Laboratory
University Park, PA 16802

A. Klibanov
Professor, Department of Chemistry
Massachusetts Institute of Technology
Department of Chemistry
Room 16-209
Cambridge, MA 02139

W. J. McLean
Sandia National Laboratories
P.O. Box 969
Livermore, CA 94550

- 3 National Institute of Standards and
Technology
Tribology Group, Ceramics Division
Mail Stop 220/A215
Gaithersburg, MD 20899
ATTN: S. M. Hsu
S. Jahanmir
P. Pei

F. A. Nichols
Project Manager, Tribology Program
Argonne National Laboratory
Building 212
9700 South Cass Avenue
Argonne, IL 60439

- 4 Office of Industrial Technologies
Forrestal Building
1000 Independence Ave., S.W.
Washington, DC 20585
ATTN: K. Friedman/CE-20
P. Salmon-Cox/CE-23
A. J. Streb/CE-20
D. Swink/CE-20

No. of
Copies

- 6 Office of Industrial Technologies
Advanced Industrial Concepts Division
Forrestal Building/CE-232
1000 Independence Ave., S.W.
Washington, DC 20585
ATTN: D. J. Boron
M. E. Gunn, Jr.
C. A. Sorrell
E. P. Huang Fu
B. Volintine
M. Quinn

- 5 Oak Ridge National Laboratory
Martin Marietta Energy Systems, Inc.
P.O. Box 2009
Oak Ridge, TN 37831-8218
ATTN: P. Angelini
B. H. Davison
R. Judkins
C. D. Scott
J. Soderstrom

- 2 Office of Transportation Materials
Office of Transportation Technologies
Forrestal Building
1000 Independence Ave., S.W.
Washington, DC 20585
ATTN: J. J. Eberhardt
J. M. Perez

B. Olafson
Vice President, Product Development
Molecular Simulations, Inc.
Western Science Center
199 South Los Robles Avenue, Suite 540
Pasadena, CA 91101

R. Palicka
President
Cercom, Inc.
1960 Watson Way
P.O. Box 70
Vista, CA 92083

No. of
Copies

G. R. Petersen
Biocatalysis Program
Jet Propulsion Laboratory
California Institute of Technology
4800 Oak Grove Drive
Pasadena, CA 91109

R. K. Sen
R. K. Sen & Associates
3808 Veazey St., N.W.
Washington, DC 20016

D. Siebers
Division Supervisor
Combustion Applications Division
Sandia National Laboratories
Livermore, CA 94551-0969

R. Tabaczynski
Ford Motor Company
Village Plaza, Suite #800
23400 Michigan Avenue
Dearborn, MI 48124

A. Thomas
Argonne National Laboratory
9700 South Cass Ave.
Argonne, IL 60439-4841

D. A. Wagner
Chief, Mechanical Technology
Allison Gas Turbine Division
General Motors Corporation
Mail Stop 548
P.O. Box 420
Indianapolis, IN 48208-0420

No. of
Copies

ONSITE

DOE Richland Field Office

R. B. Goranson

42 Pacific Northwest Laboratory

R. C. Adams
W. B. Ashton
R. S. Butner
D. E. Deonigi
J. A. Dirks
K. K. Daellenbach (10)
R. L. Eckert
L. L. Fassbender
M. P. Hattrup
K. H. Hughes
C. H. Imhoff
B. R. Kinzey
D. A. Seaver
D. L. Shankle
R. L. Watts
S. A. Weakley
G. L. Wilfert
J. K. Young (10)
Publishing Coordination
Technical Report Files (5)

END

**DATE
FILMED**

9 / 8 / 92