2

WSRC-TF-92-140

**CODE REQUIREMENTS DOCUMENT MODFLOW 2.1: A
PROGRAM FOR PREDICTING MODERATOR FLOW
PATTERNS (U)**

by I. K. Paik

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

Other Authors:

P. F. Peterson
University of California, Berkley

RECEIVED
JUL 21 1993
OSTI

This paper was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DOCUMENT: WSRC-TR-92-140

TITLE: MODFLOW 2.1: A PROGRAM FOR PREDICTING
MODERATOR FLOW PATTERNS (U)

DATE: MARCH, 1992

TECHNICAL REVIEW:

R.L. Garrett 3-16-92
Date
SAG/Functional Analysis
& Thermal Hydraulics

G.T. Geiger 3-17-92
Date
SAG/Functional Analysis
& Thermal Hydraulics

APPROVALS:

L.A. Wooten 3/20/92
Date
Manager of Safety
Analysis Group

M.J. Hitchler 3/25/92
Date
Manager of Reactor
Safety Research

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONTENTS

CHAPTER 1

INTRODUCTION	1-1
1.1 EXECUTIVE SUMMARY	1-1
1.2 CHANGES IN VERSION 2.1	1-1
1.3 THE PHYSICAL PROBLEM.....	1-1
1.4 ANALYTICAL INVESTIGATION.....	1-3
1.5 REFERENCES.....	1-4

CHAPTER 2

PHYSICAL AND MATHEMATICAL MODELS	2-1
2.1 OVERVIEW.....	2-1
2.2 NOMENCLATURE.....	2-2
2.3 VOLUME AVERAGING.....	2-4
2.4 MOMENTUM EQUATION NONDIMENSIONALIZATION	2-7
2.5 SPARJET MODELLING	2-10
2.6 NUMERICAL FORMULATION.....	2-12
2.7 PARTICLE TRACKING	2-18
2.8 DENSITY INTERFACE VORTICITY GENERATION.....	2-19
2.9 TEMPERATURE DISTRIBUTION FORMULATION.....	2-22
2.10 REFERENCES.....	2-22

CHAPTER 3

MODFLOW CODE STRUCTURE	3-1
3.1 SOLUTION METHODS.....	3-1
3.2 PROGRAM ARCHITECTURE.....	3-1
3.2 PROGRAM MAINTENANCE	3-2

CHAPTER 4

USER GUIDE	4-1
4.1 THE USER INTERFACE.....	4-1
4.2 THE DATA INPUT DECK.....	4-3

CHAPTER 5

PRELIMINARY CODE ASSESSMENT	5-1
5.1 COMPARISON WITH 1959 ISOTHERMAL FLOW TESTS.....	5-1
5.2 COMPARISON WITH 1975 SSS SYSTEM TEST.....	5-4
5.3 PREDICTED PERFORMANCE FOR K-REACTOR COASTDOWN CASE	5-10
5.4 REFERENCES.....	5-11

APPENDICES

MODFLOW 2.1 PROGRAM LISTING.....	A-1
MODFLOW 2.1 SAMPLE PROGRAM.....	B-1

Chapter 1

INTRODUCTION

This chapter provides a brief introduction to the MODFLOW code, discusses the types of problems it is designed to solve, and gives a brief description of how to use this manual.

1.1 EXECUTIVE SUMMARY

Sudden changes in the temperature of flowing liquids can result in transient buoyancy forces which strongly impact the flow hydrodynamics via flow stratification. These effects have been studied for the case of potential flow of stratified liquids to line sinks, but not for moderator flow in SRS reactors. Standard codes, such as TRAC and COMMIX, do not have the capability to capture the stratification effect, due to strong numerical diffusion which smears away the hot/cold fluid interface. A related problem with standard codes is the inability to track plumes injected into the liquid flow, again due to numerical diffusion. The combined effects of buoyant stratification and plume dispersion have been identified as being important in operation the Supplementary Safety System which injects neutron-poison ink into SRS reactors to provide safe shutdown in the event of safety rod failure. The MODFLOW code discussed here provides transient moderator flow pattern information with stratification effects, and tracks the location of ink plumes in the reactor. The code, written in Fortran, is compiled for Macintosh II computers, and includes subroutines for interactive control and graphical output. Removing the graphics capabilities, the code can also be compiled on other computers. With graphics, in addition to the capability to perform safety related computations, MODFLOW also provides an easy tool for becoming familiar with flow distributions in SRS reactors.

1.2 CHANGES IN VERSION 2.1

The primary change between versions 2.0 and 2.1 center on the development of a sparjet injection model (see section 2.5). Six sparjets are arranged circumferentially around the center of the SRS reactors, and inject jets of high velocity water upward into the moderator space. Momentum transfer from these high velocity jets helps to pump water in the moderator space, maintaining an up and over flow pattern and preventing large-scale instabilities, which resulted in power fluctuation in earlier reactor configurations [4]. In the model employed here, a mixing volume is defined in which full mixing of the injected water and moderator fluid are assumed to occur. This results in an upward acceleration on the moderator fluid, which is quantified and calculated by the MODFLOW code. In addition to the sparjet injection model, Version 2.1 also incorporates improved time step size control.

1.3 THE PHYSICAL PROBLEM

Transient thermal stratification is known to strongly impact reactor hydraulics when cold water is injected into a reactor system. The geometry of particular interest here is illustrated schematically in Fig. 1.1a, which shows cold fluid flowing up into a cylindrical, anisotropic porous medium formed by

a bank of vertical tubes, and then out around the lower circumference of the cylinder. The introduction of cold fluid can then result in stratification. Early studies of stratified flow have considered two-dimensional flow of a stably stratified fluid in a channel toward a line sink, as shown in Fig. 1.1b. Huber [1] obtained an analytic solution for the case of two fluid layers of different densities flowing toward a line sink, as illustrated in Fig. 1.1. Based on inviscid flow equations balancing inertia and gravity forces, he showed that a critical flow rate exists where the lighter fluid ceases to flow and becomes stagnant. Debler [2] performed experiments for the case of a linear density gradient in the vertical direction at $x=-\infty$, confirming the analytic prediction of Yih [3] that stagnation and isolation of the upper lighter fluid occurs for Froude numbers above a critical value. Fluid stagnation has important implications for the effectiveness of systems for injecting neutron poison ink, since stagnation at higher Froude numbers will trap ink and prevent removal from the system.

Fig. 1.1 Stratified flow to a line sink in (b) rectangular coordinate system with flow from $x=-\infty$ studied by Huber [1] and Debler [2], and in cylindrical coordinates (a) studied here.

Under isothermal conditions, the moderator flow pattern in SRS reactors is known to be up and over from full-scale experimental measurements made in 1959 [4]. These measurements have formed a basis for analysis and modeling of the Supplementary Safety System (SSS) for ink poison injection. Recently, questions have been raised about potential thermal buoyancy effects on the moderator flow patterns. After ink injection occurs, the reactor power level drops over a few seconds time. The temperature of the heavy water entering the tank bottom also drops. At a nominal full power of 1100MW, the temperature drops 25°C lower, and the heavy water becomes 1.2% denser. Buoyancy creates a tendency for the cold water to flow under the light, hot water above, creating a relatively stagnant region in the top of the tank.

Because previous tests were isothermal [4], the important role of buoyancy effects was not addressed.

The maximum height to which the cold water can rise in SRS reactor tanks is determined by the balance between hydrostatic forces, frictional pressure drop and inertia. Peterson [5] derived steady-state analytical and transient numerical models which balance buoyancy and radial friction forces, while neglecting fluid inertia and secondary flow induced by sparjet injection and septifoil cold water flow. The ink injection system is known to function properly under full-flow, full-power conditions, from tests performed in 1975 [6]. A primary concern, however, has been system performance under coastdown conditions after a loss of A.C. pumping power, due to the changing flow patterns caused by increased buoyancy effects. Peterson [5] demonstrated that the formation of stagnant regions and the larger ink residence time substantially increase the total inventory of ink in the reactor during coastdown. Because previously only the gross buoyancy-induced recirculation patterns have been modeled, a new code MODFLOW has been developed to provide detailed information on flow patterns, stratification, and ink transport rates.

1.4 ANALYTICAL INVESTIGATION

In 1977, modeling of the SSS system was performed [7], using the GRASS transient analysis system with a single-phase moderator flow model and two different material transport models. The moderator flow was modeled as simple potential flow, with flow potential varying linearly with velocity (Darcy flow), as opposed to variation with the square of velocity (non-Darcian flow). Both liquid inertia and buoyancy effects due to temperature gradients were neglected. Ink injection was modeled using both finite-difference techniques and a "marker particle" method. Finite difference techniques were found to result in excessively high levels of numerical diffusion, giving physically unrealistic results. The theory of these numerical diffusion effects is discussed further by Peterson [5]. The 1977 study also employed a marker particle method, dividing the injected ink into packets injected over each time step, and then tracking the center point of each packet as it was transported with the moderator flow. This Lagrangian method gave better results.

Accurate modeling of the moderator flow requires the simultaneous consideration of momentum convection, inertia, friction, and buoyancy forces. MODFLOW 2.1 provides accurate modeling by solving the complete two-dimensional momentum and energy equations, based on porous media modeling of the fuel assemblies. Currently the code also tracks the location of injected ink plumes, but does not model the effects of plume buoyancy and dispersion. Future work will incorporate more detailed models for plume behavior. MODFLOW models moderator flow patterns and ink dispersion for arbitrary flow histories, including full AC and pump coastdown flows. Specifically, the code includes the following components:

- 1) Treats, in an integral and coupled manner, phenomena pertinent to the quantification of moderator flow pattern and ink transport at various flow rates and power conditions, from full AC flow to pump coastdown flow rates.

- 2) The model is two-dimensional, azimuthally symmetric, with provisions for (Items h and i will be revised in a later version of MODFLOW):
 - a. varying grid spacing,
 - b. radial and axial flow resistance from fuel tubes,
 - c. fluid inertia,
 - d. cold water addition, the code will use Lagrangian techniques discussed below to track the resulting cold water front without excessive numerical diffusion,
 - e. account for buoyancy effects due to the temperature gradient using Lagrangian techniques to minimize numerical diffusion of the vorticity generated at the hot/cold fluid interface,
 - f. momentum addition from the sparjets,
 - g. coastdown caused by loss of AC power,
 - h. septifoil cooling water flow (not in Version 2.1),
 - i. ink injection from the sparjets. Lagrangian methods for tracking the ink plume is employed (Version 2.1 does not consider plume buoyancy and dispersion mechanisms),
 - j. graphical presentation of flow velocity vectors and ink distribution, for Macintosh-based systems.
- 3) The code has been preliminarily benchmarked against existing experimental results for isothermal steady-state flow and test results for ink injection in SRS reactors.

1.5 REFERENCES

1. Huber, D.G., "Irrotational Motion of Two Fluid Strata Towards a Line Sink," *Journal of the Engineering Mechanics Division, Proceedings of the ASCE*, Vol. 86, pp. 71-86, 1960.
2. Debler, W.R., "Stratified Flow into a Line Sink," *Journal of the Engineering Mechanics Division, Proceedings of the ASCE*, Vol. 85, pp. 51-65, 1959.
3. Yih, C.-S., "On the Flow of a Stratified Fluid," *Proceedings 3rd U.S. National Congress of Applied Mechanics*, Providence, Rhode Island, pp. 857-861, June 11-14, 1958.
4. DP-402, Circulation of Heavy Water Moderator in a Reactor, H.E. Wingo, November 1959.
5. SRL-SAG-90-0402, Buoyancy Effects on Ink Distributions Under A.C. and Coast-Down Conditions, P.F. Peterson, July 10, 1990.

6. DPST-75-341, SSS Test Results, C.E. Ahlfeld, May 8, 1975.
7. DPST-77-467, Grass Calculation of the SSS Test to Verify the Material Transport Model, D.E. Hostetler, September 29, 1977.

Chapter 2

PHYSICAL AND MATHEMATICAL MODELS

The program MODFLOW calculates the moderator flow distribution in SRP reactors, including the effects of inertia and stratification from buoyancy forces. This chapter presents the physical models used to describe the system, and from those models develops the finite-difference and Lagrangian formulations used in MODFLOW.

2.1 OVERVIEW

At length scales smaller than the fuel assemblies of SRP reactors, flow patterns are primarily turbulent and are quite complex. However, because the flow resistance due to the fuel assemblies can be calculated using friction factors and loss coefficients, it is possible to describe the bulk, average behavior of the flow. This description in turn allows quantification of the effects of buoyancy and stratification, and ultimately the calculation of the motion of plumes of neutron poison injected into the reactor.

As the first step in modeling moderator flow, this chapter applies the formal techniques of volume averaging to obtain averaged forms for the momentum conservation equations. Nondimensionalization and scaling of these equations identifies the primary parameters which govern the transient flow evolution in SRP reactors: the Froude number and friction factors. The momentum equations are then modified to a two-dimensional vorticity-Poisson equation formulation, to permit numerical solution. Finite-difference forms of the equations are then presented.

In upwind and other finite-difference numerical solutions, particularly for transient problems, numerical diffusion can create unrealistic answers. This effect was found to be strong for the problem of interest here, where a step decrease in the moderator inlet temperature results in transient stratification. Benchtop experiments have shown that the density interface remains sharp and distinct, but finite-difference solutions cause the interface to diffuse and become thick. Here a Lagrangian technique is applied to track the density interface, eliminating the effect of numerical diffusion. This technique requires a sharp interface, while the actual interface is distributed due to the finite time period over which the temperature changes. The sharp interface gives the earliest time for ink leaving the tank, and is thus conservative. The code also has the capability to treat the temperature distribution in a finite-difference manner, with a varying inlet temperature. With finite-difference techniques, the numerical diffusion results in much larger ink residence times.

Numerical diffusion also strongly impacts finite-difference solutions for plume dispersion. Particularly on coarse grids, plumes will disperse much more rapidly in a numerical solution than occurs physically. Here this problem is eliminated by tracking the injected ink "packets" in a Lagrangian manner. Currently buoyancy effects on the plume are not considered, but a later version will include a model for these effects.

2.2 NOMENCLATURE

(Fortran variables used in MODFLOW are given in brackets [])

- a - finite difference influence coefficient [aep, asp, ...]
- A_r - ratio of minimum radial area over total area, Eq. (11)
- b - finite difference coefficient [bz, bp]
- c - specific heat, J/kg°C (btu/lb°F)
- C_i - constant for adjusting inlet velocity at node i [cvel(i)]
- D_t - fuel outside diameter, m (in) [Dfuel]
- D_h - hydraulic diameter, Eq. (9), m (in) [Dhydr]
- f_z - vertical friction factor [xfv]
- F - force on porous medium, Eqs. (8) and (10)
- Fr - Froude number, Eq. (22)
- g - gravitational acceleration, m/s² (ft/s²) [zgrav]
- H_T - tank height, m (ft) [Htank]
- H_n - nozzle height, m (ft) [Hnoz]
- k_{eff} - effective thermal conductivity, W/m°C (btu/hrft°F)
- k_r - radial form loss coefficient [xfr]
- K - nondimensional loss coefficients, Eqs. (2-23) and (2-24)
- m - mass, kg (lb)
- $\dot{m}$ - mass flow rate, kg/s (lb/s)
- M - number of vertical nodes [mhigh]
- N - number of radial nodes [nwide]
- N_t - number of tube bank rows [tubes]
- p - pressure, kPa (psi)
- Pr - Prandtl number, Eq. (2-25)
- q - source term, W/m³ (btu/ft³)
- Q - total flow rate, m³/s (ft³/s)
- r - radial coordinate, m (ft) [rad(i)]
- R_T - tank radius, m (ft) [Rtank]
- Re - Reynolds number, Eq. (2-21)
- S - Stress tensor
- S_c - length along density interface, m (ft)
- S_t - fuel pitch, m (in) [sfuel]
- t - time (sec) [time]
- T - temperature (°C)
- u - volume average radial velocity, m/s (ft/s) [u(i, j)]
- v - volume average vertical velocity, m/s (ft/s) [v(i, j)]
- v - velocity vector, m/s (ft/s)
- V - volume, m³ (ft³)
- V_o - inlet velocity at tank bottom, m/s (ft/s) [vbot]
- W - vorticity/radius, ω/r (s⁻¹) [zeta]
- z - vertical coordinate, m (ft) [z]
- β - coefficient of thermal expansion [B]
- χ - heat flux vector W/m² (btu/ft²sec)
- μ - dynamic viscosity, kg/ms (lb/ft s) [visc]
- ω - vorticity, m/s (ft/s)
- ϕ - void fraction [void]
- Ψ - conserved quantity
- ψ - stream function, m s (ft s) [psi]

ρ - density, kg/m^3 (lb/ft^3) [ρ]

Subscripts

c - cold, density interface
 h - hot
 i - radial node number
 i n - into control volume
 j - vertical node number or jet
 k - density interface node number
 e - east node (i-1)
 f - fluid
 n - north node (j+1)
 o - inlet value
 p - center node, Poisson equation
 s - south node (j-1)
 t - tube
 T - tank
 v - vorticity equation
 w - west node (i+1)
 x - x-direction
 y - y-direction

Superscripts

* - nondimensional quantity
 n - previous time step

2.3 VOLUME AVERAGING

In porous media like compact heat exchangers, regenerators, and fibrous insulation, many of the mechanisms which govern the flow occur on scales much smaller than the tube pitch or pore size. For large tube banks it is computationally difficult to resolve flow details on these small scales. These difficulties can be addressed using volume averaging and semi-empirical closure relationships, such as friction and form loss coefficients. Traditional analysis of flow and heat transport in porous media uses Darcian or slug-flow models and neglects non-Darcian effects due to inertial convective forces. A more fundamental basis for studying such flows can come from volume-averaging techniques (Vafai and Tien [1], Slattery [2]). For porous media it becomes useful to define a *local volume average* of a quantity Ψ as

$$\langle \Psi \rangle = \frac{1}{V} \int_{V_f} \Psi \, dV \quad (2-1)$$

where V is a volume around the point of interest, sufficiently large relative to the tube spacing or pore size to permit averaging, and V_f is the fluid volume inside the volume V . With the 'volume average of a divergence' theorem (Whitaker [3], Slattery, [4]), the local volume averages of the mass, momentum, and energy conservation equations for incompressible, transient flow through a porous medium can be established as

$$\nabla \cdot \langle \mathbf{v} \rangle = 0 \quad (2-2)$$

$$\rho_f \langle (\mathbf{v} \cdot \nabla) \mathbf{v} \rangle = -\nabla \langle p \rangle + \mu_f \nabla^2 \langle \mathbf{v} \rangle + \mathbf{F} + \rho_f \mathbf{g} \quad (2-3)$$

$$\rho_f c_f \langle \mathbf{v} \rangle \cdot \nabla \langle T \rangle = -\nabla \cdot \chi + q \quad (2-4)$$

where $\mathbf{v}$ is the flow velocity vector, ρ_f the fluid density, p the fluid pressure, μ_f the fluid viscosity, c_f the fluid specific heat, T the fluid temperature, and q a source term. The effective heat flux vector, χ , is a complex function of the fluid and solid matrix thermal conductivity, solid matrix geometry, the local velocity field, and the local temperature field.

Because the details of the velocity field are not known, it is assumed here that volume average of the convective momentum terms can be approximated with the convection of the volume-average momentum, that is, the left hand side of Eq. (2-3) can be written

$$\rho_f \langle (\mathbf{v} \cdot \nabla) \mathbf{v} \rangle = \rho_f \langle \mathbf{v} \rangle \cdot \nabla \frac{\langle \mathbf{v} \rangle}{\phi} \quad (2-5)$$

introducing the void fraction ϕ . The void fraction corrects the volume-average velocity $\langle \mathbf{v} \rangle$ to the average local velocity in the void space, due to the second volume averaging required on the right hand side of Eq. (2-5),

$$\phi = \frac{V_f}{V} = 1 - \frac{\pi D_t^2}{4 S_t^2 \sin 60} \quad (\text{SRP triangular array})$$

$$= 1 - \frac{\pi D_t^2}{4 S_{tx} S_{ty}} \quad (\text{Benchtop rectangular array}) \quad (2-6)$$

for tubes of diameter D_t with pitch S_t . The body force term F is given by

$$F = \int_{A_{st}} S \cdot dA \quad (2-7)$$

where S is the fluid stress tensor and A_{st} is the surface area inside the volume. For flow in a tube bank the flow resistance is anisotropic. For turbulent flow parallel to the tubes, the vertical body force component F_z can be characterized by a friction factor f_z

$$F_z = \frac{\rho f_z}{\phi^2 D_h} \frac{v|v|}{2} \quad (2-8)$$

where the void fraction ϕ corrects vertical component v of the volume average velocity $\langle v \rangle$ to the average vertical local velocity. The hydraulic diameter is given

$$D_h = 4 \frac{S_t^2 \sin 60 - \frac{1}{4} \pi D_t^2}{\pi D_t} \quad (2-9)$$

The friction factor f_z is given by [7]

$$f_z = 0.184 Re_x^{-0.20} \quad Re_z > 30,000$$

$$f_z = 0.316 Re_x^{-0.25} \quad Re_z < 30,000$$

where the vertical Reynolds number is given by $Re_z = \rho v_{max} D_h / \mu$, with $v_{max} = v / \phi$.

For turbulent flow perpendicular to tube banks, the radial body force component can be characterized by

$$F_r = \frac{\rho f_r N_t A_r^2}{R_T} \frac{u|u|}{2} \quad (2-10)$$

where

$$A_r = S_t / (S_t - D_t)$$

is the ratio of the total flow area to the minimum radial flow area, u the radial component of the volume average velocity $\langle v \rangle$, N_t the number of tube banks

between the tank center and wall, and R_T the tank radius. The graphical radial form loss coefficient k_r from Zukauskas [5] was fit by the equations

$$\begin{aligned}
 k_r &= 0.18 & Re_r &> 200,000 \\
 k_r &= 4.233 Re_r^{-0.268} & 200,000 &> Re_r > 6,000 \\
 k_r &= \exp(4.028 - 1.118 \ln(Re_r) + 0.0635 (\ln(Re_r))^2) & 6,000 &> Re_r \quad (2-11)
 \end{aligned}$$

where the radial Reynolds number is given by $Re_r = \rho u_{max} D_t / \mu$, with $u_{max} = u S_t / (S_t - D_t)$, for triangular arrays with $S_t/D = 1.7$. The code results are not particularly sensitive to the friction factor value, and an option is provided to use constant friction factors to speed calculation, if desired.

2.4 MOMENTUM EQUATION NONDIMENSIONALIZATION

To derive scaling parameters to characterize the moderator flow, the volume-averaged continuity, Navier-Stokes, and energy equations, Eqs. (2-2) to (2-4), are nondimensionalized using the with the following characteristic quantities,

$$\begin{aligned} u^* &= u/V_0 & v^* &= v/V_0 & p^* &= (p-p_0)/\rho_f V_0^2 \\ z^* &= z/R_T & r^* &= r/R_T & t^* &= tV_0/R_T \\ T^* &= \frac{(T-T_c)}{(T_h-T_c)} & q^* &= \frac{qR_T}{\rho_f c_f (T_h-T_c) V_0} \end{aligned} \quad (2-12)$$

where starred quantities are nondimensional, r and z are the radial and axial coordinates, u and v the radial and vertical components of the average velocity $\langle v \rangle$, t time, R_T the tank radius, $V_0 = Q/\pi R_T^2$ the average upward velocity of water at the tank bottom, p_0 is the inlet pressure, and T_h and T_c the initial hot moderator and cold plenum temperatures. Incompressible mass continuity can be written from Eq. (2-2) in cylindrical coordinates,

$$\frac{1}{r} \frac{\partial(ru)}{\partial r} + \frac{\partial v}{\partial z} = 0 \quad (2-13)$$

The Navier-Stokes equations for azimuthally symmetric flow, from Eqs. (2-3), (2-5), (2-8), and (2-10), become

$$\frac{\rho_f}{\phi} \left(\frac{\partial u}{\partial t} + u \frac{\partial u}{\partial r} + v \frac{\partial u}{\partial z} \right) = - \frac{\partial p}{\partial r} + \mu \left[\frac{\partial}{\partial r} \left(\frac{1}{r} \frac{\partial(ru)}{\partial r} \right) + \frac{\partial^2 u}{\partial z^2} \right] - \frac{\rho_f k_r N_t A_r^2}{R_T} \frac{u|u|}{2} \quad (2-14)$$

$$\begin{aligned} \frac{\rho_f}{\phi} \left(\frac{\partial v}{\partial t} + u \frac{\partial v}{\partial r} + v \frac{\partial v}{\partial z} \right) &= - \frac{\partial p}{\partial z} + \rho_f (1 + \beta(T-T_c)) g_t \\ &+ \mu \left[\frac{\partial}{\partial r} \left(\frac{1}{r} \frac{\partial(rv)}{\partial r} \right) + \frac{\partial^2 v}{\partial z^2} \right] - \frac{\rho_f f_z}{\phi^2 D_h} \frac{v|v|}{2} \end{aligned} \quad (2-15)$$

where β is the coefficient of thermal expansion. In the z -direction momentum equation the Boussinesq approximation for buoyancy is introduced. The total acceleration, $g_t = g - g_j$, includes the contributions of gravity and the acceleration induced by the sparjet injection (section 2.5). Gravity g_t acts in the negative z direction.

The energy equation, from Eq. (2-4), becomes

$$\rho_f c_f \left(\frac{\partial T}{\partial t} + u \frac{\partial T}{\partial r} + v \frac{\partial T}{\partial z} \right) = k_{eff} \left[\frac{\partial}{\partial r} \left(\frac{1}{r} \frac{\partial(rT)}{\partial r} \right) + \frac{\partial^2 T}{\partial z^2} \right] + q \quad (2-16)$$

where k_{eff} is an effective thermal conductivity, including the porous matrix. The inertia terms are divided by the void fraction to correct the area-average

velocity to the local average velocity of the moderator. Now we proceed to substitute in the nondimensional terms above, to obtain

$$\frac{1}{r^*} \frac{\partial(r^* v^*)}{\partial r^*} + \frac{\partial u^*}{\partial z^*} = 0 \quad (2-17)$$

$$\frac{\partial u^*}{\partial t^*} + u^* \frac{\partial u^*}{\partial r^*} + v^* \frac{\partial u^*}{\partial z^*} = -\phi \frac{\partial p^*}{\partial r^*} + \frac{1}{Re_T} \left[\frac{\partial}{\partial r^*} \left(\frac{1}{r^*} \frac{\partial(r^* u^*)}{\partial r^*} \right) + \frac{\partial^2 u^*}{\partial z^{*2}} \right] - K_r \frac{u^* |u^*|}{2} \quad (2-18)$$

$$\begin{aligned} \frac{\partial v^*}{\partial t^*} + u^* \frac{\partial v^*}{\partial r^*} + v^* \frac{\partial v^*}{\partial z^*} = & -\phi \frac{\partial p^*}{\partial z^*} + Fr T^* \\ & + \frac{1}{Re_T} \left[\frac{\partial}{\partial r^*} \left(\frac{1}{r^*} \frac{\partial(r^* v^*)}{\partial r^*} \right) + \frac{\partial^2 v^*}{\partial z^{*2}} \right] - K_z \frac{v^* |v^*|}{2} \end{aligned} \quad (2-19)$$

$$\frac{\partial T^*}{\partial t^*} + u^* \frac{\partial T^*}{\partial r^*} + v^* \frac{\partial T^*}{\partial z^*} = \frac{1}{Pr_{eff} Re_T} \left[\frac{\partial}{\partial r^*} \left(\frac{1}{r^*} \frac{\partial(r^* T^*)}{\partial r^*} \right) + \frac{\partial^2 T^*}{\partial z^{*2}} \right] + q^* \quad (2-20)$$

We have formed three groups of nondimensional parameters, which have the names:

$$\text{Tank Reynolds Number:} \quad Re_T = \frac{\rho_f R_T V_o}{\phi \mu} \quad (2-21)$$

$$\text{Froude Number:} \quad Fr = \frac{\phi R_T \beta (T_h - T_c) g}{V_o^2} \quad (2-22)$$

$$\text{Friction Factors:} \quad K_z = f_z R / \phi D_h \quad (2-23)$$

$$K_r = k_r N_t \phi A_r^2 \quad (2-24)$$

$$\text{Prandtl Number:} \quad Pr_{eff} = \frac{c_f \phi \mu}{k_{eff}} \quad (2-25)$$

In SRP experiments with 3.5" diameter tubes [6] unsteady flow with large-scale turbulence was observed, and sparger jets were required to produce an up and over flow pattern. For the case of 4.1" diameter tubes on the same triangular pitch, steady up-and-over flow was observed. This transition can be explained from the balance of inertia and radial friction, as given by the nondimensional radial loss coefficient K_r (just as the transition from laminar to turbulent flow is given by the ratio between inertia and viscosity, the Reynolds number). Because the form factor k_r is only a weak function of Reynolds number, taking values ranging from 0.15 to 0.4, the primary factor determining the ratio between friction and inertia forces is the nondimensional geometric quantity ϕA_r^2 . The radial friction factor is plotted in Fig. 2.1 as a function of the fuel diameter to pitch ratio. As can be seen, as the fuel diameter D_t increases, the relative effect of friction increases strongly, reducing the relative importance of inertia and stabilizing the flow.

Fig. 2.1 - Nondimensional radial loss coefficient K_r (balance between friction and inertia) as a function of fuel diameter to pitch ratio, with transition point from unsteady to steady flow observed in SRP tests [6].

These nondimensional governing equations can be simplified by noting that the Reynolds number based on the tank diameter is very large. This means that the diffusion terms are negligible and can be eliminated from the momentum equations, Eqs. (2-18,2-19), and energy equation, Eq. (2-20), giving

$$\frac{\partial u^*}{\partial t^*} + u^* \frac{\partial u^*}{\partial r^*} + v^* \frac{\partial u^*}{\partial z^*} = -\phi \frac{\partial p^*}{\partial r^*} - K_r \frac{u^* |u^*|}{2} \quad (2-26)$$

$$\frac{\partial v^*}{\partial t^*} + u^* \frac{\partial v^*}{\partial r^*} + v^* \frac{\partial v^*}{\partial z^*} = -\phi \frac{\partial p^*}{\partial z^*} + \phi Fr T^* - K_z \frac{v^* |v^*|}{2} \quad (2-27)$$

$$\frac{\partial T^*}{\partial t^*} + u^* \frac{\partial T^*}{\partial r^*} + v^* \frac{\partial T^*}{\partial z^*} = q^* \quad (2-28)$$

This implies that the key parameters to match to obtain similitude are the Froude number and the two friction factors.

2.5 SPARJET MODELLING

The SRS reactors are equipped with six sparjets, which inject high-velocity water near the center of the tanks to help induce up-and-over flow. A nominal flow rate of 5800 gpm is supplied to the six sparjets, all located within the 4.7-ft radius of the moderator upflow region. Each of these has 12 rows of 3 symmetrically arranged 0.265 inch diameter holes, with rows located at 6-inch intervals lengthwise. The first row is at 24.4 inches from the reactor tank bottom. In MODFLOW, the pumping effect of the sparjets is simulated using a mixing volume model.

Fig. 2.2 - Sparjet mixing volume schematic.

The injected sparjet water is assumed to come to mechanical equilibrium (equal velocity) with the moderator fluid within a mixing volume V , illustrated in Fig. 2.2. Because the jet nozzles are placed symmetrically around the sparjets and the radial momentum contributions cancel, the model considers only the vertical momentum balance. The mass of fluid flowing out of the mixing volume, $\dot{m}_{out}$, is accelerated from the inlet velocity, v_{in} , to a higher vertical velocity v_{out} due to mixing with the sparjet fluid of velocity $v_j \cos \theta$. For uniform velocity of the moderator water entering and leaving the volume, a momentum balance can be written in the vertical direction,

$$(\dot{m}_j + \dot{m}_{in}) v_{out}/\phi = \dot{m}_{in} v_{in}/\phi + \dot{m}_j v_j \cos \theta \quad (2-29)$$

where the area average velocities v_{out} and v_{in} are adjusted to the actual velocities in the channels using the void fraction ϕ . The mass flow rate through the bottom face of the mixing volume is $\dot{m}_{in} = \rho v_{in} A_{in}$, where A_{in} is the area of the bottom of the control volume. Then Eq. (2-29) can be rewritten,

$$v_{in} (v_{out} - v_{in}) = \frac{\dot{m}_j}{\rho A_{in}} (\phi v_j \cos \theta - v_{out}) \quad (2-30)$$

where the assumption that $\rho_{moderator} = \rho_{sparjet} = \rho$ is used. Noting that the mixing volume is $V = A_{in} \Delta z$,

$$v_{in} \left(\frac{v_{out} - v_{in}}{\Delta z} \right) = \frac{\dot{m}_j}{\rho V} (\phi v_j \cos \theta - v_{out}) = \phi g_j \quad (2-31)$$

Examining the vertical momentum equation, Eq. (2-15), the left hand side of Eq. (2-31) is seen to have similar form to the convective terms. Thus the sparjet injection can be viewed as generating a vertical acceleration g_j over the mixing volume, where g_j is given by the right hand side of Eq. (2-31). This sparjet acceleration component can be added to that of gravity. Under coastdown conditions, the sparjet flow rate decreases at the same rate as tank inlet flow. This assumption is reasonable because the sparjet and fuel assembly flow rates are governed primarily by the loss coefficients, and thus remain proportional as the driving pressure difference decreases.

2.6 NUMERICAL FORMULATION

Here a mass conservation satisfying finite-difference form of the Poisson equation is derived in cylindrical coordinates. The stream function ψ gives velocities

$$u = \frac{1}{r} \frac{\partial \psi}{\partial z} \quad v = -\frac{1}{r} \frac{\partial \psi}{\partial r} \quad (2-32)$$

which automatically satisfy mass conservation,

$$\frac{1}{r} \frac{\partial(ru)}{\partial r} + \frac{\partial v}{\partial z} = 0 \quad (2-33)$$

The stream function can then be coupled with the definition of vorticity to obtain Poisson's equation,

$$\begin{aligned} \omega &= \frac{\delta u}{\delta z} - \frac{\delta v}{\delta r} \\ &= \frac{1}{r} \frac{\partial^2 \psi}{\partial z^2} + \frac{\partial}{\partial r} \left(\frac{1}{r} \frac{\partial \psi}{\partial r} \right) \end{aligned} \quad (2-34)$$

The boundary conditions on the Poisson equation come from the normal velocities. These boundary conditions are

$$v=0 \quad \frac{\partial \psi}{\partial r} = 0 \quad \text{at } 0 < r < R_T, z=H_T \quad (2-35)$$

$$v=V_o \quad \frac{\partial \psi}{\partial r} = -rV_o \quad \text{at } 0 < r < R_T, z=0 \quad (2-36)$$

$$u=V_o \frac{\pi R_T^2}{2\pi R_T H_n} \quad \frac{\partial \psi}{\partial z} = V_o \frac{R_T^2}{2H_n} \quad \text{at } r=R_T, 0 < z < H_n \quad (2-37)$$

$$u=0 \quad \frac{\partial \psi}{\partial z} = 0 \quad \text{at } r=R_T, H_n < z < H_T \quad (2-38)$$

$$u=0 \quad \frac{\partial \psi}{\partial z} = 0 \quad \text{at } r=0, 0 < z < H_T \quad (2-39)$$

where H_n is the outlet nozzle height and H_T the tank height.

Fig. 2.3 - Finite-difference grid for MODFLOW.

The numerical scheme employs a uniform rectangular grid with staggered velocity nodes as shown in Fig. 2.3a. The velocities can be written in finite-difference form as

$$u_{i,j} = \frac{1}{r_i \Delta z} (\psi_{i,j+1} - \psi_{i,j}) \quad v_{i,j} = \frac{2}{(r_{i+1}^2 - r_i^2)} (\psi_{i,j} - \psi_{i+1,j}) \quad (2-40)$$

so that any distribution $\psi_{i,j}$ will identically satisfy mass conservation, except for the mass added by the sparjets, which is a small fraction (<3%) of the total flow,

$$2\pi\Delta z(r_{i+1}u_{i+1,j} - r_i u_{i,j}) + \pi(r_{i+1}^2 - r_i^2)(v_{i,j+1} - v_{i,j}) = 0 \quad (2-41)$$

In cylindrical coordinates the mass conserving finite-difference form of Poisson's equation is then

$$\omega_{i,j} = \frac{1}{\Delta z} \left[\frac{(\psi_{i,j+1} - \psi_{i,j})}{r_i \Delta z} - \frac{(\psi_{i,j} - \psi_{i,j-1})}{r_i \Delta z} \right] + \frac{2}{\Delta r} \left[\frac{(\psi_{i+1,j} - \psi_{i,j})}{(r_{i+1}^2 - r_i^2)} - \frac{(\psi_{i,j} - \psi_{i-1,j})}{(r_i^2 - r_{i-1}^2)} \right] \quad (2-42)$$

or simplifying,

$$\omega_{i,j} \Delta r \Delta z = \frac{\Delta r}{r_i \Delta z} (\psi_{i,j+1} - 2\psi_{i,j} + \psi_{i,j-1}) + 2\Delta z \left[\frac{(\psi_{i+1,j} - \psi_{i,j})}{(r_{i+1}^2 - r_i^2)} - \frac{(\psi_{i,j} - \psi_{i-1,j})}{(r_i^2 - r_{i-1}^2)} \right] \quad (2-43)$$

The Poisson equation can then be written implicitly in terms of influence coefficients as

$$a_{pp} \psi_{i,j}^{n+1} = a_{pe} \psi_{i+1,j}^{n+1} + a_{pw} \psi_{i-1,j}^{n+1} + a_{pn} \psi_{i,j+1}^{n+1} + a_{ps} \psi_{i,j-1}^{n+1} + b_p \quad (2-44)$$

where

$$a_{pe} = \frac{2\Delta z}{(r_{i+1}^2 - r_i^2)} \quad a_{pw} = \frac{2\Delta z}{(r_i^2 - r_{i-1}^2)} \quad (2-45)$$

$$a_{pn} = a_{ps} = \frac{\Delta r}{r_i \Delta z} \quad a_{pp} = a_{pe} + a_{pw} + a_{pn} + a_{ps} \quad (2-46)$$

$$b_p = \omega_{i,j}^{n+1} \Delta r \Delta z \quad (2-47)$$

In finite-difference form, the boundary conditions become

$$\psi_{i,N}=0 \quad \text{for } i = 1 \text{ to } M \quad (2-48)$$

$$\psi_{i,1} = \psi_{i-1,1} - \frac{C_i V_0}{2} (r_{i+1}^2 - r_i^2) \quad \text{for } i = 2 \text{ to } M \quad (2-49)$$

$$\psi_{M,j}=0 \quad \text{for } j = 2 \text{ to } N \quad (2-50)$$

$$\psi_{1,j}=0 \quad \text{for } j = 1 \text{ to } N \quad (2-51)$$

where M is the number of radial nodes and N the number of vertical nodes, and it is assumed that $\Delta z \geq H_n$, such that Eq. (2-37) is represented by the change in ψ from node M,1 to node M,2. The value of ψ choosen at the solid boundaries is arbitrary, and is given as zero here. The factor C_i adjusts the nominal inlet velocity V_0 to the actual value at the node i. MODFLOW normalizes C_i such that $\sum C_i (r_{i+1}^2 - r_i^2) = R_T^2$.

For any given distribution of vorticity, $\omega_{i,j}$, it is then possible to solve the set of equations (2-44) to (2-51) to obtain the stream function, and in turn the velocity distribution through equation (2-40).

Expressions for the vorticity can be derived by considering the axial and radial momentum conservation equations, (2-14) and (2-15). When cross-differentiated and subtracted, dropping the diffusion terms due to the assumption of a high tank Reynolds number Re_T which makes these terms negligible, and the definition for vorticity, equation (2-34), is inserted, the result is

$$\begin{aligned} \frac{\partial \omega}{\partial t} + u \frac{\partial}{\partial r} \left(\frac{\omega}{r} \right) + v \frac{\partial \omega}{\partial z} \\ = \frac{\partial}{\partial r} \left(\frac{f_z}{\phi D_h} \frac{v|v|}{2} \right) - \frac{\partial}{\partial z} \left(\frac{k_r N_t \phi A_r^2}{R_T} \frac{u|u|}{2} \right) + \frac{\partial g_j}{\partial r} - \phi g \frac{\partial}{\partial r} (\beta T) \end{aligned} \quad (2-52)$$

where g_j is given by Eq. (2-31) and it is assumed that $\beta(T-T_o) \ll 1$. Vorticity is induced where the acceleration induced by the sparjets, g_j , changes with radius r .

The boundary conditions for the vorticity equation are simple, because the governing equation form (Euler equation) has no diffusive terms and thus only the inlet boundary needs to be specified,

$$\omega = 0 \quad \text{at } z=0 \quad (2-53)$$

Flow exits the end fittings of the fuel elements in a radial symmetric pattern, and thus radial momentum addition is cancelled, creating a upward and outward flow pattern. From the porous media perspective, the inlet flow can be viewed as a distributed source across the tank bottom. The flow entering the bottom of the tank is irrotational, and thus the only vorticity in the flow is generated by the tube bank frictional resistance and buoyancy due to temperature gradients.

The vorticity equation can be put in finite-difference form with the uniform rectangular grid shown in Fig. 2.2b using implicit upwind differencing, defining

$$\omega = W + Y \quad (2-54)$$

Here the vorticity distribution generated by the distributed friction resistance, W , is calculated using a standard upwind finite-difference approximation. The component of vorticity generation by buoyancy, Y , is calculated using either Lagrangian or finite-difference methods, and the results of the two techniques compared. Lagrangian treatment of buoyancy-generated vorticity at the density interface decreases numerical diffusion effects. The upwind explicit finite-difference formulation of Eq. (2-52) employed for vorticity transport has the form

$$a_{vp}^{n+1} W_{i,j}^{n+1} = a_{ve} W_{i+1,j}^n + a_{vw} W_{i-1,j}^n + a_{vn} W_{i,j+1}^n + a_{vs} W_{i,j-1}^n + a_{vp}^n W_{i,j}^n + b_v \quad (2-55)$$

where the influence coefficients are given by

$$\begin{aligned}
 a_{ve} &= \max \left(0, -\frac{r_{i+1/2} u_{i+1/2,j}^n}{\Delta r r_{i+1}} \right) & a_{vw} &= \max \left(0, \frac{r_{i-1/2} u_{i-1/2,j}^n}{\Delta r r_{i-1}} \right) \\
 a_{vn} &= \max \left(0, -\frac{v_{i,j+1/2}^n}{\Delta z} \right) & a_{vs} &= \max \left(0, \frac{v_{i,j-1/2}^n}{\Delta z} \right)
 \end{aligned} \tag{2-56}$$

$$a_{vp}^{n+1} = \frac{1}{\Delta t} \quad a_{vp}^n = \frac{1}{\Delta t} - \frac{r_{i+1}}{r_i} a_{ve} - \frac{r_{i-1}}{r_i} a_{vw} - a_{vn} - a_{vs}$$

$$\begin{aligned}
 b_v &= \frac{1}{\phi D_h \Delta r} \left(f_{zi,j}^n \frac{v_{i,j}^n |v_{i,j}^n|}{2} - f_{zi-1,j}^n \frac{v_{i-1,j}^n |v_{i-1,j}^n|}{2} \right) \\
 &\quad - \frac{N_t \phi A_r^2}{R_T \Delta z} \left(k_{ri,j}^n \frac{u_{i,j}^n |u_{i,j}^n|}{2} - k_{ri,j-1}^n \frac{u_{i,j-1}^n |u_{i,j-1}^n|}{2} \right) \\
 &\quad + G_{i,j} \\
 &\quad - \frac{\phi g \beta}{2 \Delta r} (T_{i+1,j}^n - T_{i-1,j}^n)
 \end{aligned}$$

where $G_{i,j}$ is a sparjet vorticity source term, described below. When the vorticity generated by buoyancy at the density interface is tracked separately in a Lagrangian manner (discussed in section 2.7), the last term of the expression for b_v is not required. The convective velocities are interpolated,

$$u_{i+1/2,j} = 0.25 (u_{i,j} + u_{i,j-1} + u_{i+1,j} + u_{i+1,j-1}) \tag{2-57}$$

$$v_{i,j+1/2} = 0.25 (v_{i,j} + v_{i-1,j} + v_{i,j+1} + v_{i-1,j+1}) \tag{2-58}$$

and the boundary condition is

$$W_{i,1} = 0 \quad \text{for } i = 1 \text{ to } M \tag{2-59}$$

The sparjet mixing volume is assumed to cover an integral number of nodes, as shown in Fig. 2.4, where the jet source is approximately centered radially between nodes r_{i1}, r_{i2} and is located just above the bottom node at z_{j1} . The size of the mixing volume is then varied by changing the number of radial and vertical nodes included, $N_j = i_2 - i_1$ and $M_j = j_2 - j_1$. The sparjet mixing volume is then $\pi(r_{i2}^2 - r_{i1}^2)M_j \Delta z$ where M_j is the number of vertical grid spaces in the sparjet volume. The value selected for M_j is not critical, because the sparjet mixing volumes overlap vertically, and thus the total effect depends only weakly on M_j . More important is the radial width of the mixing volume, where comparison of results with 1959 tests show that a width of 4 feet matches

experimental data well, as shown in Section 5. The vertical sparjet acceleration g_j is assumed to have the distribution shown in Fig. 2.4, being distributed uniformly over the mixing volume. The vorticity source term $G_{i,j}$, which is proportional to dg_j/dr , then takes positive values at the nodes on the left of the control volume and negative values at the nodes on the right.

Fig. 2.4 - Grid system for sparjet acceleration showing distributions of g_j and dg_j/dr .

The sparjet vorticity source term can be written as the sum over the sparjet nozzles k ,

$$G_{i,j} = \sum_k \frac{\dot{m}_j}{\rho} \frac{\phi v_j \cos \theta}{\pi (r_{i2}^2 - r_{i1}^2) M_j \Delta z \Delta r} \quad \text{for } i = i1 \text{ and } j1 \leq j \leq j2 \quad (2-60)$$

$$G_{i,j} = - \sum_k \frac{\dot{m}_j}{\rho} \frac{\phi v_j \cos \theta}{\pi (r_{i2}^2 - r_{i1}^2) M_j \Delta z \Delta r} \quad \text{for } i = i2 \text{ and } j1 \leq j \leq j2 \quad (2-61)$$

where $v_j = \dot{m}_j / \rho A_j$ is the absolute velocity of the water exiting the sparjet nozzle, A_j the area of the sparjet nozzle exit, θ the angle from vertical of the sparjet injection. The jet velocity v_j is much larger than the average upward velocity

of moderator fluid in the sparger mixing volume, and thus the moderator velocity is neglected.

2.7 PARTICLE TRACKING

Both fluid particles and the hot/cold water interface are tracked in a Lagrangian manner with a simple subroutine. The new location of a particle is found from the old location, based on an interpolated value for the radial and vertical velocities, u_{ave} and v_{ave} ,

$$r_p^{n+1} = r_p^n + \frac{u_{ave} \Delta t}{\phi} \quad (2-62)$$

$$z_p^{n+1} = z_p^n + \frac{v_{ave} \Delta t}{\phi} \quad (2-63)$$

where the void fraction ϕ is introduced to correct the volume-average velocity to the local average velocity between the tubes. The expression for the local average velocity results from considering the time required to displace the liquid in a volume V with area A and length L . The quantity of liquid to be displaced is then $V_f = \phi V = \phi AL$. The time required to displace the liquid depends on the flow rate, $Q = vA$,

$$t = \frac{\phi AL}{vA} \quad (2-64)$$

The velocity with which the liquid front moves through the volume, and thus the velocity a particle would have, is then given by

$$v_{eff} = \frac{L}{t} = \frac{v}{\phi} \quad (2-65)$$

This agrees with the expectation that the actual velocity in the space between the tubes will be greater than the volume average velocity.

The radial average velocity, u_{ave} , is found by linear interpolation as shown in Fig. 2.5a, using

$$\begin{aligned} i &= \text{int} \left(\frac{r_p^n}{\Delta r} + 1 \right) & j &= \text{int} \left(\frac{z_p^n}{\Delta z} + 0.5 \right) \\ r_i &= (i-1) \Delta r & z_j &= (j-0.5) \Delta z \\ c_{rr} &= \frac{r_p^n}{\Delta r} - (i-1) & c_{zz} &= \frac{z_p^n}{\Delta z} - (j-0.5) \\ u_{ave} &= \left(u_{i,j}(1-c_{rr}) + u_{i+1,j}c_{rr} \right) (1-c_{zz}) + \left(u_{i,j+1}(1-c_{rr}) + u_{i+1,j+1}c_{rr} \right) c_{zz} \end{aligned} \quad (2-66)$$

The vertical average velocity, v_{ave} , is found by linear interpolation as shown in Fig. 2.5b, using

$$i = \text{int} \left(\frac{r_p^n}{\Delta r} + 0.5 \right)$$

$$j = \text{int} \left(\frac{z_p^n}{\Delta z} + 1 \right)$$

$$r_i = (i-0.5) \Delta r$$

$$z_j = (j-1) \Delta z$$

$$c_{rz} = \frac{r_p^n}{\Delta r} - (i-0.5)$$

$$c_{zz} = \frac{z_p^n}{\Delta z} - (j-1)$$

$$u_{ave} = (v_{i,j}(1-c_{zz}) + v_{i,j+1}c_{zz})(1-c_{rz}) + (v_{i+1,j}(1-c_{zz}) + v_{i+1,j+1}c_{zz})c_{rz} \quad (2-67)$$

Fig. 2.5 Node system showing interpolation process for determining the velocity of a particle at point r_p^n, z_p^n .

2.8 DENSITY INTERFACE VORTICITY GENERATION

The density interface generates vorticity due to the difference in density of the fluids on the top and bottom. Because the diffusion of vorticity is small compared to convection, vorticity is convected along the interface. This can be seen by considering the generation and transport of vorticity from buoyancy forces,

$$\frac{\partial Y}{\partial t} + u \frac{\partial Y}{\partial r} + v \frac{\partial Y}{\partial z} = -\phi g \frac{\partial}{\partial r} (\beta T) \quad (2-68)$$

or

$$\frac{\partial Y}{\partial t} + u \frac{\partial Y}{\partial r} + v \frac{\partial Y}{\partial z} = \frac{u}{r} Y - \phi g \frac{\partial}{\partial r} (\beta T)$$

This in turn can be expressed in a Lagrangian manner,

$$\frac{DY}{Dt} = \frac{u}{r} Y - \phi g \frac{\partial}{\partial r} (\beta T) \quad (2-69)$$

where the vorticity component $Y = \omega_b$ results from buoyancy forces alone. By tracking discrete points along the density interface using Eqs. (2-62) and (2-63), tracking the vorticity at each of these points is also straight forward, using Eq. (2-69) to calculate the generation by buoyancy and the effect of stretching with radial motion. Referring to Fig. 2.6, the vorticity existing at the line segment between interface nodes $k-1$ and k is related to the local interface slip velocity, ΔU_{ck} , by

$$\begin{aligned} Y = \omega_b &= \frac{\Delta u}{\Delta H_{ck}} - \frac{\Delta v}{\Delta R_{ck}} \\ &= \Delta U_{ck} \left(\frac{\Delta R_{ck}}{\Delta S_{ck}} \frac{1}{\Delta H_{ck}} + \frac{\Delta H_{ck}}{\Delta S_{ck}} \frac{1}{\Delta R_{ck}} \right) \\ &= \frac{\Delta U_{ck}}{\Delta R_{ck} \Delta H_{ck}} \left(\frac{\Delta R_{ck}^2}{\Delta S_{ck}} + \frac{\Delta H_{ck}^2}{\Delta S_{ck}} \right) \\ &= \frac{\Delta U_{ck} \Delta S_{ck}}{\Delta R_{ck} \Delta H_{ck}} \end{aligned} \quad (2-70)$$

The vorticity added to any control volume in the finite difference formulation used to obtain the velocity field can then be found by summation over the segments within a distance of $\pm \Delta r/2$ and $\pm \Delta z/2$ of the node i,j ,

$$\begin{aligned} Y_{i,j} &= \sum c_r c_z \frac{\Delta U_{ck} \Delta S_{ck}}{\Delta R_{ck} \Delta H_{ck}} \frac{\Delta A_{ck}}{\Delta A_{i,j}} \\ &= \frac{1}{\Delta r \Delta z} \sum c_r c_z \Delta U_{ck} \Delta S_{ck} \end{aligned} \quad (2-71)$$

where $\Delta A_{ck} = \Delta R_{ck} \Delta H_{ck}$ is the area associated with the interface segment k , $\Delta A_{i,j} = \Delta r \Delta z$ the control volume area, and c_r and c_z linear interpolation constants which are based on the location of the interface segment. For example, for a segment located at a radius $R_{c,k-1/2}$ between finite-difference nodes i and $i+1$,

$$c_r = \frac{r_{i+1} - (R_{ck} + R_{c,k-1})/2}{r_{i+1} - r_i} \quad c_z = \frac{z_{j+1} - (H_{ck} + H_{c,k-1})/2}{z_{j+1} - z_j} \quad (2-72)$$

The finite difference form of Eq. (2-69) then looks like

$$\frac{\Delta S_{ck}}{\Delta R_{ck} \Delta H_{ck}} \left(\frac{\Delta U_{ck}^{n+1} - \Delta U_{ck}^n}{\Delta t} \right) = \frac{u}{R_{c,k-1/2}} \frac{\Delta S_{ck}}{\Delta R_{ck} \Delta H_{ck}} \Delta U_{ck}^n - \frac{\phi g \beta \Delta T}{\Delta R_{ck}} \quad (2-73)$$

where ΔT is the total temperature change, or noting that $u \Delta t = r^{n+1} - r^n$,

$$\Delta U_{ck}^{n+1} = \Delta U_{ck}^n \left(\frac{R_{ck}^{n+1} + R_{c,k-1}^n}{R_{ck}^{n+1} + R_{c,k-1}^n} \right) - \phi g \beta \Delta T \Delta t \frac{\Delta H_{ck}}{\Delta S_{ck}} \quad (2-74)$$

Thus the slip velocity ΔU_c at any location along the interface changes due to outward radial motion and buoyancy effects.

Fig. 2.6 Vorticity generation over a portion of the interface.

The initial interface condition, at the time that the dense fluid first appears at the bottom, is given by

$$\begin{aligned} \Delta U_{ck} &= 0 & H_{ck} &= 0 \\ R_{c1} &= 0 & R_{ck} &= R_{c,k-1} + R_T/(M_c - 1) \end{aligned} \quad (2-75)$$

where M_c is the number of interface nodes (50 used here). The initial interface node locations are spaced uniformly across the tank bottom. The node locations are then shifted using Eqs. (2-62) and (2-63) for a time step, and the new values of the interface slip ΔU_{ck} calculated using Eq. (2-74). Because some interface nodes are convected out of the tank, linear interpolation along the interface is used to shift the interface nodes backwards. This shifting procedure involves first calculating the length of the interface between the tank center and the tank exit,

$$S_c = \sum_{k=1}^{k_l} \Delta S_{c k} \quad (2-76)$$

where k_l is the last node remaining inside the tank. Linear interpolation then provides new values of R_c , H_c , and ΔU_c , with uniform spacing along the interface at intervals $\Delta S_{c,new} = S_c/M_c$.

2.9 TEMPERATURE DISTRIBUTION FORMULATION

With a fully Lagrangian solution for the stratification interface, the energy equation (2-28) is solved by tracking the location of the interface, because with the negligible physical diffusion indicated by scaling, the temperatures remain distinct on each side of the interface. The code also provides the capability to use finite-difference methods to solve for energy transport, allowing a variable inlet temperature to be specified. In this case, the finite-difference equations take the same form as those for vorticity, with zero source terms, Eq. (2-55).

2.10 REFERENCES

1. K. Vafai and C.L. Tien, "Boundary and Inertia Effects on Flow and Heat Transfer in Porous Media," *International Journal of Heat and Mass Transfer*, Vol. 24, pp. 195-203, 1981.
2. J.C. Slattery, "Multiphase Viscoelastic Flow through Porous Media," *A.I.Ch.E. J.*, Vol 14, No. 1, pp 50-56, (1968).
3. S. Whitaker, "Advances in Theory of Fluid Motion in Porous Media," *Ind. Engng. Chem.*, Vol. 61, No. 12, pp 14-28, (1969).
4. J.C. Slattery, *Momentum, Energy and Mass Transfer in Continua*, Krciger Press, New York (1978).
5. A. Zukauskas, "Heat Transfer from Tubes in Crossflow," *Advances in Heat Transfer*, Eds. J.P. Hartnett and T.F. Irvine, Academic Press, New York, Vol. 8, pp.93-161, 1972.
6. DP-402, Circulation of Heavy Water Moderator in a Reactor, H.E. Wingo, November 1959.
7. N.E. Todreas and M.S. Kazimi, *Nuclear Systems I*, Hemisphere Publishing Corp., New York, pg. 379, 1990.

Chapter 3

MODFLOW CODE STRUCTURE

MODFLOW is written in Fortran, and is compiled using Mactran Plus Version 4.0 for use on the Macintosh computer. The main body of the code is written in standard Fortran, and thus can be run generically on a variety of platforms. Two subroutines (hello.f and vplot.f) use special commands to access the Macintosh Toolbox, permitting interactive operation of the program and graphical output. Input to the program is provided through an input data deck, 'modflow.in', and output is shown graphically. Velocities and ink packet locations are recorded at intervals specified by the user and stored in a file 'modflow.out'. This chapter describes the numerical methods used to solve the governing equations given in Chapter 2, and outlines the architecture of MODFLOW. Appendix A provides a full source listing for MODFLOW.

3.1 SOLUTION METHODS

MODFLOW employs primarily explicit techniques for solving the governing equations presented in Chapter 2. The equations solved are:

Plume Transport - the locations of the ink packets are determined explicitly at each new time step, using the previous position and interpolated values for the velocity at the previous time step with equations (2-57) to (2-62).

Energy Transport - energy transport is solved in one of two ways. In methods 1 and 2, the density interface location is tracked in the same manner as the ink packets (equations 2-57 to 2-62). In method 3, a finite difference formulation is applied, using similar transport equations to those applied for vorticity transport (equations 2-52 to 2-55).

Vorticity Transport - the transport of vorticity, equations (2-52) to (2-55), is solved explicitly at each new time step based on the velocity and vorticity distribution at the previous time step. Vorticity generated by the tube bank is solved using a finite-difference formulation. Vorticity generated by buoyancy forces at the density interface is either included in the finite-difference solution (methods 2 and 3) or is solved for in a Lagrangian manner (method 1) using equations (2-65) to (2-70).

Poisson Equation - the Poisson equation for the stream function (equations (2-41) to (2-44)) is solved by successive over relaxation at each new time step, based on the newly calculated vorticity distribution. From the stream function solution, the new velocity field is determined.

3.2 PROGRAM ARCHITECTURE

MODFLOW consists of a main program and several subroutines. The program and subroutine names are listed in Table 3.1, with a brief description of the purpose of each.

Table 3.1 - MODFLOW program and subroutines.

Name	Purpose
modflow.f	main program - accepts data input, initializes variables, and iterates through time steps, solving for the temperature distribution, ink packet locations, vorticity distribution, stream function, velocity components, and writing output to file 'modflow.out'.
readin.f	data input - reads in data from file 'modflow.in' and removes comment statements.
hello.f	initial window - uses Macintosh Toolbox calls to generate initial "hello" window.
init.f	initial velocity distribution - if specified, reads data from an input file for the initial velocity distribution. Saves time by preventing the need to run to steady-state conditions each time the program is called.
vplot	control window - uses Macintosh Toolbox to generate the control window and graphics.
cldfrt.f	cold water interface - subroutine to shift the cold water interface in a Lagrangian manner.
move.f	move a point - shifts an ink packet or cold water interface point to a new location.
fric.f	friction factors - calculates friction factors based on the local Reynolds number.

Figure 3.1 shows the flow diagram for solving the coupled momentum, energy, and mass transport problem with the MODFLOW code. Three solution methods are provided. Method 1 is recommended as providing the minimum numerical diffusion. For long time periods, Method 1 become unstable when the top region becomes fully stagnant and the interface begins to level out. The additional numerical diffusion from Method 2 stabilizes the solution for longer time periods, providing improved results at longer times. Method 3, which is fully finite-difference, is stable, but shows large numerical viscosity. Method 1 predicts the earliest times for ink exiting the tank, and thus provides the most conservative prediction of the stratification effects.

3.3 PROGRAM MAINTENANCE

The MODFLOW code is extensively commented to aid review, revision, and updating. Because the code will be ultimately used for a variety of problems where additional routines will be required, such as particle transport problems, the code is designed such that these additions can be made easily. Nonstandard fortran routines for accessing the Macintosh toolbox are confined to two subroutines, such that programmers familiar with the Fortran language can make additions to the code.

Fig. 3.1 Flow diagram for MODFLOW.

Chapter 4

USER GUIDE

MODFLOW is a particularly simple program to use, due to its interactive user interface. Input to the program is provided by the input data deck 'modflow.in' and output is generated graphically on the screen, as well as being written to the file 'modflow.out.' The user interface allows the problem to be modified as the program is running, so that the engineer can test the effects of changing the flow rate, injecting cold water, or starting the ink plume.

4.1 THE USER INTERFACE

When run on a Macintosh II computer, MODFLOW provides a graphical user interface to provide more information about the flow pattern and the ink distribution. The interface also allows the user to interact directly with the program, starting ink flow, changing flow rates, and performing other functions. Figure 4.1 shows the interface. The following paragraphs describe the purpose and use of each of the interface components, with numbers referring to Fig. 4.1.

1. *Graphics* - MODFLOW shows graphically the velocity vectors, the location of the cold front interface, and the ink plume distribution.

Fig. 4.1 The MODFLOW user interface.

2. *Status Report* - The current time, time step size, flow rate, and the difference in density between the hot and cold water are displayed.
3. **GO Button** - Clicking this button starts the program running. The button changes to a PAUSE button, which can be clicked to stop operation, such that the window can be examined, other functions picked, and the window can be printed. Reclicking the GO Button starts MODFLOW running again.
4. **HALVE/DOUBLE TIME STEP Buttons** - These buttons change the time step size.
5. **DECREASE/INCREASE FLOW Buttons** - These buttons change the flow rate.
6. **QUIT Button** - This button stops MODFLOW.
7. **START COAST DOWN Button** - This button initiates a steady decrease in the flow rate, given by the coast-down information provided in the input deck 'modflow.in'. The time at which coast-down starts can also be set directly in the input deck.
8. **START INK Button** - This button initiates the flow of ink into the reactor, at the locations and rates set in the input deck 'modflow.in'. The time at which ink injection starts can also be set directly in the input deck.
9. **START COLD WATER Button** - This button initiates the flow of cold water into the bottom of the reactor. The time at which cold water starts can also be set directly in the input deck.
10. **CONSTANT FRICTION Check Box** - When this box is checked, constant friction factor values taken from the input data deck 'modflow.in' are used to speed computation. When the box is not checked, the values are calculated based on the local Reynolds number.
11. *Scale* - The scale for the magnitude of the velocity vectors.
12. *Ink location* - This box appears at the time that ink first leaves the reactor tank, and indicates the location of the ink front in the exterior piping. When ink returns to the reactor, the box changes to say 'ink arrived.'
13. **PRINT Button** - This button causes the window to be printed on the currently selected output device.
14. **INFO Button** - This button provides additional information about the program.
15. **SAVE Button** - This button allows the current velocity distribution to be saved in a file. When this file is listed in the input deck 'modflow.in', the program will start with this flow distribution. This button is useful for saving a steady-state flow distribution for starting of transient analysis problems.

4.2 THE DATA INPUT DECK

The data input deck 'modflow.in' provides the input information required to run modflow. Appendix B shows an example input data deck. Each item in the deck is fully commented, so that the deck can be modified and rerun to test different problems.

Chapter 5

PRELIMINARY CODE ASSESSMENT

This chapter compares the results of MODFLOW 2.1 to isothermal tests made in 1959 and tests of the SSS system made in 1975. This data is considered nonqualified since it was obtained in accordance with less stringent QA requirements. Therefore, this comparison is provided to only indicate the similarities between MODFLOW and existing test data.

5.1 COMPARISON WITH 1959 ISOTHERMAL FLOW TESTS

Figure 5.1 shows the steady-state velocity distribution predicted by MODFLOW 2.1 under the conditions examined in 1959 tests of flow in a full-scale 1/6 sector mockup of an SRP reactor [1, 2]. Figure 5.2 shows the velocity distribution that was measured during one test without sparjet injection. The test results were for the case of 4.2" diameter fuel assemblies on 7.0" centers. In the experiment the magnitude and direction of the local moderator velocities were determined by observation of dye traces through a large plexiglas window in the flat wall of the mockup. A concentrated solution of potassium permanganate was injected into the mockup in short bursts through a long probe that was inserted through openings in the plenum between fuel assemblies. The small eddies formed by injection of the dye were observed and timed with a stopwatch as they passed between reference points in the tank.

Fig. 5.1 Velocity distribution predicted by MODFLOW 2.1 for 1959 test conditions without sparjets.

Fig. 5.2 Experimentally measured velocity distribution from 1959 isothermal test without sparjets [2].

Agreement between the results of MODFLOW 2.1 and the 1959 test without sparjet injection is good. Disagreement occurs near the centerline of the tank,

where higher velocities were measured in the experiment. This effect is attributed to the walls of the test apparatus. Because the flat walls are close to the fuel assemblies, they block the radial flow of water, while at the same time the area available for vertical flow is larger. In tube assemblies, horizontal flow tends to channel between tubes, while vertical flow occurs in the shadows behind tubes. Vertical flow is promoted near the flat walls, because the regions behind tubes near the flat walls are protected from horizontal flow. The instrument tubes in the middle region of the tank create another radial flow resistance, promoting vertical flow near the tank centerline. The vertical velocities predicted across the bottom of the tank, 2.71 ft/s, are lower than the 3ft/s value measured. However, this is well within experimental accuracy, remembering that measurements were made with a stopwatch, over a time period well under one second in high velocity regions.

Fig. 5.3 Velocity distribution predicted by MODFLOW 2.1 for 1959 test conditions with sparjets.

Additional tests were performed with 3.4in diameter fuel assemblies, using sparjet injection. For the one-sixth sector tests, a single sparjet with nozzles directed upward at 45° was supplied with 475 gpm. The jet had 18 nozzles of 3/8in diameter in sets of 3 at 1 foot intervals along the lower 7 feet of the tube, with the first nozzle 2 ft from the tank bottom. This caused large eddies which occurred without sparjets with 3.4in diameter fuel to be broken up, and the average moderator velocities to be greatly increased [2]. Figure 5.3 shows a comparison of MODFLOW results for a sparjet mixing volume 4 ft wide and 3.5 ft

high, with the 1959 test results. Agreement is excellent, including the location of the turbulent recirculating zone shown by a "T" in the experimental results.

5.2 COMPARISON WITH 1975 SSS SYSTEM TEST

In 1975 the SSS system of the C reactor was tested at approximately 60% of full power, or at approximately 1200MW. At a total moderator flow rate of 150,000 gpm, activation of the SSS system resulted in a rapid 30°C decrease in the temperature of the heavy water entering the bottom of the reactor [1].

At approximately 17.4 seconds after initiation of ink injection a positive period of about 4.5 sec was detected by the period monitor and a scram occurred which inserted the safety rods. A report [3] states that "all of the top detectors are in relatively high concentrations of poison and consequently the safety rod entry is not clearly distinguished. However, in Gangs II, III, and the buckled zone the bottom detectors clearly show a sharp flux decrease at about 18 sec. Relatively small concentrations of poison occur in the regions until after about 26-30 seconds when recirculation occurs."

Figures 5.4 through 5.7 show the MODFLOW 2.1 simulation of the 1975 SSS system test, for two different flow rates and bottom inlet flow distributions. From steady state conditions, ink is injected at time 0.8 sec. Simultaneously at 0.8 sec the inlet water temperature is assumed to drop, consistent with the rapid drop in reactor power noted in the test [3]. The range of conditions studied are tabulated in Tables 5.1. In the C reactor charge the core is symmetrically equivalent in 120° increments, versus 60° increments for the K reactor. Thus the outlet nozzles set one of two possible bottom flow distributions, given as Case 1 and Case 2 in Table 5.2. Figure 5.8 shows results calculated without sparjet injection.

The sparjets are substantially more effective in mixing the tank than in the 1959 tests. This is due to the fact that there are twice as many injection holes of smaller diameter, but approximately equal flow rate. The smaller diameter result in injection velocities approximately twice those of the 1959 tests. The momentum added by the sparjets is large compared to the effects of buoyancy, and therefore the up and over flow pattern continues without modification. This contrasts to the predictions without sparjets (Fig. 5.8), where buoyancy effects are large. The predicted ink distributions in Figures 5.4 through 5.7 compare well with the neutron fluxes observed in the experiment. The resulting flow patterns are relatively insensitive to the bottom flow distribution, though total flow rate is important, particularly since it also modifies the hot/cold density difference, for a given power level. MODFLOW predicts that ink leaves the reactor between 13 and 14 seconds, and returns to the reactor after traveling through the external piping at between 23 and 25 seconds. In the test, a strong decrease in flux was observed at 30 sec.

Table 5.1 - 1975 Test bracketing cases.

Figure	Flow rate (ft ³ /s)	Temperature change (°C)	Bottom Flow distribution	Time exiting tank (sec)	Rearrival time (sec)
5.3	354.12	22.9	Case 1	13.7	23.7
5.4	"	"	Case 2	13.7	23.7
5.5	336.92	36.0	Case 1	13.0	24.8
5.6	"	"	Case 2	13.0	24.8

Fig. 5.4 MODFLOW 2.1 simulation of 1975 SSS system test results, for flow rate of 354.12 ft³/s, flow distribution Case 1.

Table 5.2 - Bottom flow distributions (relative flow, center to wall).

Node	Case 1	Case 2	Node	Case 1	Case 2
1	73.0	100	8	74.5	88.0
2	69.0	69.0	9	72.2	72.2
3	93.3	79.8	10	87.8	76.5
4	79.4	84.8	11	72.3	83.8
5	80.0	75.5	12	83.9	84.9
6	68.8	81.3	13	78.5	78.6
7	79.3	70.3

Fig. 5.5 MODFLOW 2.1 simulation of 1975 SSS system test results, for flow rate of 354.12 ft³/s, flow distribution Case 2.

Fig. 5.6 MODFLOW 2.1 simulation of 1975 SSS system test results, for flow rate of $336.92 \text{ ft}^3/\text{s}$, flow distribution Case 1.

Fig. 5.7 MODFLOW 2.1 simulation of 1975 SSS system test results, for flow rate of 336.92 ft³/s, flow distribution Case 2.

Fig. 5.8 MODFLOW 2.1 simulation without sparjet flow of 1975 SSS system test results, for flow rate of $336.92 \text{ ft}^3/\text{s}$, flow distribution Case 2, showing buoyancy effects.

Figure 5.9 shows times at which ink first was detected by conductivity meters during the 1975 test [4]. In the test, ink was observed at the top, outer region of the tank at 7 and 10 seconds, at exactly the same time and location as in the simulation. This effect was not seen with MODFLOW Version 2.0, which neglected the spar jet injection. The appearance near the outlet nozzle at 15 sec occurred 1 to 2 seconds later than predicted by MODFLOW. The appearance of recirculated material near the bottom at 27 seconds is also well predicted by MODFLOW.

TIME GO REACHED DETECTORS, SECONDS

Fig. 5.9 - Ink arrival times measured during 1977 SSS system test [4].

5.3 PREDICTED PERFORMANCE FOR K-REACTOR COASTDOWN CASE

Figure 5.10 shows ink distributions predicted under flow coast-down conditions for the K-reactor. The K-reactor differs from the C-reactor tested in 1975 in that the tank has a smaller diameter and the bottom inlet flow distribution is more uniform. In the case presented here, coastdown occurs from an initial power level of 1100 MW, with ink injection occurring at 4.82 seconds, and cold water appearing at the tank bottom at 5.5 seconds. Due to the coastdown, stratification effects are increased substantially, and ink is trapped more effectively in the top region of the reactor. This substantiates previous calculations showing that larger ink inventories remain in the reactor during a flow coastdown, improving performance of the SSS system.

Figure 5.10 presents results based on a finite-difference calculation of vorticity transport (Method 2). With both Methods 1 and 2, numerical instability was observed when the upper region becomes fully stagnant and the interface approaches a level condition, and the calculation was terminated. In experiments in a rectangular geometry [5], convective mixing and waves were observed at the interface near the wall where the numerical instability

occurs. In the physical system, these waves dissipate, but in MODFLOW the waves are constrained to a wavelength corresponding to the grid spacing, and thus instability occurs. Because the instability occurs after recirculating ink has returned to the tank, it is not of importance in assessing the SSS performance.

The numerical results show a relatively narrow plume. In reality, the plume diameter will be larger due to dispersion effects. Additionally, the ink is injected radially from the spar jets, and thus is spread over a larger diameter, increasing the size of the plume.

Fig. 5.10 MODFLOW 2.1 simulation of K-Reactor ink distribution during coast-down from 1100MW power level, using finite-difference solution for vorticity.

5.4 REFERENCES

1. SRL-SAG-910378, Input Decks for the 1959 and 1975 Test Cases of MODFLOW, R. Garrett, 1991.
2. DP-402, Circulation of Heavy Water Moderator in a Reactor, H.E. Wingo, November 1959.

Version 2.1	Rev. 0	CODE REQUIREMENTS DOCUMENT	03/11/92
-------------	--------	----------------------------	----------

3. DPST-75-341, "SSS Test Results," C.E. Ahlfeld, 1975.
4. DPST-77-467, "GRASS Calculation of the SSS Test To Verify the Material Transport Model," D.E. Hostetler, 1977.
5. P.F. Peterson and A. Akbarzadeh, "Modelling of Transient Stratified Flow in Tube Bundles," ASME National Heat Transfer Conference, Minncapolis, Minn, July 29 - July 31, 1991.

APPENDIX A

MODFLOW 2.1 PROGRAM LISTING

MODFLOW.f

```

c
c   MODFLOW.f - Version 2.1      Nov. 4, 1991  P.F. Peterson  U.C.Berkeley
c
c   Modflow calculates flow and temperature distributions in an SRP reactor
c   when cold fluid is injected into the reactor tank.
c
c   Modflow calculates the transient flow distribution based on a finite
c   difference solution of the momentum equation with buoyancy effects.
c
c   INPUT VARIABLES
c
c   Qin   - total input flow rate, ft3/s
c   BdT   - thermal expansion coefficient*temperature difference
c   delt  - time step, s
c   tink  - time of ink injection, s
c   tcold - time of step change in bottom temperature, s
c   tmax  - maximum time period for calculation, s
c   mwide - number of radial nodes
c   nhigh - number of vertical nodes
c
c   cvel(i) - array of mwide-1 values for relative bottom inlet flow rate
c
c   mcoast - 0 = constant flow rate
c           1 = coastdown from initial flow Qin, using curve in file 'coast.in'
c
c   coast(1,k) - time from file 'modflow.in', s
c   coast(2,k) - percent of original flow, from file 'modflow.in'
c
c   tjet(1) - time for ink jet injection from file 'modflow.in', s
c   fjet(jet,1) - flow rate of jet at time tjet(1), gal/sec (undilluted)
c   hjet(1jet) - height of ink packet 1jet, ft
c   rjet(1jet) - radius of ink packet 1jet, ft
c   sjet(1jet) - size of ink packet 1jet, gal (undilluted)
c
c   ntemps - number of bottom inlet temperature history items
c   btemp(1,k) - time, s
c   btemp(2,k) - fraction of final bottom temperature
c
c   nspar - number of injection points along sparjet
c   spver - spar jet effective mixing volume - vertical dimension, ft
c   sprad - spar jet effective mixing volume - horizontal dimension, ft
c   spr(k) - radial location of sparjet injector #k, ft
c   spv(k) - vertical location of sparjet injector #k, ft
c   spq(k) - volume flow through sparjet injector #k, ft3/s
c   sparea(k) - cross-sectional area of sparjet injector #k, ft2
c   spang(k) - injection angle from vertical of sparjet injector #k, degrees
c
c   PROGRAM VARIABLES
c
c   Hc(i) - height of cold moderator interface point, ft
c   Rc(i) - radius of cold moderator interface point, ft
c   Htank - height of moderator, ft
c   Rtank - reactor tank radius, ft
c   Atank - total area of reactor tank, ft
c   Dfuel - diameter of fuel assemblies, in
c   Sfuel - pitch of fuel assemblies, in
c   Arstar - ratio of minimum radial flow area to total area.
c   void - void fraction.
c   Vext - external piping volume (ft3)
c   time - time, sec
c   ntime - total number of time steps
c   rad(i) - radius of nodes, ft
c

```

```

parameter (nmax = 41,mmax = 81,inkmax=981)
character*80 words,runtit
character*12 initfl
character*12 filein,filout
dimension u(0:nmax,mmax),v(0:nmax,mmax),
*   t(0:nmax,0:mmax),told(0:nmax,0:mmax),psi(0:nmax,mmax),
*   zeta(0:nmax,0:mmax),zold(0:nmax,0:mmax),zgrav(0:nmax,0:mmax),
*   bz(nmax,mmax),gspar(0:nmax,mmax),
*   anspl(nmax),aepl(nmax),awpl(nmax),
*   bp(nmax,mmax),appl(nmax),
*   rad(0:nmax),dR2(0:nmax),dArea(0:nmax),dVol(0:nmax),
*   Hc(0:125),Rc(0:125),Uc(0:125),
*   Hcold(0:100),Rcold(0:100),Ucold(0:100),
*   vrhot(nmax),vrcold(nmax),coast(2,100),btemp(2,100),
*   tjet(21),fjet(7,21),rjett(7),hjett(7),
*   hjet(inkmax),rjet(inkmax),sjet(inkmax),
*   cvel(nmax),
*   spr(20),spv(20),spq(20),sparea(20),spang(20)
common /vel/u,v
common /temper/t,told
common /flow/psi,zeta,zold
common /grav/zgrav
common /cold/Hc,Rc,Uc
common /ccold/Hcold,Rcold,Ucold
common /inkk/hjet,rjet,sjet,njet
c
c   read in input information from file 'modflow.in'
c
filein = 'modflow.in'
filout = 'modflow.out'
call readin(nnnn,filein,filout)
read(3,'(A)') runtit
read(3,*) NWIND,Qinx,topflo,BdF,delt
read(3,*) nsolve,vorfac,ncoord,vscale
read(3,*) initl
read(3,'(A)') initfl
read(3,*) jtime,jink,mcoast,tink,tcold,tmax
read(3,*) mwide,nhigh
read(3,*) errmax,Htank,Rtank,tubes,Dfuel,Sfuel,Vext,temp
read(3,*) nfric,xfr,xfv
read(3,*) (cvel(i),i=1,mwide-1)
IF (NWIND.NE.0) THEN
  write(*,*) 'Program MODFLOW, Qin =',Qinx
ELSE
  CALL HELLO
  NFIRST = 0
  NGO = 0
ENDIF
pi = 3.141593
Vout = 0.
delr = Rtank/float(mwide-1)
delr2 = delr/2.
delz = Htank/float(nhigh-1)
delz2 = delz/2.
time = 0.
nstart = 0
jjink = 1000
jftime = 1000
icome = 0
ncoast = 1
mcold = 0
mink = 0
njet = 0
njett = 1
nh = nhigh
nh1 = nhigh-1
nh2 = nhigh-2
mw = mwide
mw1 = mwide-1
mw2 = mwide-2
zero = 0.
one = 1.

```

```

tiny = 1.e-20
if (ncoord.eq.0) then
  grav = 32.2
  Atank = pi*Rtank**2
  Atop = pi*delr**2
  * Arstar = Sfuel/(Sfuel - Dfuel)
  void = 1. - (pi*Dfuel**2)/(4.*(Sfuel**2)*0.866)
  Dhydr = 4.*(Sfuel**2)*0.866-0.25*pi*Dfuel**2)/(pi*Dfuel*12)
  voidDh = 2.*void*Dhydr*delr
  ArR = tubes*void*Arstar*Arstar/(2.*Rtank*delz)
else
  grav = 9.81
  Atank = Rtank*Sfuel
  Atop = delr*Sfuel
  Arstar = Sfuel/(Sfuel - Dfuel)
  void = 1 - tubes*pi*Dfuel*Dfuel/(4.*Atank)
  Dhydr = 4.*(Atank - tubes*pi*Dfuel*Dfuel/4.)
  * / (2.*(Rtank-tubes*Dfuel) + tubes*pi*Dfuel)
  voidDh = 2.*void*Dhydr*delr
  ArR = tubes*void*Arstar*Arstar/(2.*Rtank*delz)
endif
thous = 1000
relax = 1.2
relax1 = 1. - relax
ntime = int(amin1(thous,tmax/delt))

c
c read in coast down data
c
  read (3,*) nodat
  do 10 k = 1,nodat
    read(3,*) coast(1,k),coast(2,k)
  10 continue
c
c read in ink injection rate data
c
  read (3,*) inkin,inkdat
  read(3,*) (rjett(jet),jet=1,inkin)
  read(3,*) (hjett(jet),jet=1,inkin)
  do 20 k = 1,inkdat
    read(3,*) tjet(k), (fjet(jet,k),jet=1,inkin)
  20 continue
c
c if using fully finite difference formulation, read in bottom
c temperature history
c
  if (nsolve.eq.2) then
    read (3,*) ntemps
    do 25 k = 1,ntemps
      read(3,*) btemp(1,k),btemp(2,k)
    25 continue
  endif
c
c read in sparjet data
c
  read (3,*) nspar
  read (3,*) spver, sprad
  do 28 k = 1,nspar
    read(3,*) spr(k), spv(k), spq(k), sparea(k), spang(k)
  28 continue

  close (3)

c
c INITIALIZE THE PROBLEM
c
c calculate initial cold front locations.
c
  rr = 0.
  dr = Rtank/49.
  Rc(1) = 0.
  Hc(1) = 0.
  Uc(1) = 0.
  Rcold(1) = 0.

```

```

Hcold(1) = 0.
Ucold(1) = 0.
do 30 l = 2,50
  Rc(l) = Rc(l-1) + dr
  Hc(l) = 0.
  Uc(l) = 0.
  Rcold(l) = Rc(l)
  Hcold(l) = 0.
  Ucold(l) = 0.
30  continue
c
c  calculate node radii
c
rad(1) = 0.
if (nccord.eq.0) then
  do 50 i = 2,mwide
    rad(i) = rad(i-1)+delr
    dR2(i-1) = 2.0/(rad(i)**2 - rad(i-1)**2)
    dArea(i) = rad(i+1)**2 - rad(i)**2
    dVol(i) = dArea(i)*delz
50  continue
    dR2(0) = 0.
    dR2(mwide+1) = 0.
  else
    do 60 i = 2,mwide
      rad(i) = 1.
      dR2(i-1) = 1./delr
      dArea(i) = delr
      dVol(i) = delr*delz
60  continue
      dR2(0) = 0.
      dR2(mwide+1) = 0.
    endif
c
c  normalize the inlet flow rate values cvel(i)
c
sum1 = 0.
sum2 = 0.
do 63 i=1, mwide-1
  sum1 = sum1 + cvel(i)/dR2(i)
  sum2 = sum2 + 1./dR2(i)
63  continue
do 65 i=1, mwide-1
  cvel(i) = cvel(i)*sum2/sum1
65  continue
c
c  calculate influence coefficients for Poisson equation for psi
c
do 70 i = 2,mwide-1
  rr = rad(i)
  aepl(i) = delz*dR2(i)
  awpl(i) = delz*dR2(i-1)
  anspl(i) = delr/(rad(i)*delz)
  appl(i) = aepl(i) + awpl(i) + 2.*anspl(i)
70  continue
c
c  initialize velocity, stream function, vorticity, and temperature registers
c
do 90 i = 0,rmax
  do 80 j = 1,mmax
    u(i,j) = 0.
    v(i,j) = 0.
    t(i,j) = 0.
    told(i,j) = 0.
    psi(i,j) = 0.
    zeta(i,j) = 0.
    zold(i,j) = 0.
    zgrav(i,j) = 0.
    gspar(i,j) = 0.
80  continue
90  continue
c

```

```

c      calculate constants for sparjet injection (gspar(i,j))
c
      mswide = min( mwide - 2, max(1,int(sprad/delr)))
      nshigh = min( nhigh - 2, max(1,int(spver/delz)))
      do 110 k=1,nspar
        imid = min(mwide-1, max(1,int(1.5 + spr(k)/delr)))
        ileft = max(1, imid-mswide/2)
        irect = min(mwide, ileft + mswide)
        if (irect.ge.mwide) ileft = irect - mswide
        jbot = min(nhigh-1, max(1,int(1.5 + spv(k)/delz)))
        jtop = min(nhigh, jbot + nshigh)
        if (jtop.ge.nhigh) jbot = jtop - nshigh
        volmix = 3.1415*(rad(irect)*rad(irect)-rad(ileft)*rad(ileft))
        *      *float(nshigh+1)*delz
        gadd = spq(k)/(delr*volmix)
        gvel = void*cos(spang(k)*3.1415/180)*spq(k)/sparea(k)
        do 100 j=jbot, jtop
          gspar(ileft,j) = gspar(ileft,j) + gadd*gvel
          gspar(irect,j) = gspar(irect,j) - gadd*gvel
100      continue
110      continue
c
c      if requested in input deck, retrieve initial values from file 'initfl'
c
c      if (initl.eq.1) call init(mwide,nhigh,qinx,initfl)
c
c      *****
c      ITERATE THROUGH THE TIME STEPS
c      *****
c
c      iterate ntime time steps
c
c      do 1000 loop = 1,ntime
c
c      OPEN MACINTOSH WINDOW
c
c      IF (NWIND.eq.0) THEN
        VMAX = Qinx/Atank
        CALL VPLOT (MWIDE,NHIGH,VMAX,TIME,DELT,QIN,QINX,BdT,
        *      ARSTAR,VOID,MCOAST,MCOLD,TINK,NSTART,VEXT,VOUT,VSCALE,
        *      NFRIC,NREC,METHOD,NFIRST,NCOORD,RTANK,HTANK,INKIN,
        *      NGO,UCMAX,DELR)
        NFIRST = 10
      ENDIF
      do 800 inloop = 1,jtime
        time = time + delt
c
c      *****
c      calculate the temperature distribution if cold water
c      is being added
c      *****
c
c      if nsolve=0,1, use Lagrangian solution
c      if nsolve=2, use finite difference solution
c
c      if (mcold.ne.1.and.tcold.gt.time) go to 190
        mcold=1
c
c      if nsolve = 0 or 1, move the cold front interface points
c      one time step, and calculate the buoyancy vorticity contribution,
c      zgrav(i,j), if nsolve=1
c
c      if (nsolve.le.1) then
        call cldftr (mwide,nhigh,delz,delr,delt,rtank,
        *      rtank,grav,BdT,void,nsolve,ncoord)
c
c      if nsolve=2 find temperature using finite differences, centerline:
c
c      else
c      find bottom inlet temperature
        Tin = 1.0
        ttt = time + delt/2. - tcold

```

```

do 128 i = 2, ntemp
  if (btemp(1,i) .gt. ttt ) go to 129
  continue
129 continue
  Tin = 1 - (btemp(2,i-1) +
*         (btemp(2,i)-btemp(2,i-1))*
*         (ttt - btemp(1,i-1))/
*         (btemp(1,i) - btemp(1,i-1)))
  do 130 i = 1,mwide
    t(i,1) = Tin
    continue
130 rr = delr
    if (ncoord.eq.0) then
      dAr = delr2*delr2
      dAze = 2.*delr2*delz
    else
      dAr = delr2
      dAze = delz
    endif
    dv = dAr*delz
    IF (nwind.eq.0) then
      CALL GRAFTB(2,2,410,230,670,246)
      CALL GRAFTB(14,410,240)
      WRITE(*,*) "do 140"
    ENDIF
    do 140 j = 2,nhl
      ue = 0.25*(u(2,j)+u(2,j-1))
      vn = 0.5*(v(1,j)+v(1,j+1))
      vs = 0.5*(v(1,j)+v(1,j-1))
      aet0 = amax1(zero, -dAze*ue)
      ant0 = amax1(zero, -dAr*vn)
      ast0 = amax1(zero, dAr*vs)
      apt1 = dv/delt
      apt0 = apt1 - aet0 - ant0 - ast0
      if (apt0.lt.0.) then
        IF (nwind.eq.0) then
          CALL GRAFTB(2,2,410,230,670,246)
          CALL GRAFTB(14,30,70)
        ENDIF
        write(*,*) '(1) negative influence coef.!',i,j
      endif
      t(1,j) = (apt0*told(1,j)+aet0*told(2,j)
*         + ast0*told(1,j-1)+ant0*told(1,j+1))/apt1
140 continue
    temperature away from tank center

    do 160 i = 2,mwl
      rr = rad(i)
      if (ncoord.eq.0) then
        dAr = (rr+delr2)**2 - (rr-delr2)**2
        dAze = 2.*(rr+delr2)*delz
        dAzw = 2.*(rr-delr2)*delz
      else
        dAr = delr
        dAze = delz
        dAzw = delz
      endif
      dv = dAr*delz
      do 150 j = 2,nhl
        ue = 0.25*(u(i,j)+u(i+1,j)+u(i,j-1)+u(i+1,j-1))
        uw = 0.25*(u(i,j)+u(i-1,j)+u(i,j-1)+u(i-1,j-1))
        vn = 0.25*(v(i,j)+v(i,j+1)+v(i-1,j)+v(i-1,j+1))
        vs = 0.25*(v(i,j)+v(i,j-1)+v(i-1,j)+v(i-1,j-1))
        aet0 = amax1(zero, -dAze*ue)
        awt0 = amax1(zero, dAzw*uw)
        ant0 = amax1(zero, -dAr*vn)
        ast0 = amax1(zero, dAr*vs)
        apt1 = dv/delt
        apt0 = apt1 - aet0 - awt0 - ant0 - ast0
        if (apt0.lt.0.) then
          IF (nwind.eq.0) then

```

```

        CALL GRAFTF(2,2,410,230,670,246)
        CALL GRAFTB(14,30,70)
        ENDIF
        write(*,*) '(2) negative influence coef.!',i,j
    endif
    t(i,j) = (apt0*told(i,j)
    *      + aet0*told(i+1,j) + awt0*told(i-1,j)
    *      + ast0*told(i,j-1) + ant0*told(i,j+1))/apt1
150    continue
160    continue
c
c    temperature at tank wall
c
        IF (nwind.eq.0) then
            CALL GRAFTB(2,2,410,230,670,246)
            CALL GRAFTB(14,410,240)
            WRITE(*,*) "tank wall"
        ENDIF
    if (ncoord.eq.0) then
        dAr = (Rtank)**2 - (Rtank-delr2)**2
        dAzw = 2.*(Rtank-delr2)*delz
    else
        dAr = delr2
        dAzw = delz
    endif
    dv = dAr*delz
    do 170 j = 2,nhl
        uw = 0.25*(u(mw1,j)+u(mw1,j-1))
        vn = 0.5*(v(mw1,j)+v(mw1,j+1))
        vs = 0.5*(v(mw1,j)+v(mw1,j-1))
        aet0 = amax1(zero, -dAze*ue)
        awt0 = amax1(zero, dAzw*uw)
        ant0 = amax1(zero, -dAr*vn)
        ast0 = amax1(zero, dAr*vs)
        apt1 = dv/delt
        apt0 = apt1 - aet0 - awt0 - ant0 - ast0
        if (apt0.lt.0.) then
            IF (nwind.eq.0) then
                CALL GRAFTB(2,2,410,230,670,246)
                CALL GRAFTB(14,30,70)
            ENDIF
            write(*,*) '(3) negative influence coef.!',i,j
        endif
        t(i,j) = (apt0*told(mw,j) + awt0*told(mw1,j)
        *      + ast0*told(mw,j-1) + ant0*told(mw,j+1))/apt1
170    continue
c
c    create isotherms at temperatures 0.9, 0.5, and 0.1
c
    do 180 i = 1,mwide
        tlook = 0.9
        look = 0
        j = 1
175    j = j+1
        if (t(i,j).lt.tlook) then
            ll = i + look*mwide
            if (look.eq.1) ll = 2*mwide + 1 - i
            Hc(ll) = (float(j-2)
            *      + (tlook-t(i,j-1))/(t(i,j)-t(i,j-1)))*delz
            Rc(ll) = delr*float(i-1)
            j = j-1
            if (tlook .gt. Tin) Hc(ll) = 0
            tlook = tlook-0.4
            look = look + 1
        endif
        if (look.le.2.and.j.le.nhigh) go to 175
180    continue
        do 182 lll = ll,125
            Hc(lll)=Hc(ll)
            Rc(lll)=Rc(ll)
182    continue
    endif

```



```

190      continue
c
c      *****
c      advance the ink packets one time step
c      *****
c
      if (time.gt.tink) then
        lstep = 0
        nnjet = njet
        do 200 l = 1,nnjet
          rr = rjet(l-lstep)
          zz = hjet(l-lstep)
          call move(rr,zz,rjet(l-lstep),hjet(l-lstep),
*             mwide,nhigh,delz,delr,delt,void,uu,vv)
          if(hjet(l-lstep).gt.0.99*Htank) hjet(l-lstep)=0.99*Htank
          if(rjet(l-lstep).gt.0.99*Rtank) then
            if(hjet(l-lstep).gt.0.1*Htank) then
              rjet(l-lstep) = 0.99*Rtank
            else
              icome = 1
              do 195 ll=l-lstep,njet
                rjet(ll) = rjet(ll+1)
                hjet(ll) = hjet(ll+1)
                sjet(ll) = sjet(ll+1)
195          continue
                njet = njet-1
                lstep = lstep+1
              endif
            endif
            continue
200          if (icom.eq.1) vout = vout + Qin*delt
        endif
c
c      *****
c      solve for vorticity distribution
c      *****
c
c      calculate friction source terms for vorticity
c      if nsolve = 1 or 2, include buoyancy source term also
c
      if (nsolve.eq.0) then
        buoy = 0.
      else
        buoy = 1.
      endif
      do 210 j = 2,nhigh-1
        bz(1,j) =
*         - buoy*(grav*BdI*void/delr)*(T(2,j)-T(1,j))
        bz(nhigh,j) =
*         - buoy*(grav*BdI*void/delr)*(T(nhigh,j)-T(nhl,j))
210      continue
      do 230 i = 2,mwide-1
        do 220 j = 2,nhigh-1
          call fric (u(i,j),v(i,j),uk2h,vk2h,
*             u(i,j-1),v(i-1,j),uk2l,vk2l,
*             Sfue1,Dfue1,void,Dhydr,ArR,voidDh,temp,
*             nfric,xfr,xfv,ncoord)
          bz(i,j) = (uk2h-uk2l) - (vk2h-vk2l)
*             - buoy*(grav*BdI*void/(2.*delr))*(T(i+1,j)-T(i-1,j))
220        continue
230      continue
      do 294 j = nhigh-1,1,-1
        write(*,296) (bz(i,j),i=1,mwide-1)
c 296      format('bz',10f8.2)
c 294      continue
c      write(*,*)
c
c      advance the vorticity solution one time step
c
c      vorticity next to the tank centerline:
c

```

```

if (ncoord.eq.0) then
  rr = delr
  rrdr2p = rr + delr2
  dr2m = delr*2.
  rrdrp = rr + delr
  rrdm = rr - delr
else
  rr = 1.
  rrdr2p = 1.
  dr2m = 1.
  rrdrp = 1.
  rrdm = 1.
endif
do 240 j = 2,nhl
  ue = -0.25*(u(2,j)+u(3,j)+u(2,j-1)+u(3,j-1))
  vn = -0.25*(v(2,j)+v(2,j+1)+v(1,j)+v(1,j+1))
  vs = 0.25*(v(2,j)+v(2,j-1)+v(1,j)+v(1,j-1))
  rue = amax1(zero, rrdr2p*ue/delr)
  aez0 = rue/dr2m
  anz0 = amax1(zero, vn/delz)
  asz0 = amax1(zero, vs/delz)
  apz1 = 1./delt
  apz0 = apz1 - rue/rr - anz0 - asz0
  if (apz0.lt.0.) then
    IF (nwind.eq.0) then
      CALL GRAFTB(2,2,410,230,670,246)
      CALL GRAFTB(14,30,70)
    ENDIF
    write(*,*) '(4) negative influence coef.!',i,j
  endif
  zeta(i,j) = (apz0*zold(2,j)+aez0*zold(3,j)
    *          + asz0*zold(2,j-1)+anz0*zold(2,j+1)
    *          + bz(2,j))/apz1
c    write(*,284)2,j,aez0,awz0,anz0,asz0,
c    *          apz1,bz(2,j)
c 284    format('ewnsqb',2i3,6f12.5)
c
c    vorticity away from tank center
c
240    continue
do 270 i = 3,mwl
  if (ncoord.eq.0) then
    rr = rad(i)
    rrdr2p = rr + delr2
    rrdm = rr - delr2
    rrdrp = rr + delr
    rrdm = rr - delr
  else
    rr = 1.
    rrdr2p = 1.
    rrdm = 1.
    rrdrp = 1.
    rrdm = 1.
  endif
  do 260 j = 2,nhl
    ue = 0.25*(u(i,j)+u(i+1,j)+u(i,j-1)+u(i+1,j-1))
    uw = 0.25*(u(i,j)+u(i-1,j)+u(i,j-1)+u(i-1,j-1))
    vn = 0.25*(v(i,j)+v(i,j+1)+v(i-1,j)+v(i-1,j+1))
    vs = 0.25*(v(i,j)+v(i,j-1)+v(i-1,j)+v(i-1,j-1))
    rue = amax1(zero, -rrdr2p*ue/delr)
    ruw = amax1(zero, rrdm*uw/delr)
    aez0 = rue/rrdrp
    awz0 = ruw/rrdm
    anz0 = amax1(zero, -vn/delz)
    asz0 = amax1(zero, vs/delz)
    apz1 = 1./delt
    apz0 = apz1 - (rue + ruw)/rr - anz0 - asz0
    if (apz0.lt.0.) then
      IF (nwind.eq.0) then
        CALL GRAFTB(2,2,410,230,670,246)
        CALL GRAFTB(14,30,70)
      ENDIF
    endif
  enddo
enddo

```

```

        write(*,*) '(5) negative influence coef.',i,j
    endif
    zeta(i,j) = (apz0*zold(i,j)+aez0*zold(i+1,j)+awz0*zold(i-1,j)
    + asz0*zold(i,j-1)+anz0*zold(i,j+1)
    + bz(i,j)
    + gspar(i,j)*(Qin/Qinx)*(Qin/Qinx))/apz1
c      write(*,274) i,j,aez0,awz0,anz0,asz0,
c      *      apz1, bz(i,j), gspar(i,j)
c 274      format('ewnsbg',2i3,7f12.5)
c 260      continue
c 270      continue
c
c      solve Poisson equation for new velocity distribution
c
c      set flow rate to coast-down value (mcoast=1) or keep constant (mcoast=0)
c
    if (mcoast.eq.1) then
        ttt = time + delt/2.
        if (ttt.gt.coast(1,ncoast+1)) ncoast = min(ncoast+1,nodat-1)
        Qin = Qinx*0.01*(coast(2,ncoast) +
    *      (coast(2,ncoast+1)-coast(2,ncoast))*
    *      (ttt - coast(1,ncoast))/
    *      (coast(1,ncoast+1) - coast(1,ncoast)))
    else
        Qin = Qinx
    endif
    vbot = (1.-topflo)*Qin/Atank
    vtop = topflo*Qin/Atop
c
c      set Poisson equation boundary condition across bottom of the tank,
c      adjusting inlet velocity vbot by factor cvel(i) to adjust for nonuniform
c      velocity distribution
c
    do 300 j = 1,nhigh
        psi(1,j) = - vtop/dR2(1)
    300      continue
    do 305 i = 2,mwide
        psi(i,1) = psi(i-1,1) - cvel(i-1)*vbot/dR2(i-1)
    305      continue
c
c      iterate Poisson until converged solution is obtained
c
    do 320 i = 2,mwide-1
        do 310 j = 2,nhigh-1
            bp(i,j) = delr*delz*(zeta(i,j) + zgrav(i,j))
        310      continue
    320      continue
    do 350 iloop1 = 1,100
        err = 0.
        do 340 i = 2,mwide-1
            aee = aepl(i)
            aww = awpl(i)
            ans = anspl(i)
            app = appl(i)
            do 330 j = 2,nhigh-1
                psinew = (aee*psi(i+1,j) + aww*psi(i-1,j)
    *      + ans*(psi(i,j-1) + psi(i,j+1))
    *      + bp(i,j))/app
                err = amax1(abs(psinew-psi(i,j)),err)
                psi(i,j) = relax*psinew + relax1*psi(i,j)
c      WRITE(*,*) 'PSI,i,j,bp',PSInew,i,j,bp(1,j)
    330      continue
    340      continue
            if (errmax.gt.err) go to 360
    350      continue
        write(*,*) 'convergence problem for Poisson eqn.'
    360      continue
        IF (nwind.eq.0) then
            CALL GRAFTB(2,2,410,230,670,246)
            CALL GRAFTB(14,410,240)
            WRITE(*,361) time,iloop1
    361      FORMAT(f5.1,'s, PRES',i3)

```

Version 2.1	Rev. 0	CODE REQUIREMENTS DOCUMENT	03/11/92
-------------	--------	----------------------------	----------

```

ENDIF
c
c calculate new velocity components
c
velmax = 0.
do 380 i = 2,mwide
  dzrr = delz*rad(i)
  do 370 j = 1,nhigh-1
    u(i,j) = (psi(i,j+1) - psi(i,j))/dzrr
    velmax = max(velmax,abs(u(i,j)))
  370 continue
  380 continue
  do 400 j = 1,nhigh
    do 390 i = 1,mwide-1
      v(i,j) = (psi(i,j) - psi(i+1,j))*dr2(i)
      velmax = max(velmax,abs(v(i,j)))
    390 continue
    v(mwide,j) = v(mwide-1,j)
    v(0,j) = v(1,j)
    lstep = 0
  395 if (delt.gt.0.25*max(delr,delz)/velmax) then
    delt = delt/2.
    IF (nwind.eq.0) then
      CALL GRAFTB(2,2,410,230,670,246)
      CALL GRAFTB(14,30,60+lstep)
    ENDIF
    write(*,396)delt
    format('REDUCE TIME STEP SIZE',f7.5)
    IF (nwind.eq.0) CALL GRAFTB(14,40,75+lstep)
    write(*,397)velmax
    format('Maximum Velocity =',e8.2)
    lstep = lstep + 25
    ngo = -1
    go to 395
  endif
  400 continue
c
c write to screen
c
IF (NWND.NE.0) THEN
  write(*,*)'Poisson iterations =',iloop1,' at time ',time
  go to 420
  do 404 j = nhigh,1,-1
    write(*,406) (psi(i,j),i=1,mwide)
    406 format('psi',14f7.2)
    404 continue
  write(*,*)
  do 408 j = nhigh,1,-1
    write(*,407) (v(i,j)/void,i=1,mwide-1)
    407 format('v',14f7.3)
    408 continue
  write(*,*)
  do 412 j = nhigh-1,1,-1
    write(*,411) (u(i,j)/void,i=1,mwide)
    411 format('u',14f7.3)
    412 continue
  write(*,*)
  do 414 j = nhigh,1,-1
    write(*,413) (zeta(i,j),i=1,mw1)
    413 format('zeta',14f7.3)
    414 continue
  420 continue
ENDIF
c
c add new ink packets
c
if (time.le.tink) go to 500
jjink = jjink+1
if (njet.gt.inkmax.or.jjink.lt.jink) go to 500
jjink = 0
if (tjet(njett+1).lt.time-tink) njett = min(njett+1,inkdat-1)
fac = (time - tink - tjet(njett))/(tjet(njett+1) - tjet(njett))

```

```

do 460 jet = 1, inkin
  sjet(njet+jet) = delt*(fjet(jet,njett)
  *      +fac*(fjet(jet,njett+1) - fjet(jet,njett)))
  rjet(njet+jet) = rjett(jet)
  hjet(njet+jet) = hjett(jet)
460  continue
njet = njet+inkin
c  IF (NWIND.NE.0) THEN
c    write(*,465) (sjet(l),l=njet*inkin+1,njet*inkin+inkin)
c 465  format('new sjet',7f7.4)
c    write(*,467) (hjet(l),l=njet*inkin+1,njet*inkin+inkin)
c 467  format('new hjet',7f7.4)
c  ENDIF
500  continue
c
c  reset temperature
c
do 450 i = 1,mwide
  do 445 j = 1,nhigh
    told(i,j) = t(i,j)
445  continue
450  continue
c
c  reset vorticity, dump some vorticity from interface to the finite
c  difference solution.
c
do 440 i = 2,mwide-1
  do 430 j = 2,nhigh-1
    zold(i,j) = zeta(i,j) + (1.-vorfac)*zgrav(i,j)
430  continue
440  continue
c
c  reset cold water heights, modify the vorticity at the interface
c  using vorfac
c
ucmax = 0
do 550 l = 1,50
  Rcold(l) = Rc(l)
  Hcold(l) = Hc(l)
  Ucold(l) = Uc(l)*vorfac
  ucmax = max(ucmax,Uc(l))
550  continue
800  continue
c
c  write output to file 'modflow.out'
c
write(4,805)time
805  format('* ##### TIME = ',f7.2,
  *      ' sec #####')
write(4,810)time,Qin
810  format(f10.2,e10.3)
write(4,812) void
812  format('average radial velocity',
  *      '-divide by void fraction ',f5.3,' for local velocity-')
do 820 j = nh1,1,-1
  write(4,815) (u(i,j),i=1,mw)
815  format(15f8.4)
820  continue
write(4,822) void
822  format('average vertical velocity',
  *      '-divide by void fraction ',f5.3,' for local velocity-')
do 830 j = nh,1,-1
  write(4,825) (v(i,j),i=1,mw1)
825  format(15f8.4)
830  continue
write(4,*)'cold interface location'
IF (NSOLVE.LE.1) THEN
  IC=5
ELSE
  IC=1+(3*MWIDE)/10
ENDIF
do 840 l = 1,IC

```

```

      k1 = (l-1)*10
      write(4,835) (Hc(i),i=k1+1,k1+10)
      write(4,835) (Rc(i),i=k1+1,k1+10)
835      format(10f8.3)
840      continue
      write(4,*) 'ink packet locations/sizes (iout=1 - ink exited)'
      write(4,*) njet,vout
      do 850 l = 1,njet+6,7
        write(4,845) (hjet(i),i=1,l+6)
        write(4,845) (rjet(i),i=1,l+6)
        write(4,845) (sjet(i),i=1,l+6)
845      format(7f8.3)
850      continue
890      continue
      IF (NWIND.NE.0) THEN
        do 187 j = nhigh,1,-1
          write(*,185) (t(i,j),i=1,mwide)
185          format('t',18f6.2)
187          continue
          write(*,*)
        endif
1000      continue
      end

```

CLDFRT.F

```

c
c      CLDFRT.F  Version 2.1   P.F. PETERSON   U.C. BERKELEY   11/4/90
c
c      program to move cold front interface points and calculate new
c      vorticity contribution
c
      subroutine cldfrt(mwide,nhigh,delz,delr,delt,Rtank,
*          Htank,grav,BdF,void,nsolve,ncoord)
      parameter (nmax = 41,mmax = 81,inkmax=981)
      dimension u(0:nmax,mmax),v(0:nmax,mmax),
*          zgrav(0:nmax,0:mmax),t(0:nmax,0:mmax),told(0:nmax,0:mmax),
*          Hc(0:125),Rc(0:125),Uc(0:125),
*          Hcnew(0:100),Rcnew(0:100),Ucnew(0:100),
*          Hcold(0:100),Rcold(0:100),Ucold(0:100),
*          dRR(0:100),dHH(0:100),dSS(0:100)
      common /vel/u,v
      common /grav/zgrav
      common /cold/Hc,Rc,Uc
      common /ccold/Hcold,Rcold,Ucold
      common /temper/t,told
c
c      move cold front interface points
c
      Stot = 0.
      Smax = 0.
      call move(Rcold(1),Hcold(1),Rcnew(1),Hcnew(1),
*          mwide,nhigh,delz,delr,delt,void,uu,vv)
      do 620 l = 2,50
        call move(Rcold(l),Hcold(l),Rcnew(l),Hcnew(l),
*          mwide,nhigh,delz,delr,delt,void,uu,vv)
        if (Hcnew(l).gt.Htank) Hcnew(l)=Htank
        dHH(l) = Hcnew(l) - Hcnew(l-1)
        dRR(l) = Rcnew(l) - Rcnew(l-1)
        dSS(l) = sqrt(dHH(l)*dHH(l) + dRR(l)*dRR(l))
        Stot = Stot + dSS(l)
        Ranew = Rcnew(l)+Rcnew(l-1)
        Raold = Rcold(l)+Rcold(l-1)
        if (ncoord.eq.1) Ranew=Raold
        Ucnew(l) = Ucold(l)*(Ranew/Raold)
*          - grav*BdF*delt*void*dHH(l)/dSS(l)
        if ((Rcnew(l).gt.Rtank).and.(Smax.eq.0.)) then
          Smax = Stot - dSS(l)
*          * (Rtank-Rcnew(l))/(Rcnew(l-1)-Rcnew(l))
        endif
620      continue
      if (Smax.lt.Rtank) Smax=Stot

```

```

        if (Hcnew(1).gt.0.99*Htank) Hcnew(2)=Htank
c
c      use linear interpolation to shift all interface points
c      backward, so that all interface points are inside the tank
c
      dS = Smax/49
      Strack = dS
      S = dSS(2)
      ll = 2
      Hc(1) = Hcnew(1)
      do 650 l = 2,50
640      continue
          if (S.lt.Strack) then
              ll = ll+1
              S = S + dSS(ll)
              if ( ll.le.50 ) go to 640
          endif
          frac = (S - Strack)/(dSS(ll))
          Hc(l) = Hcnew(ll-1)*frac + Hcnew(ll)*(1-frac)
          Rc(l) = Rcnew(ll-1)*frac + Rcnew(ll)*(1-frac)
          Uc(l) = Ucnew(ll-1)*frac + Ucnew(ll)*(1-frac)
          Strack = Strack + dS
650      continue
c
c      calculate increment in vorticity at each hot/cold front node location,
c      find hot/cold vorticity 2-D distribution, if nsolve=0
c
      if (nsolve.eq.0) then
          do 707 i = 1,mwide
              do 705 j = 1,nhigh
                  zgrav(i,j) = 0.
705          continue
707      continue
          do 720 l = 2,50
              Have = Hc(l-1) + 0.5*dHH(l)
              Rave = Rc(l-1) + 0.5*dRR(l)
              i = min(mwide-1,max(1,int(Rave/delr)+1))
              j = min(nhigh-1,max(1,int(Have/delz)+1))
              cr = (Rave/delr) - float(i-1)
              cz = (Have/delz) - float(j-1)
              zadd = Uc(l)*dS/(delr*delz)
              zgrav(i,j) = zgrav(i,j) + (1.-cr)*(1.-cz)*zadd
              zgrav(i+1,j) = zgrav(i+1,j) + cr*(1.-cz)*zadd
              zgrav(i,j+1) = zgrav(i,j+1) + (1.-cr)*cz*zadd
              zgrav(i+1,j+1) = zgrav(i+1,j+1) + cr*cz*zadd
720          continue
          endif
c
c      calculate 2-D temperature distribution if nsolve=1
c
c      reset temperature
c
      do 810 i = 1,mwide
          do 800 j = 1,nhigh
              t(i,j) = 0
800          continue
810      continue
      if (nsolve.eq.1) then
          do 890 l = 1,49
              Hleft = Hc(l)
              Rleft = Rc(l)
              ncross = 0
830          it = int((Rleft/delr) + 1.5)
              jt = int((Hleft/delz) + 1.5)
              it = min(mwide+1,max(0,it))
              jt = min(nhigh+1,max(0,jt))
c
c      determine if point (l+1) crosses a radial division
c
              if (Rc(l+1).gt.delr*(float(it)-0.5).and.ncross.ne.-1) then
                  ncross = 1
                  Right = (float(it) - 0.49999999)*delr

```

```

      Hright = Hleft + (Hc(l+1)-Hleft)
      *      * (Rleft-Rright) / (Rleft-Rc(l+1))
      go to 850
    else
      if (Rc(l+1).lt.delr*(float(it)-1.5)
      *      .and.ncross.ne.-1) then
        ncross = 1
        Rright = (float(it) - 1.500001)*delr
        Hright = Hleft + (Hc(l+1)-Hleft)
      *      * (Rleft-Rright) / (Rleft-Rc(l+1))
        go to 850
      else
        Rright = Rc(l+1)
      endif
    endif
  endif
c
c  determine if point (l+1) crosses a vertical division
c
  if (Hc(l+1).gt.delz*(float(jt)-0.5)
  *      .and.ncross.ne.-1) then
    ncross = 1
    Hright = (float(jt) - 0.49999999)*delz
    Rright = Rleft + (Rc(l+1)-Rleft)
  *      * (Hleft-Hright) / (Hleft-Hc(l+1))
    go to 850
  else
    if (Hc(l+1).lt.delz*(float(jt)-1.5)
    *      .and.ncross.ne.-1) then
      ncross = 1
      Hright = (float(jt) - 1.500001)*delz
      Rright = Rleft + (Rc(l+1)-Rleft)
    *      * (Hleft-Hright) / (Hleft-Hc(l+1))
      go to 850
    else
      Hright = Hc(l+1)
    endif
  endif
850  continue
c
c  add contribution to temperature of nodes under Hc
c
  ddR = (Rright-Rleft)/delr
  do 870 j = 1, jt
    t(it, j) = t(it, j) + ddR
870  continue
  Have = (Hleft+Hright)/2.
  t(it, jt) = t(it, jt) - ddR*(float(jt) - 0.5 - Have/delz)
  if (ncross.eq.1) then
    ncross = -1
    Hleft = Hright
    Rleft = Rright
    go to 830
  endif
890  continue
  do 900 j=1,nhigh
    t(1, j) = t(1, j)*2.
    t(mwide, j) = t(mwide, j)*2.
900  continue
  endif
  return
end

```

FRIC.f

```

c
c  FRIC.F      P.F. Peterson   Version 2.1   U.C. Berkeley   11/4/90
c
c  this subroutine calculates radial and vertical friction
c  coefficients for flow in SRS reactor tank moderator spaces.
c
c  radial form loss coefficient comes from a curve fit of A. Zukauskas,

```



```

c      Heat Transfer from Tubes in Cross Flow, Advances in Heat Transfer,
c      (ed. J.P. Hartnett and T.F. Irvine), Vol 8, pg 155, 1972.
c
c      u - average radial velocity (ft/s)
c      v - average vertical velocity (ft/s)
c      Dfuel - fuel element diameter (in)
c      Sf - fuel element pitch (in)
c      temp - fluid temperature (C)
c      ArR = tubes*void*Arstar*Arstar/(2.*Rtank*delz)
c      voidDh = 2.*void*Dhydr*delr
c      xfr - constant radial friction factor (typically 0.3)
c      xfv - constant vertical friction factor (typically 0.02)
c      nfric - 0 = use simple constant friction factor to speed calculation
c              1 = use full calculation for friction factor
c      ncoord - 0 = use triangular array (SRP tank)
c              - 1 = use square array (experiment)
c
c      subroutine fric (u1,v1,uK1,vK1,u2,v2,uK2,vK2,
*      Sfuel,Dfuel,void,Dhydr,ArR,voidDh,temp,nfric,xfr,xfv,ncoord)
c      if (nfric.eq.3) then
c          vK1 = xfv*v1*abs(v1)/voidDh
c          uK1 = xfr*u1*abs(u1)*ArR
c          vK2 = xfv*v2*abs(v2)/voidDh
c          uK2 = xfr*u2*abs(u2)*ArR
c      else
c          calculate viscosity and density of water at temperature 'temp'
c          visc = 1.019e-3 - 7.36e-6*temp
c          rho = 66.34 - 0.0386*temp
c          change properties to metric units if doing rectangular problem
c          if (ncoord.eq.1) then
c              visc = visc/0.672
c              rho = rho/0.06243
c          endif
c          ten = 10.
c          forty = 40.
c          First set of velocities and friction factors
c          va = abs(v1)/void
c          Rev = (rho*va*Dhydr/visc)
c          if (Rev.gt.30000) then
c              fv = 0.184*Rev**(-0.2)
c          else
c              fv = 0.316*Rev**(-0.25)
c          endif
c          vK1 = fv*v1*va/voidDh
c          ua = abs(u1)*Sfuel/(Sfuel-Dfuel)
c          Rer = (rho*ua*Dfuel/(12.*visc))
c          if (ncoord.eq.0) then
c              if (Rer.gt.2.0e5) then
c                  fr = 0.18
c              else
c                  if (Rer.gt.6000) then
c                      fr = 4.233*Rer**(-0.268)
c                  else
c                      xlnRe = log(max(ten,Rer))
c                      fr = exp(4.028-1.118*xlnRe+0.0635*xlnRe**2)
c                  endif
c              endif
c          else
c              Rer = (rho*ua*(Sfuel-Dfuel)/(visc))
c              xlnRe = log(max(forty,Rer))
c              fr = max(0.4,4.83 - 0.69*xlnRe)
c          endif
c          uK1 = fr*u1*ua*ArR
c          IF (nwind.eq.0) then
c              CALL GRAFTB(2,2,310,300,520,316)
c              CALL GRAFTB(14,310,312)
c              WRITE(*,191) Rer,fr,ua*100
c 191      FORMAT('Re,fr,ua',f6.1,f6.3,f6.2)
c          ENDIF
c          Second set
c          va = abs(v2)/void
c          Rev = (rho*va*Dhydr/visc)

```

```

      if (Rev.gt.30000) then
        fv = 0.184*Rev**(-0.2)
      else
        fv = 0.316*Rev**(-0.25)
      endif
      vk2 = fv*v2*va/voidDh
      ua = abs(u2)*Sfuel/(Sfuel-Dfuel)
      Rer = (rho*ua*Dfuel/(12.*visc))
      if (ncoord.eq.0) then
        if (Rer.gt.2.0e5) then
          fr = 0.18
        else
          if (Rer.gt.6000) then
            fr = 4.233*Rer**(-0.268)
          else
            xlnRe = log(max(ten,Rer))
            fr = exp(4.028-1.118*xlnRe+0.0645*xlnRe**2)
          endif
        endif
      else
        Rer = (rho*ua*(Sfuel-Dfuel)/(visc))
        xlnRe = log(max(forty,Rer))
        fr = max(0.4,4.83 - 0.69*xlnRe)
      endif
      uk2 = fr*u2*ua*ArR
    endif
  return
end

```

HELLO.F

```

C
C      HELLO.F Version 2.1 P.F. PETERSON   U.C. BERKELEY   11/4/90
C
C      SUBROUTINE TO PRINT OUT INTRODUCTORY WINDOW
C
C      SUBROUTINE HELLO
CINCLUDE:HLTBI.COM
      INTEGER*2 WNDNUM, ILEFT, ITOP, IRIGHT, IBOTOM, WNDTYP, DLG, NELE, TITLN
      INTEGER*2 ITNUM, TYPE, STATE, XMOVE, YMOVE, CHSIZE, CORDVL, PPNT
      INTEGER*2 STATUS, FN
      ICOLOR=33
      IRED = 205
      IBLUE = 409
      ICYAN = 273
      WNDNUM=3
      NELE=0
      CALL WINDTB(INITWND)
      CALL WINDTB(NEWWIND, WNDNUM, 10, 20, 530, 280, 3, 2, NELE, 0)
      CALL WINDTB(WNDOUT, WNDNUM)
      CALL GRAFTB(MOVETO, 160, 50)
      WRITE(*, 30)
      CALL GRAFTB(MOVETO, 160, 70)
      WRITE(*, 40)
      CALL GRAFTB(MOVETO, 105, 100)
      WRITE(*, 50)
      CALL GRAFTB(MOVETO, 100, 120)
      WRITE(*, 60)
      CALL GRAFTB(MOVETO, 130, 140)
      WRITE(*, 70)
      CALL GRAFTB(MOVETO, 100, 160)
      WRITE(*, 80)
      CALL GRAFTB(MOVETO, 120, 200)
      WRITE(*, 90)
30    FORMAT('SRS MODERATOR FLOW PATTERN')
40    FORMAT('*****SRL-SAG 11/4/91*****')
50    FORMAT('MODFLOW 2.1 - MODELING OF SRS MODERATOR FLOW')
60    FORMAT('This program models the moderator flow and ink')
70    FORMAT('distribution in SRS reactor tanks')
80    FORMAT('*****')
90    FORMAT('by P.F. Peterson, U.C. Berkeley   11/4/91')
      RETURN

```

END

INIT.f

```

c
c      INIT.F Version 2.1 P.F. PETERSON      U.C. BERKELEY      11/4/90
c
c      Program to input initial values of stream function and vorticity
c      fields
c
      subroutine init(mwide,nhigh,Qin,initfl)
      parameter (nmax = 41,mmax = 81,inkmax=981)
      character*80 words
      character*12 initfl
      dimension u(0:nmax,mmax),v(0:nmax,mmax),
*      psi(0:nmax,mmax),zeta(0:nmax,0:mmax),zold(0:nmax,0:mmax)
      common /vel/u,v
      common /flow/psi,zeta,zold
      open (2,file=initfl)
      read(2,'(A\)' ) words
      read(2,'(A\)' ) words
      read(2,*) mw, nh
      if ((mw.ne.mwide).or.(nh.ne.nhigh)) then
        write(*,*) 'wrong grid size in file ',initfl
        stop
      endif
30    format(2i6)
      read(2,'(A\)' ) words
      read(2,*) Q
      if ((Q.gt.1.2*Qin).or.(Q.lt.0.8*Qin)) then
        write(*,*) 'wrong flow rate in file ',initfl
        stop
      endif
      read(2,'(A\)' ) words
      do 90 j = nhigh,1,-1
        read(2,*) (psi(i,j),i=1,mwide)
90    continue
      read(2,'(A\)' ) words
100   format(a80)
      do 120 j = nhigh,1,-1
        read(2,*) (zeta(i,j),i=1,mwide)
120   continue
      do 140 j = 1,nhigh
        do 130 i = 1,mwide
          zold(i,j) = zeta(i,j)
130   continue
140   continue
      close(2)
      return
      end

```

MOVE.f

```

c
c      MOVE.F Version 2.1 P.F. PETERSON      U.C. BERKELEY      11/4/90
c
c      Program to move a particle, given the velocity field u,v and
c      the time step delt
c
      subroutine move(rin,zin,rout,zout,
*      mwide,nhigh,deltz,delr,delt,void,vr,vv)
      parameter (nmax = 41,mmax = 81,inkmax=981)
      dimension u(0:nmax,mmax),v(0:nmax,mmax)
      common /vel/u,v
c
c      calculate average radial velocity vr using linear interpolation
c      j is corrected to prevent overshoot and undershoot
c
      i = int((rin/delr) + 1)
      i = max(1, min(i,mwide))

```

```

      crr = (rin/delr) - float(i-1)
      j = int((zin/delz) + 0.5)
      j = max(1, min(j,nhigh-2))
      czr = (zin/delz) - (float(j)-0.5)
      vr = (u(i,j)*(1-crr) + u(i+1,j)*crr)*(1.-czr)
      *      + (u(i,j+1)*(1-crr) + u(i+1,j+1)*crr)*czr
c
c      calculate average vertical velocity vv using linear interpolation
c      i is corrected to prevent overshoot and undershoot
c
      i = int((rin/delr) + 0.5)
      i = max(1, min(i,mwide))
      crz = (rin/delr) - (float(i)-0.5)
      j = int((zin/delz) + 1)
      czz = (zin/delz) - float(j-1)
      vv = (v(i,j)*(1-czz) + v(i,j+1)*czz)*(1.-crz)
      *      + (v(i+1,j)*(1-czz) + v(i+1,j+1)*czz)*crz
      if (rin.lt.delr/2.) vv = (v(1,j)*(1-czz) + v(1,j+1)*czz)
c
c      calculate new radial and axial positions rout and zout
c
      rout = rin + vr*delt/void
      zout = zin + vv*delt/void
      return
      end

```

READIN.f

```

c
c      READIN.F Version 2.1   P.F. PETERSON   U.C. BERKELEY   11/4/90
c
c      this subroutine reads in input data from input deck 'modflow.in'
c      and writes numerical information to scratch file 'scratch',
c      sets up input/output devices
c
      subroutine readin(nline,filein,filout)
      character*1 it(20)
      character*8 title1(20,20)
      character*12 filein,filout

      open (7,file=filein)
      open (3,status='scratch')
      open (4,file=filout)

      write (4,100)
100  format ('* ===== LISTING OF INPUT CARDS =====')
      nloop = 0
105  k=1
110  read (7,120,end=125) it(k), (title1(i,k),i=1,20)
120  format (a1,20a8)
c
c      & means end of file
c
      if (it(k).eq.'&') go to 125
      k=k+1
      if (k.lt.21) go to 110
125  nloop = nloop + 1
      kk = min(20,k)
      do 140 kkk=1,kk
         kloop = (nloop-1)*20 + kkk
         write (4,120) it(kkk), (title1(i,kkk),i=1,20)
c         write (4,130) kloop,it(kkk), (title1(i,kkk),i=1,20)
130  format (1x,i4='a1,20a8)
140  continue
      do 160 kkk=1,kk
         if (it(kkk).ne.'*'.and.it(kkk).ne.'&')
            *      write(3,120) it(kkk), (title1(i,kkk),i=1,20)
160  continue
      if (k.eq.21) go to 105

```

Version 2.1	Rev. 0	CODE REQUIREMENTS DOCUMENT	03/11/92
-------------	--------	----------------------------	----------

```

nline = (nloop-1)*20 + kk
rewind (3)
write (4,170)
170 format ('& ##### END OF INPUT INFORMATION #####')
return
end

```

VPLOT.f

```

C
C      VPLOT.F Verison 2.1 P.F. PETERSON   U.C. BERKELEY   11/4/90
C
C      SUBROUTINE TO PLOT VELOCITY VECTORS
C
C      SUBROUTINE VPLOT (MWIDTH, NHIGH, VMAX, TIME, DELT, QIN, QINX, Bdt,
*      ARSTAR, VOID, MCOAST, MCOLD, TINK, NSTART, VEXT, VOUT, VSCALE,
*      NFRIC, NREC, METHOD, NFIRST, NCOORD, RTANK, HTANK, INKIN,
*      NGO, UCMAX, DELR)
$INCLUDE:HLTBI.CON
      parameter (nmax = 41, mmax = 81, inkmax=981)
      dimension u(0:nmax, mmax), v(0:nmax, mmax),
               Hc(0:125), Rc(0:125), Vc(0:125),
               hjet(inkmax), rjet(inkmax), sjet(inkmax)
      common /vel/ u, v
      common /cold/ Hc, Rc, Vc
      common /ink/ hjet, rjet, sjet, njet
      INTEGER*2 WNDNUM, ILEFT, ITOP, IRIGHT, IBOTOM, WNDTYP, DLG, NELE, TITLN
      INTEGER*2 ITMNUM, TYPE, STATE, XMOVE, YMOVE, CHSIZE, CORDVL, PPNT
      INTEGER*2 STATUS, FN
      ICOLOR=33
      IRED = 205
      IBLUE = 409
      ICYAN = 273
      WNDNUM=3
      NELE=15
      IF (NFIRST.EQ.0) THEN
        CALL WINDTB(WNDCLD, WNDNUM)
        CALL WINDTB(INITWND)
        CALL WINDTB(NEWWIND, WNDNUM, 10, 20, 530, 360, 3, 2, NELE, 0)
        CALL WINDTB(WNDOUT, WNDNUM)
      ENDIF
      JPUT = 80
      JUMP = 0
60    CALL GRAFTB(2, 2, 2, 2, 229, 379)
      CALL GRAFTB(2, 2, 229, 225, 369, 379)
      CALL GRAFTB(2, 2, 369, 225, 529, 259)
      IF (NCOORD.EQ.0) THEN
        CALL GRAFTB(MOVETO, 30, 10)
        WRITE(*, 70)
70      FORMAT('SRS MODERATOR FLOW VER. 2.1')
        CALL GRAFTB(MOVETO, 12, 25)
        WRITE(*, 75)
75      FORMAT('*****SRL-SAG 11/4/91*****')
      ELSE
        CALL GRAFTB(MOVETO, 30, 10)
        WRITE(*, 80)
80      FORMAT('FLOW IN A RECTANGULAR TANK')
        CALL GRAFTB(MOVETO, 12, 25)
        WRITE(*, 85)
85      FORMAT('BANK - 11/4/91 - MODFLOW 2.1')
      ENDIF
C      Draw box
      JDEL = INT(160*HTANK/RTANK)/(NHIGH-1)
      JINT = 340 - JDEL/2
      IDEL = 160/(MWIDTH-1)
      IINT = 50 + IDEL/2
      IWIDE = IDEL*(MWIDTH-1)
      JHIGH = JDEL*(NHIGH-1)
      CALL GRAFTB(LINE, 1, 50, 340, 1, 65+IWIDE, 340, ICOLOR)
      CALL GRAFTB(LINE, 1, 50+IWIDE, 330, 1, 50+IWIDE, 340-JHIGH, ICOLOR)
      CALL GRAFTB(LINE, 1, 50+IWIDE, 330, 1, 65+IWIDE, 330, ICOLOR)
      CALL GRAFTB(LINE, 1, 50+IWIDE, 340-JHIGH, 1, 50, 340-JHIGH, ICOLOR)

```

```

      ITICK = 50
      DO 87 I=3,MWIDE
        ITICK = ITICK+IDEL
        CALL GRAFTB(LINE,1,ITICK,340-JHIGH,1,ITICK,342-JHIGH,ICOLOR)
        CALL GRAFTB(LINE,1,ITICK,338,1,ITICK,340,ICOLOR)
87      CONTINUE
      JTICK = 340
      DO 89 J=3,NHIGH
        JTICK = JTICK-JDEL
        CALL GRAFTB(LINE,1,50,JTICK,1,52,JTICK,ICOLOR)
        CALL GRAFTB(LINE,1,48+IWIDE,JTICK,1,50+IWIDE,JTICK,ICOLOR)
89      CONTINUE
      CALL GRAFTB(MOVETO,235,240)
      IF (NCCORD.EQ.0) THEN
        WRITE(*,90)
90      FORMAT('SCALE: 2.0ft/sec')
        IVEC = IDEL*(2*VSCALE/VMAX)
        CALL GRAFTB(LINE,1,50,335-JHIGH,1,50,175,ICOLOR)
        CALL GRAFTB(LINE,1,50,185,1,50,195,ICOLOR)
        CALL GRAFTB(LINE,1,50,205,1,50,345,ICOLOR)
      ELSE
        WRITE(*,100)
100     FORMAT('SCALE: 5.0cm/sec')
        IVEC = IDEL*(0.05*VSCALE/VMAX)
        CALL GRAFTB(LINE,1,50,340-JHIGH,1,50,340,ICOLOR)
      ENDIF
      CALL GRAFTB(LINE,1,250,250,1,250+IVEC,250,1RED)
      CALL GRAFTB(LINE,1,250+IVEC,248,1,250+IVEC,252,1RED)
      CALL GRAFTB(LINE,1,250,248,1,250,252,1RED)
c      Draw velocity vectors
      DO 210 I = 1,MWIDE-1
        JJINT = JINT
        DO 200 J = 1,NHIGH-1
          IVEC = IDEL*(U(I,J)*VSCALE/(VMAX*VOID))
          JVEC = IDEL*(V(I,J)*VSCALE/(VMAX*VOID))
          CALL GRAFTB(LINE,1,IINT,JJINT,1,IINT+IVEC,
*              JJINT-JVEC,1RED)
          JJINT = JJINT - JDEL
200      CONTINUE
        IINT = IINT + IDEL
210      CONTINUE
c      Add in ink
      SNQM = SJET(1)
      ICOME = 0
      DO 250 L = 1,NJET
        IJET = 50 + IWIDE*(RJET(L)/Rtank)
        JJET = 340 - JHIGH*(HJET(L)/Htank)
        LJET = 6*((SJET(L)/SNQM)**0.333) + 1
        CALL GRAFTB(OVAL,1,IJET,JJET,IJET+LJET,JJET+LJET)
250      CONTINUE
      IF (VOUT.GT.0.AND.NCCORD.EQ.0) THEN
        LLL = 100*(VOUT/VEXT)
        CALL GRAFTB(MOVETO,240,308)
        IF (LLL.LT.100) THEN
          WRITE(*,257)
          FORMAT('INK AT TANK EXIT')
257      ELSE
          LLL = 100
          WRITE(*,258)
          FORMAT('INK AT TANK PLENUM')
258      ENDIF
        CALL GRAFTB(LINE,1,250,315,1,350,315,ICOLOR)
        CALL GRAFTB(LINE,1,250,335,1,350,335,ICOLOR)
        CALL GRAFTB(LINE,1,350,315,1,350,335,ICOLOR)
        CALL GRAFTB(RECTAN,1,250,315,250+LLL,335)
      ENDIF
c      Draw interface between hot and cold liquids
260     IF (MCOLD.EQ.1) THEN
      IF (NSOLVE.LE.1) THEN
        IDO=49
      ELSE
        IDO=MWIDE*3

```

Version 2.1	Rev. 0	CODE REQUIREMENTS DOCUMENT	03/11/92
-------------	--------	----------------------------	----------

```

ENDIF
DO 270 L = 1, IDO
  IF (RC(L).GT.8) GOTO 270
  ICOLD1 = 50 + IWIDE*(RC(L)/RTANK)
  JCOLD1 = 340 - JHIGH*(HC(L)/HTANK)
  ICOLD2 = 50 + IWIDE*(RC(L+1)/RTANK)
  JCOLD2 = 340 - JHIGH*(HC(L+1)/HTANK)
  CALL GRAFTB(LINE, 1, ICOLD1, JCOLD1, 1, ICOLD2, JCOLD2, IBLUE)
270  CONTINUE
ENDIF
C  create control buttons
  IF (NFIRST.NE.0.OR.JUMP.EQ.1) GO TO 300
  CALL WINDTB(NEWITM, 1, WNDNUM, 1, 2, 2, 'GO',
* 230, 80, 360, 105)
  CALL WINDTB(NEWITM, 2, WNDNUM, 1, 2, 15, 'HALVE TIME STEP',
* 230, 110, 360, 135)
  CALL WINDTB(NEWITM, 3, WNDNUM, 1, 2, 16, 'DOUBLE TIME STEP',
* 230, 140, 360, 165)
  CALL WINDTB(NEWITM, 4, WNDNUM, 1, 2, 13, 'DECREASE FLOW',
* 230, 170, 360, 195)
  CALL WINDTB(NEWITM, 5, WNDNUM, 1, 2, 13, 'INCREASE FLOW',
* 230, 200, 360, 225)
  CALL WINDTB(NEWITM, 6, WNDNUM, 1, 2, 16, 'START COAST-DOWN',
* 380, 110, 510, 135)
  CALL WINDTB(NEWITM, 7, WNDNUM, 1, 2, 9, 'START INK',
* 380, 140, 510, 165)
  CALL WINDTB(NEWITM, 8, WNDNUM, 1, 2, 16, 'START COLD WATER',
* 380, 170, 510, 195)
  CALL WINDTB(NEWITM, 9, WNDNUM, 1, 2, 7, 'EXPLODE',
* 380, 200, 510, 225)
  CALL WINDTB(NEWITM, 10, WNDNUM, 1, 2, 4, 'QUIT',
* 380, 80, 510, 105)
  CALL WINDTB(NEWITM, 11, WNDNUM, 1, 2, 4, 'INFO',
* 455, 325, 495, 345)
  CALL WINDTB(NEWITM, 12, WNDNUM, 2, NFRIC, 17, 'CONSTANT FRICTION',
* 370, 260, 530, 275)
  CALL WINDTB(NEWITM, 13, WNDNUM, 1, 2, 5, 'PRINT',
* 450, 295, 500, 315)
  CALL WINDTB(NEWITM, 14, WNDNUM, 1, 2, 4, 'SAVE',
* 400, 325, 440, 345)
  CALL WINDTB(NEWITM, 15, WNDNUM, 1, 2, 6, 'CPAUSE',
* 400, 325, 440, 345)
300  CONTINUE
  CALL GRAFTB(2, 2, 249, 1, 600, 79)
  CALL GRAFTB(MOVETO, 250, 10)
  WRITE(*, 40) TIME
40  FORMAT('CURRENT TIME', F8.2, ' sec')
  CALL GRAFTB(MOVETO, 250, 25)
  WRITE(*, 50) DELT
50  FORMAT('TIME STEP SIZE', F8.3, ' sec')
  CALL GRAFTB(MOVETO, 250, 40)
  IF (NCOORD.EQ.0) THEN
    WRITE(*, 55) QIN*448.76
55  FORMAT('TOTAL FLOW RATE', F8.0, ' gpm')
  ELSE
    WRITE(*, 56) QIN*1.e6
56  FORMAT('TOTAL FLOW RATE', F8.1, ' cc/s')
  ENDIF
  IF (MCOAST.EQ.1) THEN
    CALL GRAFTB(MOVETO, 220, 270)
    WRITE(*, 301)
301  FORMAT('COAST DOWN STARTED')
  ENDIF
  IF (MCOLD.EQ.1) THEN
    CALL GRAFTB(MOVETO, 250, 55)
    WRITE(*, 302) Bdt*100.
302  FORMAT('COLD WATER IN, DENSITY =', F6.2, '%')
    CALL GRAFTB(MOVETO, 250, 70)
    IF (NCOORD.EQ.1) THEN
      UCMAX = ABS(UCMAX)
      IF (UCMAX.GT.0) Rimin = VOID*DELR*Bdt*(9.81)/(UCMAX**2)
      WRITE(*, 303) Hc(1)*100., Rimin

```

Version 2.1	Rev. 0	CODE REQUIREMENTS DOCUMENT	03/11/92
-------------	--------	----------------------------	----------

```

303      FORMAT(' Hc,max =',F6.2,'cm, Rmin=',F7.3)
      ENDIF
      ENDIF
C      check which button has been clicked
304      CALL WINDTB(GEVENT,0,IEVENT,INFO1,ITMNUM)
      IF (NGO.EQ.1.AND.IEVENT.NE.2) GO TO 310
      IF (NGO.EQ.-1) GO TO 305
      IF (IEVENT.NE.2) GO TO 304
      GOTO (305,320,330,340,350,360,370,380,390,400,410,420,430,
*         440,450,300) ITMNUM
305      IF (NGO.EQ.0) THEN
          NGO=1
          CALL WINDTB(RM/ITM,1,WNDNUM)
          CALL WINDTB(NEWITM,1,WNDNUM,1,2,5,'PAUSE',
*         230,80,360,105)
          DO 306 KK=2,14
              CALL WINDTB(SBSTAT,KK,WNDNUM,1)
306          CONTINUE
      ELSE
          NGO=0
          CALL WINDTB(RM/ITM,1,WNDNUM)
          CALL WINDTB(NEWITM,1,WNDNUM,1,2,2,'GO',
*         230,80,360,105)
          DO 307 KK=2,14
              CALL WINDTB(SBSTAT,KK,WNDNUM,2)
307          CONTINUE
          GO TO 304
      ENDIF
310      CALL GRAFTB(MOVETO,350,240)
      WRITE(*,*) 'RUNNING'
      GOTO 700
320      DELT = DELT/2.
      GOTO 300
330      DELT = DELT*2.
      GOTO 300
340      QIN = 0.8*QIN
      QINX = 0.8*QINX
      DELT = AMIN1(DELT,0.5)
      GOTO 300
350      QIN = QIN/0.8
      QINX = QINX/0.8
      DELT = AMIN1(DELT,0.5)
      GOTO 300
360      IF (NSTART.EQ.0) THEN
          NSTART = 1
          TIME = 0
          CALL GRAFTB(MOVETO,80,JPUT)
          WRITE(*,364)
364          FORMAT('RESET TIME')
          JPUT = JPUT + 12
          DELT = 0.5
      ENDIF
      MDOAST = 1
      GOTO 300
370      IF (NSTART.EQ.0) THEN
          NSTART = 1
          TIME = 0
          CALL GRAFTB(MOVETO,80,JPUT)
          WRITE(*,374)
374          FORMAT('RESET TIME')
          JPUT = JPUT + 12
      ENDIF
      IF (NJET.LT.1) THEN
          TINK = TIME
          DELT = AMIN1(DELT,0.5)
          CALL GRAFTB(MOVETO,60,JPUT)
          WRITE(*,376)
376          FORMAT('INK FLOWS, RESET DELT')
          JPUT = JPUT + 12
      ENDIF
      GOTO 300
380      IF (NSTART.EQ.0) THEN

```



```

      NSTART = 1
      TIME = 0
      CALL GRAFTB(MOVETO,80,JPUT)
      WRITE(*,384)
384      FORMAT('RESET TIME')
      JPUT = JPUT + 12
      ENDF
      IF (MCOLD.LT.1) THEN
        DELT = AMIN1(DELT,0.5)
        CALL GRAFTB(MOVETO,60,JPUT)
        WRITE(*,386)
386      FORMAT('COLD IN, RESET DELT')
        JPUT = JPUT + 12
      ENDF
      MCOLD = 1
      GOTO 300
390      VMAX = 0.5*VMAX
      JUMP = 1
      GO TO 60
400      CALL WINDTB(WNDCLO, WNDNUM)
      STOP
C      Switch between constant and variable friction factors
420      CALL WINDTB(BSTAT,12,WNDNUM,STATUS)
      IF (NFRIC.EQ.3) THEN
        NFRIC = 2
        CALL WINDTB(SBSTAT,12,WNDNUM,2)
        CALL GRAFTB(MOVETO,60,JPUT)
        WRITE(*,422)
422      FORMAT('USE EXACT FRICTION')
        JPUT = JPUT + 12
      ELSE
        NFRIC = 3
        CALL WINDTB(SBSTAT,12,WNDNUM,3)
        CALL GRAFTB(MOVETO,60,JPUT)
        WRITE(*,424)
424      FORMAT('USE CONSTANT FRICTION')
        JPUT = JPUT + 12
      ENDF
      GO TO 300
430      CALL GRAFTB(PRTSCR,1)
      CALL GRAFTB(MOVETO,60,JPUT)
      WRITE(*,434)
434      FORMAT('SENT TO PRINTER')
      JPUT = JPUT + 12
      GO TO 300
440      CALL SAVE(MWIDE,NHIGH,Qin)
      CALL WINDTB(WNDOUT,WNDNUM)
      GO TO 300
450      CALL GRAFTB(MOVETO,350,240)
      PAUSE
      GO TO 300
410      NELE=1
      CALL WINDTB(NEWWND,4,230,100,580,260,4,2,NELE,0)
      CALL GRAFTB(MOVETO,10,20)
      WRITE(*,530)
      CALL GRAFTB(MOVETO,10,45)
      WRITE(*,540)
      CALL GRAFTB(MOVETO,10,65)
      WRITE(*,550)
      CALL GRAFTB(MOVETO,10,90)
      WRITE(*,560)
      CALL GRAFTB(MOVETO,10,120)
      WRITE(*,570)
530      FORMAT('MODFLOW 2.0 - MODELING OF SRS MODERATOR FLOW')
540      FORMAT('This program models the moderator flow and ink')
550      FORMAT('distribution in SRS reactor tanks')
560      FORMAT('***** PRELIMINARY -- NO QA *****')
570      FORMAT('by P.F. Peterson, U.C. Berkeley 7/10/91')
      CALL WINDTB(NEWITM,1,4,1,2,2,'ok',295,126,323,145)
580      CALL WINDTB(DIALOG,4,ITMNUM)
      IF (ITMNUM.EQ.1) THEN
        CALL WINDTB(WNDCLO,4)

```

Version 2.1	Rev. 0	CODE REQUIREMENTS DOCUMENT	03/11/92
-------------	--------	----------------------------	----------

```

        CALL WINDTB(WNDOUT,WNDNUM)
        GO TO 300
    ELSE
        GO TO 580
    ENDIF
700    CONTINUE
        CALL GRAFTB(MOVETO,80,JPUT)
        RETURN
    END

```

Version 2.1	Rev. 0	CODE REQUIREMENTS DOCUMENT	03/11/92
-------------	--------	----------------------------	----------

APPENDIX B

MODFLOW 2.1 SAMPLE PROBLEM

1959 TEST COMPARISON (SEE FIG. 5.1)

INPUT DECK

```

* TEST CASE INPUT DATA DECK FOR MODFLOW.F
*
* Title for run (80 characters max)
Comparison with 1959 test run with 3.4" diameter fuel and sparjets operating
* 0 = use interactive Macintosh windows
* 1 = run batch mode
0
* Initial inlet flow rate, Qin (ft3/s)
307.513
* fraction of Qin which is introduced from the top, topflow
* (intended for rectangular experiment, use 0 here)
0
* Density difference between hot and cold water, BdT
0.009
* Time step (sec)
0.0125
* ##### solution technique #####
* 0 = Solve both temperature and buoyancy produced vorticity by
* with Lagrangian techniques
* 1 = Solve temperture with Lagrangian, vorticity with finite-
* difference techniques
* 2 = Solve both temperature and buoyancy with finite-difference
* techniques
1
* value between 1 and zero that determines whether vorticity is
* handled in a Lagrangian manner or finite-difference manner,
* respectively
1.0
* 0 = Solve in cylindrical coordinates
* 1 = Solve in rectangular coordinates (benchtop experiment)
0
* scale factor for velocity vectors (normally 1)
1.
* ##### initial condition guess #####
* 0 = use zero velocity initial condition
* 1 = read in initial condition from file
1
* filename in which initializing data is stored
init.59ws
* ##### for BATCH mode #####
* number of time steps between recording velocities, ect
* in output file 'modflow.out'
40
* number of time steps between ink injection packets
16
* 0 = no coast down
* 1 = run coast down starting at t=0
0
* Time at which ink is injected (sec)
1000
* Time at which cold water appears at bottom of tank (sec)
1000
* Maximum time to run calculation out to (sec)
45.
* #####
* Number of radial and vertical nodes
14 24
* convergence criteria for Poisson equation, ermax
0.001
* Moderator height, Hmint; tank radius, Rtank (ft)

```

```

15.33  8.11
*   Number of tube rows from tank center to tank wall, tubes
13
*   Fuel diameter, Dfuel; fuel pitch, Sfuel (inches)
3.4   7.0
*   Volume of external piping, ft3
3870
*   Average moderator temperature (for property calcs), temp (C)
60.35
* ##### FRICTION FACTORS #####
* 2 = Exact expression for friction (smaller time steps required)
* 3 = constant friction factor (faster operation, larger time steps)
2
* radial and vertical friction factors (constant f.f. case)
0.5   0.02
* ##### INLET FLOW RATE #####
* distribution of flow across bottom of tank (give number of radial
* nodes minus one values).
* can use the gpm per assembly value, program will normalize
* to give the correct total flow rate Qin
266   266   266   266   266   266   266
266   266   167   167   120   120
* ##### COASTDOWN CURVE #####
* number of data sets, nodat
1
*   Time (sec), Fraction of full A.C. flow
0     100
* ##### INK INJECTION RATES #####
* number of ink injection ports, inkin (7 maximum)
7
* number of data sets, inkdat
1
*   jet radii from tank center, rjett (ft)
2.50  2.50  2.50  2.50  2.50  2.50  2.50
*   jet elevations from tank bottom, hjett (ft)
2.28  3.363  4.363  5.447  6.447  8.030  9.197
*   time (sec), flow rate at each jet (gal/sec)
0     0.099  0.092  0.093  0.088  0.091  0.085  0.081
*
* ##### BOTTOM TEMPERATURE HISTORY #####
* number of data sets, ntemp (use only with finite difference solution)
*21
*   Time (sec), Fraction of full temperature difference
* 0     1.00
*
* ##### SPARJET INJECTION INFORMATION #####
* Number of spar jet injection ports (0 - do not use spar jets)
6
* Effective spar jet mixing volume
* vertical dimension and radial dimensions of volume, ft
3.5   4.0
* Information on each sparjet opening:
*   radial    vertical    nominal    outlet    angle
*   position  position    volume    area      from
*           flow rate    ft2       vertical
*           ft3/s
*   ft        ft        ft3/s      ft2       degrees
2.50         2.0        1.058      0.0138    45
2.50         3.0        1.058      0.0138    45
2.50         4.0        1.058      0.0138    45
2.50         5.0        1.058      0.0138    45
2.50         6.0        1.058      0.0138    45
2.50         7.0        1.058      0.0138    45

```

OUTPUT DECK

```

* ===== LISTING OF INPUT CARDS =====
*   TEST CASE INPUT DATA DECK FOR MODFLOW.F
*
*   Title for run (80 characters max)
Comparison with 1959 test run with 3.4" diameter fuel and sparjets operating

```

Version 2.1	Rev. 0	CODE REQUIREMENTS DOCUMENT	03/11/92
-------------	--------	----------------------------	----------

```

* 0 = use interactive Macintosh windows
* 1 = run batch mode
0
* Initial inlet flow rate, Qin (ft3/s)
307.513
* fraction of Qin which is introduced from the top, topflow
* (intended for rectangular experiment, use 0 here)
0
* Density difference between hot and cold water, BdT
0.009
* Time step (sec)
0.0125
* ##### solution technique #####
* 0 = Solve both temperature and buoyancy produced vorticity by
* with Lagrangian techniques
* 1 = Solve temperature with Lagrangian, vorticity with finite-
* difference techniques
* 2 = Solve both temperature and buoyancy with finite-difference
* techniques
1
* value between 1 and zero that determines whether vorticity is
* handled in a Lagrangian manner or finite-difference manner,
* respectively
1.0
* 0 = Solve in cylindrical coordinates
* 1 = Solve in rectangular coordinates (benchtop experiment)
0
* scale factor for velocity vectors (normally 1)
1.
* ##### initial condition guess #####
* 0 = use zero velocity initial condition
* 1 = read in initial condition from file
0
* filename in which initializing data is stored
init.59ws
* ##### for BATCH mode #####
* number of time steps between recording velocities, ect
* in output file 'modflow.out'
40
* number of time steps between ink injection packets
16
* 0 = no coast down
* 1 = run coast down starting at t=0
0
* Time at which ink is injected (sec)
1000
* Time at which cold water appears at bottom of tank (sec)
1000
* Maximum time to run calculation out to (sec)
45.
* #####
* Number of radial and vertical nodes
14 24
* convergence criteria for Poisson equation, ermax
0.001
* Moderator height, Hmint; tank radius, Rtank (ft)
15.33 8.11
* Number of tube rows from tank center to tank wall, tubes
13
* Fuel diameter, Dfuel; fuel pitch, Sfuel (inches)
3.4 7.0
* Volume of external piping, ft3
3870
* Average moderator temperature (for property calcs), temp (C)
60.35
* ##### FRICTION FACTORS #####
* 2 = Exact expression for friction (smaller time steps required)
* 3 = constant friction factor (faster operation, larger time steps)
2
* radial and vertical friction factors (constant f.f. case)
0.5 0.02
* ##### INLET FLOW RATE #####

```

```

* distribution of flow across bottom of tank (give number of radial
* nodes minus one values).
* can use the gpm per assembly value, program will normalize
* to give the correct total flow rate Qin
266      266      266      266      266      266
266      266      167      167      120      120
* ##### COASTDOWN CURVE #####
* number of data sets, nodat
1
* Time (sec), Fraction of full A.C. flow
0      100
##### INK INJECTION RATES #####
* number of ink injection ports, inkin (7 maximum)
7
* number of data sets, inkdat
1
* jet radii from tank center, rjett (ft)
      2.50      2.50      2.50      2.50      2.50      2.50
* jet elevations from tank bottom, hjett (ft)
      2.28      3.363      4.363      5.447      6.447      8.030      9.197
* time (sec), flow rate at each jet (gal/sec)
0      0.099      0.092      0.093      0.088      0.091      0.085      0.081
*
* ##### BOTTOM TEMPERATURE HISTORY #####
* number of data sets, ntemp (use only with finite difference solution)
*21
* Time (sec), Fraction of full temperature difference
* 0      1.00
*
* ##### SPARJET INJECTION INFORMATION #####
* Number of spar jet injection ports (0 - do not use spar jets)
6
* Effective spar jet mixing volume
* vertical dimension and radial dimensions of volume, ft
3.5      4.0
* Information on each sparjet opening:
* radial      vertical      nominal      outlet      angle
* position    position    volume      area          from
*            position    flow rate   ft2           vertical
*            ft          ft3/s       ft2           degrees
*
      2.50      2.0      1.058      0.0138      45
      2.50      3.0      1.058      0.0138      45
      2.50      4.0      1.058      0.0138      45
      2.50      5.0      1.058      0.0138      45
      2.50      6.0      1.058      0.0138      45
      2.50      7.0      1.058      0.0138      45
*
*
& ##### END OF INPUT INFORMATION #####
* ##### TIME = .50 sec #####
      .50      .308E+03
average radial velocity -divide by void fraction .786 for local velocity-
.0000      .0053      .0103      .0148      .0183      .0208      .0219      .0216      .0199      .0171      .0133      .0090      .0045
.0000
.0000      .0057      .0112      .0161      .0200      .0228      .0241      .0238      .0219      .0187      .0146      .0098      .0049
.0000
.0000      .0066      .0130      .0187      .0235      .0270      .0288      .0285      .0262      .0222      .0171      .0115      .0057
.0000
.0000      .0080      .0157      .0228      .0290      .0337      .0364      .0364      .0331      .0277      .0211      .0140      .0069
.0000
.0000      .0098      .0193      .0283      .0365      .0433      .0480      .0488      .0436      .0356      .0266      .0175      .0085
.0000
.0000      .0119      .0236      .0350      .0459      .0559      .0644      .0692      .0587      .0461      .0336      .0218      .0105
.0000
.0000      .0143      .0285      .0425      .0564      .0703      .0855      .1068      .0784      .0583      .0417      .0267      .0129
.0000
.0000      .0168      .0336      .0502      .0668      .0832      .0987      .1091      .0908      .0696      .0501      .0322      .0155
.0000
.0000      .0194      .0388      .0580      .0772      .0967      .1178      .1440      .1097      .0823      .0592      .0382      .0185
.0000

```

Version 2.1		Rev. 0		CODE REQUIREMENTS DOCUMENT						03/11/92		
.0000	.0221	.0442	.0658	.0871	.1082	.1303	.1567	.1227	.0942	.0689	.0450	.0219
.0000	.0251	.0499	.0740	.0970	.1184	.1375	.1497	.1314	.1065	.0804	.0534	.0263
.0000	.0285	.0566	.0835	.1085	.1315	.1527	.1763	.1502	.1239	.0958	.0650	.0323
.0000	.0326	.0646	.0949	.1226	.1465	.1650	.1751	.1675	.1469	.1178	.0817	.0412
.0000	.0377	.0747	.1096	.1413	.1678	.1870	.1964	.1983	.1819	.1506	.1067	.0545
.0000	.0439	.0870	.1281	.1655	.1968	.2192	.2302	.2443	.2337	.1998	.1447	.0748
.0000	.0512	.1018	.1506	.1958	.2345	.2623	.2700	.3077	.3080	.2722	.2023	.1061
.0000	.0595	.1187	.1765	.2317	.2818	.3237	.3548	.4013	.4126	.3772	.2895	.1556
.0000	.0683	.1366	.2044	.2709	.3343	.3907	.4313	.5105	.5488	.5243	.4211	.2352
.0000	.0771	.1545	.2325	.3113	.3902	.4671	.5361	.6440	.7191	.7233	.6188	.3686
.0000	.0854	.1714	.2593	.3502	.4453	.5457	.6528	.7905	.9153	.9766	.9109	.6042
.0000	.0926	.1862	.2829	.3850	.4951	.6162	.7497	.9312	1.1226	1.2710	1.3279	1.0498
.0000	.0981	.1978	.3018	.4134	.5374	.6805	.8537	1.0764	1.3452	1.5712	1.8849	1.9828
.0000	.1013	.2046	.3131	.4311	.5646	.7240	.9275	1.2114	1.6549	1.8543	2.5545	4.1018
9.0542												
average vertical velocity -divide by void fraction .786 for local velocity-												
.0000	.0070	.0000	.0000	.0000	.0000	.0000	.0000	.0000	.0000	.0000	.0000	.0000
.0113	.0109	.0101	.0089	.0073	.0054	.0033	.0012	-.0007	-.0023	-.0035	-.0042	-.0046
.0236	.0228	.0211	.0186	.0153	.0113	.0069	.0024	-.0016	-.0049	-.0073	-.0088	-.0096
.0378	.0366	.0340	.0302	.0250	.0186	.0113	.0038	-.0028	-.0081	-.0119	-.0143	-.0154
.0548	.0532	.0499	.0447	.0375	.0283	.0172	.0053	-.0048	-.0124	-.0176	-.0209	-.0225
.0757	.0737	.0697	.0633	.0543	.0422	.0261	.0063	-.0084	-.0185	-.0252	-.0293	-.0312
.1011	.0989	.0944	.0873	.0771	.0630	.0422	.0041	-.0153	-.0272	-.0350	-.0398	-.0420
.1316	.1293	.1246	.1172	.1070	.0943	.0808	-.0130	-.0281	-.0394	-.0475	-.0527	-.0552
.1675	.1652	.1603	.1527	.1423	.1285	.1091	-.0184	-.0407	-.0535	-.0625	-.0683	-.0711
.2090	.2066	.2016	.1939	.1838	.1718	.1586	-.0369	-.0579	-.0703	-.0800	-.0867	-.0900
.2563	.2538	.2482	.2399	.2295	.2186	.2104	-.0533	-.0747	-.0881	-.0999	-.1083	-.1125
.3099	.3070	.3004	.2906	.2781	.2638	.2471	-.0528	-.0865	-.1055	-.1218	-.1336	-.1395
.3708	.3673	.3591	.3466	.3311	.3141	.2994	-.0575	-.0973	-.1231	-.1466	-.1639	-.1727
.4405	.4361	.4255	.4094	.3886	.3641	.3381	-.0412	-.0996	-.1393	-.1750	-.2015	-.2149
.5211	.5156	.5022	.4816	.4536	.4190	.3797	-.0110	-.0932	-.1541	-.2089	-.2498	-.2707
.6149	.6084	.5921	.5663	.5301	.4833	.4284	.0379	-.0745	-.1659	-.2502	-.3142	-.3475
.7243	.7169	.6982	.6674	.6225	.5613	.4803	.1192	-.0354	-.1715	-.3008	-.4026	-.4564
.8515	.8436	.8231	.7886	.7371	.6648	.5694	.2228	.0278	-.1649	-.3606	-.5250	-.6159
.9974	.9895	.9684	.9322	.8766	.7955	.6802	.3745	.1352	-.1307	-.4228	-.6932	-.8572
1.1621	1.1547	1.1345	1.0994	1.0442	.9610	.8364	.5739	.3011	-.0451	-.4663	-.9146	-1.2352
1.3445	1.3380	1.3204	1.2895	1.2402	1.1645	1.0493	.8238	.5417	.1269	-.4405	-1.1718	-1.8550
1.5424	1.5373	1.5240	1.5005	1.4623	1.4019	1.3042	1.1374	.8753	.4200	-.2475	-1.3585	-2.9317
1.7521	1.7492	1.7419	1.7289	1.7076	1.6731	1.6154	1.5128	1.3146	.8255	.2635	-1.0743	-4.9654
1.9685	1.9685	1.9685	1.9685	1.9685	1.9685	1.9685	1.9685	1.9685	1.2359	1.2359	.8881	.8881
cold interface location												
.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
.000	.166	.331	.497	.662	.828	.993	1.159	1.324	1.490			
.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
1.655	1.821	1.986	2.152	2.317	2.483	2.648	2.814	2.979	3.145			
.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
3.310	3.476	3.641	3.807	3.972	4.138	4.303	4.469	4.634	4.800			
.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
4.965	5.131	5.296	5.462	5.627	5.793	5.958	6.124	6.289	6.455			
.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
6.620	6.786	6.951	7.117	7.282	7.448	7.613	7.779	7.944	8.110			
ink packet locations/sizes (iout=1 - ink exited)												
0 +0.000000E-01												
.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000

END

**DATE
FILMED**

9 / 7 / 93