DOE/ER/40452- 7

DE92 017390

RESEARCH & DEVELOPMENT OF A HELIUM-4
BASED SOLAR NEUTRINO DETECTOR

PROGRESS REPORT

for period 1 January 1991 - 30 June 1992

R.E.Lanou, H.J.Maris, and G.M.Seidel

Department of Physics

Brown University

Providence, RI 02912

30 June 1992

Prepared for

U.S. DEPARTMENT OF ENERGY

GRANT NO. DE-FG02-88ER40452

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed or represents that its use would not infringe privately-owned rights.

Abstract

In this report we describe results of experiments to detect low energy radiation in superfluid helium. The ultimate aim of this research is to establish the feasibility of this technique for use in detecting neutrinos from the p-p and Be-7 reactions in the sun. In these experiments we have seen the first detection of 5.5 MeV α particles via evaporation from a bath of superfluid helium. An α particle excites phonons and rotons in the liquid helium, and these excitations are sufficiently energetic to evaporate helium atoms when they reach the free surface of the liquid. The evaporated atoms are detected calorimetrically by a thin wafer suspended above the liquid. The approximate overall efficiency of this process has been determined and we compare the experimental results with expectations. We have also been able to detect evaporation induced by a flux of gamma rays from a Cs-137 source. Preparations made for new experiments are also discussed.

I Introduction

We report here on a research project to develop a method for the measurement of the spectrum of very low energy neutrinos from the sun — the neutrinos generated by the p-p and Be-7 reactions. The detection of these neutrinos and the measurement of their energies is important for several reasons. The flux expected for the p-p neutrinos is highly constrained by the optical luminosity and depends only slightly on the astrophysical model of the sun. The Be-7 neutrinos constitute a line spectrum and have a dependence on solar temperature quite different from that of the high energy B-8 neutrinos. Taken together, measurements of the fluxes and spectra of neutrinos from all three major reactions would provide all the data essential to a full resolution of the “solar neutrino problem” (SNP) and if it is established that the cause of the problem is due to properties of the neutrino, this would represent the first evidence for new physics beyond the “standard model” of nuclear and particle physics.

This past month at the “Neutrino92” conference in Granada, Spain, exciting developments were announced from the GALLEX collaboration [1,2]. These new results emphasize again the importance of measuring the p-p and Be-7 neutrinos, particularly via both the charged current and neutral current interactions using real-time techniques. Very briefly, these developments are as follows: a) the radiochemical GALLEX experiment has definitely detected p-p neutrinos by their charged current interaction and has measured a total flux of $83 \pm 19(\text{stat}) \pm 8(\text{sys})$ SNU; b) the SAGE experiment (also radiochemical, based on Ga) had earlier measured a flux of $20 \pm 20(\text{stat}) \pm 32(\text{sys})$ SNU [3]; c) new data from SAGE [4], not yet fully analyzed because of possible systematic errors, does not appear to be dramatically different from the earlier results of that group; d) new data [5] from HOMESTAKE and KAMIOKA-II,III, when added to the already extensive results of those experiments, do not change the conclusion that there is a large deficit in the measured high energy neutrino flux

from that predicted; e) preliminary analyses suggest that while it may just be possible to explain the results of these several experiments within the context of the standard solar model, the results are also consistent with two solutions of the MSW effect (matter oscillations in the sun due to neutrino mass).

This ambiguity in the origin of the effects being observed suggest that it will be useful to measure the p-p and Be-7 neutrinos separately. The fluxes from these different sources have very different temperature dependences within the standard solar model and have vastly different ratios within the two allowed solutions of the MSW effect. This latter point has been emphasized in a recent preprint by Gelb, Kwon and Rosen [6] who discuss the importance of experiments that are capable of detecting p-p and Be-7 neutrinos simultaneously.

Our project is aimed at developing a technique whereby it will be possible to detect both p-p and Be-7 neutrinos from the sun. To date there is no proven method for doing so. The challenge comes in detecting events producing an energy the order of a 100 kilovolts with low counting rates in a very large mass target having of necessity an especially low background radioactivity. Sensitivity, via the neutral current, to neutrinos other than the original electron type is also desirable and at these energies requires the use of neutrino-electron scattering. We have chosen to use superfluid helium as the detecting medium. The principles upon which the detector is based have been extensively discussed in our original paper [7] and more recently in our previous progress report (Brown University, Dept. of Physics Report: DOE/ER/40452-5; Dec. 1990).

In the following sections we discuss two principal aspects of our work during the current reporting period. The first part consists of a series of measurements in our prototype device in which both alpha particles and gamma rays were successfully detected. The second part of the research involves the improvement of the cryogenic and electronic systems to achieve higher sensitivity prior to a new set of measurements on particle detection, which have just recently begun.

II Results on particle detection

In this reporting period a crucial milestone has been reached. We have observed energy from radiation deposited in superfluid helium by detecting the quantum evaporation of atoms from the surface of the liquid.

The experimental cell has a diameter of 10 cm, a height of 25 cm and can be filled with liquid helium to various depths during the course of the experiments. The temperature of the helium in the cell is typically 70 mK. The silicon wafer on which the helium atoms (evaporated by a radiation event) are adsorbed and detected had a diameter of 7 cm and a thickness of 0.02 cm; its operating temperature was about 45 mK. Temperature changes of the wafer are detected by neutron transmutation doped (NTD) germanium thermistors mounted on the wafer. The thermistors were kindly provided to us by Prof. E.E.Haller (LBL).

In order to obtain a high sensitivity for detecting energy in a calorimetric experiment it is essential to have the heat capacity of the silicon wafer/calorimeter as small as possible. A first step in achieving this is to keep the superfluid film from covering the wafer because the film itself has a very large heat capacity. We have successfully done this by the invention of a "film burner" and have employed it as an integral part of the apparatus. A paper on the design, construction and performance of this device has recently been published [8].

The heat capacity of the wafer can be determined prior to introducing any helium into the cell by measuring the temperature rise produced when a particle of known energy hits the wafer directly, assuming the wafer thermalizes in the time of measurement. Partly for this purpose a radioactive source (in this case Am-241 providing 5.5 MeV α particles) is located in the cell and mounted well below the wafer. With a rate determined by the solid angle subtended by the wafer, the α particles range out in the silicon and deposit their full energy. The size of the temperature pulse created by this deposition is determined from

the known thermistor characteristics. Our earliest measurements of the heat capacity of a silicon wafer gave a result [8] that was a factor 20 times larger at 40 mK than the well known lattice heat capacity of silicon. Furthermore, since the large, anomalous heat capacity was determined to depend linearly on temperature, the ratio of it to the Debye T^3 lattice term increases with decreasing temperature. The origin of this added heat capacity is not fully understood, although it is suspected to result from two-level systems associated with the amorphous oxide layer on the surface of the silicon. Measurements on other silicon wafers give approximately the same anomalous heat capacity per unit area. In the data discussed immediately below [9] we used a silicon wafer of 0.02 cm thickness and 35 cm² area. In Fig. 1a we show a typical pulse when the energy of an alpha is deposited directly into the wafer; the signal to noise ratio is greater than 100 to 1. The spectrum of such pulses is shown in Fig. 2a. The width is dominated by the dependence of the thermistor response upon the position at which the α particle strikes the wafer. This has been confirmed by examining the correlation of the pulse heights from a pair of thermistors mounted on the same wafer.

In a typical experiment, liquid helium is introduced into the cell and its level carefully controlled. When the level of helium covers the source two dramatic changes occur: a) the counting rate increases and b) the pulse height decreases. The rate increase occurs because with the source covered the α particles emitted within the full 2π solid angle are stopped in the helium and can generate a signal through the creation of excitations in the liquid which subsequently evaporate atoms from the surface. The pulses are smaller for a number of reasons discussed below; however, their existence is evidence of the detection of radiation by evaporation. This assessment is confirmed by the introduction of 1 ppm of He-3 into the isotopically purified liquid He-4. Diffuse inelastic scattering of the rotons and phonons by the He-3 atoms degrades their energies sufficiently that they no longer can affect evaporation.

A typical pulse for this radiation induced evaporation signal is shown in Fig. 1b; the signal to noise is about 5 to 1. The resulting spectrum is illustrated in Fig. 2b; the unexpected

"shoulder" on the high energy side is of considerable interest. We do not yet know its origin. Our original speculation has been that the shape of the spectrum might be due to phonon down-conversion effects imposed by the geometric aperture of the source holder. Were this to prove correct it would be of no consequence for a neutrino experiment since there the events occur in the bulk liquid directly. The depth of helium above the source for these data was 7 cm. In subsequent tests we have noted a possible dependence on helium depth for the characteristics of the "shoulder". Further study of observation is needed; some preliminary results on the depth effect are discussed below.

There are several parameters in the sequence of energy deposition, evaporation and adsorption for which quantitative information can be obtained from the experiment. Of particular interest are the fraction of the original α particle energy which goes into generation of rotons energetic enough to cause evaporation, the fraction of rotons reaching the free surface which do evaporate atoms, the fraction of atoms which adhere to the wafer, and the energy "gain" when the atoms are physisorbed on the silicon wafer. What is meant by gain in this context is the ratio of energy per atom deposited on the wafer to the average energy of the evaporated atom. Each of these parameters cannot be separately isolated in the present experimental design but several relevant combinations of them can, thus providing useful information. The product of the gain and the probability of adhesion to the wafer is approximately 10 — a value very close to that predicted. Using this factor we can infer that about 0.5% of the particle energy goes into the evaporation of atoms in the present experimental configuration. The geometry of the cell and wafer combined with the kinematics of the quantum evaporation process reduces very substantially the collection efficiency in the present experimental arrangement. In a full-size detector with many wafers above the surface, the ratio of energy detected to that deposited by the particle in the liquid could be larger by a factor of 10.

Our present wafer/detector has an energy threshold of 50 keV. While this is sufficient to

detect individual 5.5 MeV α particle events occurring in the liquid, it is not adequate to see individual electron recoils obtainable by Compton scattering in the liquid from an external γ -ray source such as Cs-137, nor, for that matter, recoil electrons from neutrino scattering. However, we are able to detect a steady state temperature rise of the wafer produced by illumination of the cell with a Cs-137 source of modest activity. Consequently, as a preliminary comparison of the efficiency of electron and alpha detection and as a confirmation that we are indeed detecting radiation in the bulk liquid itself, we have "x-rayed" the helium in the cell. The external Cs-137 source was collimated to provide a beam of γ 's roughly 1 cm high at the cell, and the temperature rise of the wafer was measured as a function of the height of the collimated beam relative to the helium. The results of this experiment are shown in Fig. 3 and clearly show agreement with the known location of the top and bottom of the liquid level. From the known γ -ray flux and thermal response of the wafer, we calculate that the fraction of the average electron energy detected is consistent with what is observed for α 's.

There are many different means by which the sensitivity of the detector can be increased and its threshold energy decreased, some of which are discussed below. Using calorimetric techniques very similar to ours but for a different purpose, the Berkeley group [10] have achieved a threshold of 1 keV with a 60 gram mass of germanium as compared to the value of 50 keV for the 1.7 gram wafer of silicon obtained in our preliminary tests. If we can achieve the same level of performance as others have already obtained, we can estimate roughly the threshold level possible for a full size (10 ton) helium detector. Requiring a three-fold coincidence of 3 gram wafers and taking a linear rather than a volume scaling (the kinematics of roton propagation and the evaporation process are likely to be the determining factor), we find that a threshold of less than 10 keV should be achievable.

III System improvements

Since the completion of the experimental measurements discussed above, we have made a number of modifications to the refrigeration and electronic systems so as to improve the overall performance. Also, we have reconfigured the contents of the helium cell so as to study some of the processes of energy transfer.

The more important of the changes to the system and their consequences are the following:

1) An additional discrete heat exchanger was added to the dilution refrigerator thereby reducing the steady state operating temperature of the mixing chamber from 24 mK to 16 mK. 2) The wiring to the film burner was reconfigured so as to reduce the stray heat inputs from it to the wafer. This has decreased the steady state operating temperature of the wafer from 45 mK to 30 mK with the film burner functioning to remove the helium film. 3) The method of supporting the wafer has been modified to reduce noise generated by heating from mechanical vibrations. 4) New cabling with superior shielding has been installed in the cryostat between the thermistors and room temperature to reduce electrical noise pickup. Collectively these modifications have improved the threshold level of the detector by a factor of 4 compared to that which existed when the measurements described in the previous section were made.

At a more basic level there are two principal means by which the sensitivity of our detector can be increased substantially, perhaps by two orders of magnitude. Firstly, a decrease in the heat capacity of the wafer/calorimeter to a value comparable to that of the lattice would increase the change in temperature being measured for a given energy input by a comparable amount. Secondly, we have far from the best thermistor and associated electronics for detecting small temperature changes in the millikelvin range. We are currently addressing these issues. A more detailed discussing of status and plans can be found in the accompanying Continuation Proposal.

In order to investigate the mechanisms involved in the conversion of the energy of a particle into evaporated atoms, the understanding of which is important for the design of a large-scale detector, we have added diagnostic tools to the experimental helium cell. 1) A second wafer with its associated thermistor has been added to allow for the study of coincident signals (see Fig. 4). 2) The α particle source has been placed on the arm of a small superconducting stepping motor thereby providing a means for investigating directional properties of various processes. These two additions are in place but to date no data has been obtained using them. Research plans are also discussed in the Continuation Proposal.

In summary, we have made important progress in establishing the possibility of detecting radiation in superfluid helium. Much interesting work remains before it can be established experimentally that helium can be used as detector of solar neutrinos. We look forward to pursuing this goal by building on the results obtained so far.

IV Scientific personnel associated with the project

R.E.Lanou	Professor of Physics
H.J.Maris	Professor of Physics
G.M.Seidel	Professor of Physics
C.Enss*	Visiting Assistant Professor(Research)
F.S.Porter	Graduate Research Assistant
S.R.Bandler	Graduate Research Assistant
T.More	Graduate Research Assistant

* Dr.Enss is a low temperature physicist from the University of Heidelberg. His principal support derives from the Alexander von Humboldt Foundation.

V Recent publications

- S.R.Bandler, R.E.Lanou, H.J.Maris, T.More, F.S.Porter, G.M.Seidel and R.Torii, "Particle Detection Using Superfluid Helium", to appear in Proceedings of the IVth International Workshop on Low Temperature Detectors (Oxford, Sept. 1991). Editiones Frontieres, in press. Also Brown University Report DOE/ER/40452-6.
- R.Torii, S.R.Bandler, T.More, F.S.Porter, R.E.Lanou, H.J.Maris and G.M.Seidel, "Removal of Superfluid Film from Surfaces Below 0.1 K", Rev. Sci. Instrum. **63**, 230 (1992).
- S.R.Bandler, R.E.Lanou, H.J.Maris, T.More, F.S.Porter, G.M.Seidel and R.Torii, "Particle Detection by Evaporation from Superfluid Helium", Phys. Rev. Lett. **68**, 2429 (1992).
- R.E.Lanou, H.J.Maris and G.M.Seidel, Progress Report DOE/ER/40452-5, Dec. 1990.

References

- [1] P. Anselmann *et al*, GALLEX Collaboration, preprint GX 1-1992, submitted to Phys. Lett. B, June 1, 1992.
- [2] P. Anselmann *et al*, GALLEX Collaboration, preprint GX 2-1992, submitted to Phys. Lett. B, June 1, 1992.
- [3] A.I.Abazov *et al*, SAGE Collaboration, Phys. Rev. Lett. **67**, 3332 (1992).
- [4] Talk by T.Bowles, SAGE Collaboration, at "Neutrino92", Granada, Spain, June 1992, to appear as Proceedings in Nucl. Phys. B.
- [5] Talks by K. Lande, Homestake Collaboration and H.Tatsuka, Kamiokande Collaboration, *ibid*.
- [6] J.Gelb, W.Kwong and S.P.Rosen, University of Texas preprint UTAPHY-HEP-2.
- [7] R.E.Lanou, H.J.Maris, and G.M.Seidel, Phys. Rev. Lett. **58**, 2498 (1987).
- [8] R.H.Torii, S.R.Bandler, R.E.Lanou, H.J.Maris, T.More, and G.M.Seidel, Rev. Sci. Instrum. **63**, 230 (1992).
- [9] S.R.Bandler, R.E.Lanou, H.J.Maris, T.More, G.M.Seidel, and R.H.Torii, Phys. Rev. Lett. **68**, 2429 (1992).
- [10] T. Shutt *et al*, preprint, Center for Particle Astrophysics, University of California, Berkeley.

Change in resistance of the bolometer detector (a) when the α hits the wafer directly and (b) when the α scatters in the superfluid helium bath and the wafer is heated by evaporated helium atoms.

Figure 1.

Pulse-height distribution, expressed in terms of temperature rise, (a) for α particles hitting the bare wafer directly ($T_{\text{wafer}} = 84$ mK) and (b) for α particles stopped in the superfluid helium bath ($T_{\text{wafer}} = 50$ mK).

Figure 2.

Figure 3.

The steady-state temperature rise of the bolometer on the silicon wafer as a function of height of the γ source. The bottom of the cell is at 0 cm, the liquid is at 14 cm, and the wafer is at 15 cm.

Figure 4.

Coincidence of two wafers. A phonon pulse is generated by a heat pulser located in the superfluid helium. The evaporated atoms are simultaneously detected by the two wafers above the liquid.

**DATE
FILMED**

8/20/92