Received

DOE/PC/89782--T7

DE92 018301

SELENIUM TRANSFORMATION IN COAL MINE SPOILS

Quarterly report, Grant No. DE-FG-22-89PC-89782

Prepared by:

Asmare Atalay and K.J. Koll
University of Oklahoma
Civil Engineering and Environmental Science
202 West Boyd, Room 334
Norman, OK 73019

September 1, 1990

MASTER

TABLE OF CONTENTS

Introduction	1
Site Description	3
Lysimeter Layout in the Study Area	5
Construction of Platinum Electrodes	5
Soil Moisture, Soil Gas, and pH	8
Literature Cited	11

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

INTRODUCTION

The speciation of selenium affects the mobility and adsorption of selenium (Neal and Sposito, 1989). The redox conditions in the soil environment which affect selenium speciation, and thus, selenium availability, are Eh, pH, soil moisture conditions and concentrations of soil gases such as O_2 and CO_2 .

It is believed that selenium compounds are altered by many of the same inorganic, organic, and biochemical reactions as sulfur. From what is known about the isomorphic substitution of the close association of mineral suites of selenium and sulfur, it would be expected that the oxidation of selenium and sulfur are controlled by similar factors (Cary and Allaway, 1973). The production of large amounts of sulfuric acid in strip mine spoil banks and the contamination of creeks into which the mines drain has been observed. The amounts of selenium leaching under these conditions have not been measured. Pyrite oxidation in Missouri shales has been found to be zero order (Ainsworth, 1979). Rates of 182 to 12 ug S/g shale/day were measured. A large amount of the pyrite in shales exposed to the atmosphere would be predicted to react between 1 and 5 years. Measurement of partial pressure of O_2 , pH, and Eh in graded spoils indicate that conditions to 100 cm depth are sufficiently oxidized to favour the formation of ferric hydroxide and sulfuric acid from pyrite (Ainsworth, 1979). It appears that selenate or selenite will be formed during the oxidation of pyrite which contains selenium as an impurity and that

selenium will move with sulfuric acid in the spoil banks, streams, and soils which form the drainage system in the mined areas.

Selenate has a structure similar to sulfate, and chemically and biologically it appears to undergo reactions similar to those of sulfates (Shrift, 1972). However selenate has a lower oxidation potential than sulfate (Laking et al., 1967). Data collected by Hess and Blanchar (1979) indicate that Eh-pH conditions throughout most of the year in a Mexico soil are such that selenite would be favored over selenate. In the B-horizon (60 cm depth) of Mexico soil, the Eh-pH conditions throughout most of the year would favor the formation of elemental selenium (Hess and Blanchar, 1977). It is unlikely the competitive antagonism for plant or microbial uptake of selenite over sulfate would occur. The analogous reactions of selenium and sulfate probably do occur in environments which change drastically from reduced to highly oxidized, but the difference in oxidation potential between selenium and sulfur forms may be extremely important in environments of intermediate oxidation potential such as soils (Hess and Blanchar, 1977, Olson, 1967) or graded shale overburden piles. It is anticipated that intermediate oxidation and reduction reaction forms of selenium in soil and mine spoil will play a much more important role in its solubility, mobility, and biological activity than intermediate oxidation and reduction forms of sulfur.

The objective of this part of the study is to investigate the oxidation-reduction (redox) environment that favor the release of selenium from coal mine spoils. It is anticipated that the study

will help answer critical questions as to the form, solubility, and mobility of selenium from the spoil site to the surrounding environment. This investigation will evaluate the conditions which favor the speciation of selenium from coal mine spoils as affected by changes in the oxidation states of selenium.

SITE DESCRIPTION

An abandoned strip mine area 0.55 mile east of Henryetta, Oklahoma, is selected as the the site for this study. Henryetta is located about 86 miles east of Oklahoma City along Interstate 40. The property belongs to Mrs. Hazzel Marler who has been most kind in permitting the University of Oklahoma Civil Engineering and Environmental Science Department to use this study site. The area had been actively mined since early 1900's until the 1950's, however, it has been abandoned since mid-1950. The Oklahoma Department of Conservation had declared a portion of this area (near the county road) as hazardous, and reclaimed about 300 yards from each side of the road.

Within the selected field site, three study areas have been identified. Area one is located on a spoil pile, area two is on the reclaimed spoil land, and area three is on an unspoiled land near the perimeter of the spoiled area. Figure 1 is a simplified diagram of the site description and location. A more detailed area description and aerial photographs will be available in the future.

Figure 1. Portrayal of the coal mining site east of Henryetta. Positions 1, 2 and 3 mark the field sites for study. Areas marked A, B and C are water-filled abandoned strip mining sites. A ridge separates mining sites A and B from C.

Lysimeter Layout in the Study Area

At each study area (spoil, reclaimed, or unspoiled land), three electrode combinations (platinum and reference), gas access tubes and tensiometers will be installed at soil depths of 30, 91, and 152 cm., respectively. Figure 2 shows a site matrix identifying the distribution of each component within the matrix. Each depth symbol consists of a tensiometer, an air access tube, a platinum electrode, and a reference electrode. At each depth, pH will be measured using the reference electrode access tube.

Construction of Platinum Electrodes

The platinum electrode consists of a 2.2 cm, 18 gauge platinum wire soldered to copper wire in Type RG-58U wire and cable from Radio Shack. Nine wire and cable electrodes measuring 46, 107, 168 cm in length with solderless BNC connectors were each attached to the RG-58U coax cable. The connectors were adapted for use on the Fisher pH/MV meter. The reference electrode is the calomel reference electrode (catalog number 13-620-259) manufactured by Fisher Scientific. The calomel reference electrode attaches to the pH/MV meter by pin jack.

Figure 3 depicts the schematic for a complete assembly of the constructed platinum electrode. It consists of a 0.2 cm of 18 gauge platinum wire soldered to an equal diameter copper wire. A shrink tube (3/32 in. in diameter) was ordered from Alpha Wire

Figure 2. Site matrix for installation of nine sampling probes. Each sampling probe consists of a reference electrode, platinum electrode, tensiometer and soil gas access tube. These measurement probes are installed at depths of 30, 91 and 152 cm. The matrix indicates the distribution of the sampling devices in each site area.

Figure 3. An illustration for the design and construction of the platinum electrode which is used with a calomel reference electrode to measure Eh in a subsurface environment.

Corporation and used to seal around the solder joint for the protection of the connection from moisture and any subsequent corrosion. The coax cable end with the solder connection is then inserted through a 1/4 inch hole drilled through a 5/8 inch dowl rod 7/8 inch in length. The platinum wire extends 2.0 cm beyond the dowl rod. The entire length of cable is pushed through 1/2 inch PVC Schedule 40 tubing. The dowl rod "plug" is glued with Elmer's wood glue into the end of the PVC tubing. Each PVC tube used to construct the platinum electrodes is filled with paraffin wax to keep air and moisture from the electrode wire and connection. A second dowl rod "plug" is inserted at the top end of the PVC tube to seal the tube and support the coax cable.

Appropriately sized PVC connections with 50 cm lengths of 3/4 inches PVC were employed to design a protective cap for the platinum electrode. When Eh measurements are taken the protective cap can easily be removed from the 1/2 PVC to expose 16 cm of coax cable with BNC connectors. The reference electrodes are inserted through 3/4 inch PVC at the same depths (30, 90 or 150 cm) as the platinum electrodes.

Soil Moisture, Soil Gas, and pH

Soil moisture is measured using tensiometers purchased from Soil Moisture Equipment Corporation, Santa Barbara, CA. The 2725 series Jet Fill Tensiometer is used to measure soil moisture

potential and subsurface soil moisture to verify proper moisture conditions in the vicinity where the electrodes are buried. Flooded or ponded situations contribute to reducing conditions which support the transformation of selenate to selenite, the less soluble or less mobile form (Long, et al., 1990).

Soil gas samples (O_2 and CO_2 , primarily) will be taken using medical vacutainers with needles and 10 ml blood collection tubes. The needles are inserted through a septum screw cap on top of the 1/2 inch PVC tubes used as air access tubes. The vacutainer will withdraw approximately 10 ml of soil air. After a preselected equilibration time, the vacutainer is removed and placed in a cooler containing dry ice. The concentration of O_2 and CO_2 found in the soil air will be determined with a Gas Chromatograph equipped with a thermal conductivity detector.

Soil pH may alternatively (to that of using direct measurement via the reference electrode access tube) be measured in the field. Soil core samples will be removed from 30, 90, and 150 cm depths. The soil samples will be mixed (1:10) with deionized water and the pH measured with a portable pH meter.

Also, from the site, surface water, ground water, sediment and soil samples will be analyzed for both SeO_3^{-2} and SeO_4^{-2} concentrations. Digested samples will be used to determine total Se on a Model 951 Instrumentation Laboratory aa/ae Spectrophotometer which is equipped with a graphite furnace. Fresh soil samples extracted with deionized water will be analyzed for SeO_3^{-2} and SeO_4^{-2} levels using DIONEX AI-450 Ion Chromatography with the DIONEX conductivity and ultra violet detectors. In total, the

aqueous soil environment at the coal mine spoil site will be analyzed for Eh, pH, soil gases, soil moisture, and concentrations of selenate and selenite occurring at the site.

LITERATURE CITED

1. Ainsworth, Calvin C. 1979. Pyrite Forms and Oxidation Rates in Missouri Shales. University of Oklahoma, M.S. Thesis, pp. 1-144.
2. Cary, E. E. and W. H. Allaway. 1973. Selenium Content of Field Crops Grown in Selenite Treated Soils. Agron. J. 65: 922-925.
3. Hess, R. E. and R. W. Blanchard. 1977. Arsenic determination and Arsenic, Lead, and Copper Content of Missouri Soils. MO. Agric. Exp. Sta. Bul. No. 1020. pp. 1-46.
4. Laking, H. W. and David F. Davidson. 1967. The Relation of Geochemistry of Selenium to its Occurrence in Soils. In: Selenium in Biomedicine, Muth O. H (ed.). A. V. I. Publication Co., Westport, Conn.
5. Neal, R. H. and Sposito, G. 1989. Selenate Adsorption on Alluvial Soils. Soil Sci. Soc. Am. J. 53: 70-74.
6. Olson, O. E. 1967. Soil, Plant, Animal Cycling of Excessive Levels of Selenium. In: Selenium in Biomedicine, Muth, O. H. (ed.). A. V. I. Publishing Co. Westport, Conn.
7. Shrift, A. 1973. Metabolism of Selenium by Plants and Microorganisms. p. 763-814. In: D. L. Klayman and W. H. H. Gunther (ed.), Organic Selenium Compounds: Their Chemistry and Biology. John Wiley & Sons, Inc. New York.

END

**DATE
FILMED**

9 / 9 / 92