AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

13-93752

PREPARED FOR THE U.S. DEPARTMENT OF ENERGY,
UNDER CONTRACT DE-AC02-76-CHO-3073

PPPL-2915
UC-426

PPPL-2915

MICROWAVE REFLECTOMETRY FOR ICRF COUPLING STUDIES ON TFTR

BY

J.B. WILGEN, G.R. HANSON, T.S. BIGELOW, ET AL.

JUNE, 1993

PPPL
PRINCETON
PLASMA PHYSICS
LABORATORY

PRINCETON UNIVERSITY, PRINCETON, NEW JERSEY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial produce, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

NOTICE

This report has been reproduced from the best available copy.
Available in paper copy and microfiche.

Number of pages in this report: 6

DOE and DOE contractors can obtain copies of this report from:

Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831;
(615) 576-8401.

This report is publicly available from the:

National Technical Information Service
Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22161
(703) 487-4650

MICROWAVE REFLECTOMETRY FOR ICRF COUPLING STUDIES ON TFTR

J. B. Wilgen, G. R. Hanson[†], T. S. Bigelow, D. B. Batchelor, I. Collazo[‡],
D. J. Hoffman, M. Murakami, D. A. Rasmussen, and D. C. Stallings
Oak Ridge National Laboratory, Oak Ridge, TN 37831-8072

S. Raftopoulos and J. R. Wilson
Plasma Physics Laboratory, Princeton University, P. O. Box 451, Princeton, NJ 08543

ABSTRACT

A dual-frequency differential-phase reflectometer has been developed for use in ICRF power coupling studies on TFTR. This system has been optimized for measurements of the electron density profile in the edge-gradient region, where density fluctuations are large. Initial proof-of-principle measurements demonstrate that this is an effective way to measure the electron density profile in the plasma-edge region. A new reflectometer launcher is presently being installed on the center axis of the bay-K ICRF antenna on TFTR, along with the associated waveguide transmission line. This will allow direct measurement of the edge-density profile within the high-power-density environment of the ICRF antenna where density profile modification might be expected.

INTRODUCTION

The coupling of ICRF power to the plasma is sensitive to details of the density profile in the plasma edge region, and the high power density ICRF environment can potentially alter the edge-density profile, at least locally in the immediate vicinity of the ICRF antenna. Theoretical ICRF antenna coupling calculations show that density profile changes immediately in front of the ICRF antenna can result in changes in the antenna loading by a factor of 2 to 3. Similar loading changes have been observed experimentally during ICRF heating. Reflectometer measurements of the edge-density profile can be used to correlate changes in antenna loading with shifts of the fast wave cutoff density. Consequently, there is significant interest in obtaining detailed measurements of the shape of the edge-density profile, and it is particularly important that the measurement be performed in the ICRF antenna environment.

DUAL-FREQUENCY DIFFERENTIAL-PHASE REFLECTOMETER

A dual-frequency differential-phase reflectometer has been developed for use in ICRF power coupling studies on TFTR¹. This system has been optimized for measurements of the electron density profile in the edge-gradient region where density fluctuations are large. A differential-phase measurement was chosen because the multiplicity of fringes is thereby greatly reduced, and phase fluctuations arising from density fluctuations in the plasma are also significantly reduced. Both of these attributes are essential for reliable phase-tracking of multiple-fringe phase data.

A block diagram of the reflectometer as configured for a proof-of-principle measurement on TFTR is shown in Fig. 1. To provide the capability to measure the edge-density profile in the range between 1.0×10^{12} and $3.0 \times 10^{13} \text{ cm}^{-3}$ in high field (4.5–4.9 T) ICRF-heated TFTR plasmas, the frequency range of 91–117 GHz was chosen, corresponding to extraordinary mode polarization. Starting with a swept frequency source at low frequency, (8.0–12.4 GHz), upconversion and frequency multiplication

[†]Oak Ridge Associated Universities

[‡]Georgia Institute of Technology

MASTER

28

(doubler and tripler) are used to provide the frequencies of interest. In this way, the frequencies of two probing signals are simultaneously swept from 91 to 117 GHz while maintaining a fixed frequency separation of 250 MHz. This frequency spacing determines the radial separation of the dual cutoff layers in the plasma, which should be small in comparison with the radial correlation length of the plasma density fluctuations if a reduction in the differential-phase fluctuation level is to be effected. Amplitude fading in the reflected signal amplitude is removed through the use of constant-phase limiting amplifiers. Heterodyne detection is used to measure the differential phase delay between the two signals, which can then be used to reconstruct the shape of the density profile.

INITIAL RESULTS ON TFTR

To facilitate testing of this reflectometer in a realistic environment, it was attached via waveguide switches to share diagnostic access with the existing TFTR fluctuation reflectometer², an instrument that was specifically designed to investigate density fluctuations in the interior of the plasma. This system utilizes corrugated cylindrical waveguide to launch highly directional gaussian beams that are focused and directed into the plasma with scannable mirrors.

Differential-phase data obtained with this quasi-optical viewing system are shown in Figs. 2 and 3. For these measurements, the gaussian beams (transmitting and receiving) are aimed to intersect at $R = 3.3$ m, resulting in a saturated amplitude for the received signal whenever the reflection surface is in the range of 3.1 to 3.5 m, the region characterized by good overlap of the two beams. When the location of the plasma edge region, $R_0 + a$, is systematically scanned from 3.25 to 3.53 m, the differential-phase data changes in the expected fashion, as illustrated by the phase data in Fig. 2a. Note in particular that the differential phase typically shows a variation of only 2 to 4 fringes as the frequency is swept from 91 to 117 GHz. For most of this data, even the differential phase exhibits substantial phase fluctuations, with a typical magnitude of 1 radian rms or larger, but this does not present a serious problem in tracking the average trend in the phase. Edge-density profiles reconstructed from this data using an algorithm based on an extension of Doyle's method³ are shown in Fig. 2b. Similar data for a selection of shots with the same plasma size but different density (resulting from variation in NBI power from 0 to 27.5 MW) are shown in Fig. 3, demonstrating the expected variation in the differential phase as the density is varied.

The differential phase can be considered as consisting of two contributions, one associated with the shape of the profile through the local density gradient-dependent plasma dispersion, and another arising from the location of the plasma edge region. For the data shown in Fig. 2, shifting the location of the plasma edge by ≤ 30 cm while maintaining nearly the same profile shape is expected to contribute $\leq 1/2$ fringe to the total phase shift (i.e., the beat wavelength for 250 MHz frequency spacing is 1.2 m). This indicates that dispersive effects related to the profile shape represent the largest contribution to the differential phase. At the present time it is not clear to what extent these two contributions to the total phase can be separated. Although the reflectometer provides good information on the shape of the density profile in the edge region, it appears that the location of the plasma edge can be resolved only through detailed comparisons with other TFTR diagnostics.

Data obtained from full-sized ($R_0 + a = 3.6$ m) ICRF-heated plasmas show a similar shape for the edge-density profile. Attempts to observe modification of the edge-density profile during ICRF heating have not revealed any measurable changes, suggesting that if changes are occurring they are local to the antenna environment.

Fig. 1. A block diagram of the dual-frequency differential-phase reflectometer as configured for the proof-of-principle demonstration measurement on TFTR.

Fig. 2. (a) Measured differential-phase shift as a function of frequency and (b) reconstructed edge-density profiles for a plasma size scan where, for cases A, B, C, and D, the outer edge of the plasma ($R_0 + a$) is located at 3.25, 3.35, 3.44, and 3.53 m, respectively. Plasma conditions include $B = 4.5$ T ($I_H = 67$ kA), $I_p = 1.6$ MA, $\bar{n}_e = 3.2$ – 3.6×10^{19} m $^{-3}$, $P_{NBI} = 22.5$ MW, and $P_{ICRF} = 0$.

Fig. 3. (a) Differential-phase shift and (b) reconstructed edge-density profiles for a collection of shots where the density varies with the neutral beam power. Cases A, B, C, and D correspond to $P_{NBI} = 0, 17.5, 22.5,$ and 27.5 MW and $\bar{n}_e = 1.2, 2.8, 3.2,$ and 3.7×10^{19} m $^{-3}$, respectively. Other plasma conditions include $R_0 + a = 3.44$ m, $B = 4.5$ T ($I_H = 67$ kA), $I_p = 2.0$ MA, and $P_{ICRF} = 0$.

NEW LAUNCHER AND WAVEGUIDE TRANSMISSION LINE

A new launcher and waveguide transmission line are presently being installed on TFTR. The bay-K ICRF antenna was designed with a central diagnostic port that provides access for the reflectometer launchers on the center axis of this two-strap antenna. To eliminate the effects of spurious reflection on the reflectometer phase measurements, a pair of oversized WR-90 rectangular waveguides are used for the transmitting and receiving antennas. The launcher apertures are recessed 3 mm behind the front surface of the Faraday shield for the ICRF antenna. Stainless steel waveguides are necessary to limit disruption forces; a single quartz window is used for the vacuum feedthrough. "Tall-guide" polarization is used to achieve acceptable waveguide cross-coupling (< 40 db measured) between the closely spaced waveguides at the vacuum window.

With the exception of a downtapered section of WR-10 waveguide immediately outside the vacuum window, which serves to filter higher-order modes, the remainder of the waveguide run consists of 26 m of WR-90 waveguide leading to the reflectometer electronics located in the test cell basement. Transmission losses are reduced more than 50% by using the tall-guide polarization, resulting in an estimated round-trip transmission loss of 12 db, excluding the window/launcher assembly. For the tall-guide polarization, miter bend losses are measured to be approximately 0.4 and 0.8 db for the H-plane and E-plane bends, respectively.

CONCLUSION

Initial proof-of-principle measurements demonstrate that the dual-frequency differential-phase reflectometer is an effective way to measure the electron density profile in the plasma edge region where density fluctuations are large. An ICRF-antenna-mounted launcher and the associated waveguide transmission line are presently being installed in the bay-K ICRF antenna on TFTR. This will allow direct measurement of the edge-density profile within the high power density environment of the ICRF antenna, where density profile modification might be expected.

ACKNOWLEDGMENTS

We are indebted to E. Mazzucato, R. Nazikian, and M. McCarthy of PPPL, who generously shared their diagnostic access, without which the proof-of-principle measurement would not have been possible. We thank K. Young and N. Bretz of PPPL and S. L. Milora of ORNL for their support and encouragement. This research was sponsored by the Office of Fusion Energy, U.S. Department of Energy, under contract DE-AC05-84OR21400 with Martin Marietta Energy System, Inc. This research was supported in part by an appointment to the U.S. Department of Energy Fusion Energy Postdoctoral Research Program administered by the Oak Ridge Institute for Science and Education.

REFERENCES

1. G. R. Hanson, J. B. Wilgen, T. S. Bigelow, I. Collazo, and C. E. Thomas, *Rev. Sci. Instrum.* **63**, 4658 (1992).
2. E. Mazzucato, R. Nazikian and the TFTR group, *Proc. 19th EPS Conference on Controlled Fusion and Plasma Physics*, Innsbruck, June 1992, V2, p. 1055. [E. Mazzucato, R. Nazikian, N. Bretz, M. McCarthy, and A. Nagy, *Rev. Sci. Instrum.* **63**, 4657 (1992).]
3. E. J. Doyle, T. Lehecka, N. C. Luhmann, Jr., W. A. Peebles, and the DIII-D Group, *Rev. Sci. Instrum.* **61**, 2896 (1990).

EXTERNAL DISTRIBUTION IN ADDITION TO UC-420

Dr. F. Paoloni, Univ. of Wollongong, AUSTRALIA	Prof. I. Kawakami, Hiroshima Univ., JAPAN
Prof. M.H. Brennan, Univ. of Sydney, AUSTRALIA	Prof. K. Nishikawa, Hiroshima Univ., JAPAN
Plasma Research Lab., Australian Nat. Univ., AUSTRALIA	Director, Japan Atomic Energy Research Inst., JAPAN
Prof. I.R. Jones, Flinders Univ, AUSTRALIA	Prof. S. Itoh, Kyushu Univ., JAPAN
Prof. F. Cap, Inst. for Theoretical Physics, AUSTRIA	Research Info. Ctr., National Inst. for Fusion Science, JAPAN
Prof. M. Heindler, Institut für Theoretische Physik, AUSTRIA	Prof. S. Tanaka, Kyoto Univ., JAPAN
Prof. M. Goossens, Astronomisch Instituut, BELGIUM	Library, Kyoto Univ., JAPAN
Ecole Royale Militaire, Lab. de Phy. Plasmas, BELGIUM	Prof. N. Inoue, Univ. of Tokyo, JAPAN
Commission-European, DG. XII-Fusion Prog., BELGIUM	Secretary, Plasma Section, Electrotechnical Lab., JAPAN
Prof. R. Bouciqué, Rijksuniversiteit Gent, BELGIUM	S. Mori, Technical Advisor, JAERI, JAPAN
Dr. P.H. Sakanaka, Instituto Fisica, BRAZIL	Dr. O. Mitarai, Kumamoto Inst. of Technology, JAPAN
Instituto Nacional De Pesquisas Espaciais-INPE, BRAZIL	J. Hyeon-Sook, Korea Atomic Energy Research Inst., KOREA
Documents Office, Atomic Energy of Canada Ltd., CANADA	D.I. Choi, The Korea Adv. Inst. of Sci. & Tech., KOREA
Dr. M.P. Bachynski, MPB Technologies, Inc., CANADA	Prof. B.S. Liley, Univ. of Waikato, NEW ZEALAND
Dr. H.M. Skarsgard, Univ. of Saskatchewan, CANADA	Inst of Phycics, Chinese Acad Sci PEOPLE'S REP. OF CHINA
Prof. J. Teichmann, Univ. of Montreal, CANADA	Library, Inst. of Plasma Physics, PEOPLE'S REP. OF CHINA
Prof. S.R. Sreenivasan, Univ. of Calgary, CANADA	Tsinghua Univ. Library, PEOPLE'S REPUBLIC OF CHINA
Prof. T.W. Johnston, INRS-Energie, CANADA	Z. Li, S.W. Inst Physics, PEOPLE'S REPUBLIC OF CHINA
Dr. R. Bolton, Centre canadien de fusion magnétique, CANADA	Prof. J.A.C. Cabral, Instituto Superior Tecnico, PORTUGAL
Dr. C.R. James,, Univ. of Alberta, CANADA	Dr. O. Petrus, AL I CUZA Univ., ROMANIA
Dr. P. Lukác, Komenského Univerzita, CZECHO-SLOVAKIA	Dr. J. de Villiers, Fusion Studies, AEC, S. AFRICA
The Librarian, Culham Laboratory, ENGLAND	Prof. M.A. Hellberg, Univ. of Natal, S. AFRICA
Library, R61, Rutherford Appleton Laboratory, ENGLAND	Prof. D.E. Kim, Pohang Inst. of Sci. & Tech., SO. KOREA
Mrs. S.A. Hutchinson, JET Library, ENGLAND	Prof. C.I.E.M.A.T, Fusion Division Library, SPAIN
Dr. S.C. Sharma, Univ. of South Pacific, FIJI ISLANDS	Dr. L. Stenflo, Univ. of UMEA, SWEDEN
P. Mähönen, Univ. of Helsinki, FINLAND	Library, Royal Inst. of Technology, SWEDEN
Prof. M.N. Bussac, Ecole Polytechnique,, FRANCE	Prof. H. Wilhelmson, Chalmers Univ. of Tech., SWEDEN
C. Mouttet, Lab. de Physique des Milieux Ionisés, FRANCE	Centre Phys. Des Plasmas, Ecole Polytech, SWITZERLAND
J. Radet, CEN/CADARACHE - Bat 506, FRANCE	Bibliotheek, Inst. Voor Plasma-Fysica, THE NETHERLANDS
Prof. E. Economou, Univ. of Crete, GREECE	Asst. Prof. Dr. S. Cakir, Middle East Tech. Univ., TURKEY
Ms. C. Rinni, Univ. of Ioannina, GREECE	Dr. V.A. Glukhikh, Sci. Res. Inst. Electrophys. I Apparatus, USSR
Dr. T. Mui, Academy Bibliographic Ser., HONG KONG	Dr. D.D. Ryutov, Siberian Branch of Academy of Sci., USSR
Preprint Library, Hungarian Academy of Sci., HUNGARY	Dr. G.A. Eliseev, I.V. Kurchatov Inst, USSR
Dr. B. DasGupta, Saha Inst. of Nuclear Physics, INDIA	Librarian, The Ukr.SSR Academy of Sciences, USSR
Dr. P. Kaw, Inst. for Plasma Research, INDIA	Dr. L.M. Kovrizhnykh, Inst. of General Physics, USSR
Dr. P. Rosenau, Israel Inst. of Technology, ISRAEL	Kernforschungsanlage GmbH, Zentralbibliothek, W. GERMANY
Librarian, International Center for Theo Physics, ITALY	Bibliothek, Inst. Für Plasmaforschung, W. GERMANY
Miss C. De Palo, Associazione EURATOM-ENEA, ITALY	Prof. K. Schindler, Ruhr-Universität Bochum, W. GERMANY
Dr. G. Grosso, Istituto di Fisica del Plasma, ITALY	Dr. F. Wagner, (ASDEX), Max-Planck-Institut, W. GERMANY
Prof. G. Rostangni, Istituto Gas Ionizzati Del Cnr, ITALY	Librarian, Max-Planck-Institut, W. GERMANY
Dr. H. Yamato, Toshiba Res & Devel Center, JAPAN	Prof. R.K. Janev, Inst. of Physics, YUGOSLAVIA

**DATE
FILMED**

9 / 16 / 93

END