1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

MANUFACTURED TO AIIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

Safety Technology Section

**Steam Explosion Analysis
in Support of the SRS Reactor Safety Assessment (U)**

October 9, 1992

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

for
**Westinghouse Savannah River Company
P. O. Box 616
Aiken, SC 29802**

**Nuclear Reactor Technology
and Scientific Computations**

WSRC-RP-92-720

Project: PRA
Document: WSRC-RP-92-720
Title: Steam Explosion Analysis in Support of the
SRS Reactor Safety Assessment (U)

Approvals:

Brian Vanderfecht
B.E. Vanderfecht, Author

10/9/92
Date:

D.C. Smith
D.C. Smith, Author

10/14/92
Date:

P.G. Ellison
P.G. Ellison, Technical Reviewer

9/2/92
Date:

K.R. O'Kula
K.R. O'Kula, Manager

10/26/92
Date:

M.J. Hitchler
M.J. Hitchler, Manager

11/2/92
Date:

TABLE OF CONTENTS

PREFACE.....	1
1. INTRODUCTION	2
2. EXPLOSION INITIAL CONDITIONS	5
2.1 In-Vessel Scenarios	5
2.2 Ex-Vessel Scenarios	7
2.3 Input Variables	7
3. ALUMINUM EXPERIMENTS	13
4. REVIEW OF STEAM EXPLOSION MODELING.....	16
5. STEAM EXPLOSION BOUNDING MODEL	23
5.1 Modeling Approach.....	23
5.2 Results of the Bounding Model	26
6. NON-EQUILIBRIUM MODEL	28
6.1 Pre-Explosion Mixing	28
6.2 Explosion Model.....	28
6.3 Qualitative Description of the Non-equilibrium Model Codes.....	32
6.4 Results for the Non-Equilibrium Model	33
7. AREAS VULNERABLE TO STEAM EXPLOSION DAMAGE.....	35
7.1 In-Vessel Steam Explosion Vulnerabilities	35
7.2 Ex-Vessel Steam Explosion Vulnerabilities	36
8. DISCUSSION AND CONCLUSIONS.....	37
REFERENCES.....	39
APPENDIX A.....	43

LIST OF TABLES

Table 1. Case 1 Input values.....	8
Table 2. Case 2 Input values.....	8
Table 3. Case 3 Input values.....	9
Table 4. Case 4 Input values.....	9
Table 5. Case 5 Input values.....	10
Table 6. Case 6 Input values.....	10
Table 7. Case 7 Input values.....	11
Table 8. Case 8 Input values.....	11
Table 9. Input summary.....	12
Table 10. Ideal model results.....	27
Table 11. Non-equilibrium model results.....	34

LIST OF FIGURES

Figure 1. Phases of a Steam Explosion.....	3
Figure 2. One-dimensional Explosion Geometry.....	30
Figure 3. Fragmentation Process.....	32

PREFACE

This report has been constructed to document the steam explosion analysis for the K-reactor Probabilistic Risk Assessment (PRA). The analysis was developed during the period 1988-1990 by members of Science Applications International Corporation under contract from WSRC and by members of the PRA group at WSRC. The principal author of this report (B. E. Vonderfecht) joined the WSRC PRA group in 1991 after completion of this analysis. The authors wish to express thanks to P. G. Ellison for providing many review and editorial comments.

Analysis of PRA steam explosions has continued since completion of the work documented here. New information regarding fuel mixing in a pouring contact mode and regarding aluminum oxidation during a steam explosion has become available. The impact of this information on the PRA is being studied and will be discussed in future WSRC documentation.

1. INTRODUCTION

This report describes the application of two steam explosion models in support of the Probabilistic Risk Assessment (PRA) for the Savannah River Reactors. Theoretical models are required to estimate steam explosion yields in terms of kinetic energy, pressure shock and steam generated by the event. These quantities are used in the PRA to determine fission product barrier integrity in the reactor confinement following a hypothetical steam explosion.

The basic preconditions for a steam explosion are that hot molten material come into contact with water, and that the material's temperature be high enough to both support film boiling at its surface, and remain molten until an explosion is initiated. In a number of PRA accident sequences, aluminum-uranium debris will be hot enough to participate in a steam explosion. If the above preconditions are met, the molten material can break up into droplets suspended in the water, but separated from the liquid water by a thin layer of vapor formed at the droplet surfaces. The system can remain in this state for a period of time while the molten material and water mix due to density, and velocity differences. Such a mixture is metastable, however. If a pressure disturbance or "trigger" occurs, the vapor film may collapse in a local region of the mixture causing liquid-liquid contact. This contact will result in rapid heat transfer, raising the coolant temperature and the pressure of the coolant in the local region. The pressure disturbance propagates rapidly involving the entire mixture in the explosion and fragmenting the hot molten material. Fragmentation of the molten material results in very rapid transfer of heat from the debris to the water. Since the heat transfer occurs more rapidly than the water can expand, the water assumes a high temperature, high pressure thermodynamic state, confined only by its own inertia and the inertia of its surroundings. This water subsequently expands generating shock waves and accelerating material. The high pressure vapor produced, the shock waves, and the kinetic energy of material can all do destructive work on structures surrounding the explosion site. The evolution of the explosion from the mixing stage to triggering, fragmentation and expansion is schematically illustrated in Fig. 1.

Fuel melting is possible during several postulated severe accident scenarios for the SRS reactors. In many cases, water will exist in the reactor primary system and/or on the confinement building floor. Steam explosions are possible if molten core debris comes into contact with water. This might occur, for example, within the reactor vessel when the fuel melts within an assembly after it caddles down within the assemblies, or within the confinement building upon breaching of the primary system. The primary consequence of concern is that a steam explosion can result in physical damage to the primary system or confinement building, creating paths for fission product transport to the environment.

Coarse Mixing

Triggering/Fragmentation

Expansion

Fig. 1. Phases of a Steam Explosion

The large number of accident scenarios defined in the SRS PRA makes detailed analysis of each steam explosion scenario impractical. Thus, steam explosions must be characterized by a few significant parameters that can be addressed in the PRA. These parameters are the quantity of steam produced, and the amount of mechanical work performed. These quantities have been used to determine the effect of steam explosions on severe accident progression, and the potential release of radioactivity into the environment.

Practical considerations create conflicting demands that a model used in the PRA be both computationally efficient (to enable complete coverage of the limited, but not necessarily small set of explosions addressed in the PRA) and realistic (or give a best-estimate for the explosion behavior). Often used ideal thermodynamic models satisfy the efficiency criterion, but may greatly overestimate explosion magnitudes. On the other hand, an approach relying entirely on the experimental data is lacking since no experimental analogs exist for most of the PRA events. Indeed, an experimental program adequate for the PRA would be impractical to carry out because of the large scale of many PRA scenarios.

The present work solves these problems by employing both a bounding model based on the assumption of thermodynamic equilibrium within the explosion and a non-equilibrium model which accounts for irreversible processes to achieve more realistic results. These processes include heat transfer across temperature gradients between the explosion constituents and mechanical losses to the surrounding environment. The non-equilibrium model has been compared with existing experimental data (Oh87) and shows values for mechanical work much reduced from the equilibrium thermodynamic predictions in qualitative agreement with the experimental estimates.

This report is divided into 8 sections. Section 2 identifies the severe accident scenarios that might result in a steam explosion. Scenarios are based upon analysis of severe accident progression in the Level II PRA. The PRA is sufficiently detailed to allow the initial conditions for steam explosions to be estimated. Short reviews of steam explosion experiments and modeling are contained in sections 3 & 4. Upper bounds and best estimates of the basic measures of steam explosion magnitude for each scenario are presented in sections 5 and 6 respectively where the theory behind the two models is also summarized. These measures are: conversion of thermal energy to mechanical work, production of steam, and peak explosion pressure. Areas of concern for mechanical failure are also identified in section 7. Section 8 summarizes the analysis and draws conclusions. This work forms the basis for an evaluation of the effect of steam explosions on structural components in the reactor and contributes to the understanding of post-explosion accident progression.

2. EXPLOSION INITIAL CONDITIONS

The following scenarios determine the initial conditions used as input for the model calculations. Estimates for the quantity and temperature of molten debris and water involved, the geometry of the confining structure, and the mass of the overlying water slug were obtained depending on the particular plant damage state in question.

The assumptions employed in obtaining initial conditions are those employed in the accident analyses that have been performed in support of the PRA. The basic assumptions made are:

1. A Mark-22 charge is assumed to be operating at 2500 MW when the accident occurs.
2. Decay heat in the charge is consistent with a significant fuel burn-up (1060 MWD per assembly).

2.1 In-Vessel Scenarios

Case 1 (Single Assembly LOPA): During some accident progressions, the fuel assemblies will fill with steam while the moderator region of the vessel remains filled with water. This may occur, for example, during a LOPA without ECCS actuation. After the fuel assemblies dry out (i.e., fill with steam), the fuel tubes in the assembly will melt. As the tubes melt, the molten debris will relocate to the assembly BEFs. Water will be present in the BEF, creating the potential for small-scale steam explosions with only a few grams of debris participating. These would probably be indistinguishable from the rapid steam generation associated with debris quenching. At most they may fail the BEF. If the BEFs fail, either as a result of contact with hot debris or from a small steam explosion, molten debris from the melting fuel and target tubes would flow into the moderator, creating conditions for a steam explosion. Although a LOPA will likely involve most of the fuel assemblies in the core, no mechanism (other than recriticality) couples melt progression between individual assemblies. Thus, individual assembly BEFs would fail at slightly different times. This slight incoherency leads to the assumption that only the mass of molten fuel in one assembly would participate in a single steam explosion.

Case 2 (LOCA with Late ECCS): In some accident progressions, the water will drain from the reactor vessel, and the fuel will melt in an empty vessel. This occurs, for example, in a LOCA without ECCS actuation. As fuel melts, it will relocate to the bottom of each assembly and melt through the assembly BEF wall. It is possible that the debris will remain in a pool on the bottom of the reactor vessel for a brief period of time. If the ECCS is

recovered during this time period, water will be injected onto the pool of molten debris (stratified configuration).

Case 3 (Reactivity Insertion Accident - RIA): Under some circumstances, the fuel assemblies may rapidly melt in place while coolant is flowing in the assembly. A typical event of this type is a transient resulting from the inadvertent withdrawal of a control rod. The fuel tubes in six assemblies surrounding the affected septifoil could rapidly increase in power. Heat generation will increase to the point that either flow instability or burnout would occur. The surface of the fuel tube would subsequently transition into film boiling. Once this happens, the fuel tubes melt while water is still flowing in the coolant channel (i.e., an inverted-annular flow regime is established). A steam explosion may occur within the assembly under these conditions. (Cl91)

Case 4 (LOPA Recriticality): When the moderator region of the vessel contains water, debris from the melting fuel assemblies may be cooled inside the BEF. The debris would form cooled cylinders of debris separated by moderator. The analysis described in Ref. (Cl91) has shown that this configuration may be critical when a sufficient amount of fuel relocates into each BEF. The associated production of fission power will rapidly raise the debris temperature, and BEF failure and relocation of the debris into the moderator will occur as the debris temperature rises. At the time of BEF failure, the debris would be at a much higher temperature than in the less likely case that the debris does not initially freeze within the BEF. In addition, many of the debris columns would melt simultaneously, so a large coherent steam explosion could result.

Case 5 (RIA & Power Excursion): A steam explosion may not occur when the fuel tubes melt in the flow stream, as discussed in Case 3. This may be the case, for instance, if the debris particles are solid, or if no trigger occurred. In this event, the debris particles may be swept out of the BEF and into the moderator space. Convection within the moderator may then carry the debris fragments up into core region of the reactor. These fragments may have a high reactivity worth in this configuration, since they are no longer shielded by the target material, and they are more homogeneously mixed with the moderator. A power excursion may result that could cause melting of fuel in some or all of the assemblies. This material could mix with the flow stream within the assemblies and might produce a large coherent steam explosion.

2.2 Ex-Vessel Scenarios

Case 6 (Outlet Piping): In several of the accident scenarios, molten debris will eventually accumulate on the reactor vessel bottom. This debris will spread out on the bottom and may flow through the outlet nozzles into the effluent piping to the pump. For most accident scenarios, water will be present in the outlet piping at this time, because the outlet legs of the piping loops are the lowest points in the primary system. There is no heat source term to boil the water away. A steam explosion can occur when debris encounters water in the piping or in the pump.

Case 7 (Pump Room Floor): An ex-vessel steam explosion may occur if the primary system is breached by hot debris. Debris in the reactor outlet piping may fail the piping and fall onto the pump room floor or debris on the reactor vessel bottom may be blocked from flowing into the outlet piping if it freezes in the effluent piping nozzle muff structure. If this occurs, the debris will heat up on the reactor vessel bottom and eventually fail the bottom shield. The likely mode of failure of the bottom shield is collapse of the shield as a whole. (Ob89) If it collapses, the entire shield, as well as the molten debris, will fall into the pin room below the reactor vessel. The debris will then flow across the floor into the pump room. In either event, a large portion of the reactor fuel inventory will be deposited on the pump room floor. The pump room floor will be covered with water in many scenarios. A steam explosion may result when the debris enters this water.

Case 8 (Pump Room Sump): If a steam explosion does not occur when the debris runs onto the pump room floor, it is expected to run into the trenches in the floor, and be channeled into the sumps. If the sumps are filled with water, a steam explosion may occur.

2.3 Input Variables

Tables 1-9 list the values of the input variables used for the models and briefly discuss how each value was obtained. These represent nominal input values for each of the accident sequences described above. Realizations of these sequences found in the Level 2 PRA accident progression event tree (APET) may contain somewhat different values for fuel mass, fuel temperature and coolant depth. By using the results of sections 5 and 6, qualitative judgements were made for the effects of variations on the nominal events. Ideally, a model calculation would be carried out for every steam explosion event in the APET. In practice, however, this would require a prohibitively large number of calculations.

Table 1. Case 1 (Single Assembly LOPA) input variables.

Initial Condition	Value	Description
Debris Mass (kg)	32.6	Each assembly contains 20.9 kg of fuel and 11.7 kg of target . All fuel and target material in one assembly is assumed to participate. Explosions in various assemblies are not expected to occur simultaneously and should not be coherent.
Debris Temperature (K)	950	Data from Ref. EH90 suggests that unirradiated fuel relocates near this temperature. However, due to effects associated with irradiation and geometry, relocation temperature is not precisely known.
Water Temperature (K)	323	The temperature of the moderator water was predicted by thermal- hydraulic analysis (see Ref. Lo89).
Water Depth (m)	.83	The height of the column of molten debris in the BEF defines the water level which mixes with the debris at the time of BEF failure.
Water Pool Area (m ²)	.046	The area occupied by a single assembly
Overlying Slug Mass (kg)	153.6	Column of water in the reactor vessel above the above the area of the relocated fuel.

Table 2. Case 2 (LOCA with Late ECCS) input variables.

Initial Condition	Value	Description
Debris Mass (kg)	14080	Complete fuel and target inventory in the reactor.
Debris Temperature (K)	950	Data from Ref. EH90 suggests that unirradiated fuel relocates near this temperature. However, due to effects associated with irradiation and geometry, relocation temperature is not precisely known.
Water Temperature (K)	323	ECCS water is at ambient temperature.
Water Depth (m)	0.75	Water level assumed to participate in the explosion.
Water Pool Area (m ²)	19.2	Reactor vessel area.
Overlying Slug Mass (kg)	18638	Quantity of water assumed to be injected by ECCS before the explosion which does not participate in the explosion.

Table 3. Case 3 (Reactivity Insertion Accident - RIA) input variables.

Initial Condition	Value	Description
Debris Mass (kg)	125	Fuel inventory in six assemblies. Assemblies surrounding the control rod melt coherently. Targets do not melt.
Debris Temperature (K)	950	Data from Ref. EH90 suggests that unirradiated fuel relocates near this temperature. However, due to effects associated with irradiation and geometry, relocation temperature is not precisely known.
Water Temperature (K)	350	Based on a thermal-hydraulic analysis (Ref. Lo289), temperature of the water in the fuel tube channel will vary between 323 and 390. For this calculation, an average value was assumed.
Water Depth (m)	0.15	Water level assumed to participate in the explosion.
Water Pool Area (m ²)	0.32	Cell area occupied by six assemblies.
Overlying Slug Mass (kg)	53	Water in the six assembly channels not participating in the explosion.

Table 4. Case 4 (LOPA Recriticality) input variables.

Initial Condition	Value	Description
Debris Mass (kg)	2160	Recriticality is expected to occur when 23% of the fuel inventory has relocated into the BEF. (Cl89)
Debris Temperature (K)	2000	Fuel temperature at time of BEF failure is based on analysis in report SAIC 90/6501. (Cl89)
Water Temperature (K)	323	The temperature of the moderator water was predicted by thermal- hydraulic analysis.
Water Depth (m)	.25	The height of the molten fuel column at time of recriticality defines the water level participating in the explosion. (Cl89)
Water Pool Area (m ²)	19.2	Reactor vessel area.
Overlying Slug Mass (kg)	11196	Water in the reactor vessel not participating in the explosion.

Table 5. Case 5 (RIA & Power Excursion) input variables.

Initial Condition	Value	Description
Debris Mass (kg)	9000	Entire fuel inventory is assumed to melt during the power excursion.
Debris Temperature (K)	950	Data from Ref. EH90 suggests that unirradiated fuel relocates near this temperature. However, due to effects associated with irradiation and geometry, relocation temperature is not precisely known.
Water Temperature (K)	350	The temperature of the moderator water was predicted by the thermal- hydraulic analysis. (Lo289)
Water Depth (m)	.15	Water level assumed to participate in the explosion.
Water Pool Area (m ²)	19.2	Reactor vessel area.
Overlying Slug Mass (kg)	87360	Water in the reactor vessel not participating in the explosion.

Table 6. Case 6 (Outlet Piping) input variables.

Initial Condition	Value	Description
Debris Mass (kg)	7040	An upper bound is the pipe volume. The outlet pipes are .61 m nominal diameter and the longest one is approximately 12 meters. It could contain 3.5 m ³ or about half of the debris from a full core melt.
Debris Temperature (K)	950	Data from Ref. EH90 suggests that unirradiated fuel relocates near this temperature. However, due to effects associated with irradiation and geometry, relocation temperature is not precisely known.
Water Temperature (K)	308	Ambient temperature on the pump room floor.
Water Depth (m)	2.86	Water level assumed to participate in the explosion.
Water Pool Area (m ²)	0.193	Outlet pipe cross-section.
Overlying Slug Mass (kg)	44.83	Water in the pipe not participating in the explosion.

Table 7. Case 7 (Pump Room Floor) input variables.

Initial Condition	Value	Description
Debris Mass (kg)	14080	Full core melt.
Debris Temperature (K)	1470	Failure temperature of the stainless steel outlet piping.
Water Temperature (K)	308	Ambient temperature on the pump room floor.
Water Depth (m)	2.0	Water level in pump room can vary from .2 m to 6 m depending on accident conditions. An average value of 2 m is assumed.
Water Pool Area (m ²)	30.0	Area of floor below pipe break assumed to define the explosion zone.
Overlying Slug Mass (kg)	9336	Water on the floor not participating in the explosion.

Table 8. Case 8 (Pump Room Sump) input variables.

Initial Condition	Value	Description
Debris Mass (kg)	14080	Full core melt.
Debris Temperature (K)	950	Data from Ref. EH90 suggests that unirradiated fuel relocates near this temperature. However, due to effects associated with irradiation and geometry, relocation temperature is not precisely known. Fuel should be near relocation temperature upon entering sump.
Water Temperature (K)	308	Ambient temperature on the pump room floor.
Water Depth (m)	1.65	Depth of sump.
Water Pool Area (m ²)	13.3	Area of sump floor.
Overlying Slug Mass (kg)	1871	Water on the floor not participating in the explosion.

Table 9. Input summary.

Initial Conditions	Case 1	Case 2	Case 3	Case 4
Debris Mass (kg)	32.6	14080	125	2160
Debris Temperature (K)	950	950	950	2000
Water Temperature (K)	323	323	350	323
Water Depth (m)	.83	0.75	.15	.25
Water Pool Area (m ²)	0.046	19.2	0.32	19.2
Overlying Slug Mass (kg)	153.6	18638	53.0	11196

Initial Conditions	Case 5	Case 6	Case 7	Case 8
Debris Mass (kg)	9000	7040	14080	14080
Debris Temperature (K)	950	950	1470	950
Water Temperature (K)	350	308	308	308
Water Depth (m)	0.15	2.86	2.0	1.65
Water Pool Area (m ²)	19.2	0.193	30.0	13.3
Overlying Slug Mass (kg)	87360	44.83	3336	1871

3. ALUMINUM EXPERIMENTS

A number of experiments have been performed to study aluminum/water steam explosions. This section provides a brief survey of the existing data and discusses its applicability to PRA scenarios. Results of these experiments have been used in the PRA where possible. However, with exceptions noted below, applicability of the data has been limited to the identification of qualitative thresholds and trends in triggering probability and explosion magnitude. Prototypic experiments have not been performed for any of the steam explosion scenarios considered in the PRA.

Small scale experimental studies involving 10-20 gram drops of molten aluminum or iron oxide have been performed by Nelson and collaborators at Sandia National Laboratories. (ND81, ND92) These tests provide the most detailed results to date for aluminum/water steam explosions. The data gathered included high speed film records, pressure history in the interaction vessel, and detailed analysis of debris generated. This allowed quantitative estimates of trigger pulse strength, interaction energy yields and hydrogen generation. The small-scale single-droplet FCI model developed by Kim (Ki87) was based in-part on the high speed film data from Nelson's tests. Part of Kim's model attempts to describe the time dependent and cyclic growth and collapse of vapor bubbles around single fuel drops as observed in Nelson's tests. The single droplet model was in-turn used as a basis for fuel fragmentation in the large scale FCI model developed by Oh (see section 6). It is Oh's model which was applied in the PRA.

Due to concern over foundry accidents, many experiments have been sponsored by the aluminum industry to determine conditions which are likely to trigger a steam explosion. (Lo51, Le80, Al82, Br76) These represent the largest scale tests to date with melt masses ranging into the 10's of kilograms. However, results consisted primarily of judgements by the investigator (assisted by high speed photography in Lemmon's study (Le80)) as to whether or not an explosion occurred. Alexander et. al (Al82) attempted to measure explosion energetics, but the method used suffered from large uncertainties and may only be useful for comparisons within the test series. Briggs conducted a series of tests at Winfrith with 10-20 kg of aluminum. Brigg's high speed films showed that a region of premixed fuel was established in the lower half of the tank before an explosive interaction was initiated at the bottom of this mixture. This rapid interaction front propagated through the premixed fuel with a velocity around 200 m/s. A similar model for propagating an explosion through a premixed region was developed for Oh's large scale steam explosion model. Explosion efficiencies were calculated to be in the 10% range based on measured pressure history in the tank. In summary, the aluminum industry sponsored work has tended to confirm observations made on actual plant accidents that large-scale damaging explosions are possible

and that triggering probability for such explosions increases with water subcooling, pour-stream diameter, and fuel temperature.

Morin conducted tests in which unirradiated SRS reactor fuel was melted in a fuel assembly housing with water flowing in the assembly housing as expected during reactor operation. (MH89) The tests were designed to simulate a reactor transient from the accidental withdrawal of a control rod as described in case 3 above. Molten fuel was carried along with the flow stream exiting the fuel assembly BEF. Measurements were made of debris particle size and production rate as the molten fuel exited the BEF. The debris production rate was used to analyze the reactivity transient for the PRA (CI91) and to estimate the likelihood of a steam explosion in the assembly during the transient. No explosions occurred in the tests.

Several destructive reactivity excursions (both planned and accidental) leading to steam explosions have occurred in aluminum-uranium fueled test reactors. (Es64, MS63) In particular, the SPERT-1 destructive test was well instrumented and the data suggest that a violent pressure pulse (signifying a steam explosion) destroyed the reactor vessel several milliseconds after the planned reactivity excursion ended. Relatively little aluminum oxidation was observed in the analysis of the Spert-1 test debris. Since the fuel temperature at the time of the steam explosion was estimated to be around 1200 K, the lack of fuel oxidation supports the notion that aluminum/water steam explosions are unlikely to be driven by chemical oxidation at these temperatures (see section 8). In general, the tests lend credibility to the idea that in-vessel steam explosions can be generated by reactivity transients where fuel rapidly melts in place. In such events the mechanism for mixing fuel and water may not be a pour mode (as in most experiments to date) and could disperse fuel with high efficiency if water in coolant channels is trapped and vaporizes between molten fuel elements. However, even the well instrumented SPERT-1 test is directly applicable in quantitatively assessing the magnitude of large scale explosions from reactivity transients in SRS reactors, since accurate estimates of initial conditions and energy yields are difficult to obtain from the test data.

Steam explosion tests were performed as part of the K-Reactor restart program. (Gr92, Ch91) As much as 1 kg of lithium-aluminum control rod material just above the melting point was poured into a septifoil housing containing water. No explosive events were observed in a total of 20 tests lending further support to the difficulty of initiating explosions involving small quantities of fuel with little or no superheat. Thus, in the PRA, one may expect a low probability for triggering an explosion in a water filled BEF as fuel melts and runs down the fuel assembly housing during a LOPA.

A series of tests were conducted by Rightley and Beck at Sandia National Laboratories attempting to quantitatively study the fuel threshold temperature at which chemical oxidation of the fuel makes an important contribution to the explosive nature of the interaction. Six tests were

performed in which molten aluminum alloy at temperatures from 1000 K to 1544 K with mass ranging from 2 to 10 kg was dropped into a vessel containing $\sim 1\text{m}^3$ of room temperature water. Equivalent high-explosive (HE) energy yields were estimated for each test based on high speed film data, pressure histories, and post-test debris examination. Three of the tests resulted in violent explosions (yield greater than available thermal energy) believed by the investigators to involve significant chemical oxidation of the aluminum fuel during the explosion phase. Two tests with fuel at 1000 K did not produce a violent explosion leading the investigators to postulate a threshold temperature of 1150 K. Preliminary analysis of debris collected from one test in the series indicated that 30%-40% of the fuel was oxidized during the entire fuel quenching process. Further discussion of the Sandia tests is found in section 8.

Experiments have been conducted to study explosions which occur in a stratified geometry as in Case 2 (LOCA with late ECCS) above. Bang, et al. (BC91) conducted well instrumented tests using liquid natural gas and water or Freon and water instead of molten aluminum and water. They measured the amount of fuel involved and found that, independent of the scale, only a couple of centimeters at the surface of the fuel participated. An empirical correlation was developed by Bang and Corradini (BC91) that reproduced the results of these and other stratified geometry experiments. This correlation was used to estimate the mass of mixed fuel in the non-equilibrium model (see section 6) for case 2.

To summarize, the experimental data on aluminum/water steam explosions have been utilized in the PRA by providing qualitative information on triggering probabilities for small explosions, trends in triggering probability and yield as the scale of the interaction increases, and thresholds for chemical oxidation effects. Also, observations of small scale interactions have provided the basis for the large scale steam explosion model which was used to quantify the PRA. However, this data does not provide definitive answers to the questions of triggering and yield for the very large scale events considered in the PRA. Empirical answers to these questions must remain uncertain due to the impracticality of conducting prototypical experiments on such a large scale. Triggering of large scale explosions, although possible, is far from certain. Data from the aluminum industry and the Sandia tests show that melt/water mixing can be effective in produce violent explosions for fuel masses in the 10 kg range, but other evidence (Ga86) suggests that a pouring contact mode may become inefficient at larger scales. (i.e., mixing may scale more like the surface area of the pour rather than the volume or may occur in a stratified contact mode sharply limiting the percentage of mixed fuel) Nevertheless, due to the complex mode of interaction expected in some of the PRA scenarios (e.g., BEF recriticality, power excursion) large scale mixing may be much enhanced compared to a pouring contact mode.

4. REVIEW OF STEAM EXPLOSION MODELING

In order to place in context the steam explosion models used in the PRA, a short review of modeling efforts to date is contained in this section. Vapor explosion modeling began nearly three decades ago so the literature is extensive. Exhaustive reviews are available in references (FA90) & (Co88). This discussion will be limited to descriptions and comments on the major categories of models selected from the above references. Following experimental observations on explosion evolution discussed in section 1, models may be conveniently divided into:

1. Coarse mixing or Pre-explosion mixing models.
2. Fragmentation models.
3. Large-scale propagation and Expansion models.

Pre-explosion Mixing

Early studies of pre-explosion mixing aimed at placing bounds on the quantity of fuel allowed to premix. These studies were partly motivated by the prospect that such bounds would restrict the size of large-scale explosions that could occur in reactor accidents thus limiting the damage potential of these explosions. Cho et. al (Ch76) calculated the frictional dissipation energy required to break large fuel droplets into smaller diameters. His analysis consisted of parametric studies of required mixing energy given initial and final fuel diameters. The results indicated that, for parameter values expected in a reactor accident, the mixing energy was much smaller than the thermal energy available in the fuel. Thus, mixing energy does not provide a strong restriction on the mass of mixed fuel.

Further bounds on fuel/coolant mixing were suggested by Henry and Fauske (HF81a, HF81b) who postulated that for a vapor explosion to occur, fuel must mix as particles in a continuum of liquid coolant separated from the coolant by a vapor film. For a given fuel mass and droplet diameter they calculated the pool boiling critical heat flux and equated this with energy lost due to steam flow out the top of the pool to determine whether water could remain mixed with the fuel or would be swept out (fluidized) by the steam generated. However, application of this model to light water reactor scenarios revealed that the steady-state pool boiling critical heat flux resulted in very small quantities of mixed fuel (~100 kg). Subsequently, Park and Corradini (Pa89) extended the Henry and Fauske model by estimating the heat flux at the first onset of coolant fluidization rather than using the steady-state correlation. This lead to more realistic predictions of one or a few metric tons of mixed fuel when applied to initial conditions appropriate to a German pressurized water reactor. (Pa89) Park and Corradini also introduced a correction to account for the effect of coolant subcooling which indicated that mixing may be significantly enhanced for large subcooling. The above models are appealing since they simplify the complex transient and multidimensional nature of the mixing process with

criteria based on 1-dimensional and steady-state arguments. Because of its calculational simplicity, the model of Park and Corradini was used to estimate mixing for the PRA and is further discussed in section 6.

In contrast to the above fluidization limits, some investigators have envisioned the mixing process as a transient one driven by hydrodynamic breakup of the molten fuel jet. Theofanous and Saito (TS82) modeled jet breakup using Kelvin-Helmholtz surface instabilities, Rayleigh breakup of the jet into discrete masses, and Taylor breakup of the discrete masses. They predicted that only a few percent of available fuel (a few metric tons) could mix for in-vessel light water reactor accident scenarios. However, it was later pointed out by Epstein and Fauske (FE85) that Rayleigh breakup of the fuel jet may not take place under conditions likely in a reactor accident. Also, the Theofanous and Saito model does not account for coolant fluidization during mixing.

Models have been developed which take into account the two-dimensional transient nature of the mixing phenomenon. Bankoff et. al (Ba84) used a two-fluid two-dimensional hydrodynamics code to model mixing of a predetermined array of fuel droplets entering the coolant pool. Their results illustrated the effect of coolant fluidization as void was generated in the mixture. Since a prefragmented array is used as input to the model and mechanisms for jet breakup and fragmentation are not addressed, the model should be viewed as a parametric study of mixing efficiency for various fragment sizes. It is possible to include both fluidization effects and hydrodynamic jet breakup in a single model. This may be important since experimental observations show that for thick jets only the leading edge of the jet undergoes breakup. Thus, the fluidization models above may overpredict the effective volume of fuel which fragments and participates in pool boiling and coolant sweep-out. Chu and Corradini have developed a transient one-dimensional mixing model based on the TEXAS code which also includes dynamic fuel fragmentation due to Rayleigh-Taylor instabilities. The model was applied to a set of non-explosive tests at the Sandia FITS facility and the results were compared to the debris recovered from the tests. In one application of Chu's model to light water reactors, less than 20% (~3 metric tons) of fuel mixed before the jet reached the container bottom and roughly half of this mixed fuel was located in a vapor rich region which might not support the propagation of an explosion. Some aspects of the mixing process, such as two-dimensional coolant circulation and non-homogeneous void production, are lost to TEXAS since it is a one-dimensional model. A two-dimensional transient mixing model which includes dynamic fuel breakup has been developed by Young (Yo87) which offers the possibility of combining the advantages of both Bankoff's and Chu's analysis.

Fragmentation

Fuel fragmentation enables the rapid heat transfer which drives a steam explosion. Because of its importance, it has been the focus of much study and a host of mechanical fragmentation models have been proposed. As discussed in the previous section, a number of small scale experiments involving single drops of fuel have been performed in an effort to study fragmentation as a separate issue from other stages in a steam explosion. Fragmentation models have been tested against these observations and several have been incorporated into large scale simulations of the explosion propagation and expansion process (some of these will be discussed further below). The various models can be broadly categorized as either: 1) hydrodynamic fragmentation due to external surface forces exerted by relative velocities between different liquids in the explosion or 2) thermal fragmentation due to coolant vapor generation on the surface or in the interior of the fuel drops.

Hydrodynamic fragmentation can occur due to Rayleigh-Taylor instabilities in the boundary between liquid fuel and coolant when this boundary is accelerated in the direction of the fuel. A number of investigators have included Rayleigh-Taylor breakup mechanisms driven by drag forces or pressure pulses. However, estimates of the timescale for Rayleigh-Taylor breakup show that it may not be short enough to support a detonation shock wave required by some propagation models. Kelvin-Helmholtz surface instabilities due to relative velocities parallel to the surface of the liquid-fuel/liquid-coolant boundary have been considered as a hydrodynamic fragmentation mechanism. Also, boundary layer stripping in which the boundary layer of a fuel drop under high velocity flow suddenly detaches and fragments into a fine mist has been applied as a fragmentation mechanism. There is experimental evidence that hydrodynamic fragmentation plays a small role early in the explosion propagation. Armstrong (Ar70) performed experiments in which molten tin displayed enhanced fragmentation above a certain temperature threshold corresponding to maximum-heat-flux region of nucleate boiling in the mixture. The temperature threshold was found to be virtually independent of the melt entry velocity suggesting a thermal rather than hydrodynamic cause for enhancement. However, as the explosion progresses, relative velocities may grow large enough that hydrodynamic fragmentation becomes important.

Thermal fragmentation is thought to be initiated by the growth and collapse of vapor bubbles at the surface of the fuel drops. The kinetic energy of vapor bubble collapse has been studied as a measure of the potential for fragmentation. Other work has focused in on the specific mechanisms possible for the transfer of this bubble energy to the fuel drop. For example, Caldarola and Kastenbergh described bubble growth using the Rayleigh equation and then postulated that during collapse, microjets of coolant formed at the surface of the bubble, impinged upon the fuel and transmitted energy to the fuel drop in the form of an acoustic wave. This mechanism

yielded a very small fraction of bubble energy transmitted to the fuel and is insufficient to account for fragmentation. Fauske proposed in 1973 that if the fuel temperature was above the spontaneous nucleation temperature, the result of liquid-liquid contact upon vapor bubble collapse would be vaporization of coolant with enough violence to support a shock wave to propagate the explosion. In apparent contradiction of the Fauske model, experiments performed by Armstrong in 1970 showed significant fragmentation even for fuel/coolant contact temperatures well below the temperature for spontaneous nucleation. It is also possible that pressures generated internally may cause droplet breakup. As mentioned in the previous section, the model developed by Kim (Ki85) proposes that fragmentation occurs as the result of coolant jet penetration into fuel upon collapse of the vapor bubble. The entrained coolant undergoes rapid vaporization and fragments a portion of the outer surface of the drop as it expands. Kim's fragmentation model formed the basis for the large scale propagation and expansion model used in the PRA (see section 6).

Large-Scale Propagation and Expansion

In order to calculate damage potential, steam production and hydrogen production for the PRA, a model is needed which predicts the propagation of fragmentation and shock waves and ultimately the expansion of the high pressure mixture generated by the explosion. A number of models have been developed which fit this description and they can be categorized as follows: 1) Thermodynamic models reduce the fragmentation and heat transfer processes to a simple equilibrium criterion. These are the most simple expansion models. The application of a thermodynamic model to the PRA is described in the next section. 2) Parametric explosion models which attempt to include fragmentation rates using empirical correlations. 3) Mechanistic explosion models that incorporate one or more of the fragmentation models discussed above and base heat transfer on material properties and simplified time dependence and geometry assumptions. 4) Detailed multi-dimensional expansion models which employ general hydrodynamics codes coupled with very simple fragmentation mechanisms (perhaps just initial conditions from some fragmentation model or experimental extrapolation).

Parametric models typically make simple assumptions for the fuel fragmentation process. For example, in the model of Cho and Wright (CW74), the surface area of the fragmented fuel available for heat transfer is assumed to increase at an exponential rate. Parameters are the characteristic time for the exponential decay and the final fragmented area as determined by the final fuel diameter. Temperature can differ between fuel and coolant in the model, but the entire mass of fuel is taken to be at a single temperature as is the mass of coolant. Vapor generation is calculated from the thermodynamic equilibrium state for the coolant instead of considering excess energy deposited near the surface of the fuel coolant interface. This tends to underestimate the vapor production especially early in the explosion when the bulk coolant temperature has not

changed much. Caradarola (Ca75) developed a similar model which considered the heat transfer effect of the vapor film around the fuel drops. Caradarola's model also assumed a linear fragmentation rate. Most parametric models are limited (as are the Cho and Caldarola models) by the assumption of equilibrium in the coolant phase and do not account for effects of heating and non-equilibrium vapor generation at the fuel/coolant interface.

Parametric models have been used primarily for analyzing experiments or to perform sensitivity studies on experimental parameters. To be a useful predictive tool, a defensible basis must exist for choosing model parameters for a particular simulation. This would be difficult for the PRA since initial conditions for many scenarios lie well outside the bounds of the experimental data. However, from a historical perspective, parametric models have provided valuable insight into the important phenomenon governing explosion behavior (e.g., fragmentation time and size, or fuel-to-coolant mass ratio) and have helped to focus the analysis of more detailed mechanistic models which are discussed below.

Mechanistic models for the explosion propagation are based on explicit physical mechanisms for generating a shock wave and fragmenting fuel. High speed photography records of steam explosions reveal that propagation is closely related to the development of a shock wave which travels through the mixture. A steady state shock wave detonation model was developed by Board and Hall (BH74) based on analogy with chemical explosions. The model sidestepped the details of fragmentation behind the shock wave by assuming fuel was fragmented so efficiently, that equilibrium between the coolant and fuel was achieved behind the shock. This allowed a simple solution to the model that depended only on thermodynamic properties of the medium in front of and behind the shock wave, and standard hydrodynamics conditions for a detonation wave taken from chemical explosion theory. Due to the equilibrium condition, the model predicts extremely high pressures and energy conversion ratios not observed experimentally. This difficulty prompted others to develop variations on the Board and Hall steady-state shock propagation theory. For example, Sharon and Bankoff (SB81) constructed a steady-state model which relaxed the assumption that complete fragmentation occurred behind the shock wave. Thus, they introduced a rate process into the model to describe fragmentation. Fragments produced were still assumed to reach instantaneous equilibrium with the coolant, but the heat transfer reduction provided by the fragmentation rate allowed steady-state conditions to be achieved with much lower pressures than in the Board and Hall model. The steady-state model calculations described above were primarily directed at determining conditions necessary for achieving a detonation wave rather than estimating quantities important to reactor safety issues such as energy conversion efficiency.

Another class of mechanistic models has focused on solution of approximations to the transient hydrodynamics describing the explosion

(the non-equilibrium model described in section 6 falls into this category). Corradini (Co82) modified a one-dimensional multiphase code developed by Lawrence and Mason. The modified model included a thermal fragmentation mechanism driven by coolant jet impingement on the fuel droplets. Results of this analysis indicated that steady state conditions assumed in the models above were difficult to reach, especially as the initial void fraction in the mixture increased. Also, with a purely hydrodynamic fragmentation mechanism, the model was incapable of propagating an explosion for a small trigger pulse. The main limitation of the model for reactor safety applications was that it only considered a continuous coolant phase and could not calculate the expansion phase of the explosion where the void fraction is high. A number of other one-dimensional transient models based on hydrodynamic fragmentation mechanisms have been developed. They have been used to analyze the effects of high void fraction, inhomogeneities, and cylindrical or spherical geometries on propagation in the mixture. Results have tended to confirm that a large trigger pulse is required for propagation using hydrodynamic fragmentation mechanisms.

Two of the transient mixing models described earlier have been modified to include a fragmented fuel component in the hope of creating a single model to describe all phases of the steam explosion. The IFCI code developed by Young now includes a fragmented fuel component with its own velocity and temperature field. Also, the one-dimensional mixing model developed by Corradini et. al based on the TEXAS code has been augmented to include a simple fragmentation mechanism. Due to the increase in computational demand necessary to simulate a detonation wave, these models may not be appropriate for applications such as the present one where a number of scenarios must be analyzed.

Some investigators have focused on complex multi-dimensional effects in the expansion phase of the explosion with sophisticated multi-dimensional hydrodynamics codes. These aspects are relevant for reactor safety studies since the potential for structural damage may be reduced due to non-uniformities in pressurization during expansion. Coddington and Staniforth (CS80) applied the SIMMER code to study the Winfrith Thermir experiments. SIMMER required the input of a mechanistic model to describe fuel fragmentation and heat transfer. Application of this model in the Zion LWR probabilistic safety analysis demonstrated that the two-dimensional nature of an in-vessel explosion reduced the pressure pulse on the vessel head. In other work, Corradini (Co81) incorporated a simple explosion model into the CSQ hydrodynamics code. This model assumed that fuel and coolant during propagation can reach thermal equilibrium before the system expands significantly. Heat added to the coolant by the fuel was treated by CSQ in a manner analogous to the heat of reaction in a chemical explosion. The above analyses do not describe the complete propagation and expansion process and require input representing the initial conditions for expansion at the end of the propagation phase. This input must be obtained from a separate model for propagation or reconstructed from experimental data. For PRA applications, this would

imply a significant increase in effort compared to the use of a zero-dimensional propagation and expansion model.

5. STEAM EXPLOSION BOUNDING MODEL

This section presents the simplified steam explosion model used to calculate the upper bound on the magnitude for steam explosions in the scenarios above. The section is divided into two parts. The first part discusses the approach taken to model the steam explosion. Further details on the detailed formulation of the model and implementation of the model as a computer program are contained in appendix A. Results of applying the model to the scenarios presented in section 2.

5.1 Modeling Approach

The basic phases of a steam explosion that must be modeled are: mixing, triggering, explosion, and expansion. The physical mechanisms involved in each of these phases is described below. The simplified approach to modeling each phase is also described, with an explanation for why the approach bounds the actual phenomena.

Mixing

Mixing occurs when hot molten debris comes into contact with water. When this happens, the molten debris will break up into droplets due to density and velocity differences between the two fluids. If the molten debris is hot enough, film boiling will exist on the surface of the droplets, limiting the heat transfer from the droplet to a relatively low value, and the droplets will remain molten. Debris in this condition can participate in an explosion. Several theories have been proposed that establish limits on the quantity of debris that can be suspended in this fashion. These theories are based on fluidization limits, or detailed modeling of the forces that break up and suspend droplets. These models depend to some extent upon modeling assumptions that are more or less controversial. To produce a bounding estimate, this difficulty will be avoided by assuming all of the debris that is available will mix with water and participate in the explosion.

Triggering

Molten debris, mixed with water, that is undergoing film boiling, is in a metastable condition. The steam film is a barrier that prevents rapid transfer of heat to the water. Steam explosions occur when a mechanism, called a "trigger," causes liquid coolant contact with liquid fuel somewhere in the mixture. A trigger is a pressure disturbance that forces liquid across the steam film, or collapses the steam film on a droplet of molten debris. Rapid heat transfer when the water comes into contact with debris superheats the liquid to a high-temperature, high-pressure thermodynamic state constrained by only its own inertia and the inertia of the surrounding fluid. This causes a pressure pulse that collapses the steam film throughout the entire mixed region and initiates the explosion.

The timing of the trigger is important. In many cases debris is being added to a pool of water at some rate. The quantity of debris that participates in an explosion is limited to the debris present when a trigger first occurs. The timing of the trigger therefore limits the amount of debris that can participate in an explosion. Triggering of an explosion is known to depend upon many things. Some theories assume triggering occurs when a stream of molten debris poured into a water pool, contacts the bottom. There is experimental evidence that suggests that this is generally the case. Evidence also indicates that triggering is dependent upon many other things as well, however, and that in some cases the trigger may be delayed for an extended period of time. For the purpose of the simplified model, it will be assumed that the trigger always occurs, but only after a maximum amount of debris is allowed to mix.

Explosion

The explosion phase is the period of time during which rapid heat transfer from the debris to the water occurs. This rapid heat transfer occurs because: there is a large temperature difference between the debris and the water; there is a large debris surface area since the debris was broken up into droplets in the mixing phase; and the debris droplets fragment further during the explosion phase due to pressure forces acting upon them which further increases the surface area. To correctly calculate the heat transferred in the explosion phase would require that the surface area of the debris droplets be known both initially, and as the debris fragments during the explosion process. It also would require that the thermodynamic state of the water be tracked in detail as it expands under the inertial constraint of its own mass and that of its surroundings. This is necessary because, at some point in the explosion, the pressure may become low enough so that steam blanketing of the debris occurs once again. This will interrupt the rapid heat transfer, and limit the total energy absorbed by the water. Some investigators employ correlations for debris surface area, but, as with mixing limits, these correlations can be a source of controversy. For the simple bounding model, the calculation of heat transfer, and expansion of the water is avoided by simply assuming instantaneous temperature equilibration between the debris and the water with no change in the water volume. This is the maximum amount of heat that can be transferred to the water.

Expansion

The rapid transfer of heat to the water in the explosion phase results in a high pressure mass of water, constrained only by its own inertia and the inertia of its surroundings. This mass will expand against its surroundings. As it expands, its temperature will drop, creating the potential for additional heat transfer from the debris. As it expands it will also accelerate itself and the surroundings. If a mechanical structure is included in the surroundings, the force causing the expansion may displace the structure also. The acceleration of the exploding mass, the

acceleration of the surrounding fluid, and the displacement of structures all require mechanical work. This work comes from the thermodynamic conversion of heat energy to mechanical work that occurs in an expanding fluid. The mechanical work produced is an important measure of the magnitude of a steam explosion. A pressurized mass of fluid has the capacity to produce mechanical work. Only a portion of the thermal energy of the mass will be converted into work, however. An upper limit to the amount of work that can be produced, is set by thermodynamic laws. The maximum work is termed the "reversible work" and is defined as the work produced while changing a thermodynamic state along a reversible path. A reversible thermodynamic path is one in which the entropy of the fluid does not change. It is possible to calculate the reversible work for the water participating in a steam explosion by simply finding the entropy at the beginning of the expansion phase, and adding to it the entropy from reversible heat transfer during expansion (if any occurs). This quantity is the entropy of the expanded fluid. Given this entropy and one other thermodynamic property, which can be the expanded volume or pressure, one can find the thermodynamic state of the expanded fluid. The change of energy in the fluid that has occurred, accounting for heat transfer, is the reversible work. In a real steam explosion, some of the capacity to do work is dissipated by friction, viscosity, turbulence, or compressible shock waves.

The expansion process occurs over a brief period of time. It is useful to have a gauge of this time scale, because it provides an insight to the time dependent pressure pulse that structures may be subjected to. It also provides a basis for comparing pressure pulses that have a parametric difference. This time scale can be found, if the geometry is known, by solving the laws of kinetics. In this case a simple one-dimensional linear geometry is assumed. The velocity of expanding mass can be found by equating its kinetic energy to the work produced as it expands. The distance traveled at this velocity can be related to the expanded volume of the mass, given the assumed geometry. These two independent relationships can be used to solve for the time to reach any point in the expansion process.

This framework provides a simple steam explosion model that is straightforward since it depends on basic equilibrium thermodynamics only, and involves no rate processes or empirical data or correlations. The major disadvantage is that it may significantly over-predict the magnitude of steam explosions. It is intended that the model be used as a first step in defining the potential steam explosions identified for SRS severe accident scenarios. If this model indicates that an explosion is not significant in the accident progression, no further work need be undertaken. If an explosion is significant, however, it will be necessary to pursue some of the mitigating factors mentioned above. Significant reductions could be justified using some of the mitigating factors discussed above.

5.2 Results of the Bounding Model

Table 10 shows predictions of the upper bound limits for steam explosion magnitude for each of the eight scenarios discussed in section 2.

The ideal model yields are maximum values that only depend upon the most basic principals. The more sophisticated non-equilibrium analysis discussed below shows these values over-estimate the magnitude of PRA steam explosions. Also, it is clear from the experimental data that the ideal model over-estimates conversion ratios and peak pressures for small scale steam explosions. Experiments performed by Nelson (ND81, ND92) indicate that weakly triggered events do not exceed the critical pressure of water in the explosion zone and typically result in conversion efficiencies near 2%. Thus, ideal model results were used mainly as a guide to focus application of the non-equilibrium model (i.e., if yields predicted by the ideal model are unlikely to produce structural damage of consequence in the PRA, then it is unnecessary to apply the non-equilibrium model).

Table 10. Ideal Model Results.

Ideal Model Results	Case 1	Case 2	Case 3	Case 4	Case 5
Conversion Ratio	0.30	0.30	0.32	0.43	0.32
Debris-to-Water Mass Ratio	7	7	7	3	7
Mechanical Work (MJ)	6.15	2,650	24.4	1,820	1,760
Peak Pressure (bar)	454	454	465	1,746	465
Steam Mass (kg)	4.66	2,010	17.9	719	1,290
Steam Volume (m ³)	9.43	4,070	36.9	1,940	2,660

Ideal Model Results	Case 6	Case 7	Case 8
Conversion Ratio	0.29	0.39	0.29
Debris-to-Water Mass Ratio	7	4	7
Mechanical Work (MJ)	1,300	7,910	2,600
Peak Pressure (bar)	484	1,480	484
Steam Mass (kg)	1,010	3,520	2,010
Steam Volume (m ³)	2,010	8,980	4,025

6. NON-EQUILIBRIUM MODEL

In reality, various time-dependent processes reduce mechanical work production below the bounding model estimates. The largest reduction results from limits to the quantity of fuel which can mix with coolant before the explosion and finite heat transfer rates between materials in the explosion at different temperatures. Frictional losses to the container and work performed on the surrounding atmosphere also reduce the energy output. The mechanistic model described in this section accounts for these non-ideal effects to arrive at a more realistic estimate of the energy released.

6.1 Pre-Explosion Mixing

The pre-explosion mixing model is documented in Ref. (Pa89). The mass of debris that can mix with coolant before the explosion is based upon a "fluidization" limit. This limit is based on the hypothesis that if steam velocity exiting the top of a mixed pool exceeds a critical value, water droplets will be swept out of the mixture. Critical steam velocity at the top of the pool is calculated assuming that the water in the pool is saturated, so any heat transfer to the pool from the debris results in vapor generation. This vapor flows out the top of the pool. Heat transfer from the debris is calculated from film boiling at the surface of the debris droplets whose radius is estimated between 10 and 30 mm (based upon a limited amount of modeling and experimental evidence). Larger debris diameters result in less surface per unit debris mass, less heat transfer per unit debris mass, less steam flow and more mixed debris. The critical steam velocity is obtained by balancing gravitational forces with the drag on a coolant sphere due to the surrounding vapor. The diameter of coolant drops at the top of the pool is based on a critical Weber number for break-up in the vapor flow. Void fraction within the pool is based on the Wallis drift-flux model.

6.2 Explosion Model

The explosion model is documented in Ref. (Oh89). For completeness, a summary of the PRA-specific implementation is also provided here.

At some user specified time during the mixing process, an explosion is assumed to trigger. The mechanistic details of the trigger and how it affects the mixture are not included; however, once triggered, the explosion is self-propagating in the model. In addition, a qualitative assessment of triggering probabilities based on experimental data was made. Studies of steam explosions for geometries similar to a fuel assembly, suggest it is difficult to trigger (frequency near 1 in 100) an energetic event for fuel near the melting point falling into water in the BEFs as discussed in case 1. (Ch91, Gr92) Little prototypical data was available for the large PRA

interactions involving 100's or 1000's of kilograms, but a wide range of experiments show that energetic interactions become much more probable for these large fuel masses, especially if the fuel is highly superheated. Explosions in the PRA involving a large fuel mass (greater than a few kg) were assumed to trigger with certainty.

The moment the explosion is triggered, a one-dimensional geometry is assumed (as shown in Fig. 2) where molten fuel is homogeneously mixed with water coolant with a slug of water on top. Initially, molten debris is in the form of spherical droplets of radius in the 1 cm range. The explosion proceeds as the pre-mixed debris transfers heat to the surrounding water generating steam and pressurizing the mixture beneath the inertial constraint of the overlying slug. The rising pressure causes the injection of liquid water into the debris resulting in violent fragmentation of the debris droplets when the entrained water flashes to steam. Fragmented fuel particles are quite small (on the order of .1 mm) and generate a large surface area. Rapid heat transfer from the fragments further pressurizes the system increasing the fragmentation rate until the local pressure around the fuel particles equilibrates with the explosion zone pressure. After fuel fragmentation ends, the explosion continues to produce steam as the fragments are quenched and the mixture in the explosion zone expands to ambient pressure. Mechanical work is available in the form of kinetic energy of the overlying slug and the expanding fuel/water mixture in the explosion zone.

The energy balance equations governing the transfer of heat and mechanical energy between the various components of the explosion track total energy in the unfragmented and fragmented fuel and the liquid and vapor coolant. For the unfragmented fuel, energy is lost from conductive heat transfer to the surrounding vapor coolant ($\dot{Q}_{fg}$) and from mass transfer to the fragmented fuel:

$$\dot{E}_f = -\dot{Q}_{fg} - \dot{m}_{fr} h_f \quad (1)$$

where $\dot{m}_{fr}$ is the fragmentation rate and h_f is the fuel energy per unit mass measured with respect to some arbitrary reference temperature. $\dot{E}_f$ is obtained by equating heat conduction to the surface of the fuel with heat conduction and radiation from the surface of the fuel to the vapor coolant. An analogous equation holds for the fragmented fuel,

$$\dot{E}_{fr} = -\dot{Q}_{frg} - \dot{m}_{fr} h_{fr} \quad (2)$$

Figure 2. One-dimensional explosion geometry.

Heat transfer to the vapor from the fragmented fuel dominates that from the unfragmented fuel since, during most of the explosion, the surface area of the fragmented fuel is roughly 100 times larger than the unfragmented surface area. In the vapor coolant, heat is transferred from the vapor to the surface of the liquid coolant ($\dot{Q}_{frgc}$ and $\dot{Q}_{fgc}$ for vapor surrounding the fragmented and unfragmented fuel respectively) and to the vapor from the molten fuel. Also, energy is added to the vapor from the generation of steam and lost due to mechanical work on the overlying slug and explosion mixture;

$$\dot{E}_g = \dot{Q}_{fg} + \dot{Q}_{frg} - \dot{Q}_{fgc} - \dot{Q}_{frgc} + \dot{m}_g[i_g + C_{pc}(T_{satc} - T_c) + h_c] - P \dot{V}_g \quad (3)$$

i_g = heat of vaporization of the coolant

C_{pc} = specific heat of the coolant

T_{satc} = temperature of the saturated film at the surface of the coolant

T_c = bulk temperature of the coolant

P = explosion zone pressure

h_c = coolant internal energy relative to the reference temperature

$\dot{V}_g$ = time derivative of the explosion zone volume

The steam generation rate in the saturated surface layer of the liquid coolant can be found by balancing heat transfer from the steam to the surface layer with energy lost due to steam production and heat transfer from the surface layer to the bulk coolant ($\dot{Q}_{fc}$, $\dot{Q}_{fgc}$),

$$\dot{m}_g[i_g + C_{pc}(T_{satc} - T_c)] + \dot{Q}_{frc} + \dot{Q}_{fc} = \dot{Q}_{frgc} + \dot{Q}_{fgc}. \quad (4)$$

Volume changes in the fuel and the liquid coolant are neglected and the overlying coolant slug remains intact throughout the explosion. Each component of the explosion has a different temperature which is governed by the heat and mass transfer in the energy equations. Details of the various radiative and conductive heat transfer rates can be found in Ref. (Oh85).

The energy equations above consider only mechanical work performed by expansion of the high pressure steam and do not describe the manner in which kinetic energy is generated in the explosion mixture. It is tempting to assume non-rigid body motion for the explosion zone mixture (e.g., assuming homogeneity in the mixture at all times results in a linear velocity profile as suggested in Ref. (Oh89)). However, such an assumption violates energy conservation if the momentum of the system is determined by the force of pressurized steam on the overlying slug (e.g., the kinetic energy relative to the center of mass in the explosion mixture is absent from the energy equations). To avoid this contradiction, both the overlying slug and the explosion mixture are assumed to accelerate upward with the same velocity under the force of the high pressure steam acting on the bottom surface of the slug. Gravitational and frictional forces are included in the equation of motion for the slug.

The fragmentation model in which coolant penetrates the surface of the fuel drops and fragments part of the outer surface of the drop is schematically illustrated in Fig. 3. The volume rate of fragmentation for each fuel droplet is assumed proportional to the rate at which liquid coolant jets (propelled by the difference between local pressure around the fuel droplets and the overall explosion zone pressure) penetrate the fuel surface,

$$\dot{V} \propto \pi D_f^2 U_{fr} \quad (5)$$

where D_f is the unfragmented fuel diameter and U_{fr} is the jet penetration velocity. The jet penetration velocity is found by calculating the acceleration of a shell of coolant (with thickness near the fuel radius) through the vapor film surrounding the fuel droplets and then calculating the velocity of the jet entering the fuel from Bernoulli's equation. (Ki85) These prescriptions result in a fragmentation rate proportional to the explosion pressure. In addition, the local pressure around the fuel droplets is assumed to

exponentially decay to equilibrium pressure in the explosion zone with a relaxation time roughly equal to the jet penetration time at a given pressure. The fragmentation model is made complete by fixing the fragmented fuel diameter such that fragments have quenched when the shock wave from the explosion travels from the bottom of the container to the top and back again (denoted time τ_f) to depressurize the explosion zone and bring fuel fragmentation to a halt. Such an assumption couples the fragmentation diameter to the time integral of the shock propagation velocity. Numerically, this requires self-consistency between the fragmentation diameter input at the beginning of the calculation and the final explosion time τ_f . Further details of the fragmentation model can be found in Ref. (Oh89).

Figure 3. Illustration of the fragmentation process.
Liquid coolant impacts and penetrates the surface
of the fuel drops, quickly vaporizes, and fragments
a layer at the surface of the fuel drop.

6.3 Qualitative Description of the Non-equilibrium Model Codes

The computer model is divided into two programs: FULMIX and FCIMOD. FULMIX solves the set of non-linear algebraic equations which predict the fuel mass mixed given a set of initial conditions (see Ref. (Pt90) for more details). Results of the mixing analysis are then passed on to FCIMOD (see Ref. (Co91) for further documentation) which starts by determining the fragmented fuel diameter based on the assumed fragmentation time. Then the code calculates the thermal properties and the initial surface temperature of the fuel. Total energy for each component of the explosion is incremented in time with a Runge-Kutta algorithm that uses the differential heat transfer, mass transfer (due to fragmentation and vaporization) and mechanical work on the container. Finally, the program determines the temperature increment of each component from the new internal energy state. This process is repeated until the explosion expands to ambient pressure. If the fragmentation time is not self-consistent (as discussed above) the user should rerun FCIMOD with a new value for fragmentation time.

6.4 Results for the Non-Equilibrium Model

Predictions of the non-equilibrium model for the 8 PRA scenarios are shown in Table 11. From the table, it is apparent that in some scenarios, ineffective premixing of the fuel and water provides a strong limitation on the quantity of fuel participating in the explosion. However, this inefficiency is highly geometry dependent in the model. Also, the mass of fuel participating in the explosive heat transfer is further reduced by 60%-70% from inefficiencies in the fragmentation process.

Since the predictions of the non-equilibrium model are strongly scale dependent, it is interesting to study how the non-equilibrium model results for the nominal events depend upon variations of a single input parameter. This information might be used to parametrize the magnitude of the explosion over a range of input values. A limited sensitivity study for an application of this model to the Sandia MD-19 experiment is available in Ref. (Oh89), which also draws some qualitative conclusions about the sensitivity to initial conditions. Some preliminary sensitivity studies have been made for the SRS steam explosions. (Vo92)

It is appropriate to make some comments about the three initial conditions predicted by the APET which are most variable: fuel mass, fuel temperature and water pool depth. The mass and temperature of fuel participating in the explosion are of primary importance since they determine the total thermal energy (which is a linear function of fuel mass and temperature) available to drive the explosion. It is worth noting that in spite of the complex dependence of fragmentation rate on pressure history and explosion geometry (Oh89) roughly 40% of the fuel is fragmented in all eight cases. This is true in the examples of Ref.(Oh89) as well and merits closer study. The initial fragmentation rate is proportional to the total fuel mass. The temperature of the fuel mass has a complex effect on the explosion behavior. Higher fuel temperatures may result in greater heat transfer and higher pressures early in the explosion, but the larger mass of vapor generated early may reduce the late time heat transfer.(Oh89) The height of the coolant chamber is coupled to the quench time for the fragmented fuel and plays an important role by determining the final diameter of the fragmented fuel and therefore the surface area available for heat transfer. Larger water pool depths tend to soften the explosion by increasing the diameter of the quenched fuel and reducing the heat transfer and pressure.

Table 11. Non-equilibrium model Results.

Results	Case 1	Case 2	Case 3	Case 4
Debris Mass Mixed (kg)	27.0	1250	108.9	1180
Debris Mass Fragmented (kg)	15.0	629	58.4	577
Peak Pressure (bar)	170	141	554	87.9
Conversion Ratio	0.072	0.105	0.106	0.0796
Adjusted Conversion Ratio**	0.0596	0.0093	0.0923	0.0435
Mechanical Work (MJ)	1.75	119	11.23	170
Steam Mass (kg)	3.70	1140	13.6	248
Steam Volume (m ³)	4.34	1920	22.9	409

Results	Case 5*	Case 6	Case 7	Case 8
Debris Mass Mixed (kg)	7840	927	10060	14080
Debris Mass Fragmented (kg)	4200	495	5007	6864
Peak Pressure (bar)	554	314	28.0	117
Conversion Ratio	0.106	0.049	0.037	0.066
Adjusted Conversion Ratio**	0.0923	0.0065	0.026	0.066
Mechanical Work (MJ)	809	41.4	575	838
Steam Mass (kg)	979	126	1610	1453
Steam Volume (m ³)	1650	220	2652	2670

* Case 5 was obtained by scaling case 3 by a factor of 72 (to represent a core wide power excursion) assuming the conversion ratio and peak pressure were similar in both cases. Model computations for case 5 were not carried out.

**Adjusted conversion ratio is based on initial fuel mass rather than mixed fuel mass.

7. AREAS VULNERABLE TO STEAM EXPLOSION DAMAGE

The course of events in a severe accident can be influenced by steam explosions primarily because they may cause structural failures resulting in additional release paths for fission products. Structural failure of an element generally requires a minimum expenditure of mechanical energy which is consumed in the form of strain energy to the point of failure. An energy-based approach compares the potential for doing mechanical work generated by the steam explosion to the mechanical work required to cause structural failure of an element. This analysis is less discriminatory than dynamic analysis whereby a shock load is imposed on a structure and its dynamic response is calculated, but it has the advantage that a detailed pressure history is not required. For the purposes of the PRA, the energy-based failure theory provides sufficient insight to allow judgements about failure probability to be made.

There are several points in the primary system and in the confinement building that are vulnerable to the effects of a steam explosion. This section lists the apparent locations where such damage might occur, and discusses how the damage might influence the accident progression.

7.1 In-Vessel Steam Explosion Vulnerabilities

The SRS reactor vessel is designed to operate at relatively low pressure, but has relatively modest provisions for venting internal pressure. It is therefore susceptible to damage from both shock waves and quasi-static pressurization resulting from an in-vessel steam explosion. Areas of the vessel that may be damaged by a steam explosion include:

Reactor fuel assemblies: A steam explosion in a single or several assemblies may disrupt adjacent intact assemblies. This may disrupt coolant flow to those assemblies resulting in further fuel melting.

The vessel top shield: The vessel top shield is held in place by its own weight, by the pipe anchors securing the inlet legs of the inlet plenum and the plenum skirt that seals the reactor. Shock waves or pressurization resulting from a steam explosion may be sufficient to lift the top shield and rupture the piping anchors and the plenum skirt.

The Vessel Bottom Shield Vessel Supports: The reactor is supported by the bottom shield which sits on a concrete ledge in the wall of the pin room. Shock waves from a sufficiently large steam explosion in the reactor vessel may fracture this ledge allowing the bottom shield and a portion of the reactor vessel to fall into the pin room.

Reactor Primary Piping: The primary piping of the reactor system is more substantial than the vessel itself. It is generally made of schedule 40 stainless steel pipe. The piping is relatively confining, however, so a sufficiently large steam explosion in the reactor outlet piping might generate a shock wave large enough to rupture the pipe.

7.2 Ex-Vessel Steam Explosion Vulnerabilities

The SRS reactor confinement building is a relatively heavy walled reinforced concrete building. It is divided into two general areas: above-grade and below-grade. A ventilation system works by drawing air into both above and below grade areas and exhaust it to the atmosphere through filtered exhaust fans. Although the building is quite substantial, there are some points that are structurally weak, and more susceptible to damage. Areas of concern are:

The Motor Room Roll Doors: Between the motor rooms and the pump rooms, are relatively light weight metal roll doors. The doors influence air flow in the building. These doors could be blown out either by shock waves or by pressurization resulting from a moderate steam explosion.

The Heat Exchange Bay and Tunnel Hatches: Concrete plugs exist in the ceiling of the heat exchanger bays and the piping tunnels that run from the reactor building. Significant build-up of pressure in the below-grade area might dislodge these hatches.

The Exhaust Fans and Filters: The exhaust fans and filters are supported by and contained within a metal structure. This structure would be vulnerable to pressurization of either the below-grade or above-grade areas.

Personnel Doors: Personnel doors exist in several locations in the building. These may be blown out by shock wave or pressurization effects of steam explosion.

The Reactor Vessel: The reactor vessel separates and seals the below-grade area from the above-grade area. A large below-grade steam explosion might dislodge the reactor vessel and lift it, breaking this seal.

Concrete Structure: The concrete structure is relatively substantial. Exterior walls in the below-grade areas are backed up by earth as well. There remains the possibility, however remote, that a large steam explosion might rupture interior walls in the below-grade area, or exterior walls above-grade.

The steam explosion models presented in this report provide an estimate of the magnitude of a shock wave, in terms of mechanical work, and also an estimate of the quantity of steam produced in an explosion. By employing a similar level of detail in a follow-on structural analysis, the vulnerabilities can be assessed further along with the need for more detailed analysis.

8. DISCUSSION AND CONCLUSIONS

With regard to improving the models above, a large potential source of heat in aluminum/water steam explosions lies in the chemical energy associated with the oxidation of aluminum in steam. This energy could boost explosion yields if significant oxidation of the fuel can occur within the time-scale of the explosion. Results of recent NPR EXO-FITS experiments performed at Sandia National Laboratories (see section 3) suggest that, above a certain threshold fuel temperature, explosive oxidation can occur. Chemically boosted explosions may be a relevant consideration in the PRA for several accident sequences which result in fuel with high superheat. For example, a steam explosion resulting from BEF recriticality (case 4) can involve superheated fuel due to the energy deposited in the fuel by the criticality event. Also, fuel involved in ex-vessel steam explosions may be superheated since the failure temperature of stainless steel in the vessel bottom or outlet piping is ~ 1470 K. However, the precise location of the chemical explosion threshold and its dependence on geometry and scale effects has not been determined by the Sandia tests, so it is difficult to predict which PRA interactions with superheated fuel will result in a chemical explosion. Other accident sequences leading to steam explosions are expected to result in molten fuel with little or no superheat and should not lead to chemically boosted steam explosions.

Some initial attempts to include oxidation of fragmented fuel in the non-equilibrium model are currently underway. Preliminary results suggest that reaction rates limited by gas diffusion of the hydrogen product through the steam blanket surrounding the fragments or, at higher temperatures, vapor burning at the surface of the fragments are well within the time-scale of the explosion. However, the location of a threshold temperature at which oxidation of the fragmented fuel is self-sustaining is not well known. More experimental work is needed to determine pure-aluminum oxidation rates at various temperatures. Also, reaction kinetics and energetics at very high fuel temperatures which may be generated by rapid oxidation have not been studied.

In summary, of the numerous fuel coolant interactions which can arise from severe accident sequences studied in the SRS reactors, eight prototypical cases have been singled out for application of the ideal model and the non-equilibrium model. The non-equilibrium model predicts detailed pressure history, steam generation, and slug kinetic energy throughout the duration of the explosion and the subsequent expansion to atmospheric pressure. Qualitatively, results predicted for the eight prototypical accidents range from small explosions involving fuel from a few assemblies and producing a few tens of megajoules of energy to large explosions involving significant fractions of the total fuel inventory which can produce mechanical work in the gigajoule range. The mass of steam produced also

varied widely from a few kilograms to more than a metric ton for some of the large explosions.

The results of this analysis were incorporated into the PRA by considering effects of pressurization of the confinement building (both above and below grade) due to steam generated and effects of mechanical work (in the form of debris kinetic energy) on structures surrounding the explosion. This means the confinement may be directly bypassed when hatch covers are lifted out of place or structural damage occurs due to missile generation. There also exists the possibility for various small steam explosions inside the vessel to alter subsequent core melt and accident progression. For example, case 1 steam explosions (see chapter 2) may dislodge a sufficient number of assemblies that a recriticality in the BEFs (case 4) is precluded later on or case 3 events may prevent a later core-wide reactivity excursion (case 5). On the other hand, a steam explosion in the outlet piping may rupture the piping and allow a later ex-vessel explosion even if there is enough water on the pump room floor to cool the fuel in the outlet piping if no steam explosion occurred (thus, creating a path to a larger explosion which would not exist otherwise). The effects of steam explosions on the magnitude and timing of fission product release have been propagated through the remainder of the PRA to account for the consequences of steam explosions on risk measures.

Application of the non-equilibrium model represents a valuable step toward realistic assessment of the risk from steam explosions in SRS reactors. Frequently used thermodynamic equilibrium models overestimate the potential severity of steam explosions since they lack a consideration of temperature differences between explosion constituents and rate processes such as heat and mass transfer. Typical energy conversion ratios for equilibrium models fall in the 30% to 40% range, while the results shown above are well below 10%. The conclusion that realistic energy yields can be close to an order of magnitude smaller than ideal model predictions is also well supported by the experimental literature.

REFERENCES

Al82 - W. O. Alexander, A. T. Chamberlin, and F. M. Page, ECSC Research Report 7205-16/801/08 (1982).

Ar70 - Armstrong, D. R., "Violent Boiling with Molten Fuel and Sodium," Argonne National Labs report, ANL-7688.

Ba84 - Bankoff, S. G. and Habib A., "The Application of a User-Friendly Code to Nuclear Thermal Hydraulic Reactor Safety Problems," Nuclear Power Plant Thermal Hydraulics and Operations Topical Meeting, Taipei, Taiwan, October, 1984.

BC91 - K.H. Bang and M.L. Corradini, "Vapor Explosions in a Stratified Geometry," Nuclear Science and Engineering: 110, No. 2, May 1991.

BH74 - Board S. J., and Hall R. W., "Propagation of Thermal Explosions. 2 - Theoretical Model," CEGB Report, RD/B/N 3249.

Br76 - A. J. Briggs, "Experimental Studies of Thermal Interactions at Winfrith", Paper 6/1 of PNC N251 76-12 (Vol. 1), Proceedings of the Third Specialist meeting on Sodium/Fuel Interaction in Fast Reactors, Tokyo, March 22-26, 1976.

Cl91 - S. Clements, N. D. Woody, R. S. Whittman, "Reactivity Analysis of a Savannah River Site Reactor Under Severe Accident Conditions", SAIC Draft Report 90/6501, Sept 12, 1991.

Ch76 - D. H. Cho, H. K. Fauske, and M. A. Grolmes, "Some Aspects of Mixing in Large-Mass, Energetic Fuel-Coolant interactions," Proc. Int. Mtg. Fast Reactor Safety and Related Physics, Chicago, IL, Vol. 4, p. 1852, October 1976.

Ch91 - D. H. Cho, et al., "Scoping Tests on the Potential for Lithium/Aluminum Steam Explosions in an SRS Septifoil", WSRC-RP-91-0952, September, 1991.

Co82 - M. L. Corradini, "Proposed Model for Fuel-Coolant Mixing During a Core Melt Accident", Proc. Int. Mtg. Thermal Nuclear Reactor Safety, NUREG/EC-0027, Chicago, IL, August 1981.

Co88 - M. L. Corradini, B. J. Kim, and M. D. OH, "Vapor Explosions in Light Water Reactors: A Review of Theory and Modeling", Progress in Nuclear Energy, Vol. 22, No. 1, pp. 1-117, 1988.

Co91 - Corradini, M. L., Bang, K. Y., Oh, M. D., Tang, J., "Code Manual for a Large-Scale Vapor Explosion Model: Non-Equilibrium and A Water/Steam Equation of State: Steam.", University of Wisconsin Report, UWRSR, October 1991.

CS80 - Coddington P. and Staniforth M. G., "Calculations on Propagation Vapour Explosions Using the SIMMER Code and Their Relation to the Winfrith Thermir Experiments.", CSNI Mtg. on FCI Experiments, Karlsruhe, December 1980.

CW74 - Cho D. H., Chen W. L. and Wright R. W., "A Parametric Study of Pressure Generation and Sodium-Slug Energy From Molten-Fuel-Coolant Interactions," Argonne National Labs report, ANL-8105.

EH90 - P. G. Ellison, M. L. Hyder, C. L. Angerman, and J. P. Morin, "A Phenomenological Assessment of Nuclear Metallic Fuel Melt Behavior During Severe Accidents (U)", WSRC report WSRC-RP-90-1130, October, 1990.

Es64 - E. G. Silver, "SPERT Program Status Report", Nucl. Safety 5, 151 (1964).

FA90 - D. F. Fletcher and R. P. Anderson, "A Review of Pressure-Induced Propagation Models of the Vapour Explosion Process", Progress in Nuclear Energy, Vol. 23, No. 2, pp 137-179, 1990.

FE85 - Fauske H. K. and Epstein M., "Steam Film Instability and Mixing of Core Melt Jets and Water," ANS Thermal Hydraulic Div. Proc., ASME/AIChE National Heat Transfer Conference, Denver, August 1985.

Ga86 - T.M. Grace and R.R. Robinson, "Energetics of Smelt/Water Explosions", NUREG/CR-4745, October, 1986.

Gr92 - G. A. Greene, "Rapid Quenching of Molten Lithium-Aluminum Jets in Water Under LCRC Conditions", Brookhaven National Laboratory Report, BNL 52324, January, 1992.

KK69 - J. H., Keenan, et al., "Steam Tables", Wiley and Sons, Inc., New York, 1969.

Ki85 - B.J. Kim, "Heat Transfer and Fluid Flow Aspects of a Small-Scale Single Droplet Fuel-Coolant Interaction.", Ph. D. Thesis, University of Wisconsin-Madison, August, 1985.

Ki87 - B.J. Kim and M.L. Corradini, "Modeling of Small-Scale Single Droplet Fuel/Coolant Interactions", Nuclear Science and Engineering, February, 1988.

Lo51 - G. Long, "Explosions of Molten Aluminum in Water -- Causes and prevention", Metal Progress 71, 107 (May, 1951).

Le82 - Alexis W. Lemmon, Jr., "Explosions of Molten Aluminum and Water", in Light Metals 1980, Curtis J. McMinn, Ed;., Proceedings of a meeting of the AIME at Las Vegas, NV, Feb. 24-28, 1980, p.817.

Le91 - M.T. Leonard, et al., "MELCOR/SR-Mod3 A Computer Code For Evaluating Severe Accident Progression in Heavy Water Reactors: Reference Manuals and User's Guide", SAIC 91/6504, September 1991.

Lo89 - D. L. Y. Louie, et. al, "TRAC-PF1/MOD2 Calculations of Selected Reactor Severe Transient LOPAs, RIA, and LOHS For Mark-22 Charge Core", SAIC Draft Report 89/6505, July 1989.

Lo289 - D. L. Y. Louie, "TRAC-PF1/MOD2 Calculations of SRP Reactor Transients: Loss of Coolant Accidents", SAIC Draft 88/6517, Jan. '89

MH89 - J. P. Morin and M. L. Hyder, "The Reaction of Molten SRP Reactor Fuel with Water", Presented at the ANS Workshop on the Safety of Uranium-Aluminum Fueled Reactors, Idaho Falls, Idaho, March 15, 1989.

MS63 - R. W. Miller, et. al, "Experimental Results and Damage Effects of the Spert-1 Destructive Test", Trans. Am. Nucl. Soc.6, 138 (1963).

ND81 - L. S. Nelson and P. M. Duda, "Steam Explosion Experiments with Single Drops of Iron Oxide Melted with CO₂ Laser", Sand81-1346, Sandia National Laboratories, September, 1981.

ND92 - L. S. Nelson and P. M. Duda, and D. A. Hyndman "Thermal- and Ignition-Type Steam Explosions of Single Drops of Molten Aluminum", SAND91-1354, Draft, Sandia National Laboratories, January, 1992.

Ob89 - D. A. O'Brien, "Analysis of the response of the SRP Reactor Confinement System to Postulate Core Melt Sequences- Top and Bottom Shield Failure Analysis", WSRC-RP-89-279, Westinghouse Savannah River Company, Aiken South Carolina, August 1989.

Oh85 - Oh, M. D. , Ph. D. Thesis, University of Wisconsin-Madison, August, 1985.

Oh87 - Oh, M. D. and Corradini, M. L., "A Propagation/Expansion Model for Large Scale Vapor Explosions", Nuclear Science and Engineering:95, 225-240 (1987).

Pa89 - Park, G. C. , Corradini, M. L., "Estimates of Limits to Fuel/Coolant Mixing.", University of Wisconsin Report, UWRSR-60 (August 1989).

Pt90 - Ptacek, J. H., Park G. C., Corradini, M. L., "A Parametric Model for Fuel-Coolant Mixing, Explosion Propagation and Expansion: Users Manual", University of Wisconsin Report, UWRSR-63 ,Jan., 1990.

SB81 - A. Sharon and S.G. Bankoff, "On the existence of steady supercritical plane thermal explosions," Int. J. Heat Mass Transfer, 24,1561-1572, 1981.

TS82 - Theofanous T. G. and Saito M., "An Assessment of Class-9 (Core-Melt) Accidents for PWR Dry Containment Systems," Nuclear Eng. Design, Vol. 66, p. 307.

Vo92 - B. E. Vonderfecht, D. C. Smith, "Modelling Steam Explosions for the Savannah River Site Reactor Probabilistic Risk Assessment (U).", to be presented at the Probabilistic Safety Assessment International Topical Meeting, Clearwater Beach, Florida, January 27-29, 1993.

Yo87 - Young M. F., "IFCI: An Integrated Computer Model for All Phases of Fuel Coolant Interactions," Sandia National Laboratories, NUREG/CR-5084, SAND87-1048 (1987).

APPENDIX A.

A.1 Ideal Steam Explosion Model Description

The explosion phase is a constant-volume temperature equilibration between the debris and the water coolant. This condition is found by solving two simultaneous equations: 1) The first law of thermodynamics (energy conservation) for a closed control volume, and 2) temperature equilibrium. In order to solve this set, it is necessary to evaluate the internal energy of both the debris and the water. These are given by equations of state. For the debris, the internal energy is a function of temperature alone. For the water, the internal energy is a function of two independent state properties. For this formulation, temperature and specific volume will be used. A final equation in the set imposes constant water specific volume during the process. The equations may be written for a system of molten debris and water as:

$$m_{c,1} u_{c,1} + m_{d,1} u_{d,1} = m_{c,2} u_{c,2} + m_{d,2} u_{d,2} \quad (A.1)$$

$$T_{c,2} = T_{d,2} \quad (A.2)$$

$$v_{c,1} = v_{c,2} \quad (A.3)$$

Where:

m is mass

u is internal energy per unit mass, which is governed by an equation of state which relates it to temperature (and specific volume in the case of water)

T is temperature

v is the specific volume

Subscripts:

c is for the water coolant

d is for the debris

1 is for the state prior to temperature equilibration

2 is for the state after temperature equilibration

The equation of state relating the debris temperature to its internal energy is discussed by Nause and Leonard. The full equation of state for water, and a tabulation of properties is given by (KK69). This equation set is implicit, but can be solved for the equilibrated temperature by numerical methods. The equilibrated temperature, along with the specific volume of

the water allow the other properties of the water to be found from the appropriate equation of state.

Expansion Phase Modeling

The second step of the ideal model is the expansion of the fuel/coolant mixture. The primary goal of the expansion phase model is to calculate the maximum work that can be produced by the expansion of the water participating in the explosion. In addition, a time scale for the expansion process is formulated based upon a simple 1-dimensional geometry.

The work produced in the expansion of a unit mass of water can be calculated by finding the final state of the water, and performing an energy balance. The final state of the water can be found if two properties of the state can be specified. It is assumed that the water will expand to atmospheric pressure, providing one of the properties. The other property will be the entropy of the final state. When a system produces reversible work, the entropy of the system does not change. Therefore, the entropy of the expanded state is equal to the entropy of the initial state plus any entropy produced by heat transfer. The work produced is equal to the initial internal energy, plus any heat transferred to the water, minus the final internal energy. If there is no heat transfer to the water as it expands, the process would be isentropic, and the final entropy of the water would equal the initial entropy. Since the temperature of the water will drop as it expands, however, the potential exists for heat transfer from the debris to the water as it expands. This heat transfer will increase the entropy and internal energy of the water. The equations that govern this process are:

$$m_c s_{c,1} + dS_{ht} = m_c s_{c,2} \quad (A.4)$$

$$W_{rev} = m_c u_{c,1} + Q - m_c u_{c,2} \quad (A.5)$$

where:

s	is the specific entropy (entropy per unit mass)
dS_{ht}	is the change in total entropy due to heat transfer
W_{rev}	is the reversible work for the process
u	is the specific internal energy
Q	is the total heat transfer

and the internal energy of the water in this case is given by an equation of state dependent upon entropy and pressure: The change in entropy of the water due to heat transfer is given by:

$$dS_{ht} = \int_1^2 dQ/T_c \quad (A.6)$$

The heat transfer to the water is assumed to come from the debris. The maximum amount of work possible in a steam explosion is that produced if the debris continues to transfer heat to the water as it expands. The maximum amount of heat transfer occurs if the debris temperature remains in equilibrium with the water temperature throughout the expansion phase. In this case the heat transfer is given by equation set:

$$t_d = T_c \quad (A.7)$$

$$dQ = m_d du_d \quad (A.8)$$

Again, the internal energy of the debris is a function of its temperature given by an equation of state and is dependent only on the debris temperature.

In order to compute the change in entropy of the water from the integral expression, it is necessary to calculate the heat transferred from the debris to the water as a function of water temperature during the expansion process. This function can be derived, at least discretely, by solving the set of equations for intermediate values of pressure in the expansion process. In the explosion phase both the temperature and the entropy increase. In the expansion process the temperature decreases, and the entropy either increases due to heat transfer from the debris or remains constant.

Expansion Phase Time Scale

The expansion model yields mechanical work, but does not produce any information about the time scale of the process. Information about the time scale can only be derived from the kinetics of the explosion. A simple 1-dimensional model is used to approximate the kinetics of the reaction. This model is based upon acceleration of the mass of debris and water that participate in the explosion. The cross-sectional area over which the pressure from the explosion performs work is assumed to be equal to the volume of water involved raised to the 2/3 power.

The velocity with which the debris expands can be determined by equating the work done to the kinetic energy of the water and debris that is accelerated by the explosion. It will be assumed that only the mass accelerated by the explosion is the mass that participated. No slug of overlying water will be included. This assumption results in the minimum accelerated mass, and therefore the most rapid expansion process. The kinetic energy of the expanding mass is given by the expression:

$$KE = \int V v^2 d(m_d + m_w). \quad (A.9)$$

Where:

V is the volume of the expanding mass

v is the local velocity within the expanding volume
 m_d is the debris mass involved
 m_w is the water mass involved

The velocity of the debris is assumed to vary linearly from the base of the explosion to the expansion front. This is equivalent to the assumption that the volume expands uniformly. The velocity is given by the expression:

$$v = v_f \frac{x}{x_f} \quad (A.10)$$

where v_f is the velocity of the expansion front, and x_f is the location of the expansion front. The differential mass may be written as:

$$d(m_d + m_w) = \frac{(m_d + m_w)}{V} dV = \frac{(m_d + m_w)}{x_f} dx. \quad (A.11)$$

These two expressions can be substituted into the expression for kinetic energy. Once this is done it can be integrated analytically and set equal to the work resulting in the expression:

$$W = .5 v_f \frac{2(m_d + m_w)}{3}. \quad (A.12)$$

This allows the debris velocity to be determined during the expansion process by the expression:

$$v_f = \sqrt{\frac{6W}{(m_d + m_w)}}. \quad (A.13)$$

The simplifying assumptions made with regard to initial geometry, one-dimensional expansion, and neglect of an overlying water slug are significant. This bounding model provides a point of reference for comparison of pressure pulses from alternative parametric steam explosion cases.

A.2 Qualitative Description of the Bounding Model Code

This section describes the implementation of the ideal model as an executable computer program. The following paragraphs describe the program input, the explosion phase modeling, and the expansion phase modeling,

Input Parameters

The program accepts as input, the initial conditions for a hypothetical steam explosion, and several user specified parameters that influence the

model. The initial conditions are taken from the examinations of the accident progressions as discussed in section 2. The user specified model parameters are parameters that influence the result of the steam explosion model, but for which there is no simple method to determine their value. A brief description of each is given below.

Initial Void Fraction: When molten debris mixes with water, film boiling will occur on the surfaces of the debris droplets and a layer of vapor will form on each droplet. Some of this vapor may detach from the debris droplets, forming bubbles in the water. In most cases, the water will be subcooled so detached bubbles will rapidly collapse. These vapor voids will displace some volume. The fraction of the total volume of water and steam occupied by steam voids is the initial void fraction for the steam explosion.

Debris-to-Water Mass Ratio: Debris entering a pool of water will mix with some fraction of the water in the pool. The amount of water that participates in a steam explosion depends upon this mixing process and the debris-to-water mass ratio that results.

Expansion Heat Transfer Factor: As discussed in the previous section, there is potential to transfer heat from the debris to the water during the expansion phase. This factor controls the degree to which heat is transferred during the expansion phase. The factor is defined by the expression:

$$T_{deb} = T_{eq} - K_{HT}(T_{eq} - T_w). \quad (14)$$

where:

T_{deb} is the debris temperature
 K_{HT} is the expansion heat transfer factor
 T_{eq} is the equilibrium temperature after the explosion phase
 T_w is the water temperature

The change in internal energy of the debris is then set equal to the heat transfer to the water. This factor limits the heat transfer during the expansion phase to some fraction of the maximum amount. Some steam explosion models employ correlations for these values. For this model, a parametric approach to these values will be employed. The worst case steam explosion is determined by varying these parameters, and finding the value that results in the largest explosion. This method results in a bounding value for the steam explosion magnitude, without depending on empirical correlations.

Explosion Phase Modeling

The implicit equation set for temperature equilibration is solved by the following process:

1. The total internal energy of the debris and the water prior to equilibration is calculated.
2. An equilibrated temperature is assumed.
3. The internal energy of the water and debris corresponding to this equilibrated temperature (and constant specific volume in the case of the water). These values are totaled.

This total internal energy is compared to the energy prior to the explosion. If they are the same, the calculation is complete. If not, the assumed equilibrium temperature is adjusted accordingly and step 3 is executed again. The criteria for convergence is that the total internal energy before and after explosion agree within 0.01%.

The equation of state for water is solved by a package of subroutines taken from the MELCOR computer code (Le91). These subroutines are called the H₂O routines. The equation of state for the debris is a subroutine that simply interpolates within a table of debris energy versus temperature and returns the appropriate value.

Expansion Phase

The equations for expansion of the water are solved at a number of intermediate conditions between the equilibrated condition following the explosion, and the final expanded state. This procedure produces detailed information about the expansion process, and allows integration of water entropy change, and time. The calculation employs the specific volume as the independent variable. The expansion process is calculated by the following process:

1. First, the specific volume of the water is incremented. This increment is set such that the pressure tends to increase in steps of roughly equal ratio. While this is not necessary, it provides reasonable resolution of the expansion process throughout. For each step, a desired pressure is calculated and the corresponding volume increment is calculated based on the value of the partial derivative of pressure with volume returned by the H₂O routines.
2. The heat transfer from the debris to the water for this step is calculated next. This is done by estimating the expanded water temperature, and calculating the corresponding change in debris temperature based on the expansion heat transfer factor. The change in debris internal energy is that obtained from the equation of

state, and this is assumed to be the heat transfer to the water.

3. The change in water entropy is then calculated by dividing the heat transfer by the average water temperature for the step, and this is added to the water entropy.
4. Next, the equation of state for the water is solved based on the expanded specific volume and entropy estimate. This requires an iterative procedure, since the H₂O routines do not provide this combination of independent properties. The entropy convergence criteria is 0.02% if the desired entropy.
5. Once the correct state properties are found, the water temperature is compared to the assumed water temperature for the expansion. If the temperatures are within the convergence limits, the iteration is complete. The convergence criteria on temperature is 0.05% of the assumed temperature in Celsius. If the temperature is different than the assumed temperature, a new estimate is made and the calculation returns to step 2.
6. The mechanical work for the incremental expansion is calculated based on the change in internal energy of the water, accounting for the heat transferred. The expansion front velocity is calculated next based on the total work produced. Then the time for the incremental expansion is calculated by dividing the distance expanded by the average velocity for the increment. This is added to the previous expansion time.

The calculation then returns to step 1, and the volume is incremented again. This process is continued until the pressure of the expanding water reaches atmospheric pressure. The mechanical work can be independently calculated by integrating the pressure with respect to the volume for this process.

Distribution

Westinghouse Savannah River Company

R. T. Begley, 773-A
D. B. Rankin, 704-C
M. J. Hitchler, 992W-1
M. L. Cowen, 992W-1
M. L. Hyder, 992W-1
K. R. O'Kula, 992W-1
D. A. Sharp, 992W-1
D.K. Allison, 992W-1
R. T. Bailey, 992W-1
W. H. Baker, 992W-1
F. Beranek, 773-A
M. D. Brandyberry 992W-1
T. E. Britt, 992W-1
D. S. Cramer, 992W-1
A. B. DeWald, 992W-1
S. D. Kahook, 992W-1
D. P. Kearnaghan, 992W-1
V. E. Logan 992W-1
D. F. Paddleford, 992W-1
R. L. Olson, 992W-1
S. P. Tinnes, 992W-1
B. J. Vonderfecht, 992W-1
H. E. Wingo, 992W-1
R. W. Wittman, 992W-1
N. D. Woody, 992W-1
L. A. Wooten, 992W-1
SRTC Records, 773-A [4]

Department of Energy, Savannah River

G. Z. Morgan, 703-41A
P. S. Shieh, 703-41A
T. M. Tran, 703-41A

External

C.N. Amos
Science Applications International Corp.
2100 Air Park Road S.E.
Albuquerque, New Mexico 87106

S. D. Clement
Science Applications International Corp.
2100 Air Park Road S.E.
Albuquerque, New Mexico 87106

P.R. Davis
PRD Consulting
1935 Sabin Drive
Idaho Falls, Idaho 83401

P.G. Ellison
EG&G Idaho Inc.
P.O. Box 1625
Idaho Falls, Idaho 83402-2406

J.H. Holderness
Science Applications International Corp.
1910 Deacon Street
Los Alamos, New Mexico 87545

Kamiar M. Jamali
Dept. of Energy
OEOS-DP62/GTN
Washington, D. C. 20585

Mohsen Khatib-Rahbar
ERI
6290 Montrose Rd.
Rockville, Maryland 20852

Herbert J. C. Kouts
Defense Nuclear Facilities Safety Board
625 Indiana Avenue, N.W.
Suite 700
Washington D.C. 20004

J. D. Roarty
Defense Nuclear Facilities Safety Board
625 Indiana Avenue, N.W.
Suite 700
Washington D.C. 20004

**Thomas Matteson
1933 Little River Road
Flat Rock, North Carolina 27831**

**J. Meyer
Sciencetech
11821 Parklawn Dr.
Ste. 100
Rockville, Maryland 20852**

**David Okrent
UCLA
Boelter Hall, Room 5532
Los Angeles, CA 90024-1597**

**Norman Rasmussen
M. I. T.
77 Massachusetts Ave.
Cambridge, Massachusetts 02139**

**Desmond Stack
Los Alamos National Laboratory
Group Q-6 Mail Stop K 557
Los Alamos, New Mexico 87545**

**D. A. Ward
2108 Pisgah Road
North Augusta, South Carolina 29841**

This page intentionally left blank.

**DATE
FILMED**

7 / 27 / 93

END