1 of 2

BATTELLE

BATTELLE MEMORIAL INSTITUTE

POST OFFICE BOX 999/RICHLAND, WASHINGTON 99352

NORTHWEST

PACIFIC NORTHWEST LABORATORY

DECLASSIFIED

Copy AND SERIES NO.

DATE

1-3-69

TITLE AND AUTHOR

K P R AS Is; Alt. Tube 237NP Target

RE Shaver

CONTRACT PROJECT NO.

☐ - 1810
☐ - 1831

RESERVED FOR TECHNICAL USE

HANFORD CATEGORY AND/OR OTHER CIRCULATION RESTRICTIONS

NC

THIS DOCUMENT CONTAINS INFORMATION OF A CONFIDENTIAL NATURE. IT IS THE PROPERTY OF THE UNITED STATES GOVERNMENT. IT IS TO BE KEPT IN THE POSSESSION OF THE PERSON TO WHOM IT IS LOANED AND NOT BE REPRODUCED OR TRANSMITTED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF THE OFFICIALS OF THE UNITED STATES GOVERNMENT.

OTHER OFFICIALS OF THE UNITED STATES GOVERNMENT MAY BE LOANED TO OTHERS. IT IS THE RESPONSIBILITY OF THE LOANEE TO RETURN IT TO THE OFFICIALS OF THE UNITED STATES GOVERNMENT IN THE MANNER AND AT THE TIME SPECIFIED. IT IS THE RESPONSIBILITY OF THE LOANEE TO PROTECT IT FROM LOSS, DAMAGE, AND UNAUTHORIZED DISCLOSURE. IT IS THE RESPONSIBILITY OF THE LOANEE TO RETURN IT TO THE OFFICIALS OF THE UNITED STATES GOVERNMENT IN THE MANNER AND AT THE TIME SPECIFIED.

THIS DOCUMENT CONTAINS INFORMATION OF A CONFIDENTIAL NATURE. IT IS THE PROPERTY OF THE UNITED STATES GOVERNMENT. IT IS TO BE KEPT IN THE POSSESSION OF THE PERSON TO WHOM IT IS LOANED AND NOT BE REPRODUCED OR TRANSMITTED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF THE OFFICIALS OF THE UNITED STATES GOVERNMENT.

ROUTE TO

PAYROLL NO.

COMPANY

LOCATION

FILES ROUTE DATE

SIGNATURE AND DATE

AS-66666

DECLASSIFICATION REVIEW
 UNCLASSIFIED

By: [Signature]

DATE: 3-8-82
 U.S. GOVERNMENT PRINTING OFFICE

DECLASSIFIED

MASTER

KPR NP-237/ALT-T R4

TAPE ASSIGNMENTS A= 1732 00509

```

00000000  51 70 51 70 51 70 51 70 51 70 51 70 51 70 51 70  NO SPACING

```

Deposition Certificate and Chapter 10

DECLASSIFIED

By Authority of NS Lewis
PR-25 2-15-94
By J. E. Saincy 222-8
Verified By J. E. Saincy 222-8
3-5-94

MASTERS

THE DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

END OF CYC

1. IRO A

2. FINE APPLET 2091467

3. IRO A

4. IRO A

END OF CYC

END OF FILE 2091467

END OF FILE 2091467

ELAPSED TIME FROM START OF JOB IS 0 MIN 11 SEC

1108 FUEL CYCLE ANALYSIS CHAIN OF JASON=ACTHAE,=PLOTTER=PROTEUS=QUICK=OPTIMIZER=CURVES=HESTIA=PUFF

DATA FOR SETUP

18	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0

TOTAL COMPUTATION TIME .014 SECONDS OR .00023 MINUTES.

NEXT LINK = 10

TOTAL COMPUTATION TIME 1.725 SECONDS OR .02875 MINUTES.

NEXT LINK = 8

JASON CASE NUMBER 1001

GRAPHITE SLAB

INPUT CONTROL DATA

N	K1	K2	K3	K4	K5	DSMEQR	ECCOR	BUCK	STRCOR	MEVFIS	DEL						
2	0	1		0		0	9.3220-01	2.4796-05	1.0000-00	2.0200-02	-0.0000						
J6-	K6	K7	K9	K10	K11	K12	FPER	TPER	KDIL	UMF26	LOSREG	JPHI	MELALT	A7	SPWFR	HEIGHT	ADDER
-0	-0	-0	2	0	-3	-0	-0.00	-0.00	-0	-0.000	-0	-0	1	2.00	11.23	.692	-0.0000

INPLI FUEL COMPost IONS
ISOTOPE

REGION	TH232	U234	U235	U236	U238	PU239	PU240	PU241	PU242	DTIUENr	DILUENT VOLUME PERCENT
										NUMBER	

INPUT REGION INFORMATION

REGION NUMBER	RADIUS CM	RADIUS INCHES	MATERIAL	DENSITY GM/CC	TEMP DEG C	TEMP DEG F	VOLUME FRACTION	THICKNESS REG-INCH	NUCLEI PER BARN-CM
1	1.50000	.59055	GRAPHT	1.638	559.840	1039.712	.2500U	.59055	8.21375-02
2	3.11000	1.18110	GRAPHT	1.638	559.840	1039.712	.750-60	.59055	8.21375-02

--t: 0

• • • • •

" (

■ ■ ■ ■

OUTPUT FOR GROUP 3

CELL VALUES

AGE= 14.92 SIGMA REMOVAL=6.484E-02 SIGMA TRANSPORT=3.653E-01 FLUX DEPRES= .0000 FEXP= .0000 FCONST= .0000 SNF= .00000

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION
1	1.1107+01	7.0686+00	.00026	6.4844E-02	6.8828-05	3.8687-01	6.4775-02	3.6518-01	
2	1.1101+01	2.1206+01	.00079	6.4844E-02	6.8828-05	3.8687-01	6.4775-02	3.6518-01	
		TOTAL	.00106						

OUTPUT FOR GROUP 4

CELL VALUES

OPF LENG=6584.204 SIGMA ABSORP=1.4689E-04 SIGMA TRANSPORT=3.6533E-01 FLUX OPRES= .0000 FEXP= .0000 FCONST= .0000 SNF= .00028

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	R VALUE	SIGMA ABSORP	SIGMA SCATTER	SIGMA TRANSPORT	NEUT TEMP DEF C	SIGMA FISSION	HEAT TRANSFER NU UTILIZATION
1	4.8980+03	7.0686+00	.24930	.0024	1.4689-04	3.8687-01	3.6533-01	559.84		
2	4.8980+03	2.1206+01	.14789	.0024	1.4089-04	3.8687-01	3.6533-01	559.84		
		TOTAL	.99719							

CELL DATA

CONVERSION RATIO= .000 R INFINITE= .000 MIGRATION AREA=6584.204 MATERIAL BUCKLING=1.408E-04

FOUR GROUP EPSILON=1.000 OLD METHOD 0238 EPSILON=1.000

ZERO DIMENSIONAL ALTHAEA INPUT PARAMETERS

MENS

FUEL +/OR
TARGET DENS
OF METAL OR

MELEAGER
TEMP

PERFIS

SOPV

SNF

seA

ALLOY

DELTA

TOT

.00000

.00000

.00028

.00000

.000

.00-0

0.0000

559.04

FLUX
DEPRESSION

FCONST

FEXP

SP POWER
MW/TONNE

FUEL
TEMP

TONNES OF FUEL OR ALLOY
IN CORE

.0000

.00000

.00000

11.230

.00

.00000

ONE DIMENSIONAL ALTHAEA PARAMETERS

SS1
.19524

SS2
.36108

SS3
.36518

SS4
.36518

XISS1
.032954

XISS2
.060864

XISS3
.061521

SS4
.00000

SPFC
.00241

FUEL+TARGET
VOL FRACT-VR

VERT BUCK
BUCK

BARE HEIGHT
FOOT

1.00000

2.4796-05

0.0000

ALTHAEA ABSOLUTE FLUX GUESSES CONVERSION FACTOR=0.0000

CLAD SURFACE OF FUEL+OR TAR REGIONS	MODERATOR VOLUME	OUTSIDE SURFACE CYLINDER	CELL INFORMATION (PER FOOT OF CELL) CELL VOLUME	VOL MOD PER VOL FUEL+OR TARGET	FUEL+OR TARGET WEIGHT	MODERATOR WEIGHT	FUEL+OR TARGET VOLUME	CLADDING VOLUME
.03000	.03043	.61842	.03043	.00000	.00000	3.11214	.00000	.00000
SS FT/FT	CU FT/FT	SS FT/FT	CU FT/FT		LB/FT	LB/FT	CU FT/FT	CU FT/FT

JASON CASE NUMBER 1002

ALTERNATE TUBE - 1 P237-MC TARGET
SEU .735WT.0/0 U-235 METAL FUEL

TRIP CONTROL DATA

N	K1	K2	K3	K4	K5	OSMEZ	ECOR	BUCK	STCOR	MEVFIS	DEL							
7	0	1		0	0	0	9.3220-01	2.4796-03	1.0600-00	2.0200-02	-0.0000							
J6	K6	K7	K8	K9	K10	K11	K12	FPER	TPER	KOL	URA26	LOSS%	JPHT	MELALT	AT SPOMEH	HEIGHT	MODEP	
-0	-0	-3	2	0	5	-0	-0	-0	-0	-0	-0.000	-0	-0	2	2.04	11.23	.002	-0.0000

INPUT FUEL COMPOSITION

REGION	ISOTOPE WEIGHT PERCENT								PU239	PU240	PU241	PU242	oriUENT NUMBER	DILUENT VOLUME PERCENT
	TH232	U233	U234	U235	U236	U238	U238							
3	.000	.000	.000	.735	.000	.000	.000	.000	.000	.000	.000	.000	0	.000

INPUT REGION INFORMATION

REGION NUMBER	RADIUS CM.	RADIUS INCHES	MATERIAL	DENSITY GM/CC	TEMP DEG C	TEMP DEG F	VOLUME FRACTION	THICKNESS REG-INCH	NUCLEI PER BARN eM
1	.48493	.02550	H2O	.998	53.040	128.912	.00752	.19200	3.29620-02
2	.63246	.02490	ALUMN	2.702	114.840	238.712	.00472	.05650	6.02546-02
3	1.73990	.08500	U235 Me U238	18-900	349.840	661.712	.0718/	.43600	3.56036-04 4.74782-02
4	1.35293	.07250	ALUMN	2.702	109.840	229.712	.01714	.00460	6.02546-02
5	2.12344	.08360	H2O	.981	64.840	148.712	.03157	.10650	3.27948-02
6	2.12344	.08360	ALUMN	2.702	109.840	229.712	.01714	.00460	6.02546-02
7	5.83757	2.29826	GRAPHIT	1.638	559.840	1039.712	.84562	1.39526	8.21375-02

OPERATOR TO FUEL RATIO

A/FUEL
.7368

EhFUEL
.0000

GRAPHITZ/FUEL
20,2039

IF ARRAY IS TRIANGULAR, PITCH = 4.5775 INCHES
IF ARRAY IS SQUARE, PITCH = 4.0736 INCHES

OUTPUT FOR GROUP 1

CELL VALUES

AGE= 132.04 SIGMA REMOVAL=1.390-02 SIGMA TRANSPORT=1.926-01 FLUX OEPRES= .8389 FEXP= -7.4652 FCONST= -14.9304 SNF= .04729

REGION	FLUX	VOLUME	ABSORPTION	SIGMA	SIGMA	SIGMA	XI SIGMA	SIGMA	SIGMA		
		EMERG	FRACTION	REMOVAL	ABSORP	SCATTER	SCATTER	TRANSPORT	FISSION		
1	1.7323+00	7.5107-01	.00015	8.7381-02	2.2942-04	4.0082-01	8.7151-02	2.8699-01			
2	1.7479+00	5.0559-01	.00010	3.1189-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01			
3	1.7037+00	7.6941+00	.10238	2.3527-02	1.6015-02	3.7223-01	7.5121-03	1.5084-01	1.1573-02	2.808	
4	1.5983+00	1.0354+00	.00034	3.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01			
5	1.5602+00	3.3792+00	.00059	8.6938-02	2.2825-04	3.9879-01	8.6710-02	2.8553-01			
6	1.5306+00	2.3615+00	.00041	3.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01			
7	1.3907+00	9.0530+01	.00000	9.6922-03	0.0000	2.1816-01	9.6922-03	1.9524-01			
		TOTAL	.10396								

OUTPUT FOR GROUP 2

CELL VALUES

AGE= 70.75 SIGMA REMOVAL=1.182-02 SIGMA TRANSPORT=4.229-01 FLUX DEPRES=1.120a FEXP= 1.8530 FCONST= 3.7060 SNF= .36230

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	1.3228+00	7.5107-01	.00032	1.0061-01	6.6814-04	1.3636+00	9.9941-02	9.0415-01		
2	1.3147+00	5.0559-01	.00045	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
3	1.3502+00	7.6941+00	.30781	6.1537-02	6.0754-02	1.1624+00	7.8309-04	1.1630+00	7.7845-03	2.430
4	1.4236+00	1.8354+00	.00177	2.1874-03	1.3914-03	1.3373-01	7.6752-04	1.2919-01		
5	1.4454+00	3.3792+00	.00158	1.0010-01	6.6475-04	1.3567+00	9.9434-02	8.9956-01		
6	1.4665+00	2.3615+00	.00039	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
7	1.5354+00	9.0530+01	.00057	4.8390-03	8.4602-06	3.8276-01	4.8305-03	3.6108-01		
		TOTAL	.31487							

OUTPUT FOR GROUP 3

CELL VALUES

AGE= 9.78 SIGMA REMOVAL=9.387-02 SIGMA TRANSPORT=3.770-01 FLUX DEPRES=1.4622 FEXP= 1.3250 FCONST= 2.6110 SNF= .00511

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	7.2917-02	7.5107-01	.00015	8.8198-01	5.5268-03	1.5097+00	8.7645-01	9.9684-01		
2	6.7800-02	5.0559-01	.00006	9.6003-03	3.4944-03	8.7008-02	6.1059-03	8.4838-02		
3	7.0310-02	7.6941+00	.01588	2.9103-01	2.8160-01	4.2147-01	3.4273-03	4.2028-01	9.5206-02	2.430
4	8.2732-02	1.8354+00	.00026	9.6003-03	3.4944-03	8.7008-02	6.1059-03	8.4838-02		
5	9.0223-02	3.3792+00	.00042	8.7751-01	5.4988-03	1.5020+00	8.7201-01	9.9178-01		
6	9.5897-02	2.3615+00	.00039	9.6003-03	3.4944-03	8.7008-02	6.1059-03	8.4838-02		
7	1.0707-01	9.0530+01	.00033	5.9261-02	7.0517-03	3.8587-01	5.9170-02	3.6518-01		
		TOTAL	.07788							

OUTPUT FOR GROUP 4

LEL VALUES

DIF LENG= 68.969 SIGMA AHEAD=1.223-12 SIGMA TAIL=5.702-01 FLUX OPRES=1.374s FEXP= 1.3906 FCONST= 2.7811 SNF= .02097

REGION	FLUX	volUt-1E C43/CN	ABSORPTION FUNCTION	R VALUE	SIGMA ABSORP	SIGMA SCATTER	SIGMA TRANSPORT	NEUT TEMP DEG C	SIGMA FISSION	HEAT TRANSFER BT/LIT/ATON
1	5.5557-01	7.5107-01	.00316	.1708	1.5527-02	2.5820+00	1.5066+00	184.79		
2	5.2233-01	5.0559-01	.00114	.1799	8.8692-03	8.5200-02	9.2623-02	287.92		
3	5.4658-01	7.6941+00	.46910	.1769	2.2872-01	3.8863-01	6.1626-01	287.83	1.2309-01	2.430 1.000
4	6.2221-01	1.8354+00	.00494	.1645	3.8717-03	8.5200-02	9.2625-02	287.72		
S	6.7568-01	3.3792+00	.01395	.1544	1.2525-02	2.3097+00	1.2591+00	423.49		
5	7.7955-01	1.3615+00	.00595	.1495	3.2815-03	8.5200-02	9.1034-02	559.51		
7	7.7807-01	9.0530+01	.00505	.1430	1.4689-04	3.8687-01	3.6533-01	559.84		
		TOTAL	.50329							

CELL DATA

CONVERSION RATIO: .977 K INFINITY= .978 MIGRATION AREA= 245.24 MATERIAL BUCKLING:-8.923-0S

FOUR GROUP EPSILON=1.118 OLD METHOD U238 EPSILON=1.024

ISOTOPE CONCENTRATIONS O(FUCLEI/BARN eM)

U23S	U238
3.356036-04	4.74782-02

ZERO DIMENSIONAL ALTHAEA INPUT PARAMETERS

FUEL +/-OR

RELEASED	DATE	BY	REASON	REMARKS
1968	10/10	10/10	10/10	10/10
1969	10/10	10/10	10/10	10/10
1970	10/10	10/10	10/10	10/10
1971	10/10	10/10	10/10	10/10
1972	10/10	10/10	10/10	10/10
1973	10/10	10/10	10/10	10/10
1974	10/10	10/10	10/10	10/10
1975	10/10	10/10	10/10	10/10
1976	10/10	10/10	10/10	10/10
1977	10/10	10/10	10/10	10/10
1978	10/10	10/10	10/10	10/10
1979	10/10	10/10	10/10	10/10
1980	10/10	10/10	10/10	10/10
1981	10/10	10/10	10/10	10/10
1982	10/10	10/10	10/10	10/10
1983	10/10	10/10	10/10	10/10
1984	10/10	10/10	10/10	10/10
1985	10/10	10/10	10/10	10/10
1986	10/10	10/10	10/10	10/10
1987	10/10	10/10	10/10	10/10
1988	10/10	10/10	10/10	10/10
1989	10/10	10/10	10/10	10/10
1990	10/10	10/10	10/10	10/10
1991	10/10	10/10	10/10	10/10
1992	10/10	10/10	10/10	10/10
1993	10/10	10/10	10/10	10/10
1994	10/10	10/10	10/10	10/10
1995	10/10	10/10	10/10	10/10
1996	10/10	10/10	10/10	10/10
1997	10/10	10/10	10/10	10/10
1998	10/10	10/10	10/10	10/10
1999	10/10	10/10	10/10	10/10
2000	10/10	10/10	10/10	10/10
2001	10/10	10/10	10/10	10/10
2002	10/10	10/10	10/10	10/10
2003	10/10	10/10	10/10	10/10
2004	10/10	10/10	10/10	10/10
2005	10/10	10/10	10/10	10/10
2006	10/10	10/10	10/10	10/10
2007	10/10	10/10	10/10	10/10
2008	10/10	10/10	10/10	10/10
2009	10/10	10/10	10/10	10/10
2010	10/10	10/10	10/10	10/10
2011	10/10	10/10	10/10	10/10
2012	10/10	10/10	10/10	10/10
2013	10/10	10/10	10/10	10/10
2014	10/10	10/10	10/10	10/10
2015	10/10	10/10	10/10	10/10
2016	10/10	10/10	10/10	10/10
2017	10/10	10/10	10/10	10/10
2018	10/10	10/10	10/10	10/10
2019	10/10	10/10	10/10	10/10
2020	10/10	10/10	10/10	10/10
2021	10/10	10/10	10/10	10/10
2022	10/10	10/10	10/10	10/10
2023	10/10	10/10	10/10	10/10
2024	10/10	10/10	10/10	10/10
2025	10/10	10/10	10/10	10/10
2026	10/10	10/10	10/10	10/10
2027	10/10	10/10	10/10	10/10
2028	10/10	10/10	10/10	10/10
2029	10/10	10/10	10/10	10/10
2030	10/10	10/10	10/10	10/10
2031	10/10	10/10	10/10	10/10
2032	10/10	10/10	10/10	10/10
2033	10/10	10/10	10/10	10/10
203				

PERFIS	SDPV	SNF	SCA	OF	ALLOY	ON	DELTA	TOT	TEMP
--------	------	-----	-----	----	-------	----	-------	-----	------

00744	1.35391	.02097	.91249	18.900	1.192	4.7834	NZ	533.07
-------	---------	--------	--------	--------	-------	--------	----	--------

	SP	POWER	FUEL	TURNS OF FUEL OR ALLOY
FLUX				

FEED	DEPRESSOR	OR FCONST	FEXP	TEMP	IN CORE
1	0	0	0	0	0
2	0	0	0	0	0
3	0	0	0	0	0
4	0	0	0	0	0
5	0	0	0	0	0
6	0	0	0	0	0
7	0	0	0	0	0
8	0	0	0	0	0
9	0	0	0	0	0
10	0	0	0	0	0
11	0	0	0	0	0
12	0	0	0	0	0
13	0	0	0	0	0
14	0	0	0	0	0
15	0	0	0	0	0
16	0	0	0	0	0
17	0	0	0	0	0
18	0	0	0	0	0
19	0	0	0	0	0
20	0	0	0	0	0
21	0	0	0	0	0
22	0	0	0	0	0
23	0	0	0	0	0
24	0	0	0	0	0
25	0	0	0	0	0
26	0	0	0	0	0
27	0	0	0	0	0
28	0	0	0	0	0
29	0	0	0	0	0
30	0	0	0	0	0
31	0	0	0	0	0
32	0	0	0	0	0
33	0	0	0	0	0
34	0	0	0	0	0
35	0	0	0	0	0
36	0	0	0	0	0
37	0	0	0	0	0
38	0	0	0	0	0
39	0	0	0	0	0
40	0	0	0	0	0
41	0	0	0	0	0
42	0	0	0	0	0
43	0	0	0	0	0
44	0	0	0	0	0
45	0	0	0	0	0
46	0	0	0	0	0
47	0	0	0	0	0
48	0	0	0	0	0
49	0	0	0	0	0
50	0	0	0	0	0
51	0	0	0	0	0
52	0	0	0	0	0
53	0	0	0	0	0
54	0	0	0	0	0
55	0	0	0	0	0
56	0	0	0	0	0
57	0	0	0	0	0
58	0	0	0	0	0
59	0	0	0	0	0
60	0	0	0	0	0
61	0	0	0	0	0
62	0	0	0	0	0
63	0	0	0	0	0
64	0	0	0	0	0
65	0	0	0	0	0
66	0	0	0	0	0
67	0	0	0	0	0
68	0	0	0	0	0
69	0	0	0	0	0
70	0	0	0	0	0
71	0	0	0	0	0
72	0	0	0	0	0
73	0	0	0	0	0
74	0	0	0	0	0
75	0	0	0	0	0
76	0	0	0	0	0
77	0	0	0	0	0
78	0	0	0	0	0
79	0	0	0	0	0
80	0	0	0	0	0
81	0	0	0		

1.3745 2.7815 1.39057 11.230 349.84 391.86756

ONE DIMENSIONAL ALTHAEA PARAMETERS

FUEL+TARGET										VERT	BUCK	BARE	HEIGHT
10	000	0	000	1	000	000	000	000	000				

SS1	SS2	SS3	SS4	XISS1	XISS2	XISS3	SS4	SPEC	VOL FRACT-VR	BUCK	HORT
-----	-----	-----	-----	-------	-------	-------	-----	------	--------------	------	------

0.19258	0.42241	0.37789	0.38643	0.042507	0.098750	0.084249	0.16294	0.14583	0.07187	2.4796-05	5.6027+02
---------	---------	---------	---------	----------	----------	----------	---------	---------	---------	-----------	-----------

.....DLTHACA ABSOLUTE FLUX GUESS -- CONVERSION FACTOR=8.1906E+12.....

-----CELL INFORMATION (PER FOOT OF CELL)-----

TAR. REGIONS	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	24
--------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	----

4.4903	1.10189	1.20335	1.11523	11.46876	110.48250	10.23708	0.00888	0.00446
--------	---------	---------	---------	----------	-----------	----------	---------	---------

SG 13771	EG 13772	SG 13773	EG 13774	EG 13775	EG 13776	EG 13777	EG 13778
----------	----------	----------	----------	----------	----------	----------	----------

U-235 CASE NUMBER 1102

ALTERNATE FUEL - HP235 - AL - TARGET
SEU .735WT.0/0 U-235 METAL FUEL

INPUT-CONTROL-DATA

N	K1	K2	K4	K5	DSMEAR	ECCOR	BUCK	STRCOR	MEVFIS	DEL								
7	0	1	0		0	9.3220 01	2.4796 85	1.0600+00	2.0200+02	9.8699								
K6	K7	K8	K9	K10	K11	K12	FPER	TPER	KOIL	UR235	LO50EG	OPHI	MELALT	A7	SPWHR	HEIGHT	ADDER	
-0	-0	-0	2	0	2	-0	-0.00	-0.00	-0	-0.000	-0	-0	2	2.00	11.23	.692	-.0000	

INPUT FUEL COMPOSITIONS

ISOTOPE											DILUENT	
WEIGHT PERCENT											ftft:UENT	VOLUME
REGION	TH232	U233	U234	U235	U236	U238	PU239	PU240	PU241	PU242	NUMBER	PERCENT
3	.000	.000	.000	.800	.000	99.200	.000	.000	.000	.000	0	.000

INPUT REGION INFORMATION

REGION NUMBER	RADIUS CM.	RADIUS INCHES	MATERIAL	DENSITY GM/CC	TEMP DEG C	TEMP DEG F	VOLUME FRAC TON	THICKNESS REG-INCH	THICKNESS BARN CM	PERCENT
1	.40000	.15750	H2O	.986	33.840	128.912	.01712	.19250	3.29620-02	
2	.63246	.24900	ALUMN	2.702	114.840	238.712	.00472	.05650	6.02546-02	
3	1.73990	.68500	U235 ML	18.900	349.840	661.112	.07187	.43600	3.87522-04	
			U238						4.14471-02	
4	1.05293	.41250	ALUMN	2.702	109.840	229.712	.01714	.04450	6.02546-02	
5	2.12344	.83600	H2o	.981	64.840	148.712	.03157	.10650	3.27948-02	
6	2.29362	.90100	ALUMN	2.702	109.840	229.712	.02270	.06700	6.02546-02	
7	5.83757	2.29826	GRAPHIT	1.638	559.840	1039.712	.84562	1.39526	8.21375-02	

MODERATOR TO FUEL RATIOS

H/FOEL D/FUEL GRIPAT/FOEL
.7367 .0000 29.2037

IF ARRAY IS TRIANGULAR, PL CA - 4.37/3 INCHES
 IF ARRAY IS SQUARE, PITCH = 4.0736 INCHES

OUTPUT FOR GROUP 1 CELL VALUES

AGE= 132.01 SIGMA REMOVAL=1.340-02 SIGMA TRANSPORT=1.925-01 FLUX OEPRES= .8389 FEXP= -7.4547 FCONST= -14.9093 SNF= .04751

REGION	FLUX	VOLUME	ABSORPTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA TRANSPORT	NU
1	1.7319+00	7.5107-01	.00015	8.7381-02	2.2942-04	4.0082-01	8.7151-02	2.8699-01	1.5510-01	
2	1.74/6+00	5.0559-01	.00010	3.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3805-01		
3	1.7033+00	7.6941+00	.10259	2.3560-02	1.6048-02	3.7219-01	7.5120-03	1.5083-01	1.1605-02	2.807
4	1.5962+00	1.8354+00	.00034	3.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3805-01		
5	1.5599+00	3.3792+00	.00059	8.6938-02	2.2825-04	3.9879-01	8.6710-02	2.8553-01		
6	1.5302+00	2.3610+00	.00041	3.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3805-01		
7	1.3904+00	9.0530+01	.00000	9.6922-03	0.0000	2.1816-01	9.6922-03	1.9524-01		
TOTAL			.10417							

OUTPUT FOR GROUP 2

CELL VALUES

AGE= 70.51 SIGMA REMOVAL=1.107-02 SIGMA TRANSPORT:4.223-01 FLUX DEPRES=1.1222 FEXP= 1.8504 FCONST= 3.7008 SNF= .36542

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA A8SORP'	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	1.3157+00	7.5107-01	.00032	1.0061-01	6.6814-04	1.3636+00	9.9941-02	9.0415-01		
2	1.3074+00	5.0559-01	.00045	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
3	1.3431+00	7.6941+00	.31013	6.2308-02	6.1525-02	1.1820+00	7.8283-04	1.1626+00	8.3366-03	2.430
4	1.4171+00	1.8154+00	.00177	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
5	1.4391+00	3.3792+00	.00158	1.0010-01	6.6475-04	1.3567+00	9.9434-02	8.9956-01		
6	1.4606+00	2.3615+00	.00234	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
7	1.5295+00	9.0530+01	.00057	4.8390-03	8.4602-06	3.8276-01	4.8305-03	3.6108-01		
		TOTAL	.31116							

OUTPUT FOR GROUP 3

CELL VALUES

AGE= 9.74 SIGMA REMOVAL=3.607-02 SIGMA TRANSPORT=3.177-01 FLUX DEPRES=1.4910 FEXP= 1.2929 rcer4sr= 2.5857 SNF= .eOS67

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA A8SORP'	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	7.1179-02	7.5107-01	.00014	8.8198-01	5.5268-03	1.5097+00	8.7046-01	9.9884-01		
2	6.5197-02	5.0559-01	.00006	9.6004-03	3.4944-03	8.7008-02	6.1060-03	8.4838-02		
3	6.8279-02	7.6941+00	.07829	3.0896-01	3.0553-01	4.2167-01	3.4290-03	4.2048-01	1.0347-01	2.430
4	8.1269-02	1.8354+00	.00025	9.6004-03	3.4944-03	8.7008-02	6.1060-03	8.4838-02		
5	8.5036-02	3.3792+00	.00081	8.7751-01	5.4988-03	1.5020+00	8.7046-01	9.7777-01		
6	9.4783-02	2.3615+00	.00038	9.6004-03	3.4944-03	8.7008-02	6.1060-03	8.4838-02		
7	1.0618-01	9.0530+01	.00013	5.9201-03	7.0517-05	3.8687-01	5.7171-02	3.3918-01		
		TOTAL	.08027							

OUTPUT FOR GROUP 4

CELL VALUES

DIF LENG= 66.522 SIGMA ABSORP=1.329-02 SIGMA TRANSPORT=3.995-01 FLUX DPRES=1.396-01 FEXP= 1.3841 FCONST= 2.7681 SNF= .02088

	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	R VALUE	SIGMA ABSORP	SIGMA SCATTER	SIGMA TRANSPORT	NEUT TEMP DEG C	SIGMA FISSION	HEAT TRANSFER NO UTILIZATION
1	5.2274-01	7.5107-01	.00297	.1797	1.5527-02	2.5820+00	1.5066+00	184.79		
2	4.8977-01	5.0559-01	.00107	.1898	8.8692-03	8.5200-02	9.2023-02	287.92		
3	5.1399-01	7.6941+00	.46588	.1862	2.4151-01	3.8888+01	6.2930-01	287.83	1.3398-01	2.430 1.000
4	5.9007-01	1.3154+00	.00469	.1719	8.8707-03	8.5200-02	9.2625-02	287.72		
5	6.4311-01	3.3792+00	.01328	.1609	1.2525-02	2.3097+00	1.2591+00	423.49		
6	6.7672-01	2.3615+00	.00568	.1555	7.2805-03	8.5200+02	9.1034-02	559.51		
7	7.4470-01	9.0530+01	.60483	.1483	1.4689-04	3.8687+01	3.6533-01	559.84		
		TOTAL	.49849							

CELL DATA

CONVERSION RATIO= .918 K INFINITY:1.103 MIGRATION AREA= 243.18 MATERIAL BUCKLING: 1.164-05

FOUR GROUP EPSILON=1.111

OLD METHOD U238 EPSILON=1.024

ISOTOPE CONCENTRATIONS U-IUCLEI/BARN eM)

U235	U238
3.87322-04	4.74471-02

ZERO DIMENSIONAL ALTHAEA INPUT PARAMETERS

MELEAGER		FUEL+OR		TARGET DENS		MELEAGER	
PERFIS	SDPV	SNF	seA	ALLOY	DELTA	TOT	TEMP
100810	1.35356	02008	91248	191950	11192	4.7835-02	535107

FLUX	DEPRESS	of	FCNST	FEXP	SP POWER	FUEL	TONNES OF FUEL OR ALLOY
1.3969	2.76812	1.38408	11.230	349.84	391.80756		

ONE DIMENSIONAL ALTHAEA PARAMETERS

551	552	553	554	555	556	557	558	559	560	561	562	563	564	565	566	567	568	569	570	571	572	573	574	575	576	577	578	579	580	581	582	583	584	585	586	587	588	589	590	591	592	593	594	595	596	597	598	599	600	601	602	603	604	605	606	607	608	609	610	611	612	613	614	615	616	617	618	619	620	621	622	623	624	625	626	627	628	629	630	631	632	633	634	635	636	637	638	639	640	641	642	643	644	645	646	647	648	649	650	651	652	653	654	655	656	657	658	659	660	661	662	663	664	665	666	667	668	669	670	671	672	673	674	675	676	677	678	679	680	681	682	683	684	685	686	687	688	689	690	691	692	693	694	695	696	697	698	699	700	701	702	703	704	705	706	707	708	709	710	711	712	713	714	715	716	717	718	719	720	721	722	723	724	725	726	727	728	729	730	731	732	733	734	735	736	737	738	739	740	741	742	743	744	745	746	747	748	749	750	751	752	753	754	755	756	757	758	759	760	761	762	763	764	765	766	767	768	769	770	771	772	773	774	775	776	777	778	779	780	781	782	783	784	785	786	787	788	789	790	791	792	793	794	795	796	797	798	799	800	801	802	803	804	805	806	807	808	809	810	811	812	813	814	815	816	817	818	819	820	821	822	823	824	825	826	827	828	829	830	831	832	833	834	835	836	837	838	839	840	841	842	843	844	845	846	847	848	849	850	851	852	853	854	855	856	857	858	859	860	861	862	863	864	865	866	867	868	869	870	871	872	873	874	875	876	877	878	879	880	881	882	883	884	885	886	887	888	889	890	891	892	893	894	895	896	897	898	899	900	901	902	903	904	905	906	907	908	909	910	911	912	913	914	915	916	917	918	919	920	921	922	923	924	925	926	927	928	929	930	931	932	933	934	935	936	937	938	939	940	941	942	943	944	945	946	947	948	949	950	951	952	953	954	955	956	957	958	959	960	961	962	963	964	965	966	967	968	969	970	971	972	973	974	975	976	977	978	979	980	981	982	983	984	985	986	987	988	989	990	991	992	993	994	995	996	997	998	999
0.19258	0.42232	0.37780	0.38629	0.042507	0.098732	0.084160	0.16288	0.15144	0.07187	2.4796-05	5.6027+02																																																																																																																																																																																																																																																																																																																																																																																																																																																					

ALTHAEA ABSOLUTE FLUX GUESS - CONVERSION FACTOR = 1.9848+12

CLAD SURFACE	MODERATOR VOLUME	OUTSIDE SURFACE CYLINDER	CELL VOLUME	VOL MOD PER	FUEL+OR TARGET WEIGHT	MODERATOR HEIGHT	FUEL+OR TARGET VOLUME	CLADDING VOLUME
TAN REGIONS								
0.48903	0.10189	1.20335	0.11523	11.46876	10.48250	10.23708	0.00888	0.00446
53 FT/FT	CU FT/FT	50 FT/FT	CU FT/FT		LBS/FT	LBS/FT	CU FT/FT	CU FT/FT

JASON CASE NUMBER 1202

KPR ALTERNATE TONE = RF237-AL TARGET
SEU .735WT.0/0 U-235 METAL FUEL

INPUT CONTROL DATA

N	K1	K2	K3	K4	K5	OSWEAR	ECCOR	BUCK	STRCOR	MEVFIS	DEL						
7	0	1		0		0	9.5220-01	2.4796-05	1.0600+0	2.0200+02	-0.0000						
K6	K7	K8	K9	K10	K11	K12	FPER	TPER	FCIL	UM20	COAREG	UPHT	WELLET	AT SP	POWER	HEIGHT	ADDER
-0	-0	-0	2	0	0	-0	-0.00	-0.00	-0	-0.000	-0	-0	2	2.00	11.23	.692	-0.0000

INPUT FUEL COMPOSITIONS
ISOTOPE

REGION	TH232	U233	U234	U235	U236	U238	PU239	PU240	PU241	PU242	DILUENT NUMBER	DILUENT VOLUME PERCENT
3	.000	.000	.000	1.000	.000	99.000	.000	.000	.000	.000	0	.000

INPUT REGION INFORMATION

REGION NUMBER	RADIUS CM.	RADIUS INCHES	MATERIAL	DENSITY GM/CC	TEMP DEG C	TEMP DEG F	VOLUME FRACTION	THICKNESS REG-INCH	WELLET BARN	FEH CM
1	.48895	.19250	H2O	.986	53.840	128.912	.00702	.19250	3.29520-02	
2	.63246	.24900	ALUMN	2.702	114.840	238.712	.00472	.05650	6.02546-02	
3	1.73990	.68500	U235 ML	18.900	340.840	661.712	.07187	.43600	4.84403-04	
			U238						4.73514-02	
4	1.05295	.412950	ALUMN	2.702	104.840	229.712	.01714	.09460	6.02546-02	
5	2.12344	.83600	H2O	.986	64.840	148.712	.03157	.10650	3.27948-02	
6	2.29382	.90300	ALUMN	2.702	104.840	229.712	.02296	.09460	6.02546-02	
7	5.83757	2.29826	GRAPHIT	1.638	559.840	1039.712	.84562	1.39526	8.21375-02	

MODERATOR TO FUEL RATIOS

R/FUEL .7367
 D/FUEL .0000
 GRAPH / FUEL 26.2032

IF ARRAY IS TRIANGULAR, PITCH = 4.3773 INCHES
 IF ARRAY IS SQUARE, PITCH = 4.0736 INCHES

OUTPUT FOR GROUP 1

FELL VALUES

AGE= 131.93 SIGMA REMOVAL=1.391-02 SIGMA TRANSPORT=1.926-01 FLUX DEPLES= .0189 FLXP= -7.4224 FCONSR= -14.8448 SNF= .04816

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORB	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	1.7307+00	7.5107-01	.00015	8.7381-02	2.2942-04	4.0082-01	8.7151-02	2.8699-01		
2	1.7464+00	5.0559-01	.00010	5.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01		
3	1.7021+00	7.6941+00	.10322	2.3662-02	1.6150-02	3.7205-01	7.5120-03	1.5079-01	1.1704-02	2.805
4	1.5951+00	1.8354+00	.00034	3.4159-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01		
5	1.5588+00	3.3792+00	.00059	8.6938-02	2.2825-04	3.9879-01	8.6710-02	2.8553-01		
6	1.5292+00	2.3415+00	.00051	3.4159-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01		
7	1.3895+00	9.0530+01	.00000	9.6922-03	0.0000	2.1816-01	9.6922-03	1.9524-01		
		TOTAL	.10481							

OUTPUT FOR GROUP 2

CELL VALUES

AGE= 69.83 SIGMA REMOVAL=1.174-02 SIGMA TRANSPORT=4.220-01 FLUX uEPRES=1.1263 FEXP= 1.8429 FCONST= 3.6858 SNF= .37457

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	1.2955+00	7.5107-01	.00032	1.0061-01	6.6814-04	1.3636+00	9.9941-02	9.0415-01		
2	1.2861+00	5.0559-01	.00044	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
3	1.3228+00	7.6941+00	.31672	6.4548-02	6.3766-02	1.1808+00	7.8204-04	1.1614+00	9.9442-03	2.430
4	1.3985+00	1.8354+00	.00172	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
5	1.4210+00	3.3792+00	.00156	1.0010-01	6.6475-04	1.3567+00	9.9434-02	8.9956-01		
6	1.4423+00	2.1615+00	.00031	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
7	1.5124+00	9.0530+01	.00057	4.8390-03	8.4602-06	3.8276-01	4.8305-03	3.6108-01		
		TOTAL	.32360							

OUTPUT FOR GROUP 3

CELL VALUES

AGE= 9.60 SIGMA REMOVAL=4.740-02 SIGMA TRANSPORT=3.775-01 FLUX uEPRES=1.5000 FEXP= 1.2581 FCONST= 2.5174 SNF=-.00483

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	6.6432-02	7.5107-01	.00013	8.4200-01	5.5267-03	1.5097+00	8.7640-01	9.9684-01		
2	6.0330-02	5.0559-01	.00005	9.6006-03	3.4943-03	8.7008-02	6.1063-03	8.4838-02		
3	6.2678-02	7.6941+00	.08473	3.0344-01	3.6000-01	4.2230-01	3.4342-03	4.2110-01	1.2851-01	2.430
4	7.7290-02	1.8354+00	.00024	9.6006-03	3.4943-03	8.7008-02	6.1063-03	8.4838-02		
5	8.5624-02	3.3792+00	.00078	8.7753-01	5.4987-03	1.5020+00	8.7203-01	9.9178-01		
6	9.1727-02	2.1615+00	.00037	9.6006-03	3.4943-03	8.7008-02	6.1063-03	8.4838-02		
7	1.0174-01	9.0530+01	.00032	5.9284-02	7.0516-03	3.8687-01	5.9194-02	3.6518-01		
		TOTAL	.08662							

OUTPUT FOR GROUP 4

CELL VALUES

DIF LENG= 60.371 SIGMA ABSORP:1.461-C2 SIGMA TRANSPORT=4.00S-01 FLUX DPRES=1.4671 FEXP= 1.3647 FCONST= 2.7293 SNF= .02060

REGION	FLUX	VOLUME CMS/CM	ABSORP FRACTION	R VALUE	SIGMA ABSORP	SIGMA SCATTER	SIGMA TRANSPORT	NEUT TEMP DEG C	SIGMA FISSION	HEAT TRANSFER MW	UTILIZATION
1	4.4104-01	7.5107-01	.00251	.2006	1.5527-02	2.5820+00	1.5066+00	184.79			
2	4.0866-01	5.2559-01	.00089	.2203	8.8692-03	8.5269-02	9.2023-02	287.92			
3	4.3292-01	7.6941+00	.45656	.2145	2.8086-01	3.8966TO1	6.6942-01	287.83	1.6747-01	2.430	1.000
4	5.1039-01	1.0154+00	.00466	.1938	8.0707-03	4.5280-02	9.2525-02	287.72			
5	5.6218-01	3.5792+00	.01161	.1797	1.2525-02	2.3097+00	1.2591+00	423.49			
6	5.9504-01	2.3616+00	.00499	.1729	7.2465-03	8.5300-02	9.1034-02	559.51			
7	6.6149-01	9.0530+01	.00429	.1635	1.4689-04	3.8687-01	3.6533-01	559.84			
TOTAL			.148491								

CELL DATA

CONVERSION RATIO: .783 K INFINITY=1.065 MIGRATION AREA= 237.95 MATERIAL BUCKLING= 2.727-04

FOUR GROUP EPSILON=1.097 OLD METHOD U238 EPSILON=1.024

ISOTOPE CONCENTRATIONS (tJUCLEI/BARN eM)

U235 4.83403-04
U238 4.73516-02

ZERO DIMENSIONAL ALTHAEA INPUT PARAMETERS

PERF IS	MELEAGER SDPV	SHF	seA	FUEL +/OR TARGET DENS OF METAL OR ALLOY	DELTA	TOT	MELEAGER TEMP
.01913	1.35234	.02046	.91247	10.900	1.142	4.7835-02	533.07

FLOX	DEPRESSION OF J	FCONST	FEXP	SP POWER MW/TQINE	FUEL TEMP	TQINE 5 DP IN CORE	FUEL TOX ALLOY
1.4071	2.72933	1.36466	11.230	349.84	591.30756		

ONE DIMENSIONAL ALTHAEA PARAMETERS

SS1	SS2	SS3	SS4	SS5	SS6	SS7	SS8	SS9	SS10	FUEL+TARGET VOL. FRACT=VR	VERT BUCK BURN	BARE HEIGHT HORT
.19258	.42204	.37752	.38584	.042507	.008680	.083915	.16273	.10753	.07187	2.4796-05	5.6027+02	

ALTHAEA ABSOLUTE FLOW GROSS = CONVERSION FACTOR = 7.5111+12

CELL INFORMATION PER FOOT OF CELL 1:1

CLAD SURFACE CF FUEL+/OR TAX REGIONS	MODERATOR VOLUME	OUTSIDE SURFACE CYLINDER	CELL VOLUME	VOL MOD PER VOL FUEL+/OR TARGET	FUEL+/OR TARGET WEIGHT	MODERATOR WEIGH	FUEL+/OR TARGET VOLUME	CLADDING VOLUME
.48903	.10189	1.20335	.11523	11.46876	10.48250	10.23703	.00888	.00446
LB/FT	CU FT/FT	SB FT/FT	CU FT/FT		LB/FT	LB/FT	CU FT/FT	CU FT/FT

JASON CASE NUMBER 1204

APR ALTERNATE FUEL TYPE 237 AL-TARGET
SEU .735WT.0/0 U-235 METAL FUEL

INPUT CONTROL 01-1A

N	K1	K2	K3	K4	K5	DSMEAR	ECCOR	BUCK	STRCOR	MEVFIS	DEL						
7	0	1		a	0	a	9.3220-01	2.4796 as	1.0660-80	2.0200-02	8686ee						
K6	K7	K8	K9	K10	K11	K12	FPER	TPER	KOIL	UR426	LOSS	JP10	MELT	A7-SP	POWER	HEIGHT	ADDER
-0	-0	-0	2	0	3	-0	-1.00	.14	2	-0.000	-0	-0	4	2.00	11.23	.692	-0.0000

INPUT FUEL COMPOSITIONS
ISOTOPE

REGION	TH232	U233	U234	U235	U236	U238	PU239	PU240	PU241	PU242	DILUENT NUMBER	DILUENT VOLUME PERCENT
--------	-------	------	------	------	------	------	-------	-------	-------	-------	-------------------	------------------------------

INPUT REGION INFORMATION

REGION NUMBER	RADIUS CM	RADIUS INCHES	MATERIAL	DENSITY GM/CC	TEMP DEG C	TEMP DEG F	VOLUME FRACTION	THICKNESS INCH	NUCLEI PER CM
1	.48895	.19250	H2o	.986	53.840	128.912	.00702	.19250	3.29620-02
2	.63245	.24900	ALUMN	2.702	109.840	229.712	.00472	.10550	6.02348-02
3	1.73990	.68500	NEPr	2.723	126.840	260.312	.07187	.43600	6.26050-05
			ALUMN						6.02348-02
4	1.85293	.72950	ALUMN	2.702	109.840	229.712	.01714	.04450	6.02546-02
5	2.12344	.83800	H2O	.981	53.840	128.912	.03157	.10550	3.27948-02
6	2.29362	.90300	ALUMN	2.702	109.840	229.712	.02206	.06700	6.02546-02
7	5.83757	2.29820	GRAPH	1.808	359.800	1039.712	.04562	1.39526	8.21375-02

126.84
273.16
400-20
273.16
553.12

MODERATOR TO FUEL RATIOS

H/FUEL D/FUEL GRAPATIFOEL
 .0000 .0000 .0000

IF ARRAY IS TRIANGULAR, PITCH = 4.3773 INCHES
 IF ARRAY IS SQUARE, PITCH = 4.0736 INCHES

OUTPUT FOR GROUP 1

CELL VALUES

AGE= 151.33 SIGMA REMOVAL=1.218-02 SIGMA TRANSPORT=1.010-01 FLUX DEPRES: .8542 FEXP=-2061.4410 FCONST:-4122.8821 SNF= .05235

REGION	FLUX	VOLUME CM ³ /CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	1.9524+00	7.5137-01	.00016	8.7381-02	2.2942-04	4.0082-01	8.7151-02	2.8699-01		
2	1.9639+00	5.0559-01	.00011	3.4189-03	2.3499-04	2.0093-01	3.1859-03	1.3865-01		
3	1.9255+00	7.6941+00	.00209	3.4942-03	3.0233-04	2.0137-01	3.1919-03	1.3895-01	6.0577-05	2.959
4	1.8459+00	1.8354+00	.00037	3.4189-05	2.3499-04	2.0093-01	3.1859-03	1.3865-01		
5	1.8011+00	3.3792+00	.00065	8.6938-02	2.2825-04	3.9819-01	8.6710-02	2.8553-01		
6	1.7651+00	2.3615+00	.00046	3.4189-03	2.3499-04	2.0093-01	3.1859-03	1.3865-01		
7	1.6035+00	9.0530+01	.00000	9.6922-03	0.0000	2.1816-01	9.6922-03	1.9524-01		
		TOTAL	.00382							

OUTPUT FOR GROUP 2

CELL VALUES

AGE= 119.79 SIGMA REMOVAL=0.304-03 SIGMA TRANSPORT=3.552-01 FLUX DEPLE=1.0219 FEXP= 9.1954 FCONST= 18.3908 SNF= .52646

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	2.3855+00	7.5107-01	.00056	1.0061-01	6.6814-04	1.3636+00	9.9941-02	9.0415-01		
2	2.3931+00	5.0559-01	.00078	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
3	2.3964+00	7.6941+00	.03213	4.5111-03	3.7433-03	1.3453-01	7.6783-04	1.2998-01	2.4645-07	2.679
4	2.3967+00	1.8354+00	.00205	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2917-01		
5	2.4017+00	3.3792+00	.00251	1.0010-01	6.6475-04	1.3567+00	9.9434-02	8.9956-01		
6	2.4138+00	2.3615+00	.00309	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
7	2.4578+00	9.0530+01	.00088	4.8390-03	8.4602-06	3.8276-01	4.8305-03	3.6108-01		
TOTAL			.0431							

OUTPUT FOR GROUP 3

CELL VALUES

AGE= 11.08 5161.0 REMOVAL=8.918-02 SIGMA TRANSPORT=3.578-01 FLUX OEPRES=1.8677 FEXP= 2.1846 rceUST= 4.3691 SNF= .9672&

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	1.6752-01	7.5107-01	.00032	9.0014-01	5.4533-03	1.5097+00	8.9949-01	9.9884-01		
2	1.6742-01	5.0559-01	.00014	9.8585-03	3.4479-03	8.7008-02	6.4106-03	8.4838-02		
3	1.6819-01	7.6941+00	.02013	3.9823-02	3.3409-02	8.7633-02	6.4141-03	8.5463-02	1.1821-06	2.070
4	1.6932-01	1.8354+00	.00050	9.8585-03	3.4479-03	8.7008-02	6.4106-03	8.4838-02		
5	1.7198-01	3.3792+00	.00147	8.9958-01	5.4257-03	1.5020+00	8.9015-01	9.9178-01		
6	1.7483-01	2.3615+00	.00066	9.8585-03	3.4479-03	8.7008-02	6.4106-03	8.4838-02		
7	1.8132-01	9.0530+01	.00053	6.2213-02	6.9580-03	3.8087-01	6.2144-02	3.6315-01		
TOTAL			.02375							

CUTPUT FOR GROUP 4

CELL VALUES

DIF LENG= 456.955 SIGMA ABSORP=2.487-01 SIGMA TRANSPORT:3.706-01 FLUX DPRES:1.0267 FEXP: 3.7107 FCONST= 7.4214 SNF= .03662

REGION	FLUX	VOLUME	ABSORPTION	R	SIGMA	SIGMA	SIGMA	NEUT	SIGMA	HEAT TRANSFER
		CM ³	FRACTION	VALUE	ABSORP	SCATTER	TRANSPORT	TEMP DEG C	FISSTON	NO UTILIZATION
1	8.7142+00	7.5107-01	.04732	.0214	1.5531-02	2.5825+00	1.5071+00	184.56		
2	8.0837+00	5.0559-01	.01814	.0216	8.8723-03	8.5200-02	9.2626-02	287.52		
3	8.7010+00	7.6941+00	.49754	.0216	1.5963-02	8.5829-02	1.0034-01	287.64	1.6891-07	2.670 1.000
4	8.7299+00	1.2054+00	.06617	.0215	8.8717-03	8.5200-02	9.2625-02	287.72		
5	8.8036+00	3.3792+00	.17348	.0214	1.2525-02	2.3097+00	1.2591+00	423.49		
6	8.8526+00	2.3615+00	.07086	.0214	7.2805-03	8.5200-02	9.1034-02	559.51		
7	8.9671+00	9.0530+01	.05552	.0215	1.4689-04	3.8687-01	3.6533-01	559.84		
TOTAL			.92902							

CELL DATA

CONVERSION RATIO: .000 K INFINITY= .000 MIGRATION AREA= 794.84 MATERIAL BUCKLING=-1.419-03

FOUR GROUP EPSILON= .996 CLG METHOD U238 EPSILON=1.000

ISOTOPE CONCENTRATIONS (NUCLEI/BARN CM)

U237	POISON
6.20037-05	6.02346-02

ZERO DIMENSIONAL ALTHAEA INPUT PARAMETERS

FUEL+OR
TAP GET OEUS
OF METAL OR
PERFIS SDPV SNF seA ALLOY DELTA TOT TEMP
.00000 1.38172 .03662 .48934 2.723 1.171 4.829702 533.07

FLUX SP POWER FUEL TONNES OF FUEL FOR ALLOY
DEPRESSOR I FCONST FEXP MW/TONNE TEMP IN CORE
1.20 7.42139 3.7107 11.238 69 391.88756

ONE DIMENSIONAL ALTHAEA PARAMETERS

FUEL+TARGET VERT BUCK BARE HEIGHT
S24 SPEC VOL FRACT-VR BUCK HORT
.9164 .35520 .35764 .36849 .041264 .100148 .085662 .17584 .02147 .07187 2.4796-05 1.0687+03

ALTHAEA ABSOLUTE FLUX GUESS - CONVERSION FACTOR=9.90E+14

CLAD		MODERATOR		OUTSIDE		CELL		VOL MOD		FUEL+OR		MODERATOR		FUEL+OR		CLASSING	
SURFACE		VOLUME		SURFACE		VOLUME		PERCENT		TARGET		WEIGHT		VOLUME		VOLUME	
OF FUEL+OR				CYLINDER				VOL FUEL+OR		WEIGHT				VOLUME			
TAR REGIONS						TARGET											
.98903		.12189		1.22330		.11523		11.46876		1.51018		10.23708		.00888		.00446	
SQ FT/FT		CU FT/FT		SQ FT/FT		CU FT/FT		CU FT/FT		LBS/FT		LBS/FT		CU FT/FT		CU FT/FT	

Handwritten calculations and notes:

- Left side: $122.6 / 5.7 \approx 21.4$
- Top left: $225.6 / 22.7 \approx 9.9$
- Top middle: 1.509685
- Middle: 614.2747
- Bottom left: 5431401 , 5.5×10^6
- Right side: $122.6 = 10^3 / 8$
- Bottom right: $122.6 = 10^3 / 8$

 JASON CASE NUMBER 1302

KNR ALTERNATE TONE = TP537-AL TARGE1
 SEU .735WT.0/0 U-235 METAL FUEL

 INPUT CONTROL DATA

N	K1	K2	K3	K4	K5	DSMEAR	ECCOR	BUCK	STRONG	MEVFIS	DEL
1	0	1		0	0	0	9.3220-01	2.4770-00	1.0600+00	2.0200+02	0.0000

JB	KB	K7	K8	K10	K11	K12	PPER	TPER	KDIL	WAZE	LOSREG	SPHI	MCCLT	AT	SPWER	WEIGHT	ADDER
-0	-0	-0	2	0	3	-0	-0.00	-0.00	0	-0.000	-0	-0	2	2.00	11.23	.692	-0.0000

 INPUT FUEL COMPOSITIONS

REGION	TH232	U233	U234	U235	ISOTOPE WEIGHT PERCENT		PU239	PU240	PU241	PU242	DILUENT NUMBER	DILUENT
					U236	U238						VOLUME PERCENT
1	.000	.000	.000	1.500	.000	98.500	.000	.000	.000	.000	0	.000

 INPUT REGION INFORMATION

REGION NUMBER	RADIUS CM.	RADIUS INCHES	MATERIAL	DENSITY GM/CC	TEMP DEG C	TEMP OEG F	VOLUME FRACTION	THICKNESS REG-INCH	NUCLEI PER BARN eM
1	.44875	.19250	ALUMN	1.900	53.840	128.912	.00472	.19250	3.29620-02
2	.63246	.24900	ALUMN	2.702	114.840	238.712	.00472	.05650	6.02546-02
3	1.73990	.68500	u235 ML U238	18.900	349.840	601.712	.0718/	.43600	1.26604-04 4.71123-02
4	1.65203	.12950	ALUMN	2.702	109.840	229.712	.01714	.04450	6.02546-02
5	2.12344	.83600	H2o	.981	64.840	148.712	.03157	.10650	3.27948-02
6	2.29362	.90300	ALUMN	2.702	109.840	229.712	.02206	.06700	6.02546-02
7	5.83757	2.29826	GRAPHIT	1.638	559.840	1039.712	.84562	1.39526	8.21375-02

MODERATOR TO FUEL RATIOS

REFUEL 0.7367
 O/FUEL 0.0000
 SCRAM FUEL 29.2019

IF ARRAY IS TRIANGULAR, PITCH = 7.3773 INCHES
 IF ARRAY IS SQUARE, PITCH = 4.0738 INCHES

OUTPUT FOR GROUP 1

CELL VALUES

AGE= 131.73 SIGMA REMOVAL=1.993-02 SIGMA TRANSPORT=1.926-01 FLUX DEPRES= .8389 FCRP= -7.3429 FCONST= -14.6858 SNF= .04960

REGION	FLUX	VOLUME CM3/GM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	1.7278+00	7.5107-01	.00015	8.7381-02	2.2942-04	4.0082-01	8.7151-02	2.8699-01		
2	1.7434+00	5.0559-01	.00010	3.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01		
3	1.6993+00	7.6941+00	.10476	2.3917-02	1.6406-02	3.7110-01	7.5117-03	1.5070-01	1.1951-02	2.801
4	1.5924+00	1.8354+00	.00034	3.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01		
5	1.5562+00	3.3792+00	.00059	8.6938-02	2.2825-04	3.9879-01	8.6710-02	2.8553-01		
6	1.5267+00	2.3615+00	.00041	3.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01		
7	1.3872+00	9.0530+01	.00000	9.6922-03	0.00000	2.1816-01	9.6922-03	1.9524-01		
		TOTAL	.10034							

OUTPUT FOR GROUP 2

CELL VALUES

AGE= 67.60 SIGMA REMOVAL=1 241-02 SIGMA TRANSPORT=4.217-01 FLUX DEPRES=1.1406 FEXP= 1.8197 FCONST= 3.6395 SNF= .39349

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ASSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	1.2307+00	7.5107-01	.00030	1.0261-01	6.6814-04	1.3636+00	9.9941-02	9.0415-01		
2	1.2204+00	5.0559-01	.00042	2.1594-03	1.3919-03	1.5573-01	7.6752-04	1.2919-01		
3	1.2517+00	7.6941+00	.33789	7.2272-02	7.1492-02	1.1778+00	7.8006-04	1.1535+00	1.3822-02	2.430
4	1.3391+00	1.8354+00	.00137	2.1394-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
5	1.3632+00	3.3792+00	.00150	1.0010-01	6.6475-04	1.3567+00	9.9434-02	8.9956-01		
6	1.3860+00	2.3615+00	.00223	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
7	1.4582+00	9.0530+01	.00055	4.8390-03	8.4602-06	3.8276-01	4.8305-03	3.6108-01		
		TOTAL	.34435							

OUTPUT FOR GROUP 3

CELL VALUES

AGE= 9.25 SIGMA REMOVAL=1 000-01 SIGMA TRANSPORT=3.769-01 FLUX DEPRES=1.8103 FEXP= 1.1420 FCONST= 2.3837 SNF= 1.00398

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ASSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	5.6450-02	7.5107-01	.00011	2.8205-01	5.5265-03	1.5097+00	1.7652-01	4.4584-01		
2	4.9137-02	5.0559-01	.00004	9.6012-03	3.4942-03	8.7008-02	6.1070-03	8.4838-02		
3	5.1046-02	7.6941+00	.09485	4.9790-01	4.6445-01	4.2386-01	3.4473-03	4.2266-01	1.9002-01	2.430
4	6.8850-02	1.8354+00	.00022	9.6012-03	3.4942-03	8.7008-02	6.1070-03	8.4838-02		
5	7.4074-02	3.3792+00	.00071	8.7757-01	5.4085-03	1.5020+00	5.7207-01	4.4584-01		
6	8.4718-02	2.3615+00	.00034	9.6012-03	3.4942-03	8.7008-02	6.1070-03	8.4838-02		
7	9.7674-02	9.0530+01	.00030	5.9271-02	7.0514-05	3.8687-01	5.9201-02	3.5518-01		
		TOTAL	.09658							

OUTPUT FOR GROUP 4

CELL VALUES

OIF LENG= 50.604 SIGMA ABSQRP=1.735-32 SIGMA TRANSPORT=4.024-01 FLUX OPRES=1.6493 FEXP: 1.3194 FCONST= 2.6388 SNF= .02001

REGION	FLUX	VOLUME CM ³ /CM	ABSORPTION FRACTION	R VALUE	SIGMA ABSORP	SIGMA SCATTER	SIGMA TRANSPORT	NEUT TEMP DEG C	SIGMA FISSION	HEAT TRANSFER NU UTILIZATION
1	3.0694-01	7.51C7-n1	.00176	.2706	1.5527-02	2.5820+00	1.5066+00	184.79		
2	2.7894-01	5.0559-01	.00001	.2945	8.8692-03	8.5200-02	9.2623 02	287.92		
3	3.0239-01	7.6941+00	.43094	.2820	3.7923-01	3.9159-01	7.0971-01	287.84	2.5121-01	2.430 1.000
4	3.8198-01	1.8154+00	.00304	.2413	8.8707-03	8.5200-02	9.2625-02	287.72		
5	4.3057-01	3.3792+00	.00890	.2199	1.2525-02	2.3097+00	1.2591+00	423.49		
6	4.6149-01	2.3615+00	.00338	.2094	7.2805-03	8.5200-02	9.1034-02	559.51		
7	5.2411-01	9.0530+01	.00340	.1950	1.4689-04	3.8687-01	3.6533-01	559.84		
TOTAL			.45253							

CELL DATA

CONVERSION RATIO= .615 K INFINITY=1.155 MIGRATION AREA: 228.06 MATERIAL BUCKLING: 6.797-04

FOUR GROUP EPSILON=1.08Q OLD METHOD U238 EPSILON=1.024

ISOTOPE CONCENTRATIONS (nUCLEI/BARN eM)

U235	U238
7.3680E-04	4.7123E-02

ZERO DIMENSIONAL ALTHAEA INPUT PARAMETERS

FUEL +/OR
TARGET oEUS

PERFIS	MELEAGER SDPV	srJF	seA	ALLOY	DELTA	TOT	MELEAGER TEMP
.01519	1.34909	.02001	1.00039	18.900	1.192	4.7839-02	533.01

FUEL DEPRESSION	FCONST	FEXP	SP POWER MW/TONNE	FUEL TEMP	TONNES OF FUEL FOR ALLOY IN CORE
1.6493	2.03879	1.31945	11.23D	349.H4	391.80756

ONE DIMENSIONAL ALTHAEA PARAMETERS

SSI	SS2	SS3	SS4	XISS1	XISS2	XISS3	S24	SPEC	FUEL+TARGET VOL FRACT-VR	VERT BUCK BUCK	BARE HEIGHT HORT
19257	.42116	.37693	.38501	.042506	.098503	.083431	.16219	.20112	.07187	2.4796-05	5.6027+02

ALTHAEA ABSOLUTE FLUX GUESS - CONVERSION FACTOR=6.9173+12

CELL INFORMATION (PER FOOT OF CELL)

CLAD suRFACE OF FUEL+/OR TAR REGIONS	MODERATOR VOLUME	OUTSIDE SURFACE CYLINDER	CELL VOLUME	VOL MOD PER VOL FUEL+/OR TARGET	FUEL+/OR TARGET WEIGHT	MODERATOR WEIGHT	FUEL+/OR TARGET VOLUME	CLADDING VOLUME
.43903	.10189	1.20335	.11523	11.46876	10.48250	10.23708	.00888	.00446
sq ft/ft	cu ft/ft	sq ft/ft	cu ft/ft		lbs/ft	lbs/ft	cu ft/ft	cu ft/ft

WASCON CASE NUMBER 1402

SEU .735WT.0/0 U-235 METAL FUEL

INPUT CONTROL DATA

N	K1	K2	K3	K4	K5	DSMEAR	ECCOR	BUCK	STRCOR	MEVFIS	DEL
Z	e	1		a	g	g	9.3229 61	2.1796 05	1.0600+00	2.0200+02	0.0000
0	0	C	2	0	2	0	0.00	0.00	0	0.0000	0.0000

INPUT FUEL COMPOSITIONS

ISOTOPE

DILUENT

REGION	TH232	U233	U234	U235	U236	U238	PU239	PU240	PU241	PU242	DILUENT NUMBER	DILUENT PERCENT
1	0.00	0.00	0.00	2.00	0.00	0.00	0.00	0.00	0.00	0.00	0	0.00

INPUT REGION INFORMATION

REGION NUMBER	PORE CM.	PORE INCHES	MATERIAL	DENSITY GM/CC	TEMP DEG C	TEMP DEG F	VOLUME FRACTION	THICKNESS REG-INCH	NO. OF BARN CM
1	1.48836	1.19237	U235	18.98	114.840	238.712	0.00472	0.05650	6.02546-02
2	1.63246	1.24900	ALUMN	2.702	114.840	238.712	0.00472	0.05650	6.02546-02
3	1.73997	1.38500	U238 MC	18.980	114.840	238.712	0.01187	0.05650	6.02546-02
4	1.85293	1.49350	U238	18.98	114.840	238.712	0.01187	0.05650	6.02546-02
5	2.12344	1.68500	H2O	0.991	64.840	148.712	0.03157	0.10050	3.27948-02
6	2.29162	1.80150	ALUMN	2.702	114.840	238.712	0.00472	0.05650	6.02546-02
7	5.83757	2.29826	GRAPHIT	1.638	559.840	1039.712	0.84562	1.39526	8.21375-02

MODERATOR TO FUEL RATIOS

H/FUEL .7366
D/FUEL .0000
GRAPH/FOEL 20.2906

IF ARRAY IS TRIANGULAR, PITCH = 4.3773 INCHES
IF ARRAY IS SQUARE, PITCH = 4.0736 INCHES

OUTPUT FOR GROUP 1

CELL VALUES

AGE= 131.53 SIGMA SCATTER=1.395-02 SIGMA TRANSPORT=1.926-01 FLUX DEPRES= .8309 FEYP= -7.2651 FCONST= -14.5302 SNF= .05078

REGION	FLUX	VOLUME	ABSORPTION	SIGMA	SIGMA	SIGMA	XI SIGMA	SIGMA	SIGMA	FISSION	NU
		CM3XCM	PERCENT	REMOVAL	MASSCOP	SCATTER	SCATTER	TRANSPORT			
1	1.7249+00	7.5107-01	.00015	8.7381-02	2.2942-04	4.0082-01	8.7151-02	2.8699-01			
2	1.7405+00	5.5559-01	.00016	3.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01			
3	1.6964+00	7.6941+00	.1C626	2.4172-02	1.6661-02	3.7136-01	7.5115-03	1.5000-01	1.2199-02	2.796	
4	1.5398+00	1.4154+00	.00014	3.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01			
5	1.5536+00	3.3792+00	.00059	8.6938-02	2.2825-04	3.9879-01	8.6710-02	2.8553-01			
6	1.5341+00	2.3613+00	.00051	3.4189-03	2.3499-04	2.0095-01	3.1839-03	1.3865-01			
7	1.3849+00	9.0530+01	.00030	9.6922-03	0.0000	2.1816-01	9.6922-03	1.9524-01			
		TOTAL	.11730								

OUTPUT FOR GROUP 2

CELL VALUES

AGE= 66.43 SIGMA REMOVAL=1.265-02 SIGMA TRANSPORT=1.206-01 FLUX DEPRES=1.1486 FERP= 1.8072 FCONST= 3.6144 SNF= .90999

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	1.1957+00	7.5107-01	.00029	1.0061-01	6.6814-04	1.3636+00	9.9941-02	9.0415-01		
2	1.1847+00	5.0559-01	.00041	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
3	1.2225+00	7.6941+00	.34880	7.6670-02	7.5892-02	1.1748+00	7.7808-04	1.1556+00	1.7002-02	2.430
4	1.3070+00	1.8354+00	.00163	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
5	1.3318+00	3.3792+00	.00146	1.0010-01	6.6475-04	1.3567+00	9.9434-02	8.9956-01		
6	1.3550+00	2.3615+00	.00218	2.1594-03	1.3919-03	1.3373-01	7.6752-04	1.2919-01		
1	1.4285+00	9.0530+01	.00053	4.8390-03	8.4602-06	3.8276-01	4.8305-03	3.6108-01		
		TOTAL	.35531							

OUTPUT FOR GROUP 3

CELL VALUES

AGE= 9.17 SIGMA REMOVAL=1.029-01 SIGMA TRANSPORT=1.105-01 FLUX DEPRES 2.0382 FERP= 1.1376 FCONST= 2.2752 SNF= .00263

REGION	FLUX	VOLUME CM3/CM	ABSORPTION FRACTION	SIGMA REMOVAL	SIGMA ABSORP	SIGMA SCATTER	XI SIGMA SCATTER	SIGMA TRANSPORT	SIGMA FISSION	NU
1	5.0245-02	7.5107-01	.00010	8.8209-01	5.5264-03	1.5097+00	8.7656-01	9.9684-01		
2	4.2063-02	5.0559-01	.00004	9.6018-03	3.4941-03	8.7008-02	6.1077-03	8.4838-02		
3	4.3416-02	7.6941+00	.10100	6.2593-01	0.2247-01	4.2542-01	3.4604-03	4.2421-01	2.5089-01	2.430
4	6.3774-02	1.8354+00	.00020	9.6018-03	3.4941-03	8.7008-02	6.1077-03	8.4838-02		
5	7.3505-02	3.3792+00	.00067	8.7762-01	5.4983-03	1.5020+00	8.7812-01	9.9178-01		
6	8.0584-02	2.3615+00	.00032	9.6018-03	3.4941-03	8.7008-02	6.1077-03	8.4838-02		
7	9.4151-02	9.0530+01	.00029	5.8278-02	7.0512-05	3.8687-01	5.8208-02	3.6518-01		
		TOTAL	.10323							

OUTPUT FOR GROUP 4

CELL VALUES

DIF LENG= 44.951 SIGMA ABSORP=1.947 D2 SIGMA TRANSPORT=8.038-01 FLUX OPRES=1.8394 FEXP= 1.2761 FCONST= 2.5522 SAMP= .01955

		VOLUME	ABSORPTION	R	SIGMA	SIGMA	SIGMA	NEUT	SIGMA	HEAT TRANSFER		
RESIST FLUX		CM3/CM	FRACTION	VALUE	ABSORP	SCATTER	TRANSPORT	TEMP DEG C	FISSION	NU	UTILIZATION	
1	2.3714-01	7.5107-01	.00135	.3311	1.5527-02	2.5820+00	1.5066+00	184.79				
2	2.0849-01	5.8559-01	.00346	.3679	8.8691-03	8.5200-02	9.2623-02	287.92				
3	2.3149-01	7.6941+00	.41505	.3465	4.7766-01	3.9352-01	8.7001-01	287.84	3.3495-01	2.430	1.000	
4	3.1351+01	1.2354+10	.00295	.2803	8.8757-03	8.5200-02	9.2625-02	287.72				
5	3.6056-01	3.3792+00	.00746	.2517	1.2525-02	2.3097+00	1.2591+00	423.49				
6	3.9036-01	2.3615+00	.00328	.2378	7.2895-03	8.5200-02	9.1034-02	559.51				
7	4.5073-01	9.0530+01	.00293	.2187	1.4689-04	3.8687-01	3.0533-01	559.84				
		TOTAL	.43302									

CELL DATA

CONVERSION RATIO= .522 K U-JEFFICIENCY:1.215 MIGRATION AREA= 222.70 MATERIAL BUCKLING= 9.668-04

FOUR GROUP EPSILONi,J=1.071 OLD METHOD U238 EPSILON=1.024

ISOTOPE CONCENTRATIONs (nUCLEI/BARN CM)

U235	U238
9.63806-04	4.68731-02

ZERO DIMENSIONAL ALTHAEA INPUT PARAMETERS

FUEL +/OR TARGET DENS									
MELEAGER				OF METAL OR		MELEAGER			
PERFIS	SDPV	SNF	SCA	ALLOY	DELTA	TOT	TEMP		
.02025	1.34717	.01954	1.00036	18.900	1.192	4.7842	533.07		
FLUX DEPRESSIO(FCONST FEXP SP POWER FUEL TONNES OF FUEL OR ALLOY									
DEPRESSIO(	FCONST	FEXP	W/TONNE	TEMP	IN CORE				
1.8394	2.55218	1.27699	11.230	349.84	391.30756				

ONE DIMENSIONAL ALTHAEA PARAMETERS

										FUEL+TARGET		VERT BUCK BARE HEIGHT			
										VOL	FRACT	VR	BUCK	HORT	
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----
54	56	51	54	XIS1	XIS2	XIS3	524	SPEC							
.19256	.42359	.37650	.38431	.042506	.096404	.083119	.16189	.22687		.07187			2.4796	-.05	5.6027+02

GANDS FILED ON A-3 17/ 07/01 ADJUSTED RESONANCE INTEGRALS 10/10/01
 INCREASED MEV/FISSION (7/26/66)
 THIS LIBRARY INCLUDES AMERICIUMS AND CURIUMS

CALCULATIONS BASED ON NUCLEAR DATA FOR NEUTRON TEMPERATURES OF 0. TO 600. DEGREES.
 ZERO ON THE TEMPERATURE SCALE IS 273.16 DEGREES KELVIN. THE EPITHERMAL FLUX SHAPE FACTOR B IS 1.176246.
 THE FIRST 4 ISOTOPES ARE FISSILE AND THE NEXT 4 ARE FERTILE.

LIBRARY NAME/VERSION IS WPLT887J91467

ISOTOPE DESCENDANT LIST

ISOTOPE	CAP	N2N	ISOTOPE	CAP	N2N	ISOTOPE	CAP	N2N	ISOTOPE	CAP	N2N	ISOTOPE	CAP	N2N
1 U233W	U234		2 U235W	U236		3 PU239W	PU240		4 PU241Z	pU242		5 TH232	PA233	
3 U238	PU239W	PU240	7 U234	U235		8 PU240	PU241Z		9 PU233	U234		10 U236	NP237	
11 PU242	AM243		12 NP237	PU238		13 AM241	CM242		14 AM243	CM244		15 AM242M	AM243	
17 CV242	CM243		17 CM243	CM244		18 CM244			19 PU238	PU239W		20 POISON		
21 FPA			22 FPR			23 FPC			24 XE135			25 SM149		
25 SM151														

MODIFICATIONS TO THE BASIC LIBRARY ARE THE FOLLOWING

1	3	3	7.5400+02
1	4	4	1.0300+03
2	2	2	-6.810C+02
2	13	11	B.SOCO+01
2	4	4	-1.3360+03
17	6	2	4.3000+04
17	8	2	4.0000+35
18	6	6	2.0000+02
18	4	4	2.1000+02
16	3	3	2.3800+02
18	2	2	2.3000+02
18	1	1	1.9000+02
20	10	1	6.3000+01
20	12	1	2.1350+00
20	23	1	2.6000+00

KPR ALT-TUBE AS IS

CONTROL CONSTANTS

N11	N12	N13	N14	N15	N16	N17	N18	N19	POWER	RMULT	CLOSE	RAO
19	4	5	2	3	-0	2	3	11	4.4000+03	-0.0000	1.0000-01	-0.0000
N21	N22	N23	N24	N25	N26	N27	N28	N29	BMULT	HLO	EAE	TMAX
1	1	1	4	3	-0	4	99	-0	-1.0000+00	1.0000+05	-0.0000	8.6400+04
N31	N32	N33	N34	N35	N36	N37	N38	N39	BMULT1	BMULT2	BMULT3	BMULT4
-0	-0	-0	-0	-0	-0	-0	-0	-0	0.0000	-0.0000	-0.0000	0.0000
N41	N42	N43	N44	N45	N46	N47	N48	N49	TSLIM	ERL	ERU	HI
15	1	-0	20	-0	-0	4	-0	3	2.0000+06	2.0000-02	5.0000-02	8.6400+04
N52	N53	N55	N56	N59	CMULI	CMATCH	PERFIS	TOT				
-0	-0	-0	-0	-0	0.0000	0.0000	7.4430 03	4.7830 02				
N61	N62	N63	N64	N65	N66	N67	N68	N69	RAYK1	RAYK2	RAYK3	GSILD
1	3	2	-0	-0	-0	-0	-0	-0	7.8700-01	2.0000-01	2.5570+00	6.7500-02
N71	N72	N73	N74	N75	N76	N77	N78	N79	PERL05	DDAYS	DEXP	PERLS
-0	-0	-0	-0	-0	-0	-0	-0	-0	0.0000	-0.0000	-0.0000	-0.0000

INPUT ISOTOPE CONCENTRATIONS

ISTEP	IDFF1	NFS	IC1	IC2	IC3	IC4	Ies	IC6	IC7	Ie8	IC9	IC10	Ie11	Ie12	PERIOD	M/F
1	1001K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000
IP1	IP2	IP3	IP4	IP5	IP6	IP7	IP8	IP9	IP10	IP11	IP12	IP13	IP14	IP15	IP16	IP17
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0

FCONST=	0.0000	FEXP=	0.0000	TEMP=	0.0000	SPEC=	2.4120-03	TNL=	1.0000+00	rMOD=	5.5980+02	IE=-0
FOR t=	5.6799+07	SCA=	0.0000	PWT=	5.0000-11	DENS=	0.0000	E=	0.0000	KK=	1.0000+11	MF=-0
SIF=	2.7940-04	NFS3=	1.7110-06	NFS2=	-0.0000	NFS1=	-0.0000	GAMI=	-0.0000	GAM2=	-0.0000	NBP:-0
S12=	3.2950-02	S23=	6.0860-02	S34=	6.1520-02	S13=	-0.0000	S14=	-0.0000	S24=	0.0000	KEY: -1
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=-0
S51=	1.9520-01	S52=	3.6110-01	S53=	3.6520-01	S54=	3.6520-01	SAWD=	2.0000-01	VR =	1.0000+00	KOUT=-1
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	0.0000	SSL4=	0.0000	SNFL=	-0.0000	PWIX=	3.0000+02	KP = -0
CONV=	1.0000-03	BUCK=	2.4800-05	pF =	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	WIDTH=	2.2208-01	KP =20

BURUP OF REGION 1 IDENTIFIED AS 1001K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

3.56036-04 U238 4.74782-02

ISTEP	IDENT	HFS	IC1	IC2	IC3	Ies	IC6	Ie7	Ica	IC9	IC10	IC11	I12	PERIOD	M/F	
1	1002K	-C	-C	-C	-C	-C	-C	-0	-0	-0	-0	-0	-0	1.0	11.470-----	
ID1	ID2	ID3	ID4	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCORJST=	2.7810+00	FEXP=	1.3910+00	TEMP=	3.4980+02	SPEC=	1.4580-01	TIJL=	1.00nO+00	TMOD=	-2.8765+02	IE=	-0			
HORT=	3.6799+07	SEA=	9.1250-01	PWI=	3.0000-11	DEnS=	1.8900+01	E=	1.1920+00	XK=	1.6021+11	JMP=	-0			
SJF=	2.0970-02	NFS3=	-0.0000	NFS2=	3.6230-01	NFS1=	4.7290-02	GAM1=	0.0000	GAM2=	0.0000	NBP=	-0			
S12=	4.2510-02	S23=	9.8750-02	S34=	8.4250-02	S13=	-0.0000	S14=	-0.0000	S24=	1.6290-01	KEY=	-0			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
SS1=	1.9260-01	SS2=	4.2240-01	SS3=	3.7790-01	SS4=	3.8640-01	SAWD=	2.0000-01	VR=	7.1870-02	KOUT=	-1			
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SMFL=	-0.0000	PWMX=	5.0000+02	KF=	-0			
CONV=	1.0000-03	BUCK=	2.4800-05	pF=	5.6000-01	CLIM=	1.0000-02	ACNTRL=	1.0000+00	WIDTH=	2.2936-01	KP=	20			

BURN-UP OF REGION 2 IDENTIFIED AS 1002K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

ISTEP	IDENT	HFS	IC1	IC2	IC3	IC4	IC5	IC6	IC7	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F
1	1003K	-C	-C	-C	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000
ID1	ID2	ID3	ID4	IF1	IF2	IF3	IF4	Irs	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCORJST=	0.0000	FEXP=	0.5000	TEMP=	0.0000	SPEC=	2.4120-03	TIJL=	1.0000+00	TMOD=	5.5980+02	IE=	-0			
HORT=	3.6799+07	SEA=	0.0000	PWI=	3.0000-11	DEnS=	0.0000	E=	0.0000	XK=	1.6021+11	JMP=	-0			
SJF=	2.7940-04	NFS3=	1.7110-06	NFS2=	-0.0000	NFS1=	-0.0000	GAM1=	-0.0000	GAM2=	-0.0000	NBP=	-0			
S12=	1.2490-02	S23=	8.1780-02	S34=	6.1520-02	S13=	-0.0000	S14=	-0.0000	S24=	0.0000	KEY=	-1			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
SS1=	1.4520-01	SS2=	3.8110-01	SS3=	3.8520-01	SS4=	3.6520-01	SAWD=	2.0000-01	VR=	-1.0000+00	KOUT=	-1			
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SMFL=	-0.0000	PWMX=	3.0000+02	KF=	-0			
CONV=	1.0000-03	ROCK=	2.4800-05	pF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	WIDTH=	2.2208-01	KP=	40			

BURN-UP OF REGION 3 IDENTIFIED AS 1003K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

3.66036-04 U232 4.74742-02

STEP	IDENT	NFS	Ie1	IC2	IC3	IC4	IC5	IC6	IC7	Ie8	IC9	IC10	Ie11	IC12	PERIOD	M/F
1	1004f	-C			-0	-0	0	0	-0	0	0	-0	-e	0	1.0	11.470
ID1	ID2	ID3	ID4	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST= 2.7810+00 FEXP= 1.3910+00 TEMF= 3.4980+02 SPEC= 1.45AO-01 TNL= 1.0000+00 TMOD= -2.8765+02 IE= -0 HORT= 3.6799+07 SCA= 9.1250-01 PWI= 3.6086-11 DELFS= 1.8960+01 E= 1.1920+00 XK= 1.6021+11 dMP= 0 SIF= 2.0870-02 IFSS= -0.0000 IF42= 3.0230-01 r-IFS= 4.7290-02 GAM1= 0.0000 GAM2= 0.0000 NBP= -0 S12= 4.2510-02 S23= 9.8750-02 S34= 8.4250-02 S13= -0.0000 S14= -0.0000 S24= 1.6290-01 KEY=-0 SL12= -0.0000 SL23= -0.0000 SL34= -0.0000 SL13= -0.0000 SL14= -0.0000 SL24= -0.0000 KINO=-0 SS1= 1.9260-01 SS2= 4.2240-01 SS3= 3.7790-01 SS4= 3.8640-01 SAWD= 2.0000-01 VR= 7.1870-02 KOUT=-1 sSL1= 0.0000 SSb2= 0.0000 SSL3= 0.0000 SSL4= 0.0000 SNFL= 0.0000 PWMX= 3.0000+02 KF=-0 CONV= 1.0000-03 BUCK= 2.4800-05 pF= 5.0000-01 CLIM= 1-0COO-02 ACNTRL= 1.0000+00 WIDTH= 2.2936-01 KP= 20																

BURN-UP OF REGION 4 IDENTIFIED AS 10Q4K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

STEP	IDENT	NFS	IC1	IC2	IC3	IC4	IC5	IC6	IC7	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F
1	1005K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000
ID1	ID2	ID3	ID4	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST= 0.0000 FEXP= 0.0000 TEMF= 0.0000 SPEC= 7.4120-01 TNL= 1.0000+00 TMOD= 8.5980+12 IE= -0 HORT= 3.6799+07 seA= 0.0000 PWI= 3.0000-11 DENS= 0.0000 E= 0.0000 XK= 1.6021+11 JMP= -0 SIF= 2.7940-04 IFSS= 1.1111-02 IF42= 0.0000 IF51= 0.0000 GAM1= 0.0000 GAM2= 0.0000 NBP= -0 S12= 3.2050+02 S23= 8.2490-02 S34= 6.1520-02 S13= -0.0000 S14= -0.0000 S24= 0.0000 KEY=-1 SL12= -0.0000 SL23= -0.0000 SL34= -a.QuoO SL13= -0.0000 SL14= -0.0000 SL24= -0.0000 KINO= -0 SS1= 1.9520-11 SS2= 3.6110-01 SS3= 3.6520-01 SS4= 3.6520-01 SAWD= 2.0000-01 VR= 1.0000+00 KOUT=-1 sSL1= -0.0000 SSL2= -0.0000 SSL3= -0.0000 SSL4= -0.0000 SuFL= -0.0000 PWMX= 3.0000+02 KF=-0 CONV= 1.0000-03 LUCK= 2.4800-05 IF= 0.0000 CLIM= 1-0COO-02 ACNTRL= 0.0000 WIDTH= 2.2208-01 KP= 20																

BURN-UP OF REGION 5 IDENTIFIED AS 10Q5K COMPLETED.

DIFFUSION OUTPUT AT 0.000 5EcotJDS. POWER BASED ON OLD FLUX IS 2,4343+03

REACTIVITY WITH CONTROL RODS WITHDRAWN IS .98277

REGION	RADIUS	POWER	FLUX	PERCENT CHANGE	RE	PERCENT CHANGE	RS	PERCENT CHANGE	RF	PERCENT CHANGE	SNFD	PERCENT CONTROL
1	4.44	.00	3.148-11	4.72	.0581	96.68	.0633	96.19	.0000	-.00	.0000	-.00
2	9.03	181.34	3.111-11	19.06	.0578	-101.95	.0652	-123.59	.0000	0.13	.0000	-.00
3	17.91	.00	3.155-11	4.91	.0580	96.68	.0632	96.18	.0000	-.00	.0000	-.00
4	22.50	181.34	3.737-11	19.08	.0578	-101.95	.0652	-123.59	.0000	0.13	.0000	-.00
5	26.94	.00	3.148-11	4.72	.0581	96.68	.0633	96.19	.0000	-.00	.0000	-.00

9.895	*	ES	F	T	*
9.917	*	ES	F	T	*
10.139	*	ES	F	T	*
10.361	*	ES	F	T	*
10.583	*	ES	F	T	*
10.805	*	ES	F	T	*
11.027	*	ES	F	T	*
11.250	*	ES	F	T	*
11.472	*	ES	F	T	*
11.694	*	ES	F	T	*
11.916	*	ES	F	T	*
12.138	*	ES	F	T	*
12.360	*	ES	F	T	*
12.582	*	ES	F	T	*
12.804	*	ES	F	T	*
13.026	*	ES	F	T	*
13.248	*	ES	F	T	*
13.470	*	ES	F	T	*
13.692	*	ES	F	T	*
13.915	*	ES	F	T	*
14.137	*	ES	F	T	*
14.359	*	ES	F	T	*
14.581	*	ES	F	T	*
14.803	*	ES	F	T	*
15.025	*	ES	F	T	*
15.247	*	ES	F	T	*
15.469	*	ES	F	T	*
15.691	*	ES	F	T	*
15.913	*	ES	F	T	*
16.135	*	ES	F	T	*
16.357	*	ES	F	T	*
16.579	*	ES	F	T	*
16.802	*	ES	F	T	*
17.024	*	ES	F	T	*
17.246	*	ES	F	T	*
17.468	*	ES	F	T	*
17.690	*	ES	F	T	*
17.912	*	ES	F	T	*
18.134	*	ES	F	T	*
18.356	*	ES	F	T	*
18.578	*	ES	F	T	*
18.800	*	ES	F	T	*
19.022	*	ES	F	T	*
19.244	*	ES	F	T	*
19.466	*	ES	F	T	*
19.688	*	ES	F	T	*
19.910	*	ES	F	T	*
20.132	*	ES	F	T	*
20.354	*	ES	F	T	*
20.576	*	ES	F	T	*
20.798	*	ES	F	T	*
21.020	*	ES	F	T	*
21.242	*	ES	F	T	*
21.464	*	ES	F	T	*
21.686	*	ES	F	T	*
21.908	*	ES	F	T	*
22.130	*	ES	F	T	*
22.352	*	ES	F	T	*
22.574	*	ES	F	T	*
22.796	*	ES	F	T	*
23.018	*	ES	F	T	*
23.240	*	ES	F	T	*
23.462	*	ES	F	T	*
23.684	*	ES	F	T	*
23.906	*	ES	F	T	*
24.128	*	ES	F	T	*
24.350	*	ES	F	T	*
24.572	*	ES	F	T	*
24.794	*	ES	F	T	*
25.016	*	ES	F	T	*
25.238	*	ES	F	T	*
25.460	*	ES	F	T	*
25.682	*	ES	F	T	*
25.904	*	ES	F	T	*
26.126	*	ES	F	T	*
26.348	*	ES	F	T	*
26.570	*	ES	F	T	*
26.792	*	ES	F	T	*
27.014	*	ES	F	T	*
27.236	*	ES	F	T	*
27.458	*	ES	F	T	*
27.680	*	ES	F	T	*
27.902	*	ES	F	T	*
28.124	*	ES	F	T	*
28.346	*	ES	F	T	*
28.568	*	ES	F	T	*
28.790	*	ES	F	T	*
29.012	*	ES	F	T	*
29.234	*	ES	F	T	*
29.456	*	ES	F	T	*
29.678	*	ES	F	T	*
29.900	*	ES	F	T	*
30.122	*	ES	F	T	*
30.344	*	ES	F	T	*
30.566	*	ES	F	T	*
30.788	*	ES	F	T	*
31.010	*	ES	F	T	*
31.232	*	ES	F	T	*
31.454	*	ES	F	T	*
31.676	*	ES	F	T	*
31.898	*	ES	F	T	*
32.120	*	ES	F	T	*
32.342	*	ES	F	T	*
32.564	*	ES	F	T	*
32.786	*	ES	F	T	*
33.008	*	ES	F	T	*
33.230	*	ES	F	T	*
33.452	*	ES	F	T	*
33.674	*	ES	F	T	*
33.896	*	ES	F	T	*
34.118	*	ES	F	T	*
34.340	*	ES	F	T	*
34.562	*	ES	F	T	*
34.784	*	ES	F	T	*
35.006	*	ES	F	T	*
35.228	*	ES	F	T	*
35.450	*	ES	F	T	*
35.672	*	ES	F	T	*
35.894	*	ES	F	T	*
36.116	*	ES	F	T	*
36.338	*	ES	F	T	*
36.560	*	ES	F	T	*
36.782	*	ES	F	T	*
37.004	*	ES	F	T	*
37.226	*	ES	F	T	*
37.448	*	ES	F	T	*
37.670	*	ES	F	T	*
37.892	*	ES	F	T	*
38.114	*	ES	F	T	*
38.336	*	ES	F	T	*
38.558	*	ES	F	T	*
38.780	*	ES	F	T	*
39.002	*	ES	F	T	*
39.224	*	ES	F	T	*
39.446	*	ES	F	T	*
39.668	*	ES	F	T	*
39.890	*	ES	F	T	*
40.112	*	ES	F	T	*
40.334	*	ES	F	T	*
40.556	*	ES	F	T	*
40.778	*	ES	F	T	*
41.000	*	ES	F	T	*
41.222	*	ES	F	T	*
41.444	*	ES	F	T	*
41.666	*	ES	F	T	*
41.888	*	ES	F	T	*
42.110	*	ES	F	T	*
42.332	*	ES	F	T	*
42.554	*	ES	F	T	*
42.776	*	ES	F	T	*
43.000	*	ES	F	T	*
43.222	*	ES	F	T	*
43.444	*	ES	F	T	*
43.666	*	ES	F	T	*
43.888	*	ES	F	T	*
44.110	*	ES	F	T	*
44.332	*	ES	F	T	*
44.554	*	ES	F	T	*
44.776	*	ES	F	T	*
45.000	*	ES	F	T	*
45.222	*	ES	F	T	*
45.444	*	ES	F	T	*
45.666	*	ES	F	T	*
45.888	*	ES	F	T	*
46.110	*	ES	F	T	*
46.332	*	ES	F	T	*
46.554	*	ES	F	T	*
46.776	*	ES	F	T	*
47.000	*	ES	F	T	*
47.222	*	ES	F	T	*
47.444	*	ES	F	T	*
47.666	*	ES	F	T	*
47.888	*	ES	F	T	*
48.110	*	ES	F	T	*
48.332	*	ES	F	T	*
48.554	*	ES	F	T	*
48.776	*	ES	F	T	*
49.000	*	ES	F	T	*
49.222	*	ES	F	T	*
49.444	*	ES	F	T	*
49.666	*	ES	F	T	*
49.888	*	ES	F	T	*
50.110	*	ES	F	T	*
50.332	*	ES	F	T	*
50.554	*	ES	F	T	*
50.776	*	ES	F	T	*
51.000	*	ES	F	T	*
51.222	*	ES	F	T	*
51.444	*	ES	F	T	*
51.666	*	ES	F	T	*
51.888	*	ES	F	T	*
52.110	*	ES	F	T	*
52.332	*	ES	F	T	*
52.554	*	ES	F	T	*
52.776	*	ES	F	T	*
53.000	*	ES	F	T	*
53.222	*	ES	F	T	*
53.444	*	ES	F	T	*
53.666	*	ES	F	T	*
53.888	*	ES	F	T	*
54.110	*	ES	F	T	*
54.332	*	ES	F	T	*
54.554	*	ES	F	T	*
54.776	*	ES	F	T	*
55.000	*	ES	F	T	*
55.222	*	ES	F	T	*
55.444	*	ES	F	T	*
55.666	*	ES	F	T	*
55.888	*	ES	F	T	*
56.110	*	ES	F	T	*
56.332	*	ES	F	T	*
56.554	*	ES	F	T	*
56.776	*	ES	F	T	*
57.000	*	ES	F	T	*
57.222	*	ES	F	T	*
57.444	*	ES	F	T	*
57.666	*	ES	F	T	*
57.888	*	ES	F	T	*
58.110	*	ES	F	T	*
58.332	*	ES	F	T	*
58.554	*	ES	F	T	*
58.776	*	ES	F	T	*
59.000	*	ES	F	T	*
59.222	*	ES	F	T	*
59.444	*	ES	F	T	*
59.666	*	ES	F	T	*
59.888	*	ES	F	T	*
60.110	*	ES	F	T	*
60.332	*	ES	F	T	*
60.554	*	ES	F	T	*
60.776	*	ES	F	T	*
61.000	*	ES	F	T	*
61.222	*	ES	F	T	*
61.444	*	ES	F	T	*
61.666	*	ES	F	T	*
61.888	*	ES	F	T	*
62.110	*	ES	F	T	*
62.332	*	ES	F	T	*
62.554	*	ES	F	T	*
62.776	*	ES	F	T	*
63.000	*	ES	F	T	*
63.222	*	ES	F	T	*
63.444	*	ES	F	T	*
63.666	*	ES	F	T	*
63.888	*	ES	F	T	*
64.110	*	ES	F	T	*
64.332	*	ES	F	T	*
64.554	*	ES	F	T	*
64.776	*	ES	F	T	*
65.000	*	ES	F	T	*
65.222	*	ES	F	T	*
65.444	*	ES	F	T	*
65.666	*	ES	F	T	*
65.888	*	ES	F	T	*
66.110	*	ES	F	T	*
66.332	*	ES	F	T	*
66.554	*	ES	F	T	*
66.776	*	ES	F	T	*
67.000	*	ES	F	T	*
67.222	*	ES	F	T	*
67.444	*	ES	F	T	*
67.666	*	ES	F	T	*
67.888	*	ES	F	T	*
68.110	*	ES	F	T	*
68.332	*	ES	F	T	*
68.554	*	ES	F	T	*
68.776	*	ES	F	T	*
69.000	*	ES	F	T	*
69.222	*	ES	F	T	*
69.444	*	ES	F	T	*
69.666	*	ES	F	T	*
69.888	*	ES	F	T	*
70.110	*	ES	F	T	*
70.332	*	ES	F	T	*
70.554	*	ES	F	T	*
70.776	*	ES	F	T	*
71.000	*	ES	F	T	*
71.222	*	ES	F	T	*
71.444	*	ES	F	T	*
71.666	*	ES	F	T	*
71.888	*	ES	F	T	*
72.110	*	ES	F	T	*
72.332	*	ES	F	T	*
72.554	*	ES	F	T	*
72.776	*	ES	F	T	*
73.000	*	ES	F	T	*
73.222	*	ES	F	T	*
73.444	*	ES	F	T	*
73.666	*	ES	F	T	*
73.888	*	ES	F	T	*
74.110	*	ES	F	T	*
74.332	*	ES	F	T	*
74.554	*	ES	F	T	*
74.776	*	ES	F	T	*
75.000	*	ES	F	T	*
75.222	*	ES	F	T	*
75.444	*	ES	F	T	*
75.666	*	ES	F	T	*
75.888	*	ES	F	T	*
76.110	*	ES	F	T	*
76.332	*	ES	F	T	*
76.554	*	ES	F	T	*
76.776	*	ES	F	T	*
77.000	*	ES	F	T	*
77.222	*	ES	F	T	*
77.444	*	ES	F	T	*
77.666	*	ES	F	T	*
77.888	*	ES	F	T	*
78.110	*	ES	F	T	*

KPR ALT-TUBE AS IS

CONTROL CONSTANTS

		N13	NTRL			N16			IG	POWER	RMULT	CLOSE	RAD
19	4		2	3	-0	2	5	111	4.4000+03	-0.0000	1.0000-03	-0.0000	
fr21	N20	N23	N24	N25	N26	N27	N28	N29	BMULT	BMULT1	BMULT2	TMAX	
1	1	1	4	0	-0	4	99	-0	-1.0000+00	1.0000+05	-0.0000	8.6400+04	
		N33		N35	N36		N38	N39	BMULT1	BMULT2	BMULT3	BMULT4	
		-0		-0	-0	-0	-0	-0	-0.0000	-0.0000	-0.0000	-0.0000	
N41	N42	N43	N44	N45	N46	N47	N48	N49	TSLIM	ER[	ERU	HT	
0	0	-0	23	-0	-0	4	-0	3	2.0000+06	2.0000-02	5.0000-02	8.6400+04	
	N52	N53	N54		N56		N58	N59	CMULT	CMATCH	PERFIS	TOT	
	-0	-0	-0	-0	-0	-0	-0	-0	-0.0000	-0.0000	1.0000-03	4.7830-02	
N61	N62	N63	N64	N65	N66	N67	N68	N69	RATK1	RATK2	RATK3	GSHLD	
1	3	2	-0	-0	-0	-0	-0	-0	7.8700-01	2.0000-01	2.5570+00	6.7500-02	
JPASS	N72	N73			N16		N78	N79	PERLOS	DOAYS	DEXP	PERLS	
-0	-0	-0	-0		-0	-0	-0	-0	-0.0000	-0.0000	-0.0000	-0.0000	

INPUT ISOTOPIE CONCENTRATIONS

STEP	TEMP	ret	IC2	IC3	ICS	IC6	Ie7	Ica	IC9	Ie10	IC11	Ie12	PERIOD	M/F
1	1101K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000
IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	IF11	IF12	IF13	IF14	IF15
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST=	0.0000	FEXP=	0.0000	TEMP=	0.0000	SPFC=	2.4120-03	INL=	1.0000+00	TMOO=	5.5980+02	IE=	-0	
HURT=	3.6799+07	SCA=	0.0000	PWI=	3.0000-11	DENS=	0.0000	E=	0.0000	XK=	1.0021+11	JRP=	-0	
SNF=	2.7940-04	NFS3=	1.7110-06	NFS2=	-0.0000	NFS1=	-0.0000	GAM1=	-0.0000	GAM2=	-0.0000	NBP=	-0	
S12=	3.2950-02	S23=	6.0860-02	S34=	6.1520-02	S13=	-0.0000	S14=	-0.0000	S24=	0.0000	KEY=	-1	
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KEY=	-0	
S51=	1.9520-01	S52=	3.6110-01	S53=	3.6520-01	S54=	3.6520-01	SAWD=	2.0000-01	VR=	1.0000+00	KOUT=	-1	
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0	
CONV=	1.0000-03	BUCK=	2.4800-05	PF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	WIDTH=	2.2208-01	KP=	20	

BURN-UP OF REGION 1 IDENTIFIED AS 1101K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

3.87522-04 U238 4.74471-01

NSTEP	IOENT	NFS	IC1	IC2	IC3	IC4	ICS	IC6	IC7	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F
1	1102K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	1.7470
IC1	IC2	IC3	IC4	IC5	IC6	IC7	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F	DEL		
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST:	2.7630+00	FEXP=	1.3840+00	TEMP=	3.4980+02	SPEC=	1.5140-01	TNL=	1.0000+00	TMOD=	-2.8765+02	IE=	-0			
HORT=	3.6799+07	seA=	9.1250-01	PwI=	3.0000-11	DENS=	1.8900+01	E=	1.1920+00	XK=	1.6021+11	JMP=	0			
SEFE=	2.0850-02	NFS3=	-3.1000	NFS2=	3.8540-01	NFS1=	4.7510-02	GAMI=	0.0000	GAM2=	0.0000	NBP=	-0			
S12=	4.2510-02	S23=	9.8730-02	S34=	8.4160-02	S13=	-0.0000	S14=	-0.0000	S24=	1.6290-01	KEY=	-0			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
S51=	1.9260-01	S52=	4.2230-01	S53=	3.7780-01	S54=	3.8630-01	SAWD=	2.0000-01	VR=	7.1870-02	KOUT=	-1			
SSL1=	0.0000	SSL2=	0.0000	SSL3=	0.0000	SSL4=	0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	IEF=	0			
CONV=	1.0000-03	BUCK=	2.4800-05	PF=	5.0000-01	CLIM=	1.0000-02	ACNTRL=	1.0000+00	IDTH=	2.2936-01	KP=	20			

BURR-UP OF REGION 2 IDENTIFIED AS 1102K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

NSTEP	IOENT	NFS	IC1	IC2	IC3	IC4	IC5	IC6	IC7	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F
1	1103K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000
IC1	IC2	IC3	IC4	IC5	IC6	IC7	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F	DEL		
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST=	1.0000	FEXP=	3.0000	TEMP=	0.0000	SPEC=	2.4120-01	TNL=	1.0000+00	TMOD=	5.5480+02	IE=	-0			
HORT=	3.6799+07	seA=	0.0000	PwI=	3.0000-11	DENS=	0.0000	E=	0.0000	XK=	1.6021+11	JMP=	-0			
SEFE=	2.1900-04	NFS3=	1.7110-06	NFS2=	-0.0000	NFS1=	-0.0000	GAMI=	0.0000	GAM2=	-0.0000	NBP=	-0			
S12=	3.2850-02	S23=	6.3580-02	S34=	5.1520-02	S13=	-0.0000	S14=	-0.0000	S24=	0.0000	KEY=	-1			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
S51=	1.9520-01	S52=	3.8110-01	S53=	3.3320-01	S54=	3.6520-01	SAWD=	2.0000-01	VR=	1.0000+00	KOUT=	-1			
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0			
CONV=	1.0000-03	BUCK=	2.4800-05	PF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	IDTH=	2.2208-01	KP=	40			

BURR-UP OF REGION 3 IDENTIFIED AS 1103K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

U235 3.47542-04 U238 4.74471-02

STEP	IDENT	NFS	IC1	IC2	IC3	IC4	IC5	IC6	IC7	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F
1	1104K	-0	-C	-J	-0	-U	-0	-0	-0	-0	-0	-0	-0	-0	1.0	11.470
IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL				
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0

ECNST=	2.7680+00	FEXP=	1.3840+00	TEMP=	3.4080+02	SPEC=	1.5140-01	TNL=	1.0000+00	TMOD=	-2.8765+02	IE=	-0			
HORT=	3.6799+07	seA=	9.1250-01	PWT=	3.0000-11	DENS=	1.8000+01	E=	1.1920+00	XK=	1.6021+11	JMP=	-0			
SNF=	2.0880-02	NFS3=	-0.0000	NFS2=	3.6540-01	NFS1=	4.7510-02	GAM1=	0.0000	GAM2=	0.0000	NBP=	-0			

S12=	4.2510-02	S23=	9.8730-02	S34=	8.4160-02	S13=	-0.0000	S14=	-0.0000	S24=	1.6290-01	KEY=	-0			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
SS1=	1.9260-01	SS2=	4.2230-01	SS3=	3.7780-01	SS4=	3.8630-01	SAW0=	2.0000-01	VR=	7.1870-02	Kout=	-1			
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0			
CONV=	1.0000-03	BUCK=	2.4800-05	PF=	5.0000-01	CLIM=	1.0000-02	ACNTRL=	1.0000+00	WIDTH=	2.2936-01	KP=	20			

BURN-UP OF REGION 4 IDENTIFIED AS 1104K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

STEP	IDENT	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	IF11	IF12	PERIOD	M/F
1	1105K	-0	-0	-J	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000
IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL			
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0

FCNST=	1.0000	FEXP=	0.0000	TEMP=	0.0000	SPEC=	-2.4120-03	TNL=	1.0000+00	TMOD=	5.5980+02	IE=	-0		
HORT=	3.6799+07	seA=	0.0000	PWT=	3.0000-11	DENS=	0.0000	E=	6.0000	XK=	1.6021+11	JMP=	-0		
SNF=	2.7940-04	NFS3=	1.7110-06	NFS2=	-0.0000	NFS1=	-0.0000	GAM1=	-6.0000	GAM2=	-0.0000	NBP=	-0		

S12=	1.2050-02	S23=	6.0880-02	S34=	6.1520-02	S13=	-0.0000	S14=	-0.0000	S24=	-0.0000	KEY=	-1		
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0		
SS1=	1.9520-01	SS2=	3.6110-01	SS3=	3.6520-01	SS4=	3.6520-01	SAW0=	2.0000-01	VR=	1.0000+00	KOUT=	-1		
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0		
CONV=	1.0000-03	HOCK=	2.4800-05	PF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	WIOTH=	2.2208-01	KP=	20		

BURN-UP OF REGION 5 IDENTIFIED AS 1105K COMPLETED.

DIFFUSION OUTPUT AT 1.7557 SECONDS. POWER BASED ON OLD FLUX IS 2.0061+03

FINAL REACTIVITY FOR EACH CONTROL ITERATION WAS
1.0e00a00s

REACTIVITY WITH CONTROL RODS WITHDRAWN IS 1.01287

REGION	RADIUS	POWER	FLUX	PERCENT CHANGE	RE	PERCENT CHANGE	RS	PERCENT CHANGE	RF	PERCENT CHANGE	SHFD	PERCENT CONTROL
1	4.04	181.34	2.945+11	14.54	.0600	-96.79	.0655	-96.32	.0000	-1.00	.0000	-1.00
2	9.03	181.34	3.511+11	14.54	.0597	-102.86	.0676	-124.09	.1921	6.07	.0072	1.27
3	17.01	181.34	2.941+11	14.54	.0600	-96.78	.0654	-96.31	.0000	-1.00	.0000	-1.00
4	22.50	181.34	3.511+11	14.54	.0597	-102.86	.0676	-124.09	.1921	6.07	.0072	1.27

u n_

0127 1.0127

2.2052

21.11
11.14
7
2.2052

NORMALIZED DIFFUSION FLUXES BY MESH POINT

RADIUS	10	20	30	40	50	60	70	80	90	100
0.000	ES	F								T*
0.222	Es	F								T*
0.444	ES	F								T*
0.666	ES	F								T*
0.889	ES	F								T*
1.110	Es	F								T*
1.332	ES	F								T*
1.555	ES	F								T*
1.777	ES	F								T*
1.999	Es	F								T*
2.221	ES	F								T*
2.443	Es	F								T*
2.665	ES									
2.887	ES	F								T*
3.109	ES	F								T*
3.331	Es	F								T*
3.553	ES	F								T*
3.775	Es	F								T*
3.997	ES									
4.219	ES	F								T*
4.442	ES	F								T*
4.671	Es									
4.900	ES	F								T*
5.130	Es	F								T*
5.359	ES	F								T*
5.588	Es	F								T*
5.814	ES	F								T*
6.047	Es	F								T*
6.276	ES	F								T*
6.506	Es	F								T*
6.735	ES									
6.965	Es	F								T*
7.194	ES	F								T*
7.423	ES	F								T*
7.653	ES	F								T*
7.882	ES									
8.111	ES									
8.341	Es	F								T*
8.570	ES	F								T*
8.790	ES	F								T*
9.029	ES	F								T*
9.251	ES	F								T*
9.483	Es	F								T*

9.695	ES	F	T	*
9.911	ES	F	T	*
10.139	ES			
10.361	ES			
10.583	ES	F	T	*
10.805	ES			
11.028	ES	F	T	*
11.250	ES			
11.412	ES	E	T	*
11.694	ES			
11.916	ES	F	T	*
12.133	ES	F	T	*
12.360	ES	F	T	*
12.582	ES	F	T	*
12.814	ES	E	T	*
13.026	ES	F	T	*
13.248	ES	F	T	*
13.470	ES	F	T	*
13.692	ES	F	T	*
13.915	ES	F	T	*
14.137	ES	E	T	*
14.359	ES	F	T	*
14.581	ES	F	T	*
14.803	ES	F	T	*
15.025	ES	F	T	*
15.247	ES	F	T	*
15.469	ES			
15.691	ES			
15.913	ES	F	T	*
16.135	ES	F	T	*
16.357	ES	F	T	*
16.579	ES			
16.802	ES	F	T	*
17.024	ES	F	T	*
17.246	ES	F	T	*
17.469	ES	F	T	*
17.691	ES	F	T	*
17.912	ES			
18.134	ES	F	T	*
18.356	ES	F	T	*
18.578	ES	F	T	*
18.800	ES	F	T	*
19.022	ES	F	T	*
19.244	ES	F	T	*
19.466	ES	F	T	*
19.688	ES	F	T	*
19.910	ES	"	T	*
20.132	ES			
20.354	ES	F	T	*
20.576	ES	F	T	*
20.798	ES			
21.020	ES			
21.242	ES			
21.464	ES			
21.686	ES			
21.908	ES			
22.130	ES			
22.352	ES			
22.574	ES			
22.796	ES			
23.018	ES			
23.240	ES			
23.462	ES			
23.684	ES			
23.906	ES			
24.128	ES			
24.350	ES			
24.572	ES			
24.794	ES			
25.016	ES			
25.238	ES			
25.460	ES			
25.682	ES			
25.904	ES			
26.126	ES			
26.348	ES			
26.570	ES			
26.792	ES			
27.014	ES			
27.236	ES			
27.458	ES			
27.680	ES			
27.902	ES			
28.124	ES			
28.346	ES			
28.568	ES			
28.790	ES			
29.012	ES			
29.234	ES			
29.456	ES			
29.678	ES			
29.900	ES			
30.122	ES			
30.344	ES			
30.566	ES			
30.788	ES			
31.010	ES			
31.232	ES			
31.454	ES			
31.676	ES			
31.898	ES			
32.120	ES			
32.342	ES			
32.564	ES			
32.786	ES			
33.008	ES			
33.230	ES			

---BURRUP OF REGION 1 IDENTIFIED AS 11JIM COMPLETED.

	ABSORPTION CROSS SECTION	PERCENT THERM	REACTION RATE EPITH	RATE IN GROUP SLOWING	FISSION CROSS SECTION	PERCENT THERM	REACTION RATE EPITH	RATE IN GROUP SLOWING	N2N CROSS SECTION	
U233W	7.98464+02	77.38	4.43	17.78	.43	4.38083+02	78.55	4.57	16.42	.46
U235W	4.71088+02	89.03	4.12	6.55	.30	3.92446+02	90.59	4.14	4.94	.32
PJ239W	1.31947+03	78.98	17.38	3.49	.15	8.78252+02	90.62	15.99	3.17	.21
PJ241Z	1.27454+03	86.16	8.58	5.11	.15	9.53425+02	86.50	7.59	5.72	.19
TU232	1.39910+01	35.54	1.84	61.90	1.23	6.02686-02	.00	.00	.00	100.00
U238	3.55590+00	50.82	2.61	37.02	9.35	2.38234-01	.00	.00	100.00	1.16568-02
U238	1.37427+02	45.60	2.41	51.17	.81	1.13970+00	3.47	.18	6.12	90.23
PJ240	1.08843+03	18.89	2.18	78.82	.12	1.42450+00	3.22	.30	19.69	76.79
PA233	1.18762+02	24.57	1.58	73.79	.65					
U236	4.39927+01	7.90	.34	90.30	1.46	4.46930-01	.00	.00	100.00	
PJ242	1.33759+02	11.49	.61	87.08	.91	1.21320+00	1.02	.05	8.76	90.16
NP237	1.84178+02	63.17	6.95	19.29	.59	1.00331+00	1.26	.12	.58	98.04
AM241	2.22189+02	44.34	24.93	14.62	.11	5.53563+00	55.20	19.15	11.62	14.03
AM243	2.36466+02	32.27	1.22	66.13	.38	7.89234-01	.00	.00	.04	99.96
A242	5.86509+03	89.77	4.70	5.51	.62	1.69208+03	89.77	1.76	5.51	.92
C242	1.46673+01	89.77	4.70	5.51	.02					
C243	6.45415+02	89.77	4.70	5.51	.02	4.62058+02	89.77	4.70	5.51	.02
C244	7.90795+01	12.59	.69	85.02	1.70	2.09282+00	31.46	3.36	1.94	63.24
PJ238	3.59734+02	92.69	2.57	4.68	.60	1.42397+01	69.10	1.94	12.86	16.10
PGISO	-0.00000	90.36	9.64	.00	.00					
FPA	5.86745+02	89.77	4.70	5.51	.02					
Fp3	6.60024+02	29.93	3.19	66.87	.01					
FpC	4.83129+01	68.14	3.57	28.28	.02					
XE135	2.10997+06	99.27	.71	.02	.00					
SX149	6.12242+04	98.94	.53	.53	.00					
SX151	1.12508+04	87.82	4.62	7.56	.00					

ISOTOPE DESCENDANT CONCENTRATION DESTROYED				ADS	ABSAV	ALPHA	HEAT	POWER	QOLTY.
U233W	U234	-0.00000	0.00000	.00000	.00000	.11500	.0000	.0000	.0000
U235W	U236	3.87522-04	0.00000	.18256	.18256	.20039	93.0417	93.0817	.0000
PU239W	PU240	-0.00000	0.00000	.00000	.00000	.50238	.0000	.0000	86.2273
PU241Z	PU242	-0.00000	0.00000	.00000	.00000	.33630	.0000	.0000	.0000
TH232	PA233	-0.00000	0.00000	.00000	.00000	229.75028	.0000	.0000	
U238	PU239W	4.74471-02	0.00000	.16872	.16872	13.92611	6.9183	6.9183	
U234	U235W	-0.00000	0.00000	.00000	.00000	119.58179	.0000	.0000	
PU240	PU241Z	0.00000	0.00000	.00000	.00000	763.07711	.0000	.0000	
PA233	U234	0.00000	0.00000	.00000	.00000				
U236	PU237	0.00000	0.00000	.00000	.00000	97.43299	.0000	.0000	
PU242	AM243	0.00000	0.00000	.00000	.00000	112.75584	.0000	.0000	
MP237	PU238	0.00000	0.00000	.00000	.00000	182.57105	.0000	.0000	
AM241	CM242	0.00000	0.00000	.00000	.00000	113.26078	.0000	.0000	
AM243	CM244	0.00000	0.00000	.00000	.00000	298.61387	.0000	.0000	
AM242M	AM243	0.00000	0.00000	.00000	.00000	.25000	.0000	.0000	.0000
CM242	CM243	0.00000	0.00000	.00000	.00000				
CM243	CM244	0.00000	0.00000	.00000	.00000	.39682	.0000	.0000	.0000
CM244	PU238	0.00000	0.00000	.00000	.00000	.00000	.0000	.0000	
PU238	PU239W	0.00000	0.00000	.00000	.00000	24.26273	.0000	.0000	
FISSION PRODUCTS				.01104	.01104				

POISON = 0.0000 FPA = 0.0000 FPB = 0.0000 FPC = 0.0000 XE135 = 3.7348-09 SM149 = 3.6543-08
SM151 = 8.1608-08

TIME/HEAT	PAV/PHI	PMR/KRAT	THEUT/MA	PMXV/PMH	RID/R	FFF/DIS	XMLT/AMLT	ZTA/J	EPS/G	CR/ABSOR	CAB/FRA8
0.00000	9.72372+00	9.72372+00	284.910	1.00000	.88370	2.84384	1.04253	1.35176	1.04189	86.2273	.0000
0.00000	1.51053-11	1.51053-11	32.677	1.00000	.36756	1.00497	1.00253	.89194	.83327	.5848	40.9036

```

-----
U234 = 3.3165-18 PU240 = 3.1869-10 PA233 = 7.3913-19 U236 = 9.2361-08 PU242 = 3.5009-13 PU239 = 4.7447-02 PU238 = 4.7447-02
AM241 = 1.2619-17 AM243 = 0.0000 AM242 = 0.0000 CM242 = 0.0000 CM243 = 0.0000 CM244 = 0.0000
PU238 = 4.6687-13 POISON = 0.0000 EPA = -4.4415-09 FPB = 6.0042-08 FpC = 3.4947-07 XE135 = 3.7394-09
SM149 = 3.6622-08 SM151 = 8.1940-08
-----
TIME/MEAT PMV/PM1 PMV/PM10 TIEUT/WA PMV/PMHV RID/R FFF10IS XMT/AMET ZTATJ EPS/Q CR/ABSOR CBR/FRAR
8.63990+04 9.72870+00 9.73308+00 284.802 1.00051 .88370 2.84384 1.04300 1.35241 1.04182 86.0700 1.8782
9.75885+10 3.51053-17 1.01519+00 32.710 .99949 .06756 1.40543 1.04276 .89184 .83041 .3852 40.8817
-----

```

SHUT-UP OF REGION 2 IDENTIFIED AS 11)2K COMPLETED.

ABSORPTION PERCENT REACTION RATE IN GROUP					FISSION PERCENT REACTION RATE IN GROUP					N2N	
ISOTYPE	CROSS SECTION	TERM	EPITH	SLOWING	FAST	CROSS SECTION	TERM	EPITH	SLOWING	FAST	CROSS SECTION
U235W	4.86484+02	77.36	4.43	17.78	.43	4.38083+02	78.55	4.57	16.42	.46	
U235W	4.71088+02	89.03	4.12	6.55	.30	3.92446+02	90.59	4.14	4.94	.32	
PJ239W	1.31947+03	78.98	11.38	3.49	.15	8.18252+02	80.02	15.99	3.17	.21	
PJ241Z	1.27454+03	86.16	8.58	5.11	.15	9.53425+02	86.50	7.59	5.72	.19	
TU232	1.38070+01	35.04	1.84	61.90	1.23	6.02686+02	.00	.00	.00	100.00	
U238	3.55590+00	50.82	2.81	37.02	9.35	2.38234+01	.00	.00	.00	100.00	1.16568-02
U234	1.37427+02	45.60	2.41	51.17	RI	1.13970+00	3.47	.18	6.12	90.23	
Pu240	1.08843+03	18.89	2.18	78.82	.12	1.42450+00	3.22	.30	19.69	76.79	
PA233	1.18702+02	24.51	1.58	13.19	.05						
U236	4.39927+01	7.90	.34	90.30	1.46	4.46930+01	.00	.00	.00	100.00	
PJ242	1.38309+02	11.40	.61	87.08	.91	1.21320+00	1.02	.05	8.76	90.16	
NP237	1.84178+02	63.17	16.95	19.29	.59	1.00331+00	1.26	.12	.5a	98.04	
PU241	1.27189+02	16.34	20.93	14.62	.11	5.53563+00	55.20	19.15	11.62	14.03	
AM243	2.36466+02	32.27	1.22	66.13	.38	7.89234+01	.00	.00	.04	99.96	
AM242Z	5.86509+03	89.71	4.73	5.51	.02	4.69208+03	89.77	4.70	5.51	.02	
CM242	1.46673+01	89.77	4.73	5.51	.02						
CM243	6.45414+02	89.77	4.73	5.51	.02	4.62058+02	89.77	4.71	5.51	.02	
CM244	7.90195+01	12.59	.69	85.02	1.70	2.00282+00	31.46	3.36	1.94	63.24	
PJ238	3.59734+02	92.69	2.57	4.08	.66	1.42397+01	69.10	1.94	12.86	16.10	
POISON	-0.00000	90.36	9.64	.00	.00						
EPB	5.86745+02	89.77	4.73	5.51	.02						
EPB	6.60024+02	29.93	3.19	66.87	.01						
FPC	4.83129+01	68.14	3.57	28.28	.02						
XE135	2.10997+06	99.27	.71	.02	.00						
SM149	6.12242+04	98.94	.53	.53	.00						
SM151	1.12508+04	87.82	4.62	7.56	.00						

ISOTOPE	DESCENDANT	COEFFICIENT	DESTROYED	ASS	ARSAV	ALPHA	HEAr	POWER	COEFF.
U233W	U234	-0.00000	0.00000	.00000	.00000	.11500	.0000	.0000	.0000
U235W	U236	3.87522-04	0.00000	.18256	.18256	-.20034	-.7340417	-.240817	.0000
PU239W	PU240	-0.00000	0.00000	.00000	.00000	.50238	.0000	.0000	86.2273
PU241Z	PU242	0.00000	0.00000	.00000	.00000	.33680	.6006	.0000	1.0000
TH232	PA233	-0.00000	0.00000	.00000	.00000	229.75030	.0000	.0000	
U235	PU239W	-4.74471-32	0.00000	.15472	.15472	13.92611	6.9183	6.9183	
U234	U235W	-0.00000	0.00000	.00000	.00000	119.58130	.0000	.0000	
PU240	PU241Z	0.00000	0.00000	.00000	.00000	763.07712	.0000	.0000	
PA233	U234	0.00000	0.00000	.00000	.00000				
U236	PU237	0.00000	0.00000	.00000	.00000	97.43299	.0000	.0000	
PU242	AM243	0.00000	0.00000	.00000	.00000	112.75584	.0000	.0000	
AM243	PU238	0.00000	0.00000	.00000	.00000	102.57144	.0000	.0000	
AM241	CM242	0.00000	0.00000	.00000	.00000	113.26078	.0000	.0000	
AM243	CM244	0.00000	0.00000	.00000	.00000	258.61389	.0000	.0000	
AM242M	AM243	0.00000	0.00000	.00000	.00000	.25000	.0000	.0000	.0000
CM242	CM243	0.00000	0.00000	.00000	.00000				
CM243	CM244	0.00000	0.00000	.00000	.00000	.39632	.0000	.0000	.0000
CM244		0.00000	0.00000	.00000	.00000	.00000	.0000	.0000	
PU238	PU239W	0.00000	0.00000	.00000	.00000	24.26273	.0000	.0000	
FISSION PRODUCTS				.01104	.01104				

POISON = 0.0000	FPA = 0.0000	FPB = 0.0000	FPC = 0.0000	XE135 = 3.7348-09	SM149 = 3.6543-08
SM131 = 4.1508-05					
TEMPERATURE	POWER/HEAT	TEMPERATURE	TEMPERATURE	TEMPERATURE	TEMPERATURE
0.00000	9.72373+00	9.72373+00	284.910	1.00000	.88370
0.00000	3.51054 11	1.01519+00	32.677	1.00000	.06750
					2.84384
					1.04253
					1.35176
					1.04189
					86.2273
					.0000
					.3848
					97.9035

U233Y = 6.2401-21	U235W = 3.1869-19	PU239W = 4.7649-07	PU241Z = 3.5019-15	TP232 = 1.18000	U238 = 4.7447-02
U234 = 3.3165-18	PU24C = 3.1869-19	PA233 = 7.3913-19	U236 = 9.2361-08	PU242 = 8.5488-17	NP237 = 1.6832-09
U241 = 1.2515-17	AM242 = 0.0000	CM242 = 0.0000	CM243 = 0.0000	CM244 = 0.0000	
PU238 = 4.6687-13	POISE-1 = 0.0000	FPA = -4.4415-00	FPB = 6.0042-06	FpC = 3.4947-07	XE135 = 3.7394-09
SM149 = 3.6622-08	SM151 = 8.1940-08				

TIME/HEAT	FAV/PHI	FWN/KNLY	TNEUT/WA	PMXV/BNRW	RID/R	EFF/DIS	XMLT/XMLT	2TA/J	EPS/Q	CR/ABSOR	CAB/FRAB
8.63990+04	9.72871+00	9.73309+00	284.802	1.00051	.88370	2.84384	1.04300	1.35241	1.04182	86.0700	1.8782
9.72866(+00)	3.77145(+11)	1.01519(+00)	32.710	.99949	.06756	1.40543	1.04276	.89184	.83041	.3852	0.8417

BURN-UP OF REGION 4 rDETtTtFIEO AS 1104K COMPLETED.

DIFFUSION; ONTPUT AT 8.539e+04 SECONDS. POWER BASED ON OLD FLUX IS 4.4e+01

KEACTIVITY WITH CONTROL RODS WITHDRAWN IS 1.01490

REGION	RADIUS	POWER	FLUX	PERCENT CHANGE	RE	PERCENT CHANGE	RS	PERCENT CHANGE	RF	PERCENT CHANGE	SNFD	PERCENT CONTROL
1	4.44	.00	2.884-11	-3.52	.0600	-.00	.0655	-.04	.0000	-.00	.0000	-.00
2	9.03	101.35	3.461-11	1.44	.0597	-.09	.6675	.03	.1921	-.81	.0000	.00
3	17.91	.00	2.949-11	-1.45	.0599	-.05	.0654	-.02	.0000	-.00	.0000	-.00
4	21.50	101.35	3.461-11	-1.45	.0597	-.05	.0655	-.02	.1921	-.01	.0000	-.00
5	26.94	.00	2.942-11	-1.45	.0600	-.04	.0655	-.02	.0000	-.00	.0000	-.00

NORMALIZED DIFFUSION FLUXES BY MESH POINT

RADIUS	0	10	20	30	40	50	60	70	80	90	100
0.000	*	Es	F								T*
0.222	*	Es	F								T*
0.444	*	Es	F								T*
0.666	*	Es	F								T*
0.888	*	Es	F								T*
1.111	*	Es	F								T*
1.332	*	Es	F								T*
1.555	*	Es	F								T*
1.777	*	Es	F								T*
1.999	*	Es	F								T*
2.221	*	Es	F								T*
2.443	*	Es	F								T*
2.665	*	Es	F								T*
2.887	*	Es	F								T*
3.109	*	Es	F								T*
3.331	*	Es	F								T*
3.553	*	Es	F								T*
3.775	*	Es	F								T*
3.997	*	Es	F								T*
4.219	*	Es	F								T*
4.441	*	Es	F								T*
4.663	*	Es	F								T*
4.885	*	Es	F								T*
5.107	*	Es	F								T*
5.329	*	Es	F								T*
5.551	*	Es	F								T*
5.773	*	Es	F								T*
5.995	*	Es	F								T*
6.217	*	Es	F								T*
6.439	*	Es	F								T*
6.661	*	Es	F								T*
6.883	*	Es	F								T*
7.105	*	Es	F								T*
7.327	*	Es	F								T*
7.549	*	Es	F								T*
7.771	*	Es	F								T*
7.993	*	Es	F								T*
8.215	*	Es	F								T*
8.437	*	Es	F								T*
8.659	*	Es	F								T*
8.881	*	Es	F								T*
9.103	*	Es	F								T*
9.325	*	Es	F								T*
9.547	*	Es	F								T*

Time (min)	Sample	ES	F	T	ES	F	T
9.695	ES						
9.917	ES						
10.139	ES						
10.361	ES						
10.583	ES						
10.805	ES						
11.027	ES						
11.250	ES						
11.472	ES						
11.694	ES						
11.916	ES						
12.138	ES						
12.360	ES						
12.582	ES						
12.804	ES						
13.026	ES						
13.248	ES						
13.470	ES						
13.692	ES						
13.915	ES						
14.137	ES						
14.359	ES						
14.581	ES						
14.803	ES						
15.025	ES						
15.247	ES						
15.469	ES						
15.691	ES						
15.913	ES						
16.135	ES						
16.357	ES						
16.579	ES						
16.802	ES						
17.024	ES						
17.246	ES						
17.468	ES						
17.690	ES						
17.912	ES						
18.141	ES						
18.371	ES						
18.600	ES						
18.829	ES						
19.059	ES						
19.288	ES						
19.517	ES						
19.747	ES						
19.976	ES						
20.206	ES						
20.435	ES						
20.664	ES						
20.894	ES

<PR ALT.-TUOE HP237-AL TARGET

CONTROL CONSTANTS

N11	N12	N13	NTRL	KM	N16	N17	NREG	IG	POWER	RMuLT	CLOSE	RAD
1	1	1	2	1	1	1	1	1	4.4000+03	-0.0000	1.0000-03	-0.0000
N21	N22	N23	N24	N25	N26	N27	N28	N29	BMULT	HLO	EAE	TMAX
1	1	1	4	1	-0	4	99	-0	-1.0000+00	1.0000+05	-0.0000	8.6400+04
N31	N32	N33	N34	N35	N36	N37	N38	N39	BMULT1	BMuLr2	BMULT3	BMULT4
1	1	1	1	1	1	1	1	1	-0.0000	-0.0000	-0.0000	0.0000
N41	N42	N43	N44	N45	N46	N47	NSHUF	N49	TSLIM	ERL	ERU	HI
0	1	-C	20	-J	-0	4	-0	3	2.0000+06	2.0000-02	5.0000-02	8.6400+04
N51	N52	N54	N56	N58	N59	CMULT	CMATCH	PERFIS	TOT			
-0	-0	0	0	e	2	a.eace	8.8086	0.0000	6.0308 62			
N61	N62	N63	N64	N65	N66	N67	N68	N69	RAYK1	RAYK2	RAYK3	GSHLO
1	3	2	-0	-0	-0	-0	-0	-0	7.8700-01	2.0000-01	2.5570+00	6.7500-02
N72	N73	N74	N76	N78	N79	PERLOS	DDAYS	DEXP	PERLS			
-0	0	e	-0	e	0	0.0000	-0.0000	0.0000	0.0000			

INPUT IDENTIFICATION

ISTEP	IGENT	Ie1	IC3	IC4	IC5	IC6	IC7	Ica	IC9	Ie10	Ie12	PERIOD	M/F
1	1201K	-0	-J	-0	-0	-0	-0	-0	-0	-0	-0	1.0	0.000
-----IF1-----IF2-----IF3-----IF4-----IF5-----IF6-----IF7-----IF8-----IF9-----IF10-----MSTEP-----TIMEDR-----DEL-----													
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST=	0.0000	FEXP=	0.0000	TEMP=	0.0000	SPEC=	2.4120-03	TNL=	1.0000+00	yMOD=	5.5980+02	IE=	-0
HORI=	3.6799+07	SCA=	0.0000	PWT=	5.0000-11	DENS=	0.0000	E=	&0°00	XK=	1.021+11	JMP=	-11
SNF=	2.7940-04	NFS3=	1.7110-06	NFS2=	-0.0000	NFS1=	-0.0000	GAM1=	-0.0°00	GAM2=	-0.0000	NBP=	-0
S12=	3.2950-02	S23=	6.0860-02	S34=	6.1520-02	S13=	-0.0000	S14=	-0.0000	S24=	0.0000	KEY=	-1
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0
S51=	1.9520-01	S52=	3.6110-01	S53=	3.6520-01	S54=	3.6520-01	SAWD=	2.0000-01	VR=	1.0000+00	KOUR=	-1
SSL1=	0.0000	SSL2=	0.0000	SSL3=	0.0000	SSL4=	0.0000	SNFL=	-6.0000	PWAX=	3.0000+02	KF=	0
CONV=	1.0000-03	BUCK=	2.4800-05	PF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	WIDTH=	2.2208-01	KP=	20

BURN-UP OF REGION 1 IDENTIFIED AS 1201K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

4.34-03-04 U238 4.73514-02

ISTEP	IDENT	NFS	Ic1	Ic2	Ic3	Ic4	Ic5	Ic6	Ic7	Ic8	Ic9	Ic10	Ic11	Ic12	PERIOD	M/F
1	1202K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	11.470
ID1	ID2	ID3	ID4	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCCNST=	2.7290+00	FEXP=	1.3650+00	TEMP=	3.4980+02	SPEC=	1.6750-01	TNL=	1.0000+00	TM00=	-2.8765+02	IE=	-0			
HART=	3.6799+07	SCA=	9.1250-01	PWI=	3.0600-11	DENS=	1.8900+01	E=	1.1920+00	XK=	1.6021+11	JMP=	-0			
SNF=	2.0600-02	NFS3=	-0.0000	NFS2=	3.7480-01	NFS1=	4.8160-02	GAM1=	0.0000	GAM2=	0.0000	NBP=	-0			
S12=	4.2510-02	S23=	9.8680-02	S34=	8.3920-02	S13=	-0.0000	S14=	-0.0000	S24=	1.6270-01	KEY=	-0			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
S1=	1.9260-01	S52=	4.2200-01	S53=	3.7750-01	S54=	3.8590-01	SAWD=	2.0000-01	VR=	7.1870-02	KOUT=	-1			
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SfJFL=	-0.0000	PWMX=	3.0000+02	KF=	-0			
CONV=	1.0000-03	SUCK=	2.4800-05	PF=	8.7407-01	CLIM=	1.0000-02	ACNTRL=	1.0000+00	WIDTH=	2.2936-01	KP=	20			

BURN-UP OF REGION 2 IDENTIFIED AS 1202K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

ISTEP	IDENT	NFS	Ic1	Ic2	Ic3	Ic4	Ic5	Ic6	Ic7	Ic8	Ic9	Ic10	Ic11	Ic12	PERIOD	M/F
1	1203K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000
ID1	ID2	ID3	ID4	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCCNST=	0.0000	FEXP=	3.0000	TEMP=	0.0000	SPEC=	2.4120+03	TNL=	1.0000+00	TM00=	-5.5980+02	IE=	-0			
HART=	3.6799+07	SCA=	0.0000	PWI=	3.0600-11	DENS=	0.0000	E=	0.0000	XK=	1.6021+11	JMP=	-0			
SNF=	2.7940-04	NFS3=	1.7110-06	NFS2=	-0.0000	NFS1=	-0.0000	GAM1=	-0.0000	GAM2=	-0.0000	NBP=	-0			
S12=	1.2450-02	S23=	0.0850-02	S34=	0.1520-02	S13=	-0.0000	S14=	-0.0000	S24=	-0.0000	KEY=	-1			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
S51=	1.9520-01	S52=	3.6110-01	S53=	3.6520-01	S54=	3.6520-01	SAWD=	2.0000-01	VR=	1.0000+00	KOUT=	-1			
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0			
CONV=	1.0000-03	BOCK=	2.4800-05	pF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	WIDTH=	2.2208-01	KP=	40			

BURN-UP OF REGION 3 IDENTIFIED AS 1203K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

6.76150-05 PC150M 6.02348-02

JSTEP	IDENT	NFS	IC1	IC2	IC3	IC4	ICS	IC6	IC7	ICA	IC9	IC10	IC12	PERIOD	M/F	
101	102	103	104	IF1	IF2	IF3	IF4	IFS	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEOR	DEL
-0	-C	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
<p>PCONST= 7.4210+00 FEXP= 3.7110+00 TEMF= 1.2684+02 SPEC= 2.1470-02 TNL= 1.0000+00 TMOO= -2.8765+02 IE=-0</p> <p>HORT= 3.6799+07 SCA= 4.8930-01 PWI= 3.0000-11 OJIS= 2.7230+00 E= 1.1717+06 XK= 1.6021+11 JMP= -0</p> <p>SXF= 3.6620-02 NFS3= -0.0000 rJFS2= 5.2650-01 rJFS1= 5.2350-02 GAM1= 6.0000 GAM2= 0.0000 NBP= -0</p> <p>S12= 4.1260-02 S23= 1.0010-01 S34= 8.5660-02 S13= -0.0000 S14= -0.0000 S24= 1.7580-01 KEY=-0</p> <p>SL12= -0.0000 SL23= -0.0000 SL34= -0.0000 SL13= -0.0000 SL14= -0.0000 SL24= -0.0000 KIND=-0</p> <p>SS1= 1.9160-01 S52= 3.5520-01 SS3= 3.5760-01 S54= 3.6850-01 SAWD= 2.0000-01 VR= 7.1870-02 KOUT=-1</p> <p>SSL1= -0.0000 SSL2= -0.0000 SSL3= -0.0000 SSL4= -0.0000 SNFL= -0.0000 PWMX= 3.0000+02 KF= -0</p> <p>CONV= 1.0000-03 BUCK= 2.4800-05 pF= 1.2593-01 CLIM= 1.0000-02 ACNTRL= 0.0000 WIDTH= 2.2936-01 KP= 20</p>																

BURN-UP OF REGION 4 IDENTIFIED AS 12C4K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

JSTEP	IDENT	NFS	IC1	IC2	IC3	IC4	IC5	IC6	IC7	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F
101	102	103	104	IF1	IF2	IF3	IF4	IFS	IF6	IF7	IFA	IF9	IF10	MSTEP	TIMEOR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
<p>PCONST= 7.5000 FEXP= -0.0000 TEMF= -0.0000 SPEC= -2.4120-03 TNL= -1.0000+00 TMOO= -5.5980+02 IE= -0</p> <p>HORT= 3.6799+07 seA= 0.0000 PWI= 3.0000-11 DENS= 0.0000 E= 0.0000 XK= 1.6021+11 JMP= -0</p> <p>SXF= 2.7940-04 NFS3= 1.1110-00 rJFS2= -0.0000 rJFS1= -0.0000 GAM1= 0.0000 GAM2= -0.0000 NBP= -0</p> <p>S12= 3.2550+02 S23= 8.2060-02 S34= 6.1520-02 S13= -0.0000 S14= -0.0000 S24= -0.0000 KEY= -1</p> <p>SL12= -0.0000 SL23= -0.0000 SL34= -0.0000 SL13= -0.0000 SL14= -0.0000 SL24= -0.0000 KIND= -0</p> <p>SS1= 1.9520-01 S52= 3.3110-01 SS3= 3.5520-01 S54= 3.6520-01 SAWD= 2.0000-01 VR= -1.0000+00 KOUT= -1</p> <p>SSL1= -0.0000 SSL2= -0.0000 SSL3= -0.0000 SSL4= -0.0000 SNFL= -0.0000 PWMX= 3.0000+02 KF= -0</p> <p>CONV= 1.0000-03 eUfK= 2.4800-05 pF= -0.0000 CLIM= 1.0000-02 ACNTRL= -0.0000 WIDTH= 2.2208 01 KP= 20</p>																

BURN-UP OF REGION 5 IDENTIFIED AS 12C5K COMPLETED.

DIFFUSION OUTPUT AT 0.0000 SECONDS. POWER BASED ON OLD FLUX IS 1.5482+03

REACTIVITY WITH CONTROL RODS WITHDRAWN IS .96000

FLUX REDUCED BY A FACTOR OF 1.209 DUE TO POWER PEAK IN REGION 2

REGION	RADIUS	power	FLUX	PERCENT CHANGE	RE	PERCENT CHANGE	RS	PERCENT CHANGE	RF	PERCENT CHANGE	SNFD	PERCENT CONTROL
1	4.44	.00	4.370-11	26.29	.0452	95.73	.0503	95.20	.0000	-.00	.0000	-.00
2	9.03	.00	4.437-11	39.23	.0425	-215.45	.0490	-241.71	.1599	-24.87	.0000	-.00
3	17.91	.00	4.800-11	37.50	.0554	94.55	.0377	93.61	.0000	-.00	.0000	-.00
4	22.50	.00	5.513-11	54.08	.0296	41.96	.0505	29.67	.0583	56.88	.0000	-.00
S	26.94	.00	5.514-11	45.60	.0284	93.20	.0288	91.62	.0000	-.00	.0000	-.00

NORMALIZED DIFFUSION FLUXES BY MESH POINT

RADIUS	*	10	20	30	40	50	60	70	80	90	100
0.000	ES	F						T			●
0.222	ES	F						T			●
0.444	ES	F						T			●
0.666	ES	F						T			●
0.888	ES	F						T			●
1.110	ES	F						T			●
1.332	ES	F						T			●
1.555	ES	F						T			●
1.777	ES	F						T			●
1.999	ES	F						T			●
2.221	ES	F						T			●
2.443	ES	F						T			●
2.665	ES	F						T			●
2.887	ES	F						T			●
3.109	ES	F						T			●
3.331	ES	F						T			●
3.553	ES	F						T			●
3.775	ES	F						T			●
3.997	ES	F						T			●
4.219	ES	F						T			●
4.442	ES	F						T			●
4.671	ES	F						T			●
4.900	ES	F						T			●
5.130	ES	F						T			●
5.359	ES	F						T			●
5.58d	ES	F						T			●
5.813	ES	F						T			●
6.047	ES	F						T			●
6.276	ES	F						T			●
6.506	ES	F						T			●
6.135	ES	F						T			●
6.965	ES	F						T			●
7.194	ES	F						T			●
7.423	ES	F						T			●
7.653	ES	F						T			●
7.882	ES	F						T			●
8.111	ES	F						T			●
8.341	ES	F						T			●
8.570	ES	F						T			●
8.799	ES	F						T			●
9.029	ES	F						T			●
9.251	ES	F						T			●
9.473	ES	F						T			●

Time (min)	ES	F	T	Other
9.095	ES	F		*
9.917	ES	F		
10.139	ES			
10.361	ES	F		
10.583	ES	F		
10.805	ES	F		
11.023	ES	F		
11.250	ES			
11.472	ES	F		
11.694	ES			
11.916	ES	F		
12.138	ES	F		
12.360	ES	F		
12.582	ES			
12.804	ES	F		
13.026	ES			
13.248	ES	F		
13.470	ES			
13.692	ES	F		
13.915	ES	F		
14.137	ES	F		
14.359	ES			
14.581	ES	F		
14.803	ES	F		
15.025	ES	F		
15.247	ES			
15.469	ES	F		
15.691	ES			
15.913	ES	F		
16.135	ES			
16.357	ES	F		
16.579	ES			
16.802	ES			
17.024	ES			
17.246	ES	F		
17.468	ES	F		
17.690	ES	F		
17.912	ES	F		
18.141	ES	F		
18.371	ES			
18.593	ES	F		
18.829	ES			
19.059	ES	F		
19.288	ES			
19.511	ES	F		
19.747	ES			
19.976	ES	F		
20.206	ES			
20.435	ES	F		
20.664	ES			
20.894	ES

<PR ALT.-TUBE r-IP237-t,L TARGET

CONTROL CONSTANTS

N12					N16			NREG	IG	rOWER	RMULT	CLOSE	RAO
2					-0				111	4.4000+03	-0.0000	1.0000-03	-0.0000
N21	N22	N23	N24	N25	N26	N27	N28	N29	BMULT	HL0	EAE	TMAX	
1	1	1	4	5	-0	4	99	-0	-1.0000+00	1.0000+05	-0.0000	8.6400+04	
N31	N32	N33	N34	N35	N36	N37	N38	N39	BMULT1	BMULT2	BMULT3	BMULT4	
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0.0000	-0.0000	-0.0000	-0.0000	
N41	N42	N43	N44	N45	N46	N47	NSHUF	N49	TSLIM	ERC	ERU	HI	
0	0	-0	20	-0	-0	4	-0	3	2.0000+06	2.0000-02	5.0000-02	8.6400+04	
N51	N52	N54	N56	N58	N59	CMULT	CMATCH	PERFIS	TOT				
-0	-0	-0	-0	-0	-0	-0.0000	-0.0000	1.5190-02	4.7840-02				
N61	N62	N63	N64	N65	N66	N67	N68	N69	RAYK1	RAYK2	RAYK3	GSFLU	
1	1	2	-0	-0	-0	-0	-0	-0	2.0700-01	2.0000-01	2.5570+00	6.7510-02	
N71	N72	N73	N74	N75	N76	N77	N78	N79	PERLOS	DDAYS	DEXP	PERLS	
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0.0000	-0.0000	-0.0000	-0.0000	

INPUT STOP IC CONCENTRATIONS

NSTEP	IDENT	IFS	IC1	IC2	IC3	IC4	res	IC6	IC7	Ica	ICc	IeIO	ICII	IC12	PERIon	M/F
1	1301K	-C	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000
IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	IF11	IF12	IF13	IF14	IF15	IF16	IF17
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST=	0.0000	FEXP=	0.0000	TEMP=	0.0000	SPEC=	2.4120-03	TNL=	1.0000+00	TM00=	5.5980+02	IE=-0				
HORT=	3.6799+07	seA=	0.0000	PWI=	3.0000-11	DEfis=	0.0000	E=	0.0000	XK=	1.6021+11	JMP=	-0			
SNF=	2.7940-04	NFS3=	1.7110-36	NFS2=	-0.0000	NFS1=	-0.0000	GAM1=	-0.0000	GAM2=	-0.0000	NFP=	-0			
512=	3.2950-02	523=	6.0860-02	534=	6.1520-02	513=	-0.0000	514=	-0.0000	524=	0.0000	KEY=	-1			
SL13=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SLT3=	-0.0000	SLT4=	-0.0000	SL29=	-0.0000	KTRJ=	-0			
551=	1.9520-01	552=	3.6110-01	553=	3.6520-01	554=	3.6520-01	SAWD=	2.0000-01	VR =	1.0000+00	KOUT=	-1			
SsL1=	-0.0000	sSL2=	-0.0000	SsL3=	-0.0000	SsL4=	-0.0000	SNFL=	-0.0000	PWAX=	3.0000+02	KF =	-0			
CONV=	1.0000-03	BUCK=	2.4800-05	pF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	WIDTH=	2.2208-01	KP =	20			

NUMBER OF REGION 1 IDENTIFIED AS 1301K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

U235W 7.26004-04 U238 4.71123-02

NSTEP	IDENT	NFS	Ic1	IC2	IC3	IC4	IC5	IC6	IC7	IC8	IC9	Ic10	Ic11	IC12	PERIOD	M/F
1	1302K	-0	-0	-0	-0	-0	-0	-0	-0	0	0	-0	-0	-0	1.0	11.70
I01	I02	I03	I04	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIME0A	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST=	2.6390+00	FEXP=	1.3190+00	TEMP=	3.4980+02	SPEC=	2.0110-01	TNL=	1.0000+00	TMOD=	-2.8765+02	IE=	-0			
HORT=	3.6799+07	seA=	1.0000+00	PwI=	3.0000-11	DENS=	1.0000+01	E=	1.1920+00	XK=	1.6021+11	JMP=	-0			
SNF=	2.0010-02	NFS3=	-0.0000	NFS2=	3.9350-01	rIFS1=	4.9600-02	GAMI=	0.0000	GAM2=	0.0000	N8P=	-0			
S12=	4.2510-02	S23=	9.8500-02	S34=	8.3430-02	S13=	-0.0000	S14=	-0.0000	S24=	1.6220-01	KEY=	-0			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
S51=	1.9260-01	SS2=	4.2120-01	S53=	3.7690-01	S54=	3.8500-01	SAWD=	2.0000-01	VR=	7.1870-02	KOUT=	-1			
sSL1=	0.0000	sSL2=	-0.0000	sSL3=	0.0000	sSL4=	0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0			
CONV=	1.0000-03	BUCK=	2.4800-05	pF=	8.7407-01	CLIM=	1.0000-02	ACNTRL=	1.0000+00	WIDTH=	2.2936-01	KP=	20			

BURN-UP OF REGION 2 IDENTIFIED AS 1302K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

NSTEP	IDENT	NFS	Ic1	IC2	IC3	IC4	IC5	IC6	IC7	IC8	IC9	Ic10	Ic11	IC12	PERIOD	M/F
1	1303K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000
I01	I02	I03	I04	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIME0A	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST=	1.0000	FEXP=	0.0000	TEMP=	0.0000	SPEC=	-2.4120-03	TNL=	1.0000+00	TMOD=	-5.5000+02	IE=	-0			
HORT=	3.6799+07	seA=	0.0000	PwI=	3.0000-11	DENS=	0.0000	E=	8.0000	XK=	1.6021+11	JMP=	-0			
SNF=	2.7940-04	NFS3=	1.0000-00	NFS2=	0.0000	rIFS1=	-0.0000	GAMI=	0.0000	GAM2=	0.0000	N8P=	-0			
S12=	3.1000-02	S23=	4.0000-02	S34=	6.1520-02	S13=	-0.0000	S14=	-0.0000	S24=	0.0000	KEY=	-1			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
S51=	1.7520-01	SS2=	3.5100-01	S53=	3.0520-01	S54=	3.6520-01	SAWD=	2.0000-01	VR=	1.0000+00	KOUT=	-1			
sSL1=	-0.0000	sSL2=	-0.0000	sSL3=	-0.0000	sSL4=	-0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0			
CONV=	1.0000-03	BUCK=	2.4800-05	pF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-6.0000	WIDTH=	2.2208-01	KP=	-40			

BURN-UP OF REGION 3 IDENTIFIED AS 1303K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

NP237 6.26050-05 POISON 6.42144-02

ISTEP	IDENT	NFS	Ie1	IC2	IC3	IC4	res	IC6	Ie7	IC8	IC9	IC10	Ie11	Ie12	PERIOD	M/F
1	1304K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	11.470
101	102	103	104	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST=	7.4210+20	FEXP=	3.7110+00	TEMP=	1.2184+02	SPEC=	2.1470-02	TNL=	1.0000+00	TMOD=	-2.8785+02	IE=	-0			
HORT=	3.6799+37	seA=	4.8900-01	PwI=	3.0000-11	DENS=	2.1230+00	E=	1.1707+00	XK=	1.0021+11	JMP=	-0			
SNE=	3.6620-02	NFS3=	-0.0000	NFS2=	5.2650-01	NFS1=	5.2350-02	GAM1=	0.0000	GAM2=	0.0000	NBP=	-0			
SL2=	4.1260-02	SL23=	1.0010-01	SL34=	8.5660-02	SL13=	-0.0000	SL14=	-0.0000	SL24=	1.7580-01	KEY=	-0			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
SSL1=	1.9160-01	SSL2=	3.5520-01	SSL3=	3.5700-01	SSL4=	3.6850-01	SAWD=	2.0000-01	VR=	7.1870-02	KOUT=	-1			
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0			
CONV=	1.0000-03	BUCK=	2.4800-05	PF=	1.2593-01	CLIM=	1.0000-02	ACNTRL=	0.0000	WIDTH=	2.2936-01	KP=	20			

BURN-UP OF REGION 4 IDENTIFIED AS 1304K COMPLETED.

INPUT ISOTOPIE CONCENTRATIONS

ISTEP	IDENT	NFS	IC1	IC2	IC3	IC4	IC5	IC6	IC7	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F
1	1305K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	0.000
101	102	103	104	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST=	0.0000	FEXP=	1.0000	TEMP=	0.0000	SPEC=	2.4120-03	TNL=	1.0000+00	TMOD=	5.5980+02	IE=	-0			
HORT=	3.6799+37	seA=	0.0000	PwI=	3.0000-11	DENS=	0.0000	E=	0.0000	XK=	1.6021+11	JMP=	-0			
SNE=	2.7940-04	NFS3=	1.7110-06	NFS2=	-0.0000	NFS1=	-0.0000	GAM1=	-0.0000	GAM2=	-0.0000	NBP=	-0			
SL1=	3.2950-02	SL2=	8.1560-02	SL3=	6.1520-02	SL4=	-0.0000	SL5=	-0.0000	SL6=	0.0000	SL7=	0.0000	KEY=	-1	
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
SSL1=	1.9520-01	SSL2=	3.6110-01	SSL3=	3.6520-01	SSL4=	3.6520-01	SAWD=	2.0000-01	VR=	1.0000+00	KOUT=	-1			
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0			
CONV=	1.0000-03	BUCK=	2.4800-05	PF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	WIDTH=	2.2208-01	KP=	20			

BURN-UP OF REGION 5 IDENTIFIED AS 1305K COMPLETED.

DIFFUSION OUTPUT AT 0.0000 SECONDS. POWER BASED ON OLD FLUX IS 2.0953E3

FINAL REACTIVITY FOR EACH CONTROL ITERATION WAS

.99999987

ρ'

REACTIVITY WITH CONTROL RODS WITH GRAMM IS 1.08717

FLUX REDUCED BY A FACTOR OF 1.201 DUE TO POWER PEAK IN REGION 2

CONTROL RODS			FLUX	PERCENT CHANGE	RE	PERCENT CHANGE	RS	PERCENT CHANGE	PERCENT CHANGE	SNFD	PERCENT CONTROL	
1	4.44	.00	3.293-11	8.90	.0523	96.31	.0589	95.91	.0000	.00	.0000	-.00
2	9.03	300.00	3.996-11	24.92	.0488	-229.39	.0574	-250.13	.1897	-26.38	.0575	8.02
3	17.01	.00	4.039-11	25.56	.9398	95.15	.9127	94.35	.0000	ega	.0000	.99
4	22.50	.04	5.605-11	46.48	.0328	47.65	.0339	36.65	.0652	61.43	.0000	-.00
5	24.94	.00	4.753-11	35.44	.0313	43.04	.0314	72.42	.0000	-.00	.0000	-.00

OK @ 1.26 ρ' / 235

NORMALIZED DIFFUSION FLUXES 9Y MESH POINT

BURN-UP OF REGION IDENTIFIED AS TASK COMPLETED.

BSCppTIOfl		PERCENT REACTION RATE IN GROUP				FISSION		PERCENT REACTION RATE IN GROUP				N2N	
ISOTOP	CROSS SECTION	THERM	EPITR	SLOWING	FAST	CROSS SECTION	THERM	EPITR	SLOWING	FAST	CROSS SECTION		
U235	4.02627+02	77.75	4.21	17.54	.44	3.15994+02	78.43	4.35	16.24	.52			
U235W	4.02627+02	90.11	3.85	5.75	.34	3.3615C+02	91.49	3.81	4.33	.37			
PU239W	1.12685+03	79.71	16.05	3.47	.17	7.51114+02	81.31	15.30	3.15	.25			
PU241Z	1.09481+03	86.60	8.18	5.05	.17	8.19600+02	86.90	7.23	5.65	.22			
U238	1.18472+01	35.42	1.76	61.41	1.41	5.94058+02	.00	.00	.00	100.00			
U238	3.14574+00	49.67	2.53	37.31	10.41	2.34823-01	.00	.00	.00	100.00	1.14899-02		
U238	1.18274+02	45.42	2.29	50.96	.93	1.10876+00	3.04	1.6	5.34	91.42			
PU240	9.33534+02	19.03	2.08	78.76	.13	1.35947+00	2.92	.26	17.52	79.31			
Pa233	1.81171+G2	24.94	1.52	73.48	.C6								
U236	3.74801+01	8.03	.33	89.96	1.69	4.40532-01	.00	.00	.00	100.00			
PU242	1.17539+02	11.58	.53	86.79	1.05	1.17969+00	.91	.05	7.65	91.40			
U237	1.57294+02	63.92	16.22	19.17	.69	9.86422-01	1.11	.10	.Sc	98.30			
A241	2.47962+02	43.19	23.11	14.59	.12	4.81161+00	54.73	18.01	11.35	15.91			
A243	2.02062+02	32.71	1.17	65.60	.44	7.77893-01	.00	.un	.03	99.97			
A242	5.05436+03	90.08	4.47	5.42	.03	4.64327+03	90.08	4.47	5.42	.03			
C242	1.26391+01	90.08	4.47	5.42	.03								
C243	5.56165+02	95.08	4.47	5.42	.03	3.98165+02	90.08	4.47	5.42	.03			
C244	6.74457+01	12.76	.67	84.61	1.96	1.9658A+00	28.96	2.92	1.75	66.37			
PU238	3.10877+02	92.80	2.44	4.01	.75	1.25538+01	67.81	1.80	12.38	18.01			
porSON	0.00000	90.33	9.17	.00	.00								
FPA	5.05609+02	90.08	4.47	5.42	.03								
FpB	5.62710+02	30.35	3.06	66.58	.01								
FpC	1.14313+01	68.62	3.45	27.95	.02								
XE135	1.82413+06	99.31	.68	.02	.00								
S149	5.28910+04	98.97	.51	.52	.00								
S151	9.69135+03	88.16	4.45	7.45	.00								

ISOTOPE	DESCENDANT	CONCENTRATION	DESTROYED	ASS	ABSAV	ALPHA	HEAr	POWER	CONV.
U233W	U234	-0.00000	0.00000	.00000	.00000	.11475	.0000	.0000	.0000
U235W	U236	7.26604-04	0.00000	.29255	.29255	.19776	95.4668	95.6668	.0000
PU239W	pu24Q	-0.00000	0.00000	.00000	.00000	.50024	.0000	.0000	46.8773
PU241Z	PU242	-0.00000	0.00000	.00000	.00000	.33578	.0000	.0000	.0000
TH232	PA233	-0.00000	0.00000	.00000	.00000	199.26978	.0000	.0000	.0000
U235	PU239W	4.71125-02	0.00000	.14820	.14820	12.50618	4.3332	4.3332	
U234	U235W	-0.00000	0.00000	.00000	.00000	1u5.68106	.0000	.0000	
PU240	PU241Z	0.00000	0.00000	.00000	.00000	685.68807	.0000	.0000	
PA233	U234	0.00000	0.00000	.00000	.00000				
U235	PU237	0.00000	0.00000	.00000	.00000	a4.07901	.0000	.0000	
PU242	AM243	0.00000	0.00000	.00000	.00000	98.63610	.0000	.0000	
AP237	PU238	0.00000	0.00000	.00000	.00000	158.45911	.0000	.0000	
AM241	CM242	0.00000	0.00000	.00000	.00000	110.85849	.0000	.0000	
AM243	CM244	0.00000	0.00000	.00000	.00000	258.75536	.0000	.0000	
AM242M	AM243	0.00000	0.00000	.00000	.00000	.24999	.0000	.0000	.0000
CM242	CM243	0.00000	0.00000	.00000	.00000				
CM243	CM244	0.00000	0.00000	.00000	.00000	.39631	.0000	.0000	.0000
CM244		0.00000	0.00000	.00000	.00000	.00000	.0000	.0000	
PU238	pu239W	0.00000	0.00000	.00000	.00000	23.76351	.0000	.0000	
FISSTON PRODUCTS				.61706	.61706				

POISON = 0.0000 FPA = 0.0000 FPB = 0.0000 FPC = 0.0000 XE135 = 6.7308-09 SM149 = 6.4869-08
SM151 = 1.4193-17

TEMPERATURE	POWER/PU	PERCENTAGE	HEAT/VA	WATT/PMW	WATT/PMW	EFFICIENCY	WATT/AMT	WATT/AMT	EPS/0	CR/ABSOR	CR/FRAG
0.00000	1.72937+01	1.72937+01	283.270	1.00000	.85036	3.30220	1.30296	1.60235	1.02671	46.8773	.0000
0.00000	3.99551-11	1.01520+00	51.062	1.00000	.05/44	1.04644	1.30296	.90044	.88042	.4194	28.6075

U237	= 8.9061-21	U235W	= 7.2555-04	PU239	= 4.7250-07	PU241Z	= 3.2543-13	T4232	= 0.0000	U238	= 4.7112-02
U234	= 3.5918-18	PU240	= 3.0630-10	PA233	= 8.2449-19	U236	= 1.6662-07	PU242	= 7.8221-17	NP237	= 1.8788-09
AM241	= 1.1837-17	AM243	= 0.0000	AM242	= 0.0000	CM242	= 0.0000	CM243	= 0.0000	CM244	= 0.0000
PU239	= 5.0579-13	POISon	= 0.0000	EPA	= -1.5431-09	FPB	= 1.0550-01	EpC	= 6.1878-07	xE135	= 6.7326-09
SM149	= 6.4888-08	SM151	= 1.4216-07								

TIME/HELT	PAW/PMI	PMR/PMAT	TIMEUT/HA	PMxV/PMHV	RID/R	FFF/DIS	XMLET/AMLT	ZTA/ZJ	EPS/6	CR/AM50R	CAB/FRAR
8.63990+04	1.72945+01	1.72953+01	283.208	1.00005	.85036	3.30220	1.30274	1.60235	1.02670	46.8634	12.0014
1.72997+17	3.95537+11	1.01525+00	51.067	.99995	.05744	1.64648	1.30285	.90627	.88044	.4796	28.6023

BURN UP OF REGION 2 IDENTIFIED AS 100% COMPLETED.

ISOTOPE	ABSORPTION CROSS SECTION	PERCENT THERM	REACTION RATE EPITH	REACTION RATE SLOWING	REACTION RATE FAST	FISSION CROSS SECTION	PERCENT THERM	REACTION RATE EPITH	REACTION RATE SLOWING	REACTION RATE FAST	N2N CROSS SECTION
U233W	5.93375+02	90.52	2.00	-7.36	.12	5.36972+02	91.09	2.00	8.74	.13	
U235W	6.27510+02	94.95	1.81	3.17	.08	5.27436+02	95.75	1.80	2.37	.08	
Pu239W	1.63858+03	95.85	7.75	1.41	.04	1.10245+03	91.67	1.00	1.21	.00	
Pu241Z	1.65818+03	94.37	3.61	1.98	.04	1.24237+03	94.55	3.19	2.21	.05	
Ta232	1.14528+01	69.47	1.22	37.80	.51	2.04929+02	.00	.00	.00	100.00	
U238	1.75052+01	14.67	.31	84.37	.65	8.10058+02	.00	.00	.00	100.00	3.96362+03
U234	1.27633+02	69.69	1.42	28.60	.30	4.42112+01	12.72	.26	7.93	79.09	
Pu240	7.51834+02	38.89	1.73	59.32	.06	5.89465+01	11.22	.40	24.30	64.08	
Pa233	6.65495+01	47.69	1.19	50.80	.02						
U236	2.52133+01	19.58	.32	79.23	.87	1.51968+01	.00	.00	.00	100.00	
Pu242	6.36672+01	76.75	.35	72.23	.51	4.43333+01	3.98	.08	12.05	83.89	
Np237	1.97347+02	63.83	7.82	8.15	.19	3.55637+01	5.04	.17	.74	94.05	
Am241	3.17545+02	82.03	10.40	6.64	.03	5.53766+00	70.85	10.54	5.84	4.77	
Am243	1.88700+02	57.32	.84	41.67	.16	2.68412+01	.00	.00	.00	99.94	
Am242B	7.79739+03	95.97	1.94	2.08	.01	6.23792+03	95.97	1.94	2.08	.01	
Am242	1.94996+01	95.97	1.94	2.08	.01						
Am243	6.58244+02	95.97	1.94	2.08	.01	6.14289+02	95.97	1.94	2.08	.01	
Am244	4.87172+01	29.05	.62	69.40	.94	1.44485+00	64.77	2.67	1.41	31.15	
Pu238	4.86732+02	97.28	1.04	1.52	.17	1.58240+01	88.30	.95	5.82	4.93	
POISON	-0.00000	96.04	3.96	.00	.00						
Fp8	5.14293+02	54.59	2.25	43.16	.00						
FpC	5.46567+01	85.68	1.73	12.58	.01						
XE135	2.98468+06	99.72	.27	.01	.00						
Sm149	3.65151+04	99.61	.25	.16	.00						
Sm151	1.47562+04	95.17	1.93	2.90	.00						

ISOPE DESCENDANT CONCENTRATION			DESTROYED	A8S	ABSAV	ALPHA	HEAT	POWER	CONV.
U233W	U234	-0.00000	0.00000	.00000	.00000	.10504	.0000	.0000	.0000
U235W	U236	-0.00000	0.00000	.00000	.00000	.18974	.0000	.0000	.0000
PU239W	pu240	-0.00000	0.00000	.00000	.00000	.48631	.0000	.0000	.0000
PU241Z	PU242	0.00000	0.00000	.00000	.00000	.33478	.0000	.0000	.0000
TH232	PA233	-0.00000	0.00000	.00000	.00000	557.86575	.0000	.0000	.0000
U233	PU239W	-0.00000	0.00000	.00000	.00000	215.09749	.0000	.0000	.0000
U234	U235W	-0.00000	0.00000	.00000	.00000	288.14095	.0000	.0000	.0000
PU240	PU241Z	0.00000	0.00000	.00000	.00000	124.22860	.0000	.0000	.0000
PA233	U234	0.00000	0.00000	.00000	.00000	187.70193	.0000	.0000	.0000
U236	PU237	0.00000	0.00000	.00000	.00000	164.91141	.0000	.0000	.0000
PU242	AM243	0.00000	0.00000	.00000	.00000	187.70193	.0000	.0000	.0000
TH237	PU238	0.00000	0.00000	.00000	.00000	553.91031	.0000	.0000	.0000
AM241	CM242	0.00000	0.00000	.00000	.00000	125.54216	.0000	.0000	.0000
AM243	CM244	0.00000	0.00000	.00000	.00000	782.02304	.0000	.0000	.0000
AM242M	AM243	0.00000	0.00000	.00000	.00000	.25000	.0000	.0000	.0000
CM242	CM243	0.00000	0.00000	.00000	.00000	.39682	.0000	.0000	.0000
CM243	CM244	0.00000	0.00000	.00000	.00000	.00000	.0000	.0000	.0000
CM244		0.00000	0.00000	.00000	.00000	.00000	.0000	.0000	.0000
PU238	PU239W	0.00000	0.00000	.00000	.00000	29.75841	.0000	.0000	.0000
FISSEION PRODUCTS									

POISON	6.0235-02	FPA	0.0000	FPB	0.0000	FPC	0.0000	XE135	-0.0000	SM149	-0.0000
SM131	0.0000										
TIME/MEAT	1.46843-02	1.46843-02	287.650	1.00000	.96820	1.92307	.00130	.00031	11.87715	.0000	.0000
0.00000	5.60500-11	1.01520+00	.004	1.00000	.00389	1.02668	.00130	.25036	.97992	.0002	.0000

U233 = 6.8535-16	U233W = 1.3247-16	PU235W = 6.7841-11	PU241Z = 5.3500-17	TU232 = 0.0000	U238 = 0.0000
U234 = 6.3590-13	PU240 = 5.8113-14	PA233 = 5.4783-14	U236 = 2.0214-20	PU242 = 0.0000	NP237 = 6.2545-05
AM241 = 0.0000	AM243 = 0.0000	AM242M = 0.0000	CM242 = 0.0000	CM243 = 0.0000	CM244 = 0.0000
PU233 = 5.9623-08	POISON = 6.0235-02	FPA = -2.9457-15	FPB = 2.1533-14	FpC = 9.0861-14	XE135 = 1.3560-15
SM149 = 1.0308-14	SM151 = 5.9111-14				

TIME/REACT	POW/THI	PRR/PRY	INVT/HA	PMQV/PRIV	HIQ/0	FFF/DIS	XMLT/AMLT	2TAYJ	EPSX0	CR/ABSOR	CAB/FRAB
8.63990+04	1.50141-02	1.53439-02	287.660	1.02197	.96820	1.92307	.00136	.00056	7.06071	*****	.0000
1.50139-02	5.67903-11	1.01520-10	.705	.997803	.93359	1.02672	.00133	.23063	.97993	.0502	.0000

BURN-UP OF REGION 4 IDENTIFIED AS 1384K COMPLETED.

DIFFUSION-1 OUTPUT AT 8.6397+04 SECONDS, POWER BASED ON OLD FLUX IS 5.9655+03

REACTIVITY WITH CONTROL RODS WITHDRAWN IS 1.09175

FLUX REDUCED BY A FACTOR OF 1.209 DUE TO POWER PEAK IN REGION 2

REGION	RADIUS	POWER	FLUX	PERCENT CHANGE	RE	PERCENT CHANGE	RS	PERCENT CHANGE	RF	PERCENT CHANGE	SNFD	PERCENT CONTROL
1	4.44	.00	2.963-11	-11.15	.0522	-.17	.0588	-.24	.0000	-.00	.0000	-.00
2	11.01	.00	3.668-11	-8.94	.0487	-.30	.0573	-.22	.0000	-.00	.0000	-.00
3	17.91	.00	3.698-11	-8.99	.0397	-.18	.0426	-.16	.0000	-.00	.0000	-.00
4	22.50	.00	5.141-11	-9.02	.0328	-.13	.0338	-.13	.0000	-.00	.0000	-.00
5	26.94	.00	4.360-11	-9.03	.0313	-.12	.0318	-.12	.0000	-.00	.0000	-.00

nORMALIZED DIFFUSION FLUXES BY MESH PoIfiT

9.695	*	ES	F
9.917	*	ES	F
10.139	*	E	T
10.361	*		
10.583	*	E	T
10.805	*		
11.027	*	-E	P
11.250	*		
11.472	*	E	F
11.694	*		
11.916	*	E	T
12.138	*		
12.360	*	E	F
12.582	*		
12.804	*	E	F
13.026	*		
13.248	*	E	F
13.470	*		
13.692	*	C	F
13.915	*		
14.131	*	E	L
14.359	*	ES	F
14.581	*	ES	F
14.803	*	ES	F
15.025	*	ES	F
15.247	*	ES	F
15.469	*	ES	F
15.691	*	ES	F
15.913	*	ES	F
16.135	*	ES	F
16.357	*	ES	F
16.579	*	ES	F
16.802	*	ES	F
17.024	*	ES	F
17.246	*	ES	F
17.468	*		
17.690	*	E	F
17.912	*		
18.131	*	E	T
18.371	*		
18.609	*	E	P
18.829	*		
19.059	*	E	F
19.288	*		
19.511	*	L	F
19.747	*		
19.978	*	E	F
20.206	*		
20.435	*	E	F
20.664	*		
20.894	*	E	F
21.123	*	E	F

KPR ALT-TUBE NP237-AL TARGET

CONTROL CONSTANTS

N11	N12	N13	N14	N15	N16	N17	N18	N19	POWER	RMULT	CLOSE	RAD
-0	-0	-0	-0	-0	-0	-0	-0	-0	4.4000+03	-0.0000	1.0000+03	-0.0000
N21	N22	N23	N24	N25	N26	N27	N28	N29	BMULT	HL	E-AE	TMAX
1	1	1	4	1	-0	4	99	-0	-1.0000+00	1.0000+05	-0.0000	8.6400+04
N31	N32	N33	N34	N35	N36	N37	N38	N39	3MULT1	BMULT2	BMULT3	BMULT4
-0	-0	-0	-0	-0	-0	-0	-0	-0	0.0000	a.Bu60	0.0000	0.0000
N41	N42	N43	N44	N45	N46	N47	N48	N49	TSLIM	ERL	ERU	HI
0	0	-0	20	-0	-0	4	-0	3	2.0000+06	2.0000-02	5.0000-02	8.6400+04
N51	N52	N53	N54	N55	N56	N57	N58	N59	CMULT	CMATCH	PERFIS	TOT
-0	-0	0	0	-0	0	-0	0	0	9.0000	9.9086	2.0250 02	4.7840 92
N61	N62	N63	N64	N65	N66	N67	N68	N69	RAYK1	RAYK2	RAYK3	GSHLD
1	3	2	-0	-0	-0	-0	-0	-0	7.6700-01	2.0000-01	2.5570+00	6.7500-02
NPASS	N72	N73	N74	N75	N76	N77	N78	N79	PERLOS	DOAYS	OEXP	PERLS
-0	-0	0	0	-0	0	-0	0	0	0.0000	0.0000	0.8000	0.0000

INPUT ISOTOPIC CONCENTRATIONS

NSTEP	IOERT	NFS	Ie1	IC2	IC3	IC5	IC6	IC7	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F
1	1401K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000
IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	IF11	IF12	IF13	IF14	IF15	IF16
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST=	0.0000	FEXP=	0.0000	TEMP=	0.0000	SPEC=	2.4120-03	TNL=	1.0000+00	TMOD=	5.5980+02	IE=	-0		
AORI=	3.6799+01	SCA=	0.0000	PWT=	3.0000-11	DENS=	0.0000	E=	0.0000	XK=	1.6021+11	JMP=	-0		
	2.7940-04	NFS3=	1.7110-06	NFS2=	-0.0000	NFS1=	-0.0000	GAM1=	-0.0000	GAM2=	-0.0000	NBP=	-0		
S12=	3.2950-02	S23=	6.0860-02	S34=	6.1520-02	S13=	-0.0000	S14=	-0.0000	S24=	0.0000	KEY=	-1		
S12=	-0.0000	S23=	-0.0000	S34=	-0.0000	S13=	-0.0000	S14=	-0.0000	S24=	-0.0000	KEY=	-0		
S51=	1.9520-01	S52=	3.6110-01	S53=	3.6520-01	S54=	3.6520-01	SAWO=	2.0000-01	VR=	1.0000+00	KOUT=	-1		
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	0.0000	SSL4=	-0.0000	SHFL=	-6.0000	PWMX=	3.0000+02	KF=	-0		
CONV=	1.0000-03	BUCK=	2.4800-05	pF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	WIDTH=	2.2208-01	KP=	-20		

BURRUP OF REGION 1 IDENTIFIED AS 14QIK COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

U235W 9.68806-04 U238 4.68731-02

NSTEP	IOENT	NFS	rel	IC2	IC3	IC5	ICo	IC?	Ica	ICg	Iel0	IC12	PERIOD	M/F		
1	1402K	-0	-0	-3	-0	-0	-0	-0	-0	-0	-0	-0	1.0	11.470		
ID1	102	ID3	ID4	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST=	2.5520+00	FEXP=	1.2760+00	TEMP=	3.4980+02	SPEC=	2.2690-01	TNL=	1.0000+00	TMOO=	-2.8765+02	IE=	-0			
HORI=	3.6799+07	SCA=	1.0000+00	PwI=	3.0000-11	DENS=	1.8YCO+01	E=	1.1920+00	XK=	1.6021+11	JRP=	-0			
SNF=	1.9550-02	NFS3=	-0.0000	NFS2=	4.0g90-01	tIFS1=	5.0780-02	GAM1=	0.0000	GAM2=	0.0000	NBP=	-0			
S12=	4.2510-02	S23=	9.8400-02	S34=	8.3120-02	S13=	-0.0000	S14=	-0.0000	S24=	1.6190-01	KEY=	-0			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
S51=	1.9260-01	S52=	4.2060-01	S53=	3.7650-01	S54=	3.8430-01	SAWD=	2.0000-01	VR=	7.1870-02	KOUT=	-1			
SSC1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0			
CONV=	1.0000-03	BUCK=	2.4800-J5	pF=	8.7407-01	CLIM=	1.0000-02	ACNTRL=	1.0000+00	WIDTH=	2.2936-01	KP=	20			

BURN-UP OF REGION 2 IDENTIFIED AS 1402K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

NSTEP	IOENT	NFS	IC1	IC2	IC3	IC4	IC5	IC6	IC?	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F
1	1403K	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000
ID1	102	ID3	ID4	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0
FCONST=	0.0000	FEXP=	0.0000	TEMP=	0.0000	SPEC=	2.7120-03	TNL=	1.0000+00	TMOO=	5.5900+02	IE=	-0			
HORI=	3.6799+07	seA=	0.0000	PwI=	3.0000-11	DENS=	0.0000	E=	0.0000	XK=	1.6021+11	JMP=	-0			
SNF=	2.7940-04	NFS3=	1.1110-J6	NFS2=	-0.0000	AFSI=	-0.0000	GAM1=	-0.0000	GAM2=	-0.0000	H6P=	-0			
S12=	1.2450-02	S23=	8.0600-02	S34=	8.1520-02	S13=	-0.0000	S14=	-0.0000	S24=	0.0000	KEY=	-1			
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KIND=	-0			
S51=	1.9320-01	S52=	3.6110-01	S53=	3.6520-01	S54=	3.6520-01	SAWD=	2.0000-01	VR=	1.0000+00	KOUT=	-1			
sSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0			
CONV=	1.0000-03	BOCK=	2.4800-J5	pF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	WIDTH=	2.2208-01	KP=	40			

BURN-UP OF REGION 3 IDENTIFIED AS 1403K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

NP237 6.26050-05 POISON 6.02348-02

NSTEP	IOENT	NFS	Ie1	Ie2	IC3	Ie5	ICo	IC7	Ie8	IC10	IC11	IC12	PERIOD	M/F	
1	1404K	-0	-0	-0	-0	-0	-0	-0	0	0	-0	-0	6	1.0	11.470

ID1	ID2	ID3	ID4	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0

FCONST=	7.4210+00	FEXP=	3.7110+00	TEMP=	1.2684+02	SPEC=	2.1470-02	TNL=	1.0000+00	TMOD=	-2.8765+02	IE=	-0
HORT=	3.6799+07	SCA=	4.8930-01	PwI=	3.6088-11	DENS=	2.7230+00	E=	1.1707+00	XK=	1.6021+11	JMP=	0
SNF=	3.6620-02	r,FS3=	-0.0000	NFS2=		r,JFsl=	5.2350-02	GAMI=	0.0000	GAM2=	0.0000	Nap=	-0

S12=	4.1260-02	S23=	1.0010-01	S34=	8.5660-02	S13=	-0.0000	S14=	-0.0000	S24=	1.7580-01	KEY=	-0
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KINO=	-0
55t=	1.9160-01	552=	3.5520-01	SS3=	3.5760-01	554=	3.6850-01	5AWD=	2.0000-01	VR=	7.1870-02	KOUT=	-1
SSL1=	-0.0000	SSL2=	swcses	SSL3=	0.0000	SSL4=	0.0000	SNFL=	0.0000	PWMX=	3.0000+02	KF=	9
CONV=	1.0000-03	BUCK=	2.4800-05	pF=	1.2593-01	CLIM=	1.0000-02	ACNTRL=	0.0000	wIDTH=	2.2936-01	KP=	20

BURU-UP OF REGION 4 IDENTIFIED AS 1404K COMPLETED.

INPUT ISOTOPIC CONCENTRATIONS

NSTEP	IOENT	NFS	Ie1	Ie2	IC3	Ie4	IC5	IC6	IC7	IC8	IC9	IC10	IC11	IC12	PERIOD	M/F
1	140SK	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	1.0	.000

ID1	ID2	ID3	ID4	IF1	IF2	IF3	IF4	IF5	IF6	IF7	IF8	IF9	IF10	MSTEP	TIMEDR	DEL
-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0	-0

FCONST=	0.0000	FEXP=	0.0000	TEMP=	0.0000	SPEC=	2.4120-03	TNL=	1.0000+00	TMOD=	0.5980+02	IE=	-0
HORT=	3.6799+07	seA=	0.0000	PwI=	3.0000-11	DENS=	0.0000	E=	9.0000	XK=	1.6021+11	JMP=	-0
SNF=	2.940-04	r,FS3=	1.7110-06	NFS2=	-0.0000	r,JFsl=	-0.0006	GAMI=	0.0010	GAM2=	0.0000	NBP=	0

S12=	-0.0000	S23=	-0.0000	S34=	-0.0000	S13=	-0.0000	S14=	-0.0000	S24=	0.0000	KEY=	-1
SL12=	-0.0000	SL23=	-0.0000	SL34=	-0.0000	SL13=	-0.0000	SL14=	-0.0000	SL24=	-0.0000	KINO=	-0
55t=	1.9510-01	552=	3.5110-01	SS3=	3.5520-01	554=	3.6520-01	5AWD=	2.0000-01	VR=	1.0000+00	KOUT=	-1
SSL1=	-0.0000	SSL2=	-0.0000	SSL3=	-0.0000	SSL4=	-0.0000	SNFL=	-0.0000	PWMX=	3.0000+02	KF=	-0
CONV=	1.6000-03	BUCK=	2.4800-05	pF=	0.0000	CLIM=	1.0000-02	ACNTRL=	-0.0000	wIDTH=	2.2288-01	KP=	20

BURU-UP OF REGION 5 IDENTIFIED AS 140SK COMPLETED.

DIFFUSION OUTPUT AT 0.0000 SECONDS. POWER BASED ON OLD FLUX IS 2.5637+03

FINAL REACTIVITY FOR EACH CONTROL ITERATION WAS
 .99999980

REACTIVITY WITH CONTROL DONE WITH PROGRAM IS 1.16450

FLUX REDUCED BY A FACTOR OF 1.200 DUE TO POWER PEAK IN REGION 2

REGION	RADIUS	POWER	FLUX	PERCENT CHANGE	PERCENT CHANGE	RS	PERCENT CHANGE	RE	PERCENT CHANGE	SNED	PERCENT CONTROL
1	4.44	1.77	3.19E+11	2.04	.0505	.0608	.0635	.0000	-1.00	.0000	-1.00
2	9.03	300.00	3.54E+11	15.29	.0539	.0644	-252.37	.2140	-26.38	.1189	14.42
3	11.91	.00	3.67E+11	10.42	.0432	.0465	94.82	.0000	1.00	.0000	-1.00
4	22.50	.04	5.19E+11	42.30	.0352	.0364	40.99	.0702	64.21	.0000	-1.00
5	26.90	.20	5.42E+11	32.19	.0335	.0424	42.72	.0000	-1.00	.0000	-1.00

@ 1.423 w/ 235
 11

NORMALIZED DIFFUSION FLUXES BY MESH POINT

RADIUS	10	20	30	40	50	60	70	80	90	100
0.000	ES	F					T			*
0.222	ES	F					T			*
0.444	ES	F					T			*
0.666	ES	F					T			*
0.888	ES	F					T			*
1.110	ES	F					T			*
1.332	ES	F					T			*
1.555	ES	F					T			*
1.777	ES	F					T			*
1.999	ES	F					T			*
2.221	ES	F					T			*
2.443	ES	F					T			*
2.665	ES	F					T			*
2.887										*
3.109	E	F					T			*
3.331										*
3.553	E	F					T			*
3.775										*
3.997										*
4.219										*
4.442	E	F					T			*
4.671										*
4.900	E	F					T			*
5.130										*
5.359	E	F								*
5.588										*
5.814	E	F					T			*
6.047										*
6.276	E	F					T			*
6.506										*
6.735										*
6.965										*
7.194	E	F					T			*
7.423										*
7.653	E	F					T			*
7.882										*
8.111	E	F					T			*
8.341										*
8.570	E	F					T			*
8.799										*
9.029	F	F					T			*
9.251										*
9.473	E									*
9.695	F	F								*

9.895	*	F				*
9.917	*					*
10.139	*	E	F		T	*
10.361	*					*
10.583	*	E	F		T	*
10.805	*					*
11.028	*	E	F		T	*
11.250	*					*
11.472	*	E	F			*
11.694	*					*
11.916	*	E	F		T	*
12.138	*					*
12.360	*	E	F		T	*
12.582	*					*
12.804	*	E	F		T	*
13.026	*					*
13.248	*	E	F		T	*
13.470	*					*
13.692	*	E	F		T	*
13.915	*					*
14.137	*	E	F			*
14.359	*					*
14.581	*	E	F		T	*
14.803	*					*
15.025	*	E	F		T	*
15.247	*					*
15.469	*	E	F		T	*
15.691	*					*
15.913	*	E	F		T	*
16.135	*					*
16.357	*	E	F			*
16.579	*					*
16.802	*	E	F		T	*
17.024	*					*
17.246	*	E	F		T	*
17.468	*					*
17.690	*	E	F		T	*
17.912	*					*
18.141	*	E	F			*
18.371	*					*
18.601	*	E	F		T	*
18.829	*					*
19.059	*	E	F		T	*
19.288	*					*
19.511	*	E	F		T	*
19.747	*					*
19.976	*	ES	F		T	*
20.206	*	ES	F		T	*
20.435	*	ES	F		T	*
20.664	*	ES	F		T	*
20.893	*	ES	F		T	*

21.123	*	ES F	T	*
21.352	*	ES F	T	*
21.582	*	ES F	T	*
21.811	*	ES F	T	*
22.040	*	ES F	T	*
22.270	*	ES F	T	*
22.499	*	ES F	T	*
22.721	*	ES F	T	*
22.943	*	(SF	T	*
23.165	*	ESF	T	*
23.387	*	ESF	T	*
23.610	*	ESF	T	*
23.832	*	E-5F	T	*
24.054	*	ESF	T	*
24.276	*	ESF	T	*
24.498	*	ESF	T	*
24.720	*	ESF	T	*
24.942	*	ESF	T	*
25.164	*	ESF	T	*
25.386	*	ESF	T	*
25.608	*	ESF	T	*
25.830	*	ESF	T	*
26.052	r	E5F	T	*
26.274	*	ESF	T	*
26.497	*	ESF	T	*
26.719	*	ESF	T	*
26.941	*	ESF	T	*
RADIUS	0			
	10			
	20			
	30			
	40			
	50			
	60			
	70			
	80			
	90			
	100			

BOUND OF REGION IDENTIFIED AS 100% COMPLETE.

ISOTOPE	ABSORPTION PERCENT REACTION RATE IN GROUP					FISSION PERCENT REACTION RATE IN GROUP					N2N
	CROSS SECTION	THERM	DEPTH	SLOWING	FAST	CROSS SECTION	THERM	DEPTH	SLOWING	FAST	
U233W	3.98835+02	73.80	4.41	20.77	.59	3.58664+02	75.12	5.08	19.13	.62	
U235W	3.68633+02	88.64	4.45	6.49	.42	3.07167+02	90.18	4.47	4.90	.46	
PU239W	1.06029+03	16.14	19.52	4.13	.20	7.04525+02	77.93	18.00	5.76	.30	
PU241Z	1.01587+03	83.96	9.74	6.10	.21	7.60236+02	84.30	8.62	6.82	.26	
U232	1.23982+01	36.60	1.86	56.71	.53	6.69772+02	.00	.00	.00	100.00	
U238	3.18464+00	44.18	2.84	41.38	11.60	2.64752+01	.00	.00	.00	100.00	1.29543-02
U234	1.24575+01	47.47	2.49	56.02	.03	1.24177+00	2.48	.15	5.34	92.03	
PU240	1.00666+03	15.88	2.13	81.85	.14	1.52194+00	2.35	.25	17.53	79.87	
PA233	1.07756+02	21.0A	1.58	77.27	.07						
U236	4.13232+01	6.56	.33	91.39	1.72	4.96679+01	.00	.00	.00	100.00	
PU242	1.28885+02	9.57	.59	86.80	1.04	1.32693+00	.73	.05	7.81	91.61	
NP237	1.53642+02	58.91	12.32	21.98	.79	1.10961+00	.89	.10	.50	98.52	
AM241	5.78037+02	30.28	22.80	16.80	.14	4.79772+00	49.34	19.92	12.75	17.99	
AM243	2.11833+02	28.12	1.23	70.18	.47	8.77035+01	.00	.00	.03	99.97	
AM242W	4.65747+03	88.02	5.36	6.59	.03	3.72600+03	83.02	5.36	6.60	.03	
CM242	1.16473+01	88.02	5.36	6.59	.03						
CM243	5.12533+02	58.92	5.36	6.59	.03	3.36971+02	83.02	5.36	6.60	.13	
CM244	7.36558+01	10.52	.67	86.78	2.03	2.08557+00	24.58	3.04	1.85	70.53	
PU238B	2.84833+02	71.23	3.94	4.50	.93	1.22072+01	63.81	2.05	14.25	20.88	
POISON	-0.00000	88.99	11.01	.00	.00						
EPA	4.65936+02	aB.D!	5.36	6.60	.03						
F23	5.92479+02	25.96	3.21	70.82	.01						
FFC	4.01282+01	61.78	3.88	32.32	.02						
XE135	1.64524+06	99.15	.83	.02	.00						
SM149	4.77233+04	98.73	.42	.05	.03						
SM151	8.97176+03	85.74	5.24	9.01	.00						

ISOTOPE	DESCENDANT	CONCENTRATION	DESTROYED	ABS	ARSAV	ALPHA	HEAT	CONV.
U233W	U234	-0.00000	0.00000	.00000	.00000	.11760	.0000	.0000
U235W	U236	-9.68806-04	0.00000	.35713	.35713	.20010	95.7508	95.7508
PU239W	PU240	-0.00000	0.00000	.00000	.00000	.50497	.0000	.0000
PU241Z	PU242	0.00000	0.00000	.00000	.00000	.33625	.0000	.6000
TH232	PA233	-0.00000	0.00000	.00000	.00000	184.11072	.0000	.0000
U238	PU239W	-4.68731-02	0.00000	.14927	.14927	11.02877	4.0032	4.0032
U234	U235W	-0.00000	0.00000	.00000	.00000	96.09995	.0000	.0000
PU240	PU241Z	0.00000	0.00000	.00000	.00000	660.43369	.0000	.0000
PA233	U234	0.00000	0.00000	.00000	.00000			
U236	PU237	9.68806	0.00000	.00000	.00000	82.12984	.0000	.8e39
PU242	AM243	0.00000	0.00000	.00000	.00000	95.96390	.0000	.0000
MP237	PU238	0.00000	0.00000	.00000	.00000	137.46531	.0000	.0000
AM241	CM242	0.00000	0.00000	.00000	.00000	108.09430	.0000	.0000
AM243	CM244	0.00000	0.00000	.00000	.00000	240.53270	.0000	.0000
AM242M	AM243	0.00000	0.00000	.00000	.00000	.24999	.0000	.0000
CM242	CM243	0.00000	0.00000	.00000	.00000			
CM243	CM244	0.00000	0.00000	.00000	.00000	.39681	.0000	.0000
CM244		0.00000	0.00000	.00000	.00000	.00000	.0000	.0000
PU238	PU239W	0.00000	0.00000	.00000	.00000	22.33326	.0000	.0000
FISSIOM PRODUCTS				.01993	.01993			

POISON = 0.0000	FPA = 0.0000	FP8 = 0.0000	FPC = 0.0000	XE135 = 8.5795-09	SM149 = 8.7102-08						

SM151 = 1.8510-07											

TIME/HEAT	PAV/PHI	PWR/WLAT	THEUT/WA	PMXV/PMNV	RIO/R	FFF/DIS	XMLT/AMLT	ZTAR/J	EPS/0	CR/ABSOR	CAB/FRA
0.00000	1.86126+01	1.86126+01	282.377	1.00000	.83709	3.32358	1.38436	1.69040	1.02540	38.3230	.0000
0.00000	5.54165-11	1.01520+00	61.999	1.00000	.06439	1.81468	1.38436	.91293	.88305	.5476	24.9922

U234	= 5.4207-21	U235	= 2.1771-04	PU236	= 4.1812-07	PU242	= 2.3314-13	U232	= 0.0000	U238	= 4.8073-02
U234	= 3.0901-18	PU240	= 2.2747-10	PA233	= 8.2005-19	U236	= 1.8210-07	PU242	= 4.5702-17	NP237	= 1.8690-09
AM241	= 8.3997-18	AM243	= 0.0000	AM242	= 0.0000	CM242	= 0.0000	CM243	= 0.0000	CM244	= 0.0000
PU238	= 4.3518-13	POISON	= 0.0000	FPA	= -8.0683-09	FPB	= 1.1337-07	FPC	= 6.6557-07	XE135	= 8.5826-09
SM149	= 8.1069-08	SM151	= 1.8527-07								

AORF-OP OF REGION 2 IDENTIFIED As 1402K COMPLETED.

2 of 2

	ABSORPTION	PERCENT	REACTION	RATE	IN	GROUP	FISSION	PERCENT	REACTION	RATE	IN	GROUP	N2N
ISOTOPE	CROSS-SECTION	TERM	ENTR	SLOWING	FAST	CROSS-SECTION	TERM	ENTR	SLOWING	FAST	CROSS-SECTION		
U233W	5.95848+02	29.87	2.13	7.87	.13	5.37020+02	98.48	2.13	7.87	.14			
U235W	6.28053+02	94.58	1.94	3.40	.08	5.27569+02	95.44	1.93	2.55	.09			
PU239W	1.64504+03	90.22	8.22	1.51	.04	1.10611+03	91.09	7.49	1.30	.66			
PU241Z	1.66032+03	93.97	3.87	2.12	.04	1.24380+03	94.16	3.42	2.37	.05			
Th232	1.17788+01	58.67	1.23	10.57	.53	2.25835+02	.00	.00	.00	100.00			
U238	1.85962+01	13.77	.32	85.26	.65	8.72931-02	.00	.00	.00	100.00	4.27125-03		
U234	1.30518+02	88.10	1.45	10.00	.31	4.71747-01	11.09	.25	7.98	79.87			
PU240	7.84733+02	37.15	1.78	61.01	.06	6.19681-01	10.48	.41	24.44	64.68			
Pa233	8.97412+01	46.95	1.23	52.60	.03								
U236	2.66904+01	18.44	.33	80.35	.88	1.63763-01	.00	.00	.00	100.00			
PU242	9.81115+01	25.28	.56	73.64	.52	4.78153-01	3.70	.08	12.04	84.18			
Np237	1.99185+02	82.81	8.31	8.67	.20	3.81781-01	4.68	.17	.74	94.41			
Am241	9.19982+02	81.87	11.04	7.05	.01	5.81124+00	77.59	11.15	6.10	5.87			
Am243	1.94298+02	55.51	.88	43.45	.17	2.89244-01	.00	.00	.06	99.94			
Am242m	7.79799+03	95.68	2.08	2.24	.81	6.23840+03	95.68	2.98	2.24	.91			
Cm242	1.95011+01	95.68	2.08	2.24	.01								
Cm243	4.58115+03	95.68	2.08	2.24	.81	6.14336+02	95.68	2.08	2.24	.81			
C1244	5.12184+01	27.55	.63	70.86	.96	1.48129+00	62.98	2.79	1.48	32.74			
U238	9.81115+02	25.28	1.12	1.63	.18	1.57213+01	87.50	1.02	8.21	5.28			
POISON	-0.00000	95.75	4.25	.00	.00								
FPA	7.80101+02	95.68	2.08	2.24	.61								
Fp3	5.30618+02	52.75	2.34	44.91	.00								
FpC	3.50410+01	84.75	1.84	13.70	.01								
XE135	2.97640+06	99.70	.30	.01	.00								
Sq149	3.58787+04	99.58	.22	.22	.00								
SM151	1.47664+04	94.82	2.07	3.11	.00								

ISOTOPE	DESCENDANT	CONCENTRATION	DESTROYED	ASS	ABSAV	ALPHA	HEAr	POWER	CONV.
U233W	U234	-0.00000	0.00000	.00000	.00000	.10552	.0000	.0000	.0000
U235W	U236	-0.00000	0.00000	.00000	.00000	.10947	.0000	.0000	.0000
PU239W	PU240	-0.00000	0.00000	.00000	.00000	.48723	.0000	.0000	.0000
P02412	PU242	-0.00000	0.00000	.00000	.00000	.33437	.0000	.0000	.0000
TH232	PA233	-0.00000	0.00000	.00000	.00000	531.75567	.0000	.0000	.0000
U233	U234W	-0.00000	0.00000	.00000	.00000	212.03232	.0000	.0000	.0000
U234	U235W	-0.00000	0.00000	.00000	.00000	275.45575	.0000	.0000	.0000
PU240	PU241Z	-0.00000	0.00000	.00000	.00000	1263.34900	.0000	.0000	.0000
PA233	U234	0.00000	0.00000	.00000	.00000				
U236	NP237	0.00000	0.00000	.00000	.00000	161.98157	.0000	.0000	.0000
PU242	AM243	0.00000	0.00000	.00000	.00000	184.04822	.0000	.0000	.0000
NP237	PU238	0.00000-05	0.00000	.00000	.00000	320.72733	100.0000	100.0000	.0000
AM241	CM242	0.00000	0.00000	.00000	.00000	125.12848	.0000	.0000	.0000
AM243	CM244	0.00000	0.00000	.00000	.00000	275.74331	.0000	.0000	.0000
AM242M	AM243	0.00000	0.00000	.00000	.00000	.25000	.0000	.0000	.0000
CM242	CM243	0.00000	0.00000	.00000	.00000				
CM243	CM244	0.00000	0.00000	.00000	.00000	.39632	.0000	.0000	.0000
CM244		0.00000	0.00000	.00000	.00000	.90000	.0000	.0000	.0000
PU238	PU239W	0.00000	0.00000	.00000	.00000	29.54240	.0000	.0000	.0000
F1531000 PRODUCTS									

POISON = 6.0235-02 FPA = 0.0000 FPB = 0.0000 FPC = 0.0000 Xe135 = -0.0000 SM149 = -0.0000
SM151 = -0.0000

TIME/HEAT	FACTOR	PERCENTAGE	THEORY/MAX	PERCENTAGE	RIC/R	FFF/DIS	XMULT/MULT	ZTA/J	FPS/B	CR/ABSOR	CAB/FRAG
0.00000	1.46218-02	1.46218-n2	287.650	1.00000	.96731	1.93038	.00139	.00031	12.62094	.0000	.0000
0.00000	5.19898-11	1.01520+00	.005	1.00000	.03638	1.02663	.00139	.23055	.97853	.0504	.0000

U234 = 5.9531-13 PU240 = 4.7489-14 PA233 = 5.4785-14 U236 = 186604-20 PU242 = 0.0000 NP237 = 6.2549-05
AM241 = 0.0000 AM243 = 0.0000 AM242M = 0.0000 CM242 = 0.0000 CM243 = 0.0000 CM244 = 0.0000
PU238 = 5.5820-08 POISON = 6.6235-02 EPA = -2.3783-t5 FPB = 1.7384-14 FpC = 7.8196-14 XE135 = 1.1731-15
SM14Y = 1.4234-14 SM151 = 5.1472-14

TIME/HEAT-----PRV/HHI-----PRR/HHOT-----THEUT/HHI-PMV/PMNY-----R10/R--FPP/O13--XMBT/1M1T--ZTAPJ-----CP570-----CR/MSOR-CA8/F100-----
8.63990+04 1.49079-C2 1.51939-02 287.660 1.01919 .96731 1.93038 .00145 .00054 7.69637***** .0000
-----1.59077-52-----2.15098-11-----1.01523+00 .005 .98081-----03638--1.02672-----00142-----23081-----9785-----10504-----0000-----

BURN UP OF REGION 4 IDENTIFIED AS 14u4K COMPLETED.

DIFFUSION OUTPUT AT 8.639e+04 SECONDS. POWER BASED ON OLD FLUX IS 4.2671+03

REACTIVITY WITH CONTROL RODS WITHDRAWN IS 1.17e-61

FLUX REDUCED BY A FACTOR OF 1.239 DUE TO POWER PEAK IN REGION 2

REG10r.j	RADIUS	POWER	FLUX	PERCENT CHANGE	RE	PERCENT CHANGE	RS	PERCENT CHANGE	RF	PERCENT CHANGE	SNFD	PERCENT CONTROL
1	4.44	.00	2.440-11	-19.60	.0579	-.24	.0658	-.33	.0000	-.00	.0000	-.00
2	9.13	.00	3.721-11	-17.23	.0537	-.37	.0642	-.31	.2134	-.30	.0000	-.00
3	11.91	.00	3.135-11	-17.30	.0430	-.23	.0464	-.22	.0000	-.00	.0000	-.00
4	22.30	.00	4.433-11	-17.36	.0351	-.18	.0363	-.17	.0701	-.17	.0000	-.00
5	26.94	.00	3.770-11	-17.37	.0335	-.17	.0340	-.16	.0000	-.00	.0000	-.00

NORMALIZED DIFFUSION FLUXES BY MESH POINT

RADIUS		10	20	30	40	50	60	70	80	90	100
0.000	ES	E						T			*
0.222	ES	F						T			*
0.444	ES	F						T			*
0.666	ES	F						T			*
0.889	ES	F						T			*
1.110	ES	F						T			*
1.332	ES	F						T			*
1.555	ES	F						T			*
1.777	ES	F						T			*
1.999	ES	F						T			*
2.221	ES	F						T			*
2.443	ES	F						T			*
2.665	E							T			*
2.887	E							T			*
3.109	E	F						T			*
3.331	E	F						T			*
3.553	E	F						T			*
3.775	E	F						T			*
3.997	E	F						T			*
4.219	E	F						T			*
4.442	E	F						T			*
4.671	E	F						T			*
4.900	E	F						T			*
5.130	E	F						T			*
5.359	E	F						T			*
5.588	E	F						T			*
5.818	E	F						T			*
6.047	E	F						T			*
6.278	E	F						T			*
6.506	E	F						T			*
6.735	E	F						T			*
6.965	E	F						T			*
7.194	E	F						T			*
7.423	E	F						T			*
7.653	E	F						T			*
7.882	E	F						T			*
8.111	E	F						T			*
8.341	E	F						T			*
8.570	E	F						T			*
8.799	E	F						T			*
9.029	E	F						T			*
9.251	E	F						T			*
9.473	E	F						T			*

9.695	*	E	F							*
9.917	*									*
10.139	*	E	F							*
10.361	*									*
10.583	*	E	F						T	*
10.805	*									*
11.028	*	E	F						T	*
11.250	*									*
11.472	*	E	F							*
11.694	*									*
11.916	*	E	F						T	*
12.138	*									*
12.360	*	E	F						T	*
12.582	*									*
12.804	*	E	F						T	*
13.026	*									*
13.248	*	E	F						T	*
13.470	*									*
13.692	*	E	F						T	*
13.915	*									*
14.137	*	E	F							*
14.359	*									*
14.581	*	E	F						T	*
14.803	*									*
15.025	*	E	F						T	*
15.247	*									*
15.469	*	E	F						T	*
15.691	*									*
15.913	*	E	F						T	*
16.135	*									*
16.357	*	E	F						T	*
16.579	*									*
16.802.1	*	E	F						T	*
17.024	*									*
17.246	*	E	F						T	*
17.468	*									*
17.690	*	E	F						T	*
17.912	*	E	F						T	*
18.141	*	E	F						T	*
18.371	*	E	F						T	*
18.600	*	E	F						T	*
18.829	*	E	F						T	*
19.059	*	E	F						T	*
19.288	*									*
19.517	*	E	F							*
19.747	*	ES	F						T	*
19.976	*	ES	F						T	*
20.206	*	ES	F						T	*
20.435	*	ES	F						T	*
20.664	*	ES	F						T	*
20.894	*	ES	F						T	*

.....BEGIN EDITTING OF BURNUP INFORMATION. START TIME = 34.377 SECONDS
.....
.....EDIT PROCESSED 16 RECORDS. FINISH TIME = 34.680 SECONDS ..
.....
.....TOTAL TIME303 SECONDS

.....TOTAL COMPUTATION TIME 34.685 SECONDS OR57808 MINUTES.

.....NEXT LINE = 99

.....CALLING EX1.....

.....TOTAL COMPUTATION TIME 34.690 SECONDS OR57817 MINUTES.

alii

Association for Information and Image Management
 1100 Washington Avenue, Suite 1100
 Silver Spring, Maryland 20910
 301/587-8202

Centimeter

Inches

MANUFACTURED TO AIIM STANDARDS
 BY APPLIED IMAGE, INC.

DATE

LMED

12/19/94

END