**Neutron Cross Section Measurements
Using the Oak Ridge Electron
Linear Accelerator**

**Performance Report
August 1991 - June 1992**

06/28/92

**R. R. Winters
Principal Investigator
Department of Physics
Denison University
Granville, OH 43023**

**J. Leslie Hicks, Jr.
Vice President for Finance
and Management
Denison University
Granville, OH 43023**

June 1992

Prepared for the Department of Energy

DOE Grant No. DE-FG02-87ER40326.A005

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed or represents that its use would not infringe privately-owned rights.

ABSTRACT

During this reporting period the work supported by the U.S. Department of Energy Grant No. DE-FG02-87ER40326.A005 has resulted in two publications [Phys. Rev. C 44, 657 (1991) and Astrophys. J. Supp. 80, 403 (1992)] and two papers presented at professional meetings. The neutron scattering measurement for this budget period has been completed along with scattering measurements for carbon and ^{28}Si . The carbon scattering yield serves to define the detector efficiencies. The silicon sample was available and is of importance in both nuclear physics and reactor physics.

PERFORMANCE REPORT

Introduction

Except for the unanticipated ^{28}Si scattering cross section measurement, this report will closely follow the outline of work proposed for this and the previous budget periods. Emphasis will be placed on the completed or nearly completed work.

I. A Dispersive Optical Model for $n + ^{40}\text{Ar}$

Status: 100% completed.

Publication: "Evidence for parity dependence in the neutron- ^{40}Ar optical model potential", Phys. Rev. C 44, 657 (1991). Reprints included with this report.

II. Maxwellian-Averaged Neutron Capture

Status: 100% completed.

Publication: "On the calculation of Maxwellian-averaged capture cross sections", Astrophys. J. Supp. 80, 403 (1992). Reprints included with this report.

III. ^{12}C , ^{28}Si , ^{88}Sr : Neutron Scattering Measurements

Status: 100% completed.

These scattering measurements were done with the time-of-flight technique using neutron pulses from the ORELA water-moderated tantalum target. The flight path was 200.192 ± 0.014 meters. The silicon and carbon samples were natural silicon and graphite cylinders. The strontium sample was metal cylinders isotopically enriched to 99.816% ^{88}Sr .

These measurements were among the first using the new data acquisition system controlled by the IBM PS2 computers. As a check on the reliability of the system, data were taken using both the old SEL and the new PS2 computers.

The scattering data were obtained with a 0.3 g/cm^2 ^{10}B filter to eliminate low-energy neutrons associated with the previous burst, and with two filters of ^{238}U to reduce the intensity of the gamma flash from the target. One ^{238}U filter (0.5 cm thick) covered the whole collimator, the other (2.5 cm thick) shadowed only the tantalum part of the target. The measurements covered the energy region from approximately 10 keV to 5 MeV. The electron beam burst width was 8 nsec resulting in an energy resolution at higher energies of approximately $0.11 [E(\text{MeV})]^{1/2}$ percent.

Six neutron detectors were located 19.1 cm from the center of the chamber at angles of 35° , 55° , 90° , 120° , 140° , and 160° for the ^{88}Sr and ^{28}Si measurements. The laboratory angles for the carbon measurement were adjusted to produce approximately the same center-of-mass scattering angles as for the other two samples. Each neutron detector consisted of a 7.62 cm long by 4.32 cm diameter cylinder of NE-110 which was viewed at each end by RCA 8850 photomultiplier tubes. Additional details of the experimental arrangement for these scattering measurements can be found in Horen et al. (1986).

The threshold for each phototube was set below the single photoelectron level, and a fast coincidence between the two tubes of each detector was required to define an event. The summed anode signals for events registered by any one detector were split into two pulse-height windows and a 45,000 channel time-of-flight (TOF) spectrum was taken for each window. The lower window was from threshold to about 14 photoelectrons, which corresponds to 160 keV proton energy for these detectors. The upper window was for summed pulses greater than 14 photoelectrons. The two TOF spectra for a detector had equal counts at about 300 keV neutron energy. For coincidence events in any two detectors, only one pulse height window of 45,000 diameter was used for each detector. For coincidence events in three or more detectors, one time-of-flight window of 5000 channels was used for each coincidence combination. Thus over one million time-of-flight channels are recorded for each scattering measurement. The efficiencies of the six detectors are quite similar and the carbon scattering measurement serves to normalize the efficiencies. Details on the calculated efficiencies for these two phototube detectors are given in Hill et al. (1985).

The fast outputs of the six detectors were multiplexed to provide the stop signal and to set an eight-bit tag generator of an EG&G clock. The system was designed so that if an event corresponding to the γ -flash were detected in any detector that detector was biased off for that entire ORELA cycle. A 100 nsec coincidence window was used to record events registered in any other detector within ± 50 nsec of a registered event. Moreover, no detector could register more than one event per ORELA burst. The reason for restricting the detectors to one γ -event/burst was to avoid counting after-pulse events triggered primarily by high energy gammas from the γ flash.

Transferring these data from the IBM PS2 computer to the ORELA VAX and subsequent deadtime correction required a significant amount of my time during this reporting period. The problems were solved and now such data can be processed in a straightforward way using the programs PS2EODF, PS2ODF, PS2SPLIT, and PS2STP1 which Jack Craven and I wrote. The results of such

processing for ^{88}Sr for a region spanning 430 keV to 1.7 MeV for the detectors at scattering angles 30° and 90° are shown in Figure 1.

IV. ^{90}Zr : Neutron Scattering Measurement

Status: Measurement 100% completed.

Analysis: 10% completed.

The data from the ^{90}Zr neutron scattering cross section measurement reported in the last reporting period have now been deadtime corrected and a preliminary conversion to scattering cross section has been completed. In Figure 2 are shown results for scattering angles 35° and 90° over the energy range 20 to 100 keV.

V. R-Matrix Parameter Analysis of the ORELA Neutron Transmission ^{90}Zr Low Energy Measurement

Status: 25% completed.

Very little time has been devoted to this analysis during this reporting period. There seems little interest in these parameters until the measurement to higher energy ($\approx$ MeV) is completed. The status of that measurement is discussed in the last section of this report.

VI. R-Matrix Parameter Analysis of the $n+^{208}\text{Pb}$ Cross Section Measurement

Status: 99% completed.

The R-Matrix analysis of the neutron transmission made at the ORELA 500 meter station on flight path 1 is essentially complete. In Table I of the previous report were given the resulting R-Matrix parameters over the energy range 79 keV to 1.7 MeV. These parameters are essentially unchanged. Two regions of analysis continue to cause problems. As shown in Figures 3 and 4, the regions from 870 to 900 keV and 1185 to 1210 keV are very complicated and satisfactory solutions for resonance placement and J^π assignments have not yet been discovered. We continue to work on this problem.

VII. Total Cross Section Measurements for ^{40}Ca , ^{88}Sr , and ^{90}Zr

Because of scheduling problems, these measurements have been rescheduled to fall 1992, the latter part of the current budget period. The measurements will be done using narrow (5 nsec) ORELA electron bursts at the 200 meter station on flight path 1.

Conclusions

The work during this reporting period has been very interesting and productive. Given acceptable operating conditions for the ORELA during the next reporting period, I am confident that satisfactory progress will be made toward completing the work proposed for the Grant period.

Acknowledgements

I am particularly grateful to Stan Whetstone, USDOE for his steadfast support and to the USDOE for the funding which has made this work possible. My colleagues at the Oak Ridge National Laboratory, J. A. Harvey and N. W. Hill, have been generous with their time and energy as we completed the papers and made the neutron scattering measurements. I am also very grateful for the collaboration with R. F. Carlton, Middle Tennessee State University.

References

- D.J. Horen, C.H. Johnson, J.L. Fowler, A.D. MacKellar, and B. Castel, Phys. Rev. C 34, 429 (1986).
- N.W. Hill, J.A. Harvey, D.J. Horen, G.L. Morgan, and R.R. Winters, IEEE Transactions on Nuclear Science, NS-32, 367 (1985).

Figure Captions

1. Observed scattering corrected for deadtime losses for n-⁸⁸Sr for scattering angles 35° (a) and 90° (b) over the energy interval 430 keV to 1.7 MeV.
2. Scattering cross section for n-⁹⁰Zr for scattering angles 35° (a) and 90° (b) over the energy interval 20 to 100 keV. The two curves in each panel present the observed yield normalized to the total neutron cross section divided by 4π and $\sigma_{\text{total}}/4\pi$.
3. Measured total neutron cross section for ²⁰⁸Pb (symbols) and the best R-matrix fit so far attained for the energy region 870 to 900 keV. The dashed curves show the partial-wave structure used in this particular attempt.
4. Similar to Figure 3 except for the region 1185 to 1210 keV.

9-AUG-1992 09:50 WINTERSSA

9-AUG-1992 09:51 WINTERSSA

Figure 1

27-MAY-1992 14:35 CAPLTONA

27-MAY-1992 14:33 CAPLTONA

Figure 2

Figure 3

Figure 4

**DATE
FILMED**

8 / 13 / 92