CLASSIFICATION)

HW-59756 A

DATE _____

4-29-59

GENERAL ELECTRIC

HANFORD ATOMIC PRODUCTS OPERATION - RICHLAND, WASHINGTON

X

RESTRICTED

THIS DOCUMENT CONTAINS RESTRICTED DATA AS
DEFINED IN THE ATOMIC ENERGY ACT OF 1954.
TRANSMITTAL AND DISCLOSURE OF ITS
CONTENTS IN WHOLE OR TO AN UNAUTHORIZED
PERSON IS PROHIBITED.

TITLE

DESIGN OF PRODUCTION TEST IP-247-A-8-FP,
IRRADIATION OF 1.47% ENRICHED SELF-SUPPORTED
I & E FUEL ELEMENTS IN RIBLESS PROCESS TUBES

□

OTHER OFFICIAL CLASSIFIED INFORMATION

THIS MATERIAL CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS. TITLE 18, U. S. C. , SECS. 793 AND 794, THE TRANSMISSION OR REVELATION OF WHICH IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

AUTHOR

W. H. Hodgson
and
R. E. Hall

ISSUING FILE

JUN 12 1954

300 AREA

~~CLASSIFIED FILES~~

THIS DOCUMENT MUST BE LEFT UNATTENDED OR WHERE AN UNAUTHORIZED PERSON MAY HAVE ACCESS TO IT. WHEN NOT IN USE IT MUST BE STORED IN AN APPROVED LOCKED REPOSITORY WITHIN AN APPROVED GUARDED AREA. WHILE IT IS YOUR RESPONSIBILITY AND UNTIL YOU HAVE OBTAINED A SIGNED RECEIPT FROM CLASSIFIED DES, IT IS YOUR RESPONSIBILITY TO KEEP IT AND ITS CONTENTS WITHIN THE LIMITS OF THIS REGION AND FROM AN UNAUTHORIZED PERSON. RE TRANSMITTAL TO THE STORAGE AT YOUR STAGE OF EFFICIENCY IS NOT APPLICATED. IF COPIES ARE OBTAINED, RETURN THEM FROM THE RELATED ISSUING OFFICE. ALL PERSONS READING THIS DOCUMENT ARE REQUESTED TO SIGN IN THE SPACE PROVIDED BELOW.

ROUTE TO:

PAYROLL NO.

LOCATION

FILES	ROUTE	DATE
-------	-------	------

SIGNATURE AND DATE

300 files

NOT FOR EXPORT
FORM NO. 10-64
REVISED 1-64
REPLACED BY IAW-597.53A REV.

CONFIDENTIAL

54-3000-340 (3-57) AG. 41 2171271 MAR 57

(CLASSIFICATION)

DECLASSIFIED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

DECLASSIFIED

✓ HW-59756-A

4-29-51

document [REDACTED]
[REDACTED] 1954.
Its transmittal [REDACTED] of its
content in any manner to [REDACTED]
is prohibited.

This document consists of
6 pages. [REDACTED]
of [REDACTED]

DESIGN OF PRODUCTION TEST IP-247-A-8-FP,
IRRADIATION OF 1.47% ENRICHED SELF-SUPPORTED
I & E FUEL ELEMENTS IN RIBLESS PROCESS TUBES

Distribution

1. FW Albaugh	25. DG Kern
2. JA Ayres	26. WK Kratzer
3. RS Bell	27. LW Lang
4. HE Berg-JS Ship	28. AR Maguire
5. JE Bergman	29. NR Miller
6. AG Blasewitz	30. HC Money
7. RW Bown	31. JF Music
8. JH Brown (170 D)	32. TD Naylor
9. JJ Cadwell	33. R Nilson
10. AC Callen	34. EV Padgett-CA Strand
11. KE Carpenter	35. RS Paul
12. VR Cooper	36. CA Priode-WG Alber
13. RL Dickeman	37. RE McGrath
14. GC Fullmer-RO Brugge	38. RW Reid
15. SM Gill	39. GW Riedeman
16. OH Greager	40. JE Ruffin
17. CN Gross	41. HG Spencer-RR Bloomsrand
18. FW Grubb	42. JT Stringer
19. LT Hagie	43. JW Talbott
20. RE Hall	44. EA Weakley
21. WH Hodgson-WA [REDACTED]	45. EC Wood
22. JL Jaech	46. [REDACTED]
23. PC Jerman	47. 300 Files
24. RT Jessen	

Classification Cancelled and Changed To

DECLASSIFIED

By Authority of DS Lewis

CG-PR-2 (PR-24) 1-11-94

By J. E. Savely 4-21-94

Verified By [REDACTED] Maly

4-21-94.

MASTER

DECLASSIFIED

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED 870

DESIGN OF PRODUCTION TEST IP-247-A-8 FP, IRRADIATION
OF 1.47% ENRICHED SELF-SUPPORTED I & E FUEL ELEMENTS
IN RIBLESS PROCESS TUBES

INTRODUCTION

To evaluate the self-supported fuel element concept, tests are underway to determine the performance of collapsible bridge-rail supported fuel elements in ribless process tubes under present reactor operating conditions at B Reactor. It appears expedient, however, to extend this evaluation to future operating conditions in order to establish the relative feasibility of conversion to self-supported fuel elements in ribless tubes in all present reactors. Utilization of 1.47% U-235 enrichment will provide fuel element powers comparable to those attainable under proposed future conditions. Since I & E fuel elements of this enrichment have previously attained exposures in excess of 2000 MWD/T at specific powers averaging 75 KW/ft in C Reactor¹, this test will specifically evaluate the feasibility of the self-supported fuel element concept. The purpose of this report is to present the design of a test to fabricate and evaluate self-supported fuel elements under conditions of comparable severity to those expected for future loadings of this geometry.

OBJECTIVE

The objective of this test is to evaluate the resistance of projection fuel elements to jacket corrosion at high specific power.

TEST SUMMARY

Four columns of 1.47 per cent U-235 I & E fuel elements will be irradiated in the ribless tube demonstration facility in B Reactor to a goal sufficient to demonstrate significant improvement of performance of self-supported fuel elements over standard I & E fuel elements.

BASIS

Preliminary testing^{2,3} of both solid and OIIN I & E self-supported fuel elements in the ribless tube facility in 105-B has indicated that the concept of a self-supported fuel element in a ribless process tube is feasible under current operating conditions. Specifically, it has shown that the bridge-rail supports are adequate, do not severely obstruct flow channels, and do not of themselves create an area of rapid corrosion. Nine columns of solid self-supported and four of I & E self-supported fuel elements have been discharged to date without evidence of excessive localized rapid corrosion. In summary, nothing has been found as yet

1. HW-43078 C, "Production Test IP-1-A-73 MT, Evaluation of I & E Slugs Operating at High Specific Powers, F. W. Van Wormer, 9-13-56, Secret.
2. HW-50991 A, "Production Test IP-84-A, Evaluation of Slugs Having Projection for Use in Ribless Tubes", R. E. Hall, 3-12-58, Secret.
3. HW-50991 B, "Supplement A to Production Test IP-84-A, Evaluation of Slugs Having Projections For Use in Ribless Tubes", R. E. Hall, 9-29-58, Secret

DECLASSIFIED

to indicate that the self-supported fuel element will not prevent misalignment and associated jacket corrosion ruptures.

Prior to removal of the ribless process tubes from B Reactor, it is desirable to evaluate self-supported I & E fuel elements under future reactor operating conditions. It is necessary that this pilot test loading be accomplished on as rapid a schedule as possible in order that this program may be adequately integrated with the zirconium tube replacement schedule for which tubes are currently being procured.

The method chosen to pilot these conditions involves the use of enriched (1.47% U-235) fuel elements to attain high specific power, oversize fuel elements to attain high annular coolant temperatures with respect to the interior coolant channel, and short charging to control the maximum corrosion rate.

FABRICATION OF TEST MATERIAL

1. Components

- a) Cans and Spires - Can and spire components shall be X-8001 alloy aluminum of the CIIN (1.460" x 0.375") dimension reduced in length to fit a 7 inch length core. Canned fuel dimensions shall be 1.460" x 0.375" x 7.640".
Designation of components to be cut-down D-2.
- b) Cores • Cores will be seven inch length, enriched (1.47% U-235) uranium I & E (1.370" OD x 0.481 ID) and shall meet all quality requirements for cores used for IP-1-A-73 MT⁴.
- c) Supports • The bridge-rail supports shall be the same type used previously³ except that the height shall be reduced to retain the effective rib outside diameter of 1.600". Eight ribs shall be attached, four to each end at 90° spacing, using spot welding techniques.

2. Assembly

All fuel elements shall be fabricated by the Dip Process (Lead Dip Process for Heat Treated Uranium, HW-47029).

3. Quality of Material

All standard quality control measures will be applied in fabrication of fuel elements.

4. Quantity of Material

A total of 104 acceptable fuel elements is required for this test.

- 4. HW-43078 A, "Design of Production Test IP-1-A-73-MT, Evaluation of I & E Slugs Operating at High Specific Powers", W. C. Riley and F. W. Van Wormer, 5-16-56, Secret.

DECLASSIFIED

Comparison Standards

No comparison Standards will be required for this test.

TESTINGPre-Irradiation Testing and Measurements

1. Measurement of length, ID and OD 1/2 inch from each end and in the center, and warp is required for each test fuel element. Weight of all test fuel elements is required.
2. Identity and position of measured fuel elements will be recorded by a series and position number stamped on the base of each element.

IRRADIATION TEST

Four columns of 20 pieces each shall be charged in order into ribless process channels in B Reactor. Exposure goal will be based on the demonstration of a significant improvement of performance over standard elements or until one rupture is sustained, at which time the test will be discharged.

POST IRRADIATION EXAMINATION

All fuel elements irradiated as part of this test shall be visually examined and weighed; and shall have weight losses, diameter growth and warp recorded. Ribs shall then be removed from a few selected elements for nondestructive can-wall thickness determination. Two selected elements may be examined destructively in the radiometallurgy laboratory.

TEST AUDIT

Notebook HW-59756 is to be used to record all data pertaining to this test. Any unusual incidents, whether or not they seem important at the time, are to be recorded in the notebook. The Appendix to this report contains a list of items to be used as a guide for preparation of the notebook.

TEST LIMITATIONS OR HAZARDS

Precautions for handling and storage of the unirradiated enriched uranium for this test are outlined in specification NS-0 in HW-47013.

R. E. Hall
 R. E. Hall
 Reactor Fuels
 Process and Reactor Development
 Irradiation Processing Department

W. H. Hodgson
 W. H. Hodgson
 Process Engineering
 Engineering Section
 Fuels Preparation Department

DECLASSIFIED

5. HW-47013, "Nuclear Safety Specifications, Fuel Element Manufacturing Process", 12-10-56, Confidential

APPENDIX

DATA TO BE RECORDED IN PRODUCTION TEST NOTEBOOK.

I. Fuel Element Core

A. Lot Number

B. Heat Treatment

1. Technique
2. Form of material when treated
3. Attendant conditions

C. Finished Dimensions (Pre-assembly)

D. Properties

1. Orientation data
2. Tensile data
3. Other significant properties

E. Pre-assembly treatment (including inspection)

II. Can Lot Number

III. Assembly Process

- A. Process Used
- B. Brief Explanation of Process
- C. Attendant Conditions

IV. Post Assembly Treatment

- A. Protective Coating
- B. Autoclaving
- C. Other Treatment
- D. Inspection

V. Pre-Irradiation Examination

- A. Dimensions
- B. Warp

DECLASSIFIED

VI. Irradiation

A. Coolant Temperature

1. Inlet
2. Outlet

B. Panellit and crossheader Pressures

- C. Number of shutdowns (controlled and scram)
- D. Other

VII. Post Irradiation Examination

A. Visual

- B. Warp (and other profilometer data)
- C. Fracture data
- D. Other

VIII. Log. Running account with dates recording the progress of the PT, unusual incidents (such as a slight change in process during assembly), and other deviations whether or not they seem pertinent at the time of occurrence.

DECLASSIFIED