AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

**Design of an 80 K Liner Prototype in SSCL ASST
for Synchrotron Light Interception***

Q. Shu, W. Chou, D. Clark, W. Clay, Y. Goren, et al.

Superconducting Super Collider Laboratory[†]
2550 Beckleymeade Ave.
Dallas, TX 75237

May 1993

*Presented at the Fifth Annual International Symposium on the Super Collider, May 6-8, 1993 San Francisco, CA.

[†]Operated by the Universities Research Association, Inc., for the U.S. Department of Energy under Contract No. DE-AC35-89ER40486.

MASTER

DESIGN OF AN 80 K LINER PROTOTYPE IN SSCL ASST FOR SYNCHROTRON LIGHT INTERCEPTION

Q. S. Shu, W. Chou, D. Clark, W. Clay, Y. Goren, R. Kersevan,
V. Kovachev, P. Kraushaar, K. Leung, J. Maddocks, D. Martin,
D. Meyer, R. Mihelic, G. Morales, J. Simmons, G. Snitchler,
M. Tuli, W. Turner, L. Walling, K. Yu, and J. Zbasnik

Superconducting Super Collider Laboratory*
2550 Beckleymeade Avenue
Dallas, TX 75237-3997

INTRODUCTION

The Superconducting Super Collider (SSCL) is the first proton superconducting accelerator designed to operate at 20 TeV (each beam) with beam current of 72 mA in which synchrotron radiation is a significant design factor. The Collider will produce a synchrotron power of 0.14 W/m and 18 kW total at 4.2 K. This synchrotron light will produce considerable photodesorbed gases in the beam vacuum. The photodesorbed gases may greatly reduce the beam lifetime and scattered beam power may lead to quenching of superconducting magnets. The Collider availability may be unacceptable without properly addressing this concern. A liner is one method under consideration to minimize the presence of photodesorbed gases. Such a liner may improve Collider cryogenic thermal efficiency that would allow a potential luminosity upgrade.

A liner prototype has been developed for prototype testing at the Accelerator System String Test (ASST) facility since the half cell (five dipoles, one quadrupole and one spool piece with a beam position monitor) is an existing basic unit of the Collider. The liner operational temperature was required to be 80 K based on photodesorption data available from the CDG and SCDG measurements.¹ Those data showed that liners at lower temperatures 20 K or 4.2 K had either unacceptable impedance margins or excessively long conditioning periods. An 80 K liner also replaces the 4 K dynamic heat load of the synchrotron radiation with a static heat load, independent of the beam intensity, and transfers the intercepted heat to the liquid nitrogen system. In January of 1993 new photodesorption data indicated the viability of 4 K and 20 K systems.¹

Developing a liner system presents scientific and technical challenges. The system design addresses photodesorption, particle beam stability, magnetic field quality, beam induced wake fields, rf impedance, cryogenics, magnet quenching (especially quenches induced Lorentz pressure), and many other interdisciplinary technical problems. This paper

* Operated by the Universities Research Association, Inc., for the U. S. Department of Energy under Contract No. DE-AC35-89ER40486.

presents the results of trade studies, analyses and engineering design of an 80 K liner and also briefly discusses the preliminary consideration of lower temperature liners.

80 K ASST LINER CONFIGURATION

As shown in Figure 1, an 80 K Liner System consists of an 80 K perforated tube (the liner tube) located coaxially inside the 4.2 K magnet bore tube. The liner temperature is maintained at 80 K by high pressure GHe loops of 0.25 g/s. The GHe flow is recooled by LN_2 in the cooling pipe of a magnet cryostat. A special end conducting cooling structure is designed to cool the quadrupole magnet liner since the ASST quadrupole beam tube ID (32.3 mm) is much smaller than an ASST dipole ID (42.3 mm). Low heat leak supports hold the liner in the center of the beam tube. A thin layer of cryosorber (0.5 mm) on the inner surface of the 4.2 K beam tube pumps the photodesorbed gases through the holes on the liner tube. The rf joint, a good thermal contact joint, assures the continuity of the image current and aids assembly and maintenance. The magnet interconnect with these joints, and a compact heat exchanger are included in a cryogenic box. The cryogenic box also allows each liner to have up to a 54-mm thermal contraction during cooldown and warmup. However, the liner is discontinuous when routed through the Beam Position Monitor (BPM).

Figure 1. A schematic layout of the ASST 80 K liner system.

80 K LINER TUBE DESIGN

Figure 2 shows the tube cross section of the Collider Dipole Magnet (CDM) liner and Collider Quadrupole Magnet (CQM) liner. A uniform and maximum possible liner inner diameter (ID) is needed due to: (1) particle beam commissioning, (2) particle beam dynamic stability, and (3) safety margin. However, the maximum liner ID is constrained by: (1) the available magnet beam tube inner diameter (ID), and (2) the minimum liner radial space. Using parallel loop cooling, the minimum liner radial space is 6 mm and using end conducting cooling, the radial space needs to be 3.5 mm. Tables 1 and 2 show the maximum liner ID and the liner impedances in various options, respectively.

Figure 2. The cross sections of the (A) CDM liner and (B) CQM liner.

Table 1. Possible maximum liner ID in various cases.

Object	Dipole Beam tube ID, mm	Magnet Liner ID, mm	Quad Beam tube ID, mm	Magnet Liner ID, mm	Spool Beam tube ID, mm	Piece Liner ID, mm
ASST	42.3	25.3	32.3	25.3	32.3	25.3
GD, B & W	32.3	20.2	32.3	20.2	32.3	20.2
Desired	42.3	31	42.3	31	42.3	31

Table 2. Comparison of impedances.

Case	Liner ID, mm	Hole/Slots Coverage	Z (liner) M ohm/m	Z (other) M ohm/m	Z (total) M ohm/m	Safety margin
Baseline	32.3			40	40	6.7
With liner	25.3	2 mm, 2%	22	112	133	2
With liner	25.3	2 mm, 4%	44	112	156	1.7
With liner	25.3	2 × 6, 2%	8	112	120	2.2
With liner	33	2 mm, 4%	15	40	55	4.9

The liner tube design also must meet the following requirements:

1. Inner wall conductivity and thickness	$\sigma \cdot \delta > 2 \times 10^5 \text{ Ohms}^{-1}$
2. Liner impedance	$Z L/n < 0.34 \text{ Ohm}$
$Z T < 20 \text{ M Ohm/m}$
3. Inner wall photodesorption coefficient
$\alpha = 0.3$ for H_2	$\eta = 0.02$
4. Liner pump speed	600 l/m/s for H_2
5. Total liner heat leak to 4 K	< 1 W for dipole
6. Cryosorber pump speed	1200-3000 l/m/s for H_2
7. Cryosorber pumping capacity	30 Torr l/m at 294K
8. Cryosorber activation temperature	294 K; regeneration < 80 K H_2 ,
<294 K all Gases; recovery
fraction regeneration > 98%
9. Liner quench survivability and ASME code	100 quenches in 25 yrs
10. Radiation dose tolerance	1400 MRad in 25 yrs

RETROFIT ASSEMBLY, END COOLING AND HEAT LOAD BUDGET

An extensive trade study has been performed to develop a retrofit 80 K liner structure and flow return cooling loop, Figure 3A. If an 80 K liner is chosen for collider upgrade, the structure will help its insertion into magnets to be retrofitted in the tunnel. As shown in Figure 3B, the CQM liner is refrigerated through thermal conduction by 80 K GHe in a compact heat exchanger at the end of the liner tube outside the CQD cold mass. The maximum temperature increase ΔT could be less than 5 K for a Spool Piece liner, and 10 K for a CQM. Table 3 shows the heat load budget. Radiation is difficult to reduce to budgeted levels because the cryosorber likely to have an emissivity near unity.

Table 3. Fixed or static 80 K liner heat budget.

	Dipole (w)	Quadrupole (w)	Spool (w)	Half Cell (w)
Supports	0.5	0.5	0.3	3.30
I R Radiation	0.2	0.06	0.04	1.1
Interconnects	0.05	0.05	0.05	0.35
BPM	—	—	0.26	0.26
Total	0.75	0.61	0.73	5.01

Figure 3. (A) Assembling a CDM liner, (B) Assembling a CQM liner.

INTERFACE BETWEEN CQM, BPM, AND SPOOL PIECE

Figure 4 shows the liner interfaces with the CQM, BPM and the Spool Piece. Details were discussed in the liner design report.

Figure 4. Liner interfaces between the CQM, BPM and the Spool Piece.

LOWER TEMPERATURE LINERS

Several concepts of 4.2 K and 20 K Liners have been studied as a result of the new photodesorption tests. Concept A had a complex extruded shape with three supports integral to the liner tube. Concept B showed a circular beam tube with three brazed hat shaped supports running the full length of the tube (to ensure even thermal distribution between liner and bore tube). Concept C showed the same support system as proposed for 80 K liner, i.e., discrete supports located every 1 m. All three concepts would be optimized for good thermal contact between the liner and beam tube. In the three concepts, the cryosorber is located on the liner outer surface. If the photodesorption coefficient at lower temperature is much less than at higher temperature, the number of the holes on the liner and the rf transverse impedance in the structure will be further reduced. Concept D considered addition of a 4.2 K channel on the liner tube to boost cooling capacity. The 20 K liner system concept is very similar to the 80 K system, but with the option of cryosorber on liner outer surface.

REFERENCES

1. 80 K ASST Liner Design Report, edited by Q. S. Shu, in preparation.

**DATE
FILMED**

9/10/93

END