DOE/PC/89757--4

DE92 040020

7-4

DE-AC22-89PC89757-4

THERMODYNAMICS AND SURFACE STRUCTURE OF COALS

Quarterly Report for the Period
July 1, 1990 to September 30, 1990

John W. Larsen, Deanna M. Quay,
James E. Roberts, and Patrick C. Wernett

Department of Chemistry
Lehigh University
Bethlehem, Pa. 18015

PREPARED FOR THE UNITED STATES DEPARTMENT OF ENERGY
Under Contract DE-AC22-89PC89757

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER
jb

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

SCOPE AND OBJECTIVES OF WORK

Scope:

An understanding of the surface structure and chemistry of coals is necessary to understand and intelligently optimize processes dominated by surface interactions. In applications such as coal cleaning and coal slurries, the interactions occurring at the coal surface are critical. In all chemical reactions of solid coal, the reagent must first encounter the coal surface. How much of the surface is open to a molecule and the interactions occurring on contact are important, often crucial parameters. Our present scientific understanding of the coal surface and its interactions are rudimentary and inadequate to support the development of new processes and to allow full understanding of the technology which has already been developed, largely on a trial-and-error basis.

Objectives:

The objectives of this work are to investigate the surface structure and surface interaction thermodynamics of a variety of coals and treated coals in order to develop an understanding of the coal surface and how it changes. The surface structure of coals will be analyzed by:

- 1) deposition of NMR relaxation agents to provide spectra of those atoms near the surface which yield direct information about the structure of the surface groups.

2) using ^{129}Xe NMR as a probe to determine pore size distributions and the surface polarity of coals.

3) mapping out the steep dependence of surface area on adsorbate size for a variety of coals.

Thermodynamic studies of coals will be studied by:

4) inverse gas chromatography to obtain full desorption isotherms of coals.

5) to use classical calorimetric studies of coal surface-adsorbate interactions to generate a thermodynamic data base.

Present Work:

Our work this quarter has been:

(1) The BET gas adsorption and fractal analysis of Argonne: Pocahontas No. 3, Upper Freeport, and Pittsburgh No. 8 coals.

(2) The determination of relaxation times of model compounds to aid in the experimental design for the deposition of relaxation agents on coals to characterize the structure of surface groups in coals.

The BET Gas Adsorption and Fractal Analysis of Argonne Coals*

Background:

The surface area and pore structure of coals are among their most important physical properties. They are well studied and good reviews are available.¹⁻⁴ We have presently determined the BET surface areas of the full series of Argonne coals using CO₂, N₂ and a series of aliphatic hydrocarbons. We present here our data on three Argonne bituminous coals. The adsorption data are inconsistent with the generally accepted structure of coal pore systems, that is an interconnected network of bottle-necked pores. The adsorption data suggest that most pores are closed and to reach them an adsorbate must diffuse through solid coal rather than through an interconnected pore network. The CO₂ BET surface areas for the Argonne coals are much larger than those obtained using the hydrocarbon gases, even though CO₂ is of similar size to cyclopropane and similar size and shape to ethane. We believe the much larger CO₂ surface areas are due to the solubility of CO₂ in coals^{5,6} (however see reference 7 for a conflicting view). This solubility allows CO₂ to penetrate into pores that are inaccessible from the external surface to insoluble molecules.

Coals are molecular sieves and it has been universally accepted that they contain an interconnected pore network of high surface area, the pores having constricted openings which results in the observed size discrimination.¹⁻⁴ This pore structure was

first proposed by Bond⁸. The coal surface is an important aspect of the coal's physical structure. All reagents either pass through the coal surface or react at it.

Experimental:

We measured the surface areas of the Argonne coals using standard multipoint volumetric BET techniques^{3,9}, a series of aliphatic alkanes, N₂, and CO₂. All samples were dried by evacuation at 10⁻⁶ torr overnight on a Micromeritics Digisorb 2500 stainless steel adsorption rig. Twenty four hours equilibration for the first adsorption point and six hours equilibration for each subsequent point was allowed for the cyclic hydrocarbon gases, except where otherwise noted. Six hours equilibration between adsorption points was used for all the other gases except N₂.¹⁰ The data and measurement conditions for Argonne: Pocahontas No. 3, Upper Freeport, and Pittsburgh No. 8 coals are presented in figures 1-3 respectively.

Discussion:

The coal surface areas obtained using CO₂, ethane and cyclopropane, all of similar cross sectional area, cannot be rationalized using a constricted pore model. Ethane (cylindrical) and cyclopropane (planar) have different shapes and slit like or cylindrical pores would discriminate between them. Both report

much lower BET surface areas than CO_2 , which is similar in shape to ethane (both cylindrical) and similar in size to cyclopropane and ethane. Diffusion through constricted openings cannot be responsible for this size discrimination.

To see whether adsorption on the coal surface might be responsible for the observed dependence of measured surface area on adsorbate size, a fractal analysis of the data was performed using the approach developed by Avnir and Pfeiffer.¹¹⁻¹⁵ A plot of $\log N$ (BET monolayer surface coverage) vs. $\log \sigma$ (cross-sectional area of the adsorbate) has a slope of $-D/2$ where D is the fractal dimensionality of the solid and must be between 2 and 3.¹¹⁻¹⁵ The plots in Figures 1 (Argonne Pocahontas No. 3), 2 (Argonne Upper Freeport), and 3 (Argonne Pittsburgh No. 8) have fractal dimensionalities of 12, 11, and 16 respectively based on the cyclic hydrocarbons. All of these are impossible values from a fractal standpoint. The observed surface areas are not controlled by a coal surface property.

We believe the dependence of the observed coal surface areas on adsorbate size are due to sharply differing diffusion rates of the adsorbate through solid coal to reach the pores. The extraordinarily steep dependence of the measured surface area on adsorbate size is similar to diffusion rates through glassy polymers on molecular size.¹⁶ The hydrocarbons reach only a small portion of the pores, that portion dependent on their diffusion rates. Those diffusion rates fall very rapidly as molecular size increases as expected for diffusion through a glassy polymer. All

of the coals are glassy polymers under these conditions.^{17,18} CO_2 is soluble in coals, diffuses rapidly reaching closed pores, and so will report a large total pore surface area. These surface areas will be slightly overestimated due to the solubility of CO_2 in coals, but this effect is thought to be small (although this may be becoming controversial).^{1,5-7} Very small molecules like helium can diffuse reasonably rapidly through coals, resulting in accurate helium densities and valid pore volumes determined from them. Apparently, CO_2 is sufficiently polar to have an efficient interaction-based diffusion mechanism. To verify slow diffusion, ethane uptake was followed, in this laboratory, for 130 hours at 25°C on an Argonne Illinois No. 6 coal. Adsorption was continuous during this time and equilibrium had not been reached when the experiment was terminated.

The only other explanation of these data is that coal surface areas are not being measured, just the solubility of the probe molecules in the coals. This argument is controvert by recent neutron diffraction studies of coal pores and by the agreement between CO_2 coal surface areas and those obtained from low-angle X-ray scattering experiments.^{19,20} Disagreement between the CO_2 and X-ray surface areas of two brown coals have also been reported.²¹

We propose that most pores in coal are closed. They cannot be reached by diffusion through a pore network but can only be reached by diffusion through solid coal. CO_2 gives accurate total surface areas because it dissolves in and rapidly diffuses through

solid coals, reaching all the pores. This surface area is irrelevant to materials which are only slightly soluble or insoluble in coals for these can only reach a small portion of the pores. Thus, the diffusion rate controls the determined pore size. For the large molecules involved in direct liquefaction and most organic reactions, the effective surface areas of these coals are very small, only a few m^2/g .

The consequences of this structure model for coal processing and reaction are significant. These coals cannot be considered high (hundreds of m^2/g) surface area materials which are easily accessible. It will be a low surface area, impermeable solid. The advantages of fine grinding are obvious. Using solvents which will cause coal to become rubbery rather than glassy will enhance diffusion and thus reactivity.

Determination of the Surface Structure of Coals By the Deposition of NMR Relaxation Agents

Present Work:

Our work this quarter has been directed at examining spectra and determining relaxation times of a model compound with and without the deposition of relaxation agents. The techniques developed will be applied to coals.

Background:

The use of NMR as a surface technique has never been applied

to organic solids to the best of our knowledge. Solid state NMR has been applied extensively to coal and related systems. It is a powerful technique, because line positions and intensities are indicative of geometry, bonding hybridization and population of distinct functionalities as well as the local environment of the atom. The NMR spectrum can be influenced by many factors including through-space dipolar coupling between an unpaired electron spin and the spin of the carbon atom. The unpaired electron can act as a relaxation sink, significantly shortening the spin-lattice relaxation time (T_1) of the coupled carbon-13 atom. This shortening of the T_1 can broaden the signal to the point where it disappears. The effective range of interaction of the paramagnetic center with the carbon spin is proportional to the inverse sixth of the separation of the two spins (r^{-6})²². It is a relatively short range, on the order of one nanometer. Assuming that the paramagnetic centers are deposited on the surface of our sample, the short range of this interaction indicates that this would indeed be a surface technique.

We propose to deposit NMR relaxation agents and shift reagents on the surface of coals. The dipolar coupling of the unpaired electron spin of the relaxation agent and the carbon spin should significantly shorten the carbon T_1 to broaden it away. We propose to obtain the ^{13}C NMR spectrum of a coal before and after the deposition of the relaxation agent and subtract the spectra. The difference spectra will represent the functionalities within one nanometer of the surface and should accurately reflect the

surface composition of the coal. The NMR shift reagents will be used in a complimentary experiment.

In order to determine the effectiveness of copper(II) as a relaxation agent, we deposited known concentrations of copper(II) on a well characterized model compound. We chose an aryl sulfonate silica gel ion exchange resin as our model compound because it is well characterized and because there are different types of carbon functionalities at varying distances from the surface. We did not find that the signal was broadened away. Since the broadening mechanism is based on T_1 behavior, we decided to monitor them. By depositing increasing concentration of copper(II) on the resin and monitoring the effect on the T_1 values, we observed a definite decrease in T_1 and increase in the depth of effectiveness. See Table 1. Since we have no idea what an effective relaxation agent concentration might be, we used varying concentrations of copper(II). From these results we expect that a large concentration of relaxation agent deposited on the sample could broaden the surface peaks away. These results also suggest that copper(II) may not be the best relaxation agent, so we plan to look at some other transition and lanthanide metals.

Experimental:

Our model compound is an aryl sulfonate ion exchange resin produced by J. T. Baker, Inc. All NMR spectra were obtained using a General Electric GN-300 NMR spectrometer operating at 75.4 MHz

for ^{13}C and utilizing a Doty 7mm probe. Approximately 200 mg of sample were used for each experiment and the samples were examined under Magic Angle Sample Spinning (MASS) conditions.²³ We are currently searching for further suitable model compounds and researching the NMR chemical shift reagents to be used in these studies.

Preliminary work on this project had been started by Mike Alaimo, under the supervision of Dr. James Roberts, in which varying amounts of copper (II) were deposited on the silica gel surface. Percent surface coverage was determined on a charge equivalence basis. Samples of 0, 5, 10, 30, and > 90% copper (II) have been made. Deposition was carried out by dissolving known amounts of copper(II)chloride in water and titrating into a slurry of the silica gel with gentle stirring. Alaimo analyzed the filtrate of the >90% loaded sample for residual copper using atomic adsorption spectroscopy and found it to be minimal.

Discussion:

We began by studying the spin-lattice relaxation time (T_1) and an optimization of the cross polarization conditions for an aryl sulfonate silica gel. Cross polarization is a technique commonly used in solid state NMR involving the transfer of magnetization from protons to carbons.²³ This technique theoretically improves sensitivity by a factor approximately equal to the ratio of the gyromagnetic ratios. For carbon the

theoretical improvement is 4, but the actual increase in sensitivity is only about a factor of 3. A typical spectrum of this aryl sulfonate silica gel obtained using cross polarization is presented in Figure 4. To optimize the cross polarization conditions we used an experiment that compared signal intensity to varying Hartman-Hahn contact times.²³ An optimal contact time was found to be approximately 1 millisecond.

Relaxation times are very sensitive to exposure to unpaired electrons. The effect of a paramagnetic center in close proximity to an atom should have a profound effect on its T₁ relaxation time, shortening it significantly. The relative changes in the various T₁'s should serve as a depth profile of different atoms from the paramagnetic center.

There are a number of ways to measure T₁ values. One common method is an inversion recovery experiment. Inversion recovery experiments are based on a 180°- τ - 90° pulse sequence. This NMR pulse sequence results in tipping the net magnetization vector 180° so that it is in a non-equilibrium state along the -z axis. During the time period τ , the magnetization vector begins to relax back along the z-axis to its original state. After time τ , the magnetization vector receives a 90° pulse into the x-y plane so that its intensity can be measured. By performing this experiment with varying τ lengths, the different amounts of magnetization at each time τ can be compared simply by monitoring peak intensity. We use a modification of this pulse sequence in which the proton's magnetization is transferred to the carbon atoms

following the τ period. This allows one to determine the proton T_1 values by monitoring the carbon spectrum. The values we determined for our proton T_1 's for the silica gel sample were approximately 0.12 seconds. A typical plot used to determine proton T_1 's by this method is shown in Figure 5. The T_1 's are calculated using the following variation of the Bloch equation:²⁴

$$y = M_0(1 - 2e^{-x/T_1})$$

where y is the peak area (intensity), x is the relaxation time (τ), and M_0 is the amplitude at $x \gg T_1$. The individual points (y) are fit to a linear regression analysis using a Lotus 123 spreadsheet. The data are very sensitive to the value chosen for M_0 , so an equilibrium value for M_0 must be established at long τ values. Long T_1 values considerably increase experimental time. Another disadvantage to this experiment is that the carbon peaks of interest often appear on top of a broad background signal. This background signal arises from plastic parts used in the probe design. Fortunately, much of this background noise is lost when cross polarization is used because the KEL-F plastic in the probe does not have many protons. An advantage to this T_1 determination method is that it is not cross polarization dependent. Deposition of paramagnetic centers on the silica gel may hinder cross polarization and if this occurs, this technique would still be useful since it is not cross polarization dependent.

Similar methods used to determine ^{13}C T_1 's in this laboratory we term T1CP²⁵ and T1NOE²⁶. Both experiments involve cross polarization followed by a $90^\circ - \tau - 90^\circ$ pulse sequence for carbon.

For these experiments, the cross polarization and the first 90° pulse establish a non-equilibrium magnetization along the z-axis. The magnetization vector relaxes back to M_0 during the τ period. The second 90° pulse tips the magnetization vector into the x-y plane so it can be measured. Phase cycling cancels out M_0 . The T1NOE also includes a series of proton pulses during the τ period to saturate and thereby suppress any transient nuclear Overhauser effects (NOE). The advantage of these two techniques is that the magnetization vector decays exponentially to zero, eliminating the tedious establishment of the M_0 equilibrium required for the inversion recovery pulse sequence. The major disadvantage of these two techniques is their dependence on cross polarization to be effective. For observing materials having few protons or an abundance of unpaired electrons, these two methods would be difficult or impossible to use. The data here are processed using the following equation:²⁷

$$y = A(1 - (e^{-x/T_1}))$$

where A is the amplitude at $x = 0$ and plotted using the same linear fit described above. The observed ^{13}C decay pattern is non-linear, a common phenomenon with solids.²⁸ This non-linearity is caused because solids often have varying T_1 's for different orientations. Because of this non-linearity, our data were fit using the initial slope method of analysis, in which the first several points are used to plot the straight line.

Each experiment has its advantages and disadvantages. One must consider relative relaxation times and why the experiment is

being done to determine which experiment is best in each case. In general, the experiments requiring the shortest τ times allow for the greatest number of acquisitions and thus the greatest signal to noise per unit time. One must balance time and ability to cross polarize when selecting the optimal experiment.

The experiments we used to determine the ^{13}C T_1 values were T1CP and T1NOE. Initial studies used T1CP and subsequent studies used T1NOE to ensure that there was no interference from nuclear Overhauser effects. The T_1 values we obtained ranged from 0.6 to 1.1 seconds for various carbons using T1CP and 0.48 to 0.95 seconds using T1NOE for the silica gel with no copper. We then began investigating the effect of varying levels of copper (II) ions bound to the silica gel (see Table 1 for actual T_1 values). Each T_1 value in Table 1 represents the average of at least 3 experiments except for the >90% copper (II). The ^{13}C T_1 at >90% copper (II) is the result of only one experiment. We had difficulties doing this experiment due to problems with cross polarization caused by the large number of unpaired spins from the copper. Figure 6 depicts the method in which the ^{13}C T_1 's were determined. Notice the plot for ^{13}C T_1 's are non-linear (Figure 6), unlike the proton T_1 's (Figure 5). Only the first several points were used to define the slope for the ^{13}C T_1 's.

As can be observed by examining Table 1, relaxation times for both ^{13}C and ^1H decrease substantially upon addition of copper (II) ions. The relative influence of the carbon T_1 values varies with the amount of copper ion and the proximity of the carbon to

the surface. This seems to indicate that relaxation agents may be a good probe to observe the surfaces of many materials including coals.

We are presently also searching for suitable model compounds to carry out this work. Ideal model compounds would have:

- a) known chemical structure both on the surface and in the bulk
- b) several distinct types of ^{13}C functionalities
- c) different distinguishable surface and bulk functionalities
- d) high surface area ($> 100\text{m}^2/\text{g}$)
- e) negative surface charge or groups that would attract positively charged NMR shift reagents or relaxation agents.

We are presently examining several possible candidates, primarily ion exchange resins and functionalized polymer microparticles.

Future Work:

Next quarter, we plan to apply this copper relaxation agent to an Argonne Beulah Zap lignite. We have chosen this coal primarily because it is low rank and has a high concentration of oxygen functional groups. We expect the oxygen and carboxylic acid functionalities to bind with the copper (II). We hope to observe similar effects with the coal that we observed in the aryl silica gel. These effects include:

- a) a shortening of relaxation times
- b) a relative depth profile created by varying concentrations of copper (II)

c) a loss of features in the spectra

We also plan to investigate some of the lanthanide metals as possible NMR chemical shift or relaxation agents. Our present plan is to use dysprosium (III), praseodymium (III), and europium (III) ions as probes similar to the way we used the copper. Chelated praseodymium and europium compounds have been used successfully in the past as chemical shift reagents and background information indicates that dysprosium should have a similar, but more pronounced effect, than the europium or praseodymium.²⁹ The lanthanide work will be initially performed on our model compound, the aryl silica gel. We will also begin using a carboxylic acid ion-exchanged silica gel resin. We plan to switch to this resin because the carboxylic acid groups will more closely model the coal.

Figure 1. BET Tiling Experiment on Argonne
Pocahontas No. 3 Coal
91% C, 4.7% H, 3% O, 0.9% S, 5% ash (daf)

Figure 2. BET Tiling Experiment on Argonne
Upper Freeport Coal
87% C, 5.5% H, 4% O, 2.8% S, 13% ash (daf)

Figure 3. BET Tiling Experiment on Argonne
Pittsburgh No. 8 Coal
83% C, 5.8% H, 6% O, 1.6% S, 9% ash (daf)

Note: Cyclopropane had 6 hrs. equilibration between
all adsorption points.

Figure 4. This is a carbon-13 NMR spectrum of aryl sulfonate silica gel taken using cross polarization with 1920 acquisitions.

DQMA01. 201 DMQ
MAC01 T1CP 4KHZ

03JUL90

T1CP1H for an Aryl Sulfonate Silica Gel

Figure 5. This representative proton T_1 plot for the aryl sulfonate silica gel uses all points in the regression.

Single Exponential T₁ Calculation

Carbon for Aryl Sulfonic Acid 28.8ppm

Figure 6. This is a carbon T₁ plot for the aryl sulfonate silica gel peak at 28 ppm. Because of the non-linearity of the plot only the first six points were used in the regression.

Table 1
Relaxation Time, T1 (Seconds) for Aryl Silica
Gel Unbound and with Varying % Copper(II)

	Unbound	5%	10%	30%	>90%
C-13 127 ppm	0.48 (0.09)	0.089(0.013)	0.081 (0.010)	0.075 (0.0012)	0.019 (0.0010)
C-13 28 ppm	0.95 (0.027)	0.16 (0.020)	0.19 (0.075)	0.035 (0.0021)	0.050 (0.0018)
C-13 13 ppm	0.85 (0.12)	0.19 (0.035)	0.17 (0.071)	0.089 (0.0052)	0.041 (0.0029)
T1CP1H	0.20 (0.11)	0.0071 (0.00005)	0.0075 (0.002)	0.0037 (0.001)	0.0018 (0.0001)

REFERENCES

1. Marsh, H. Carbon 1987, 25, 49-58.
2. Mahajan, O. P. In Coal Structure; Meyers, R. A., Ed.; Academic Press: New York, 1982.
3. Mahajan, O. P.; Walker, P. L., Jr. In Analytical Methods for Coal and Coal Products; Karr, C., Jr., Ed., Academic Press: New York 1979; Vol. 1.
4. Sharkey, A. G., Jr.; McCartney, J. T. In Chemistry of Coal Utilization, Second Supplementary Volume; Elliott, M. A., Ed., Wiley: New York, 1981.
5. Reucroft, P. J.; Patel, H. Fuel 1986, 65, 816-820.
6. Reucroft, P. J.; Sethuraman, A. R. Energy Fuels 1987, 1, 72-75.
7. Stacy, W. O.; Jones, J. C. Fuel 1986, 65, 1171-1173.
8. Bond, R. L. Nature (London) 1956, 178, 104-105. Bond, R. L.; Spencer, D. H. T. Brennst. - Chem. 1956, 37, 233-234.
9. Brunauer, S.; Emmett, P. H.; Teller, E. J. Am. Chem. Soc. 1938, 60, 309-319.
10. Larsen, J. W.; Wernett, P. C. Energy Fuels 1988, 2, 719-720. The N₂ surface areas for all the Argonne coals were determined using the Micromeritics Digisorb 2500 automated 5-point BET N₂ adsorption program.
11. Pfeifer, P.; Avnir, D. J. Chem. Phys. 1983, 79, 3558-3565.
12. Avnir, D.; Farin, D.; Pfeifer, P. J. Chem. Phys. 1983, 79, 3566-3571.
13. Avnir, D.; Farin, D.; Pfeifer, D. Nature (London) 1984, 308, 261-263.
14. Farin, D.; Volpert, A.; Avnir, D. J. Am. Chem. Soc. 1985, 107, 3368-3370.
15. Farin, D.; Peleg, S.; Yavin, D.; Avnir, D. Langmuir 1985, 1, 399-407.

16. Van Krevelen, D. W. Properties of Polymers; Elsevier: New York, 1976, pp 403-425.
17. Brenner, D. Fuel 1985, 64, 167-173.
18. Lucht, L. M.; Larson, J. M.; Peppas, N. A. Energy Fuels 1987, 1, 56-68.
19. Spitzer, Z.; Ulicky, L. Fuel 1977, 55, 212-224.
20. Winans, R. E.; Thiyagarajan, P. Energy Fuels 1988, 2, 355-358.
21. Setek, M.; Snook, I. K.; Wagenfeld, H. K. In The Chemistry of Low Rank Coals; Schobert, H. H., Ed., American Chemical Society: Washington, D.C., 1984, pp 95-108.
22. Sternlicht, H. J. Chem. Phys. 1965, 42, 2250.
23. Fyfe, C. A. in Solid State NMR for Chemists; C. F. C. Press: Ontario, (1984).
24. Martin, M. L.; Delpuech, J. J.; Martin, G. L. in Practical NMR Spectroscopy; Heyden and Son, Ltd.: London, (1980).
25. Torchia, D. A. J. Mag. Res. 1978, 30, 613.
26. Naito, A.; Ganapathy, S.; Akasaka, K.; McDowell, C. A. J. Mag. Res. 1983, 54, 226.
27. General Electric Company, NMR Instruments, GN Series Software Manuel.
28. Torchia, D. A.; Szabo, A. J. Mag. Res. 1982, 49, 107.
29. Horrocks, N. D, Jr.; Sipe, J. P. III J. Am. Chem. Soc. 1971, 93, 6800.

END

**DATE
FILMED**

10 / 21 / 92