Energy Division

A Study of Changes in Foundation Insulation Levels in the United States

**Jeffrey E. Christian
Oak Ridge National Laboratory
Oak Ridge, Tennessee 37831**

**Melissa K. Voss
St. Mary's College
Winona, Minnesota**

October 1992

**Prepared by the
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U.S. DEPARTMENT OF ENERGY
under Contract No. DE-AC05-84OR21400**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

402

CONTENTS

LIST OF FIGURES	v
LIST OF TABLES	vii
ABSTRACT	ix
EXECUTIVE SUMMARY	xi
1. INTRODUCTION	1
2. PROJECT DESCRIPTION	3
3. DISCUSSION OF COMPOSITE RESULTS	5
3.1 RESPONDENTS	5
3.2 INSULATION APPLICATIONS: YESTERDAY AND TODAY	5
3.2.1 Basement Insulation	8
3.2.1.1 Conditioned basements	8
3.2.1.2 Unconditioned basements	8
3.2.2 Crawl Space	11
3.2.3 Slab-on-Grade	11
3.3 STRUCTURAL MATERIALS	11
3.4 INSECT CONTROL IMPACTS	15
3.5 PROTECTIVE COVERING	15
3.6 ENERGY CODES	18
3.7 HOW MUCH INSULATION?	20
3.8 WHAT MOTIVATES FOUNDATION INSULATION DECISIONS?	20
3.9 INFORMATION SOURCES	23
3.10 RESEARCH ISSUES	26
4. GEOGRAPHIC BREAKDOWN	29
4.1 SOUTHEAST	29
4.2 EAST	29
4.3 NORTHEAST	29
4.4 MIDWEST	30
4.5 WEST	30
4.6 NORTHWEST	30
5. CONCLUSION	31
APPENDIX A	33
APPENDIX B	43

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1 Map of U.S. showing geographic regional responses analyzed	6
2 Breakdown of the respondees	7
3 Foundation structural materials used	14
4 Does insect control impact foundation insulation?	16
5 What is used to protect exterior foundation insulation which extends above grade?	17
6 Is foundation insulation enforced by local codes?	19
7 How much foundation insulation is required by local codes?	21
8 What has caused foundation insulation practices from 1982 to 1992?	22
9 What information source do you use when deciding on foundation insulation?	24
10 Why has there been no change in foundation insulation levels in some areas from 1982 to 1992?	25
11 What research is needed in this area?	27
B-1 Southeast response to questions 1 and 3-9	45
B-2 East response to questions 1 and 3-9	50
B-3 Northeast response to questions 1 and 3-9	55
B-4 Midwest response to questions 1 and 3-9	60
B-5 West response to questions 1 and 3-9	65
B-6 Northwest response to questions 1 and 3-9	70
B-7 Southwest response to questions 1 and 3-9	75

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1 How are you or others in your area insulating — <u>Conditioned</u> Deep Basements?	9
2 How are you or others in your area insulating — <u>Unconditioned</u> Deep Basements?	10
3 How are you or others in your area insulating — Crawl Spaces?	12
4 How are you or others in your area insulating — Slab-on-Grade Foundations?	13
A.1 How are you insulating — <u>Conditioned</u> Deep Basements?	38
A.2 How are you insulating — <u>Unconditioned</u> Deep Basements?	39
A.3 How are you insulating — Crawl Spaces?	40
A.4 How are you or others in your area insulating — Slab-on-Grade Foundations?	41
B.1 How conditioned deep basements are insulated in Southeast	46
B.2 How unconditioned deep basements are insulated in Southeast	47
B.3 How crawl spaces are insulated in Southeast	48
B.4 How slab-on-grade foundations are insulated in Southeast	49
B.5 How conditioned deep basements are insulated in East	51
B.6 How unconditioned deep basements are insulated in East	52
B.7 How crawl spaces are insulated in East	53
B.8 How slab-on-grade foundations are insulated in East	54
B.9 How conditioned deep basements are insulated in Northeast	56

LIST OF TABLES (continued)

<u>Table</u>	<u>Page</u>
B.10 How unconditioned deep basements are insulated in Northeast	57
B.11 How crawl spaces are insulated in Northeast	58
B.12 How slab-on-grade foundations are insulated in Northeast	59
B.13 How conditioned deep basements are insulated in Midwest	61
B.14 How unconditioned deep basements are insulated in Midwest	62
B.15 How crawl spaces are insulated in Midwest	63
B.16 How slab-on-grade foundations are insulated in Midwest	64
B.17 How conditioned deep basements are insulated in West	66
B.18 How unconditioned deep basements are insulated in West	67
B.19 How crawl spaces are insulated in West	68
B.20 How slab-on-grade foundations are insulated in West	69
B.21 How conditioned deep basements are insulated in Northwest	71
B.22 How unconditioned deep basements are insulated in Northwest	72
B.23 How crawl spaces are insulated in Northwest	73
B.24 How slab-on-grade foundations are insulated in Northwest	74

ABSTRACT

For almost 10 years the U.S. Department of Energy (DOE) has sponsored a small research effort with the objective of working with the building industry to see that cost-effective foundation insulation levels are installed in all U.S. buildings. One of the first discoveries in 1983-84 was that less than 5% of the existing buildings had foundation insulation and less than 30% of new construction included foundation insulation. After producing foundation handbooks, actively working with energy code and standards groups (ASHRAE and Council of American Building Officials: Model Energy Code Committee), conducting field experiments, and developing computer models for predicting energy savings has any measurable progress been made toward the fulfillment of this DOE objective? Also, in order to derive maximum energy savings impact for this ongoing research activity, market feedback of progress toward attainment of the objective is needed. Using the network of building experts available to the Building Thermal Envelope Systems and Materials program, a short mail survey was developed, administered, and results analyzed. This study concludes that foundation insulation usage on new residential buildings has increased from 1982 levels of around 25% to 1992 levels of around 50%. Government handbooks and recent changes in local enforced codes and standards are identified as major contributors to this improvement. Progress has been made but more is needed to capture the remaining 40% of the foundations that should be insulated. Several issues are reported as obstacles that need to be overcome to capture the remainder of the foundation market.

EXECUTIVE SUMMARY

Background

In the early 1980s residential foundation efficiency lagged behind above-grade envelope construction practices. The U.S. Department of Energy (DOE) recognized this discrepancy and developed a research program aimed at accelerating building industry acceptance of energy-efficient foundations. This study attempts to determine how much more foundation insulation is used in the early 1990s compared to the early 1980s. This study also provides needed market feedback on progress toward the attainment of an important DOE research goal. This information could be used to sharpen the focus of future building foundation research.

Objective

The two objectives of this report are (1) to obtain an estimate of the progress made toward the DOE building foundation research project goal of working with the building industry to see that cost-effective foundation insulation levels are installed in residential U.S. buildings, and (2) to sharpen the focus of future research in this area.

Approach

The approach taken was to develop and administer a mail survey. The network of corresponding building experts available to the Building Thermal Envelope Systems and Materials Program provided representation of all major U.S. geographic regions. This report presents the results for all 43 individuals who responded to this survey in six major U.S. regions.

Results

In 1982, only 26% of the conditioned basements built were insulated, compared with 54% in 1992. In 1982, only 15% of respondees reported enforced building codes were in place requiring foundation insulation, but in 1992, 56% reported the presence of an enforced code. Of those basement walls insulated, about half were insulated on the interior basement wall surface; the other half on the exterior. A total of 67% of builders in the Southeast and Northeast indicated that insect control impacted foundation insulation decisions, but this was not an issue in the Midwest or Northwest. When asked what motivated the application of foundation insulation, the two major motivators mentioned were: to be energy efficient (36%) and to meet energy codes (32%). Government handbooks (42%) were cited as the number one major source for foundation insulation decisions. The foundation (43%) and moisture control (39%) handbooks were the most frequently cited specific references.

Conclusions

This study concludes that foundation insulation usage on new residential buildings increased from 1982 levels of around 25% to 1992 levels of around 50%. Government handbooks and recent changes in local enforced codes and standards were identified as major contributors to this improvement. Progress has been made but more is needed to capture the remaining 40% of the foundations that should be insulated. Several issues are reported as obstacles that need to be overcome to capture the remainder of the foundation market.

In the mid 1980s, a major reason most builders were not insulating foundations was a "lack of information and clear guidance." The development of the foundation handbooks and incorporation of research results into national and state codes changed this. These survey results suggest that a lack of information is no longer the major problem. A more

dedicated focus to practical cost-effective technology development and demonstration could make a difference in capturing the remaining 40–50% of foundations that should be insulated.

1. INTRODUCTION

In the early 1980s, few building energy codes were required and even fewer jurisdictions enforced building foundation insulation. Were foundations better insulated in 1992 than in the early 1980s? What kept every new building foundation from having cost-effective levels of insulation? These are just a few of the questions that require insight in order to evaluate the effect of past U.S. Department of Energy (DOE) foundation research and better determine future needs. The major objective of the DOE Building Foundations Research has been to lead building contractors to cost-effective, energy-efficient building foundations on all U.S. building stock.

This study attempts to identify the particular tools and methods currently used by builders, consultants, and architects in different regions of the United States to develop foundation designs. The study makes a comparison of the difference in insulation methods and levels used in 1982 compared with those used in 1992. The survey attempts to solicit those impediments that are preventing energy-efficient foundations from attaining universal acceptance across all regions of the U.S. where foundation efficiency is a good investment.

2. PROJECT DESCRIPTION

One objective of this marketing research project was to determine the impact of DOE foundations research over the last ten years. This included the effect of government handbooks, ASHRAE 90.2P, and Model Energy Code (MEC) changes of October 1988. We approached the project by collecting available data, selecting a target audience, developing and administering a mail survey, and analyzing the results. We wanted a representative target audience that would be illustrative of the entire United States. We chose the recipients of the survey because they had previous correspondence with the Building Thermal Envelope Systems and Materials Program. We sent the survey to each recipient, along with an informational letter, and a no-postage-required return envelope.

We sent the survey to people of many different professions, and asked each person to identify himself or herself. Each recipient of the survey was asked to provide information on foundation insulation representative of buildings in their geographic area. The survey was designed to produce comparative data for analysis. The majority of the questions requested information be given for both 1982 and 1992 so that data could be compared and differences in insulation practices distinguished between the past and the present. Appendix A shows the foundation insulation survey form we distributed.

3. DISCUSSION OF COMPOSITE RESULTS

3.1 RESPONDENTS

We sent the survey to 400 individuals on the ORNL Building Thermal Envelope Systems and Materials Program mailing list, and 43 individuals responded. In general, this group represents building experts consisting of lead builders, building material suppliers, and researchers. There was an even distribution of respondents from each of the seven regions of the United States with the exception of the Southwest, which had only one respondent. Figure 1 shows the regions used to evaluate different parts of the U.S., and Fig. 2 shows the percentages of major disciplines that responded to this survey. The occupations of the respondents varied; most respondents were engineers, and the least were builders. This was not a statistically balanced sample. We weighted the responses equally, but this could introduce errors because an answer from a respondent from an area with a great deal of new construction was weighted the same as one from an area with very little new construction.

3.2 INSULATION APPLICATIONS: YESTERDAY AND TODAY

Question 2 dealt with the type, quantity, and location of insulation applied to different types of foundations. From 1982 to 1992 there was a 28% increase in various insulation techniques for conditioned deep basements. For unconditioned deep basements there was a 24% increase in insulation applications from 1982 to 1992. There was a 25% increase in insulation applications in crawl spaces, and a 43% increase in insulation application in slab-on-grade foundations. The following analysis is representative of all of the respondents. Section 4 discusses the regional data.

ORNL-DWG 92-4808

Fig. 1. Map of U.S. showing geographic regional responses analyzed.

Please indicate which discipline best identifies your occupation or research.

ENGINEER	ARCHITECT	BUILDER	ENERGY OFFICER	EDUCATOR	CONTRACTOR	CONSULTANT	OTHER
11	6	1	2	6	6	9	8
23%	12%	2%	4%	12%	12%	19%	16%

RESULTS: QUESTION 1

N=43

other:

VP-Marketing
 Sales Manager-Electric Utilities
 Polyurethane Foam Chemical Manufacturer
 Specialty Products Manager
 Mkt. Development Manager
 Researcher
 Former Building Official
 Energy Specialist

PERCENT OF TOTAL

Fig. 2. Breakdown of the respondents.

3.2.1 Basement Insulation

3.2.1.1 Conditioned basements

Table 1 shows the total composite average of the 31 respondents to this question. In 1982, only 26% of the conditioned basements built were insulated, compared with 54% in 1992. In 1992, of the basements that were insulated, about half were insulated on the exterior of the basement wall, the other half on the interior surface. Of those walls insulated on the exterior, 40% were insulated only on the top portion and 60% were insulated uniformly across the entire wall.

Although the percent of basement walls constructed with pressure treated wood in 1992 was under 10%, the data indicate that about 25% were left uninsulated, 25% were insulated to R-11, 25% were insulated to R-19, and 25% were insulated to R-30.

3.2.1.2 Unconditioned basements

Table 2 shows the total composite response to the question asking how unconditioned basement walls are insulated in their area. In 1982, only 12% of unconditioned basements were insulated, compared with 38% in 1992. Of those unconditioned basement walls that were insulated, the percentage breakdown between interior and exterior was about the same as that reported for conditioned basements.

In 1982, 41% of floors had no insulation separating the unconditioned basement space, compared with 32% in 1992. We are not sure if this means that there is no insulation in the walls or the basement ceiling of these basements, because some of those 32% may have insulation in the basement walls.

TABLE 1. How are you or others in your area insulating – Conditioned Deep Basements? (Percent of total)*

Configuration	Description	1982			1992		
		INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION	INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION
A. Concrete or masonry foundation walls with exterior or interior insulation
Exterior: half wall	NO INSULATION	☐	74%		☐	46%	
	4 FT:R-5 RIGID	☐	2	c	☐	4	c
	4 FT:R-10 RIGID	☐	2	c	☐	6	c
	OTHER _____	☐	0	-	☐	2	b, d
Exterior: full wall	8 FT:R-5 RIGID	☐	3	c	☐	5	c
	8 FT:R-10 RIGID	☐	3	c	☐	5	c
	8 FT:R-15 RIGID	☐	0	-	☐	4	e
	8 FT:R-20 RIGID	☐	0	a	☐	2	c
	OTHER _____	☐	6	-	☐	1	d
Interior: full wall	8 FT:R-6 RIGID	☐	1	a	☐	2	a
	8 FT:R-8 RIGID	☐	2	a, c	☐	5	a, c
	8 FT:R-11 BATT	☐	3	b	☐	5	b
	8 FT:R-19 BATT	☐	3	b	☐	7	b
	OTHER _____	☐	1	b	☐	6	b
B. Pressure-treated wood foundation walls
Wood: full wall	NO INSULATION	☐	21%		☐	28%	
	8 FT:R-11 BATT	☐	14	b	☐	21	b
	8 FT:R-19 BATT	☐	17	b	☐	26	b
	8 FT:R-30 BATT	☐	24	b	☐	25	b
	OTHER _____	☐	24	-	☐	0	-
			100%				
			100%				

*Results: Question 2

N = 31

Note: Each percentage represents the average percentage of buildings indicated as insulated this way by the total respondents. Each letter represents the type of insulation most frequently indicated as used by the respondents. A dash represents no available data.

Table 2. How are you or others in your area insulating – Unconditioned Deep Basements? (Percent of Total)*

Configuration	Description	1982			1992		
		INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION	INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION
A. Concrete or masonry foundation walls with exterior or interior insulation
Exterior: half wall		88%			62%	
	NO INSULATION	☐			☐		
	4 FT:R-5 RIGID	☐	1	c	☐	3	a
	4 FT:R-10 RIGID	☐	5	c	☐	4	c
	OTHER _____	☐	0	-	☐	2	d
Exterior: full wall						
	8 FT:R-5 RIGID	☐	1	a, c	☐	7	a, c
	8 FT:R-10 RIGID	☐	1	c	☐	3	c
	8 FT:R-15 RIGID	☐	0	-	☐	0	-
	8 FT:R-20 RIGID	☐	0	-	☐	0	-
	OTHER _____	☐	0	e	☐	1	e
Interior: full wall						
	8 FT:R-6 RIGID	☐	0	c	☐	1	a
	8 FT:R-8 RIGID	☐	1	b	☐	3	b
	8 FT:R-11 BALL	☐	0	b	☐	2	b
	8 FT:R-19 BATT	☐	3	b	☐	6	b
	OTHER _____	☐	0	b	☐	6	b
	B. Pressure-treated wood foundation walls						
		100%		100%
Wood: full wall						
	NO INSULATION	☐	26%		☐	28%	
	8 FT:R-11 BATT	☐	18	b	☐	14	b
	8 FT:R-19 BATT	☐	26	b	☐	20	b
	8 FT:R-30 BATT	☐	30	b	☐	22	b
	OTHER _____	☐	0	-	☐	16	b
C. Concrete or masonry foundation walls with ceiling insulation							
		100%		100%
Ceiling						
	NO INSULATION	☐	41%		☐	32%	
	8 FT:R-11 BATT	☐	21	b	☐	20	b
	8 FT:R-19 BATT	☐	26	b	☐	21	b
	8 FT:R-30 BATT	☐	0	-	☐	7	b
	OTHER _____	☐	12	d	☐	20	d
		100%		100%			

*Results: Question 2

N = 25

Note: Each percentage represents the average percentage of buildings indicated as insulated this way by the total respondents. Each letter represents the type of insulation most frequently indicated as used by the respondents. A dash represents no available data.

3.2.2 Crawl Space

Table 3 shows the composite result of the 30 respondents who indicated they had some crawl spaces in their area. In 1982, 20% of crawl spaces had insulation either in the ceiling or on the walls of all nonvented crawl spaces, but this figure increased to 45% in 1992. When unvented crawl space walls were insulated, 80% of the time the insulation was on the inside wall in 1992. In 1982 and in 1992, only 27–33% of vented crawl spaces had insulation in the ceiling. The wording of this question did not enable the analysis to determine the percentage of crawl spaces that are ventilated and what percent are not ventilated.

3.2.3 Slab-on-Grade

Table 4 shows the composite result for the 23 respondents who indicated there were some slab-on-grade foundations in their area. In 1982, only 17% of slab-on-grade foundations were believed to have at least some insulation, but this figure increased to 60% in 1992. The data indicate that of those insulated in 1992, 12% were insulated on the exterior of the foundation wall. The most common insulation location was on the inside vertical surface of the foundation wall (32%). The dominant material used to insulate slabs was XEPS ("c") followed by EPS ("a"). The occasional indication that batts ("b") were the dominant material used to insulate slab edges suggested there may have been some confusion by several respondents when asked to identify insulation type.

3.3 STRUCTURAL MATERIALS

Poured concrete was indicated most frequently as the type of structural material used (54%) and light concrete blocks were indicated least frequently (6%). Question 3 should have specifically requested the type of structural material used to construct crawl space and basement walls. We believe that the slab-on-grade foundation, which is poured concrete, tends to overstate the percent of poured concrete used to construct foundation walls. The

**Table 3. How are you or others in your area insulating – Crawl Spaces?
(Percent of Total)***

Configuration	Description	1982			1992		
		INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION	INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION
A. Unvented crawl space - concrete or masonry foundation walls with exterior or interior insulation
Exterior: vertical	NO INSULATION	☐	80%	_____	☐	55%	_____
	2 FT:R-5 RIGID	☐	2	c	☐	4	c
	2 FT:R-10 RIGID	☐	3	c	☐	3	c
	OTHER _____	☐	1	-	☐	2	c
Interior: vertical	2 FT:R-5 RIGID	☐	2	a, c	☐	6	a, c
	2 FT:R-10 RIGID	☐	3	c	☐	6	c
	OTHER _____	☐	2	b	☐	4	b
Interior: vertical and horizontal	2 FT/2 FT:R-5 RIGID	☐	3	-	☐	2	c
	2 FT/4 FT: R-5 RIGID	☐	3	c	☐	5	c
	2 FT/2 FT:R-10 RIGID	☐	0	-	☐	4	c
	2 FT/4 FT: R-10 RIGID	☐	0	-	☐	6	b
	OTHER _____	☐	1	b	☐	3	b
			100%		100%		
B: Unvented crawl space - pressure-treated wood foundation walls
Within wood and wall	NO INSULATION	☐	98%	_____	☐	90%	_____
	2 FT: R-11 BATT	☐	1	b	☐	4	b
	2 FT: R-19 BATT	☐	1	b	☐	4	b
	OTHER _____	☐	0	-	☐	2	e
			100%		100%		
C: Vented crawl space - concrete or masonry foundation walls with ceiling insulation
Ceiling	NO INSULATION	☐	73%	_____	☐	67%	_____
	R-11 BATT	☐	11	b	☐	10	b
	R-19 BATT	☐	8	b	☐	8	b
	R-30 BATT	☐	4	b	☐	5	b
	OTHER _____	☐	4	d	☐	10	b

*Results: Question 2

N = 30

Note: Each percentage represents the average percentage of buildings indicated as insulated this way by the total respondents. Each letter represents the type of insulation most frequently indicated as used by the respondents. A dash represents no available data.

Table 4. How are you or others in your area insulating -- Slab-on-Grade Foundations ? (Percent of Total)*

Configuration	Description	1982			1992		
		INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION	INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION
Exterior: vertical	NO INSULATION	☐	83%		☐	40%	
	2 FT: R-5	☐	1	a	☐	4	a
	2 FT: R-10	☐	2	c	☐	6	c
	4 FT: R-5	☐	1	c	☐	3	c
	4 FT: R-10	☐	1	c	☐	2	c
	4 FT: R-15	☐	1	d	☐	0	a
	4 FT: R-20	☐	0	-	☐	3	c
	OTHER _____	☐	0	-	☐	1	d
Interior: vertical	2 FT: R-5	☐	1	a	☐	4	a
	2 FT: R-10	☐	1	c	☐	3	c
	4 FT: R-5	☐	0	c	☐	3	c
	4 FT: R-10	☐	1	b	☐	2	c
	4 FT: R-15	☐	0	-	☐	0	-
	4 FT: R-20	☐	1	b	☐	7	b
	OTHER _____	☐	0	-	☐	1	d
Interior: horizontal	2 FT: R-5	☐	1	a	☐	3	a
	2 FT: R-10	☐	1	a	☐	4	c
	4 FT: R-5	☐	0	c	☐	2	c
	4 FT: R-10	☐	0	-	☐	4	c
	OTHER _____	☐	1	d	☐	1	d
Exterior: horizontal	2 FT: R-5	☐	1	a	☐	2	a
	2 FT: R-10	☐	3	c	☐	4	c
	4 FT: R-5	☐	0	-	☐	0	c
	4 FT: R-10	☐	0	c	☐	1	c
	OTHER _____	☐	0	-	☐	0	c

*Results: Question 2
N = 23

100%

100%

Note: Each percentage represents the average percentage of buildings indicated as insulated this way by the total respondents. Each letter represents the type of insulation most frequently indicated as used by the respondents. A dash represents no available data.

What kind of structural materials are used?

WOOD	CONCRETE BLOCKS	LIGHT CONCRETE BLOCKS	POURED CONCRETE
8%	32%	6%	54%

RESULTS: QUESTION 3
N=38

PERCENT OF TOTAL

Fig. 3. Foundation structural materials used.

composite data, shown in Fig. 3, suggest that the largest single structural material used, following poured concrete, is normal weight concrete blocks (32%). Other market data suggest that wood foundations make up 2% of structural materials used for foundations, so the 8% for wood found in this survey is high.

3.4 INSECT CONTROL IMPACTS

One frequently voiced reason why foundation insulation is not installed is the concern that insect control around building foundations will be compromised. Several termite control contractors will not guarantee their work when exterior insulation extends above grade, providing hidden passage of termites to above-grade wood.

The results from Question 4 (shown in Fig. 4) clearly indicate that this is predominantly a concern in the southern United States. The composite data indicate that only 32% feel this is a concern in their area. However, 57% of the seven respondents from the southeast and southwest regions were concerned about foundation insulation location affecting insect-control techniques. With the predominance of monolithic poured slab-on-grade foundations in the South, as well as increasing health concerns, it is clear that many slab edges will not be insulated without an innovative technique for insulating this type of foundation. Pest control operators want a perimeter vision strip on the exterior edge of the foundation.

3.5 PROTECTIVE COVERING

The added task of installing a suitable protective covering for the above-grade portion of exterior-applied foundation insulation was another major reason builders often cited when asked why they didn't insulate foundations. Figure 5 shows the most common type of covering is stucco (35%), followed by metal flashing (18%) and pressure treated wood (12%). Surprisingly, three respondents indicated they installed no protection, despite the fact that U.V. and mechanical abuse is likely to reduce the useful life of the insulation.

Does insect control impact foundation insulation decisions?

YES	NO
12	26
32%	68%

RESULTS: QUESTION 4
N=38

Comments:

YES

- That's why knowledgeable builders poison the soil around the foundation. (Penn.)
- (Cal.) (2)
- Because of possibility of termites getting in back of insulation, and because some pest control companies will not guarantee their work when insulation is used, we use pressure treated foundation if client allows-or sparfic insulated blocks. (NH)
- For some builders. (Me.)
- Perceived problems with rotting and termites both favor Masonry foundations for most clients. (Ga.)
- (Vir.)
- On the west coast. (Can.)
- Strongly. (Ill.)
- Completely, this is an extremely important situation for us. (SC)
- (Fla.)
- (Mass.)

NO

- (Wis.)
- (Wash.)
- (Ky.)
- (Tenn.)
- (Kan.)
- (Neb.)
- (Minn.) (4)
- (Ore.) (3)
- (DC)
- (NJ)
- (Ark.)
- (Col.) (2)
- (Oh.)
- (Penn.)
- (Id.)
- (Ga.)
- (Ill.) (2)
- We have carpenter ants which have attacked all plastic foams as well as wood, but no termites. (Ark.)
- Heating + Cooling Degree Day impact decisions. (Fla.)

Fig. 4. Does insect control impact foundation insulation?

If you install insulation on the outside, what do you use for protective covering for the above grade portion?

STUCCO	PAINT	METAL FLASHING	PRESSURE TREATED WOOD	PLASTIC LAMINATE	NOTHING	OTHER
14	4	7	5	3	3	4
35%	10%	18%	12%	8%	7%	10%

RESULTS: QUESTION 5
N=27

- Other:
- Elastomeric Coating with reinforcement
 - Metal siding
 - InsulGuard Protection Board
 - Normally left up to the subcontractor

PERCENT OF TOTAL

Fig. 5. What is used to protect exterior foundation insulation which extends above grade?

We received several comments regarding the need for further research on enhancing the durability of various protective covering systems. One respondent noted: "it has been my experience that stucco paint as protectors is not a permanent solution and fails within 2-3 years due to freeze/thaw cycles in Wisconsin." Another respondent observed that "many builders lack confidence in protective coverings for exterior insulation (high costs, lack of durability, aesthetic concerns)."

No single coating material seems to dominate. Readily available materials tend to be chosen more often than specialty products designed exclusively for this application.

3.6 ENERGY CODES

Figure 6 shows the composite results to Question 6, which examined the role of building energy codes and their enforcement in the increasing use of foundation insulation on new construction over the last ten years.

For 1982 only 14% of respondents reported enforced building codes; in 1992, 56% reported the presence of an enforced code. It is interesting to look back at the increasing use of insulation reported in Question 2. The average increase in use of any type of foundation insulation rose from 17-26% to 45-60%. There appears to be a strong correlation between enforced codes requiring foundation insulation and actual foundation insulation application.

Because DOE research activities over the last ten years have been used as the technical basis for increasing several national and state energy codes and standards, some credit for this increase in energy codes can justifiably be attributed to DOE efforts. Yet, in 1992, a large percentage of respondents (44%) still reported no enforced foundation insulation requirement in their area, and responses to Question 2 indicated that 40-55% of the foundations were still not getting insulated.

Are codes requiring foundation insulation enforced in your area?

1982	
YES	NO
5	32
14%	86%

RESULTS: QUESTION 6A
N=34

1992	
YES	NO
20	16
56%	44%

NEITHER YEARS: Tenn., Fla. (2), Kan. (2), Vir., Ore., Ga. (3), Cal., Penn., Ill., SC, Oh.

Fig. 6. Is foundation insulation enforced by local codes?

3.7 HOW MUCH INSULATION?

The second half of Question 6 generated some interesting information. One respondent reported that if you convert basements into habitable space in New Hampshire, the walls must be insulated. If this requirement could be successfully enforced nationwide, it would capture a large fraction of the existing building stock that currently doesn't have basement insulation. Unfortunately, owners frequently convert unconditioned basements to conditioned space and install inadequate insulation levels.

Another respondent noted that Wisconsin has just changed its code to require basement floor insulation. No available study has been conducted that has convincingly shown basement floor insulation is cost effective from an annual energy savings perspective, although several studies have claimed various degrees of thermal comfort enhancement.

Based on several comments from the Northwest, the most extensive levels of foundation insulation are required in this area, even more than in Wisconsin, Minnesota, and New England.

A final observation is that there are varying degrees of code enforcement, even within the same area. Figure 7 shows a listing of all the comments received from respondents to Question 6.

3.8 WHAT MOTIVATES FOUNDATION INSULATION DECISIONS?

Question 7 asked respondents if the insulation practice had changed in their area from 1982 to 1992, and what had influenced these changes. This question attempted to identify what succeeded in motivating changes in insulation practice. Figure 8 shows results and comments resulting from this question. Obviously, enforced codes (32%) and information that helps designers to economically justify the first cost of foundation

If so, how much insulation is required? Please explain.

1982:

- I don't believe it was required. (Wis.)
- It depends on the town and the building inspector. 1986 State Energy requires R-19 in floors over unheated basements. You have option of insulating basement ceiling or exterior foundation wall, inside or outside. If basement is converted to habitable space foundation walls must be insulated to R-18. (NH)
- R-10 - 2 ft. (Ga.)
- R-8. (Can.)
- Minimum Property Standards-above grade walls only, R-20. (DC)
- Some house R-19 floor. (Ore.)
- Builder/Buyer specification or option. (Fla.)
- Varied depending on financing [0 to R-11]. (Id.)
- R-5 minimum. (Ill.)

1992:

- 1" foam on exterior of foundations. New for 1992 in WI is foam is required under basement floors.
- R-11 - R-19 in floor/slab is R-7, if one insulates the crawl wall-computer program determines the R Value. (Cal.)
- Foundation to R-10 on floor, over unheated basement to R-19. R-10 to frost line on some residences (owner-built/custom built-exempt) Ashrae 90.1 for commercial or institutional new construction-but enforcement is severely limited. (Me.)
- Exposed crawl spaces are now required to be insulated. (Neb.)
- R-10 - 2 ft. (Ga.)
- R-10 to frost line or R-5 over entire wall. (Minn.)
- R-12 soon to be R-20 (maybe). (Can.)
- Under floor/crawl space R-25, slab on grade R-10, below grade basement walls R-21. (Ore.)
- R-5 for 8 ft. wall unconditioned basement or R-10 down to frost line (approx. 4'). (Minn.)
- MODEL ENERGY CODE provisions. (DC)
- Municipalities enforce UBC, but there is a booklet which describes the Alaska State thermal standards which are indexed by region and HDD. (Ark.)
- R-10. (Minn.)
- R-10. (Ark.)
- All houses R-25 or above. (Ore.)
- Code doesn't allow foundation insulation for crawl spaces. (Ore.)
- Usually minimum levels-builder/buyer increases levels in some mkt. (Fla.)
- State minimum R-19. (Id.)
- R-5 minimum. (Ill.)
- Only one city in our county has a code requirement for foundation insulation, R-10. (Ill.)

RESULTS: QUESTION 6B

N=24

Fig. 7. How much foundation insulation is required by local codes?

If the insulation practice has changed in your area from 1982 to 1992, what influenced this change?

36%	To be more energy/cost efficient.	(20)
32%	Passing of new energy codes in your state.	(18)
11%	Others in your local community have insulated.	(6)
9%	Utility/state education-incentive:	(5)
12%	Other reasons:	(7)

- Trouble with old practices.
- Higher quality construction now as compared to 1982.
- My selling them on extra.
- Push by foam suppliers to insulate crawl walls rather than the floor.
- Manufacturers needing a market extension due to high degree of competition in historical sectors.
- Selling houses.
- Knowledgeable home buyers.

RESULTS: QUESTION 7
N=25

PERCENT OF TOTAL

Fig. 8. What has caused foundation insulation practices from 1982 to 1992?

insulation (36%) played a major role in the increasing use of foundation insulation. A popular write-in response not listed as an option on the survey was the impact of utility and state education and incentive programs (9%).

3.9 INFORMATION SOURCES

Question 8 asked what information source was used when it was time to specify foundation insulation. Figure 9 shows results from this question. The largest single source used when deciding on foundation insulation guidance was government handbooks (41%), and the Foundation and Moisture Control Handbooks were cited most frequently. Energy codes were the source 15% of the time, and research papers served as sources 11% of the time.

Question 9 tried to determine what could be done to attack those areas where foundation insulation is still not standard practice. The results shown in Fig. 10 suggest there is no single reason for not installing foundation insulation. In the mid 1980s, people frequently complained that there wasn't sufficient information, but that doesn't seem to be the problem in 1992. Reducing the added first cost would help encourage foundation insulation, and providing additional information on the relative maintenance cost of insulated versus uninsulated foundations might also make a difference. We base this observation on several of the comments. One respondent remarked that there was "no available correlation between cost of insulating and cost of retrofitting and repair (cracks, etc.)." Another respondent observed that "there is a lack of effective trouble-free systems."

From this point, foundation research should focus on technology development and demonstration instead of providing additional performance information on popular commercially available foundation systems.

What do you refer to when insulating, or advising others?

41%	Government handbooks:	Moisture Control Handbook	39%	(17)
		Bld. Foundation Design Handbook	20%	(9)
		ZIP Program	4%	(2)
		Insulation Fact Sheet from DOE	14%	(6)
		Builder's Foundation Handbook	23%	(10)
21%	Magazine/news articles	(13)		
15%	Energy codes	(9)		
3%	Research papers	(2)		
11%	Other reasons	(7)		
8%	Personal experience	(5)		
1%	Suggestions from neighbors/friends	(1)		

- State of Maine publication.
- Manuals of practice.
- Our product brochures.
- Utility requirement to get best rates.

RESULTS: QUESTION 8
N=38

PERCENT OF TOTAL

Fig. 9. What information source do you use when deciding on foundation insulation?

If you or others in your area have not changed foundation insulation levels in the 1990s, why?

27%	Had already been insulating adequately in the 1980s.	(7)
8%	Not enough information available on insulation.	(2)
11%	Have information, but do not understand the benefits of insulating.	(3)
19%	Foundation insulation is not cost effective.	(5)
35%	Other reasons:	(9)

- Only progressive builders will follow my proposals.
- We receive a benefit in the summer with no insulation. Our Cooling Degree Days are 4 times our Heating Degree Days.
- A/C/Heating/Air Circulation + Mass contact are to be considered on a case by case basis.
- No correlation between cost of insulating and cost of retrofitting & repair (cracks, etc.).
- We have changed.
- Training the public of their need-lack of time.
- Not forced to.
- Moisture, insects, molds, and rodents are real problems with foundation insulations.
- Lack of an effective trouble-free "system".

RESULTS: QUESTION 9
N=23

PERCENT OF TOTAL

Fig. 10. Why has there been no change in foundation insulation levels in some areas from 1982 to 1992?

3.10 RESEARCH ISSUES

Question 10 was meant to help determine what research could lead to more complete acceptance of energy-efficient foundations. We identified several good suggestions for future work in the respondents' comments, which are shown in Fig. 11. Promising research areas gleaned from the comments are

1. Need for guidance on when not to ventilate crawl spaces.
2. How much insulation should be used around heated slabs.
3. Quantify the added benefit of thermal comfort resulting from foundation insulation above and beyond those levels justified solely on annual energy savings.
4. Develop a more cost-effective protective coating for exterior-applied insulations.
5. Positively pressurized basements and crawl spaces need study to determine optimum construction technique as well as moisture and radon control effectiveness.
6. Spray-applied foundation insulations need study (foam, cellulose, and fiberglass).

Are there any particular issues you think need to be addressed to help you better insulate or advise others on building foundations in the future?

Location of Respondents Comments

- PA** *—I need more comparative data—what gain does insulation have on comfort and economy?*
- WI** *—It has been my experience that stucco paint on protectors are not permanent solutions and fail within 2-3 years due to freeze/thaw cycles here.*
- ME** *—Insect damage; moisture control; more education is needed; many builders lack confidence in coating for exterior insulation (high costs, lack of durability, esthetics concerns).*
- TN** *—Please make your upcoming publication contractor-friendly. Scientific papers are useless without simple, obvious instructions for implementation.*
- FL** *—Quality Control Application of Materials.*
- KS** *—Should crawl spaces be vented? Do vents allow moisture to enter crawl spaces, causing problems?*
- FL** *—You need to access Degree Day information.*
- MN** *—Insulating under heat slabs & in-ground heating systems.*
- CA** *—Use Spray Applied Polyurethane Foam! on the exterior - stop promoting old concepts through building codes!*
- MN** *—More standards on a national level like the State of MN Energy Dept. has implemented.*
- DC** *—Need information on shallow foundations.*
- AK** *—Should vapor retarders be used under poured slabs and footings?*
- MN** *—Water proof between interior insulation & block of concrete.*
- AK** *—Better understanding of need for crawl-space venting, and alternatives to crawl-space venting. (Few homeowners shut crawlspace vents in winter, yet insulation location is typically crawlspace walls, not floor).*
- KS** *—Payback on investment.*

Fig. 11. What research is needed in this area?

RESULTS: QUESTION 10—CONTINUED

OR	—Need for ventilation in crawl spaces.
NJ	—Code requirements & approvals of new techniques, better literature, information and design manuals.
CO	—Need continuing publicity on the effectiveness of basement insulation.
GA	—Ground temperature and transmission rates.
PA	—More local workshops for builders.
SC	—New foundation recommendations are a problem for us. <i>We find building crawl spaces and floor insulation is a best bet considering energy, moisture, insect inspections, etc.</i>
IL	—1) <i>Impact of insulation on drainage, soil moisture, condition of footing drains.</i> —2) <i>Reducing likelihood of inward bowing of unreinforced masonry basement walls.</i>
FL	—More research on the influence of moisture-vapor, liquid, and frost/solid on system performance..... <i>joint leakage and thermal bridges..with time.</i>
ID	—Public education on a massive National scale. <i>General public is just plain uninformed.</i>
IL	—Cost effectiveness-see enclosed letter.
MN	—Consider positively pressurizing foundations (basements and crawlspaces) using ventilation systems or tube fans to control moisture, radon, and backdrafting.
KS	—We would appreciate a more rigorous study of the effectiveness of wet-spray cellulose in both foundation applications and in sidewall applications. <i>It is our feeling that the product has merit and should receive fair consideration as an optional measure. (See attached letter).</i>

RESULTS: QUESTION 10

N=29

Fig. 11. (continued)

4. GEOGRAPHIC BREAKDOWN

We evaluated six of the seven regions separately from the composite data reported in Sect. 3. The small sample size prevented a meaningful evaluation for the Southwest. The results are shown graphically in Appendix B for all questions except number 2, which is in tabular form. In this section, we provide several observations about regions when their data deviates significantly from the composite data.

4.1 SOUTHEAST

Detailed results are shown in Fig. B-1 and Tables B.1-B.4. Because slab-on-grade tends to be the dominant construction in the Southeast, it is interesting to note that the respondents indicated 95% of the slabs in this area weren't insulated in new construction in 1982 and that nothing has changed in 1992, as Table B.4 shows. These results are consistent with the answer to Question 6 on whether codes are enforced, of which 88% said no in 1992.

4.2 EAST

Results are shown in Fig. B-2 and Tables B.5-B.8. The percent of conditioned basements with at least some insulation has increased in this region from 42% in 1982 to 80% in 1992. Because this area includes Washington, D.C., it is not surprising that this region more heavily depends on government handbooks to decide on how much insulation to use (60%) compared with composite average of 41%.

4.3 NORTHEAST

The six respondents from this area indicate in 1982 that almost nobody insulated conditioned deep basements (96%), compared with 66% in 1992. This suggests much energy is still being lost in this part of the country, which uses basement foundations almost exclusively. It is also interesting to note that 67% of the builders are concerned about

foundation insulation affecting insect control, despite the predominant heating climate of the region.

Government handbooks are heavily used in this region as well (67%). In 1992, 50% of the areas had no enforced foundation insulation codes.

4.4 MIDWEST

Results are shown in Fig. B-4 and Tables B.13–B.16. In 1982 only 19% of the conditioned basement walls were insulated; in 1992 53% were insulated. Insect control is not an issue when deciding on how to insulate basements in the Midwest.

4.5 WEST

Results are shown in Fig. B-5 and Tables B.17–B.20. Slab-on-grade insulation grew from 7% in 1982 to 47% in 1992. Building codes in this area were enforced in this region in 1982, and continued to be enforced in 1992.

4.6 NORTHWEST

Results from this region are shown in Fig. B-6 and Tables B.21–B.24. Insect control is not an issue when deciding on foundation insulation, but radon control is. Unvented crawl spaces are not permitted. Code enforcement increased significantly from only 11% in 1982 to 88% in 1992. This area requires more foundation insulation than any other region of the country (R-25 floor insulation, R-10 slab edge insulation, and R-21 basement wall insulation).

5. CONCLUSION

This survey reports that more foundation insulation was being placed on new construction in 1992 than was being installed in 1982, from around 25% to about 50%. It appears that stricter enforcement of foundation insulation requirements directly correlates with this increase. DOE foundation research provided the technical support for most of the changes in foundation insulation levels in national and state codes. DOE foundation research efforts also contributed significantly to this increase in energy-efficient foundations, because 41% of respondents reported that they used government handbooks to make foundation insulation decisions.

In some areas, as many as 67% of respondents reported government handbooks as major information sources. The two foundation and moisture control handbooks were most frequently cited as specific sources.

In the mid 1980s, a major reason most builders were not insulating foundations was a "lack of information and clear guidance." The development of the foundation handbooks and incorporation of research results into national and state codes changed this. These survey results reinforce the belief that a lack of information is no longer the major problem.

A more dedicated focus to practical cost-effective technology development and demonstration could make a difference in capturing the remaining 40-50% foundations that are not being insulated and should be. Several good research topics that merit further study include:

1. Need for guidance on when not to ventilate crawl spaces.
2. Optimum insulation configurations for heated slabs.
3. Quantified benefit of thermal comfort resulting from foundation insulation above and beyond those levels justified solely on annual energy savings.
4. Develop a more cost-effective protective coating for exterior-applied insulations.

5. **Positively pressurized basements and crawl spaces, optimum construction techniques, as well as moisture and radon control effectiveness.**
6. **Performance characterization of spray-applied foundation insulations (foam, cellulose, and fiberglass).**

APPENDIX A

FOUNDATION INSULATION-BTESM END-USER SURVEY

NAME: _____

ORGANIZATION: _____

CITY, STATE: _____

TELEPHONE NO.: _____ DATE _____

1.) Please indicate which discipline best identifies your occupation or research.

☐
☐
☐
☐

Engineer
Architect
Builder
State Energy Officer

☐
☐
☐
☐

Educator
Contractor
Consultant
Other, please specify _____

2.) The next few pages are referring to new buildings built in your area. Please indicate by looking at each configuration and description: the amount of insulation installed and location (by filling in the circles); the percent of new buildings insulated this way (by writing down the percentages); and the type of insulation (using the codes from the table below) for 1982 and 1992. An example has been given.

TYPE		
a.)	EPS	-Expanded Polystyrene, foam boards (white)
b.)	BATT	-Batts
c.)	XEPS	-Extruded Polystyrene, (blue, green, pink)
d.)	PI	-Polyisocyanurate
e.)	___	-Other

Example-TABLE 1: How are you insulating - Conditioned Deep Basements?

CONFIGURATION	DESCRIPTION	1982			1992		
		INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION	INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION
A: Concrete or Masonry Foundation Walls with Exterior Insulation
EXTERIOR: HALF WALL	NO INSULATION	●	50	-	○		
	4 FT:R-5 RIGID	●	40	c	●	50	c
	4 FT:R-10 RIGID	○			●	30	c
	OTHER R-4	●	10	b	●	20	a

3.) What kind of structural materials are used?

Wood _____ %
 Concrete Blocks _____ %
 Light Concrete Blocks _____ %
 Poured Concrete _____ %

4.) Does insect control impact foundation insulation decisions?

5.) If you install insulation on the outside, what do you use for protective covering for the above grade portion? _____

- a.) stucco
- b.) paint
- c.) metal flashing
- d.) pressure treated plywood
- e.) plaster laminate
- f.) other _____

6a.) Are codes requiring foundation insulation enforced in your area?

1982		1992	
YES	☐	YES	☐
NO	☐	NO	☐

6b.) If so, how much insulation is required? Please explain.

1982: _____

1992: _____

7.) If the insulation practice has changed in your area from 1982 to 1992, what influenced this change?

- ☐ To be more energy/cost efficient.
- ☐ Passing of new energy codes in your state.
- ☐ Others in your local community have insulated.
- ☐ Other reason _____

8.) What do you refer to when insulating, or advising others?

☐
☐
☐
☐

Suggestions from neighbors/friends.

Government handbooks: -----

Magazine/news articles.

Other _____

☐
☐
☐
☐
☐

Moisture Control Handbook

Building Foundation Design Handbook

ZIP Program

Insulation Fact Sheet from DOE

Builder's Foundation Handbook

9.) If you or others in your area have not changed foundation insulation levels in the 1990's, why?

☐
☐
☐
☐
☐

Had already been insulating adequately in the 1980's.

Not enough information available on insulation.

Have information, but do not understand the benefits of insulating.

Foundation insulation is not cost effective.

Other reason _____

10.) Are there any particular issues you think need to be addressed to help you better insulate or advise others on building foundations in the future?

THANK YOU VERY MUCH FOR YOUR COOPERATION, YOUR RESPONSES ARE APPRECIATED.

Table A.1. How are you insulating – Conditioned Deep Basements?

Configuration	Description	1982			1992		
		INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION	INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION
A: Concrete or masonry foundation walls with exterior or interior insulation							
Exterior: half wall	NO INSULATION	☐	_____	_____	☐	_____	_____
	4 FT:R-5 RIGID	☐	_____	_____	☐	_____	_____
	4 FT:R-10 RIGID	☐	_____	_____	☐	_____	_____
	OTHER _____	☐	_____	_____	☐	_____	_____
Exterior: full wall	8 FT:R-5 RIGID	☐	_____	_____	☐	_____	_____
	8 FT:R-10 RIGID	☐	_____	_____	☐	_____	_____
	8 FT:R-15 RIGID	☐	_____	_____	☐	_____	_____
	8 FT:R-20 RIGID	☐	_____	_____	☐	_____	_____
	OTHER _____	☐	_____	_____	☐	_____	_____
Interior: full wall	8 FT:R-6 RIGID	☐	_____	_____	☐	_____	_____
	8 FT:R-8 RIGID	☐	_____	_____	☐	_____	_____
	8 FT:R-11 BATT	☐	_____	_____	☐	_____	_____
	8 FT:R-19 BATT	☐	_____	_____	☐	_____	_____
	OTHER _____	☐	_____	_____	☐	_____	_____
B: Pressure-treated wood foundation walls							
Wood: full wall	NO INSULATION	☐	_____	_____	☐	_____	_____
	8 FT:R-11 BATT	☐	_____	_____	☐	_____	_____
	8 FT:R-19 BATT	☐	_____	_____	☐	_____	_____
	8 FT:R-30 BATT	☐	_____	_____	☐	_____	_____
	OTHER _____	☐	_____	_____	☐	_____	_____

Table A.2. How are you insulating – Unconditioned Deep Basements?

Configuration	Description	1982				1992			
		INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION		INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION	
A: Concrete or masonry foundation walls with exterior or interior insulation									
Exterior: half wall	NO INSULATION	☐	_____	_____		☐	_____	_____	
	4 FT:R-5 RIGID	☐	_____	_____		☐	_____	_____	
	4 FT:R-10 RIGID	☐	_____	_____		☐	_____	_____	
	OTHER _____	☐	_____	_____		☐	_____	_____	
Exterior: full wall	8 FT:R-5 RIGID	☐	_____	_____		☐	_____	_____	
	8 FT:R-10 RIGID	☐	_____	_____		☐	_____	_____	
	8 FT:R-15 RIGID	☐	_____	_____		☐	_____	_____	
	8 FT:R-20 RIGID	☐	_____	_____		☐	_____	_____	
	OTHER _____	☐	_____	_____		☐	_____	_____	
Interior: full wall	8 FT:R-6 RIGID	☐	_____	_____		☐	_____	_____	
	8 FT:R-8 RIGID	☐	_____	_____		☐	_____	_____	
	8 FT:R-11 BALL	☐	_____	_____		☐	_____	_____	
	8 FT:R-19 BATT	☐	_____	_____		☐	_____	_____	
	OTHER _____	☐	_____	_____		☐	_____	_____	
B: Pressure-treated wood foundation walls									
Wood: full wall	NO INSULATION	☐	_____	_____		☐	_____	_____	
	8 FT:R-11 BATT	☐	_____	_____		☐	_____	_____	
	8 FT:R-19 BATT	☐	_____	_____		☐	_____	_____	
	8 FT:R-30 BATT	☐	_____	_____		☐	_____	_____	
	OTHER _____	☐	_____	_____		☐	_____	_____	
C: Concrete or masonry foundation walls with ceiling insulation									
Ceiling	NO INSULATION	☐	_____	_____		☐	_____	_____	
	8 FT:R-11 BATT	☐	_____	_____		☐	_____	_____	
	8 FT:R-19 BATT	☐	_____	_____		☐	_____	_____	
	8 FT:R-30 BATT	☐	_____	_____		☐	_____	_____	
	OTHER _____	☐	_____	_____		☐	_____	_____	

Table A.3. How are you insulating – Crawl Spaces?

Configuration	Description	1982			1992		
		INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION	INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION

A: Unvented crawl space – concrete or masonry foundation walls with exterior or interior insulation

Exterior: vertical	NO INSULATION 2 FT: R-5 RIGID 2 FT: R-10 RIGID OTHER _____	☐ _____ ☐ _____ ☐ _____ ☐ _____	☐ _____ ☐ _____ ☐ _____ ☐ _____
Interior: vertical	2 FT: R-5 RIGID 2 FT: R-10 RIGID OTHER _____	☐ _____ ☐ _____ ☐ _____	☐ _____ ☐ _____ ☐ _____
Interior: vertical and horizontal	2 FT/2 FT: R-5 RIGID 2 FT/4 FT: R-5 RIGID 2 FT/2 FT: R-10 RIGID 2 FT/4 FT: R-10 RIGID OTHER _____	☐ _____ ☐ _____ ☐ _____ ☐ _____ ☐ _____	☐ _____ ☐ _____ ☐ _____ ☐ _____ ☐ _____

B: Unvented crawl space – pressure-treated wood foundation walls

Within wood wall	NO INSULATION 2 FT: R-11 BATT 2 FT: R-19 BATT OTHER _____	☐ _____ ☐ _____ ☐ _____ ☐ _____	☐ _____ ☐ _____ ☐ _____ ☐ _____
--	--	--	--

C: Vented crawl space – concrete or masonry foundation walls with ceiling insulation

Ceiling	NO INSULATION R-11 BATT R-19 BATT R-30 BATT OTHER _____	☐ _____ ☐ _____ ☐ _____ ☐ _____ ☐ _____	☐ _____ ☐ _____ ☐ _____ ☐ _____ ☐ _____
---	---	---	---

Table A.4. How are you or others in your area insulating – Slab-on-Grade Foundations ?

Configuration	Description	1982			1992		
		INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION	INSULATION AMOUNT AND LOCATION	PERCENT INSULATED THIS WAY	TYPE OF INSULATION
Exterior: vertical	NO INSULATION 2 FT: R-5 2 FT: R-10 4 FT: R-5 4 FT: R-10 4 FT: R-15 4 FT: R-20 OTHER _____	☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	_____ _____ _____ _____ _____ _____ _____ _____	_____ _____ _____ _____ _____ _____ _____ _____	☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	_____ _____ _____ _____ _____ _____ _____ _____	_____ _____ _____ _____ _____ _____ _____ _____
Interior: vertical	2 FT: R-5 2 FT: R-10 4 FT: R-5 4 FT: R-10 4 FT: R-15 4 FT: R-20 OTHER _____	☐ ☐ ☐ ☐ ☐ ☐ ☐	_____ _____ _____ _____ _____ _____ _____	_____ _____ _____ _____ _____ _____ _____	☐ ☐ ☐ ☐ ☐ ☐ ☐	_____ _____ _____ _____ _____ _____ _____	_____ _____ _____ _____ _____ _____ _____
Interior: horizontal	2 FT: R-5 2 FT: R-10 4 FT: R-5 4 FT: R-10 OTHER _____	☐ ☐ ☐ ☐ ☐	_____ _____ _____ _____ _____	_____ _____ _____ _____ _____	☐ ☐ ☐ ☐ ☐	_____ _____ _____ _____ _____	_____ _____ _____ _____ _____
Exterior: horizontal	2 FT: R-5 2 FT: R-10 4 FT: R-5 4 FT: R-10 OTHER _____	☐ ☐ ☐ ☐ ☐	_____ _____ _____ _____ _____	_____ _____ _____ _____ _____	☐ ☐ ☐ ☐ ☐	_____ _____ _____ _____ _____	_____ _____ _____ _____ _____

APPENDIX B

RESULTS: GEOGRAPHIC BREAKDOWN
N=8

SOUTH EAST
PERCENT OF TOTAL

1. Please indicate which discipline best identifies your occupation or research.

5. If you install insulation on the outside, what do you use for protective covering for the above grade portion?

8. What do you refer to when insulating, or advising others?

3. What kind of structural materials are used?

6. Are codes requiring foundation insulation enforced in your area?

	YES	NO
1982		100%
1992	12%	88%

6b. If so, how much insulation is required?
1982: R-10-2 ft.; builder/buyer specification.
1992: R-10-2 ft.; minimum levels.

4. Does local control impact foundation insulation decisions?

YES	NO
3	3
50%	50%

7. If the insulation practice has changed in your area from 1982 to 1992, what influenced this change?

9. If you or others in your area have not changed foundation insulation levels in the 1990's, why?

Fig B-1. Southeast response to Questions 1 and 3-9.

Table B.1. How conditioned deep basements are insulated in Southeast.

N=5 SOUTHEAST

CONDITIONED DEEP BASEMENTS		1982	1992
EXTERIOR: HALF WALL			
NO INSULATION		67%	50%
4 FT: R-5			
4 FT: R-10		6%	10% c
OTHER			
EXTERIOR: FULL WALL			
8 FT: R-5		5%	7%
8 FT: R-10		11%	7% c
8 FT: R-15			
8 FT: R-20			3% c
OTHER			
INTERIOR: FULL WALL			
8 FT: R-6			
8 FT: R-8		6%	4% d
8 FT: R-11			7% b
8 FT: R-19			
OTHER		5%	12% d
WOOD: FULL WALL			
NO INSULATION		95%	95%
8 FT: R-11			
8 FT: R-19		5%	5%
8 FT: R-30			
OTHER			

Table B.2. How unconditioned deep basements are insulated in Southeast

N=5 SOUTHEAST

UNCONDITIONED DEEP BASEMENTS		1982	1992
EXTERIOR HALF WALL			
NO INSULATION		81%	58%
4 FT R-5			
4 FT R-10	c	11%	19%
OTHER			
EXTERIOR FULL WALL			
8 FT R-5		5%	9%
8 FT R-10			
8 FT R-15			
8 FT R-20			
OTHER			
INTERIOR FULL WALL			
8 FT R-6			
8 FT R-8	d	3%	14%
8 FT R-11			
8 FT R-19			
OTHER			
WOOD FULL WALL			
NO INSULATION			
8 FT R-11			
8 FT R-19	b	100%	100%
8 FT R-30			
OTHER			
CEILING			
NO INSULATION		25%	90%
8 FT R-11	b	50%	3%
8 FT R-19			5%
8 FT R-30			
OTHER	d	25%	2%

N=5 SOUTHEAST

Table B.3. How crawl spaces are insulated in Southeast

CRAWL SPACES		1982	1992
EXTERIOR VERTICAL			
NO INSULATION			
2 FT R-5	17%	c	17%
2 FT R-10	33%	c	17%
OTHER			
INTERIOR VERTICAL			
2 FT R-5	33%		32%
2 FT R-10			
OTHER			17%
INTERIOR VERTICAL AND HORIZONTAL			
2 FT 2 FT R-5			
2 FT 4 FT R-5	17%	c	17%
2 FT 2 FT R-10			
2 FT 4 FT R-10			
OTHER			
WITHIN WOOD WALL			
NO INSULATION			
2 FT R-11	50%	b	50%
2 FT R-19	50%	b	50%
OTHER			
CEILING			
NO INSULATION	95%		
R-11	4%	b	75%
R-19			19%
R-30			
OTHER	1%	d	6%

Table B.4. How slab-on-grade foundations are insulated in Southeast.

N=4 SOUTHEAST

SLAB-ON-GRADE FOUNDATIONS		1982	1992
EXTERIOR VERTICAL			
NO INSULATION		95%	95%
2 FT R-5			
2 FT R-10			
4 FT R-5	3%	c	3%
4 FT R-10	1%	c	1%
4 FT R-15			
4 FT R-20			
OTHER			
INTERIOR VERTICAL			
2 FT R-5	1%	c	1%
2 FT R-10			
4 FT R-5			
4 FT R-10			
4 FT R-15			
4 FT R-20			
OTHER			
INTERIOR HORIZONTAL			
2 FT R-5			
2 FT R-10			1%
4 FT R-5			
4 FT R-10			
OTHER			
EXTERIOR HORIZONTAL			
2 FT R-5			
2 FT R-10			
4 FT R-5			
4 FT R-10			
OTHER			

RESULTS: GEOGRAPHIC BREAKDOWN N=5

EAST PERCENT OF TOTAL

1. Please indicate which discipline best identifies your occupation or research.

3. What kind of structural materials are used?

4. Does insect control impact foundation insulation decisions?

YES	NO
1	3
25%	75%

5. If you install insulation on the outside, what do you use for protective covering for the above grade portion?

6a. Are codes requiring foundation insulation enforced in your area?

	YES	NO
1982		100%
1992	33%	67%

6b. If so, how much insulation is required?

1982: Above grade walls only, R-20
1992: Model Energy Code provisions.

8. What do you refer to when insulating, or advising others?

9. If you or others in your area have not changed foundation insulation levels in the 1990's, why?

Fig. B-2. East response to Questions 1 and 3-9.

Table B.5. How conditioned deep basements are insulated in East

EAST

N=4

CONDITIONED DEEP BASEMENTS		1982	1992
EXTERIOR: HALF WALL			
NO INSULATION	58%		20%
4 FT: R-5	3%	a,c	a,c
4 FT: R-10			c
OTHER			
EXTERIOR: FULL WALL			
8 FT: R-5	4%	a	
8 FT: R-10	4%	c	c
8 FT: R-15			
8 FT: R-20			
OTHER	12%		
INTERIOR: FULL WALL			
8 FT: R-6			
8 FT: R-8	5%	a	a
8 FT: R-11	9%	b	b
8 FT: R-19	5%	b	b
OTHER			
WOOD: FULL WALL			
NO INSULATION	70%		10%
8 FT: R-11	7%	b	b
8 FT: R-19	5%	b	b
8 FT: R-30			c
OTHER	18%		

Table B.6. How unconditioned deep basements are insulated in East

EAST

UNCONDITIONED DEEP BASEMENTS		1982		1992	
EXTERIOR HALF WALL					
NO INSULATION		80%		60%	
4 FT R-5				4%	a
4 FT R-10				10%	c
OTHER					
EXTERIOR FULL WALL					
8 FT R-5		5%	a	5%	a
8 FT R-10				9%	c
8 FT R-15					
8 FT R-20					
OTHER		1%		1%	
INTERIOR FULL WALL					
8 FT R-6		1%	a	1%	a
8 FT R-8		10%	a	4%	a
8 FT R-11		3%	b	6%	b
8 FT R-19					
OTHER					
WOOD FULL WALL					
NO INSULATION		80%		80%	
8 FT R-11		17%	a	20%	b
8 FT R-19					
8 FT R-30					
OTHER					
CEILING					
NO INSULATION		77%		60%	
8 FT R-11		4%	b	18%	b
8 FT R-19		19%	b	22%	b
8 FT R-30					
OTHER					

Table B.7. How crawl spaces are insulated in East.

EAST

N=3

CRAWL SPACES		1982	1992
EXTERIOR: VERTICAL			
NO INSULATION		80%	50%
2 FT. R-5		2%	a 8%
2 FT. R-10			
OTHER			c 8%
INTERIOR: VERTICAL			
2 FT. R-5		2%	a 5%
2 FT. R-10			
OTHER			b 8%
INTERIOR: VERTICAL AND HORIZONTAL			
2 FT/2 FT. R-5		10%	5%
2 FT/4 FT. R-5			6%
2 FT/2 FT. R-10			c 9%
2 FT/4 FT. R-10			
OTHER		6%	1%
WITHIN WOOD WALL			
NO INSULATION		97%	75%
2 FT. R-11		3%	b 8%
2 FT. R-19			17% b
OTHER			
CEILING			
NO INSULATION		80%	40%
R-11		14%	b 19%
R-19		6%	b 32%
R-30			9%
OTHER			

Table B.8. How slab-on-grade foundations are insulated in East.

EAST

N=3

SLAB-ON-GRADE FOUNDATIONS		1982	1992
EXTERIOR: VERTICAL			
NO INSULATION			9%
2 FT: R-5		a	6%
2 FT: R-10		a	5%
4 FT: R-5			4%
4 FT: R-10			3%
4 FT: R-15			
4 FT: R-20			7%
OTHER			
INTERIOR: VERTICAL			
2 FT: R-5		a	8%
2 FT: R-10		a	5%
4 FT: R-5			5%
4 FT: R-10			
4 FT: R-15			
4 FT: R-20			
OTHER			
INTERIOR: HORIZONTAL			
2 FT: R-5		a	8%
2 FT: R-10		a	5%
4 FT: R-5			5%
4 FT: R-10			22%
OTHER			
EXTERIOR: HORIZONTAL			
2 FT: R-5		a	8%
2 FT: R-10			
4 FT: R-5			
4 FT: R-10			
OTHER			

RESULTS: GEOGRAPHIC BREAKDOWN
N=6

NORTH EAST
PERCENT OF TOTAL

1. Please indicate which discipline best identifies your occupation or research.

5. If you install insulation on the outside, what do you use for protective covering for the above grade portion?

8. What do you refer to when insulating, or advising others?

3. What kind of structural materials are used?

6a. Are codes requiring foundation insulation enforced in your area?

	YES	NO
1982	25%	75%
1992	50%	50%

6b. If so, how much insulation is required?
1982: R-10 to frostline on some residences;
1992: ASHRAE 90.1 for commercial or institutional new construction; 1986 State Energy requires R-19 in floors over unheated basements.

7. If the insulation practice has changed in your area from 1982 to 1992, what influenced this change?

9. If you or others in your area have not changed foundation insulation levels in the 1990's, why?

Fig. B-3. Northeast response to Questions 1 and 3-9.

Table B.9. How conditioned deep basements are insulated in Northeast.

N=4 NORTHEAST

CONDITIONED DEEP BASEMENTS		1982		1992	
EXTERIOR: HALF WALL					
NO INSULATION		96%		66%	
4 FT: R-5				3%	a
4 FT: R-10				3%	c
OTHER					
EXTERIOR: FULL WALL					
8 FT: R-5				2%	c
8 FT: R-10		1%	c	5%	c
8 FT: R-15					
8 FT: R-20					
OTHER					
INTERIOR: FULL WALL					
8 FT: R-6				2%	
8 FT: R-8				2%	c
8 FT: R-11				3%	b
8 FT: R-19		3%	b	14%	b
OTHER					
WOOD: FULL WALL					
NO INSULATION		90%		90%	
8 FT: R-11					
8 FT: R-19		5%		5%	
8 FT: R-30		5%	b	5%	b
OTHER					

Table B.10. How unconditioned deep basements are insulated in Northeast.

N=4 NORTHEAST

UNCONDITIONED DEEP BASEMENTS		1982	1992
EXTERIOR: HALF WALL			
NO INSULATION		95%	85%
4 FT. R-5			
4 FT. R-10			1%
OTHER			
EXTERIOR: FULL WALL			
8 FT. R-5			3%
8 FT. R-10		2%	5%
8 FT. R-15			
8 FT. R-20			
OTHER			
INTERIOR: FULL WALL			
8 FT. R-6			
8 FT. R-8			
8 FT. R-11			1%
8 FT. R-16		3%	5%
OTHER			
WOOD: FULL WALL			
NO INSULATION			
8 FT. R-11			
8 FT. R-19			
8 FT. R-30		100%	100%
OTHER			
CEILING			
NO INSULATION		70%	70%
8 FT. R-11		19%	8%
8 FT. R-19		11%	15%
8 FT. R-30			7%
OTHER			

Table B.11. How crawl spaces are insulated in Northeast.

N=4 NORTHEAST

CRAWL SPACES		1982		1992	
EXTERIOR: VERTICAL					
NO INSULATION		73%		93%	
2 FT. R-5		3%	a	2%	a
2 FT. R-10					
OTHER		2%			
INTERIOR: VERTICAL					
2 FT. R-5				2%	a
2 FT. R-10		15%	c	3%	c
OTHER					
INTERIOR: VERTICAL AND HORIZONTAL					
2 FT/2 FT. R-5					
2 FT/4 FT. R-5		7%	a		
2 FT/2 FT. R-10					
2 FT/4 FT. R-10					
OTHER					
WITHIN WOOD WALL					
NO INSULATION		95%		95%	
2 FT. R-11					
2 FT. R-19		5%	b	5%	b
OTHER					
CEILING					
NO INSULATION		80%		78%	
R-11		10%	b	16%	b
R-19		10%	b	6%	b
R-30					
OTHER					

Table B.12. How slab-on-grade foundations are insulated in Northeast.

N=4 NORTHEAST

SLAB-ON-GRADE FOUNDATIONS		1982	1992
EXTERIOR VERTICAL			
NO INSULATION		89%	54%
2 FT. R-5		1%	6%
2 FT. R-10			
4 FT. R-5			
4 FT. R-10			1%
4 FT. R-15			
4 FT. R-20			
OTHER			
INTERIOR VERTICAL			
2 FT. R-5			6%
2 FT. R-10			4%
4 FT. R-5			
4 FT. R-10			2%
4 FT. R-15			
4 FT. R-20			
OTHER			
INTERIOR HORIZONTAL			
2 FT. R-5			5%
2 FT. R-10			11%
4 FT. R-5			
4 FT. R-10			
OTHER			
EXTERIOR HORIZONTAL			
2 FT. R-5			
2 FT. R-10			11%
4 FT. R-5			
4 FT. R-10			
OTHER			

RESULTS: GEOGRAPHIC BREAKDOWN
N=12

MIDWEST
PERCENT OF TOTAL

1. Please indicate which discipline best identifies your occupation or research.

3. What kind of structural materials are used?

5. If you install insulation on the outside, what do you use for protective covering for the above grade portion?

6a. Are codes requiring foundation insulation enforced in your area?

	YES	NO
1982	1%	90%
1992	70%	30%

6b. If so, how much insulation is required?

1982: R-5
1992: R-10; R-10 to frostline; R-5 over entire wall; exposed crawlspaces; R-5 for 8 ft wall unconditioned basements or R-10 to frostline; R-5; R-10; 1" foam on exterior of foundation.

8. What do you refer to when insulating, or advising others?

4. Does insect control impact foundation insulation decisions?

YES	NO
1	9
10%	90%

7. If the insulation practice has changed in your area from 1982 to 1992, what influenced this change?

9. If you or others in your area have not changed foundation insulation levels in the 1990's, why?

Fig. B-4. Midwest response to Questions 1 and 3-9.

Table B.13. How conditioned deep basements are insulated in Midwest.

MIDWEST

N=9

CONDITIONED DEEP BASEMENTS		1982	1992
EXTERIOR: HALF WALL			
NO INSULATION	81%		47%
4 FT: R-5	2%	c	c
4 FT: R-10	1%	c	c
OTHER			d
EXTERIOR: FULL WALL			
8 FT: R-5	4%	c	c
8 FT: R-10	1%	c	c
8 FT: R-15			e
8 FT: R-20			
OTHER			d
INTERIOR: FULL WALL			
8 FT: R-6	4%	a	a
8 FT: R-8	1%	c	c
8 FT: R-11	2%	b	b
8 FT: R-19			
OTHER	4%	b	b
WOOD: FULL WALL			
NO INSULATION	90%		90%
8 FT: R-11	3%	b	
8 FT: R-19	7%	b	b
8 FT: R-30			e
OTHER			

Table B.14. How unconditioned deep basements are insulated in Midwest.

MIDWEST

N=6

UNCONDITIONED DEEP BASEMENTS		1982		1992	
EXTERIOR HALF WALL					
NO INSULATION		85%			45%
4 FT R-5		3%	c		
4 FT R-10		1%	c		c
OTHER					d
EXTERIOR FULL WALL					
8 FT R-5		4%	c		c
8 FT R-10		1%	c		c
8 FT R-15					
8 FT R-20					
OTHER					d
INTERIOR FULL WALL					
8 FT R-6		1%	c		d,a
8 FT R-8		3%	c,b		c,b
8 FT R-11		2%	c		b
8 FT R-19					
OTHER					e,b
WOOD FULL WALL					
NO INSULATION		90%			90%
8 FT R-11		3%	b		
8 FT R-19		7%	b		b
8 FT R-30					b
OTHER					c
CEILING					
NO INSULATION		83%			80%
8 FT R-11		9%	b		
8 FT R-19		8%	b		b
8 FT R-30					b
OTHER					c

Table B.15. How crawl spaces are insulated in Midwest

CRAWL SPACES		1982	1992
EXTERIOR VERTICAL			
NO INSULATION		89%	51%
2 FT R-5		1%	7%
2 FT R-10			5%
OTHER			2%
INTERIOR VERTICAL			
2 FT R-5		2%	12%
2 FT R-10		1%	7%
OTHER		1%	8%
INTERIOR VERTICAL AND HORIZONTAL			
2 FT 2 FT R-5			
2 FT 4 FT R-5			
2 FT 2 FT R-10			
2 FT 4 FT R-10			
OTHER		6%	8%
WITHIN WOOD WALL			
NO INSULATION		90%	90%
2 FT R-11		4%	
2 FT R-19		6%	6%
OTHER			4%
CEILING			
NO INSULATION		79%	83%
R-11		6%	5%
R-19		12%	5%
R-30			4%
OTHER			3%

N=10

MIDWEST

Table B.16. How slab-on-grade foundations are insulated in Midwest.

SLAB-ON-GRADE FOUNDATIONS		1982	1992
EXTERIOR VERTICAL			
NO INSULATION			
2 FT R-5		1%	22%
2 FT R-10			15%
4 FT R-5		3%	5%
4 FT R-10		1%	6%
4 FT R-15		2%	3%
4 FT R-20			
OTHER			d
INTERIOR VERTICAL			
2 FT R-5		2%	5%
2 FT R-10		3%	5%
4 FT R-5		1%	6%
4 FT R-10			4%
4 FT R-15			
4 FT R-20			
OTHER			d
INTERIOR HORIZONTAL			
2 FT R-5		2%	3%
2 FT R-10			4%
4 FT R-5		1%	5%
4 FT R-10			1%
OTHER		3%	4%
EXTERIOR HORIZONTAL			
2 FT R-5		1%	
2 FT R-10			1%
4 FT R-5			1%
4 FT R-10			6%
OTHER			

N=5

MIDWEST

RESULTS: GEOGRAPHIC BREAKDOWN
N=3

WEST
PERCENT OF TOTAL

1. Please indicate which discipline best identifies your occupation or research.

5. If you install insulation on the outside, what do you use for protective covering for the above grade portion?

8. What do you refer to when insulating, or advising others?

3. What kind of structural materials are used?

4. Does insect control impact foundation insulation decisions?

YES	NO
1	2
33%	67%

7. If the insulation practice has changed in your area from 1982 to 1992, what influenced this change?

6a. Are codes requiring foundation insulation enforced in your area?

	YES	NO
1982	100%	
1992	100%	

6b. If no, how much insulation is required?

1982: R-11-R-19 in floor/slab is R-7.

9. If you or others in your area have not changed foundation insulation levels in the 1990's, why?

Fig. B-5. West response to Questions 1 and 3-9.

Table B.17. How conditioned deep basements are insulated in West.

WEST

N=3

CONDITIONED DEEP BASEMENTS		1982	1992
EXTERIOR: HALF WALL			
NO INSULATION		89%	20%
4 FT: R-5			22% ^a
4 FT: R-10			
OTHER			
EXTERIOR: FULL WALL			
8 FT: R-5		11%	7% ^{a,d}
8 FT: R-10			
8 FT: R-15			
8 FT: R-20			
OTHER			
INTERIOR: FULL WALL			
8 FT: R-6			
8 FT: R-8			22% ^a
8 FT: R-11			29% ^b
8 FT: R-19			
OTHER			
WOOD: FULL WALL			
NO INSULATION		100%	100%
8 FT: R-11			
8 FT: R-19			
8 FT: R-30			
OTHER			

Table B.18. How unconditioned deep basements are insulated in West.

UNCONDITIONED DEEP BASEMENTS		1982	1992
EXTERIOR: HALF WALL			
NO INSULATION		100%	70%
4 FT. R-5			30 ^a
4 FT. R-10			
OTHER			
EXTERIOR: FULL WALL			
8 FT. R-5			
8 FT. R-10			
8 FT. R-15			
8 FT. R-20			
OTHER			
INTERIOR: FULL WALL			
8 FT. R-6			
8 FT. R-8			
8 FT. R-11			
8 FT. R-19			
OTHER			
WOOD: FULL WALL			
NO INSULATION			
8 FT. R-11			
8 FT. R-19			
8 FT. R-30			
OTHER			
CEILING			
NO INSULATION		100%	40%
8 FT. R-11			60% ^b
8 FT. R-19			
8 FT. R-30			
OTHER			

N=3

WEST

Table B.19. How crawl spaces are insulated in West.

CRAWL SPACES		1982	1992
EXTERIOR VERTICAL			
NO INSULATION		75%	90%
2 FT. R-5			2%
2 FT. R-10			
OTHER			3%
INTERIOR VERTICAL			
2 FT. R-5			
2 FT. R-10			
OTHER			
INTERIOR VERTICAL AND HORIZONTAL			
2 FT.2 FT. R-5		25%	1%
2 FT.4 FT. R-5			
2 FT.2 FT. R-10			
2 FT.4 FT. R-10			4%
OTHER			
WITHIN WOOD WALL			
NO INSULATION		100%	100%
2 FT. R-11			
2 FT. R-19			
OTHER			
CEILING			
NO INSULATION		35%	15%
R-11		65%	18%
R-19			67%
R-30			
OTHER			

N=2

WEST

Table B.20. How slab-on-grade foundations are insulated in West

N=3

WEST

SLAB-ON-GRADE FOUNDATIONS		1982	1992
EXTERIOR: VERTICAL			
NO INSULATION		93%	47%
2 FT. R-5			7%
2 FT. R-10			7%
4 FT. R-5			
4 FT. R-10			
4 FT. R-15			
4 FT. R-20			
OTHER			
INTERIOR: VERTICAL			
2 FT. R-5		7%	16%
2 FT. R-10			
4 FT. R-5			
4 FT. R-10			
4 FT. R-15			
4 FT. R-20			
OTHER			
INTERIOR: HORIZONTAL			
2 FT. R-5			13%
2 FT. R-10			10%
4 FT. R-5			
4 FT. R-10			
OTHER			
EXTERIOR: HORIZONTAL			
2 FT. R-5			
2 FT. R-10			
4 FT. R-5			
4 FT. R-10			
OTHER			

RESULTS: GEOGRAPHIC BREAKDOWN N=8

NORTH WEST PERCENT OF TOTAL

1. Please indicate which discipline best identifies your occupation or research.

5. If you install insulation on the outside, what do you use for protective covering for the above grade portion?

8. What do you refer to when insulating, or advising others?

3. What kind of structural materials are used?

6a. Are codes requiring foundation insulation enforced in your area?

	YES	NO
1982	11%	89%
1992	88%	12%

6b. If so, how much insulation is required?
1982: Some houses R-19 floor; 0-R-11; R-8
1992: All houses R-25 or above; R-10; R-12; under floor/crawl space R-25; slab-on-grade R-10; below grade basement walls R-21.

7. If the insulation practice has changed in your area from 1982 to 1992, what influenced this change?

9. If you or others in your area have not changed foundation insulation levels in the 1990's, why?

Fig. B-6. Northwest response to Questions 1 and 3-9.

Table B.21. How conditioned deep basements are insulated in Northwest.

N=5 NORTHWEST

CONDITIONED DEEP BASEMENTS		1982		1992
EXTERIOR: HALF WALL				
NO INSULATION		70%		50%
4 FT: R-5		8%	c	
4 FT: R-10		5%	c	c
OTHER				1% b
EXTERIOR: FULL WALL				
8 FT: R-5		5%	c	
8 FT: R-10		1%	a	9% c
8 FT: R-15				
8 FT: R-20		1%	a	1% c
OTHER				1%
INTERIOR: FULL WALL				
8 FT: R-6				
8 FT: R-8				
8 FT: R-11		8%	b	6% b
8 FT: R-19		2%	b	7% b
OTHER				22% b
WOOD: FULL WALL				
NO INSULATION		1982		1992
8 FT: R-11		50%	b	
8 FT: R-19		50%	b	100% b
8 FT: R-30				
OTHER				

Table B.22. How unconditioned deep basements are insulated in Northwest.

N=3 NORTHWEST

UNCONDITIONED DEEP BASEMENTS		1982	1992
EXTERIOR: HALF WALL			
NO INSULATION		90%	50%
4 FT R-5			
4 FT R-10			
OTHER			
EXTERIOR: FULL WALL			
8 FT R-5			
8 FT R-10			
8 FT R-15			
8 FT R-20			
OTHER			
INTERIOR: FULL WALL			
8 FT R-6			
8 FT R-8		5%	b
8 FT R-11		5%	b
8 FT R-19			
OTHER			45%
			b
WOOD: FULL WALL			
NO INSULATION			
8 FT R-11		100%	b
8 FT R-19			50%
8 FT R-30			
OTHER			50%
			b
CEILING			
NO INSULATION		97%	87%
8 FT R-11			
8 FT R-19		3%	b
8 FT R-30			2%
OTHER			b

Table B.23. How crawl spaces are insulated in Northwest.

N=5 NORTHWEST

CRAWL SPACES		1982	1992
EXTERIOR: VERTICAL			
NO INSULATION		58%	30%
2 FT. R-5			8%
2 FT. R-10		8%	16%
OTHER			6%
INTERIOR: VERTICAL			
2 FT. R-5		8%	c
2 FT. R-10			
OTHER		17%	b
INTERIOR: VERTICAL AND HORIZONTAL			
2 FT/2 FT. R-5			
2 FT/4 FT. R-5			
2 FT/2 FT. R-10			
2 FT/4 FT. R-10			
OTHER		9%	b
WITHIN WOOD WALL			
NO INSULATION			
2 FT. R-11		100%	b
2 FT. R-19			b
OTHER			
CEILING			
NO INSULATION		60%	
R-11			
R-19		32%	b
R-30		8%	b
OTHER			b

Table B.24. How slab-on-grade foundations are insulated in Northwest.

N=3 NORTHWEST

SLAB-ON-GRADE FOUNDATIONS		1982	1992
EXTERIOR, VERTICAL			
NO INSULATION	75%		
2 FT. R-5	1%	a,c	
2 FT. R-10	3%	c	c
4 FT. R-5			
4 FT. R-10	4%	c	c
4 FT. R-15	2%	d	
4 FT. R-20			c
OTHER			
INTERIOR, VERTICAL			
2 FT. R-5	1%	a	
2 FT. R-10			a,c
4 FT. R-5			
4 FT. R-10	4%	b	
4 FT. R-15			
4 FT. R-20	4%	b	b
OTHER			
INTERIOR, HORIZONTAL			
2 FT. R-5	3%	a	
2 FT. R-10	3%	a	a,c
4 FT. R-5			
4 FT. R-10			
OTHER			a,c
EXTERIOR, HORIZONTAL			
2 FT. R-5			
2 FT. R-10			
4 FT. R-5			
4 FT. R-10			
OTHER			a,c

RESULTS: GEOGRAPHIC BREAKDOWN
N=1

SOUTH WEST
PERCENT OF TOTAL

1. Please indicate which discipline best identifies your occupation or research

3. What kind of structural materials are used?

4. Does insect control impact foundation insulation decisions?

YES	NO
1	0
100%	

6a. Are codes requiring foundation insulation enforced in your area?

	YES	NO
1982		100%
1992		100%

6b. If so, how much insulation is required?
1982:
1992:

9. If you or others in your area have not changed foundation insulation levels in the 1990's, why?

Fig. B-7. Southwest response to Questions 1 and 3-9.

INTERNAL DISTRIBUTION

1-10.	J. E. Christian	30.	J. O. Kolb
11.	G. E. Courville	31.	T. G. Kollie
12.	M. A. Broders	32.	M. A. Kuliasha
13.	R. B. Shelton	33.	P. M. Love
14-23.	C. L. Brown	34.	W. R. Mixon
24.	M. A. Brown	35.	ORNL Patent Office
25.	R. S. Carlsmith	36.	Central Research Library
26.	A. O. Desjarlais	37.	Document Reference Section
27.	P. D. Fairchild	38.	Laboratory Records - RC
28.	S. K. Fischer	39-41.	Laboratory Records
29.	M. B. Gettings		

EXTERNAL DISTRIBUTION

42. Robert L. Alumbaugh, Naval Civil Engineering Laboratory, Port Hueneme, CA 93043-5003
43. James L. Anderson, Foam Enterprises, Inc., 13630 Watertower Circle, Minneapolis, MN 55441
44. Aaron Applegate, P.O. Box 292, Okemos, MI 48805
45. Erv Bales, University Heights, New Jersey Institute of Technology, Newark, NJ 07102
46. Roger Barker, Georgia Pacific Corp., 133 Peachtree St., N.E., 20th Floor, Atlanta, GA 30303
47. Mark Bomberg, National Research Council Canada, Ottawa, Ontario, Canada K1A 0R6
48. J. Boone, Wichita Insulation, 12727 E. Kellogg, Wichita, KS 67207
49. Jean Boulin, Dept. of Energy, CE-43, FORSTL, 1000 Independence Ave., S.W., Washington, D.C. 20585
50. Maribeth S. Bradfield, NCMA, 2302 Horse Pen Road, Herndon, VA 22071-3406
51. Stephen G. Braun, North American Insulation Mfgs. Assoc., Suite 310, 44 Canal Center Plaza, Alexandria, VA 22314-1592
52. Jeffrey R. Brisley, Knauf Fiberglass, 240 Elizabeth Street, Shelbyville, IN 46176
53. Donald E. Brotherson, One E. Saint Mary's Road, Champaign, IL 61820
54. Bruce G. Buchanan, Computer Science Dept., University of Pittsburgh, 206 Mineral Industries Building, Pittsburgh, PA 15260
55. CAREIRS Librarian, 2000 N. 15th Street, Suite 407, Arlington, VA 22201-2627
56. Dave Crouse, Stepan, 22 W. Frontage Road, Northfield, IL 60093
57. Jack Davis, Florida Power Corp., P.O. Box 14042, St. Petersburg, FL 33733
58. Clayton DeKorne, Journal of Light Construction, RR 2, Box 146, Richmond, VT 05477
59. Rene M. Dupuis, Structural Research, Inc., 3213 Laura Lane, Middleton, WI 53562

60. W. M. Edmunds, Owens-Corning Fiberglas, 2790 Columbus Road, Granville, OH 43023
61. Helen English, Passive Solar Industries Council, 1511 K Street, N.W., Suite 600, Washington, D.C. 20005
62. P. R. Fiset, Room 126, Holdsworth Hall, University of Massachusetts, Amherst, MA 01003
63. William Freeborne, U.S. Dept. of Housing and Urban Development, 451 Seventh St., S.W., Room 8138, Washington, D.C. 20410
64. Warren R. French, French Engineering, Inc., 15531 Kuykendahl, Suite 275, Houston, TX 77090
65. Charles Gilbo, Journal of Thermal Insulation, 1820 Westcott Drive, Lancaster, PA 17603-2371
66. Pat Gleason, Idaho Dept. of Water Resources, 1301 N. Orchard St., Boise, ID 83706
67. Leon R. Glicksman, M.I.T., 4-209, 77 Massachusetts Avenue, Cambridge, MA 02139
68. William P. Goss, Mechanical Engineering Dept., University of Massachusetts, Amherst, MA 01003
69. Thomas Greeley, BASF, 100 Cherry Hill Road, Parsippany, NJ 07054
70. Tim Grether, Owens/Corning Fiberglas, Fiberglas Tower, Toledo, OH 43659
71. Jack Gusler, G.W.S., 2706 Wyndham Lane, Orlando, FL 32808
72. Joseph R. Hagan, Center for Applied Engineering, 10301 Ninth Street, North, St. Petersburg, FL 33716
73. David A. Harris, National Institute of Building Sciences, 1201 L Street, N.W., Suite 400, Washington, D.C. 20005
74. Tom Harris, BASF Canada, Inc., 345 Carlingview Drive, Rexdale, Ontario, Canada M9W 6N9
- 75-77. Donna Hawkins, Dept. of Energy, CE-40, FORSTL, 1000 Independence Ave., S.W., Washington, D.C. 20585
78. Phil Hendrickson, Dow Chemical, USA, P.O. Box 515, Granville, OH 43023
79. Bion Howard, 14513 Kent Drive, Upper Marlboro, MD 20772
80. Helen M. Ingram, Udall Center for Studies in Public Policy, The University of Arizona, 803/811 East First Street, Tucson, AZ 85719
81. Michael Ivanovich, P.O. Box 2218, Boulder, CO 80306
82. Richard Karney, Dept. of Energy, CE-421, FORSTL, 1000 Independence Ave., S.W., Washington, D.C. 20585
83. Mark Kelley, Building Science Engineering, 85 Depot Road, Harvard, MA 01451
84. Philip Knight, Lockwood Green, Oak Ridge Turnpike, Oak Ridge, TN 37830
85. Richard Kramer, National Pest Control Assoc., 8100 Oak Street, Dunn Loring, VA 22027
86. Walter Kroner, Rensselaer Polytechnic Institute, Architectural Research, Greene 103, 110 8th Street, Troy, NY 12180
87. Gene Leger, Leger Designs, 256 Middle Branch Road, New Boston, NH 03070
88. John J. Leimanis, Dept. of State, FBO/BDE/ESB, P.O. Box 12248, Rosslyn Station, Arlington, VA 22219
89. Fran Lichtenberg, The Society of the Plastics Industry, 355 Lexington Avenue, New York, NY 10017
90. Calvin D. MacCracken, Calmac Manufacturing Corporation, 101 West Sheffield Avenue, P.O. Box 710, Englewood, NJ 07631
91. Robert F. Martin, Roof Maintenance Systems, P.O. Box 67, Farmingdale, NJ 07727
92. William F. Martin, Roof Design Works, Inc., 516 Renford Drive, Knoxville, TN 37919
93. Jerry Marx, Safety & Buildings Division, P.O. Box 7964, Madison, WI 53707

94. Merle F. McBride, Owens-Corning Fiberglas, 2790 Columbus Road, Granville, OH 43023-1200
95. David McCaa, Certainteed Corporation, 1400 Union Meeting Road, Blue Bell, PA 19422-0761
96. Duvon McGuire, Regal Industries, Inc., Route 1, Box 46, Crothersville, IN 47229
97. R. Gerry Miller, Center for Applied Engineering, Inc., 10301 9th Street, N., St. Petersburg, FL 33716
98. Pat Mulroy, Blackgold, Inc., 4502 Burlingame Road, Topeka, KS 66609
99. NCAT Library, National Center for Appropriate Technology, P.O. Box 3838, Butte, MT 59702
100. Bruce D. Nelson, Minn. Dept. of Public Service, 150 E. Kellogg Blvd, #790, St. Paul, MN 55101
101. Ned Nisson, Energy Design Update, P.O. Box 1709, Ardenia Station, New York, NY 10023
102. David G. Ober, 25 Wiggins Avenue, Bedford, MA 01730
103. Larry Plocher, Central Insulation, 9835 Highway 284, Waconia, MN 55387
104. Frank Powell, 12218 Cattail Lane, Jacksonville, FL 32223
105. Donald Prowler, 2302 Locust Street, Philadelphia, PA 19103
106. Paul Remmele, Morton Buildings, Inc., P.O. Box 399, Morton, IL 61550
107. A. Sterett Robertson, DowElanco, P.O. Box 681428, Indianapolis, IN 46268-1189
108. David Roodvoets, Dow Chemical U.S.A., 3825 Columbus Road, S.W., F Bldg., Granville, OH 43023
109. William Rose, Small Homes Council, 1 East St. Mary's Road, Champaign, IL 61820
110. W. J. Rossiter, NIST, Bldg. 226, Rm. B348, Gaithersburg, MD 20899
111. Russell Rudy, Kansas Weatherization Assistance, Dept. of Commerce, 400 S.W. 8th Street, Suite 500, Topeka, KS 66603
112. Thomas Sayre, Sizemore/Floyd Architects, 600 W. Peachtree Street, Suite 1000, Atlanta, GA 30308
113. Peter Scofield, Department of Energy, CE-421, FORSTL, 1000 Independence Ave., S.W., Washington, D.C. 20585
114. Richard Seifert, University of Alaska, Cooperative Extension Service, Arctic Health Research 104, Fairbanks, AK 99775-5200
115. Stephen Selkowitz, Windows and Daylighting Group, Lawrence Berkeley Laboratory, One Cyclotron Road, Building 90-3111, Berkeley, CA 94720
116. Morton Sherman, Consultant, 6723 14th Avenue, North, St. Petersburg, FL 33710-5405
117. Jacqueline B. Shrago, Office of Technology Transfer, 405 Kirkland Hall, Vanderbilt University, Nashville, TN 37240
118. S. E. Smith, Physical Sciences Group, 48 Chester Street, Somerville, MA 02144
119. Lawrence G. Spielvogel, Lawrence G. Spielvogel, Inc., 203 Hughes Road, King of Prussia, PA 19406-3785
120. Richard Spray, Agricultural Engineering, 210 McAdams Hall, Clemson University, Clemson, SC 29634-0357
121. Bruce Spurlock, Southern Services, 64 Perimeter Center, Atlanta, GA 30346
122. Raymond L. Sterling, Underground Space Center, 500 Pillsbury Drive, S.E., Minneapolis, MN 55455
123. Ed Story, Insul-Tray, Inc., E. 1881 Crestview Drive, Shelton, WA 98584-9082
124. William R. Strzepek, Dow U.S.A., P.O. Box 515, Granville, OH 43023
125. Anton TenWolde, U.S. Dept. of Agriculture, Forest Products Laboratory, One Gifford Pinchot Drive, Madison, WI 53705-2398

126. Timothy Tong, Dept. of Mechanical & Aerospace Eng., Arizona State University, Tempe, AZ 85287
127. George Tsongas, Mechanical Engineering Dept., Portland State University, P.O. Box 751, Portland, OR 97207
128. Adrian Tuluca, Steven Winter Associates, Inc., 50 Washington Street, Norwalk, CT 06854
129. R. P. Tye, 292 Jerusalem Road, Cohasset, MA 02025
130. Carl R. Vander Linden, Vander Linden & Assoc., 5 Brassie Way, Littleton, CO 80123
131. Martha G. Van Geem, Construction Technology Laboratory, 5420 Old Orchard Road, Skokie, IL 60077
132. Jack Verschoor, 179 Gail Avenue, Bailey, CO 80421
- 133-142. Melissa Voss, Rural Route 3, Box 122, Macomb, IL 61455
143. Jack R. Warner, 6427 Forest Road, Cheverly, MD 20785
144. David J. Williams, Dow Chemical, P.O. Box 515, Granville, OH 43023
145. Martin Williams, Department of Economics, Northern Illinois University, DeKalb, IL 60115
146. Andrew Wynn, Central Maine Power Company, Edison Drive, Augusta, ME 04336
147. Office of the Assistant Manager for Energy Research and Development, DOE-ORO, P.O. Box 2001, Oak Ridge, TN 37831-8600
- 148-187. BTESM Library, Oak Ridge National Laboratory, P.O. Box 2008, Bldg. 3114, Oak Ridge, TN 37831-6070
- 188-197. OSTI, U.S. Dept. of Energy, P.O. Box 62, Oak Ridge, TN 37831

END

**DATE
FILMED**

1 / 7 / 93