Cascades of High Energy Particles—in Parallel

Ed May, High Energy Physics Division, Argonne

Introduction

Simulating the response of calorimetric-based detectors to highly energetic particles is important to the design and use of detectors for elementary particle studies at high-energy particle accelerators—both those currently in operation (e.g., at Fermilab) and those being planned (e.g., at the Superconducting Super Collider).

A typical calorimeter might consist of many layers of lead and plastic scintillator. A high-energy electron or positron entering this stack will create a cascade of secondary particles in the lead. As the charged particles cross the plastic scintillator, light is generated. This light is measured by phototubes and is recorded by a data acquisition system.

Such measurements help determine the direction and energy of the initiating high-energy particle. A probabilistic model is used to identify the interactions of the electrons, positrons, and photons. The model describes the creation and ultimate absorption of all of the particles in the generated cascade.

A typical cascade may involve thousands to hundreds of thousands of elementary interactions, depending on the starting energy (see Fig. 1). Monte Carlo simulations are used to track each particle of the cascade. Because of the stochastic nature of the elementary interactions and the sampling construction of many calorimeter designs, the simulation must generate a large number of individual cascades to accurately determine the properties of a specific design.

RECEIVED
SEP 20 1990
OSTI
MASTER

Figure 1: A typical cascade in a calorimeter stack. The cascade begins at the left and travels horizontally. Each electron or positron track in the plastic between elementary interactions is shown as a short line segment. The vertical lines represent the boundaries between the lead and plastic.

A number of well-understood serial Fortran codes exist that include all of the important physics and geometry tracking for coding calorimeter designs. For example, the EGS4 code system developed at SLAC has been used for many years. However, the ever-higher energies of the newer accelerators require very long run times on serial computers.

The advent of parallel computers now offers a promising alternative. High-energy particle cascades present many opportunities for parallelism, since each cascade is independent of previous or subsequent cascades—and, indeed, once a particle has been created within a cascade, its subsequent development is independent of other particles in the cascade.

PARMACs and Parallelism

We have used the ACRF-developed PARMACs code system to produce parallel versions of the simulation codes for both shared-memory and distributed-memory MIMD machines. The PARMACs system provides a number of high-level parallel constructs, which are easily inserted into a Fortran code. A macro processor then expands these into the appropriate code for the target parallel computer, thus achieving portability. Portability is important, because the simulation codes have a long lifetime and run on many different computers at a number of institutions and laboratories throughout the world. Some level of performance may be sacrificed by the programmer, in that the PARMACs system chooses the low-level primitives to implement the parallelism. At the coarse granular level (with parallel machines with 8-40 processors) this is usually not a problem, however; it is well overshadowed by the portability and transparency of the implementation of the parallel structure onto the Fortran code.

The parallel approach we have used most frequently is the *master* with many *workers*. The *master* organizes and gives out cascades to the *workers*. The shared-memory simulation code was originally developed and debugged on the Sequent Balance B21000 at the ACRF. It was then moved without modification to the Encore MultiMax and the Alliant FX/8 and ran correctly, with the expected level of speedup as afforded by the multiplicity of faster processors. A typical speedup curve for the Encore is shown in Figure 2.

To further explore the portability of such techniques on a wider range of parallel architectures, we reimplemented the simulation using the message-passing features provided in the PARMACs system, which allow code to run on both shared-memory and distributed-memory systems. We then tested the new version on a network of Sun workstations and on the Intel IPCS/2 hypercube. The performance achieved was similar to that for the shared-memory version on the Encore. In the case of the network of Suns (see Figure 2), the speedup turns over much sooner, as expected from using the ethernet as the communications channel. However, the existence of an X window-based message display and monitoring system within PARMACs makes the Sun version a useful debugging environment.

In general, we find the message-passing environment better for our purposes. Not only is a wide class of machine potentially supported, but we have found it somewhat easier to debug than the monitor-based shared-memory paradigm. All of this work was done in collaboration with Jim Patterson and is described in more detail in Ref. 1.

contd. p. 8

"Cascades," from p. 7

Tech Transfer

An improved version of PARMACs is being developed. This new system, called P4, removes the sometimes troublesome M4 macro processing, uses a more modern remote procedure call mechanism, and will (soon) use XDR external data representation for parallel programming in a heterogeneous distributed environment. Working with Dave Leibfritz and David Malon at Argonne, we have developed new parallel versions of EGS4 simulations and ISAJET generators on the ACRF Balance. The codes have been ported to the four-processor Apollo DN10000 and the Silicon Graphics eight-processor 4D/380. Beyond the benchmarking exercise, we will be using these codes as design tools at the SSC laboratory computing facilities now being assembled for calorimeter design.

We also plan to implement P4 and the EGS4 simulation on the ACRF BBN TC2000. The Butterfly has a great attraction for us, with its large number of powerful RISC processors. To date, our experience with the TC2000 Butterfly is quite good; preliminary results are presented in Ref. 2.

References

1. E. May, "Portable Parallel Programming in a Fortran Environment," Proceedings of the 1989 Conf. on Computing in HEP, Oxford, 1989.
2. W. Celmaster and E. N. May, *Interactive Radiation Transport Simulation on the BBN TC2000 Parallel Computer, EGS4: A Case History*, ANL-HEP-PR-90-10.

EGS4 Benchmark on Parallel Computers

Figure 2: Speedup curve on the Encore, a network of Sun workstations, and the TC2000

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

END

**DATE
FILMED**

11/01/93