HW-55914 ~~DEL~~

CHEMICAL PROCESSING DEPARTMENT
MONTHLY REPORT
FOR
APRIL, 1958

DE93 001777

Classification Cancelled (Change to

By Authority of Chairman

115 Lewis 6-192

Re IL Phillips 7-31-72

Df Krishna 8-4-92

Compiled By
OPERATION MANAGERS

May 21, 1958

CLASSIFICATION REVIEW FOR
DECLASSIFICATION BUT LEFT
UNCHANGED /

HANFORD ATOMIC PRODUCTS OPERATION
RICHLAND, WASHINGTON

84

23

U.S. SEC Division of Classification

Work performed under Contract No. W-31-109-Eng-52 between the Atomic Energy Commission and General Electric Company

[illegible]

MASTER

**DECLASSIFIED
WITH DELETIONS**

15-00000

4 p.

DECLASSIFIED

HW-55914

DEL

DISTRIBUTION

Copy Number

1	W. E. Johnson
2	H. M. Parker
3	H. D. Tibbels
4	J. H. Warren
5	O. C. Schroeder
6	C. T. Groswith
7	W. N. Mobley
8	T. G. LaFollette
9	K. G. Grimm
10	H. P. Shaw
11	V. R. Cooper
12	C. R. Bergdahl
13, 14 & 15	Atomic Energy Commission, Hanford Operations Office Attention: J. E. Travis, Manager
16 & 17	Atomic Energy Commission, Washington 25, D. C. Attention: E. J. Bloch, Director, Division of Production
18	Atomic Energy Commission, Washington 25, D. C. Attention: F. P. Baranowski, Chemical Processing Branch
19	Extra Copy
20	300 File
21	Record File

DECLASSIFIED

DECLASSIFIED

TABLE OF CONTENTS

Distribution	A-2
Table of Contents	A-3
General Summary	A-4 through A-6
Staff	A-7
Number of Employees	A-8
Patent Summary	A-9
Production Operation	B-1 through B-5
Purex Operation	C-1 through C-6
Redox Operation	D-1 through D-11
Finished Products Operation	E-2 through E-8
Power and General Maintenance Operation	F-1 through F-3
Financial Operation	G-1 through G-5
Facilities Engineering Operation	H-2 through H-13
Research and Engineering Operation	J-3 through J-20
Employee Relations Operation	K-2 through K-14

DECLASSIFIED
WITH DELETIONS

HW-55914 **DEL**

CHEMICAL PROCESSING DEPARTMENT
MONTHLY REPORT

APRIL, 1958

GENERAL SUMMARY

PRODUCTION

The separations plants operated in accordance with the established schedules, and plutonium production slightly exceeded the commitment. The production of UO_3 was 102% of the commitment while UO_3 shipments were 57 tons ahead of the schedule at the end of the shipping period on April 20, 1958.

ENGINEERING

Operation of Purex Plant under psuedo two-cycle conditions (elimination of the HS and 1A columns as well as the co-decontamination cycle concentrator, HCP) proved highly successful. This mode of operation is scheduled for continuation until shutdown for conversion to a true two-cycle flowsheet during June. A new low of 0.25% Pu loss was registered. The final uranium stream was three fold lower in Pu than ever before. Gamma activity in the recovered HNO_3 was also down to 250-1500 microcuries/gal. versus 10,000-24,000 in the prior month.

Studies on the performance of the Purex solvent washing system as a function of the reagent (sodium carbonate vs. sodium hydroxide) disclosed no advantages in solvent quality or iodine solution as a function of the reagent.

Four of a total of six special batches of E metal (enriched uranium) were processed through Redox and carefully analysed in conjunction with an IPD program to correlate plutonium conversion ratios as a function of other reactor and fuel variables. Final correlations will be reported by IPD.

It has been demonstrated that boric acid, of interest as a nuclear poison in the dissolvers, is removed from the solvent extraction process via aqueous waste. In the event of a process upset and transfer to UNH calciners it will only be removed to 35 percent of the entering level.

The active filter media in the Task II hydrofluorinator was changed from a fragile carbon element to a porous metallic element (Poroloy) fabricated from Hastelloy "C". The experimental material has performed satisfactorily and promises to improve the durability of this system.

A new washing procedure for recovery of plutonium from Recuplex waste reduced the plutonium content in the waste to a level permitting cribbing.

DECLASSIFIED
WITH DELETIONS

DECLASSIFIED

HW-55914 **DEL**

In the development of the plutonium trichloride process for the 234-5 Building, it was observed that the density of the PuCl_3 is sensitive to temperature during formation, reduction to metal yields display an anomaly - higher yields on small scale than on a large scale, a problem in charge sticking due to penetration of the MgO reduction crucible that did not occur with the higher melting fluoride slag, and in the recovery of plutonium within the slag it appears possible to drive the chloride overhead by boiling off nitric acid, - thereby permitting subsequent recovery in the Recuplex facility.

Process design work covering the installation of ammonia scrubbers in the Purex dissolver cells was completed. This work included the design of the scrubber vessel, the cold side piping and instrumentation, and needed new jumpers identified from cell layout studies.

A revised scope study of the Purex block bail reinforcement problem has been completed. The new scope is based on accomplishing the required fabrication in "M" cell to minimize the operational interference of normal canyon functions.

A prototype installation of an air activated powder transfer valve and control system was made on the H calciner in the 224-UA Building. The unit was put into operation April 21 and has functioned satisfactorily since that time. Observations and measurements made have shown the valve to be able to maintain a seal between the calciner and the powder pickup bin while passing a continuous stream of UO_3 powder.

Studies have been initiated to establish the adaptability of the present E metal dissolver concept to routine processing of irradiation reactor fuel material of higher enrichment.

Specification HWS-6335 has been prepared covering design and construction of a remotely operated shear for cutting scrap jumpers in the canyon. The purpose of the shear is to reduce the size of scrap jumpers and conserve burial box space.

Scoping work was completed during the month on the shielding barrier to be provided from Task I through Task IV in the 234-5 Building. Detailed studies were made on several alternate methods of constructing this shielding barrier in order to obtain the maximum amount of shielding at minimum cost. The results and conclusions of these studies have been documented in HW-55865.

A definitive process design and scope criteria covering the use of the UO_3 Plant continuous calciners in the E metal segregated production program was completed. This work covers all facets of E metal segregation with the exception of possible alternate methods of E metal powder handling.

Proposals for process design and fabrication of a facility for recovering krypton and xenon from the Purex dissolver off-gas were received this month from Union Oil, Air Products, Linde, Air Reduction, and Arthur D. Little Companies.

A report has been prepared summarizing results of the preliminary discussions and an analysis of the proposals.

DECLASSIFIED

DECLASSIFIED [REDACTED]

HW-55914 **DEL**

GENERAL

Annual statements showing the investment, as of December 31, 1957, of each participant in the Stock Bonus Plan have been received. In past years these statements have been delivered promptly to the employees concerned; however, this year the statements will be held and delivered along with a statement showing interest accumulated in the pension plan and value of insurance held.

The HAMTC has notified CPD of three new cases which they wish to take to arbitration. One of these involves the right to contract work to outside concerns. The Union contends that the Department has no such right, at least when there have been substantial reductions in personnel within the maintenance crafts.

Arrangements were completed for a program scheduled for May 9, in recognition of Power and General Maintenance Operation achieving One Million Man Hours without a disabling injury.

The increased number of exempt personnel during the month was due largely to the change in job classification of 28 non-exempt Chief Operators to the exempt rolls as Specialists-Separations Process. The number of non-exempt personnel decreased accordingly.

DECLASSIFIED
[REDACTED]

STAFF

Vice President and General Manager, Atomic Products Division . F. K. McCune
General Manager, Hanford Atomic Products Operation W. E. Johnson
General Manager, Chemical Processing Department W. K. MacCready
Manager, Production Operation J. H. Warren
Manager, Purex Operation O. C. Schroeder
Manager, Redox Operation C. T. Groswith
Manager, Finished Products Operation W. N. Mobley
Manager, Power & General Maintenance Operation T. G. LaFollette
Manager, Financial Operation K. G. Grimm
Manager, Facilities Engineering Operation H. P. Shaw
Manager, Research and Engineering Operation V. R. Cooper
Manager, Employee Relations Operation D. S. Roberts

CHEMICAL PROCESSING DEPARTMENT
NUMBER OF EMPLOYEES
APRIL 30, 1958

OPERATION	EXEMPT		OTHER		TOTAL	
	3-31-58	4-30-58	3-31-58	4-30-58	3-31-58	4-30-58
GENERAL MANAGER'S GROUP	10	10	1	1	11	11
PRODUCTION	7	7	3	3	10	10
PUREX	43	53	239	223	282	276
REDOX	53	63	277	264	330	327
FINISHED PRODUCTS	54	61	282	263	337	324
POWER AND GENERAL MAINTENANCE	42	43	229	224	271	267
FINANCIAL	21	19	45	47	66	66
FACILITIES ENGINEERING	75	74	23	21	98	95
RESEARCH AND ENGINEERING	64	64	23	23	87	87
EMPLOYEE RELATIONS	30	30	52	55	82	85
	399	424	1174	1124	1574	1548

UNCLASSIFIED

HW-55914 DEL

UNCLASSIFIED

DECLASSIFIED

HW-55914 **DEL**

CHEMICAL PROCESSING DEPARTMENT

PATENT SUMMARY
FOR
MONTH OF APRIL, 1958

All persons engaged in work that might reasonably be expected to result in inventions or discoveries advise that, to the best of their knowledge and belief, no inventions or discoveries were made in the course of their work during the period covered by this report except as listed below. Such persons further advise that, for the period therein covered by this report, notebook records, if any, kept in the course of their work have been examined for possible inventions or discoveries.

INVENTOR

None

TITLE

None

J. W. Warren

ACTING GENERAL MANAGER
CHEMICAL PROCESSING DEPARTMENT

DECLASSIFIED

DECLASSIFIED
WITH DELETIONS

HW-55914

DEL

CHEMICAL PROCESSING DEPARTMENT
PRODUCTION OPERATION

APRIL, 1958

I. RESPONSIBILITY

There were no changes in the responsibility assigned to the Production Operation during the month.

II. ACHIEVEMENT

A. Production Statistics

1. Purex Operation

	<u>April</u>	<u>March</u>
Tons Uranium processed	450.22	423.94
Average production rate during operation (T/D)	18.5	16.1
Total waste loss (%)		
Uranium	0.14	0.11
Plutonium	0.25	0.42
Average cooling time (days)	93	91
Minimum cooling time (days)	81	85
On-line efficiency (%)	81.5	85.2

2. Redox Operation

	<u>April</u>	<u>March</u>
Tons Uranium processed	106.8	104.6
Average production rate during operation (T/D)	7.6	6.2
Total waste loss (%)		
Uranium	0.31	0.27
Plutonium	0.33	0.39
Average cooling time (days)	93	92
Minimum cooling time (days)	87	85
On-line efficiency (%)	47.2	54.0

3. 234-5 Operation

	<u>April</u>	<u>March</u>
Batches input to Task I	269	303
Runs completed through Task III	184	182
Batches through Product Recovery	86	81
Reduction yield (%)	97.0	98.2
Waste disposal (units)	672.54	638.97

DECLASSIFIED
WITH DELETIONS

DECLASSIFIED

HW-55914 DEL

4. UC₃ Operations

	<u>April</u>	<u>March</u>	<u>To Date</u>
UO ₃ loaded (tons)	474.12	647.29	
UC ₃ approved for shipment (tons)	559.14	613.58	26,884.70
UC ₃ shipped (tons)	513.75	457.12	26,463.27
UNH backlog (tons)	209	142	

5. Power

	<u>200 East</u>	<u>200 West</u>
Raw water pumped (gpm)	7,132	3,327
Filtered water pumped (gpm)	809	767
Maximum steam generated (lbs./hr.)	192,000	119,000
Average steam generated (lbs./hr.)	134,210	88,242
Total steam generated (M lbs.)	96,631	63,534
Coal consumed, est. (tons)	5,798	4,109

6. Waste Storage

	<u>Equivalent Tons U</u>	<u>April</u>	<u>March</u>
Salt waste reserve storage capacity-Redox	3,049		3,156*
Salt waste reserve storage capacity-Purex	14,303		14,717*
Coating waste reserve storage capacity-Redox	41,211		41,318
Coating waste reserve storage capacity-Purex	42,973		43,387

*At 1100 TU/SX-Farm Tank and 3800 TU/A-Farm Tank.

B. Production Planning and Scheduling Operation

A new official forecast covering a period of eighteen months was prepared and issued to HCO-AEC. Except for a change in discharge concentrations, all major assumptions were essentially the same as those employed in the previous official forecast. The most significant change concerned the discharge concentration of I & E fuel elements, which was increased to 800 MWD/T versus the previous assumption of 650 MWD/T. This resulted in an over-all 10% decrease in uranium discharges during the next 18 months. Somewhat less total enriched metal was shown to be available, with equilibrium discharges (after completion of I and E loadings) reducing from 50 to 40 tons per month. Redox capacity was shown to be utilized only for enriched uranium processing, following the start of this type of production during the second quarter of FY 1958.

In accordance with a request made by HCO-AEC, the cost and feasibility of blending UNH streams of different uranium enrichments at HAPO was evaluated on a preliminary basis. The two cases studied were: (1) blending 37.5% enriched UNH with depleted E metal UNH to yield a

DECLASSIFIED

DECLASSIFIED

HW-55914 **DEL**

0.947% enriched end product; and (2) blending depleted E metal UNH with the normal stream of depleted natural uranium to yield a 0.7115% enriched end product. Study results indicated that although a reasonable degree of feasibility exists for either blend program at HAPO, considerably more exhaustive engineering work will be required for corroborative purposes before feasibility could be firmly established.

Two waste studies were completed during the month to develop information for presentation at the Washington public hearings on waste disposal. The first study was concerned with airborne contamination and control in the 200 Areas and was issued as HW-55569 RD. The second study was concerned with capital costs of waste facilities, operating and maintenance expenses of these facilities, and the research and development efforts on waste disposal.

There has been no change in the liquid level of Tank 105-SX since the vapor system was blanked-off last month. Close observations during the next two months are expected to establish that the previous liquid decreases were caused by vapors escaping into the vapor vent system.

Preliminary soil absorption evaluations conducted by HLO personnel indicated that 216-S-7 Crib may not be exhausted for several years. To date the crib has received about four column volumes of waste as compared with an estimated capacity of ten column volumes. Additional tests are being undertaken to confirm and supplement previous investigations.

C. Finished Products and Customer Liaison

The Fission Products Market Survey has progressed satisfactorily. Preliminary results of the survey indicate two distinct markets, commercial and military, with possibilities of the second being the only one at present creating optimism. The relatively high costs of cesium and other fission products in comparison with machine-generated radiation together with recent improvements in the technology of chemical polymerization, may very well lead to an early conclusion of the HAPO directed survey. On the other hand, the Martin Company is quite optimistic concerning the military potential and predicts a good market in this area, especially for strontium-90. The military potential (classified uses) is being determined by the AEC.

D. Essential Materials

A study was conducted at the request of HOO-AEC covering the consumption of essential materials in the 234-5 process during the latter part of 1951.

The first tank car of liquid sodium dichromate was received on April 28th. Plans to change to the exclusive use of liquid dichromate in lieu of dry material have been established.

E. Reports and Documents

1. Prepared and Issued

HW-55561	Redox Plant Production Schedule, April, 1958 B. F. Campbell
HW-55562	Purex Plant Production Schedule, April, 1958 B. F. Campbell
HW-55563	UO ₃ Plant Production Schedule, April, 1958 B. F. Campbell
HW-55564	234-5 Plant Production Schedule, April, 1958 B. F. Campbell
HW-55569 RD	History of Airborne Contamination and Control - 200 Areas, April 1, 1958, R. E. Roberts
HW-55603	Chemical Processing Department Daily Production Reports - January 1, 1958 Through March 31, 1958, H. F. Tew
HW-55610	Essential Material Consumption - Purex - Chemical Processing Department, for March, 1958 M. A. Thress
HW-55630	Chemical Processing Department Waste Status Summary - March 1 Through March 31, 1958, R. E. Roberts
HW-55648	Essential Material Area Report to Cost and Purchasing - Production Operation - Chemical Processing Department, March 1 Through March 31, 1958, M. A. Thress

DECLASSIFIED

DECLASSIFIED

HW-55914

DEL

HW-55681 Purex Plant Shutdown, April 10, 1958, R. E. Tomlinson

HW-55792 Blending UNH Streams of Different Uranium Enrichments, April 18, 1958, B. F. Campbell

HW-55861 Redox Plant Shutdown, April 25, 1958, R. E. Tomlinson

HW-55886 RD First and Second Quarters FY 1959 Forecast of Nuclear Materials Requirements, April 29, 1958, H. F. Tew

CLVI-358 Official Quarterly Forecast Chemical Processing Department - January, 1958 through December, 1958 - April 29, 1958, B. F. Campbell

HW-55450 History and Costs of Waste Storage at HAPO, March 24, 1958, R. E. Roberts

2. Prepared for Signature and Issuance

HW-55570 Production - March, 1958, W. E. Johnson

CLVI-355 HAPO Production Forecast - April 25, 1958, W. E. Johnson/V. R. Chapman

III. ORGANIZATION AND PERSONNEL

A. Force Summary

	<u>Beginning of Month</u>	<u>End of Month</u>
Exempt	7	7
Non-exempt	<u>3</u>	<u>3</u>
Total	10	10

B. Safety

There were no plant injuries incurred by Production Operation personnel during April, 1958.

C. Security

There were no security violations in the Production Operation during the month.

R. E. Tomlinson

Acting Manager
Production Operation

CHEMICAL PROCESSING DEPARTMENT
PUREX OPERATION

April, 1958

I. RESPONSIBILITY

There were no changes in the scope of responsibility of the Purex Operation.

II. ACHIEVEMENT

A. Processing Experience

1. Production Statistics

a. Production - Percent of Monthly Commitment.

Uranium	107.1 Percent
Plutonium	105.7 Percent

b. Production Rates

April 1 through April 3	1.92 CF
April 5 through April 13	1.92 CF
April 19 through April 30	2.16 CF

c. Operating Continuity 81.5 Percent

d. Waste Losses

Uranium	0.14 Percent
Plutonium	0.25 Percent

e. Product Recovered from Waste Streams by Reprocessing

Uranium	12,042 Lbs.
Plutonium	261 Units

f. Product Recovered from UO_3 Plant Wastes

Uranium	16.3 Tons
---------	-----------

g. Product Re-Treated in Silica Gel

Uranium	120 Tons
---------	----------

h. Recovered UO_3 Acid Used 446,907 Lbs.

DECLASSIFIED

DECLASSIFIED

2. Normal Processing

Processing continued from the March production period at a 1.92 CF rate until April 4 when a scheduled outage of 16 hours duration was made to bypass the precycle HC column, the HA concentrator, and the partition cycle 1A column, thus completing another step in converting the plant from three-cycle to two-cycle operation. Operations were then resumed at the same rate and continued until April 14. A scheduled 5-day shutdown was then taken to permit longer aging of the irradiated metal in the 100 Area basins. This shutdown afforded an opportunity to perform numerous equipment repairs and flushes of a shutdown nature; and in addition, as a further step in converting the plant to two-cycle operation, jumpers were installed to recycle the aqueous waste stream from the final uranium cycle 2D column and the final plutonium 2A column to the precycle HA column via the H4 concentrator. Operations were resumed on April 19 at a 2.16 CF rate and continued throughout the remainder of the month with the pseudo two-cycle operation.

Prior to the 5-day shutdown, both products met shipping specifications; however, the decontamination efficiency of the precycle HA column diminished just preceding the outage as a result of the rework of a large volume of non-refluxed 2WW recycle material. This condition continued upon resumption of operations following the shutdown until the rework material was depleted and the process fully recovered. As a result, 132 tons of high gamma uranium were segregated for processing through the silica gel unit, and three batches of plutonium were recycled through the building.

The aqueous waste backcycle stream, called the 3WB stream in the two-cycle flowsheet, was then started to recover the product from the final uranium cycle 2D column and the final plutonium cycle 2A column. Subsequent operation of the extraction columns was stable and high decontamination efficiency and product recovery was achieved.

Early in the month it was necessary to route the final plutonium stream through the L Cell concentrator package when the ion exchange resin push system became inoperative due to mechanical and instrument difficulties. An intolerable leak then developed in a piping weld on the line between the stripper and concentrator in the L Cell package and repairs to the ion exchange unit were expedited in time to pick up the production load. Operation of the ion exchange was somewhat erratic for a few days thereafter, but normalcy was attained by the end of the month.

The plutonium waste loss of 0.25 percent for the month is a new record low for the Purex Plant.

Self-concentration in the underground waste storage tanks 241-A-101, 102 (receiving building salt wastes), and 103 continued at rates of 10.0, 6.4, and 3.0 gallons per minute, respectively. Approximately 80,000 gallons of water collected in the 106 tank from

flushes and from the cyclone separator drain was pumped to 101 tank.

3. Special Processing

The final uranium cycle rates were increased two tons per day the latter part of the month to permit the rework of waste material from the UO_3 facility. Approximately 16 tons of uranium were reprocessed.

Early in the month, the uranium product was noted to have a high gamma ratio due to some short half-life fission products - presumably U^{237} and Np^{239} . Approximately 66 tons of this product was segregated and stored until the activity decayed off.

The silica gel facility was de-winterized and regenerated in preparation for treatment of 132 tons of uranium with a gamma ratio of 8.0. By the end of the month, essentially all of this material had been processed and the gamma ratio reduced to within specifications.

During the 5-day shutdown period, the waste concentration and acid recovery cell (F) was given a thorough caustic flush, which included the fractionating towers of the #1 and #2 acid waste concentrators.

B. Radiation Experience

The total monthly emission of radio-iodine was 30.3 curies. The CPD weekly limit of 10 curies was exceeded in one 7-day period. To control the emission rate, the vessel vent reactor was regenerated in mid-month and the B dissolver reactor was regenerated the later part of the period. The addition of mercuric nitrate to virgin feed batches was discontinued following regeneration of the vessel vent reactor since samples of the off-gas obviated the need for chemical additions to suppress iodine evolution from the vessel vent system.

Five persons were subjected to possible internal deposition of plutonium. Four cases involved air contamination above the permissible limit without respiratory protection, and the fifth case occurred when an operator received a puncture wound while working through rubber gloves in the ion exchange unit. Initial bioassay results indicate that no deposition occurred in any of the incidents.

Seventeen cases of skin contamination occurred during the month and all cases were readily decontaminated.

A total of 212 authorizations for 100 mrem per day exposure were approved for canyon decontamination, following cell work, and in the decontamination and repair of equipment.

Burial of the original L Cell concentrator package and the original final uranium cycle 2D column was performed without incident or spread of contamination.

DECLASSIFIED

DECLASSIFIED

HW-55914 **DEL**

C. Mechanical Experience

The remote crane became inoperative on April 1 as a result of a broken shaft on one of the two bridge drive wheels. The shaft was replaced and the crane returned to service in a period of 32 hours. Process continuity was not affected. Representatives of the FEO have been requested to investigate the cause of failure of the wheel shaft.

The high capacity acid concentrator feed pump F7, installed for two-cycle operation on March 13, failed due to excessive shaft seal leakage and high amperage and was replaced on April 21. This makes a total of four canyon pump failures at Purex since startup.

The canyon tunnel door was damaged beyond repair when one side slipped out of the track and permitted one side to close while the other side remained open several feet. This same door had been previously damaged and repaired during construction activities prior to acceptance by CPD, and consequently a spare was provided on the original Purex project. The spare door was used as a replacement.

The impact stud on the electrical jumper attached to the precycle HA column waste stream rotameter jumper sheared off during the installation of two-cycle jumpers and the two jumpers could not be separated for replacement. Pending fabrication of a special remote tool to loosen the broken stud, the column interface position is being controlled manually.

The installation of three in-line gamma monitors (HSP, LBP, and 2EU) was completed by Minor Construction forces. The monitors are now in service and operating satisfactorily.

The #1 acid concentrator liquid level dip legs, which are an integral part of the concentrator, became inoperative and an alternate jumper equipped with dip legs was installed as a replacement.

D. Analytical Experience

With the conversion to the pseudo two-cycle operation, the analytical work load increased somewhat, especially in samples for the gamma scan. Also process modifications required corresponding modifications of some of the analytical methods. At month's end the sample load has been considerably reduced and the analytical methods are in good control.

The responsibility for the 100 Area reactor water effluent analyses and the counting of the Purex Radiation Monitoring air samples has been accepted by the laboratory and both programs are in full operation. Additional training will be required before both programs can be fully integrated into the laboratory schedule. Approval was received at the end of the month to purchase a 256 channel pulse height analyzer to better facilitate the reactor effluent analytical program.

E. Improvement Experience

1. Process Tests and Revisions

(For more detailed information on these and other items see the Research and Engineering portion of the CPD monthly report.)

Following jumper changes to bypass the precycle HC column and the partition cycle 1A column on April 4; and installation of the jumpers on April 18 to backcycle the aqueous waste streams of the final uranium cycle 2D column and the final plutonium cycle 2A column, all production was accomplished on the pseudo two-cycle operation without benefit of an HS column, which is part of the two-cycle conversion package. The excellent decontamination efficiency and product recovery achieved in this test further demonstrates the feasibility of the proposed two-cycle operation.

2. Inventions and Discoveries

No inventions or discoveries were reported by Purex personnel during April.

F. Events Influencing Cost

The ceramic berl saddle coating unit was again placed in operation and 87 cubic feet of saddles were coated with silver nitrate during the period. The cost of this work was performed \$10,000 below the best vendor bid estimate. CPD will profit by the savings.

Some reduction in steam and essential material (HNO_3) usage is expected to result from the two-cycle conversion steps made during the month.

III. ORGANIZATION AND PERSONNEL

A. Safety

There were no disabling injuries or serious accidents at Purex during April. A total of seven medical treatment cases were reported.

B. Security

There were no security violations reported during April.

C. Personnel Activities

R. M. Hill, Radiation Monitoring Supervisor, resigned on April 30 to accept employment elsewhere.

On April 1, eleven Separations Chief Operators were promoted to the newly-created position of Specialist - Separations Process, which obviates the old Chief Operator classification.

DECLASSIFIED

DECLASSIFIED

HW-55914 **DEL**

One Level 4 Manager and one Level 4 Specialist attended the Management Conference on Communications.

A two-hour training session was conducted to instruct personnel in the safe working techniques around and inside glove hoods. Purex Process Operators, Maintenance Craftsmen, and Radiation Monitoring personnel attended.

S. H. Smolen

Acting Manager
PUREX OPERATION

SG Smolen: JCG:gt

DECLASSIFIED

DECLASSIFIED

HW-35914 **DEL**

CHEMICAL PROCESSING DEPARTMENT
REDOX OPERATION

APRIL, 1958

I. RESPONSIBILITY

There were no changes in the scope of responsibility of the Redox Operation this month.

II. ACHIEVEMENT

A. Processing Operation

1. Production Rates and Operating Continuity

Processing Operations were maintained as per schedule throughout the month. Operations were started at 0715 on 4-13-58 at a nominal 80% rate. Except for a delay of approximately 20 hours on 4-22-58 and 4-23-58, when the silic operation was shut down for column flushing, operations were continuous until 0645 on 4-28-58, at which time the monthly production was achieved.

The monthly production commitment was exceeded by 6.8% while operating at 47% of the total hours in the month. The mechanical efficiency for the month was 94%. No canyon equipment failures were experienced during the April production run.

All UNH produced during the month was within shipping specifications; however, 24, E-12 batches with excessive gamma activity were ozonated and processed through silica gel to meet shipping specifications. All plutonium produced, except four PR cans immediately following start-up, was within shipping specifications. The four PR cans, which were above gamma specifications, were reprocessed via the head-end procedure. Product waste losses were 0.33% and 0.31% for plutonium and uranium, respectively, and all waste solutions produced were within discard specifications.

Iodine-131 emission to the 291-S stack was well under control throughout the month averaging 0.26 curies per day. No uncontrolled high emissions occurred.

Two batches of E-metal were processed through the C-2 dissolver during the month. This completes the initial six shipments, on a test basis, which was agreed to during December, 1957.

Twelve of the 16 containers of waste material received from the Argonne National Laboratory have now been processed through the Redox Plant without incident. The four remaining containers, which contain alkaline wastes in contrast to the acidic wastes already processed, will be processed, but with additional precautions to assure recovery and complete dissolution of the solids that may be present.

DECLASSIFIED

DECLASSIFIED

HW-55914 **DEL**

Decontamination efforts on the Redox canyon crane were continued during the scheduled shutdown at the beginning of the month. The crane is now in presentable condition, but further work to improve and maintain its condition are warranted and will be continued during future shutdown periods.

2. Equipment Experience

a. H-2 Centrifuge

The H-2 centrifuge, which was installed on 2-11-58, was replaced during the scheduled shutdown period early in the month (4-4-58). Replacement was necessary due to a leak in the hydraulic lines to the right hand skimmer. As reported in March, investigation disclosed that the lining in the flexible hoses in the centrifuge hydraulic lines was "Fluorflex-T", a teflon base compound. It has been estimated that the radiation intensity at the hose position on the H-2 centrifuge is such that teflon will begin to be affected in approximately ten hours. This could very well explain the early leak which developed in the right hand skimmer. For this reason, the hydraulic lines on the replacement centrifuge were altered to a solid pigtail type stainless steel. To date, centrifuge performance has been satisfactory.

b. F-1 Pump

The F-1 feed tank pump was replaced on 4-11-58 due to excessive leakage at the flange. The original pump had been in service for approximately seven months.

c. Other Canyon Cell Equipment

A total of ten jumpers were installed during the month. Four of the jumpers were in connection with the H-2 centrifuge change-out and two were on Project CG-686, "In-Line Monitoring Instruments, Redox and Purex".

B. Maintenance Operation

The replacement H-2 centrifuge which was installed on 4-4-58 is equipped with solid stainless steel pigtail type hydraulic lines and lead shielded hydraulic cylinders to prevent radiation damage to the neoprene hydraulic cups. Skimmer performance with the solid hydraulic lines seems to be much improved in that the response to movements of the control lever is smooth and immediate. A new lubrication jumper was also installed to avoid any radiation damage to lubricants. It is expected that the modifications made will prolong the life of the centrifuge skimmers and thus resolve the difficulties which have been experienced with this equipment.

Leakage at the flange of the F-1 feed tank pump became excessive during the latter part of March and the pump was replaced on 4-11-58

DECLASSIFIED

after 31 weeks of service. The new pump, like the old one, is an open head pump designed to allow the liquid leaking past the throttle bushing to return to the tank. Although the open head type pump has been very successful in the F-1 position several modifications were made on the replacement pump in an effort to extend the pump life. These included: (1) an additional shield to deflect the liquid back into the tank, (2) glass bearings, and (3) a glass throttle bushing. The latter two modifications should minimize wear and thus lessen the amount of leakage. Optimism is very high as to the future performance of this pump.

The experimental direct drive agitator, which was installed in the D-2 crib sampling tank on 1-21-58, was removed this month and sent to the 221-U Canyon Building for inspection. The unit has experienced a series of electrical difficulties including a burn-out of one of the wall connectors. It is felt that the failures are due to some electrical fault in the motor wiring or junction box. Mechanically, the unit has proven very satisfactory.

Fabrication of a proto-type silver reactor and heater for the Process Chemistry Operation was completed this month. This equipment is to be used in an effort to resolve the difficulties recently encountered with a Purex reactor. As a safety measure, the unit has been provided with explosion proof shielding.

Operation of the 60 Ton Canyon Crane was comparatively trouble free this month. Preventive maintenance included the replacement of the ten ton limit switch, the brake drum on the left hand side, and brushes on the main travel motor generator. The left hand optic head was also replaced during the month because of its failure to change optic powers. The difficulty experienced appears to be in the rotary solenoids which are under-designed. To correct this difficulty, plans are now being made to double the number of solenoids in the optic heads.

C. Waste Handling and Decontamination Operation

1. Waste Handling

Redox Coating Waste Received (S Farm)	15,380 gallon
Redox Salt Waste Received (SX Farm)	114,747 gallon
Total Gallons Boil-Off Salt Waste	149,040 gallon
Waste Received at TX (221-U)	25,000 gallon

2. Equipment Decontamination and Repair

a. Regulated Steam Pit

A total of fifteen vehicles, three pieces of heavy equipment, and seven miscellaneous items were decontaminated during the month. The total manhours charged to this operation was 148.

b. Railroad Equipment

DECLASSIFIED

HW-55914

DEL

A total of 356 manhours was charged to this operation. The work included the decontamination of two locomotives and one burial string, changing casks in well cars No. 37 and 99, decontamination, repair and modification work on well cars No. 98 and 99.

c. 221-U Building

Purex Operation Equipment

Run-in of the P-J-1 pump was completed and the pump returned to the customer. Final testing of the A-D-4 agitator was completed and the equipment made ready for shipment. A net savings of \$11,153 over the cost of new equipment has been realized.

Redox Operation Equipment

The J-19-4P-130 (F-1) pump was decontaminated, dismantled, repaired, and is now awaiting final testing prior to shipment. Pumps J-19-23P and J-19-2P-137 have been reassembled after decontamination and repair, but are awaiting a new motor and new bearings, respectively. One H-2 centrifuge electrical jumper was successfully decontaminated and made ready for repair.

3. Miscellaneous Activities

- a. One Redox equipment burial was conducted during the month and included unrepairable and grossly contaminated equipment removed from the 202-S Building Canyon.
- b. Decontaminated the vertical door to the 202-S Building railroad tunnel. Sand blasting which was incorporated into the decontamination procedure proved to be very successful.
- c. Decontaminated and placed in overground storage ten (10) Armstrong filters for the Finished Products Operation.
- d. Decontaminated sections 6 and 7 in the 221-T Canyon Building electrical gallery for the Power and General Maintenance Operation.
- e. One spent silver reactor from the Bismuth Phosphate Plant (221-T) was loaded and shipped to the Oak Ridge National Laboratory on 4-29-58.

4. Special Activities

Plans and preparations are now being made for the loan of a 40 inch "Bird" centrifuge to the Chemical Engineering Development Group of the Hanford Laboratories Operation. Present schedules indicate that the item will be used for approximately 18 to 20 months in the 321 Building, 300 Area, for development

studies on fission product recovery (notably cesium recovery). This centrifuge is identical to the proposed production scale equipment.

The Irradiation Processing Department has contacted the Waste Handling and Decontamination Operation on the possibility of having their dummy slugs decontaminated in the 221-U Canyon Building. Three buckets were received on 4-29-58 to be decontaminated on a test basis. Future business will be contingent upon cost and effective decontamination.

D. Analytical Control Operation

1. Control Statistics

<u>Month</u>	<u>Samples</u>	<u>Determinations</u>
March	2140	5458
April	2202	5650

2. Assistance to Process

Specific activity and the Isotope Correction Factor for Chalk River material in shipment No. 5 were evaluated from analyses by alpha energy scans, thermal emission mass spectrometer, X-Ray and plutonium procedures. Results have been forwarded to S. S. Accountability Operation for use in furnishing a statement of plutonium and uranium received to the AEC.

Rush analysis by gamma ray spectrophotometer for radioactive elements on metal coupons removed from 100 Area reactors has been set up for 24 hour coverage for the Reactor and Fuels Research and Development Operation. Various standards have been requested from the Hanford Laboratories Operation for application to these gamma scan analyses to insure provision of increased interpretation and accuracy.

Assistance was given to the Purex Analytical Control Operation in identifying a low gamma energy component that caused their uranium product to be out of specifications.

Studies were completed this month on the apparent discrepancies in amounts of iodine found in the gas discharged through the Redox stack as reported by Radiological Sciences and the Redox Analytical Laboratory. Differences which appear to be due to sampling variations are currently being resolved.

3. Equipment Experience

Both Gamma Ray Spectrophotometers are now operating on the normal long scan time cycle. This insures adequate backup for the high priority short half-life scanning of the 100 Area metal coupon samples and still provides rapid service to the Redox Plant since the UNH material can be scanned by an abbreviated procedure

DECLASSIFIED

DECLASSIFIED

HW-55914 DEL

rather than by the faster gear drive used in the past. A "Counting Rate Correction Factor" has also been introduced for the gamma scans to eliminate any errors introduced by the changing counting characteristics and the differences in response between the two instruments. This will insure that valid quantitative results are furnished where counting rates are requested.

4. Analytical Procedures

Referee and standard range limits for samples submitted in the Quality Control Program were revised as dictated by performance over the past six months. The majority of these limits were made tighter or had no change and indicates improved performance by laboratory personnel. Concentrations of standard samples were reviewed and changed where necessary to be of approximate concentration with plant samples.

A study was made this month to determine the feasibility of applying a uniform iron correction to the Redox L-6 Pu sample by X-ray determination. The variation in the amounts of iron found and the absence of any correlation with Pu content has dictated the necessity for continuing individual analyses on each L-6 batch.

A test on the I^{131} procedure set up several months ago to determine efficiency of the 293-S Building caustic scrubber for removing iodine from the off-gas showed that ruthenium did not interfere with the results obtained.

E. Radiation Monitoring Operation

Radiation control in the Redox Operation was again quite good during the month. Six radiation occurrences were recorded.

In support of considerable preventive maintenance work on the 60 Ton Canyon Crane, the crane decontamination program was continued this month. The east catwalk was decontaminated, reducing general personnel dose rates from 1500 mrad/hr to 500 mrad/hr. The west catwalk was cleaned as time limits allowed, and the general levels were reduced from 5000 mrad/hr to 1000 mrad/hr. Significant also was the change-out of the left hand crane optic in nine hours as compared to 54 manhours required in making a previous replacement during March. This was primarily due to the decontamination work which has been accomplished.

Two highly contaminated equipment transfers were made from the 202-S Building to the 221-U Canyon Building this month without incident. The equipment included an H-2 centrifuge and an H-2 electrical power jumper which are to be decontaminated and repaired. Dose rates up to 1.2 r/hr at 50 feet were encountered during the transfers.

Several entries were made to the 233-S Building Greenhouse in prep-

for the installation of the IS-1 pump and catch tank during the early part of May. Plastic men and plastic lean-ins were used and contamination control was excellent.

F. Improvement Experience

1. Process Tests and Revisions

Information related to this item is covered in the Research and Engineering portion of the Department Report.

2. Miscellaneous Improvement Items

Two micro-cleaner filter chambers were installed in the inert gas header at a point near the entrance of the inert gas to the 233-S Building. A catch tank with diffusing baffle plates was also installed to separate the moisture from the inert gas. These installations are expected to significantly improve the quality of the inert gas to the 233-S Building.

In the Waste Handling and Decontamination Operation excellent results in high level decontamination are being achieved on test runs using Turco 4501 solution. Equipment pieces reading up to 2 r/hr have been decontaminated to 200 c/m. Further tests are being made to determine optimum temperatures, concentrations, corrosion, methods of application and waste disposal.

A recirculator line was installed on the recovered acid storage tank at the 293-S Building on 4-2-58. This will provide better blending of the recovered acid from the 293 acid absorber and subsequently more accurate sample analyses.

Preliminary work for reclaiming spent silver nitrate reactors was started this month in the Waste Handling and Decontamination Operation. Laboratory studies and experience indicate that the spent reactors can be successfully flushed and recharged with fresh silver nitrate. The reclamation cost is expected to be about \$2,000/unit as compared with approximately \$7,500/unit for fabrication of new reactors.

3. Inventions or Discoveries

There were no inventions or discoveries of a patentable nature reported in the Redox Operation during the month of April, 1958.

G. Events Influencing Costs

The first tank car shipment of liquid dichromate was received at the Redox Plant on 4-28-58. The use of liquid dichromate in place of solid will eliminate troublesome handling and storage problems as well as result in an annual cost savings in essential materials of approximately \$5,000.

DECLASSIFIED

DECLASSIFIED

HW-55914 DEL

Much experience has been gained during the past eight months by the Redox Waste Handling and Decontamination Operation with respect to the reclamation of highly radioactive equipment. Equipment pieces with radiation levels greater than 300 rad/hr at five feet have been successfully reduced to 25 mrad/hr at surface to allow contact maintenance. Sixteen pieces of equipment ranging from pumps to concentrator heat exchangers with a current value of approximately \$86,000 have been recovered to date at a cost of \$30,000.

In addition to the above, this operation has decontaminated 65 automotive vehicles, 15 locomotives, 21 flatcars, 10 Chalk River casks, and 67 pieces of miscellaneous equipment. Also, five process pumps and one agitator with a total value of \$40,000 have been cleaned and dismantled ready for repair.

The first IBM run issued by the Financial Operation indicates a spare equipment inventory for Redox of \$1,526,359. Some discrepancies have been uncovered and corrections are being made so that future runs will become increasingly more accurate. It is felt, however, that the above figure is within 5% of our actual inventory. Spare parts and spare equipment inventories were reduced by \$3,350 and \$14,600 respectively, this month.

Expenditures for equipment took a decided drop for the month of March, in that \$8,425 was spent for equipment compared to an average monthly cost of \$30,000 for the first eight months of FY 1958. On the other hand, the applied material costs were \$10,200 over the budget primarily due to the installation of a reboiler section in the 233-S Building. Installation of the liquid dichromate system, fabrication of a prototype silver reactor for the Process Chemistry Operation, and fabrication of several flexible electrical connectors.

H. Plant Development and Expansion

i. Preparatory Engineering

Replacement of the Redox 216-S-7 Crib

Since last months reporting, data secured by Chemical Effluents Technology indicates that the life of the existing condensate crib is to be longer than formerly expected. "Spike" samples, using the critical elements, have been taken from a soil column using earth's representative of the 216-S-7 crib. Preliminary estimates are that this crib may last two years. Project proposal preparation will continue, but schedules for design, bidding, etc., will be relaxed from the original completion date of October, 1958.

Cask Car Contamination

In a meeting between representatives of the Redox, Purex, and Production Operations, it was agreed that the hinged lid proposal

lacks the necessary justification for the expenditure of \$128,000. Concurrence was reached that submerged cask flushing in the 105 basins, supplemented by well jet-out facilities, is the first alternate to be taken. A Contingency Maintenance Request (OPG 5.3) has been approved by level three managers for installation of flushing manifolds in all CPD process casks. Estimate for the work, including decontamination, is \$24,396. A work review for performance by plant forces has been approved by the legal staffs of AEC and GE. Transfer area procedures at each 105 Building must be modified to incorporate submerged flushing of each cask in the basin prior to transfer to the well cars. The Redox Operation will assume the integration of this procedure change.

CA-783, Additional Fire Protection, 222-S

A revision of the project proposal has been made, incorporating a complete sprinkler system for the second floor of the 222-S Building. Preliminary estimates place the cost at \$4,500 under the cost of a partial system. This is accounted for by elimination of a detector system, a changed market situation since the first estimate was made in September, 1957 and highly competitive bidding for the Commission's fire protection business.

Decontamination Building - Waste Handling and Decontamination Operation

A design order in the amount of \$2,000 has been issued to the Project Operation for preparation of a project proposal for a vehicle and equipment decontamination building at W Plant. Location is to be near the 211-U railroad spur where necessary service facilities are available. The building is to be of insulated steel, to contain a trestle-type pit for railroad equipment cleaning and a pit and rack for automobile decontamination. Ventilation is to be provided in the pits to allow steam cleaning. A 211-U tank is to be employed for hold-up storage of contaminated drainage. Preliminary estimate is \$180,000 with a three year pay-out. The cost is of this magnitude because of construction features that permit future installation of a 200 North Area crane for handling of casks in the power fuels program.

2. Design and Construction Liaison

CG-648, Redox Auxiliary Iodine Removal and Nitric Acid Recovery

Design is progressing on revisions to the oxygen analyzer piping and a fail-safe system for the three way valves. The 5 HP motor on the acid tank pump (to 202-S) was replaced by a 7 1/2 HP motor on 4-29-58. This motor change was necessary to prevent overloading when the dissolver metering instrumentation is installed.

CG-686, In-Line Monitoring Instruments - Redox

DECLASSIFIED

DECLASSIFIED

HW-55914 **DEL**

The 2 EU sampler jumper was installed on 4-28-58. Installation of a glass lined cell in the sampling box will permit utilization of this monitor during May. The leak in the IBP monitor has been confirmed as in-cell by pressure testing to the canyon wall. Regasketing of the jumper is expected to correct this condition. The L-9 alpha monitor is currently being calibrated and an estimated in service date of May 10, 1958 has been forecasted.

CG-692, Modifications to Redox 233-S Concentration Building

All exceptions to project close-out have been completed by work order to the Redox Maintenance Operation. A Physical Completion Notice has been issued showing a total cost of \$126,333, an approved overrun of approximately 5%. This is the final report on Project CG-692.

CG-717, Transfer Facilities for Redox Non-Boiling Wastes

The Construction Operation has completed all work except for minor clean-up. All equipment at the SX Tank Farm is ready for pump-out of the 103 SX Tank. Jumper changes are currently being made and actual pumping of non-boiling salt waste to the TX Tank Farm for permanent storage will be done during May, 1958.

CG-720, Modifications to Redox SWP Facilities

All exceptions to the project have been completed either by Construction Operation or by work order to Redox Maintenance. This is the final report on Project CG-720.

CG-722, Utilization of 224-J Acid at Redox

The project proposal revision 3 requesting performance of work by the HAPO CPFT Contractor has been routed to the HAPO Manager for approval.

CG-764, Test Wells - 216-BC Crib Area

Drilling on the first well (699-35-53) was begun 3-31-58. Government drilling equipment was used on well 699-35-54 where contamination was encountered at a depth of 20 feet as expected. Continuous monitoring is provided at this site to maintain surveillance over radiological conditions and contractor's personnel. The contractors completion date is 7-8-58.

CG-772, "E" Metal Dissolvers - Redox

Revision I of the project proposal is circulating within GE for approvals. The scope provides for two vessels in place of three, design for processing power fuels and provision for dissolution of the higher enrichment elements. Forty drawings are required. A list of engineered material has been furnished

by CEO and materials for the first dissolver are being located. Comment issues of drawings are scheduled for the first week in May.

I. Reports Issued

No secret reports were issued by Redox Operation personnel during the month of April, 1958.

III. ORGANIZATION AND PERSONNEL

A. Safety

There were no disabling injuries, serious accidents or incidents in the Redox Operation during April, 1958. Fourteen medical treatment injuries were reported during the month.

B. Security

There were no security violations in the Redox Operation during the month of April, 1958.

C. Personnel Activities

Effective April 1, 1958 the Redox Chief Operators were reclassified to Specialist and placed on the exempt roll.

J. C. Langford, Analytical Chemist, attended the National Convention of the American Chemical Society in San Francisco on April 14 - 18, where he presented a paper on "The Analysis of Trace Activities of Cesium - 137 and Cobalt-60 in Hanford Waste Solutions". He also discussed radiochemical problems and radiochemical instrumentation at the Stanford Research Institute and the University of California Radiation Laboratory.

On April 2, 1958 the American Petroleum Committee on deep-well waste disposal was conducted on a tour of the Redox Plant. This committee was at HAPO for a series of conferences on our waste disposal practices.

On April 15, 1958, Messrs. Robert C. Scheid and John R. Craig of the Central Intelligence Agency visited the Redox Plant. They were accompanied by John G. Anderson of AEC Intelligence.

Chas. S. Grosz
 Manager
 Redox Operation

CT Groszwith:HWM:rc

DECLASSIFIED

CHEMICAL PROCESSING DEPARTMENT
FINISHED PRODUCTS OPERATION
MONTHLY REPORT

APRIL 1958

DECLASSIFIED
WITH DELETIONS

I RESPONSIBILITY

There were no changes during the month in the responsibilities assigned to the Finished Products Operation.

II ACHIEVEMENTS

A. Metal Finishing Operation

Seventy-six percent (76%) of the schedule for plutonium buttons was satisfied. Operating activities for April were somewhat unusual for the preparation of plutonium metal. Considerable time was lost during the first nineteen operating days of the month due to a lack of feed from the primary plants, and schedules suffered. It was possible for Redox and Purex to recover significantly on the last week-end of the month and a goodly supply of feed was available for the last three days of the month. Equipment and process difficulties of a severe nature were encountered and satisfactory progress was not demonstrated, and the commitment for button production for the month was not met although year to date schedules are slightly ahead. Enough material was on hand to satisfy delivery schedules and, therefore, there will be unfavorable impact on customer sites. The feed situation is such that the material on hand at month-end can be processed during May. There will be no overall adverse effects on departmental output.

B. Product Recovery Operation

Recuplex experienced a record month in all phases of operation. Completed were 95 slag crucible dissolver runs, 115 batches of fluoride and/or oxide powders dissolved in newly installed small pots and 57 metal dissolving runs. 85.7 Kg of plutonium were produced through the extraction section which had an 89.7% operating efficiency, 1761 liters per day instantaneous rate and column losses at 0.43% of throughput. Backlog of recoverable scrap currently in Product Recovery Feed Storage Inventory has been reduced by 71 Kg to 153 Kg.

DECLASSIFIED
WITH DELETIONS

DECLASSIFIED

HW-55914 **DEL**

C. Uranium Reduction Operation

April production was routine with schedules being exceeded again by two percent. All shipping schedules were met easily. April production was accomplished on a five-day work week during the last half of the month. A total of 293,079 lbs. of 100% nitric acid was shipped to Purex during April along with 130,053 lbs. being sent to Redox. At month end there was 181 tons of uranium as UNH stored in various locations awaiting processing through the Uranium Reduction Operation.

April was again routine with regard to mechanical difficulties. One calciner was overhauled due to shear pin failures brought on by faulty design of a "keeper" used to retain these pins within the equipment.

Operations were shut down from Friday midnight to Monday 12-8 shift during the last two weeks of the month to ascertain if a five-day work week was feasible at this location. Only minor difficulties arose as a result of these shutdowns and the plan appears practical. Two more shutdowns of this type are planned to firm up procedures needed to insure a minimum of lost time, and maximum equipment efficiency under this type program. Current plans call for a change to a standard five-day work week at this location by mid May.

D. Maintenance Operation

The major maintenance problems in Z Plant continued to concern the equipment in 9B Hood (Continuous Task I and II). The bulk of the trouble during the month consisted of leakage and plugging of the off-gas system. Maintenance activities in the various other Tasks, Recuplex and the Plutonium Metallurgy Operation (HLO) were routine. Maintenance of the 234-5 Building general was also routine but with one major item which involved the plugging of the P-6 drain system (contaminated sewers).

Equipment performance at the Uranium Reduction plant during the month continued favorable with a normal (consistent with the last three months) amount of maintenance repair work required. There were five minor calciner failures during the month and the usual amount of maintenance repair work on electrical, motors, pumps, filter system, Hammel-Dahl valves and instruments. All calciner modification work approved and scheduled to date has been completed.

E. Analytical Control Operation

A total of 6681 determinations were performed on 1310 samples received in the Analytical Control Laboratory during the month.

One hundred ten percent (110%) of the April commitment for 6506 and 6507 parts met the Inspection requirements. Since the

DECLASSIFIED

DECLASSIFIED

HW-55914 DEL

E. Analytical Control Operation (Cont'd)

actual numbers are small, this does not indicate the magnitude of fabrication difficulties nor the amount of actual inspection time involved. Rework was high, some parts requiring additional work as many as three times. However, the quality of accepted pieces is good. Radiographic quality of material was very good this month. Oxidation and corrosion difficulties have been corrected, and at the moment, are no longer a problem. Installation of an Electro-dryer will proceed as planned in order to fully insure a dry hood atmosphere.

F. Radiation Monitoring Operation

Eight radiation occurrences were documented in April as compared to seven in March. The breakdown for the various operations is as follows: Metal Finishing 2; Maintenance 4; Uranium Reduction 2; Product Recovery, Radiation Monitoring and Analytical Control none. Fifteen cases of skin contamination were reported in April as compared to twenty-one in March. The breakdown for the various operations is as follows: Metal Finishing 4; Product Recovery 1; Maintenance 6; Analytical Control 2; Uranium Reduction 2; and Radiation Monitoring none.

Further improvement was noted in the radiation exposure problems associated with plutonium reduction, fabrication and recovery. If the present rate of exposure accumulation continues through the year the average exposure will be 2.6 r for operators in the Metal Finishing and Product Recovery Operations.

The stack emission daily average during April was 260 uc plutonium as compared to 186 uc in March. A new additional filter box was placed in the exhaust system of the 9B Hood and during the following week emissions were sharply reduced (to as low as 10 to 20 uc/day). Continued improvement is anticipated. Also, a study of all contributing sources of stack contamination is in progress.

G. Improvement Experience

1. Process Tests and Revisions

Information relating to this item will be covered in the Research and Engineering portion of the Department report. Other information concerning Weapon Data will be covered in a separate report to be written at a later date.

2. Inventions or Discoveries

No inventions or discoveries of a patentable nature were reported during the month.

DECLASSIFIED

DECLASSIFIED

HW-55914 **DEL**

H. Events Influencing Cost

In the Uranium Reduction Operation a reduction of total manpower by four, made possible by elimination of four former Chief Operators should affect costs favorably for April and subsequent months.

A standard five-day work week will be established at the Uranium Reduction Operation during May which will again reduce manpower requirements there by 15% to 18%, and further reduce unit costs.

I. Plant Development and Expansion

1. Project CG-691 - Improved Task I and II

The installation of equipment has proceeded largely as expected during the month. Functional testing was started in Hood 7A. It is anticipated that all construction work will be complete by the middle of May.

2. Project CG-723 - Recuplex Conversion

Construction forces have started the installation of the filtrate concentrator. On-site fabrication has been completed and deliveries are expected May 1. Work orders were issued to plant forces for their portion of this work.

3. Project CG-734 - RMC Button Line

Detailed design completion has been delayed until May 15, due to additional work required in providing shielding. The procurement of material and equipment has been started and requisitions have been issued in the amount of \$215,000. Only long delivery items have been ordered for Hood 6 (Lag Feed Storage) until an equipment evaluation and cost estimate can be obtained.

4. Project CG-745 - RMC Fabrication Line

Project plans and schedules were reviewed taking into account an apparent change in the fabrication schedule, effective July 1. Since this review, another change in schedule has taken place and, of course, another review will be necessary. At the present time it has been decided to expedite the inspection portion of the equipment to be provided. The special fabrication hoods will be installed as originally scheduled, that is, by November.

The removal of the obsolete RG equipment has been completed by construction forces who are now in the process of removing the soffit which provided a part of the barrier partition.

DECLASSIFIED

DECLASSIFIED

HW-55914 DEL

5. Project CG-756 - Fire-Resistant Filters, Etc.

The replacement filter boxes provided by this project are scheduled for shipment April 30. No installation work will be planned until all materials are on site. Construction forces have completed some of the preparatory work on the installation of these boxes, such as the removal of wall section in order to accommodate the work. The oil in the hydraulic system of the freight elevator was replaced with a fire resistant type.

6. Project CG-789 - Additional Fire Protection, 234-5

Facilities Engineering has started a review of building structure, material handling, and operational procedures in order to determine what additional fire protection may be required. A third party review was conducted during the month but the opinions are not yet available.

7. Project CAC-798 - Cribs and Test Wells, 234-5

A project proposal requesting \$125,000 has been submitted to the AEC for approval for design and construction of a crib and test wells for 234-5 wastes. Beneficial use of the cribs is scheduled for nine months after authorization.

8. Project CGC-800 - Reduction of Radiation Exposure, RMA

A project proposal has been submitted to the AEC requesting \$30,000 for design necessary to reduce radiation levels on the RMA Line, 234-5 Building. Revision I of the proposal is being prepared asking for completion of design funds and construction funds. This revision is to be submitted in May.

9. Project CG-725 - Liquid Waste Handling, 224-U

The Facilities Engineering Operation has been requested to review a pot concentration approach to solution of this problem as a means of reducing capital investment as compared with the presently planned approach.

10. Project CG-722 - Utilization of 224-U Acid

There were no significant developments with respect to the Finished Products Operation.

11. Project CG-770 - Feed System and Powder Pick-up, 224-U

This project will be completed and closed out in May.

12. Project CG-767 - Miscellaneous Improvements, 224-U

There were no significant developments with respect to the Finished Products Operation.

J. Reports Issued

HW-55809 Chemical Processing Department, Finished Products
Operation, Z Plant Monthly Report, March 1958, W. N. Mobley

III ORGANIZATION AND PERSONNEL

A. Organization Changes

As a result of the discontinuance of the non-exempt classification, "Separations Chief Operator", and the establishment of the new exempt position, "Specialist, Processing", the following changes were made in the Finished Products Operation.

1. Chief Operators, J. A. Clark and D. H. Doerge, were promoted to the new classification and assigned to the Redox Operation.
2. Chief Operators, E. E. Clark, L. G. Swanson, J. A. Florian, and R. P. Monroe, were promoted to the new classification and assigned to the Product Recovery Operation.
3. Chief Operator, V. C. Haugen, was promoted to the new classification and assigned to the Metal Finishing Operation.
4. Chief Operators, D. H. Underwood and A. G. Gilbert, were promoted to the new classification and assigned to the Uranium Reduction Operation.
5. T. B. Griffith, Supervisor, Processing, Metal Finishing Operation, was reclassified to the new position of Specialist, Processing and was assigned to the Uranium Reduction Operation.
6. Chief Operators, R. E. Seymour, W. H. Smith and D. McKenzie, were reclassified to Separations Process Operators and assigned to Redox, Metal Finishing, and Uranium Reduction Operations, respectively.
7. V. W. Smith, Supervisor, Processing, Days, Uranium Reduction Operation, was transferred to the same position in the Metal Finishing Operation replacing Mr. Griffith. Mr. Smith's former duties were absorbed by Shift Supervision, Analyst, and Specialist at his former location.

In addition to the above changes which resulted from the reclassification the following also took place.

1. W. W. Kinney, Technical Graduate, from the Rotational Program was employed by the Metal Finishing Operation in the position of Specialist, Processing.
2. R. E. Preston, Supervisor, Analytical Control, was transferred to the Redox Operation to fill a vacancy in a similar position there.

DECLASSIFIED

HW-55914 DEL

III ORGANIZATION AND PERSONNEL (Cont'd)

B. Safety Experience

No disabling injuries or near serious accidents occurred during the month. Ten medical treatment injuries were experienced as compared to fourteen in March. The frequency rate decreased from 2.18 to 1.92.

C. Radiation Experience

All significant information relative to radiation experience in the Finished Products Operation is carried in this report under Radiation Monitoring (Item II-F).

D. Security Experience

No security violations were experienced during the month.

E. Personnel Activities

Approximately thirty employees, exempt and non-exempt, attended the various training courses offered by the Employee Relations Operation, ranging from PBM-1 to Cost Control.

Twenty-seven employees heard the tape recording of Major Mayer's speech, "The New Weapon - Brainwashing".

Approximately thirty supervisors viewed and discussed the management film entitled, "Patterns".

Recuplex Operators attended a series of training lectures conducted by the Process Technology group. Benefits are evident in the fine operational performance experienced this month.

W. N. Mobley, Manager, Finished Products Operation, and G. E. Backman, Manager, Radiation Monitoring Operation, Finished Products Operation, attended a Symposium on Plutonium Fuel Elements. Mr. Backman presented a paper entitled, "Radiation and Contamination Control in the 234-5 Building", to the assembly.

F. Miscellaneous

During the month, P. B. Fisk, Supervisor, Final Inspection, visited the Dow Chemical Company, Rocky Flats Plant, for the purpose of observing their testing of the first two 65 model assemblies manufactured at HAPO.

W. N. Mobley, Manager
Finished Products Operation

WNM:JPT:jjh

DECLASSIFIED

HW-55914 ~~DEL~~

CHEMICAL PROCESSING DEPARTMENT
POWER AND GENERAL MAINTENANCE OPERATION

APRIL 1958

I. RESPONSIBILITY

The responsibilities assigned the Power and General Maintenance Operation remained unchanged during April.

II. ACHIEVEMENT

A. Operating Continuity

There were no outages of steam, water, or emergency electrical services that affected continuity of operation of the prime production plants during the period covered by this report.

B. Inspection, Maintenance, and Replacement

The HS pulse column, required for the Purex facility on Project CA-513-E (Two-Cycle Process), is complete and will remain in the deep cell at 277-W until required at the plant. The fabrication of the 58 cell pipe jumpers required for the conversion is complete with the exception of three which were delayed pending delivery of jet assemblies. These, however, will be completed by May 2nd.

Fabrication of the new 200 BR machining hood for the Finished Products Operation is on schedule and concentrated efforts are being made to meet a completion date of May 16 (two weeks earlier than originally scheduled). Construction of the hood proper is complete and installation of electrical controls and circuitry is 80% complete.

Fabrication of a casting hood for Hanford Laboratories Operation for use at 231-Z in connection with preparation of U-233 fuel elements is complete.

Fabrication of a prototype silver reactor heater and absorber for Redox Operation has been started and is 10% complete.

A vendor fabricated, high vacuum, plutonium casting furnace for 234-5 was assembled and tested satisfactorily, enabling development engineers to study the need for any revisions to adapt it to process requirements.

A large piece of equipment on the vacuum cleaner principle was fabricated for Purex for use in removing Berl saddles from the floor of A cell following the recent accident to the silver reactor in this cell.

The Shops Operation supplied a 40" Bird Centrifuge to Redox and an F-10 pump to Purex. Eight pieces of process equipment -- 6 pumps and 2 agitators were run-in and placed in standby status. Modification of 2 spare centrifuges for Redox is in process, one being 25% complete and the other just started.

An F-5 evaporator tank for Redox was made ready for installation on an emergency basis.

Ten new jumpers were fabricated, three jumpers were modified, and two other jumpers which had been in Purex cells were revised due to design changes. Modification of a large "doughnut" jumper for Purex was completed.

A rupture occurred in the six inch raw water line to the 241-S Tank Farm. Immediately an existing eight inch auxiliary was placed in service providing uninterrupted water supply during repair of the broken line.

Although the No. 4 Boiler at 284-W was removed from service due to a continuous blowdown valve failure, there was no interruption of steam service caused by this failure.

The No. 1 Boiler, 284-W, and the No. 4 Boiler, 284-E, were inspected by the Traveler's Insurance Company and found to be in good working condition.

The replacement of steam turbine drives with electric drives on the Erie City Boiler cinder return fans is now complete in both 284-E and W.

The Power Engineering Operation completed corrections to the ventilation systems in the 1704-K, 165-KE and KW, and 105-H Buildings. Rebalance of 105-DR systems is in progress.

Construction has been completed on nine of the ten burial boxes for Project CA-513-E, Purex Two-Cycle Conversion Program. Three of these were unusually large units ranging from forty to fifty feet long and twelve to fifteen feet high. All boxes will be stored on flat cars pending disposition by Purex Operation.

Three major burials were consummated for Redox and two for Purex under rigidly controlled SWP conditions. All burials proceeded without incident despite gusty winds to thirty m.p.h. during the burial.

A new method of dry contaminated waste removal has been instituted at the 202-S Building. A large portable container was converted into a water-tight walk-in type container for receiving dry contamination waste, and is marked and painted appropriately as a radiation zone. Periodically the entire unit is emptied in the 200-W dry waste burial ground.

C. Improvement Experience

The spring weed control program was initiated in both 200 East and West Areas with the application of 2-4,D to approximately 245 acres.

Savings in the amount of approximately \$10,000 annually will be realized in that the roll was reduced by two (net) people during the month.

III. ORGANIZATION AND PERSONNEL

A. Safety and Security

The Operation incurred no disabling injuries during the month. The 18 medical treatment cases reported reflect a frequency rate of 4.19.

There were no incidents reported in which a breach of security was evident.

B. Personnel Activities

A.E. Leinberger, Foreman, Electrical Shop, visited the G.E. Co., Service Shops Facilities, Spokane, Washington, on April 24 to discuss servicing of electrical motors.

R.W. Gooldy, Foreman, Machine Shop, visited the Phillips Petroleum Co., Arco, Idaho, on April 30th to discuss and compare inspection methods and machining tolerances for MTR fuel elements.

Eight employee suggestions were submitted, of which seven contained ideas worthy of acceptance. Four awards totaling \$87.50 were presented to personnel of this Operation for suggestions previously submitted.

Five training sessions were held as scheduled for P&GM 1958 Craft Training Program. A total of 158 craft personnel attended these sessions.

T. S. LeFollett, Manager
Power and General Maintenance Operation

DECLASSIFIED

CHEMICAL PROCESSING DEPARTMENT
FINANCIAL OPERATION

April, 1958

I. RESPONSIBILITY

There were no significant changes in the responsibilities assigned to the Financial Operation during the month.

II. ACHIEVEMENT

A. Product Cost

Considerable difficulty was experienced with computing services' tabulations in connection with March closings. Despite these difficulties, operating statements for the month of March were issued on April 10, 1958. All major computing services' tabulations were one to two days late and approximately \$20 000 of costs were dropped from the runs in error necessitating manual distribution. As a result of this problem it was necessary for the Product Cost Operation to work 56 hours of unplanned overtime.

Unmatched detail has been reduced approximately 300% by local key punching and transmission of work order master cards to the Computing Operation via the transceiver. This reduction in unmatched detail has resulted in an appreciable savings in clerical effort.

Depreciation reporting was reviewed and revised so that April reporting will reflect depreciation by end function, organization and source of charge.

HAPC operating budgets for FY 1959 and 1960 have been reviewed by the General Manager, HAPC and submitted to the local Commission. In general all department budgets were reduced, primarily salaries, by the General Manager, HAPC. CPD's portion of this submission is currently being transmitted to the Product Cost Operation for review. As soon as the revised submission is received it will be analyzed and advice transmitted to CPD components as to the status of their budget.

The annual physical inventory of coal, taken March 31, was reconciled and the report issued during the month. The physical inventory varied from book by 2.3%; however, no book adjustment was made since the accuracy of the coal pile survey is only plus or minus 10%.

B. Personnel Accounting

Annual statements showing the investment, as of December 31, 1957, of each participant in the Stock Bonus Plan have been received. In past years these statements have been delivered promptly to the employees concerned; however, this year the statements will be held and delivered along with a statement showing interest accumulated in the pension plan and value of insurance held.

Latest information received indicates that the forms, for insurance data, ordered by the Computing Operation will be received sometime during the week ending May 4, 1958, making it possible to distribute the entire package with weekly checks on May 16, 1958. Statements of exempt employees will be delivered the same day.

A 1.77% cost-of-living increase in base pay rates and base isolation pay became effective on April 28, 1958, for most nonexempt employees. Under the provisions of the General Electric Better Living Program, base pay rates of most nonexempt employees have been increased 13.08% since decentralization on September 1, 1956. Isolation pay has increased \$1.12 per week (from \$8.96 to \$10.08) and shift differential has increased from 16¢ to 18¢ per hour during this period.

During April Personnel Accounting issued 76 checks against the Contract and U. S. Savings Bond bank accounts, as follows:

	<u>No. of Checks</u>	<u>Amount</u>
Contract Account covering payment of employee and employer FICA Taxes, Federal Withholding Tax, Union Dues, Insurance Premium, and other deductions from employees' earnings.	56	\$277 851
U. S. Savings Bond Account covering purchase of U. S. Savings Bonds and refund of unused balances.	<u>20</u>	<u>51 308</u>
Total	<u><u>76</u></u>	<u><u>\$329 159</u></u>

As of April 30, 1958, 31 CPD employees have taken advantage of the new banking service offered in March and authorized deposit of their salary checks in banks outside of Richland.

Statistics

1. <u>Number of CPD Employees</u>	<u>Monthly</u>	<u>Weekly</u>	<u>Total</u>
Employees at Beginning of Month	399	1 174	1 573
Additions and Transfers In	1	5	6
Removals and Transfers Out	(3)	(28)	(31)
Transfers from Weekly to Monthly	0	0	0
Transfers from Monthly to Weekly	(1)	1	0
Employees at the end of the Month	<u><u>396</u></u>	<u><u>1 152</u></u>	<u><u>1 548</u></u>
2. <u>Overtime Payment During Month</u>			
	<u>April</u>	<u>March</u>	
Nonexempt	\$ 9 943*	\$10 285*	
Exempt	2 815	1 614	
Total	<u><u>\$12 758</u></u>	<u><u>\$11 899</u></u>	

*Payments to nonexempt employees cover a four week period.

3. <u>Gross Payroll</u>	<u>April</u>	<u>March</u>
Nonexempt	\$589 985*	\$590 754*
Exempt	325 295	321 050
Total	<u>\$915 280</u>	<u>\$911 804</u>

*Payments to nonexempt employees cover a four week period.

C. General Accounting

A Sundry Receivables Account was established in CPD's General Ledger during the month in accordance with the procedure written and approved during March. Receivable items of this nature were formerly booked on R&UO's records.

Eighty-six checks totaling \$339 042.90 were prepared by CPD during April, 1958. General Books issued 30 of these checks totaling \$9 884.23. No checks for contaminated personal effects were issued during the month.

Additional posting reference keys have been ordered for the posting machine to enable conversion of the cash advance manual posting procedure to a machine operation. After this conversion, all General Books posting will be done on the Burroughs posting machine which eliminates considerable clerical effort.

A letter concerning the control budget classification of meetings sponsored by the American Management Association was prepared and circulated to counterparts in other HAPO components.

The March General Ledger Trial Balance and Reports of Travel and Living expense were delivered to Contract Accounting on schedule.

There were 25 active CPD projects with \$14 226 000 authorized funds as of March 31, 1958. Expenditures and commitments of \$9 954 000 and \$806 000, respectively, have been incurred against these projects. Cost of \$310 000 was incurred during March.

The preliminary cost closing for CG-643 - Redox Capacity Increase - Phase III, \$120 259, was completed during April.

During April, total funds of \$1 380 000 for Project CG-719, "Additional Facilities for Purex Tank Farm Vapor Wastes", were authorized by Directive HW-412, Modification 4.

Appropriation Requests totaling \$182 463 were approved in April. These included Dissolver Off-gas Scrubbers (\$107 000), 256 Channel Pulse Height Analyzer (\$30 120), Milling Machine (\$23 600), Lathe (2) (\$15 000), and an Electric Air Dryer (\$1 843).

Appropriation Requests in process and unapproved at April 30, 1958, totaled \$38 735.

A proposal for Project CAC-798, "Crib & Test Wells - 234-5", in the amount of \$125 000 was forwarded to the Commission for approval.

The CWIP Plant and Equipment Changes in Progress Report and the Summary Cost Report and Estimate for March were delivered to Contract Accounting as scheduled.

Plant and Equipment balances at March 31, 1958, were as follows:

<u>Plant and Equipment</u>	<u>Asset</u>	<u>Reserve</u>	<u>Net Book</u>
In Service	\$203 077 383	\$ 61 051 848	\$142 025 535
Held for Future Use	6 416 336	3 419 482	2 996 854
Not Used Nor Currently Useful	<u>105 046 142</u>	<u>105 046 142</u>	<u>-</u>
	<u>\$314 539 861</u>	<u>\$169 517 472</u>	<u>\$145 022 389</u>

Activity relative to physical inventories of plant and equipment was as follows:

P&GM, Power Operation - Report issued.
 P&GM, Layaway - Reconciliation and report in progress.
 P&GM, Administration - Reconciliation and report in progress.
 Purex, Operation - Reconciliation in progress.
 Finished Products, Operation - Physical count completed.

D. Auditing

Field work in connection with an audit of cost Accumulation was completed and a formal audit report was issued April 8, 1958.

During the month CPD auditing activity was limited since all CPD auditors are assisting the Traveling Auditors in their examination of HAPCO accounts and records.

E. Procedures

A meeting was held with Data Processing Operation and formats were drawn up to punch cost distribution corrections and work order master cards. This key punching is expected to result in a savings of a minimum of eighty hours of clerical effort in the Product Cost Operation.

All level 3 operations were contacted in order to complete a survey of estimated computer usage through 1965.

F. Measurements

A revised CPD productivity report for CY 1957 was issued. This revised report minimizes the effect of varying MWD levels of material received from IPD, for processing in the primary plant, thereby reflecting a more realistic picture of CPD's own productivity.

Productivity reports for Redox and Purex, which will reflect the contributions made by these facilities to overall CPD productivity, are being readied for issuance early in May.

Cost and production analysis reports for Redox, Purex and Finished Products, comparing actual costs and production with forecast, were prepared and issued to interested level 3 managers.

III. ORGANIZATION AND PERSONNELA. General

A financial seminar, "An Introduction to Finance", directed to the level 3 managers was started during the month.

B. Safety and Security

A safety and security meeting for all Financial Operation personnel was held on April 24, 1958.

No medical treatment or disabling injuries were experienced during the month.

No security violations occurred in April.

C. Personnel Activities

B. M. Dobbs, Manager - Product Cost, accompanied L. I. Brecke of the Finished Products Operation and two local AEC representatives on a trip to the Dow Chemical Company plant at Boulder, Colorado. The purpose of the trip was to compare the cost system of the Rocky Flats installation with the cost system of the Chemical Processing Department.

D. Reports Issued

HW-55607	CPD Operating Report - March, 1958	M.M. McDonald
HW-55642	Essential Materials Inventory and Consumption Report - March, 1958	S.R. Myers
HW-55714	Redox Cost and Production Analysis - March, 1958	G.H. Temple
HW-55715	Purex Cost and Production Analysis - March, 1958	G.H. Temple
HW-55716	Finished Products Cost and Production Analysis - March, 1958	G.H. Temple
HW-55725	CPD Unit Cost Information-March, 1958	B.M. Dobbs
HW-55864	Redox Essential Material Comparison	R.E. Middaugh
CLVI-342	CPD Cost and Production Analysis - March, 1958	K.G. Grimm
CLVI-353	CPD Productivity Report - CY 1957	K.G. Grimm
CLVI-354	CPD Productivity Report - First Quarter CY 1958	K.G. Grimm
TS-RD	Product Cost Report - March, 1958	B.M. Dobbs

Manager - Finance

DECLASSIFIED

HW-55914 DEL

May 7, 1958

CHEMICAL PROCESSING DEPARTMENT
FACILITIES ENGINEERING OPERATION

April, 1958

I. RESPONSIBILITY

There were no significant changes in responsibilities assigned to the Facilities Engineering Operation during the month.

II. ACHIEVEMENTS

PUREX OPERATION

A. Research and Development

Rare Gas Recovery

Proposals for process design and fabrication of a facility for recovering krypton and xenon from the Purex dissolver off-gas were received this month from Union Oil, Air Products, Linde, Air Reduction, and Arthur D. Little Companies.

A report has been prepared summarizing results of the preliminary discussions and an analysis of the proposals.

A draft of a specification document defining vendor responsibility has been completed, following submittal of data on April 25 by Purex Technology on the composition of T-XB treated dissolver off-gas. This document, which is intended to define vendor responsibility throughout the Phase I, II and III work, would presumably be made a part of the proposed contract.

Meetings were held with the local AEC on April 18 and 25 to inform the Commission of progress to date on krypton-xenon recovery, and to explore methods of financing the Phase I work under the contract.

B. Process Technology

Tank 241-A-103

The air lift circulators in tank 103-A were shut down on April 29, to begin further investigation of the bumping phenomena. Continuous recording equipment has been installed to determine the rate of rise, maximum pressure, and any vertical displacement of the dome.

DECLASSIFIED

DECLASSIFIED

HW-55914 DEL

If turning off the air to the circulators does not induce a bump, it will be advantageous to improve the present testing instrumentation with high-speed, manually activated, recording instruments to obtain more sensitivity and better data as is currently planned at Redox.

C. Plant Engineering

Ammonia Scrubbers

Process design work covering the installation of ammonia scrubbers in the Purex dissolver cells was completed. This work included the design of the scrubber vessel, the cold side piping and instrumentation, and needed new jumpers identified from cell layout studies. The work order cost for the Purex installation, including all necessary installed equipment together with one spare scrubber, totaled \$107,000.

Spare Silver Reactor

Final design of the new type Purex silver reactor, Model 3, was completed and the approved drawing prints were transmitted to Purex for the use in on-site procurement of a replacement spare unit.

Prototype Anion Exchange Conversion

Detailed design work has been initiated on the two most critical items in the anion exchange unit needing correction; namely, the hood ventilation system, and the enclosures around the mezzanine piping. It is planned to connect the "N" Cell Hood to the current PR Hood ventilation system in accomplishment of the first item above. The mezzanine enclosures will be vented through a filter to the West Sample Gallery exhaust duct.

Jumper Cutter

Specification HWS-6335 has been prepared covering design and construction of a remotely operated shear for cutting scrap jumpers in the canyon. The purpose of the shear is to reduce the size of scrap jumpers and conserve burial box space. The final specification was prepared after a survey of what is commercially available as standard equipment or by special design.

Block Bail Reinforcement

A revised scope study of the Purex block bail reinforcement problem has been completed and the study submitted to Purex management. The new scope is based on accomplishing the required fabrication in "M" cell to minimize the operational interference of normal canyon

DECLASSIFIED

HW-55914

DEL

functions. The revised design of the bail reinforcement permits better canyon deck clearance and bail strength.

Based on a one-shift operation, the cost estimate for making the modification is \$192,000; however, for an estimated premium of \$15,000, the work could be accomplished on a three-shift basis and the job time shortened by approximately 60 percent.

D. Project Activities*

CA-513-E - Two-Cycle Conversion

All fabrication work and cold-side gallery work required prior to the shutdown of Purex Plant was completed at the end of the month except for three jumpers and the last of ten burial boxes. This remaining work will be completed by May 5, 1958. The shutdown of Purex Canyon to start flushing is scheduled for May 22, 1958. Detailed planning is underway for delivery of equipment to the canyon prior to, and during, shutdown. At the present time there are no foreseeable factors that would require delay of the plant shutdown for the two-cycle conversion.

REDOX OPERATION

A. Research and Development

Neutron Instrumentation in 233 Building

The fabrication and installation of a neutron monitor on the L-16 tank is in progress. A probe well for the tank, a plastic lean-in panel for the hood, BF₃ tubes, and amplifiers are being fabricated on-site. Other equipment has been ordered, and promised delivery dates are good on all items except a recorder.

- - - - -

* For complete information on projects, refer to the following reports:

Semimonthly Status Report
AEC-HOO Monthly Progress Report of
Construction Jobs

DECLASSIFIED

DECLASSIFIED**B. Process Technology****Redox 241-SX-107**

Redox Technology initiated a "bump" in the 107-SX on April 28, 1958. Cold water was discharged through the air line of one of the circulators for 30 seconds to initiate the sudden release of heat. The tank farm instrumentation recorded a maximum pressure of 34 inches of water (approximately 8.4 percent of the hydrostatic head). The heat flow during the pressure surge was approximately 5,280,000 BTU for 20 minutes or a rate of 15,840,000 BTU per hour.

The fact that the pressure surge in the Redox 107-SX Tank had to be initiated manually will simplify the instrumentation and recording equipment for additional testing. If it is known within a very few minutes of when the bump will occur, a more sensitive pressure-recording instrument can be used to record more rapid rates of pressure rise. Also, a vibration pick-up instrument can be installed on the pump pit above the 107-SX to record any movement of the dome.

Failed Piping

Three lengths of Teflon compound tubing are on order with the Resistoflex Corporation; delivery is expected on May 15, 1958. These pieces will be tested on an experimental basis as lining to repair the failed pipes in the concrete walls. Tools for pulling and installing the lining are being designed and assembled, and should be ready for use within three weeks. The tests should be complete by June 15, 1958.

C. Project Activities**CG-717 - Transfer Facilities for Redox Non-Boiling Wastes**

All presently authorized construction work has been completed on Project CG-717. As indicated in Document HW-57764, it is estimated that air lift circulators for waste storage tanks 102, 103 and 105-SX will not be required prior to January 1, 1960.

CG-720 - Modifications to Redox SWP Facilities

Work has been essentially completed on Project CG-720, and the Physical Completion Notice has been issued. The final cost of the work was approximately 14 percent under the authorized funds.

DECLASSIFIED

DECLASSIFIED

HW-55914 DEL

FINISHED PRODUCTS OPERATION - Z PLANT

A. Research and Development

Shielding Barrier Task I Through Task IV

Scoping work was completed during the month on the shielding barrier to be provided from Task I through Task IV. Detailed studies were made on several alternate methods of constructing this shielding barrier in order to obtain the maximum amount of shielding at minimum cost. The results and conclusions of these studies have been documented in HW-55865 which is presently being circulated for approval. The work proposed in this document consists of three separate installations for the Task I through IV portion of the RM Line:

1. A Zone 1 - Zone 3 shielding barrier to yield a maximum Zone 1 whole body radiation exposure rate of less than 0.5 mrem per hour.
2. A hood vacuum cleaning system to enable better control and removal of plutonium powder.
3. A new powder storage hood between Task II and III to eliminate the transportation of plutonium powder through the entire length of Task III to the present storage hood.

Improvements on Task I and Task II Equipment

The fluorothene valve and teflon wear plate assembly installed on the vacuum drum filter in Hood 9B has given excellent service to-date. Permanent drawings have been made of these parts and a complete assembly will be fabricated for use on Hood 9A. The vacuum drum filter cloth made from linear polyethylene has been received and will be tested at the next filter cloth change.

The Hastelloy C poroloy filter has been installed and to-date has been cleaned on two different occasions. Since no change has been observed in the initial pressure drop across this filter, a similar unit will be installed in Hood 9A. New designs have also been developed for the agitators in the PRT and RCTR tanks used on Project CG-691. These designs were developed to provide a shaft with higher critical speed, to eliminate the bearing below the motor, and utilize a different type of shaft seal.

234-5 Building Radiation Study

The study of Z Plant radiation initiated in February with a special sampling program is continuing with three Purex batches having been

sampled to date. A fourth batch from Redox production is planned. The study is being conducted in three phases: (1) spectrographic analysis in gram quantity or less; (2) growth and shielding data on bulk sampling of kilogram quantity; and (3) radiation data taken on the process hoods.

A study is in progress to determine estimates of the amounts of radiation operators receive while working in specific locations on the RM Line. A work sampling program to determine the time breakdown of operators by activity and location is almost complete. The results are to be correlated with radiation levels along the line to determine average exposures received per unit. Time breakdowns indicate the particular operations and activities that should receive close attention in the program to reduce radiation exposure.

B. Project Activities

CG-691 - Continuous Task I and Task II

The acceptance tests previously prepared for this project have been revised and up-dated to allow for the modifications made in recent weeks to the process equipment. One process engineer will be assigned on a full-time basis to assist in the start-up and adjusting of the H-7 and H-9A equipment

CG-734 - RMC Button Line

The present evaluation of the various fire hazards in the 234-5 Building have led to the conclusion that all hydraulic systems should be operated with a fire-resistant oil. This will require that new specifications be prepared for the various hydraulic equipment to be used on project CG-734. Work has been initiated to revise the existing specifications. With the completion of the scope work on the RMA shielding project, it has been possible to proceed with the detail design of similar shielding along the RMA Line.

CG-756 - Fire Resistant Exhaust Filters - Z Plant

The carbon steel filter boxes have been completed and received from the off-site fabricator. The first stainless steel filter boxes have been received from the off-site fabricator and the balance of five units are scheduled to be completed on or before May 16, 1958.

DECLASSIFIED

FINISHED PRODUCTS OPERATION - UO₃ PLANTA. Research and DevelopmentUO₃ Powder Pickup Seal Pot

Preliminary testing of a device which would combine the functions of the pickup bins beneath the continuous UO₃ calciners and the valves used to seal the calciners from the pickup bins has been completed. This testing demonstrated the feasibility of the method, and on basis of the tests a full sized unit will be constructed. This unit will contain some plastic components so that further cold testing of the unit will be possible.

Air Activated Powder Valve

A prototype installation of an air activated powder transfer valve and control system was made on the H calciner in the 224-UA Building. The unit was put into operation April 21 and has functioned satisfactorily since that time. Observations and measurements made have shown the valve to be able to maintain a seal between the calciner and the powder pickup bin while passing a continuous stream of UO₃ powder.

B. Process TechnologyRecovery of UO₃ from Used Filter Bags

Action has been initiated to move and install a modified laundry tumbler in "E" cell of the 224-U Building. This unit is to serve as a prototype installation for the recovery of UO₃ powder from used filter bags. At present there is more than \$156,000 worth of UO₃ powder stored in used filter bags in the UO₃ Plant. It is planned to recover a large portion of this powder by tumbling the bags in a modified laundry tumbler that has been secured from the salvage yard. By a combination of agitation, impact, and air passage, it is envisioned that the powder can be dislodged from the filter bags and picked up in a vacuum system. A second objective of this method will be the cleaning of used filter bags in a way that will allow their reuse in the plant.

E-Metal Segregation in Continuous Calciners

A definitive process design and scope criteria covering the use of the UO₃ Plant continuous calciners in the E-metal segregated production program was completed. This work covers all facets of E-metal segregation with the exception of possible alternate methods of E metal powder handling.

It was recommended that the proposed changes be made on an expedited basis to permit using the continuous calciners for E-metal production at the outset of the program. A progressive approach to this segregation scheme should permit interim operation of the continuous calciners on E-metal prior to complete installation of all facilities.

C. Plant Engineering

Powder Handling System - UO₃

A scope study is underway to determine an economical powder handling system for segregated material. It is believed that a system of milling and loading the powder shipping container directly under the calciner unit which is processing segregated material can be economically justified. Scope drawings of such a system will be prepared so that cost estimates can be compared with present operating expenses of the 224-U powder handling system.

GENERAL ACTIVITIES

A. Research and Development

New Production Reactor Fuel Reprocessing

Studies have been initiated to establish the adaptability of the present E-metal dissolver concept to routine processing of irradiation reactor fuel material of higher enrichment. The possibility of introducing neutron absorbers and moderators in the slug annulus to increase the allowable enrichment is being studied.

Replacement Reactor Study

Chemical processing cost data on several alternates of replacing existing HAPO reactors with new reactors have been assembled and transmitted to Irradiation Processing Department. Briefly, replacement economics are being investigated by IPD covering new production and dual purpose reactor capacity to replace plutonium production in each case from: (1) F and H reactors; (2) B, C, and F reactors; and (3) improved and expanded B, D, DR, F and H reactors. In all instances, the replacement reactor schemes resulted in less annual chemical processing cost, at constant plutonium production, than the appropriate base case with the existing reactors due to higher conversion ratios and higher exposures anticipated for the new reactors.

DECLASSIFIED

DECLASSIFIED

HW-55914

DEL

Remote Stud Design

A final report has been received on Contract DDR-10 with the Industrial Research Division of Washington State College. This contract covers the testing of canyon studs under varying conditions of loading and lubrication. The report has been assigned number GEH-23860 and placed in files.

A significant conclusion from this report is that the standard impact wrench can stress a standard stud beyond the yield joint by prolonged impacting if the threads are lubricated. If the threads are thoroughly cleaned, the wrench can do no damage.

B. Plant Engineering

Organizational Analysis - General Maintenance Operation

An analysis of work performed by the General Maintenance Operation is being conducted as part of the review of Essential Work Program. The purpose of the study is to find improvements in organization and procedures, to clarify duties and responsibilities, and to determine what work is essential with respect to fulfilling the objectives of the component.

Burial Box Construction

The possibilities of making burial boxes from pressed or fabricated sheet steel panels are being investigated. The use of all-steel construction in burial boxes would promote safer handling of higher contaminated vessels under both normal and hazardous conditions and may offer a cost advantage.

C. Project Activities

Project Cost information as of April 20, 1958:

Total authorized funds - active projects	\$15,391.000
Total cost-to-date	9,956,000
Commitments and open work releases	938,000
Unencumbered balance	4,497,000

Costs charged to above projects 3-23-58 to 4-20-58.	253,000
--	---------

Project CG-643 was dropped from active status during this period.

Authorized funds \$211,500 - Total cost \$118,639

III. ORGANIZATION AND PERSONNEL

A. Personnel

G. R. Ruzicka, Engineer II, terminated April 11 to accept employment elsewhere.

B. Safety

No significant items to report on safety.

C. Inventions

None.

D. Reports Issued

HW-55509	Scope Design of Waste Handling Facilities, UO ₃ Plant, 224-U Building, Project CG-725, Revision 1," by J. M. Gerhart, April 4, 1958.
HW-55547	Definitive Scope of a Facility Utilizing the Continuous Calciners for UO ₃ Plant, E-Metal Product Segregation, Project CG-767," by L. D. Gustafson, April 4, 1958.
HW-55548	Installation of Ammonia Scrubbers in Purex, by R. J. Pence, April 4, 1958.
CLVI-345	Separations Costs - Dual Purpose Reactor Study, by H. P. Shaw, April 10, 1958.
HW-55842	Purex Rare Gas Recovery Equipment, Selection of Vendor, by L. R. Michels, April 29, 1958.
GEH-23860	Report on Stresses Produced in Remote Studs by Impact and Slowly Applied Tightening Torque, by the Division of Industrial Research, Washington State College, April 1958.
HW-55865	Design Scope - Reduction of Radiation Exposure RMA Line, 234-5 Building, by D. E. Braden, April 28, 1958.
HW-55804	Report on Visit to Rocky Flats, by V. W. Wood, April 23, 1958.
HW-55176, Part III	Index of CPD Crib Building Numbers - Designs of CPD Radioactive Liquid Waste Disposal Sites, V. W. Wood, April 22, 1958.

DECLASSIFIED

HW-55914 DEL

HW-55764 Project CG-717, Transfer Facilities for Redox Non-Boiling Wastes, by H. W. Stivers, April 16, 1958.

HW-55874 Modified Scope - Reinforcement of Purex Canyon Block Bails, by W. H. Koontz, April 29, 1958.

HW-55604 Preliminary Forecast of Utilization of B, T, & U Buildings, by L. W. Finch, April 7, 1958.

HW-55356 Project CG-772, Rev. 1 - E-Metal Dissolvers, Redox, by D. A. Snyder, March 19, 1958.

HW-55497 Project CAC-798, Crib and Test Wells for 234-5 Building Wastes, by D. A. Snyder, April 23, 1958.

HW-55615 Plant and Equipment Analysis Report (CG-772) E-Metal Dissolvers, Redox, by D. A. Snyder, April 29, 1958.

HW-55665 Plant and Equipment Analysis Report (CAC-798) Crib and Test Wells for 234-5 Building Wastes, by D. A. Snyder, April 23, 1958.

HW-54997 Preliminary Project Proposal, Reduction of Radiation Exposure, RMA Line, 234-5 Building, by D. A. Snyder, April 30, 1958.

E. Trips

R. M. Shervem attended the SAM-ASME Management Engineering Conference in New York City on April 24 and 25. This trip included visits to the Aircraft Gas Turbine Division at Evendale, Ohio, and to the Methods and Time Standards Services Operation at Schenectady, N.Y. on April 28. The purpose of these visits was to discuss mutual maintenance problems and evaluate the possibility of the Chemical Processing Department joining the General Electric Task Force on Maintenance programs.

E. L. Reed attended the ASME Plant Engineering and Maintenance Conference in Pittsburgh on April 14-15, and consulted with Manufacturing and Engineering Services personnel in Schenectady and New York City on April 16-19 on engineering problems, and personnel placement.

G. A. Conner visited Electric Steel Foundry, Portland, Oregon, April 7-8 for consultation on problems of fabrication of Hastelloy valves. On April 17-24 he visited the following companies: (1) Youngstown Welding and Engineering Company, Youngstown, Ohio, to consult on welding problems associated with fabrication of a titanium tube bundle; (2) Struthers-Wells Corporation, Warren, Pennsylvania, to discuss the possibility of utilizing titanium cladding for CPD process vessels; and

(3) Nooter Corporation, St. Louis, Missouri, to discuss specifications for lethal service on stainless steel concentrator for the 224-U Building.

V. W. Wood visited the AEC installation at Rocky Flats, Colorado, on April 14, 1958, to discuss radioactive waste treatment methods and facilities.

L. R. Michels of Process Design and Development and E. T. Merrill of the Hanford Labs visited the Brea Laboratories of the Union Oil Company of California on April 4, 1958, to discuss the application of Union's hypersorption process to the separation of rare gases.

F. Visitors

Mr. Arthur L. Brown, an industrial fire protection consultant from Boston, Massachusetts, visited the 234-5 and 222-S Buildings during the period of April 21-28 for the purpose of evaluating the fire risks and recommending appropriate fire protection.

Mr. R. E. Meyers of Betz Laboratories visited the 200 Areas on April 15 for the purpose of preliminary investigation on water and steam treatment problem.

Messrs. D. E. Cummings and Lee Gaumer of the Air Products Company, visited HAPO on April 1, 1958, to present the Air Products proposal on rare gas processing and to inspect the Purex 293-A Facility.

Mr. Vladimir Hwochinsky of the Linde Company visited Hanford on April 14, 1958, to review the Linde proposal with HAPO personnel on rare gas processing and to inspect the Purex 293-A Facility.

Mr. Joseph Gervais of the Linde Company visited HAPO on April 14, to supply information on the cost of liquid nitrogen.

Messrs. C. Yuenger and R. Akerlow of Stearns-Roger Company of Denver, Colorado, visited HAPO informally on March 31, 1958, to discuss Stearns-Roger qualifications in the cryogenic field.

W. B. Suddarth, Acting

Manager

Facilities Engineering Operation

DECLASSIFIED

HP Shaw:FC:mh

DECLASSIFIED

HW-55914 DEL

CHEMICAL PROCESSING DEPARTMENT
RESEARCH AND ENGINEERING OPERATION

APRIL 1958

PUREX PROCESS TECHNOLOGY

Feed Preparation

Irradiated uranium with exposure rates of 2.2 to 6.9 MW/T and cooling times of 81 to 119 days was dissolved to form solvent extraction feed. Control of radioiodine was excellent (0.6 curies per day) until the metal solution in the storage tanks was digested at 90° C to hydrolyze 2WW which had been backcycled to head end. When approximately 10.5 curies were released from the vessel vent system during a four day period, the temperature of the solution was returned to 50° C, and the vessel vent silver reactor was regenerated. Samples taken since regeneration indicate 0.2 - 0.3 curies of iodine are now released from this source daily.

A series of samples, taken to determine the composition of the off-gases in the following locations during the operation of two dissolvers: (a) entering the backup absorber, (b) entering the backup scrubber, and (c) leaving the backup scrubber, had the average analyses indicated below:

<u>Constituent</u>	<u>Entering Absorber, Volume Per Cent</u>	<u>Entering Scrubber, Volume Per Cent</u>	<u>Leaving Scrubber, Volume Per Cent</u>
NO ₂	7.0	2.9	1.6
NO	3.2	1.5	1.2
O ₂	11.5	11.1	11.1
N ₂	71.2	79.3	80.3
H ₂ O	5.6	3.7	4.3
N ₂ O	∠ 0.1	∠ 0.1	∠ 0.1
H ₂	0.6	0.6	0.6
A	0.9	0.9	0.9
Flow, SCFM	1280	1235	1200

Solvent Extraction

Typical performance of the solvent extraction cycles which operated 84 percent of the month is tabulated below:

Cycle	Log Decontamination Factor, dF		Instantaneous Loss, Per Cent Plutonium	Recycle, Per Cent	
	Uranium	Plutonium		Uranium	Plutonium
First	4.3(a)	3.8(a)	0.05	-	-
Final	2.3	3.9	0.007	5.7	0.25
Ion Exchange	-	>0.6	-	-	15.0
Overall	6.6	>8.3	0.057	5.7	15.25

(a) Based on a calculated value of 2.5×10^8 uc/gal for HAF.

On April 3 the Precycle equipment was shutdown, and, while the remainder of the plant continued on stream, the process was converted from a three-cycle to a two-cycle flowsheet on a test basis. This was accomplished by routing the HAF directly to the IBXF Tank, thus bypassing the HC and IA Columns and the HCP Concentrator. Operation of the plant during the ten day test period was so successful that, after a five day scheduled shutdown, use of the two-cycle flowsheet was continued in favor of returning to the three-cycle process. Continuous 2WW and XAW backcycle to the HAF was utilized to eliminate 2DW, 2AW and ion exchange waste losses during the test, but use of the 3WB stream of the two-cycle flowsheet (HW-52389) was inaugurated after the shutdown.

Operation of the plant during the test period was at $CF = 1.92$. At the start of the test the gamma activities of the 2AF and 2DF jumped 50- to 100-fold, respectively, above normal three-cycle operation but dropped to 20- and 40-fold, respectively. In order to improve the decontamination performance of the 2A and 2D Columns, the nitric acid concentration of the 2AF was reduced until the 2AW plutonium loss reached 0.3 to 0.5 percent, and the 2DX was reduced until the 2DW uranium loss was about six percent. The gamma ratio of the uranium product, which had risen to 7.5 because of short-life gamma emitters (later identified as I-131, Np-239 and U-237) while the plant was still on a three-cycle process, increased to 9.0 and then declined rapidly to about 2.5. After only a few days' storage, batches above a 3.5 gamma ratio decayed to well within specifications because very little Zr-Nb and Ru were present. Although the 2BP analyses leveled out at 2×10^{-11} G/AT, a gamma burst which increased the gamma activity of the 2AF by a factor of five occurred when the IBX, IBS and Final Plutonium Cycle streams were reduced from a $CF = 1.92$ to a $CF = 1.44$ rate to decrease the load on the Ion Exchange Unit. Consequently, two batches of plutonium concentrated in the L-Cell Package, because of equipment difficulties in the Ion Exchange Unit (see Plutonium Concentration), were borderline with respect to the G/AT specification.

Toward the end of the two-cycle test period the rate of the 2WW addition to the HAF was increased to empty the rework tank. The additional 2WW plus the shorter reflux time and possible foreign material from the rework tank sharply increased the gamma activity of the intercycle streams by 10- to 15-fold. However, the final products were substantially unaffected when the majority of the activity followed the plutonium and was removed by the Ion Exchange Unit. The final batch of uranium prior to shutdown had a gamma ratio of 4.1 and was

DECLASSIFIED

DECLASSIFIED

segregated to permit decay of the short-life gamma emitters which still persisted.

Startup of the plant after the scheduled shutdown was at a CF = 2.16 rate on the two-cycle flowsheet utilizing 3WB (steam-stripped and concentrated 2AW and 2DW, plus XAW) introduced directly into the HA Column fourteen inches below the feed point. However, until the 3WB reached normal inventory, previously-produced 2WW (the concentrator heel) was blended with the HAF, and another surge in the 2AF and 2DF gamma activity to levels 100- and 10-fold above normal two-cycle levels resulted. Ninety percent of the gamma activity in the final uranium product, which had a gamma ratio as high as fifteen, was Zr-Nb. At the time the Zr-Nb concentration was at its peak throughout the plant, use of the 3WB stream was initiated, and the gamma activity of all process streams began to drop sharply and then gradually leveled out at the normal two-cycle gamma activity levels. One hundred and thirty-two tons of uranium with an average gamma ratio of eight (90 percent Zr-Nb) were segregated for silica gel treatment, and one pass through the beds reduced the gamma ratio to ≤ 2 . All batches of plutonium produced by the Ion Exchange Unit were well within the G/AT specifications.

Since the HAW is the only aqueous solvent extraction system waste stream, a record low plutonium loss of 0.25 percent was established for the month despite a considerable loss experienced during transfers for 2WW backcycle (see Waste Treatment). Recovery performance of the organic continuous HA Column was excellent. A slight increase in plutonium loss occurred near the end of the month when the column became slightly unstable as a result of reducing the HAF nitric acid concentration from 0.57 M to 0.38 M. Increasing the acidity to 0.48 M re-established proper column operation.

Shortly after startup several batches of plutonium, concentrated in L-Cell Package during the period of high gamma activity in the intercycle streams, required recycling to head end. This material, added to the high plutonium recycle from the Ion Exchange Unit, increased the concentration of plutonium in the system by a factor of 1.8. However, during the period of high plutonium inventory, operation of the solvent extraction system was normal, and no unusual waste losses were experienced.

Other items of interest which occurred during the month are as follows:

- (a) Neither a thirty percent increase in the 2DIS flow nor a reduction in the 2DF temperature from 40° to 25° C had any effect on the decontamination in the Final Uranium Cycle.
- (b) A three-fold decrease in the plutonium concentration of both the IBU and the final uranium product was experienced with the advent of two-cycle operation.
- (c) No adverse effect was noted when the Final Uranium Cycle was increased to CF = 2.40 to rework waste uranium solution from the UO₃ Plant.

Plutonium Concentration

Shortly after conversion to the two-cycle test operation, a minor mechanical failure forced shutdown of the Ion Exchange Unit. Two batches of plutonium, which were subsequently concentrated in the L-Cell Package, analyzed 6.4 and 7.5×10^{-11} G/AT (normal batches = $\frac{1}{2} \times 10^{-11}$), but were successfully processed to yield buttons with radiation readings only ten percent above normal. The remaining batches produced during the test period were all processed in the Ion Exchange Unit and continued to analyze below the detectable gamma activity limit. Although the gamma activity of the feed climbed to 100-fold above normal at times, radiation readings in the ion exchange hood peaked at only three-fold above the normal 2 mr/hr and rapidly returned to normal as the feed gamma activity decreased. This test confirmed the feasibility of the original plan to operate the Ion Exchange Unit without shielding.

When mechanical difficulties forced a switch from the Ion Exchange Unit to the L-Cell Package almost immediately after plant startup, several batches of off-standard plutonium were concentrated in the package prior to the time the 2BP met gamma specifications. Recycle of this material plus additional plutonium solution that collected in the sump when a leak developed in the I4 Concentrator recirculation loop resulted in an excessive buildup of plutonium in the system (180 percent normal) and overloaded the Ion Exchange Unit. At the same time an accumulation of resin fines in the unit, after about sixty days of operation, caused intermittent plugging of the slipwater take-off screen. Although changes in operating techniques alleviated this latter problem, unstable operation of the unit and the excessive plutonium inventory both contributed to the high (up to 45 percent) plutonium recycle in the XAW. Gradual reduction of the plutonium inventory in the system is reducing the overload on the unit, and substitution of a larger mesh screen in the XAW take-off will assist in elimination of the fines from the system. Other measures are being taken to increase the simplicity and mechanical reliability of the unit.

Solvent Treatment

Both solvent systems performed excellently during the month with an overall solvent loss of 0.28 percent of the solvent throughout. Although the gamma activity of the IOO ranged from 1900 to 3000 uc/gal., the plutonium retention value consistently indicated good solvent quality. A previous reduction in the IOS acidity (to 0.05 M HNO_3) permitted 25 percent reduction in the carbonate scrub flow to the G7 Turbomixer. Unstable operation of the HA Column, which was previously attributed to entrained aqueous carbonate solution in the IOO, was eliminated by continuously decanting the IOO tank.

Waste Treatment and Acid Recovery

Operation of the Waste Treatment and Acid Recovery equipment was somewhat erratic during the month. Various mechanical difficulties and the high uranium concentration of the 2WW in the concentrator were the major sources of the operation upsets. The new IWF pump, which had been in service for only one month, was replaced "on-the-fly" when the seal failed. Because of the high 2IW uranium

DECLASSIFIED

backcycle to the 2WW, the maximum steam pressure on the IWW and 2WW Concentrator tube bundles and the F8 Rework Tank coil was reduced to 30 lb/sq.in. to eliminate the possibility of a reaction between decomposition products of TBP and UNH. However, with the advent of the 3WB stream (2AW and 2IW steam-stripped and concentrated in H4 Concentrator and combined with the XAW) the 2WW Concentrator receives only the overheads from the IWW Concentrator as feed.

Waste volumes sent to the underground storage tanks during the month averaged 150, 592, 14, and 209 gallons per ton of uranium for neutralized IWW and equipment flushes, solvent washes, centrifuge cleanouts, and cell drainage, respectively. Coating waste volume per ton of uranium was 225 gallons. Overall waste losses for the month were 0.25 percent for plutonium and 0.15 percent for uranium. These losses are considerably higher than those expected from the two-cycle flowsheet after it has been shaken down. One major loss experienced this month, but which should not reoccur, was caused by partial plugging of the 2WW Concentrator overflow line which resulted in 2WW blending with the IWF. Coating waste losses were unexplainably lower for both plutonium and uranium and accounted for only five percent of the overall losses in each case.

Continuous backcycle of 2WW, utilizing refluxing in the Rework Tank except for periods of transfer into the HAF, was successful until just prior to plant shutdown when extra heavy 2WW additions, plus the lack of sufficient refluxing, produced sharp increases in the intercycle stream gamma activities. When plant operations were resumed after the shutdown, interim use of the 2WW backcycle prior to inauguration of 3WB backcycle, again caused skyrocketing gamma activities in the intercycle streams. A change to use of the 3WB, which is steam-stripped prior to concentration, rapidly returned the process to normal conditions.

The gamma activity of the recovered acid dropped from last month's peak of 10,000 - 24,000 uc/gal. to 250 - 1500 uc/gal. after conversion to the two-cycle process (lower concentrator tower throughputs) and flushing the IWW and 2WW Concentrator towers with five percent caustic solution.

Self-concentration continues in Tanks 101, 102, and 103 at boiloff rates of 10.5, 5.4, and 3.8 gal/min., respectively. Installation of a dome deflection measuring device on TK-241-A-103 has been completed and a test is currently in progress to measure the rate of pressure buildup within the tank whenever a "bump" occurs.

DECLASSIFIED

REDOX TECHNOLOGY OPERATION**DECLASSIFIED**Acid Recovery and Iodine Control

The efficiency of the acid absorber averaged approximately 80 percent at acid concentrations of 51 percent. The results of the study to determine the quantity of acid lost via condensation in the dissolver off-gas lines (to the stack drain tank) are only qualitative to date. The collection of acidic condensate downstream of the acid recovery unit, combined with increased collection rates in the stack drain tank during periods of dissolver operation, indicate that some acid is being lost by this method. The installation of temporary instrumentation has been recommended by Redox Technology to obtain the required additional data for confirmation of this point.

Because the continuous oxygen analyzer in the acid recovery system is still being readied for service, manual air bleed-in to the absorber feed gases was started during the month. Insufficient operating time with the additional oxygen has been accumulated to permit evaluation of the change. Replacement of the controller for the acid absorber scrub water supply near month-end has resulted in elimination of the cyclic variations in controller operation and should result in improved acid recovery.

The emission of iodine-131 to the stack averaged 0.42 curie per day during dissolver operation compared to 0.17 curie per day during periods with no dissolvers in operation. Improved sampling techniques indicated during the month that negligible quantities (less than 0.03 curie per day) of radioiodine were emitted from the canyon and vessel ventilation system and from the acid recovery unit. However, the sample data indicated also that significant quantities (perhaps as much as 0.3 - 0.4 curie per day) were emitted via leakage through the dissolver off-gas diversion valves. A proposed method of correcting the situation was submitted by Redox Technology to Redox Operation and is currently being studied. An earlier proposal by Redox Technology for the conversion of the caustic scrubber to a back-up nitric acid absorber is being acted on by Operations personnel at month-end.

Feed Preparation

The last two batches of the current series of seven small charges of slightly enriched uranium were dissolved, analyzed, blended with normal production, and processed normally. The last charge consisted of 175 pounds of uranium containing 1.44 percent uranium-235 before irradiation. This charge was the first processed in the Redox plant to contain greater than 0.94 percent uranium-235.

Reduction of the amount of fresh sodium dichromate added to the feed treatment step was permitted by utilizing the dichromate present in the routinely-reworked concentrated salt waste. Sodium dichromate chemical savings of greater than \$3.60 per ton of uranium are being realized by the reduced consumption.

DECLASSIFIEDExtraction

Operation of the HA Column was continued with acidified HAS (0.1 M HNO_3). This, combined with the observance of the established minimum HAX flow of 450 flow ratios at processing rates 60 percent of phase II or less and a maximum plutonium concentration of 0.3 gram per gallon of HAP, resulted in negligible deposition of plutonium in the HA Column. This was shown by material balance data and by low plutonium pick-up (less than 2 grams per flush) during two dilute nitric acid flushes.

During the past two months, operation of the HA and LA Columns for about 8 and 10 days, respectively, at 96 percent of phase II instantaneous rates (following dilute nitric acid flushes) has resulted in flooding of the two columns. This frequent flooding at lower-than-normal volume velocities is due to the presence of solids which are present in larger-than-normal quantities, probably due to inadequate clarification of the feed solution by centrifuging during the latter part of calendar 1957. In order to better remove these solids, a 3 percent HF-20 percent HNO_3 flush was given the HA, HS, and LA Columns at month-end.

Back cycling of about 15 percent of the LAW to the LAFS stream was continued successfully during the month, with no apparent adverse effect on decontamination. (See below.)

Decontamination

All plutonium product was well within fission product activity specifications, with the exception of one batch collected immediately after start-up which was successfully reworked. A test to determine the effect on plutonium decontamination of lowering the 2A Column interface from the disengaging section to approximately the 2AF introduction point was evaluated by means of the 2BP in-line gamma monitor. No significant loss of decontamination resulted from the lowered interface or from the rising interface after the test, indicating no deleterious decontamination effects in the organic-continuous scrub section and indicating a negligible quantity of "scrubbable" solids in the 2A Column.

All final uranium product during the month met gamma activity specifications. During the early part of the operating period, tail-end ozonation (decontamination factor about 1.6) and silica gel treatment (decontamination factor about 2.8) were required to bring the uranium product within specifications. During the latter part of the operating period, over-all decontamination of the uranium product improved markedly, with the gamma activity falling from 1.6 to 0.8 times specification activity without tail-end treatment. The improved decontamination is the result of improved and steady column operation, supplemented by a probable beneficial effect of lowering the 2D Column interface from the upper scrub-packed section ($L/V = 0.05$) to the lower scrub-packed section ($L/V = 0.12$). The total effect of the lowered interface on fission product decontamination is unknown, but is to be evaluated in the near future. The lowered interface resulted in a 50 percent increase in sodium contamination in the uranium product, but the total sodium content remained within specifications.

A test of the effect on product decontamination of increasing the HAS flow ratio from the normal 25 to 40 was performed during the month. Although the data are clouded by numerous interferences, it appears that the change improved HA Column decontamination by as much as a factor of two.

Product Recovery

Over-all uranium and plutonium recoveries during the report period were 99.69 and 99.67 percent, respectively. During normal, steady-state operation, extraction recovery averaged 99.93 and 99.80 percent for uranium and plutonium, respectively.

Lowering the IO Column interface for column aspiration control resulted in erratic instantaneous uranium losses (via the IOO stream to the concentrated salt waste) of up to 0.8 percent compared to normal losses of less than 0.1 percent. (The IOF stream contains about 1.5 percent of the plant uranium through-put which is normally removed by the IO Column raffinate and back-cycled to the HAIS Concentrator for control of solids formation in the HAIS stream.)

Waste Storage

The 107-SX Tank was held without agitation for one month. During this period the tank contents boiled without bumping from a concentration factor of 2.22 to 2.42, while the sludge temperature increased gradually from 294 to 302°F. A pressure surge was then induced by injecting water into the bottom of the tank. The maximum pressure due to the induced bump was 1.16 psig; this pressure was 8.9 percent of the hydrostatic head in the tank. A total of 5.3 million BTU of heat was released in the form of steam during the 20-minute duration of the pressure surge. Tests such as this one will be continued with additional instrumentation to show the rate of pressure rise.

DECLASSIFIED

FINISHED PRODUCTS TECHNOLOGY OPERATION**DECLASSIFIED**URANIUM CONVERSION OPERATIONProcess Performance

All UO_3 shipped met product specifications.

Nine hundred eighty eight (988) pounds of nitric acid per ton of uranium processed (93.7% of theoretical) were recovered at an average concentration of 50%.

The average operating rate of the calciners was 6.9 tons uranium per calciner for each day on the line. This is the fourth consecutive month that rates have been 6.8 tons per day or greater.

Process Improvement

The TA-3 nitric acid absorber was converted to automatic control by allowing the product acid specific gravity to control the reflux water addition rate. While routine operation is satisfactory, start-up control requires improvement. It is planned to move the control point to a higher plate.

The absorber chloride purge was converted to automatic operation whereby purging of the optimum bubble-cap plate is accomplished for 15 minutes every 6 hours.

Installation of automated start-up and shut-down was completed on the ED-2 100% UNH concentrator. Initial operation has been satisfactory.

Stronger thermowells for powder bed temperature sensing instrumentation have been installed in all calciner units. Bending of two thermowells and failure of one other, all of which were of the old design, was experienced during the month. No agitator damage resulted from any of the failures. Feed point temperature measurement on K-calciner was converted to thermocouples instead of the gas bulb sensing elements. On this calciner the thermowells have been shortened by three inches to decrease the bending moment.

An air-activated powder discharge valve and a small collection bin were installed on H-calciner in place of the larger collection bin and rotary discharge valve. Operation has been essentially trouble-free.

Work was completed in preparing the powder handling system for a test to determine the operating efficiency of a primary bag filter housing. The empty unit will be used as a stilling chamber for settling unmilled UO_3 from the calciner discharge. Preliminary tests indicate a high degree of attrition in the present cyclone and/or conveying system.

METAL FINISHING OPERATIONRecuplex

Ninety-five runs, consisting of crucibles, fragments, powders, metal scraps, and cleanouts, were processed through the SC Hood. Slurry losses reached a new low and averaged 0.12% of the recovered Pu.

Thirteen kilograms of plutonium were recovered by dissolution of powders in beakers which reduced the processing load in the SC Hood.

Two runs of crucibles made from low silica MgO (less than 0.5% silica) were processed. Total solids present after filtration was about one-half of that contained in standard runs.

The SE columns processed 1580 liters per day at 90% operating efficiency for an average instantaneous rate of 1760 liters per day. Waste losses to crib averaged 0.0065 g/L, or 0.43% of the Pu processed.

A washing procedure was tested for removal of recoverable amounts of plutonium from the extraction column waste (CAW). The waste was washed with a single batch contact of degraded solvent containing DBP. A 10:1 volume ratio of CAW and solvent, respectively, was used. About 75% of the plutonium was recovered, which allowed the waste to be cribbed without rework through the columns. The degraded solvent was then given a 60-liter standard ferrous ammonium sulphate-sulfamic acid wash. The volume of material to be reworked, 60-liters vs 1500-liters for a normal CAW volume, greatly reduced the reprocessing time.

Task I - II

Two hundred sixty-nine runs were processed with an average supernate recycle of 1.6% of the feed.

The fragile porous carbon filter element in the fluorinator off-gas system was replaced with a Poroloy unit made of 0.005-inch Hastaloy "C" wire woven and compressed on a mandrel to form a cylinder with a 0.040 inch wall thickness. Pore size is nominally 50 microns. Operation of the Poroloy unit was satisfactory. Three brushings to remove powders were required during a period of 230 operating hours before the unit was removed for chemical cleaning. The unit was reinstalled at month end.

DECLASSIFIED

PROCESS CHEMISTRY OPERATIONPROCESS ASSISTANCE**DECLASSIFIED**Purex Process Studies

It has been suspected that recent Purex iodine emissions were a consequence of a change in the solvent washing process. In order to check this possibility, laboratory measurements were made of the iodine picked up by an air stream bubbling through samples of the solvent as they were put through the two washing procedures. In the former procedure (washes with 0.01 M KMnO_4 - 3% Na_2CO_3 , 3% Na_2CO_3 , and 3% Na_2CO_3 in the order named), 0.02% of the iodine in the sample was released to the air stream. In the replacement procedure (0.01 M KMnO_4 - 3% Na_2CO_3 , 5% HNO_3 , 3% Na_2CO_3), 0.04% of the iodine went into the air. Although the difference is believed significant, the increase in iodine released with the second procedure is not great enough to explain the plant emissions.

Laboratory tests were also made of the effect of replacing the final (sodium carbonate) solvent wash with a sodium hydroxide wash. The change had no effect upon the iodine decontamination of the solvent, and improved the Zr-Nb and Ru clean-up only slightly. The addition of 0.01 to 0.05 M $\text{Na}_2\text{S}_2\text{O}_3$ to the final solvent wash, either carbonate or caustic, had no effect upon the fission product decontamination of the solvent.

Redox Process Studies

Recent studies of the behavior of boric acid in the Redox process have shown that it strongly favors the aqueous phase in both the acid-deficient precycle and the acid, second Pu cycle. In consequence, adequate decontamination from any boric acid added to the dissolvers as a neutron poison should be easily achieved. Any boron which follows the uranium through the process to the product UNH, however, will in the main be found in the UO_2 after calcination. In a laboratory test, it was found that calcination of UNH removed only about 35 per cent of the boric acid initially present.

A short service job was done for Redox in examining the crystals found in a barrel of "Nonisol-300" (a polyoxyalkylene fatty acid ester used as an anti-foam agent). The crystals were found to have properties corresponding to those of glutaric acid.

Silver Reactor Studies

An experimental silver reactor (glass pipe: diameter, 2 inches; length, 8 feet) has been assembled and preliminary shake-down runs made. The unit will be used for studies of the causes of reactor plugging and decrease in efficiency and of methods of cleaning and recharging.

Purex Waste Concentration Studies

For several months laboratory studies have been made of the relationships between Purex waste composition and the properties of the waste as it is concentrated by evaporation. Curves relating boiling point to sodium ion concentration have been prepared for simulated waste solutions containing as additives, ferric ion (to 0.45 M), sulfate ion (to 1 M), and nitrite ion (to 2 M). Neither the iron nor the sulfate had much effect upon the sodium molarity-boiling point relationship. The nitrite, however, markedly lowered the sodium concentration at which the slope of the curve changed to give a much greater rate of increase of boiling point with increase in sodium concentration. For example, with 2 M nitrite, the break came at about 11 M sodium ion.

ANALYTICAL ASSISTANCE

High Gamma Activities in Purex Final Product Uranium Streams

The principal source of the high gamma activity observed in the Purex final uranium cycle during the early part of April has been identified as neptunium-239. This conclusion is based on the following experimental evidence:

1. Approximately 70-80% of the gamma activity associated with the 2DF(K-1) and 2EU (K-4) could be separated from the uranium using the conventional neptunium TTA separation procedure.
2. Gamma spectrometer scans of the isolated activity were nearly identical to scans of pure neptunium-239, having photopeaks corresponding to gamma energies of 0.12, 0.23, and 0.28 M.E.V.
3. Radioactive decay studies of the isolated activity, carried out over a 13-day period, showed that over 95% of this activity decayed with a half-life of 2.3 days.

Comparison of the neptunium-239 activities found in the 2DF and the 2EU indicate that only 10% of the neptunium-239 followed the uranium through the final solvent extraction cycle.

About 10-20% of the γ activity associated with the 2EU decayed with a 6.5 day half-life and was identified as uranium-237.

Analysis of Special "E" Metal Dissolver Solutions

As a service to the Reactor Study Group of IPD, a program was initiated to analyze selected groups of "E" metal fuel elements. The primary purpose of the program is to provide the Reactor Studies Group with accurate analytical values (Pu, U, U-235, and plutonium isotopic composition) for the establishment and the prediction of pile conversion ratios. Work has been completed on the first four batches (out of a total of six) of "E" metal material and the results are summarized below.

DECLASSIFIED

DECLASSIFIED

Research and Engineering

HW-55914

DEL

SPECIAL "E" METAL PROGRAM ANALYTICAL RESULTS

Analytical Measurement

	<u>Tube Number</u>			
	<u>2163-B</u>	<u>2062-B</u>	<u>2162-B</u>	<u>2063-B</u>
<u>Grams Pu</u> (2)				(1)
<u>Ton U</u>	518.1	522.2	527.5	

U^{235} (wt.%)	0.8585	0.8652	0.8640	---
------------------	--------	--------	--------	-----

Plutonium Isotopic Composition

Mass Number (Wt.%)

238	0.013	0.011	0.010	---
239	94.37	94.37	94.32	
240	5.24	5.25	5.27	
241	0.37	0.35	0.38	
242	0.01	0.02	0.02	

Plutonium Specific

<u>Activity, d/m/g</u>	1.598×10^{11}	1.594×10^{11}	1.591×10^{11}
------------------------	------------------------	------------------------	------------------------

- (1) Batch #4, tube No. 2063-B, was contaminated with the heel of a previous dissolution and analytical values were not reported.
- (2) Precision of G/T values is $\sim 1.8\%$ at 95% C.L., based on 16 independent uranium and plutonium assay values.

QUALITY CONTROL AND STANDARDS

During the month the quality control program for the Chemical Processing Department analytical laboratories was maintained as usual. The Analytical Control Quality Report-January-March, 1958, HW-55672, was issued. Analytical bias corrections for accountability source data for eleven accountability control points were issued for the period July, 1957 through April, 1958. In the future, these corrections will be issued to the SS Accountability Operation on a monthly basis.

The Standards Laboratory continued the production of calibrated glassware and standard solutions. Two electroplated discs, free of Am-Cm, containing 100,000 d/m and 200,000 d/m were prepared for the Radiological Physics Operation. Five plutonium nitrate neutron standards were prepared for the Process Control Development Operation. Two plutonium samples were requested by the Chemical Instrumentation Operation for isotopic analysis. The laboratory completed the installation of a glove box and a Metler five-place balance for working plutonium standards. The calibration and checking of geometry discs for the alpha counters was in good control at month end.

234-5 DEVELOPMENT OPERATIONPlutonium Trichloride Preparation

A metal reduction process based on the chemistry of plutonium trichloride instead of plutonium tetrafluoride offers the process advantage of a greatly decreased neutron field. Work continued on the preparation, reduction, and recovery steps.

The chlorination rate of plutonium dioxide by carbon tetrachloride has been determined, semi-quantitatively, at different temperatures. At a bed depth of 0.7 cm plutonium dioxide is chlorinated in 3 hours at 400 C, 2.5 hours at 450 C, and 1.5 hours at 500 C.

Plutonium trichloride prepared at 450 C or less is not as dense as that prepared at higher temperatures. The bulk density of the latter is 2.33 or about twice that of the trichloride prepared at lower temperature, 1.16.

Four and one-half kilograms of plutonium trichloride have been prepared from plutonium dioxide and carbon tetrachloride. There has been no difficulty in preparing the 300 - 400 gram batches. Analysis of the material indicates a good conversion to the trichloride, with a Cl/Pu ratio of 2.9.

Plutonium Trichloride Reduction

Fifteen small scale reductions have been made to date. Variables tested have been the amount of water present in the chloride, the amount of iodine booster and the calcium excess.

Thirty gram scale reductions with no iodine booster have produced yields up to 96 percent. An increase in yield is normally obtained with an increase in the size of the reduction. Work has started on one kilogram scale reductions.

No serious crucible sticking problem has been observed in the small scale work although it was necessary to increase the thickness of the sand packing.

Plutonium trichloride kept over Drierite in desiccators for 21 days has shown no tendency to heat up during the mixing operation when the mixing was accomplished in a normal hood atmosphere.

As stated in the previous monthly report, HW-55571 J, a small scale reduction was made in a Glascast crucible. Analyses of the metal produced indicated a large pick-up of silicon (10,000 ppm or greater) and boron (1000 ppm) from the Glascast crucible, also some increase in the aluminum.

DECLASSIFIED

DECLASSIFIED

Research and Engineering

HW-55914

DEL

Chloride Removal from Synthetic Slag and Crucible Material

Dissolution, iodine removal, and chloride removal were effected with 13.4 M HNO_3 (60%). Dissolution and iodine removal were accomplished in the manner now employed at the Recuplex facility except that an air sparge was used instead of carbon dioxide. The chloride removal step was found to be more easily controlled than the preceding dissolution and iodine removal steps. Chloride removal during iodine evolution was minor.

Following iodine removal, boil-off with two mols of nitric acid per mol of chloride brought the chloride concentration down to 200 ppm. With a mol ratio of 2.65/1 the remaining chloride was less than 4 ppm. Chloride removal was effected at constant volume with a solution boiling in the range of 126 - 130 C, with air sparge.

The total acid required for dissolving and to bring the acidity to a suitable concentration for iodine evolution (5 M HNO_3) is about 38 mols per kg of slag and crucible material. The removal of chloride to 100 ppm would require an additional 17 mols of nitric acid.

Anticipated incidental benefits of silica coagulation and plutonium dissolution in the chloride removal step have not been ascertained. The next work will be with "hot" material.

Purex Ion Exchange Solids

Solid material found in the Purex ion exchange concentrator was found to be mainly plutonium (IV) polymer. A small amount of nearly white, easily suspended, solid material remained after removal of the green polymer. This material has not been identified but is suspected to be resin fines.

Cell Materials for an Electrolytic Reduction Process

The continuous Task III process will be based on the electrolysis of molten plutonium trichloride in a NaCl-KCl-BaCl_2 melt. One problem is to find a container material which will hold the melt at 800 C in a hydrogen - hydrogen chloride atmosphere. In cold tests the melt penetrated completely through porous zirconia and magnesium oxide. Silicon nitride absorbed the melt. This crucible material may be satisfactory when it is completely saturated with the melt.

Silicon carbide, and silicon carbide bonded with silicon nitride absorbed some of the melt with silicon carbide absorbing the smallest amount.

Zircon, stabilized zirconia and high density alumina held the melt. On cooling, the melt separated from the sides of the crucibles and was removed in one piece.

A magnesium oxide crucible flame-sprayed with nickel held the melt. The magnesium oxide appeared to have absorbed some of the melt.

Thoria was tried but the crucible broke and no observations were made.

None of the crucibles, other than the thoria, appeared to be harmed physically. The next step will be to test the crucible in a hydrogen - hydrogen chloride atmosphere.

Ceramic Development

The ceramic development effort supports the electrolytic plutonium reduction experiments by providing special ceramic cells. Slip-cast magnesia reduction cells (LS-9) with integral drain tubes were successfully made during this month. The casting of the integral cell was achieved by the use of a removable bottom plug in the plaster mold. The plug (made of plaster) forms the inside of the combined riser and drain tube. Shortly after casting, the plug is removed from inside the riser and drain tube, allowing natural shrinkage to occur. This method is based on a suggestion made by R. J. Anicetti. A small diamond wheel is on order for use in trimming the cell riser.

DECLASSIFIED

ORGANIZATION AND PERSONNEL

DECLASSIFIEDPersonnel

M. J. Rasmussen is on loan from Process Chemistry Operation to 234-5 Development Operation for a 3 to 6 month period beginning 4/21/58.

Trips

V. R. Cooper, Manager Research and Engineering Operation was Chairman of a Session at the American Chemical Society Meeting in San Francisco April 14 through 18. A. Brunstad, 234-5 Development Operation presented a paper. R. J. Kofoed, Process Chemistry Operation also attended.

R. J. Kofoed and A. Brunstad visited Stanford Research Institute on April 16 to discuss radiation stability of esters of phosphoric acid and solvents stability with Dr. EM Kinderman. They also visited the University of Calif. Radiation Laboratories at Berkeley on April 18 to inspect heavy element radiochemistry facilities and discuss glove-box design with Dr. SG Thomson. These were field trips as part of the ACS meeting.

H. H. Hopkins, Jr. and H. W. Crocker, 234-5 Development Operation visited R. D. Baker of the Los Alamos Scientific Laboratory on April 7 and 8 to discuss trichloride processes. Mr. Hopkins and Mr. Crocker also visited J. W. Pringle of the Dow Chemical Company, Rocky Flats Plant on April 9 to discuss recovery and casting methods.

R. E. Tomlinson and B. F. Judson, Advance Process Development Operation visited L. G. Cook of the General Electric Research Laboratory, Schenectady on March 30; E. Miller of the Atomic Energy Commission, Division of Production on April 1; M. Michaelis of the A. D. Little Co., Boston, Mass. on April 2; T. A. DeBacker of the Martin Company, Baltimore, Maryland on April 3 for consultation on fission product market survey.

M. N. Raile, Finished Products Technology Operation visited W. Wright, L. M. Meyers and J. Fasulo of the Dow Chemical Company, Rocky Flats Plant on April 9, 10 and 11 to serve on inspection team for Hanford Products and exchange of information.

R. E. Smith and A. E. Smith, Finished Products Technology Operation visited M. D. Martin of the University of Calif. Radiation Laboratory at Livermore, California on April 14 through April 18 to attend gaging meeting sponsored by UCRL and to discuss weapons futures.

Visitors

W. J. Maraman of the Los Alamos Scientific Laboratory visited R. E. Smith, A. E. Smith and M. N. Raile on April 14 to discuss plutonium processing and fabrication.

DECLASSIFIEDVisitors (Continued)

R. C. Scheid and J. R. Craig with the Central Intelligence Agency of the Defense Department and J. A. Anderson with the Atomic Energy Commission, Division of Intelligence, Washington, D.C. visited E. R. Irish on April 14 to discuss Purex process and tour plant and shops. Mr. Craig and Mr. Scheid also visited M. J. Szulinski on April 15. Mr. Scheid, Mr. Anderson and Mr. Lloyd K. Belt visited with E. R. Irish and M. K. Harmon on April 16 to discuss separation process and plant design from an intelligence standpoint.

Lee Chajson of the Westinghouse Atomic Power Department visited E. R. Irish and H. M. Jones on April 2 to discuss Purex technology and accountability experience and methods.

J. M. Termini with The Permutit Company, New York City visited W. H. Swift on April 22 to discuss ion exchange resins.

F. W. Tober of Savannah River Plant, Augusta, Georgia visited H. H. Hopkins on April 24 and 25 to discuss plutonium purification and reduction processes. Mr. Tober also visited E. R. Irish, W. H. Swift and H. H. Hopkins on April 25 and 26 to discuss ion exchange resins.

J. T. Tinker of E. I. duPont de Nemours, Wilmington, Delaware visited E. R. Irish, W. C. Schmidt and B. F. Judson on April 28 to discuss filtration.

F. D. Sheldon of General Engineering Laboratory, Schenectady visited E. R. Irish on April 30 to discuss Purex process and equipment, and tour plant.

J. O. Larry of Los Alamos Scientific Laboratory visited H. H. Hopkins on April 23 to discuss plutonium purification and reduction processes.

W. Leaders and W. Tomkins of Mallinckrodt Chemical Works, St. Louis visited M. J. Szulinski on April 17 to discuss Commercial Uranium Processing.

L. A. Matheson and I. B. Venable of Dow Chemical Company, Rocky Flats Plant visited R. E. Smith and M. N. Raile on April 17 to discuss plutonium processing and fabrication.

W. McNeese and A. Morgan of Los Alamos Scientific Laboratory visited R. E. Smith, A. E. Smith and M. N. Raile on April 17 to discuss plutonium processing and fabrication.

Members of the American Petroleum Institute Committee on Deep Disposal of Wastes and other responsible AEC contractor personnel from other sites visited E. R. Irish, G. L. O'Neill and H. M. Jones on April 2 to tour Purex plant and discuss waste disposal methods and experience.

Inventions

None

DECLASSIFIED

V. R. Cooper, Manager
Research and Engineering Operation

DECLASSIFIED

HW 55914

EMPLOYEE RELATIONS OPERATION
MONTHLY REPORT -- APRIL 1958

I. RESPONSIBILITY

There were no changes in responsibility during the month of April.

II. ACHIEVEMENT

FIRE PROTECTION OPERATION

A. Fire Responses

There was one fire response during the month. In 222-S building, 200 W Area, transformer burned out in hand counting machine which caused smoke to be ejected from machine but there was no fire.

B. Fire Extinguisher Service, 200 E, 200 W, Batch Plant, BY Telephone Exchange, and Yakima Barricade.

During the month 385 fire extinguishers were inspected, 5 installed and relocated, 2 delivered to new location, 15 seals broken and not reported, 65 services, and 355 weighed. There were 36 gas masks inspected, and 28 serviced. This included installing three canisters to each case, placing face piece in plastic bags, and sealing case. Fifteen hand lines were inspected.

C. Training of Personnel in other Operations.

Three men were given instructions on driving evacuation buses.

D. Services Performed for Other Operations

Burned down temporary building in "S" Area 200 W. This building was to be removed and by burning it \$1,700 was saved, as it would cost this amount to have it removed.

E. Training for Fire Protection Personnel

Three officers attended supervisory training school during the month. Five officers attended the A.E.C. course entitled "Fire Hazards in Atomic Industry" which was held in the 300 Area.

UNION RELATIONS OPERATION

The preponderance of grievances continues to be on jurisdictional matters. Five out of six CPD grievances discussed at Step II during the month involved jurisdictional issues.

The HAMTC advised that they wish to arbitrate three recent CPD grievances. The cases are: C. H. Row - The Union is endeavoring to force the Company to utilize Chemical Workers in the handling of PR and RC cans in addition to a Teamster Truck Driver. The Company contends that only one employee is needed to perform this job. The second case is the E. E. Lange grievance in which the Union protests the Company having taken monitoring supervisors off shift. They claim this has resulted in a change in working conditions which the Company failed to negotiate with the Union. The Company claims the right to make adjustments in the supervisory force without negotiations. The third case is the C. L. Williams grievance. The Union takes exception to an off-site contract that the Company awarded to a Portland, Oregon firm to cover the fabrication of six stainless steel filter boxes. The job is estimated at \$15,000. The Union contends that when the Company finds it appropriate to lay off craftsmen, that this should preclude contracting work to outside business concerns. The Company's position, of course, is that all work other than production and maintenance which can be made available to outside vendors on a low-bid basis should be handled in this manner.

	<u>April</u>	<u>March</u>
Bargaining Unit Employees in CPD	832	854
Bargaining Unit Employees Utilizing Check-off	577	588
Percentage of Total Bargaining Unit Employees Utilizing Check-off	69.4	68.8

Following is the grievance statistics summary for the month of April, 1958:

	<u>Unit</u>	<u>Nonunit</u>
Grievances received year to date:	66	1
Grievances pending at Step II on 3-31-58	12	0
Grievances received during the month	11	0
Satisfactorily answered at Step I	2	0
Settled at Step I through expiration of 90-day time limit	1	0
Processed at Step II	6	0
Pending at Step II on 4-30-58	14	0
Pending at arbitration		
Active	8	0
Inactive	4	0

DECLASSIFIED

DECLASSIFIED

HW-55914 **DEL**

HEALTH AND SAFETY OPERATION

<u>Chemical Processing Department</u>	<u>April</u>	<u>March</u>	<u>Year to Date</u>
Disabling Injuries	0	0	0
Serious Accidents	0	1	1
Medical Treatment Injuries	54	46	204
Overexposure Incidents	1	1	2
Potential Overexposure Incidents	0	1	1
Radiation Occurrences	23	21	91
Fires	1	2	4
Security Violations	0	4	4

The Overexposure Incident consisted of a localized skin overexposure to a process operator from coverall contamination received during a valve replacement in the Purex Sample Gallery.

The fire incident occurred when a four-fold counter transformer shorted. There was no actual fire; damage was insignificant.

Programs

Preparation of CPD Radiation Control Standards, and revision of the Radiation Monitoring Procedures Manual in conjunction with the three Radiation Monitoring components, is in progress.

Arrangements were completed for an outdoor program scheduled for May 9, in recognition of Power and General Maintenance Operation achieving one Million Man Hours without a disabling injury.

Copies of "Road Toll" were secured from Richland Police Department and distributed to all CPD exempt personnel.

Tape recordings of safety talks by Mr. R. J. Cordiner and Mr. B. F. Fairless and two movies, "Safe As You Make It" and "Safety In The Office" were presented in three safety meetings.

C. R. Powell, Public Relations Director of Lehigh Safety Shoe Company, presented two safety meetings in the 200 Areas on April 4, 1958. The meetings were attended by 250 people.

The Department approved the HAPD Mosquito Control Program. CPD will underwrite a portion of the aerial spraying operation, and in addition, take necessary local action through the Landlord.

A Project Proposal to install automatic sprinkler protection in 222-S Building for protection of the metal deck roof was approved by CPD.

A safety flyer was issued in support of Clean-Up Week, April 7 - 12.

Preparation of a CPD Safety Meeting Package is in progress.

Six safety messages were posted on the marquee boards.

The summer program of the Tri-City Construction Safety Council, to provide safety and first aid training for all Tri-City Construction foremen is continuing. The Department is represented by the Specialist, Safety and Fire Prevention.

Training and Education

Four talks on CPD Radiation Protection goals and achievements were presented as part of the Management Skills program.

The Manager, Health and Safety, the Specialists, Safety and Fire Prevention, and the Specialist, Accident Prevention, attended the supervisors communications work shop conducted by Employee Relations Communications Operation.

The Specialists, Radiation Investigation and Audit, and Safety and Fire Prevention attended a 3-day course on "Fire Hazards in Atomic Industry" presented by AEC Safety and Fire Protection.

Advice and Counsel

- Redox - Preparation of Emergency Evacuation and Fire Procedure, and procedures for use of oxalic acid and sulfuric acid for cleaning purposes for the Waste Handling and Decontamination Operation; 276 Building - conducted quarterly tests on fog system, 804 enclosure fog system and the Silo Sample Gallery heat detector devices; 202-S - new supply room, recommendations for storage of flammable liquids and First Aid Fire Appliance; provision of aluminum grooved and mineral filled non-slip treads for 202-S concrete stair steps; south pipe gallery - improved safety control of yellow line limits for the non-use of eye protection and head covering; 222-S - disposal of defective cylinder of chlorine and nitrogen dioxide gas; safety meeting material and assistance.

- Purex - 202-A - identification of Piping Systems; coating interior of sodium nitrate make-up tank; suggestion No. OP 1538 "Widening of maintenance aisle by moving wall", not accepted; checking safety showers for loss of operation; procedure for conduction drop test on elevators for checking the wedge clamp safety device; approved sketch for provision of a suspended catwalk at the crane maintenance platform; improved method of handling chemical drums in the Aqueous make up; noise level control; safety meeting material and planning.

- Finished Products - Uranium Reduction Operation use of forklift trucks and necessity for overhead protection for fork lift truck driver; Metal Finishing - setting up burning welding Permit for Construction Operation; col-lateral contractor personnel to renovate a hood structure in re-cuplex; proper venting of the Hydrogen Peroxide piping system; proper valve assembly for helium manifold systems; noise level control; safety meeting material and planning.

DECLASSIFIED

DECLASSIFIED

DEL

HW-55914

- P & GM - Corrected use of unguarded rotary type lawn mower; periodic checking and testing of building sprinkler systems; safety meeting material and assistance for two meetings; noise level control.
- Facilities
- Engineering - 222-S - Proposed installation of additional fire protection; 269-W and 211-U Tank Farm - decontamination facilities; safety meeting material and assistance.
- HLO - A summary of CPD training activities in radiation protection was prepared. HLO was requested by Contract Administration to consolidate this information for HAPO for transmittal to the AEC for use in hearings before the Joint Committee on Atomic Energy.
- IPD - A review was made of the feasibility of Radiation Monitor rotation between IPD and CPD and letter of non-concurrence was issued.
- R & UO - Assistance was given Industrial Medical Operation in conducting a study on Industrial Sanitation for the University of Oklahoma Medical Center.
- HOO-AEC - Clarification of reporting and communication of Accidents, Injuries and Property Damage.

Inspection, Investigation and Audit

Inspections were made of 269-W Decontamination Facility, 202-S and 233-S Buildings.

Made inspections and attended several conferences concerned with the planning for, and engineering study of additional fire protection in the 234-5 Building.

A Medical Treatment Injury resulting in a chip fracture of the left great toe was investigated. Injured was not wearing safety shoes. The injured had recently purchased 8" safety boots but was unable to wear the boots because a large fold had developed in the lining at the junction of leather toe box liner and the lining. Central Stores was contacted and will return the shoes to the vendor for replacement.

Audit of Research and Engineering was issued.

The follow-up audit of Power and General Maintenance Shops was completed.

Audit of Purex is in progress.

Reports Issued

Quarterly roster - CPD Plutonium Deposition Cases

Overexposure Incident Report CPD 58-1

Overexposure Incident Report CPD 58-2

Potential Overexposure Incident Report CPD 58-1

Accident Prevention Council Meeting Minutes

Physical Security Controls Task Force Summary

Monthly Health, Safety and Security Statistical Report

As We See It monthly summary of CPD Medical Treatment Injuries and HAPO Serious Accidents

PERSONNEL DEVELOPMENT AND PLACEMENT

A. Employment

DECLASSIFIED

	<u>Exempt</u>	<u>Non-Exempt</u>	<u>Total</u>
<u>Additions</u>	30	4	34
New Hires	0	0	0
Reactivates	0	2	2
Re-Hires	0	0	0
Re-Engages	0	0	0
Transfers from other components	1	1	2
Changes from exempt to non-exempt	29	1	30
<u>Removals</u>	4	57	61
Retired	0	0	0
ROF	0	6	6
Deceased	0	1	1
Illness	0	4	4
Leave of Absence	0	0	0
Transfer to other components	0	10	10
Resigned	3	7	10
Changes from exempt to non-exempt	1	29	30

Requisitions (Non-Exempt)

Number on Hand 4/1/58	2
Number Received	2
Number Filled	1
Number on Hand 4/30/58	3

Request for Transfer (Exempt)

Number on Hand 4/1/58	21
Number Received	1
Number Transferred	0
Number Closed Out	2
Number on Hand 4/30/58	20

Applications for Employment (Exempt)

Applications received during April	0
Hired	0
Closed Out	0
Invited for Interviews	0
Applications on Hand 4/30/58	0
Open Requisitions	1

Service Pins

A total of 11 pins were issued as follows:

15 Yrs. service	0 Male	0 Female
10 Yrs. service	7 Male	0 Female
5 Yrs. service	2 Male	2 Female

DECLASSIFIED

DECLASSIFIED

HW-55914-

DEL

The increased number of exempt personnel during the month was due largely to the change in job classification of 28 non-exempt Chief Operators (Sep.) to the exempt rolls as Specialists - Separations Process. The number of non-exempt personnel decreased accordingly.

During the month ten Separations Utility Operators and nine craftsmen were declared as being excess. Of this number five Separations Utility Operators and one craftsman were ROP'd. The other eight craftsmen were transferred in accordance with the HAMTC agreement and displaced less senior craftsmen in other HAPO components. One of the Separations Utility Operators was transferred to FPD, two are being transferred to other General Electric plants, one voluntarily terminated and another is on an illness leave and probably will not return.

Twelve interviews with the AEC were held with CPD personnel during the month for open positions in the AEC organization, other than HOO.

Mr. B. B. Delack, Consultant, Manufacturing Personnel Inventory and Placement Service visited with CPD on April 30th.

Status - Personnel Development Program for Non-Exempt Employees

<u>Month</u>	<u>February</u>	<u>March</u>	<u>April</u>	<u>Total</u>
Number of appraisals scheduled	93	106	102	414
Number of appraisals delinquent as of 4/30/58	2	7	63	74

Military Service Records

Records show that CPD has a total of 127 employees who are subject to military training through Selective Service or Armed Forces Reserve action.

	<u>Exempt</u>	<u>Non-Exempt</u>
Ready Reserve	13	13
Standby Reserve	15	6
Deferments Requested		1
Deferments Granted		0
Deferment Requests Pending		3

B. Personnel Training and Development

Participation in Training Courses

Exempt	181
Non-Exempt	372
G.E. Supervisory Selection Program - No. Completed	3
G.E. Supervisory Selection Program - Revaluation	1
Technical Graduates on Rotation	6
Employees counseled in self-development	2
Films shown	9
OPG's issued (1 new, 5 revised)	6

Secretarial training for Level 3 CPD secretaries was inaugurated in April. Nine CPD Level 3 secretaries reported for the first session of training.

Two new groups started Dr. Conant's course "Understanding People" on April 10.

Major Mayer's tape on brainwashing was presented to 14 different groups consisting of approximately 200 people.

The sound slide film and discussion program "Drum Handling" was used in two meetings covering about 30 people.

The "Management Conference on Communications" was conducted by the Specialist, Communication. Five sessions were held and covered the major portion of the managers and Level 4 individual contributors.

Level 3 managers are enrolled in an eleven week course "An Introduction to Finance" conducted by the Financial Operation. Material is similar to the business training course but adapted to non-financial people. This course will assist the managers in the work of a professional manager.

C. Office Services

Duplicating

Total Copies Produced	148,652
Verifax Copies Produced	698
Embosograf Signs Made	117
Ozomatic Copies Produced	13,498

Mail

Total Pieces of Mail Handled	81,773
Registered Deliveries	521
Library Mail, Pounds	777

Addressograph

Instrument Charts Imprinted	8,832
Bulletins, O.P.G.'s, Etc.	9,793

During the month the Embosograf machine was transferred to R and U Printing. This machine, due to its cumbersome operation, has been a source of complaints among employees. A study of the operation was made several months ago with the intent of possibly mechanizing the unit. However, the estimated cost of approximately \$1,200 was prohibitive. The woman operating the machine has complained many times that she has developed shoulder pains which she believed were caused by the physical effort required to operate the machinery. It was a considered opinion that this machine was a little too heavy for the average female employee. As a result R and U Office Facilities was contacted and, since they have some male employees in Printing, agreed to accept the machine from us.

DECLASSIFIED

DECLASSIFIEDEMPLOYEE COMPENSATION OPERATION

Considerable material was accumulated in preparation for off-site reconciliation work. A reconciliation trip was scheduled for the week of April 28 but postponement became necessary. The trip will be rescheduled to a later date.

A preliminary organization study and evaluation of involved positions was completed for a component of the Redox Operation.

AEC approval was received for the removal of the Fixed Rate status from Fire Protection Captains and Lieutenants. Effective June 1, 1958 these positions will assume normal exempt status. There are ten incumbents to the subject positions.

Three jobs were reviewed during the month, 1 secretarial and warranted promotional action taken, 1 semi-technical for which a new classification was established and 1 clerical for which no change is warranted.

One clerical job is presently being reviewed.

Revised job descriptions for Laboratory Assistants were prepared and evaluated both under the proposed new semi-technical evaluation plan and under our present paired factor comparison system. The conclusions reached were that the revised descriptions represented calibers of work for which higher classifications were warranted than those presently assigned to the jobs.

A statistical compilation of nonbargaining unit classification trends is presently under study to determine comparatively what the CPD picture is on this matter.

Several meetings were held during the month in connection with the semi-technical proposal (rate structure and evaluation plan) both with CPD Lab Management and personnel of other Departments relative to certain proposed promotional action by our Lab Management.

Administratively 177 papers were processed in regard to additions to roll, reductions from roll, change in status, and change in salaries.

SUGGESTION PLAN

	<u>MARCH</u>	<u>APRIL</u>
Suggestions Received	57	77
Acknowledgements to Suggestors	49	65
Suggestions Pending Acknowledgement	9	21
Suggestions Referred to Operations for Investigation	49	65
Suggestions Pending Referral to Operations	9	21
Suggestions Completed and Closed	143	82
Adopted Suggestions Approved by Board	34	1
Adopted Suggestions Pending Approval By Board	4	27
Total Net Tangible Savings	\$23,857.14	\$4,400.96
Total Cash Awards Paid During Month	\$ 2,392.50	\$ 502.50

Total number of suggestions outstanding to operations at the end of the month:

<u>MARCH</u>	<u>APRIL</u>
116	111

AVERAGE AGE OF OPEN SUGGESTIONS

PARTICIPATION IN BENEFIT PLANS

	<u>MARCH</u>	<u>APRIL</u>
Insurance Plan	99.7	99.7
Pension Plan	99.2	99.4
Stock Bonus Plan	58.4	60.4
Good Neighbor Fund	61.9	61.3

Letters, together with a brochure and sign up authorization were sent to all non-participants in the stock bonus plan on April 18th.

J. E. Hoff, an employee of P & GM Operation died on April 3rd. All matters pertaining to this case are progressing satisfactorily.

DECLASSIFIED

COMMUNICATION**DECLASSIFIED**A. Statistics

GE NEWS items
 General Manager's meeting with exempt employees
 Management News Bulletins
 Employee Location Records mailed out
 Priority Messages

13
 2
 7
 19
 3

B. Comments on Statistics

Thirteen items were carried in the GE NEWS during the month. These included a story about a speaking engagement by a CPD employee; two pictures and cutlines about the Purex Lobby Safety display; a picture and cutline of a CPD retirement; a service award story; an obituary; a picture and story of a CPD chemist for use in a Chemical Progress Week feature; an attendance award story; a picture, cutline and feature story on a CPD history writer; a story on the Department General Manager's participation in the Advanced Management Course at Crotonville; a picture and cutline of a CPD employee who is Chairman of the Kennewick Cancer Drive; a promotion story; a picture and cutline used in a spring clean-up feature; and four pictures and cutlines of suggestion award winners.

Three priority messages were sent out during the month. These concerned the change in the Goethal bus schedule, an IPD disabling injury, and the R. J. Cordiner-Robert Paxton appointments.

C. Other Employee Communication Activities

Five Management Conferences on Communication were conducted during the month. Those courses were attended by 58 management people from all CPD Operations.

A letter encouraging participation in the Company Savings & Stock Bonus Plan was prepared for the Employee Relation Manager's signature and was included in a packet of information sent to all CPD employees not participating in the Plan. This packet also included a pamphlet and an authorization card. In addition, exempt employees not participating in the Plan received a copy of the Company's ANNUAL REPORT for 1957.

A letter was prepared for the Employee Relation Manager's signature to be sent to all Level 3 managers discussing the progress that has been made in those areas that appeared as unfavorable or "low favorable" on the last attitude survey.

The Upward Communication Report was prepared for the Employee Relation Manager during the month.

D. Public Communication

Some arrangements were made for Relations and Utilities in connection with Representative Hosmer's visit to CPD on April 7.

Two press releases for national publicity purposes were reviewed and approved.

The CPD portion of the Atomic Products Division fact sheet was reviewed and approved at the request of Press Relations, R & U.

Four papers were cleared through Communication during the month.

A final draft of CPD's portion of the Annual HAPO TV Program was prepared and sent to the Acting General Manager for his review and comments.

III. ORGANIZATION AND PERSONNEL

A. Meetings

Personnel in the Employee Relations Operation attended over eighty meetings during the month. In addition to Safety, Security, Round Table, and Information meetings, members of the group attended meetings with their counterparts in other departments. Personnel also participated in the following meetings:

Discussion with A. M. Brown, Fire Protection Consultant, on study of additional fire protection for 234-5 Building.

Information meeting with T. G. Gerry, Representative of Carboline Company, on Coatings, Linings, and Finishes, in Purex Operation.

Representatives from Health and Safety participated in Financial Operation safety meeting and safety meeting of Waste Handling and Decontamination.

The Personnel Development Specialist attended a meeting of GESNE instructors, H. C. Mayer, and W. P. Allen of the Richland Adult Evening School. Preliminary arrangements were made to transfer technical and vocational courses to the adult evening school. These will not longer be offered when the University of Washington assumes the management of the school on July 1.

Four Step II grievance meetings were attended during the month, and the Industrial Relations Council met twice.

DECLASSIFIED

DECLASSIFIED

HW 55914

DEL

Representatives of Employee Compensation Operation attended meetings with certain third and fourth level managers regarding development of communication material, and also wage administration meetings regarding development of new wage structure.

The Communication Specialist, along with those from other HAPO departments, met with Joe Morton of the Schenectady News Bureau. Mr. Morton handles the national publicity and signed article placement for the various components within Atomic Products Division.

B. Training

Fire Protection Personnel participated in 65 inside drills, and 54 outside drills, in which 11,290' of hose and 580' of ladders were used. The percentage of time spent in training was 12.5.

C. Safety and Security

Two medical treatment injuries occurred in the Fire Protection Operation and one in Personnel Development Operation. There were no security violations.

D. S. Roberts, Manager
Employee Relations

END

**DATE
FILMED**

12 / 22 / 92