1 of 2

Derivative Classifier

Assessment of Plutonium in the Savannah River Site Environment^(U)

W. H. Carlton
A. G. Evans
L. A. Geary
C. E. Murphy, Jr.
J. E. Pinder
R. N. Strom

Approved by

A. L. Boni
Research Manager
Environmental Technology Section

SAVANNAH RIVER SITE

Westinghouse Savannah River Company
Savannah River Technology Center
Aiken, SC 29808

DEVELOPED FOR THE U.S. DEPARTMENT OF ENERGY UNDER CONTRACT NO. DE-AC09-89SR18035

CONTENTS

<i>Executive Summary</i>	<i>i</i>
<i>Chapter 1. Introduction</i>	<i>1-1</i>
Plutonium in the Global Environment	1-3
Plutonium in Regional Environments	1-3
Plutonium in the Savannah River Site Environment	1-4
References	1-4
<i>Chapter 2. Origin of Plutonium at the Savannah River Site</i>	<i>2-1</i>
Origin of Plutonium at SRS	2-3
Irradiation In Production Reactors	2-3
Other Sources Because of SRS Operations	2-3
SRS Test Reactors	2-3
Neutron Activities Analysis	2-4
Materials Originating Offsite	2-4
Disposition of Plutonium at SRS.....	2-4
Plutonium in Fuel and Targets Irradiated in Production Reactors	2-4
Plutonium Purchased offsite	2-6
Plutonium in Certain Fuels Irradiated Offsite	2-6
Neutron Activation Analysis Samples.....	2-6
Global Fallout Plutonium	2-6
References	2-6
<i>Chapter 3. Releases and Stored Inventories of Plutonium at the SRS</i>	<i>3-1</i>
Releases and Stored Inventories of Plutonium at the SRS	3-3
Reactor Facilities	3-3
Facility Operations	3-3
Pathways for Release	3-3
Emission Control	3-3
Release Monitoring	3-4
History of Releases	3-5
C Reactor	3-5
K Reactor	3-6
L Reactor	3-8
P Reactor	3-9
R Reactor	3-11
Separations and Liquid Waste Facilities	3-13
Chemical Separation Facility Operations	3-13
Pathways for Release	3-13
Release Monitoring	3-14
History of Measured Releases	3-14

Table of Contents

F-Area Separations	3-14
Releases to Seepage Basins	3-14
Releases to Atmosphere	3-16
H-Area Separations	3-17
Releases to Seepage Basins	3-18
Releases to Atmosphere	3-18
Releases to Streams	3-19
Effluent Treatment Facility	3-19
Waste Tank Farms	3-19
Solid Waste Disposal Facility	3-21
Savannah River Technology Center	3-21
Other Facilities	3-24
References	3-25
<i>Chapter 4. Plutonium Concentration and Transport Mechanisms</i>	<i>4-1</i>
The Global Fallout Background	4-3
Atmospheric Concentration and Transport	4-4
Atmospheric Concentration	4-5
Sources and SRS Concentrations	4-5
Concentrations and Distance from SRS Sources	4-6
Isotopic Ratios of Atmospheric Concentrations	4-7
Deposition Rate	4-7
Soil Concentration	4-8
Soil Concentrations and Distance from SRS Sources	4-8
Summary of Air Concentration and Deposition	4-9
Comparison with Earlier Work	4-9
Simple Model Estimates of the Dispersion and Fate of SRS Plutonium	4-10
Surface Water Transport	4-11
Surface Waters on the Savannah River Site	4-11
Lower Three Runs Creek	4-11
Upper Three Runs Creek	4-11
Steel Creek	4-12
Fourmile Branch	4-12
Pen Branch	4-12
Site Stream Summary	4-12
Savannah River	4-13
Savannah River Estuary	4-14
Groundwater Concentrations and Transport	4-14
SRS Groundwater System	4-14
Plutonium in SRS Groundwater	4-17
General	4-17
Alpha Monitoring	4-17
General Separations Area	4-17
Solid Waste Disposal Facility	4-17
General Separations Area Seepage Basins	4-18
F Area Seepage Basins	4-18
The H Area Seepage Basins	4-19
TNX Seepage Basins-CMX/TNX Seepage Basins	4-19
SRTC Seepage Basins	4-19
Groundwater Samples	4-20
Reactor Areas Seepage Basins	4-20
Summary and Environmental Assessment	4-21
References	4-21

Chapter 5. Environmental Research of Plutonium by the Savannah River Ecology Laboratory	5-1
Plutonium Behavior in Agroecosystems	5-3
The Behavior of Plutonium in Pond B	5-5
Inventory of Plutonium in Pond B.....	5-6
Seasonal Variation in the Plutonium Contents of the Water Column	5-7
References	5-8
Chapter 6. Assessment of Dose/Risk for Savannah River Site Plutonium Releases	6-1
Ralationship of Dose to Risk and Health Effects	6-3
Ionizing Radiation	6-3
Cancer Risk Estimates	6-3
Plutonium Exposure and Dose to Man	6-3
Distribution and Retention of Cesium in the Human Body	6-3
Plutonium Dosimetry.....	6-3
Models of PlutoniumTransport and Dose.....	6-4
Modeling Atmospheric Dispersion of Radioactive Releases	6-4
MAXIGASP	6-5
POPGASP	6-5
Modeling Doses from Liquid Releases.....	6-5
Verification of Models Using Monitoring Data	6-6
Atmospheric Releases.....	6-6
Liquid Releases	6-6
Impact of SRS Plutonium Releases on the Offsite Population.....	6-7
Doses from Atmospheric Releases	6-7
Doses from Liquid Releases	6-7
Comparisons of Plutonium Doses Near SRS with Applicable Regulations	6-8
Atmospheric Releases.....	6-8
Liquid Releases	6-8
Summary of Dosimetric Impacts	6-8
References	6-13

Appendix A. Physical Properties of Plutonium	A-1
Appendix B. Environmental Monitoring	B-1
Air	B-3
Rainwater	B-4
Surface Water	B-4
Effluent Outfalls.....	B-4
Site Streams and Seepage Basins	B-4
Savanna River	B-4
Ground Water	B-5
Drinking Water	B-5
Other Environmental Matrices	B-5
Soil and Sediments.....	B-5
Dairy Products and Food Stuffs	B-6
Vegetation	B-6
Wildlife	B-7
Fish	B-7
Deer.....	B-7
Ducks	B-8

Table of Contents

List of Tables

3-1.	Gross Alpha Releases from C&K Areas by Year (Curies).....	3-7
3-2.	Gross Alpha Releases from L & P Areas by Year (Curies)	3-10
3-3.	Alpha Releases from Misc Areas by Year (Curies)	3-12
3-4.	Plutonium Releases from Separation Areas by Year	3-15
3-5.	Gross Alpha Activity in F-Area Drinking Water, 1989	3-16
3-6.	Gross Alpha Activity in H-Area Drinking Water	3-19
3-7.	Plutonium in SRS High-Level Waste Storage Tanks	3-19
3-8.	Alpha Releases from Misc Areas by Year (Curies)	3-20
3-9.	Solid Plutonium Wastes in the SWDF	3-21
3-10.	Plutonium Releases from SRTC by Year (Curies)	3-23
4-1.	Sediment Sample Plutonium Isotopic Ratios (Alberts, 1986).....	4-12
4-2.	Sediment Concentrations (pCi/gm dry weight of ²³⁸ Pu and ^{239,240} Pu in Creeks (Gladden 1985)	4-13
4-3.	Sediment Concentrations (pCi/gm dry weight) of Plutonium in the Savannah River Floodplain	4-14
4-4.	Comparison of Plutonium Concentration in Burial Ground Monitoring Wells between 1980 and 1986.....	4-18
4-5.	Alpha Activity Discharged to Reactor Seepage Basins, Data on Activities from Hetrick and Martin (1989).	4-20
5-1.	Estimates of parameter values for the Pu transfer model presented in Fig. 5.1.	5-3
5-2.	The inventories of ^{239,240} Pu in components of the Pond B ecosystem, the percent of the total inventory of 11.6 mCi of ^{239,240} Pu in the various components, and the ratio of concentration in biota to that in filtered water	5-4
6-1.	Site-and Age-specific Parameters for Atmospheric Releases	6-9
6-2.	Site- and Age-specific Parameters for Liquid Releases	6-9
6-3.	Additional Site- and Age-specific Parameters for Liquid Releases	6-10
6-4.	Offsite Doses from Atmospheric Releases of ^{238, 239} Pu	6-11
6-5.	Offsite Doses from Stream Releases of Plutonium	6-12
A-1.	Characteristics of Radioactive Plutonium Isotopes That May Be Present at SRS Due to Site Operations	A-3

List of Figures

2.1.	SRS Facilities that had the Potential to Release Plutonium	1-6
3.1.	Stream and River Water Sampling Locations	3-3
3.2.	Gross Alpha Releases to Atmosphere, C Area	3-5
3.3.	Gross Alpha Releases to Streams, C Area	3-5
3.4.	Gross Alpha Releases to Seepage Basins, C Area	3-5
3.5.	Gross Alpha Releases to Atmosphere, K Area	3-6
3.6.	Gross Alpha Releases to Streams, K Area	3-6
3.7.	Gross Alpha Releases to Seepage Basins, K Area	3-6
3.8.	Gross Alpha Releases to Atmosphere, L Area	3-8
3.9.	Gross Alpha Releases to Streams, L Area	3-8
3.10.	Gross Alpha Releases to Seepage Basins, L Area	3-8
3.11.	Gross Alpha Releases to Atmosphere, P Area	3-9
3.12.	Gross Alpha Releases to Streams, P Area	3-9
3.13.	Gross Alpha Releases to Seepage Basins, P Area	3-9
3.14.	Plutonium Releases to Seepage Basins, R Area	3-11
3.15.	Plutonium Releases to Seepage Basins, F Area	3-14
3.16.	Plutonium Releases to Atmosphere, F Area	3-16
3.17.	Gross Alpha Activity in Drinking Water, and Cooling Water, 200-F	3-17
3.18.	Gross Alpha Releases to Streams, F Area	3-17
3.19.	Plutonium Releases to Seepage Basins, H Area	3-18
3.20.	Plutonium Releases to Atmosphere, H Area	3-18
3.21.	Alpha Releases to Streams, H Area	3-19
3.22.	Gross Alpha Activity in Drinking Water, and Cooling Water, 200-H	3-19
3.23.	Gross Alpha Releases to Streams, SRTC	3-22
3.24.	Alpha Releases to Basins, SRTC	3-22
3.25.	Alpha Releases to Atmosphere, SRTC	3-24
3.26.	Gross Alpha Releases to Streams, D Area	3-24
3.27.	Gross Alpha Releases to Seepage Basins, Central Shops	3-27
4.1.	A Comparison of Atmospheric Concentrations of ¹³⁷ Cs and ²³⁹ Pu at Four Most Distant Sampling Locations	4-3
4.2.	Comparison of Fallout Plutonium Isotope Ratios to SRS Ratios at the Most Distant Sampling Stations	4-3
4.3.	Comparison of Deposition and Air Concentration of ²³⁹ Pu	4-4
4.4.	Comparison of ²³⁹ Pu Air Concentrations and Sources	4-5
4.5.	Comparison of ²³⁸ Pu Air Concentration and Sources	4-5
4.6.	²³⁹ Pu Air Concentration Versus Distance from SRS Source	4-6

Table of Contents

4.7.	^{238}Pu Air Concentration Versus Distance from SRS Source	4-6
4.8.	Distribution of Slopes for Plutonium Isotopes Air Concentration Versus Distance	4-6
4.9.	The Fraction of ^{238}Pu in Atmospheric Plutonium as a Function of Distance from this SRS Source	4-7
4.10.	Distribution of ^{238}Pu Activity as a Function of Particle Diameter	4-7
4.11.	Distribution of Slope of Plutonium Deposition as a Function of Distance from the SRS Release Point	4-8
4.12.	Fraction of ^{238}Pu in Deposition Versus the Distance from the SRS Source	4-8
4.13.	^{239}Pu Deposition in Soil Versus Distance from the SRS Source	4-9
4.14.	^{238}Pu Deposition in Soil Versus Distance from SRS Source	4-9
4.15.	^{238}Pu Fraction in Soil as a Function of Distance from SRS Sources	4-9
4.16.	Comparison of the Influence of Fallout and SRS Releases on ^{239}Pu Air Concentration at the Site Perimeter	4-10
4.17.	Comparison of the Influence of Fallout and SRS on ^{238}Pu on Air Concentration at the Site Perimeter	4-10
4.18.	Stratigraphic and Hydrostratigraphic Nomenclature Used on the Savannah River Site	4-15
4.19.	Hydraulic Head Differences Across Confining Unit Near the Cretaceous/ Tertiary Boundary	4-16
4.20.	Location Map of Waste Disposal Sites in the General Separations Area	4-17
4.21.	Location of the Old TNX Seepage Bains	4-19
4.22.	Location of the M-Area Settling Basin and the SRTC Seepage Basins	4-19
5.1.	A model of Pu transport in agroecosystems involving processes occurring while the crop growing in the field and when the crop is mechanically harvested using a combine	5-4
5.2.	The ^{239}Pu Concentrations for grains from wheat, soybean, and corn agroecosystems as a result of atmospheric deposition, resuspension, and root uptake for a hypothetical scenario in which a nuclear facility operates for 30 years and deposits $2.7 \text{ pCi } ^{239}\text{Pu}$ $\text{m}^{-2}\text{d}^{-1}$ onto areas already containing $2,000 \text{ pCi m}^{-2}$ from global fallout	5-5
5.3.	Inventories of $^{239,240}\text{Pu}$ in the water column of Pond B for samples collected from February 1983 to December 1986. Inventories are computed from determinations of $^{239,240}\text{Pu}$ concentrations in seston and filtered water collected at 1, 4, 8, and >9m depths and plotted as a function of the time since November 1, the nominal date of turnover. Vertical lines demark the usual dates for the development of stratification (March 10) and the onset of anoxia in waters >9m deep (April 15). Standard errors (vertical bars) are presented for means when data are available from both stations 1 and 2	5-7
6.1.	Simplified Pathways Between Radioactive Materials Released to the Atmosphere and Man	6-4
6.2.	Simplified Pathways Between Radioactive Materials Released to Ground or Surface Waters and Man	6-6
B.1.	Location of Air Monitoring Stations	B-3
B.2.	Air Sampling Station and Component Diagram	B-3
B.3.	Milk Sample Locations	B-6
B.4.	Food Sample Locations	B-6

B.5.	Vegetation Sampling Locations Inside the Solid Waste Disposal Facility	B-7
B.6.	Vegetation Sampling Locations Outside the Solid Waste Disposal Facility	B-7
B.7.	Fish Sample and Water Treatment Plant Locations Along the Savannah River.....	B-7

Executive Summary

Plutonium in the Savannah River Site Environment is published as a part of the Radiological Assessment Program (RAP). It is the fifth in a series of eight documents on individual radioisotopes released to the environment as a result of Savannah River Site (SRS) operations. The earlier documents describe the environmental consequences of tritium, iodine, uranium, and cesium. Documents on strontium, carbon, and technetium will be published in the future. These are living documents, and current plans call for the revision and update of each one on a two-year schedule.

Plutonium exists in the environment as a result of above-ground nuclear weapons tests, the Chernobyl accident, the destruction of satellite SNAP 9-A, plane crashes involving nuclear weapons, and small releases from reactors and reprocessing plants.

Plutonium has been produced at SRS during the operation of five production reactors and released in small quantities during the processing of fuel and targets in chemical separations facilities. Approximately 0.6 Ci of plutonium was released into streams and about 12 Ci was released to seepage basins, where it was tightly bound by clay in the soil. A smaller quantity, about 3.8 Ci, was released to the atmosphere. Virtually all releases have occurred in F- and H-Area separation facilities.

Plutonium concentration and transport mechanisms for the atmosphere, surface water, and ground water releases have been extensively studied by Savannah River Technology Center (SRTC) and ecological mechanisms have been studied by Savannah River Ecology Laboratory (SREL).

The overall radiological impact of SRS releases to the offsite maximum individual can be characterized by a total dose of 15 mrem (atmospheric) and 0.18 mrem (liquid), compared with the dose of 12,960 mrem from non-SRS sources during the same period of time (1954-1989). Plutonium releases from SRS facilities have resulted in a negligible impact to the environment and the population it supports.

This page intentionally left blank.

Chapter 1. Introduction

This page intentionally left blank.

Plutonium in the Global Environment

Radioactive isotopes of plutonium exist in nature at minute levels. The natural mechanism for plutonium production is the capture of naturally occurring neutrons by uranium. Plutonium produced by this mechanism is primarily localized in ore deposits containing uranium.

Man-made sources that contribute plutonium to the global environment are above-ground nuclear weapons tests, nuclear reactor operations, and accidents. Nuclear weapons testing has been the most significant man-made source of plutonium in the global environment. Above-ground testing has introduced about 320,000 Ci of $^{239,240}\text{Pu}$ to the atmosphere, much of which has deposited on the earth as fallout, both on a regional and a global scale (Eisenbud, 1987a). ^{239}Pu and ^{240}Pu are indistinguishable by alpha spectroscopy, and are usually reported as ^{239}Pu . ^{238}Pu was also released from nuclear weapons, but in much smaller quantities; about 9,000 Ci. Since the mid-1960s when the USA and USSR ceased above-ground testing, plutonium concentrations as a result of the fallout mechanism in the atmosphere have decreased dramatically.

Another man-made source that contributes plutonium to the global environment is nuclear reactor

operations. Ideally, all of the plutonium produced in nuclear power reactors is contained in the fuel until reprocessing occurs. However, under accident conditions plutonium can be released to the global environment, as demonstrated by the Chernobyl nuclear reactor accident in 1986.

The accident at Chernobyl in the USSR, released 800 Ci of ^{238}Pu and 1,700 Ci of $^{239,240}\text{Pu}$ to the environment (Legasov et al., 1987). The conditions at Chernobyl were severe enough to inject some of the plutonium into high altitudes. This allowed plutonium to be distributed globally. However, most of the plutonium was deposited as regional fallout in Europe.

For decades ^{238}Pu has been used as an electricity generating heat source in satellites. A satellite launched in 1964 failed to reach orbit velocity and released 17,000 Ci of ^{238}Pu when it burned up during reentry (Eisenbud, 1987b).

Several plane crashes involving nuclear weapons have been reported. One occurred in 1964 at Thule, Greenland, and released 29 Ci of ^{239}Pu on sea ice which melted when the weather warmed transferring the ^{239}Pu to the sea (Aarkrog, 1984).

Plutonium in Regional Environments

Man-made sources that contribute plutonium to regional environments are nuclear weapons tests, nuclear reactor operations, and nuclear fuel reprocessing operations.

Above-ground nuclear weapons tests produce regional and global fallout. Plutonium may also enter the atmosphere and regional environments if an underground test were to vent.

The non-routine operation of experimental, research, power, and production nuclear reactors has released small quantities of plutonium to regional environments.

Nuclear fuel reprocessing operations have been the most significant localized source of plutonium. Reprocessing facilities are located in several countries worldwide. Reprocessing consists of chemical separation of materials that have been irradiated in experimental, research, power, and production reactors. As a result of the chemical separations process, the plutonium content of irradiated materials can be released to the environment via aqueous waste streams or stacked gases.

Plutonium in the SRS Environment

Numerous radioactive isotopes of plutonium are made in the fuel and targets of the production reactors at the SRS. Some of the isotopes are short-lived and decay to insignificant activity levels during the time interval between end of irradiation and commencement of reprocessing by chemical separations at SRS, while others are produced in extremely small quantities.

The radiological properties of 12 radioactive isotopes of plutonium which are in use or produced at the SRS are tabulated in Appendix 1, Table A1-1. Only two isotopes, ^{238}Pu and ^{239}Pu , are significant for purposes of radiation exposure in the environment at the SRS. Over the 34-year operating history of the SRS, about 4.8 Ci of ^{238}Pu , 11 Ci of ^{239}Pu , and 0.6 Ci identified as "gross alpha" have been released to the environment (Hetrick and Martin, 1990).

References

Aarkrog, A., et al., 1984, "Further Studies of Plutonium and Americium at Thule, Greenland". *Health Physics* 46, 29-44.

Eisenbud, M. 1987a, "Environmental Radioactivity", Academic Press, p. 335.

Eisenbud, M., 1987b, "Environmental Radioactivity", Academic Press, p. 365.

Hetrick, C. S. and D. K. Martin, 1990, "Radioactive Releases at the Savannah River Site 1954-1988", WSRC-RP-89-737, Westinghouse Savannah River Company, Aiken, SC.

Legasov, V.A., et al., 1987, "Information on the Accident at the Chernobyl Nuclear Power Station and its Consequences, Prepared for IAEA", Soviet Atomic Energy (English Translation), 61: 845-868.

This page intentionally left blank.

M93A030.04

Figure 2.1. SRS Facilities that had the Potential to Release Plutonium

Chapter 2. *Origin of Plutonium at the Savannah River Site*

This chapter gives a general overview of the origin, uses, and disposition of plutonium at SRS under normal operating conditions. The locations of the SRS facilities which had the potential to release plutonium are shown in Figure 2.1. The greatest releases of ^{239}Pu occurred during the early years of site operation and originated in the chemical separation facilities, located near the center of the 800-square-kilometer site. The history of actual releases from specific SRS facilities is presented in Chapter 3.

This page intentionally left blank

Origin of Plutonium at the Savannah River Site

Plutonium at the Savannah River Site (SRS) predominantly originated in the fuel and targets that were irradiated in the nuclear materials production reactors. Other site operations and offsite sources contributed to the inventory of plutonium at the SRS.

Irradiation in Production Reactors

Most of the plutonium at SRS was formed during the irradiation of nuclear fuel and targets during operation of the five production reactors. The role of the production reactors was to produce special nuclear materials—principally tritium and plutonium—for national defense purposes. Additional radionuclides, such as ^{238}Pu , which is a power source for certain deep-space missions, were occasionally produced for other government purposes.

Although the reactors became operational in 1953-1955, they have not operated continuously. They have alternated between operating periods for production and shutdown periods for maintenance or the replacement of fuel and targets. As of 1988, one reactor was inactive and one was on standby. The three remaining reactors were shut down after 1988 for maintenance and safety upgrades. The history of individual reactor operations is presented in Chapter 3.

The principal mechanism for ^{239}Pu production in the reactors is neutron capture by ^{238}U . When a reactor is operating, neutron-induced fission reactions occur in the ^{235}U fuel of the reactor core. In addition to fission products, each neutron-induced fission reaction in the fuel produces several neutrons, some of which induce additional fission reactions and maintain the chain reaction. Some of the remaining neutrons interact with target materials in the reactor. The principal isotope resulting from neutron capture by ^{238}U is ^{239}U . The ^{239}U rapidly decays (with a 23.5 minute half life) to ^{239}Np , which in turn decays with a 2.36 day half life to ^{239}Pu . Certain target materials, such as ^{238}U , also undergo neutron-induced fission as a competing reaction. In the case of ^{238}U targets, fission also occurs in the minor constituents, such as ^{235}U and ^{239}Pu . Two other significant competing reactions occur in the fuel and target elements. They are significant because they lead to the formation of ^{237}Np , which is the target material for the production of ^{238}Pu .

In the fuel, some of the ^{235}U captures a neutron to form ^{236}U . The ^{236}U in turn captures a neutron to

form ^{237}U , which decays to ^{237}Np . As ^{235}U is recycled through the irradiation and recovery process, the isotopic fraction of ^{236}U increases, resulting in increasing amounts of ^{237}Np formation. Neptunium has been recovered in special operations in H Area and fabricated into targets to produce ^{238}Pu . The second reaction producing ^{237}Np occurs in the ^{238}U targets. In some cases, fission neutrons interacted with the ^{238}U before the neutrons were slowed down by the heavy water moderator. The two principal interactions between ^{238}U and fast neutrons are fission, as mentioned above, and an (n,2n) reaction which results in the formation of ^{237}U . The ^{237}U subsequently decays to ^{237}Np .

Other isotopes of plutonium, especially ^{240}Pu and ^{241}Pu , are produced in SRS reactors, principally as unwanted byproducts resulting from neutron capture by ^{239}Pu . The ^{240}Pu content is intentionally minimized because of its adverse effect on weapons yield. The ^{241}Pu content is kept intentionally low to minimize buildup of its daughter, ^{241}Am . The decay daughters of ^{241}Am emit gamma radiation, which increases personnel exposure during handling and storage of nuclear weapons.

Other Sources Due to SRS Operations

Small quantities of plutonium were produced at SRS by test reactors and neutron activation analysis. The activity levels of plutonium from these sources were insignificant when compared to activity levels in irradiated nuclear fuel and targets. However, these sources are discussed in the following subsections to provide a complete overview of potential plutonium releases.

SRS Test Reactors

Several small nuclear reactors were in use at two SRS locations from the 1950s through the 1970s. The Heavy Water Components Test Reactor (HWCTR), located in B Area, was used in the early 1960s to test prototype fuels for a proposed heavy water power reactor. The other test reactors were located in M Area. The Process Development Pile and the Lattice Test Reactor were used as zero-power mock-up facilities to test components for the production reactors. The Subcritical Experimental Pile also was used to test component designs. The Standard Pile provided neutrons for experiments such as neutron radiography and neutron activation. These facilities were used from the mid-1950s to the late 1970s.

Neutron Activation Analysis

Neutron activation analysis is an analytical technique for measurement of elemental compositions in materials. The ^{252}Cf neutron activation facilities and the C and K production reactors were used for the analysis of low levels of ^{129}I and uranium. For example, from the late 1970s to mid-1980s, environmental samples were activated in C Reactor to determine uranium content. Traces of plutonium were produced in the irradiated uranium samples.

Materials Originating Offsite

Certain fuel irradiated at offsite non-commercial facilities was shipped to the SRS for reprocessing. While awaiting reprocessing, the fuel was stored in the Receiving Basin for Offsite Fuel (RBOF) located in H Area. This fuel contained varying amounts of plutonium and ratios of plutonium isotopes, depending on the irradiation history. Plutonium scrap also has been sent to SRS from within the DOE complex for purification and recovery.

Some plutonium was purchased from offsite vendors in neutron sources. ^{239}Pu -beryllium neutron sources are used to calibrate radiation survey instruments.

Plutonium fluoride neutron sources also are used for radiation survey instrument calibration. Some ^{238}Pu -beryllium sources were used as reactor startup sources for the zero-power reactors in M Area or as instrument response sources in the same facilities. The plutonium was of SRS origin, but the sources were fabricated at Mound Laboratories. Sealed plutonium oxide sources of up to several hundred grams also have been obtained from offsite locations for calorimeter calibration. Lesser quantities of plutonium have been purchased from offsite vendors to use as standards for calibration of other analytical instruments or to determine chemical yield in analytical chemical procedures.

Plutonium-contaminated soil and other debris from Spain and Greenland also are buried at the SRS. These materials were recovered from the crash sites of aircraft carrying nuclear weapons.

The SRS and its vicinity have been subjected to global fallout of plutonium since the 1940s. During the era of extensive atmospheric nuclear weapons testing in the 1950s and early 1960s, fallout was often found to be the predominant source of plutonium in the vicinity of the SRS. Environmental plutonium is discussed elsewhere.

Disposition of Plutonium at the SRS

Because of the potential use of plutonium for nuclear weapons, strict accountability is maintained on the material. The sources of plutonium are categorized as follows:

Major sources

- fuel and targets irradiated in production reactors
- certain fuels irradiated offsite
- scrap and recovery materials from other DOE sites

Minor sources

- fuel and targets irradiated in SRS test reactors
- commercially purchased plutonium
- soil and other debris from aircraft crash sites
- neutron activation analysis samples
- global fallout

Plutonium in Fuel and Targets Irradiated in Production Reactors

Under ideal operating conditions, plutonium is contained within the cladding of fuel and target elements during both irradiation and cooling. Cooling is the interval between the end of irradiation and the beginning of chemical separations. Irradiated materials are stored underwater in reactor basins for most of this time. Beginning in the 1970s, the cooling time was at least 200 days for most irradiated materials.

Under normal operating conditions, it was possible for traces of plutonium to escape from irradiated fuel and target elements to the reactor moderator or to the water in the cooling basins through small defects in the cladding. Air and water at reactors were monitored for such possible releases of plutonium. Actual releases are described in greater detail in Chapter 3.

Occasionally, the small defects developed into holes or splits in the cladding. This was called a failure of the element. When a failure occurred, the reactor was shut down and the failed element was transferred into a container called a "harp". The harp was stored underwater in the reactor basin and vented to the reactor stack. Failures occurred more frequently in the early years of operation than in later years.

A failed element had the potential to contaminate the moderator with plutonium—SRS reactors used heavy water as a moderator. These small quantities generally were not measurable by routine methods.

Water in the reactor cooling basins also had the potential to become contaminated with plutonium. Beginning in the 1960s, basin water routinely was decontaminated by passing the water through ion exchange resins to remove most of the radionuclides. Spent resins were reworked in the Resin Regeneration Facility in H Area or buried in the Burial Grounds [in 1990 the Burial Ground was renamed as Solid Waste Disposal Facility (SWDF)].

After the cooling period, fuel and targets were treated in the chemical separation areas. During the chemical separation process, targets were treated by the Purex process in F Area to recover ^{239}Pu , ^{237}Np , and ^{238}U from irradiated ^{238}U . The Purex process extracted plutonium and uranium into an organic solvent for separation and purification from waste products. Fuel was treated by the HM process in H Area to recover ^{235}U and ^{237}Np from irradiated ^{235}U ; until 1959, the Purex process was used in H Area. The principal difference is that the HM process uses mercuric nitrate as a catalyst to enhance dissolution of the irradiated fuel. Also in H Area ^{238}Pu occasionally was recovered from ^{237}Np targets by the Frames process.

The clarification of dissolver solution and the solvent extraction of uranium, plutonium, and neptunium occurred in process tanks. The vapor space was exhausted to the process vessel vent system and then to the atmosphere through a high efficiency sand filter and 61-meter stacks.

Aqueous wastes from the chemical separation processes were evaporated and then sent to underground storage tanks for radioactive waste. Separation of plutonium and uranium from the fission products is not quantitative, so traces of these materials are contained in the waste in storage. The condensate from evaporation of stored liquid waste was sent to the separations area seepage basins until November 1988 when use of the seepage basins was terminated. Miscellaneous aqueous wastes were treated periodically by the evaporation process. Beginning in November 1988, condensate was sent to

the Effluent Treatment Facility where it was treated to remove radionuclides and chemicals before being discharged to Upper Three Runs Creek.

All ventilation air in the plutonium processing facilities (FB Line and HB Line) now passes through a graded sand filter before being discharged through the 61-meter stacks. Ventilation gases from the cabinets are filtered through HEPA filters before being routed to the sand filters. In the early days of operation, exhaust air from the B Line facilities was filtered through HEPA filters only and exhausted through short stacks on the roof of the canyon buildings. The HEPA filters provided excellent filtration, but after a fire at the Rocky Flats facility demonstrated the vulnerability of HEPA filter installations to smoke pluggage, the ventilation systems for the plutonium handling facilities at SRS were modified to provide additional filtration.

During the reprocessing of ^{237}Np targets in H Area by the Frames process, offgases from dissolution of cooled ^{237}Np targets were passed through the sand filter instead of a silver-nitrate reactor before exhausting through the 61-meter stack. This process modification was instituted because the irradiation of ^{237}Np targets produced much less iodine than the irradiation of ^{235}U fuel.

The Frames process used ion exchange rather than solvent extraction to separate and purify ^{238}Pu and ^{237}Np from waste products. The treatment for air and aqueous wastes from ion exchange steps is similar to the HM process.

High-level liquid wastes generated in the SRTC operations were stored in temporary waste tanks where short-lived radionuclides decayed to insignificant levels. Periodically, the contents of waste tanks were shipped to F Area and processed through the waste system. Solid wastes generated in the SRTC handling operations were allowed to decay to low levels and then buried in the SWDF.

Most of the atmospheric and aqueous effluents in the chemical separations areas and SRTC have been monitored for possible plutonium releases. Those not specifically monitored for plutonium were monitored for gross alpha. Monitoring techniques and measured releases from the chemical separation areas are described in Chapter 3.

The distributions to the atmosphere, seepage basins, and SWDF had a direct impact on the environment. Plutonium released through stacks was transported through the atmosphere and deposited both onsite and offsite.

Plutonium Purchased Offsite

As indicated earlier, some plutonium has been purchased from offsite vendors for use as analytical standards or neutron sources. Analytical standards have been purchased in two forms: certified liquid standards used to calibrate counting instruments or to determine chemical yields in analytical procedures and sealed sources used to calibrate calorimeter baths.

Liquid standards are disposed of as low-level waste after being used. Sealed neutron sources and calorimeter standards are both accountable sources and radiation hazards and are kept in secure, shielded vaults when not in use.

Plutonium in Certain Fuels Irradiated Offsite

Irradiated fuels received from certain offsite facilities were stored underwater in RBOF until the fuel was ready for chemical separations. The fuel then entered the regular process stream in H Area. The disposition of plutonium became the same as described for fuel irradiated in SRS production reactors. Plutonium in Fuel and Targets Irradiated in Test Reactors Fuels and targets from the various test reactors were sent primarily to the RBOF for cooling before chemical separation. Some were sent to the SRTC for research or to reactor materials fabrication facilities. Reactor materials fabrication facilities only received fuel or targets that were not irradiated; this material was blended into the standard fabrication process for targets and fuel to be used in the production reactors. Because only undetectable quantities of naturally produced plutonium occurred in the fabricated materials, such as ^{238}U , no monitoring for plutonium was conducted at fabrication facilities.

Neutron Activation Analysis Samples

Environmental samples were analyzed by high-sensitivity neutron activation for the detection of trace levels of uranium and ^{129}I . Typically, the uranium analysis was nondestructive; therefore, any plutonium produced from fission of uranium was not released. The plutonium content was minute and the samples were disposed in the SWDF as solid radioactive waste.

Global Fallout Plutonium

Most global fallout occurs because of atmospheric nuclear weapons tests. It has been estimated that 320 kCi of $^{239,240}\text{Pu}$ and 9 kCi of ^{238}Pu have been injected into the atmosphere from these tests through 1974. An additional 17 kCi of ^{238}Pu was injected into the atmosphere as the result of the abortive re-entry of the SNAP 9A satellite (Eisenbud, 1987). The Chernobyl accident also contributed about 2.5 kCi of ^{238}Pu , ^{239}Pu , and ^{240}Pu to the atmospheric inventory (Eisenbud, 1987). Most of the plutonium injected into the atmosphere has returned to the earth's surface as fallout. While distribution of the fallout over the terrestrial environment is not uniform, it has been estimated that Plutonium deposition in the north temperate latitudes has been about 1.4 mCi/km² (Eisenbud, 1987). At that rate of deposition, the Savannah River Site has received about 1.2 Ci of fallout $^{239,240}\text{Pu}$ over its approximately 325 mi² area, and the Savannah River drainage system (10,579 mi²) (Langley and Marter, 1973) has received approximately 38 Ci of fallout plutonium. This compares with a total of 3.8 curies of plutonium isotopes released to the atmosphere from SRS operations (see Chapter 3).

References

Eisenbud, M., 1987. "Environmental Radioactivity from Natural, Industrial and Military Sources", Third Edition, Academic Press, Orlando, FL.

Langley, T.M., and W.L. Marter, 1973. "The Savannah River Plant Site", USDOE Report DP-1323. E. I. du Pont de Nemours & Co. Aiken, SC.

Chapter 3. Releases and Stored Inventories of Plutonium at the SRS

This chapter presents a discussion on plutonium at SRS facilities in terms of possible release pathways, emission control features, and annual releases to the aqueous and atmospheric environments. Specific radiochemical analyses for plutonium were made only in those locations where Pu releases were likely to occur. Gross alpha analyses (or unidentified alpha) were performed in most other locations. To be conservative, it is assumed that all the gross alpha releases were ^{239}Pu (except for releases from the fuel fabrication facilities where no plutonium is handled). Of the two isotopes of plutonium produced in the largest quantity, ^{239}Pu results in a slightly higher dose to man than ^{238}Pu .

Releases and Stored Inventories of Plutonium at the SRS

Routine operations at SRS facilities have released plutonium to the regional environment surrounding the SRS. The most significant releases occurred during the early years of site operations when plutonium was released to the atmosphere, seepage basins, and site streams. The greatest releases of plutonium originated in the F- and H-Area chemical separation facilities. The locations of these facilities and the stream sampling locations are shown in Figure 3.1, which also shows the location of other facilities having the potential to release plutonium. The only significant release of plutonium from the reactor areas occurred in 1957 as a result of the failure of an experimental fuel element in 100-R. The R-Area release was to seepage basins, not plant streams. All of the other peaks shown in the figures are relatively small and of little significance.

Reactor Facilities

The five production reactors at the SRS are identified by the letter designations C, K, L, P, and R. The reactors were designed to irradiate various targets to produce special nuclear materials (principally tritium and plutonium) for national defense purposes. Specific radionuclides for other government purposes were also produced, such as ^{238}Pu , which is a power source for certain deep-space missions.

Facility Operations

Although the reactors became operational in 1953-1955, they have not operated continuously. They have been shut down periodically for maintenance, safety upgrades, or replacement of fuel and targets. In 1988, three reactors were shut down for extensive maintenance and safety upgrades; prior to 1988 one reactor was placed on inactive status and another on standby.

When a nuclear reactor is operating, nuclear fission reactions occur in the reactor core. The principal components of the core are the fuel, targets, control rods, and moderator. Control rods are neutron-absorbing materials that are positioned in the core to control the power level of a reactor.

The moderator in SRS reactors is heavy water, which is circulated around the fuel and target elements in the reactor core. The moderator decreases the kinetic energy (slows the speed) of neutrons emitted in the fission process. Slow neutrons have a greater

probability for interaction with fuel and target materials than fast neutrons. The moderator also functions as the primary coolant to remove heat from fuel and target elements. Heat is then transferred from the moderator by heat exchangers to the secondary coolant. SRS reactors used either river or pond water as the secondary coolant.

In reactors that used water from the Savannah River as the secondary coolant, the river water was passed through the shell side of the heat exchanger and discharged to a site stream that flows to the Savannah River. Reactors that used pond water as the secondary coolant discharged the water from the heat exchanger to a canal that flowed to a series of cooling ponds. Cooled pond water was recirculated through the heat exchanger.

Under normal operating conditions, fuel and target elements were irradiated for a specified time, removed from the reactor core, and stored underwater in the Vertical Tube Storage (VTS) basin of the reactor building. Storage in VTS for the cooling period, which, as of 1988, was at least 200 days, allowed short-lived radionuclides to decay to low levels before reprocessing of the fuel and targets began. After cooling, the elements were moved to the disassembly basin and prepared for transfer to the chemical separations areas.

The abnormal condition of a fuel or target failure is detected by sensors in the reactor core. When a failure occurred, the reactor was shut down and the failed element was transferred into a container called a "harp". The harp was stored underwater in the reactor basin and vented to the reactor stack.

Pathways for Release

During normal reactor operations, traces of plutonium can escape from irradiated fuel or target elements if a defect develops in the cladding. The defect typically was a micro-scale crack. If a defect develops while the element is in the reactor core, plutonium escapes from the irradiated material to the moderator by leaching of plutonium from the exposed irradiated material.

Circulating moderator and basin water were the primary pathways by which aqueous plutonium was released to the environment. Moderator could have mixed with the secondary coolant if a leak existed in

the reactor heat exchanger. Any plutonium released by this pathway was not quantified; however, the secondary coolant was monitored for beta-gamma activity which would have been many orders of magnitude higher than the plutonium activity. Leakage to the secondary coolant was a minor pathway compared to the basin water pathway.

Initially, reactor basin waters were purged directly to site streams to remove the heat generated by the stored irradiated fuel and targets. After installation of basin heat exchangers, deionizers, and filters in the 1960s, the volume of purged water decreased significantly as did the releases of radioactivity.

Periodic purges were performed to eliminate tritium, the accumulation of which resulted in exposure to operating personnel. Purges have been discharged to earthen seepage basins as well as streams. When discharged to streams, the purge water became diluted with much larger volumes of secondary cooling water. Reactor basin discharges to site streams ceased in 1978.

After 1978, reactor basin discharges were directed to the reactor seepage basins. SRS soils have a high affinity for plutonium, thus most Pu discharged to basins remains fixed in the first few inches of soil in the basins.

A source of wastewater that had low potential for containing plutonium was the reactor process sewer system. This system principally received cooling water from the shell side of heat exchangers for reactor basins and other miscellaneous process waters. Process sewer water was sampled daily and analyzed for radionuclides.

Other wastewater was collected in process sumps at the reactor facilities. Occasionally, this wastewater contained moderator from leaks that developed during reactor operations or spills that occurred when line breaks were made during maintenance periods. The wastewater was collected and analyzed for both radionuclides and moderator content. Possible disposition methods, depending on analysis results, were processing through the Heavy Water Rework Facility or the waste evaporators in the separation areas, or discharging to seepage basins or streams.

The only known mechanism for atmospheric releases of plutonium from the reactor areas is from resuspension of particulates from dried liquids. All the fuel handling activities for irradiated materials that could contain Pu are accomplished under water, thus minimizing the likelihood of generation of plutonium-contaminated particulates or aerosols. All

the process area air from the reactor buildings is filtered through HEPA filters before discharge to atmosphere, further minimizing the likelihood of Pu releases.

Emission Control

Various measures were implemented to minimize releases of radioactivity. One of these was the extensive improvement in the quality of materials fabricated for irradiation. Such improvement minimized the formation of defects in the cladding of fuel and targets.

In the reactor areas, procedural changes had been implemented to reduce releases. Provisions were made in 1963 for the recirculation of basin water through heat exchangers to be cooled and deionized for the removal of radionuclides (except tritium), which reduced discharge volumes considerably. Prior to 1963, basin water was purged continuously to site streams. Although the deionizers were effective in removing particulates, permanent sandfilters were installed in the late 1960s to maintain water clarity. The residues collected on the sand filters were transported to F Area to be processed and stored in waste tanks. Spent deionizer resin was transported to H Area for regeneration.

Having accounted for the removal of heat, most radionuclides, and particulates, only the accumulation of tritium prevented the indefinite recirculation of basin water. To reduce tritium exposure to workers in basin areas, basin water periodically was purged to site streams or to reactor seepage basins. No purges to site streams have occurred since 1978.

Under normal operation conditions, moderator and some residual radionuclides adhered to fuel and target surfaces when they were removed from the reactor core. To reduce the adhered radioactivity, flushing of these elements during the discharge process was implemented in the late 1960s. This removed most of the adhered moderator and some residual radionuclides (such as plutonium). After flushing, the elements were stored in the VTS. The flush water was collected in drums for treatment in the D-Area Heavy Water Rework facility.

Atmospheric releases were minimized by the use of a confinement system which was intended not only for routine operations but also for a reactor incident. The system consisted of a demister filter bank, a particulate HEPA filter bank, and the carbon filter bank.

Release Monitoring

The initial procedure to determine atmospheric releases of radioactivity was to measure the air filters for gross beta-gamma activity.

The filters were submitted for laboratory analysis of alpha emitters only if activity was detected above background. After the early 1970s, the procedure was changed to submit all samples to the laboratory to quantify the gross alpha releases as well as the beta-gamma activity. Because of the low release rates and small potential for Pu release, specific radiochemical analyses for plutonium were not made.

In a like manner, aqueous alpha releases to streams and seepage basins were not quantified until the 1970s. The exception to this practice was the monitoring of plutonium releases to the R-Area seepage basin system following the failure of an experimental fuel element in the isolation basin in 1957. Because plutonium was known to be released to the basin in this incident, specific radiochemical analyses were performed.

History of Releases

C Reactor

C Reactor was operational from 1955 until it was shut down for extensive maintenance in 1985; it was placed in standby mode in 1987. Reactor basin purges were discharged into Fourmile Branch and three seepage basins, designated 904-66G, -67G, and -68G. The seepage basins were used from 1959 to 1970 and again from 1978 through 1984. The total measured aqueous releases of alpha activity from C Reactor during its operational lifetime were 9.7 millicuries to Fourmile Branch and 3.8 millicuries to the seepage basins. The total measured atmospheric releases of alpha emitting isotopes from C Area were 38 microcuries (3.8×10^{-5} Ci). Measured annual alpha releases by year from C Area are shown in Figures 3.2 (releases to atmosphere), Figure 3.3 (releases to stream), Figure 3.4 (releases to seepage basins), and in Table 3-1.

Figure 3.2 Alpha Releases to Atmosphere, C Area

Figure 3.3 Alpha Releases to Streams, C Area

Figure 3.4 Gross Alpha Releases to Seepage Basins, C Area

Table 3-1. Gross Alpha Releases from C & K Area by Year (Curies)

Year	100-C** Atmos Fig 3.2	100-C** Basins Fig 3.4	100-C** Stream Fig 3.3	100-K** Atmos Fig 3.5	100-K** Basins Fig 3.7	100-K** Stream Fig 3.6
1954	—	—	—	—	—	—
1955	—	—	—	—	—	—
1956	—	—	—	—	—	—
1957	—	—	—	—	—	—
1958	—	—	—	—	—	—
1959	—	—	—	—	—	—
1960	—	—	—	—	—	—
1961	—	—	—	—	—	—
1962	—	—	—	—	—	—
1963	—	—	—	—	—	—
1964	—	—	—	—	—	—
1965	—	—	—	—	—	—
1966	—	—	—	—	—	—
1967	—	—	—	—	—	—
1968	—	—	—	—	—	—
1969	—	—	—	—	—	—
1970	—	—	—	—	—	—
1971	—	—	—	—	—	—
1972	—	—	4.000x10 ⁻⁵	—	4.700x10 ⁻⁴	4.160x10 ⁻³
1973	2.340x10 ⁻⁶	—	3.000x10 ⁻³	4.990x10 ⁻⁶	—	4.000x10 ⁻³
1974	2.830x10 ⁻⁶	—	—	2.220x10 ⁻⁶	1.000x10 ⁻³	—
1975	6.060x10 ⁻⁶	—	5.000x10 ⁻³	3.900x10 ⁻⁶	2.000x10 ⁻³	—
1976	3.810x10 ⁻⁶	—	1.000x10 ⁻³	3.290x10 ⁻⁶	5.000x10 ⁻³	—
1977	2.580x10 ⁻⁶	—	1.150x10 ⁻⁴	1.910x10 ⁻⁶	6.820x10 ⁻⁴	5.600x10 ⁻⁵
1978	7.300x10 ⁻⁷	2.820x10 ⁻⁵	2.449x10 ⁻⁵	1.770x10 ⁻⁶	3.502x10 ⁻⁴	—
1979	7.000x10 ⁻⁷	8.900x10 ⁻⁵	2.000x10 ⁻⁶	6.400x10 ⁻⁷	2.820x10 ⁻⁴	1.180x10 ⁻⁴
1980	9.300x10 ⁻⁷	2.840x10 ⁻⁴	—	2.630x10 ⁻⁶	3.700x10 ⁻⁴	2.400x10 ⁻⁵
1981	3.998x10 ⁻⁶	9.900x10 ⁻⁴	2.680x10 ⁻⁴	3.620x10 ⁻⁶	1.515x10 ⁻³	—
1982	7.000x10 ⁻⁷	5.360x10 ⁻⁴	1.940x10 ⁻⁴	1.370x10 ⁻⁶	7.466x10 ⁻⁴	2.200x10 ⁻⁴
1983	7.200x10 ⁻⁷	1.213x10 ⁻³	—	3.540x10 ⁻⁶	8.362x10 ⁻⁴	1.320x10 ⁻⁴
1984	2.421x10 ⁻⁶	4.780x10 ⁻⁴	—	2.740x10 ⁻⁶	8.370x10 ⁻⁴	1.700x10 ⁻⁵
1985	1.160x10 ⁻⁶	1.720x10 ⁻⁴	—	1.642x10 ⁻⁶	6.886x10 ⁻³	—
1986	1.700x10 ⁻⁶	1.754x10 ⁻⁵	—	3.830x10 ⁻⁶	1.085x10 ⁻³	1.340x10 ⁻⁴
1987	6.400x10 ⁻⁷	—	1.200x10 ⁻⁵	4.405x10 ⁻⁶	2.641x10 ⁻⁴	1.310x10 ⁻⁴
1988	2.684x10 ⁻⁶	—	1.200x10 ⁻⁵	1.580x10 ⁻⁶	6.415x10 ⁻⁵	—
1989	4.541x10 ⁻⁶	—	4.300x10 ⁻⁵	3.697x10 ⁻⁶	6.277x10 ⁻⁶	7.990x10 ⁻⁴

** Based on gross alpha analyses
 — Not analysed

K Reactor

K Reactor was operational from 1954 until the 1988 shutdown. Reactor basin purges were discharged to Pen Branch and to two basins designated 904-65G and 904-88G. Because basin 904-65G had poor seepage characteristics, it received disassembly basin purges only in 1959 and 1965. Basin 904-88G was used to receive disassembly basin purges and occasional miscellaneous wastewater discharges from 1965 through 1989.

The total measured aqueous releases of alpha activity from K Reactor through 1989 were 9.8 millicuries to Pen Branch and 22 millicuries to the seepage and containment basins. Measured atmospheric releases of alpha emitting activity were 48 microcuries (4.8×10^{-5} Ci). Measured annual alpha releases by year from K Area are shown in Figure 3.5 (releases to atmosphere), Figure 3.6 (releases to stream), Figure 3.7 (releases to seepage basins), and in Table 3-1.

Figure 3.5 Alpha Releases to Atmosphere, K Area

Figure 3.6 Alpha Releases to Streams, K Area

Figure 3.7 Alpha Releases to Seepage Basins, K Area

L Reactor

L Reactor was operational from 1954 to 1968, when it was placed in standby. It was refurbished beginning in the early 1980s, restarted in 1985, and operated until the 1988 shutdown. To provide thermal mitigation of secondary cooling water from the restarted reactor's heat exchanger, L Lake was constructed in the early 1980s by damming Steel Creek. Therefore, during L Reactor's second operational period, secondary cooling water from the reactor heat exchanger was discharged to L Lake which drains into Steel Creek.

Reactor basin purges were discharged to Steel Creek, L Lake, and a seepage basin designated 904-64G. The 904-64G seepage basin was used intermittently

in 1958, 1959, 1961 to 1965, 1967 to 1969, and 1985 through 1989. The L Area Oil and Chemical Basin (904-83G) was used from 1961 to 1979 to receive wastewater containing various oils and chemicals from all of the reactor areas. It is adjacent to the 904-64G seepage basin.

The total measured aqueous releases of alpha activity from L Reactor through 1989 were 2.0 millicuries to Steel Creek and L Lake and 2.3 millicuries to the seepage basins. Measured atmospheric releases of alpha emitting activity were 10 microcuries (1.0×10^{-5} Ci). Measured annual alpha releases by year from L Area are shown in Figure 3.8 (releases to atmosphere), Figure 3.9 (releases to stream), Figure 3.10 (releases to seepage basins), and in Table 3-2.

Figure 3.8 Alpha Releases to Atmosphere, L Area

Figure 3.9 Alpha Releases To Streams, L Area

Figure 3.10 Alpha Releases To Seepage Basins, L Area

P Reactor

P Reactor was operational from 1954 until the 1988 shutdown. Reactor basin purges were discharged to Steel Creek and Par Pond during 1954 to 1956, 1969, and 1971 to 1977, and to three seepage basins during 1957 to 1968, 1970, and 1978 through 1989. The seepage basins have designations 904-61G, -62G, and -63G.

Reactor cooling water and miscellaneous effluents were discharged to Steel Creek until 1963; most of the cooling water later was diverted to Par Pond.

When L Lake was constructed in the mid-1980s, all aqueous effluents were diverted to Par Pond.

The total measured aqueous releases of alpha activity from P Reactor through 1989 was 17 millicuries to the Steel Creek/Par Pond system and 9.9 millicuries to the seepage basins. Measured atmospheric releases of alpha-emitting activity were 30.8 microcuries (3.08×10^{-5} Ci). Measured annual alpha releases by year from P Area are shown in Figure 3.11 (releases to atmosphere), Figure 3.12 (releases to stream), Figure 3.13 (releases to seepage basins), and in Table 3-2.

Figure 3.11 Alpha Releases To Atmosphere, P Area

Figure 3.12 Alpha Releases To Streams, P Area

Figure 3.13 Alpha Releases To Seepage Basins, P Area

Table 3-2. Gross Alpha Releases from L & P Areas by Year (Curies)

Year	100-L** <u>Atmos</u> Fig 3.8	100-L** <u>Basins</u> Fig 3.10	100-L** <u>Stream</u> Fig 3.9	100-P** <u>Atmos</u> Fig 3.11	100-P** <u>Basins</u> Fig 3.13	100-P** <u>Stream</u> Fig 3.12
1954	—	—	—	—	—	—
1955	—	—	—	—	—	—
1956	—	—	—	—	—	—
1957	—	—	—	—	—	—
1958	—	—	—	—	—	—
1959	—	—	—	—	—	—
1960	—	—	—	—	—	—
1961	—	—	—	—	—	—
1962	—	—	—	—	—	—
1963	—	—	—	—	—	—
1964	—	—	—	—	—	—
1965	—	—	—	—	—	—
1966	—	—	—	—	—	—
1967	—	—	—	—	—	—
1968	—	—	—	—	—	—
1969	—	—	—	—	—	—
1970	—	—	—	—	—	—
1971	—	—	—	—	—	—
1972	—	2.250x10 ⁻³	—	—	—	6.600x10 ⁻⁴
1973	—	—	—	1.588x10 ⁻⁶	—	—
1974	—	—	—	1.160x10 ⁻⁶	—	7.000x10 ⁻³
1975	—	—	—	4.180x10 ⁻⁶	—	5.000x10 ⁻³
1976	—	—	—	4.360x10 ⁻⁶	—	1.000x10 ⁻³
1977	—	3.200x10 ⁻⁵	—	2.400x10 ⁻⁶	—	1.469x10 ⁻³
1978	—	3.179x10 ⁻⁶	—	8.300x10 ⁻⁷	3.965x10 ⁻⁵	5.054x10 ⁻⁵
1979	—	—	—	4.000x10 ⁻⁷	3.170x10 ⁻⁴	—
1980	—	—	—	3.500x10 ⁻⁶	1.460x10 ⁻⁴	—
1981	—	—	9.500x10 ⁻⁵	1.070x10 ⁻⁷	6.070x10 ⁻⁴	7.000x10 ⁻⁵
1982	3.000x10 ⁻⁷	—	2.100x10 ⁻⁵	4.500x10 ⁻⁷	2.832x10 ⁻³	9.500x10 ⁻⁵
1983	9.600x10 ⁻⁷	—	5.900x10 ⁻⁵	4.000x10 ⁻⁷	1.495x10 ⁻³	1.360x10 ⁻⁴
1984	8.300x10 ⁻⁷	—	3.580x10 ⁻⁴	6.300x10 ⁻⁷	3.098x10 ⁻³	2.220x10 ⁻⁴
1985	6.400x10 ⁻⁷	—	2.230x10 ⁻⁴	1.602x10 ⁻⁶	8.610x10 ⁻⁴	—
1986	6.220x10 ⁻⁷	1.166x10 ⁻⁵	—	2.840x10 ⁻⁶	2.976x10 ⁻⁴	—
1987	7.140x10 ⁻⁷	8.651x10 ⁻⁶	4.100x10 ^{-5*}	2.770x10 ⁻⁶	1.753x10 ⁻⁴	—
1988	1.541x10 ⁻⁶	7.598x10 ⁻⁶	—	1.940x10 ⁻⁶	3.065x10 ⁻⁶	—
1989	4.427x10 ⁻⁶	1.162x10 ⁻⁷	1.260x10 ^{-3*}	3.785x10 ⁻⁶	3.500x10 ⁻⁵	1.110x10 ^{-3*}
—	Releases to Lakes					
**	Based on gross alpha analyses					
—	Not analysed					

R Reactor

R Reactor was the first operational production reactor at SRS. It operated from late 1953 until 1964, when it was placed on inactive status. Reactor basin water was discharged into Lower Three Runs Creek from 1954 to 1958, into Par Pond from 1958 to 1964, and into a seepage basin system from 1957 to 1964. R Reactor had six seepage basins, designated 904-103G, -104G, -57G, -58G, -59G, and -60G.

The original seepage basin, 904-103G, was used only from June to December 1957. Use of this basin was terminated due to surface outcropping and leakage into an abandoned sewer. The basin was backfilled in 1958. Basins 904-104G, -57G, -58G, and -59G were used from 1957 to 1960. These four basins were deactivated, backfilled, and covered with asphalt in 1960. Basin 904-60G was used from 1958 to 1964; it was backfilled in 1977.

Reactor heat exchanger cooling water and miscellaneous effluents were discharged to Lower Three Runs Creek from 1954 to 1958. After 1958, these effluents were discharged to Par Pond, which was constructed by the damming of Lower Three Runs Creek. Initially, R-Reactor effluents were discharged directly to Par Pond. Beginning in 1961, a canal and pond system that eventually drained into Par Pond (Figure 3.1) replaced direct discharges into Par Pond.

The only measured releases of alpha emitting activity from R Area were 0.30 Ci of ^{239}Pu discharged to the 100-R seepage basin system in 1957 following the failure of an experimental fuel element. Annual R-Area plutonium releases to seepage basins are shown in Figure 3.14, and in Table 3-3.

Figure 3.14. Plutonium Releases to Seepage Basins, R Area

Table 3-3. Alpha Releases from Misc Areas by Year (Curies)

Year	100-R Basin Fig 3.14*	400-D Stream Fig 3.26**	C Shops Basin Fig 3.27**	ETF Stream No Fig**
1954	—	—	—	—
1955	—	—	—	—
1956	—	—	—	—
1957	3.000x10 ⁻¹	—	—	—
1958	—	—	—	—
1959	—	—	—	—
1960	—	—	—	—
1961	—	—	—	—
1962	—	—	—	—
1963	—	—	—	—
1964	—	—	—	—
1965	—	—	—	—
1966	—	—	—	—
1967	—	—	—	—
1968	—	—	—	—
1969	—	—	—	—
1970	—	—	—	—
1971	—	—	—	—
1972	—	1.103x10 ⁻²	—	—
1973	—	2.640x10 ⁻³	—	—
1974	—	6.000x10 ⁻⁵	—	—
1975	—	8.900x10 ⁻⁵	—	—
1976	—	1.960x10 ⁻⁴	—	—
1977	—	4.100x10 ⁻⁵	—	—
1978	—	2.800x10 ⁻⁵	—	—
1979	—	2.100x10 ⁻⁵	—	—
1980	—	6.000x10 ⁻⁶	2.000x10 ⁻⁶	—
1981	—	1.860x10 ⁻⁴	1.000x10 ⁻⁶	—
1982	—	3.160x10 ⁻⁴	1.300x10 ⁻⁶	—
1983	—	5.260x10 ⁻⁴	4.730x10 ⁻⁴	—
1984	—	5.890x10 ⁻⁴	1.000x10 ⁻⁶	—
1985	—	7.440x10 ⁻⁴	—	—
1986	—	5.000x10 ⁻⁵	—	—
1987	—	—	—	—
1988	—	—	—	—
1989	—	1.720x10 ⁻⁴	—	1.820x10 ⁻⁴

* Based on Specific Radiochemical Analysis
 ** Based on Gross Alpha Analysis
 — Not analysed
 EPT Not Operational Until 1989

Separation and Liquid Waste Facilities

Two chemical separation facilities and their associated liquid-waste storage facilities are located near the center of the site (Figure 3.1). The separation areas are identified by letter designations F and H. In these areas, the products of interest from reactor irradiation are chemically separated and purified from waste products. The greatest releases of plutonium to the environment at SRS originated from these facilities.

Chemical Separation Facility Operations

The two chemical separation facilities were used to reprocess irradiated fuel and targets in canyon buildings (221-F and 221-H). Irradiated materials were dissolved and the products of interest were chemically separated and purified from waste fission and activation products. Occasional special campaigns for production of radionuclides such as ^{238}Pu and ^{252}Cf have occurred.

Beginning in late 1954, ^{239}Pu , ^{237}Np , and ^{238}U were generally recovered from irradiated ^{238}U targets in F Area, which used the Purex chemical extraction process. In H Area ^{239}Pu and ^{238}U were also recovered from ^{238}U targets by the Purex process during the period 1955-1959. The H-Area facility then was modified to recover ^{235}U from irradiated ^{235}U fuel. A further modification in 1963 allowed the recovery of ^{237}Np from the fuel. The HM process, which stood for H Modified Purex, was used for chemical extraction of the uranium. The Frames process was also used occasionally in H Area to recover ^{238}Pu and ^{237}Np targets. This process used ion exchange for separation and purification.

Waste facilities in or adjacent to the separation facilities were designed for liquid-waste handling. Depending on activity level, liquid wastes were stored in waste tanks or sent to either seepage basins or the Effluent Treatment Facility (ETF). In November 1988, the ETF became operational to treat the wastes that were previously sent to seepage basins. The seepage basins were closed in 1988 and as of 1990 were being decommissioned.

Pathways for Release

Unlike the reactor facilities, which have released alpha activity to the environment almost exclusively through aqueous effluents, the separation facilities

have released plutonium through both atmospheric and aqueous effluents.

In the separation processes, plutonium is present in process streams as nitrate salts in strong nitric acid solutions until it is precipitated and reduced to Pu metal. In the precipitation and reduction processes carried out in the B-Line facilities, some particulates are formed containing plutonium oxides. Work in the B-Line facilities is carried out in cabinets containing inert gas to minimize the risk of pyrophoric oxidation of plutonium metal. At the present time, exhaust gases from F- and H-Area B Lines are routed through high efficiency particulate (HEPA) filters then discharged to the atmosphere through a sandfilter and a 61-m stack. In the early days of operation, B-Line exhaust gases were vented through HEPA filters directly to atmosphere from short stacks on the roof of the canyon buildings.

Aqueous releases occurred when residual plutonium was present in high-level and low-level aqueous waste streams. Before high-level wastes were stored in tanks, an evaporation process was used to reduce volume. During evaporation, some spattering occurred carrying plutonium into the condensate from the evaporators. From startup of the separation facilities (1954 for F Area, 1955 for H Area) until 1988, this condensate was sent to the seepage basins. After 1988, the condensate was sent to the ETF. Occasional leaks in cooling water coils in separations process vessels released small quantities of radioactivity to Fourmile Branch. These leaks had the potential to include plutonium.

The disposition of various process waters from the separation facilities depended on the results of analyses of the water for radioactivity. Water was concentrated in evaporators prior to storage, sent to seepage basins or to the ETF, temporarily retained in basins, or released to site streams.

The major sources of wastewater previously discharged to the seepage basins were the overheads from the nitric acid recovery unit and the process evaporators in both F and H Areas. In H Area, water from the Resin Regeneration Facility and RBOF were also discharged to the Seepage Basin system. A flow sheet for liquid waste handling can be found in the reference Jacobsen et al., 1973. Because of the date of this reference, it does not show that the ETF has replaced the seepage basins.

Organic waste streams from the solvent extraction process may contain residual traces of plutonium. Spent organic solvent was sent to the SWDF for incineration.

Release Monitoring

Atmospheric releases of plutonium from separation facilities have been quantified since shortly after startup in 1954. Reprocessing of irradiated material began in F Canyon in November 1954. The first sampling period for plutonium in atmospheric effluents was December 14, 1954, to January 7, 1955. Continuous sampling was accomplished by passing a portion of stack air through a filter that trapped particulates containing plutonium. The filter was changed weekly and analyzed for plutonium.

Aqueous releases of plutonium to seepage basins have been quantified since startup. Several techniques were used to monitor stream releases. Process cooling water in F Area was monitored in-line for beta-gamma and alpha activity. In H Area, batches of process cooling water were monitored prior to release. When liquid effluents were released to seepage basins, they were continuously sampled. Samples were collected weekly and analyzed for plutonium content. Effluent Treatment Facility discharges were sampled prior to release to Upper Three Runs Creek.

History of Measured Releases

Gross alpha measurements were used to infer plutonium releases to plant streams by assuming all of the alpha activity to be ^{239}Pu . The large atmospheric releases occurred during startup of both facilities. The exceptions to this generalization were the 1969 releases from H Area when supporting tiles in the sand filter collapsed and the resulting loss of sand caused filtration efficiency to drop.

F-Area Separations

Aqueous waste from F Canyon initially was sent to waste tanks and a seepage basin designated 904-49G, also known as the Old F-Area Seepage Basin. The capacity of this basin proved to be inadequate, and it was abandoned in 1955 after three additional seepage basins were constructed. These basins, designated 904-41G, -42G, and -43G, were in use from 1955

until 1988 when wastewaters were diverted to the ETF. The latter basins were also known as F Seepage Basins 1, 2, and 3. The variations in releases to seepage basins are due to variations in normal operations and throughput.

Additionally, an earthen retention basin (281-3F) was used from 1955 to 1973 for the temporary containment of segregated cooling water that was potentially contaminated by process upsets. Use of a lined retention basin was implemented in 1973.

Releases to Seepage Basins

The total measured aqueous release of plutonium to the F-Area seepage basin system through 1988, when discharges to the seepage basins were terminated, was 7.21 Ci (5.66 Ci ^{239}Pu and 1.55 Ci ^{238}Pu). Measured annual releases of plutonium are shown in Figure 3.15 and Table 3-4. The maximum annual release, 0.934 Ci, occurred in 1969.

Migration of plutonium from the F-Area Basin system has been negligible. Migration is discussed further in Chapter 4.

Figure 3.15. Plutonium Releases to Seepage Basins, F Area

Table 3-4. Plutonium Releases from Separations Area by Year

Year	F Area Atmos Fig 3.16*	F Area Stream Fig 3.18**	F Area Basin Fig 3.15*	H Area Atmos Fig 3.20*	H Area Stream Fig 3.23**	H Area Basin Fig 3.19*
1954	—	2.400×10^{-3}	—	—	—	—
1955	2.221×10^0	4.510×10^{-2}	6.760×10^{-2}	4.410×10^{-1}	1.250×10^{-3}	4.650×10^{-2}
1956	2.800×10^{-2}	3.700×10^{-2}	2.656×10^{-1}	3.000×10^{-3}	5.100×10^{-3}	2.945×10^{-1}
1957	3.800×10^{-2}	2.200×10^{-3}	7.620×10^{-2}	4.750×10^{-3}	1.800×10^{-3}	3.620×10^{-2}
1958	1.900×10^{-2}	2.000×10^{-3}	3.640×10^{-1}	1.900×10^{-3}	9.000×10^{-3}	1.260×10^{-1}
1959	2.100×10^{-2}	2.000×10^{-3}	4.040×10^{-1}	2.850×10^{-3}	1.100×10^{-2}	1.280×10^{-1}
1960	7.032×10^{-2}	9.300×10^{-3}	2.028×10^{-1}	7.000×10^{-4}	7.500×10^{-3}	5.670×10^{-2}
1961	9.000×10^{-3}	7.000×10^{-3}	1.676×10^{-1}	2.800×10^{-3}	9.800×10^{-3}	1.145×10^{-1}
1962	6.160×10^{-3}	2.900×10^{-3}	2.828×10^{-1}	4.980×10^{-3}	8.600×10^{-3}	3.160×10^{-1}
1963	2.860×10^{-3}	5.000×10^{-3}	2.821×10^{-1}	6.400×10^{-4}	1.100×10^{-2}	9.128×10^{-2}
1964	2.220×10^{-3}	3.000×10^{-3}	9.030×10^{-2}	3.340×10^{-3}	1.200×10^{-2}	7.296×10^{-2}
1965	3.300×10^{-3}	2.000×10^{-3}	3.168×10^{-1}	1.320×10^{-2}	9.000×10^{-3}	2.894×10^{-1}
1966	2.400×10^{-3}	4.100×10^{-3}	6.224×10^{-1}	7.665×10^{-3}	1.000×10^{-2}	2.850×10^{-2}
1967	2.731×10^{-3}	1.030×10^{-2}	7.363×10^{-1}	7.613×10^{-3}	5.400×10^{-3}	3.280×10^{-2}
1968	2.021×10^{-3}	6.800×10^{-3}	3.320×10^{-1}	3.647×10^{-3}	5.100×10^{-3}	6.500×10^{-2}
1969	1.905×10^{-3}	4.500×10^{-3}	4.769×10^{-1}	5.844×10^{-2}	6.100×10^{-3}	1.353×10^{-2}
1970	3.330×10^{-3}	9.300×10^{-3}	2.950×10^{-1}	5.550×10^{-3}	7.800×10^{-3}	5.400×10^{-2}
1971	1.880×10^{-3}	1.180×10^{-2}	1.800×10^{-1}	6.310×10^{-3}	—	2.700×10^{-2}
1972	5.800×10^{-4}	5.460×10^{-3}	2.100×10^{-1}	3.210×10^{-3}	—	3.000×10^{-2}
1973	1.500×10^{-4}	8.780×10^{-3}	5.770×10^{-2}	1.300×10^{-3}	—	3.590×10^{-2}
1974	1.280×10^{-3}	5.430×10^{-3}	3.650×10^{-2}	1.660×10^{-3}	1.920×10^{-3}	4.070×10^{-2}
1975	1.200×10^{-4}	4.540×10^{-3}	1.630×10^{-2}	4.000×10^{-4}	1.770×10^{-3}	1.420×10^{-2}
1976	1.000×10^{-4}	2.350×10^{-3}	7.000×10^{-3}	1.400×10^{-4}	2.750×10^{-3}	3.000×10^{-3}
1977	1.040×10^{-4}	2.790×10^{-3}	1.200×10^{-2}	—	3.200×10^{-3}	2.000×10^{-3}
1978	2.260×10^{-4}	2.501×10^{-3}	7.000×10^{-3}	—	2.706×10^{-3}	1.000×10^{-2}
1979	2.450×10^{-4}	4.500×10^{-3}	1.600×10^{-2}	1.540×10^{-4}	3.680×10^{-3}	—
1980	3.980×10^{-4}	3.120×10^{-3}	1.000×10^{-2}	8.370×10^{-4}	2.480×10^{-3}	6.000×10^{-3}
1981	7.710×10^{-4}	5.790×10^{-3}	4.108×10^{-2}	2.027×10^{-3}	9.400×10^{-4}	1.191×10^{-2}
1982	1.052×10^{-3}	6.200×10^{-3}	2.096×10^{-2}	6.520×10^{-4}	1.960×10^{-3}	6.281×10^{-3}
1983	4.990×10^{-4}	4.450×10^{-3}	7.538×10^{-3}	2.210×10^{-4}	1.370×10^{-3}	2.384×10^{-3}
1984	3.500×10^{-4}	2.914×10^{-2}	1.800×10^{-2}	1.100×10^{-4}	7.310×10^{-4}	—
1985	4.230×10^{-4}	5.137×10^{-3}	2.000×10^{-2}	7.400×10^{-5}	7.700×10^{-4}	—
1986	2.070×10^{-4}	7.193×10^{-3}	7.460×10^{-3}	4.500×10^{-5}	9.350×10^{-4}	6.762×10^{-4}
1987	2.310×10^{-4}	3.338×10^{-3}	2.351×10^{-3}	4.200×10^{-5}	1.447×10^{-2}	2.255×10^{-4}
1988	2.860×10^{-4}	4.669×10^{-3}	1.312×10^{-3}	4.500×10^{-5}	6.490×10^{-4}	7.077×10^{-5}
1989	6.060×10^{-4}	8.386×10^{-3}	—	7.300×10^{-5}	1.957×10^{-3}	—

* Based on Specific Radiochemical Analysis
 ** Based on Gross Alpha Analysis

Releases to Atmosphere

The total measured atmospheric release of plutonium from F Area through 1989 was approximately 2.46 Ci. Measured annual releases of plutonium are shown in Figure 3.16, and Table 3-4. The maximum annual release, 2.22 Ci, occurred in 1955. The release in 1955 was due to startup problems with the filtration system.

Cooling water for portions of the F-Area separation process line was pumped from deep wells and discharged to Fourmile Branch after use. This water was used either in the "once through" or "segregated" cooling water systems used to control temperatures in the separation process. Because of the possibility of cooling coil leakage, these cooling water streams had the potential to contain measurable amounts of radioactivity. Cooling coils were used in the head-end dissolvers; hence, a mixture of many fission and activation products was available as a potential contaminant of the cooling system. Uranium was a predominant chemical constituent of this mixture, but the majority of the alpha activity was due to the transuranic activation products.

In order to minimize release of radioactivity into the cooling system when a leak did occur, positive pressure was maintained in the cooling coils in all process vessels. After the water was used, it was monitored and released into Fourmile Branch. If activity levels in the water exceeded discharge limits, the contaminated water was held in a plastic lined "diversion" basin and sent to the seepage basins until 1988. Since 1988, contaminated water was transferred to either the H-Area waste tank farm or it was sent to the ETF for cleaning.

Radioactivity levels were measured slightly downstream from the F-Area cooling system release point. Specific radiochemical analyses for uranium/plutonium were not made on water discharged from the segregated cooling water system. Because the cooling water used in the process is pumped from deep wells drawing from the Middendorf aquifer (as is the drinking water for F Area), a portion of the activity measured at the outfall is present before use due to trace amounts of natural radioactivity in the well water. The natural background activity of the cooling water is not measured, but can be inferred by examining the activity measured in drinking water samples. The data on gross alpha activity found in F-Area drinking water samples in 1989 is summarized in Table 3-5, and is typical of values obtained in prior years.

Figure 3.16. Plutonium Releases to Atmosphere, F Area

An estimate of the average gross alpha concentration in cooling water can be obtained by dividing the annual release (Ci) by the annual total flow (liters) listed in Cummins, Hetrick, and Martin (1991). The resulting range of values obtained for the period 1954-1988 was 0.87 pCi/L to 19.61 pCi/L with an average of 3.18 ± 3.94 pCi/L. This average is not significantly different from the average drinking water concentration in F Area in 1989. This suggests that the gross alpha activity discharged in F-Area cooling water is primarily the naturally occurring radioactivity found in the well water from which the cooling water is derived.

Table 3-5. Gross Alpha Activity in F-Area Drinking Water, 1989

Sample Loc	No. Samples	Max Conc pCi/L	Min Conc pCi/L	Annual Average, pCi/L
221-F	13	12.4	0.78	4.40 ± 3.37*
701-1F	4	7.47	1.90	3.85 ± 2.47*
704-F	5	5.09	1.47	3.26 ± 1.29*
772-F	5	7.09	1.24	4.41 ± 2.60*
Overall Average				3.98 ± 5.08†

* The error value listed in the standard deviation (1σ error)
† The error value listed was calculated using the propagation of errors method ($\sigma_a^2 = \sigma_1^2 + \sigma_2^2 + \dots + \sigma_n^2$)

A plot of gross alpha activity in the drinking and cooling water from F Area confirms that the two are equivalent except during periods of known cooling coil leaks or process incidents as shown in Figure 3.17 and Table 3-5.

Annual releases to Fourmile Branch are shown graphically in Figure 3.18. As noted above, the uncorrected "unidentified alpha" levels must be used to estimate the possible plutonium releases to the stream. No corrections are made to the "unidentified alpha" data since in most cases the drinking water data agrees with the release data. For the following described incidents or process equipment failures, isotopic analyses would have been helpful but were not performed. The plutonium releases were certainly much smaller than the "unidentified alpha" measurements. The high releases in 1955 and 1956 were associated with evaporator coil leaks. Alpha spectrometry measurements on a few samples taken in late 1955 showed that the predominant activity was due to ^{238}U , but the presence of plutonium cannot be ruled out. The 1984 release resulted from runoff to the storm sewer system from the uranium recovery facilities (A Line). The 1984 release was probably predominantly depleted uranium.

Figure 3.17. Gross Alpha Activity in Drinking Water and Cooling Water, 200-F

Figure 3.18. Gross Alpha Releases to Streams, F Area

H-Area Separations

H Canyon has been operational since July 1955. In addition to the general chemical separation operations, H Area includes the Effluent Treatment Facility and Receiving Basin for Offsite Fuels (RBOF), with an adjacent regeneration facility for resins from other areas. Certain offsite noncommercial irradiated fuels are stored underwater in RBOF as are some SRS fuel elements that have failed. This facility is equipped to disassemble and cut fuel for inspection.

Aqueous waste from H Canyon was sent to waste tanks and the four seepage basins designated 904-44G, -45G, -46G, and -56G. The basins, which also were known as H Seepage Basins 1, 2, 3, and 4, were in use from 1955 until 1988 when wastewaters were diverted to the ETF. Basin 904-46G has been inactive since 1962.

In addition, an earthen retention basin, designated 281-3H, was used from 1955 to 1973 to temporarily contain water that was potentially contaminated by process upsets. Use of a lined retention basin was implemented in 1973.

Releases to Seepage Basins

The total measured aqueous release of plutonium to the H-Area seepage basin system through 1988, when discharges to the seepage basins were terminated, was 4.36 Ci (2.40 Ci ^{238}Pu and 1.96 Ci ^{239}Pu). Measured annual releases are shown in Figure 3.19, and Table 3.5. The maximum annual release, 0.650 Ci, occurred in 1969. The variations in releases to seepage basins are due to variations in normal operations and throughput.

The F and H Effluent Treatment Facility became operational in November 1988 to receive aqueous wastes previously discharged to the separation area seepage basins.

Figure 3.19. Plutonium Releases to Seepage Basins, H Area

Releases to Atmosphere

The total measured atmospheric release of plutonium from H Area to the atmosphere through 1989 was 1.26 Ci (0.68 Ci ^{238}Pu and 0.58 Ci ^{239}Pu). Measured annual releases are shown in Figure 3.20, and Table 3-4. The maximum annual release, about 0.62 Ci (0.56 Ci ^{238}Pu and 0.06 Ci ^{239}Pu), occurred in 1969 when supporting tiles in the sand filter collapsed. Loss of sand from the filter resulted in reduced filtration efficiency.

Figure 3.20. Plutonium Releases to Atmosphere, H Area

Releases to Streams

As with F Area, portions of the H-Area process equipment are cooled with water derived from deep wells. After use, the cooling water is monitored and discharged into Fourmile Branch. Figure 3.21 shows gross alpha releases from H-Area based on unmodified "unidentified alpha" data. Once again the comparison between effluent monitoring data is in fairly close agreement with the drinking water data. Drinking water data for 1989 is shown in the Table 3.6 The range of values of annual average concentrations obtained from release data was 0.77-10.75 pCi/L, with an average of 4.05 ± 2.84 pCi/L for the period 1955-1988 (H Area did not begin operations until 1955).

A plot of gross alpha activity in the drinking water and cooling water from H Area confirms that the two are equivalent except during periods of known cooling coil leaks as shown in Figure 3.22.

Table 3-6. Gross Alpha Activity in H-Area Drinking Water

Sample Loc	No. Samples	Max Conc pCi/L	Min Conc pCi/L	Annual Average, pCi/L
221-H	14	5.74	0.94	$3.04 \pm 1.53^*$
701-1H	5	3.77	1.91	$2.68 \pm 0.73^*$
704-H	5	4.48	1.02	$2.91 \pm 1.41^*$
Overall Average				$2.88 \pm 2.20^\dagger$

* The error value listed in the standard deviation (1σ error)
 $\dagger$ The error value listed was calculated using the propagation of errors method ($\sigma_a^2 = \sigma_1^2 + \sigma_2^2 + \dots \sigma_n^2$)

Figure 3.21 Alpha Releases to Streams, H Area

Effluent Treatment Facility

Operation of the ETF was not begun until 1989, so only one year's release data is available for this report. No specific radiochemical analyses for plutonium were performed on the ETF releases, only gross alpha. Gross alpha releases for the ETF in 1989 were 0.18 mCi as shown in Table 3-8.

Waste Tank Farms

Recovery of all the plutonium from Purex process streams is not possible, so a small fraction of the plutonium is transferred to the F-Area waste storage tanks, along with the fission products and induced activities. No attempt is made to recover the plutonium produced in the fuel tubes when enriched uranium is recovered using the HM process in H Area. Thus the H-Area waste storage tanks contain more plutonium than the F-Area waste storage tanks. The combined total plutonium inventory in waste storage tanks is shown in Table 3-7

Table 3-7. Plutonium in SRS High-Level Waste Storage Tanks

Isotope	Inventory, Curies
^{238}Pu	1.60×10^6
^{239}Pu	2.20×10^4
^{240}Pu	1.04×10^4
^{241}Pu	1.42×10^6
^{242}Pu	1.70×10^1

Decay Corrected to December 31, 1990 (DOE, 1991)

Figure 3.22. Gross Alpha Activity in Drinking Water and Cooling Water, H-Area

Radioactivity has leaked into the ground from certain waste tanks. In 1960, H-Area Tank 16 leaked about 100 liters of waste into the surrounding soil (Poe, 1974). In 1961, F-Area Tank 8 leaked about 6,000 liters of waste onto the soil (Odum, 1976). Plutonium was not included in the reported inventory of

radionuclides in either tank and contaminated soil was not analyzed for Pu. Plutonium and the other actinides present in the high-level waste are almost exclusively in the sludge in the waste tanks (DOE, 1991), so the likelihood of significant plutonium releases to the soil in either of these incidents is small.

Table 3-8. Alpha Releases from Misc Areas by Year (Curies)

<u>Year</u>	<u>100-R Basin Fig 3.14*</u>	<u>400-D Stream Fig 3.26**</u>	<u>C Shops Basin Fig 3.27**</u>	<u>ETF Stream No Fig**</u>
1954	—	—	—	—
1955	—	—	—	—
1956	—	—	—	—
1957	3.000x10 ⁻¹	—	—	—
1958	—	—	—	—
1959	—	—	—	—
1960	—	—	—	—
1961	—	—	—	—
1962	—	—	—	—
1963	—	—	—	—
1964	—	—	—	—
1965	—	—	—	—
1966	—	—	—	—
1967	—	—	—	—
1968	—	—	—	—
1969	—	—	—	—
1970	—	—	—	—
1971	—	—	—	—
1972	—	1.103x10 ⁻²	—	—
1973	—	2.640x10 ⁻³	—	—
1974	—	6.000x10 ⁻⁵	—	—
1975	—	8.900x10 ⁻⁵	—	—
1976	—	1.960x10 ⁻⁴	—	—
1977	—	4.100x10 ⁻⁵	—	—
1978	—	2.800x10 ⁻⁵	—	—
1979	—	2.100x10 ⁻⁵	—	—
1980	—	6.000x10 ⁻⁶	2.000x10 ⁻⁶	—
1981	—	1.860x10 ⁻⁴	1.000x10 ⁻⁶	—
1982	—	3.160x10 ⁻⁴	1.300x10 ⁻⁵	—
1983	—	5.260x10 ⁻⁴	4.730x10 ⁻⁴	—
1984	—	5.890x10 ⁻⁴	1.000x10 ⁻⁶	—
1985	—	7.440x10 ⁻⁴	—	—
1986	—	5.000x10 ⁻⁵	—	—
1987	—	—	—	—
1988	—	—	—	—
1989	—	1.720x10 ⁻⁴	—	1.820x10 ⁻⁴

* Based on Specific Radiochemical Analysis
 ** Based on Gross Alpha Analysis
 EFT Not Operational Until 1989

Solid Waste Disposal Facility

The Solid Waste Disposal Facility (formerly called the Burial Grounds) are storage sites for disposal of radioactive solid wastes. The first burial ground, designated 643-E, was used from 1952 to 1972. The new burial ground, designated 643-7E is adjacent to the original and has been in use since 1969.

Neptunium, plutonium, and all the other artificially created elements with atomic numbers greater than 92 are lumped into a category of elements referred to as TRU (TRansUranic) materials. Because waste materials containing TRU elements are generally more hazardous than wastes containing uranium or fission products, special procedures and techniques are used in their storage in the Solid Waste Storage Facility (Burial Grounds). The current waste storage definitions and practices are outlined below and were instituted in 1986 (SAIC, 1988).

Non-TRU Waste - solid waste containing alpha contamination 10 nCi/g and non-alpha waste such as low-activity and intermediate-activity beta-gamma waste, is buried in earthen trenches with a cover of at least four feet of soil.

Bulky TRU Wastes - solid waste, such as canyon equipment, may contain TRU nuclides but is so intensely contaminated with gamma emitters that is not feasible to monitor the alpha content. This waste is buried directly in soil on top of a six foot backfill to keep the equipment above water that might accumulate in the bottom of the trench.

Intermediate-Activity TRU Waste - solid waste containing 10 nCi/g but 0.5 Ci/container, held in 90-mil thick polyethylene containers inside galvanized steel drums stored on a concrete surface pad. The maximum amount of alpha activity is 0.5 Ci per drum. Containers are normally 55-gallon drums, but boxes may be used to contain larger items.

The TRU pads had been in operation since 1972. Until 1985, the intermediate- level TRU waste drums were covered with a polyethylene bag and the TRU pad was covered with four feet of soil as the pad filled. The practice changed in 1985 in anticipation of movement of TRU wastes to the WIPP facility in New Mexico.

High-Activity TRU Waste - solid waste containing 0.5 Ci/container. It is held in 90-mil thick polyethylene containers inside galvanized steel drums placed into secondary concrete culverts. These containers are placed on a concrete pad. Each drum

can contain 0.5 Ci, but concentrations and quantities of radionuclides are limited by heat load and criticality criteria. As was the case with the intermediate-level TRU wastes above, the storage pads had been in use since 1972, but were covered with 4 feet of soil when the pad was filled with waste containers. High-level TRU wastes are slated to be shipped to the WIPP facility in New Mexico.

Bulky TRU Waste - equipment from TRU facilities that will not fit into 55-gallon drums includes large filters, glovebox panels, and other large items. These are put into carbon steel boxes and stored on the pad. HEPA filters from TRU facilities are packaged in polyethylene boxes. The polyethylene boxes are placed into secondary concrete culverts.

The quantity of plutonium stored in the SWDF as solid waste is summarized in the Table 3-9.

Table 3-9. Solid Plutonium Wastes in the SWDF

Isotope	Total Curies*
^{238}Pu	471,194.0
^{239}Pu	9,168.0
$^{242}\text{Pu}(<60\%)$	19,543.0
$^{242}\text{Pu}(>60\%)$	0.5

*Inventory corrected for decay through 12/31/86 (SAIC, 1988)

Liquid waste that potentially contained trace quantities plutonium was also stored at the SWDF. Degraded solvent from the separations areas was burned at the SWDF in the early years of operations. Beginning in 1975, it was stored in steel tanks at the Burial Ground pending later incineration. As of 1987, 655 of the 755 cubic meters of degraded solvent stored in the tanks since 1975 has been incinerated (Jagge et al., 1987).

Savannah River Technology Center

SRTC provided research and development support for the production facilities of SRS. Laboratory facilities handled radioactivity that ranged from environmental levels to highly radioactive material that was manipulated in shielded cells. Liquid radioactive wastes were accumulated in holding tanks pending shipment to F Area for treatment and disposition. Trade wastes from nonradioactive drains were routed to Tim's Branch.

Monitoring of liquid wastes discharged to plant streams from SRTC began in 1970. Analysis was for gross alpha activity only; no specific radiochemical analyses for plutonium were made. During the period 1970 through 1989, a total of 11.4 mCi of gross alpha activity was released to Tim's Branch. The maximum yearly release, 3.5 mCi, occurred in 1970. Release data are shown in Figure 3.23.

Figure 3.23. Gross Alpha Releases to Streams, SRTC

From 1954 to 1983, a seepage basin system was used for low activity wastes. The first two seepage basins, both designated 904-53G, were placed into service in 1954. The last two, 904-54G and -55G, were added in 1958 and 1960. Gross alpha measurements on wastes released to SRTC seepage basins were made from the beginning of use of the basins in 1954 and continued until 1977. The total recorded alpha activity released to the SRTC basins from 1954 through 1982 was 4.16 Ci. The maximum release year was 1970 when 1.14 Ci of alpha emitting activity was released. Specific radiochemical analysis for plutonium in the seepage basin waste streams were not initiated until 1974. Recorded release of plutonium to the SRTC basins totaled 11.8 mCi for the period 1974 through 1982 (8.9 mCi ^{238}Pu , 2.9 mCi ^{239}Pu). The basins were

Figure 3.24. Alpha Releases to Basins, SRTC

taken out of service in 1983. A significant amount of the total alpha activity released to the SRTC basins (3.69 Ci out of total of 4.16 Ci) occurred between 1968 and 1973 when SRTC was engaged in research on and recovery of ^{244}Cm and other transplutonic materials, such as ^{252}Cf , but specific analyses for ^{244}Cm were not begun until 1973, so release of plutonium to the basins during the maximum release period cannot be ruled out. Seepage basin release data are shown graphically in Figure 3.24, and Table 3-10. Experimental studies using high levels of radioactivity were performed in shielded cells. Air vented from the shielded cells passed through a carbon bed to remove iodine, then through HEPA filters before exhausting through a 50-meter stack. In the early years of operation, a caustic scrubber was also used to purify air from the shielded cells. After the 1970s, a sand filter was used before air was vented to the stack.

Air exhausted from other parts of the laboratory was passed through HEPA filters, and released through 30-meter stacks. If air radioactivity exceeded specific limits, the air was diverted to the sand filter before being exhausted from the stack.

Table 3-10. Plutonium Releases from SRTC by Year (Curies)

Year	SRTC Atmos Fig 3.25*	SRTC Stream Fig 3.23**	SRTC Basin Fig 3.24**	SRTC Basin Fig 3.24*
1954	—	—	2.800x10 ⁻⁴	—
1955	—	—	2.470x10 ⁻²	—
1956	—	—	7.871x10 ⁻²	—
1957	—	—	3.562x10 ⁻²	—
1958	—	—	4.358x10 ⁻²	—
1959	—	—	1.912x10 ⁻²	—
1960	—	—	3.000x10 ⁻²	—
1961	—	—	2.900x10 ⁻²	—
1962	—	—	4.000x10 ⁻²	—
1963	—	—	2.870x10 ⁻²	—
1964	—	—	3.210x10 ⁻²	—
1965	—	—	3.900x10 ⁻²	—
1966	—	—	1.700x10 ⁻²	—
1967	—	—	2.940x10 ⁻²	—
1968	—	—	2.587x10 ⁻¹	—
1969	—	—	9.440x10 ⁻¹	—
1970	3.100x10 ⁻⁴	3.500x10 ⁻³	1.136x10 ⁰	—
1971	1.600x10 ⁻⁴	—	9.794x10 ⁻¹	—
1972	—	—	7.180x10 ⁻²	—
1973	—	—	3.014x10 ⁻¹	—
1974	—	1.260x10 ⁻³	2.210x10 ⁻²	5.400x10 ⁻⁴
1975	—	2.204x10 ⁻³	2.677x10 ⁻³	1.078x10 ⁻³
1976	—	1.014x10 ⁻³	5.060x10 ⁻⁴	3.100x10 ⁻⁵
1977	—	6.310x10 ⁻⁴	3.299x10 ⁻⁵	1.241x10 ⁻⁵
1978	—	4.410x10 ⁻⁴	—	9.237x10 ⁻⁵
1979	—	5.000x10 ⁻⁴	—	8.219x10 ⁻⁵
1980	—	1.440x10 ⁻⁴	6.170x10 ⁻⁴	1.020x10 ⁻⁴
1981	—	2.860x10 ⁻⁴	—	8.150x10 ⁻⁴
1982	—	2.370x10 ⁻⁴	8.370x10 ⁻⁴	1.940x10 ⁻⁴
1983	—	7.000x10 ⁻⁵	—	—
1984	—	1.000x10 ⁻⁴	—	—
1985	—	1.300x10 ⁻⁴	—	—
1986	—	1.570x10 ⁻⁴	—	—
1987	—	2.600x10 ⁻⁴	—	—
1988	—	2.060x10 ⁻⁴	—	—
1989	—	2.710x10 ⁻⁴	—	—

* Based on Specific Radiochemical Analysis
 ** Based on Gross Alpha Analysis

The total recorded atmospheric release of gross alpha activity from SRTC through 1989 was 2.62 mCi. The total recorded releases of plutonium from 1970 through 1989 were 0.47 mCi. The data are shown graphically in Figure 3.25, and in Table 3-10.

Figure 3.25. Alpha Releases to Atmosphere, SRTC

Other Facilities

All documented plutonium releases from SRS facilities were listed in the previous sections. A number of other facilities handled materials containing plutonium. These were the test reactors, the Heavy Water Rework Facility, and the heat exchanger repair facility in Central Shops.

No monitoring of alpha activity was done for any of the test reactors. These facilities were operated at essentially zero power level, and the risk of release of plutonium from the elements being tested was minimal.

The Heavy Water Rework Facility, located in D Area, consisted of four distillation towers and associated equipment for removal of ordinary water that accumulated in the heavy water moderator used in the reactors. Leaks in the system were vented through a 21-meter stack. The aqueous waste stream was sent to Beaver Dam Creek. The predominant radioactivity associated with this facility was tritium. There was a potential for traces of plutonium to be present in the moderator, as was described in the section on reactor facilities. No specific monitoring for plutonium is performed because of the low potential for a release. Gross alpha releases were monitored, however, beginning in 1972. The measured total alpha activity releases from 1972

through 1989 were 16.7 mCi. Measured releases of alpha activity from D Area are shown in Figure 3.26 and Table 3-8

Figure 3.26. Alpha Releases to Streams, D Area

Central Shops at the SRS is responsible for fabrication and repair of equipment that is used in the separation and reactor areas of the site. Though equipment is decontaminated before it is sent to Central Shops, some radioactive material occasionally is present and normally is removed during cleaning operations prior to repair of the equipment. The contamination is transferred along with other liquid waste streams to a seepage basin. The yearly releases for alpha activity are shown in Figure 3.27 and Table 3-8. The total alpha activity release for this location is 0.49 mCi.

Figure 3.27. Alpha Releases to Seepage Basins, Central Shops

References

Cummins, C.L., C.S. Hetrick, and D.K. Martin, 1991, "Radioactive Releases at the Savannah River Site 1954-1989", WSRC-RP-91-684, Westinghouse Savannah River Company, Aiken, SC.

Jacobsen, W.R., W.L. Marter, D.A. Orth, and C.P. Ross, 1973, "Control and Treatment of Radioactive Liquid Waste Effluents at the Savannah River Plant", DP-1349, E. I. du Pont de Nemours and Company, Aiken, SC.

Odum, J.V., 1976, "Soil Contamination Adjacent to Waste Tank 8", DPSPU-76 -11-4, E. I. du Pont de Nemours and Company, Aiken, SC.

Poe, W.L., 1974, "Leakage from Waste Tank 16", DP-1358, E. I. du Pont de Nemours and Company, Aiken, SC.

SAIC, Science Applications International Corporation, 1988. "Safety Analysis - 200 Area Savannah River Plant Burial Ground Operations", DPSTSA-200 -10, Prepared for E. I. du Pont de Nemours & Co. Savannah River Laboratory, Aiken SC.

Taylor, R.W., 1989, "Effluent Treatment Facility Emissions Monitoring", DPST-89-309, E.I. du Pont de Nemours and Company, Aiken,

SC.U. S. Department of Energy, 1991. "Integrated Data Base for 1991: U. S. Spent Fuel and Radioactive Waste Inventories, Projections, and Characteristics", DOE/RW-0006, Rev 7, Prepared by Oak Ridge National Laboratory, Oak Ridge, TN.

This page intentionally left blank

Chapter 4. Plutonium Concentration and Transport Mechanisms

There are a number of plutonium isotopes found in the environment. The primary source of plutonium in the global environment is the atmospheric fallout from nuclear testing. In this chapter, we will address the transport of three isotopes, ^{238}Pu , ^{239}Pu , and ^{240}Pu . These are the only plutonium isotopes in the SRS environment that are the result of SRS activities. Because of the difficulty in separately measuring ^{239}Pu and ^{240}Pu , and the similarity in the source of these isotopes at SRS, it is common to measure their undifferentiated sum. In the following sections, plutonium identified as ^{238}Pu is only that isotope, while plutonium identified as ^{239}Pu is the sum of the ^{239}Pu and ^{240}Pu plutonium measured, unless specifically identified as one isotope or the other.

In some sense, the identification of the isotope is not important to a discussion of transport since the isotopes are chemically and physically very similar and are transported through the environment by the same processes. However, the distribution of the two isotopic types, ^{238}Pu and $^{239,240}\text{Pu}$ differs at SRS because of their source. Most of the atmospheric ^{238}Pu releases are from H Area while the majority of ^{239}Pu releases are from F Area. In order to determine how the plutonium released from SRS affects the surrounding environment and population, it is necessary to determine transport of SRS releases and their interaction with the plutonium background from other sources.

This page intentionally left blank.

The Global Fallout Background

The global fallout of ^{239}Pu from atmospheric nuclear testing is the major source of background in the vicinity of SRS. The fallout at any location varies with latitude (Perkins and Thomas, 1980) and other factors related to elevation, local topography, and vegetation type (Pinder and Paine, 1980). The ^{239}Pu atmospheric testing fallout has been shown to be closely correlated with ^{137}Cs fallout from the same source. In another volume of this series (Carlton et al., 1992) the ^{137}Cs air concentration measured at the SRS sampling stations outside the Site perimeter has been shown to be dominated by atmospheric testing fallout. Figure 4.1 shows that the ^{239}Pu concentration at these same stations is closely correlated to ^{137}Cs concentration. The data presented by Perkins and Thomas (1980) suggest that the ^{137}Cs concentration is 10,000 times greater than the ^{239}Pu . The best fit of the SRS outer ring (100 mile) stations indicates a factor of about 5,000.

From the close relationship between ^{137}Cs and ^{239}Pu air concentrations, we conclude that the ^{239}Pu concentration at this outer ring is a good approximation of the ^{239}Pu background. Since there are estimates of ^{137}Cs air concentration available for years when the ^{239}Pu concentration was not measured, it is possible to estimate the ^{239}Pu concentration for periods when measurements are not available. This will be used later to estimate the relative contribution of ^{239}Pu from the SRS and background sources.

Figure 4.1. A Comparison of Atmospheric Concentrations of ^{137}Cs and ^{239}Pu at Four Most Distant Sampling Locations

The ^{238}Pu background is somewhat more difficult to estimate. There are two sources of ^{238}Pu background. ^{238}Pu is found in the fallout from atmospheric nuclear testing; however, the primary source of ^{238}Pu was the burn-up of a ^{238}Pu power supply in a space satellite that failed to orbit in 1964. As shown in Figure 4.2, the average annual ratio of $^{238}\text{Pu}/^{239}\text{Pu}$ from atmospheric testing was about 0.01 before the burn-up of the SNAP (Satellite Nuclear Auxiliary Power) power source. After 1964, the ratio increased at two Northern Hemisphere stations to 0.4 before decreasing to around 0.1 by 1971. The ratio was similar at SRS most distant set of sampling stations when measurements were first made in 1974, and did not change greatly through 1981 when the measurements stopped. When measurement were begun again in 1986, the ratio at the SRS stations was around 0.6. The higher ratios after 1986 suggest that the fraction of ^{238}Pu fallout has fallen in the local ^{238}Pu air concentration. This is likely caused by the depletion of ^{238}Pu fallout in the stratosphere and the larger fraction (but not a larger absolute amount) from SRS releases, which have a higher ratio of $^{238}\text{Pu}/^{239}\text{Pu}$. From this evidence, it appears that the average concentration of ^{238}Pu at the four most distant SRS sampling stations may be a reasonable estimate of the ^{238}Pu background for periods before 1981.

Figure 4.2. Comparison of Fallout Plutonium Isotope Ratios to SRS Ratios at the Most Distant Sampling Stations

In addition to air concentration, the deposition of plutonium into open containers is measured. The deposition is a combination of plutonium which settles into the container (dry deposition) and plutonium that enters in rainwater (wet deposition). The plutonium from dry deposition will be washed into the container by the water of later rainfall. This water is collected from the gages and analyzed to get the total deposition. Since the deposited plutonium comes from the air above the gage, it is reasonable to assume that the concentration of plutonium in the gage should be proportional to the concentration in the air (Figure 4.3). The proportionality constant is called a deposition velocity because it has the units of distance/time. The average deposition velocity can be calculated for each of the plutonium isotopes for which air concentration and deposition was measured at the SRS outer ring sampling stations. The deposition velocity for ^{239}Pu is 0.0018 m/s, which is a reasonable value, similar to that estimated for ^{129}I at SRS (Murphy, 1991). The deposition velocity for ^{238}Pu estimated in the same way is 0.0036 m/s for the ^{238}Pu . While slightly higher, this value is within reason for deposition of a radionuclide associated with atmospheric particles.

Therefore, it appears that, during the years in which measurements are available, the background concentration and deposition of ^{238}Pu and ^{239}Pu can be estimated from the SRS sampling stations. Furthermore, an estimate of ^{137}Cs can be used to estimate these background values for periods when

Figure 4.3. Comparison of Deposition and Air Concentration of ^{239}Pu

plutonium measurements are not available. Cumulative deposition to the surface from atmospheric testing and the SNAP burn-up have been estimated in Perkins and Thomas (1980). For the SRS latitude, the cumulative soil background is estimated to be .037 mCi/km² ^{238}Pu and 2.0 mCi/km² ^{239}Pu .

Atmospheric Concentrations and Transport

The objective of this section is to use the data collected by the SRS monitoring network to determine the influence of SRS releases on plutonium in the SRS environment. There are three ways that this can be accomplished. The pattern of annual average plutonium content in various parts of the SRS environment can be compared to the annual releases from SRS. If peaks in the environmental concentration coincide with peaks in SRS releases, it is reasonable to assume that the source of the environmental plutonium is SRS.

The second method for detecting the SRS influence is to look at the spatial pattern of the plutonium in the environment in the vicinity of the SRS. If the concentration in the environment is greatest near the plutonium facilities and decreases with distance from these facilities, then it is reasonable to suggest that some part of the environmental plutonium is from the facilities. The third method is to look at the ratio of

the two plutonium isotopes. The ratio for SRS releases is greater than the ratio in fallout. If the ratio in the environment in the vicinity of the SRS is greater than that from fallout, then it is likely that there is some contribution from SRS releases. Furthermore, if the ratio increases as the plutonium-handling facilities are approached, then both the spatial pattern and the ratio support a SRS contribution to the environmental plutonium concentration.

The existence of confirmation of an SRS contribution to the environmental plutonium concentration, in itself, does not indicate whether the contribution of SRS releases is a significant environmental hazard. It only demonstrates our ability to monitor for this element. If we can demonstrate that we can adequately monitor plutonium in the environment, then we can confirm the estimates that are made of the potential health hazard.

Three types of monitoring data are available to investigate the patterns and isotopic composition of atmospheric plutonium. Plutonium air concentrations were measured from 1974 to 1981 and again from 1986 through 1989. Deposition of plutonium to open rain gages was measured from 1974 to 1981 and less extensively from 1986 to 1989. Plutonium in the upper eight centimeters of soil has been measured every year since 1974. The plutonium content of soil is a good measure of the integrated deposition.

Atmospheric Concentration

Sources and SRS Concentrations

Figure 4.4 shows the temporal pattern of the SRS ^{239}Pu releases and average air concentration at the SRS perimeter sampling stations. The pattern of fallout is approximately proportional to the fission yield of nuclear test detonations. SRS releases are in curies of ^{239}Pu . Air concentration measurements are available since 1974. The air concentration estimated from measured ^{137}Cs measurements is also shown. The agreement between ^{239}Pu measurements and ^{137}Cs measurements suggests there is a significant contribution of fallout plutonium to the ^{239}Pu

Figure 4.4. Comparison of ^{239}Pu Air Concentration and Sources

concentration. The naturally occurring isotope beryllium-7, produced in the stratosphere, is also plotted as an indicator of annual variation in the mixing between the upper atmosphere and the earth's surface. The ^{239}Pu concentrations does appear to peak during years when the ^7Be concentration is highest. The relationship of ^{239}Pu concentration and both ^{137}Cs and ^7Be indicates that during the period of measurements, 1974-1989, there is a significant contribution of fallout ^{239}Pu but little to indicate the size of SRS contribution.

Figure 4.5 shows the temporal pattern for SRS ^{238}Pu releases and air concentrations. Once again, the air concentration was measured only after 1974. During this period, the temporal pattern of air concentration is similar to that for ^{239}Pu . This suggests that there is a significant contribution of fallout ^{238}Pu . However, the relationship between ^{238}Pu and ^{137}Cs is not as strong.

In both cases, the analysis of temporal variation does not show evidence of the effect of SRS releases but does indicate a relationship to fallout. Unfortunately, the periods of the largest SRS releases are not included in the record of air concentration.

Figure 4.5. Comparison of ^{238}Pu Air Concentration and Sources

Figure 4.6. ^{239}Pu Air Concentration Versus Distance from SRS Source

Concentrations and Distance from SRS Sources

Figures 4.6 and 4.7 illustrate the relationship between ^{239}Pu and ^{238}Pu average annual concentration and distance from the primary source of each isotope (98% of ^{238}Pu releases are from H Area and 81% of ^{239}Pu releases are from F Area). These measurements, for the years between 1986 and 1989, show a clear decrease in air concentration with distance from the source of the SRS releases. This is also evident in the data for most years between 1974 and 1981, even though measurements were made at fewer locations.

Figure 4.7. ^{238}Pu Air Concentration Versus Distance from SRS Source

The lines on the illustration show the slope of the decrease in concentration as distance from the source increases. Theory indicates this slope should be close to -1.0 if the decrease is caused solely by the dilution of the release in a larger volume of air as it moves away from the source. As shown by Murphy (1991), near the source, the slope is decreased by the existence of a background level unrelated to distance and by the increase of vertical mixing as the plume moves away from the source. In the case of tritium (Murphy et al. 1991), the slope was -0.76 over a five-year period. In both isotopes of plutonium, the slopes are somewhat greater than for tritium, indicating that the concentration is decreasing faster than accounted for by dilution. The most likely cause of the additional decrease is deposition of some of the plutonium onto the surface of vegetation and the soil.

Figure 4.8. shows the distribution of slopes for the years when air measurements were made. All the measurements have negative slopes. The slopes for ^{238}Pu are somewhat more negative than those for ^{239}Pu . This can be explained by the lower background for ^{238}Pu in the measurements. From these measurements, it is clear that there is a measurable influence of SRS releases on plutonium concentration in the vicinity of the releases. Notice that both figures show much less slope between the most distant measurement points, which are at the site perimeter, and the outermost measurement stations. This indicates that while there is clear evidence of SRS releases on the basis of air concentrations, it is less clear how large this influence is outside the site perimeter.

Figure 4.8. Distribution of Slopes for Plutonium Isotopes Air Concentration Versus Distance

Isotopic Ratios of Atmospheric Concentrations

Figure 4.9 illustrates the spatial variation in the isotopic composition of plutonium around the SRS. The period between 1974 and 1981, and between 1986 and 1989 are plotted separately. There is a clear decrease in the ^{238}Pu contribution to the plutonium concentration with distance from the major source of ^{238}Pu (H Area). At the outermost sampling stations, the mean ^{238}Pu fraction approaches that of atmospheric fallout. This is both confirmation that the contribution of SRS to the atmospheric plutonium concentration extends beyond the site boundary, and an indication that the influence of SRS decreases significantly as distance from SRS increases. The decrease in the ^{238}Pu ratio during the period from 1986-1989 is not as clear as it was during the earlier period, although the measurements certainly indicate an effect of the SRS. The lack of a smooth relationship with distance from the source is probably caused by the larger relative effect of measurement and sampling error caused by the lower plutonium concentrations found in the atmosphere during this period. The trend toward a larger fraction of ^{238}Pu during the later period may, as it suggests, be an indication of a larger proportion of plutonium from SRS sources. This is the result of proportionately less fallout plutonium in the later period, even though SRS releases were also less during that period.

Figure 4.9. The Fraction of ^{238}Pu in Atmospheric Plutonium as a Function of Distance from this SRS Source

Deposition Rate

Atmospheric plutonium is associated with suspended particles. The size of the particles has a significant influence on the deposition of plutonium on vegetation and other surfaces. Large particles, with high settling velocities, fall from the air under the influence of gravity. The larger the particle, the greater the rate of deposition. Small particles, with diameters less than one micrometer, are kept suspended by turbulence in the air. Smaller particles are deposited by impaction on surfaces, such as vegetation. The efficiency of penetration through the fluid boundary layer of a surface is very low for particles about one micrometer in diameter. Particles of very small diameter actually deposit on surfaces somewhat more rapidly because of "Brownian" diffusion. This leads to minimum deposition of particles with diameters near one micrometer.

Studies of plutonium bearing particles in SRS stack releases indicate that the particles are not pure plutonium or plutonium oxide, but particles of other composition which contain some plutonium (Sanders and Boni, 1980). The distribution of plutonium activity by particle size has been measured in the stack and at the ground at two locations at different distances from the release point (Gay and Watts, 1981). In the stack (Carlson et al., 1983) and at the ground surface location nearest the stack, the distribution had peaks at the largest- and smallest-size particles measured. The distribution at the furthest distance from the stack did not have the peak at the large-diameter end of the distribution (Figure 4.10).

Figure 4.10. Distribution of ^{238}Pu Activity as a Function of Particle Diameter

The most probable cause of the change in the distribution shape is deposition of the larger particles between the stack location and the second location. Any deposition rate for plutonium must be interpreted in terms of an integrated average of the deposition rate of the different size of particles carrying the plutonium.

As shown in Figure 4.3, deposition is correlated with air concentration. This is reasonable because the deposited plutonium comes from the air above the deposition collector. Because of this relationship between air concentration and deposition, one would also expect a relationship between the amount of deposited plutonium and distance from the SRS source. This is the case for the deposition data collected between 1974 and 1981 when data was collected at a sufficient number of stations to allow analysis. The distribution of deposition versus distance slopes is shown in Figure 4.11. The magnitudes of the slopes are very much like those shown previously for air concentration. The ^{238}Pu fraction of the deposition also is very much like that found for air concentration with one exception (Figure 4.12). The ^{238}Pu fraction at the most distant set of sampling locations is greater than expected. There is no explanation for the discrepancy in the ^{238}Pu fraction at the most distant sampling location; however, this fraction is based on only three measurements because the stations were not sampled in every year. In summary, the deposition measurements are consistent with the air concentration measurements for the same period. The

Figure 4.11. Distribution of Slope of Plutonium Deposition as a Function of the Distance from the SRS Release Point

SRS is the source of some fraction of the plutonium deposited around the Site. As was the case in the air concentration measurements, the ^{238}Pu fraction suggests that the contribution of the SRS, compared to the contribution due to fallout, decreases with distance from the site perimeter.

Soil Concentration

Soil Concentration and Distance from SRS Sources

The amount of ^{238}Pu and ^{239}Pu in the top 8 cm of soil has been measured at the same sampling sites since 1974. The soil concentration is a measure of the cumulative deposition over the period before each measurement. Since the great majority of ^{239}Pu was released in a single year, 1955, and the majority of ^{238}Pu was released in 1969, the soil deposition actually is almost entirely a measure of deposition during the years of the greatest releases. The annual measurements, all made after the majority of the releases, are actually a succession of samples of the deposition from these releases. Therefore, the measurements do not show the steady accumulation of plutonium isotopes in the soil that would be expected if a steady accumulation had taken place over the period of measurement.

Pinder and Paine (1980) have analyzed the source of variability for soil plutonium samples and concluded

Figure 4.12. Fraction of ^{238}Pu in Deposition Versus the Distance from the SRS Source

that most of the variability is due to distance from the source with additional variation due to topography and other local phenomena. The plots of soil concentrations versus distance from the primary source of each isotope, illustrated in Figures 4.13 and 4.14, clearly show the effect of distance from the source. The slopes of these plots are in the range expected from the air concentration and deposition data presented previously, though it should be remembered that the slopes are characteristic of the years of greatest release of plutonium-years when no air concentration or deposition measurements were made.

Figure 4.13. ^{239}Pu Deposition in Soil Versus Distance from the SRS Source

Figure 4.14. ^{238}Pu Deposition in Soil Versus Distance from SRS Source Soil Isotopic Ratios

Figure 4.15. ^{238}Pu Fraction in Soil as a Function of Distance from SRS Sources

Figure 4.15 shows the ^{238}Pu fraction in soil plutonium. The same pattern is present as for air concentration and deposition. The following analysis is presented to estimate the contribution of SRS plutonium at the site perimeter.

Summary of Air Concentration and Deposition

Comparison with Earlier Work

In the early 1970s, the DOE Office of Health and Environmental Research funded a transuranic program to investigate the dispersion and environmental cycling of plutonium and the other transuranic elements in the SRS environment (Corey et al. 1981). Other aspects of this research will be summarized in this report. The results of studies of soil deposition, deposition to rain gages, deposition to sticky paper, and air concentration indicated a slope of decreasing concentration with distance from the source of -1.3 (Horton and Gay 1982). This slope is somewhat higher than the slopes shown here for air concentration, deposition, and soil concentration. Part of the difference can be explained by the subtraction of the plutonium background from the measurements in Horton and Gay before the analysis of the slope. Subtraction of the the background determined in the earlier part of this section will move the slopes closer to the value of -1.3.

However, slopes measured near the facilities seem to be greater than those measured at greater distances, even after correction for background. This can be explained if there is a fraction of the plutonium

associated with heavier particles, which are deposited near the source and a fraction associated with lighter particles, which would dominate the slope of the curve further from the source. This conjecture, already corroborated by the particle-size distributions shown in Figure 4.10, can be further tested with a computational model of plutonium dispersion and deposition.

Simple Model Estimates of the Dispersion and Fate of SRS Plutonium

The model used in this analysis assumes that the radial average plutonium isotope concentration decreases at the same rate as measured tritium concentration (see Murphy et al., 1991) when there is no deposition. The dispersion will produce a slope of a somewhat greater rate when the deposition is present. The total dispersion is computed as the sum of two curves. The first representing a fraction of large-size particles which result in a concentration depletion curve with a slope of -1.3. The fraction of large-size particles was estimated to be 0.2, based on the data shown in Figure 4.10. The rest of the particles are assumed to be small and disperse with the same concentration-versus-distance slope as measured tritium air concentration (about -0.76). The composite curve has a slope of about 1.0 over the distance from 5.0 to 100 km, which is similar to the curves for soil concentration shown previously. The relationship between releases and air concentration

represented by the curves can be used to estimate the air concentration of plutonium isotopes at a given distance from the SRS release point for periods when measurements are not available. This has been done to determine the average and annual variations in the effect of the SRS on the plutonium air concentration at the site perimeter.

The contribution of fallout plutonium has also been estimated. The ^{239}Pu fallout is estimated from the air concentration at the furthest stations from the SRS when this is available. If there were no measurements available, the fallout was estimated from the relationship to ^{137}Cs fallout at the same stations (See Hayes et al., 1992 for atmospheric concentration estimates near the SRS). The ^{238}Pu fallout was estimated from the fraction of ^{238}Pu in fallout. The fraction was assumed to be 0.01 before the SNAP burn-up. After 1964, the ^{238}Pu fraction was derived from the ratios in Figure 4.2.

The results are shown in Figures 4.16 and 4.17. The air concentration of ^{239}Pu normally is dominated by fallout. There are two years when the SRS contribution is a little greater than the fallout, both after the highest fallout period has passed. The only year when SRS ^{239}Pu was the major contributor to the atmospheric plutonium contribution was in 1955. The integrated contribution of the SRS to the ^{239}Pu at the site perimeter is 56%. This compares to 68% based on the soil isotopic composition.

Figure 4.16. Influence of Fallout and SRS Releases on ^{239}Pu Air Concentration at the Site Perimeter

Figure 4.17. Comparison of Influence of Fallout and SRS ^{238}Pu on Air Concentration at the Site Perimeter

The SRS releases less ^{238}Pu than ^{239}Pu . However, the amount of ^{238}Pu fallout is also lower. For this reason, the contribution of ^{238}Pu from SRS sources is almost always greater than fallout. The SRS contribution being about 60% of the total ^{238}Pu in the air at the site perimeter over the entire period of SRS ^{238}Pu releases. This agrees well with an analysis based on isotopic ratios in the soil.

In addition to predicting isotopic ratios that agree with measured values, the model predicts that 30% of the plutonium released from SRS sources is deposited on the site. This agrees reasonably well with the integrated soil concentration as determined by integration of the deposition curve (Carlson et al., 1983).

The result of the analyses presented in this section indicate:

- the SRS sampling network has been capable of monitoring the effect of SRS releases on the concentration of plutonium isotopes released by SRS.
- SRS has been a significant contributor to plutonium in the atmospheric environment at the site perimeter.
- Most of the SRS contribution is attributed to the single years immediately after startup of SRS plutonium facilities. For the other years of SRS operation, the contribution of SRS to atmospheric plutonium has been equal to or less than fallout. The SRS contribution to the total plutonium air concentration is less than 10% at the four most distant sampling locations (an average distance of 155 km) for the years 1974-81 and 1986-89.
- The combination of SRS and fallout plutonium to the atmosphere is small compared to fallout from other radionuclides, such as ^{137}Cs , or from naturally occurring atmospheric radionuclides, such as ^7Be .

Surface Water Transport

Surface Waters on the Savannah River Site

Plutonium transported by surface waters on the SRS, originated from three sources

- fallout deposited
- atmospheric releases from SRS operations
- direct releases to streams

Fallout deposited on the Savannah River watershed has been estimated at 55 Ci with a $^{238}\text{Pu}/^{239,240}\text{Pu}$ ratio of 0.04 to 0.18 (Hayes, 1980). Approximately 1.5 Ci was deposited directly on water impoundments and 1.2 Ci was deposited within the boundaries of the SRS. *Atmospheric plutonium releases from SRS operations*, including unidentified alpha, have totaled about 3.8 Ci and *direct releases to streams* have totaled 0.6 Ci (Cummins, 1991). Several streams have received cooling water from reactors and process water from separations facilities, with about 90% of the liquid releases occurring in the separation areas (F & H). A small fraction of the plutonium entering the streams was transported directly to the Savannah River while most was deposited in stream beds, flood plains, or ponds and slowly released offsite. There is a strong correlation in the behavior

of plutonium and cesium (Holloway, 1981) which will be utilized in subsequent sections to estimate the transport of plutonium when the concentrations are too small to be easily measured.

Lower Three Runs Creek

Lower Three Runs Creek has the second largest drainage area of streams on the SRS. Both P and R reactors have discharged effluents to the Lower Three Runs system. On the main SRS site, a large impoundment, Par Pond (2,600 acres), was constructed in 1958 to provide recirculating cooling water through P and R reactors. Several smaller ponds were built between the reactors and Par Pond to provide additional cooling for reactor cooling water before it entered Par Pond. The average natural flow rate of Lower Three Runs Creek at the Par Pond dam is 1 m³/sec. From the Par Pond dam, the creek flows 38 kilometers to the Savannah River.

Upper Three Runs Creek

Upper Three Runs Creek is the largest on site with a watershed of 540 km², a natural flow rate of 7 m³/sec, and a length of 40 km. Effluents are received from M Area and SRTC, and since 1988, the Effluent Treatment Facility in H Area has been releasing

treated water. There have been no significant releases of plutonium to Upper Three Runs Creek.

Steel Creek

Steel Creek is 18 km in length and has a watershed of 90 km². The natural flow rate is 1 m³/sec, but was as high as 22 m³/sec when both P and L reactors discharged cooling water to Steel Creek in the early 1960s. P Reactor cooling water was diverted to Par Pond in 1964 and L Reactor was shut down in 1968, then restarted in 1985. P Reactor disassembly basin water continued to flow to Steel Creek. L Lake was built in 1985 to provide cooling for L Reactor discharges. Steel Creek travels about 3 km through the Savannah River swamp before entering the Savannah River (Murphy, 1991).

Fourmile Branch

Fourmile Branch has a watershed of 57 km², is approximately 24 km long and has a natural flow of 0.14 m³/sec. It receives effluent from F and H Areas and, until 1985, received cooling water from C Reactor. Almost 90% of the plutonium and unidentified alpha released to streams from site operations has flowed into Fourmile Branch; for this reason, it has received more study. Concentrations of plutonium in the water ranged up to 0.223 pCi/L while the same samples contained unidentified alpha up to 1.340 pCi/L (Holloway, 1981). The concentration of ²³⁸Pu exceeded the concentration of

^{239,240}Pu at all measuring points, just the reverse of fallout Pu ratios. This confirms that most of the plutonium came from SRS operations.

Pen Branch

Pen Branch has a watershed of 55 km², is approximately 24 km long and has a natural flow of 0.2 m³/sec. Once it reaches the Savannah River swamp, the flow path becomes relatively undefined as it flows through the swamp parallel to the Savannah River for about 8 km before entering Steel Creek. Pen Branch receives cooling water from K Reactor.

Site Stream Summary

Sediment samples taken from site streams (Alberts, 1986) have been analyzed for plutonium and isotopic ratios determined (See Table 4-1). Fourmile Branch, Steel Creek, and Pen Branch have elevated ratios of ²³⁸Pu/^{239,240}Pu relative to fallout, indicating that these streams have received plutonium effluent from site operations. Both Upper Three Runs and Lower Three Runs show ratios similar to that of the Savannah River upstream of the SRS, indicating little contribution from site operations. Note that the ratios do not indicate the quantity of plutonium released from SRS operations, nor do they distinguish between a liquid release and an atmospheric release which is subsequently deposited on a stream drainage area.

Table 4-1. Sediment Sample Plutonium Isotopic Ratios (Alberts, 1986)

Sampling Location	²³⁸ Pu / ^{239,240} Pu
Upper Three Runs (Treadway Bridge)	0.141
Fourmile Branch (Road A)	3.29
Steel Creek (Road A)	2.64
Pen Branch (Road A)	1.84
Lower Three Runs (Road S-3-17)	0.167
Savannah River (Jackson)	0.189

Table 4-2 contains an extensive listing of stream sediment data and indicates that the deposition of plutonium is not uniform in the sediments. In addition, many of the samples are near or below the lower limit of detection, reflecting the small quantity of plutonium released as a liquid effluent. Prior to 1982, each data point represents one analysis of composited sediment samples from each location. From 1982 on, duplicate and triplicate analyses were performed.

Savannah River

The Savannah River forms most of the border between Georgia and South Carolina and drains approximately 25,900 km² in eastern Georgia and western South Carolina. The flow rate averages about 285 m³/sec at Augusta and increases to 340 m³/sec downriver near Clyo, GA. Water from the Savannah River is used at two water treatment plants, Beaufort-Jasper and Port Wentworth.

Table 4-2. Sediment Concentration (pCi/gm dry weight of ²³⁸Pu and ^{239,240}Pu in Creeks (Gladden 1985).

Year	Upper Three Runs Mouth	Four Mile Branch Swamp	Pen Branch Swamp	Steel Creek Swamp	Lower Three Runs Mouth
²³⁸ Pu					
1977	0.003	0.24	0.003	0.132	0.007
1978	0.006	0.12	0.02	0.09	0.04
1979	<.001	0.02	0.022	0.006	0.001
1980	0.004	0.085	0.02	0.004	0.002
1981	0.001	0.003	<.001	NA	0.001
1982	NA	NA	NA	NA	NA
1983	0.002	0.08	0.003	0.03	0.005
^{239,240} Pu					
1977	0.014	0.092	0.004	0.04	0.011
1978	0.02	0.07	0.04	0.05	0.04
1979	<.001	0.012	0.021	0.046	0.003
1980	0.029	0.035	0.044	<.001	0.008
1981	0.004	0.002	<.001	NA	0.003
1982	NA	NA	NA	NA	NA
1983	0.007	0.11	0.02	0.04	0.001
NA=no analysis					

Table 4-3. Sediment Concentrations (pCi/gm dry weight) of Plutonium in the Savannah River Floodplain.

Year	Upstream of SRS at Demiers Landing	Downstream of SRS at US 301
²³⁸ Pu		
1977	<.0006	0.0035
1978	<.0004	<.001
1979	<.0002	<.001
1980	0.003	NA
1981	<.001	0.001
1982	NA	0.005
1983	0.004	0.001
^{239,240} Pu		
1977	0.001	0.0015
1978	0.006	0.002
1979	0.002	0.001
1980	0.005	NA
1981	0.002	0.001
1982	NA	0.008
1983	NA	0.004
NA = no analysis		

Table 4-3 shows plutonium concentrations in Savannah River floodplain sediments both upriver and downriver from the SRS (Gladden, 1985). In all cases, the measured values are near the lower limit of detection and there is little indication of SRS contribution.

Savannah River Estuary

Several researchers have studied the levels of plutonium in the sediments of the Savannah River estuary. One of the earliest studies (Hayes, 1975) compared the levels of plutonium in the Savannah River estuary with levels in the estuaries of the Neuse and Newport rivers. Although levels in the Newport estuary, which received plutonium only from fallout,

were three times higher than the Savannah or Neuse, the elevated ratio of ²³⁸Pu to ^{239,240}Pu in the Savannah indicated that SRS releases were a contributor to plutonium in the estuary. Another study (Goldberg, 1979) argued that the elevated levels of ²³⁸Pu in the Savannah River estuary resulted from atmospheric releases, rather than liquid releases, at the Savannah River Site.

Hayes (1987) determined that fallout was the primary source of plutonium in the estuarine sediments, but that a slightly elevated ²³⁸Pu to ^{239,240}Pu ratio could represent a small contribution from SRS operations. Olsen (1989) found that fallout plutonium greatly exceeded SRS plutonium in the estuary and accounted for 75% of the total plutonium as far as 30 km upriver from the river mouth.

Groundwater Concentrations and Transport

SRS Groundwater System

The Savannah River Site lies on the Atlantic Coastal Plain about 20 miles southeast of the edge of the Piedmont Physiographic Province. The Coastal Plain is underlain by a seaward dipping wedge of sediments that thins and overlaps the crystalline rocks of the Piedmont. Early investigations of the hydrogeology at the site, such as Siple (1967),

established three geologic and hydrogeologic systems or provinces on the site: 1) crystalline basement rocks composed of metamorphic and intrusive igneous rocks; 2) well-indurated Triassic-aged sediments in the Dunbarton Basin; and 3) the overlapping, weakly consolidated Cretaceous to Recent coastal plain sediments.

The crystalline basement rocks have very low permeabilities. Water is stored primarily in the

fractures and joints in the rocks. The permeability of the Triassic rocks is also likely to be relative low. Two test wells drilled into the Triassic rocks showed that the water in these rocks are geopressed and that the hydraulic heads of the waters are above land surface. The origin of the overpressuring is uncertain but has been ascribed to osmotic pressure across the overlying impermeable confining units (Marine, 1974).

Both the crystalline basement rocks and the Triassic rocks are overlain by varying thicknesses of weathering residue containing degraded minerals and clay. Overlying these old soils is a depositional blanket of indurated, poorly sorted clayey sediments of the Cape Fear Formation (Bledsoe, 1988). This unit and the residual soils hydraulically separate and isolate the younger, sedimentary materials from the Triassic sediments and the crystalline basement rocks.

The third hydrogeologic system is the Cretaceous and younger sedimentary rocks of the Coastal Plain sediments. The sediments were largely deposited in shallow marine and fluvial environments (Gohn, 1988). The thickness of the sedimentary units

increases toward the southeast across the site. At the northwest boundary, the sedimentary section is about 700 feet thick and it is about 1,400 feet thick at the southeastern boundary (Fallaw, 1990). As more detailed information has become available the stratigraphic names applied to the various units have been modified based on the predilections of successive investigators. The principal aquifers on the site have frequently been named after the principal formations, for example, the Barnwell Formation and the Barnwell Aquifer. As stratigraphic names have changed, the names of the aquifers have also been changed as a result.

Figure 4.18 compares some of the changes that occurred in the hydrostratigraphic nomenclature since the mid-1960s. The currently recommended nomenclature (Aadland et al., 1992) takes into account the progressive thickening of the aquifers across the site and the effectiveness of the confining units that separate the aquifer units. The recent changes avoid tying the aquifer nomenclature to the lithostratigraphic names and extend five existing hydrostratigraphic nomenclature from surrounding regions into the SRS.

Figure 4.18. Stratigraphic and Hydrostratigraphic Nomenclature Used on the Savannah River Site

At the base of the coastal plain sediments is an aquitard composed of residual soils of the Cape Fear Formation. Overlying this confining unit are two aquifers in Cretaceous sands (Aquifer IA and IB). These sands are generally considered to be prolific water producers and are generally the source of water for water-supply wells on the site. They are separated from each other by the relatively less permeable beds that make up the Black Creek Formation.

The Tertiary aquifers are separated from the underlying Cretaceous aquifer units by confining beds of the Black Mingo Group, especially the Ellenton Formation. On the Northwestern corner of site, the separation is not as effective as in the southern portion.

In the Southeastern area, the Tertiary section can be divided into two separate aquifers, Aquifer Unit IIA (Formerly called the "Congaree Aquifer") and Aquifer Unit IIB (frequently referred to as the "Barnwell Aquifer" or "Watertable Aquifer"). The aquitard or confining beds that separate these two units is a glauconitic clayey zone of the McBean Formation that is locally referred to as the "green clay." This clay pinches out and becomes more sandy toward the northwest.

In some areas of the site, it is necessary to modify the hydrostratigraphic nomenclature due to local changes in lithologies and topography. For example, in some portions of the site an aquitard unit referred to as the "tan clay" subdivides the uppermost aquifer into two separate zones. In southern portions of the site, the "tan clay" unit is thin or sporadic and does not form a consistent aquitard.

The level of the water table is controlled primarily by local topographic features. The surface of the Atlantic Coastal Plain at the site is a relatively flat plateau (the Aiken Plateau) that has been dissected by stream erosion. The incision of the streams has left relatively isolated, flat-lying surfaces separated by 90 to 125 feet deep stream valleys. The depth to the water table below land surface varies from 0 feet, when it outcrops in the stream valleys or wetlands, to a depth of 125 feet below the remnant plateau areas. The depth of the water table is usually controlled by the elevation of the nearest tributary stream of the Savannah River. At many localities on site the water table is situated in Tertiary sediments of low water-producing capabilities and perched water tables exist sporadically across the site.

The direction of groundwater flow at any locality may change or even reverse as one goes into successively deeper aquifers. The aquifers in the

Tertiary sediments receive local recharge and flow is generally toward nearby stream valleys. In general, flow at the water table is toward minor tributaries and deeper Tertiary aquifers flow toward major tributaries of the Savannah River. The deepest aquifers at SRS, Aquifer System I, receive recharge in the outcrop areas of the Cretaceous sediments to the north of the site. Groundwater flow beneath the site in System I is toward the Savannah River.

Over much of the site, the potentiometric surface, or hydraulic "head" of the deeper aquifers in the Cretaceous sediments is higher than that of the overlying Tertiary aquifer (Christensen and Gordon, 1983). This head reversal is an important characteristic of many of the waste disposal areas and has provided protection to the deeper aquifers on the site from downward transport of contaminants. Figure 4.19 outlines the areas where there is an upward hydraulic gradient across the confining units near the Cretaceous-Tertiary boundary.

Figure 4.19. Hydraulic Head Differences Across Confining Units Near the Cretaceous/Tertiary Boundary

Plutonium in SRS Groundwater

General

Groundwater monitoring on the Savannah River Site is performed by the Environmental Monitoring Section of Environmental Protection Department using a system of wells that have been installed around each of the facilities and especially around each of the waste disposal areas or seepage basins. The majority of these wells are sampled on a quarterly basis and the results reported in the Annual Savannah River Site Environmental Reports.

Alpha Monitoring

Monitoring of the SRS groundwater for radioactive contaminants began in the early 1950s. Gross alpha, nonvolatile beta, total radium, and tritium are routinely monitored as the primary indicators of radioactivity in groundwater. Plutonium activity is measured on samples from areas where plutonium is known to have been discharged or buried.

The areas that are specifically monitored for plutonium included several sites in the general separation area, the TNX area, and the A-Area seepage basins.

General Separations Area

Analyses have been performed primarily by alpha spectroscopy to determine ^{238}Pu , $^{239/240}\text{Pu}$, and ^{242}Pu . Alpha spectroscopy was also used to determine ^{241}Pu during the period of 1989 to 1991. The ^{241}Pu results using the alpha spectroscopy method were very unsatisfactory due to the low-level of precision of the technique. The Environmental Monitoring Section switched to the more reliable beta spectroscopy methods for ^{241}Pu analysis; however, there are insufficient data currently available to access the extent of ^{241}Pu migration in groundwater.

Solid Waste Disposal Facility

At the Savannah River Site, solid radioactive waste is stored at the centrally located SWDF in the General Separations Area (Figure 4.20). The original 76 acre burial site, the "Old Burial Grounds", is designated as area 643-E and operated between 1953 and 1972. A second area, a 119 acre site, designated 643-7E, was opened to receive radioactive solid wastes. Chapter 3 of this document discusses the history and inventory of plutonium at this site.

The newer SWDF area sits on a water table divide. The groundwater beneath about half of the 643-7E area and of the Old Burial Grounds, flows southward toward Fourmile Branch. Groundwater from beneath the northern half of the 643-7E area flows toward Upper Three Runs.

Figure 4.20. Location Map of Waste Disposal Sites in the General Separations Area

In the Old Burial Ground, site 643-E, plutonium contaminated waste were routinely disposed of in waste trenches until 1965. After 1965, retrievable concrete containers were used for the burial of alpha emitting wastes. The estimated inventory of plutonium in the SWDF is shown in Table 3-9.

Table 4-4. Comparison of Plutonium Concentration in Burial Ground Monitoring Wells between 1980 and 1986

(After Ryan, 1983 and McIntyre and Wilhite, 1988)

Well ID	Gross Alpha 1980 ¹	²³⁸ Pu (pCi/L) 1980 ¹	²³⁸ Pu (pCi/L) 1986 ²	²³⁸ Pu (pCi/L) 1980 ¹	²³⁸ Pu (pCi/L) 1986 ²
A-3	(0)	11	0.1	0	0.04
A-9	(1)	0	—	0	—
C-1	(0)	4	0.16	2	0.03
C-3	(1)	2	0.34	0	0.16
C-15	(8)	2	0.21	2	12.1
C-17	(12)	0	0.66	0	64.5
B-13	(1)	0	0.07	0	1.02
E-17	(0)	0	—	0	—
G-21	(33)	17	—	4	—
I-9	(0)	2	0.27	0	0.07
I-13	(18)	2	0.47	0	0.01
I-17	(3)	2	0.08	0	0.01

0 = Less Than Detection Limit
 — = Well Not Sampled
¹ From Ryan, 1983
² From McIntyre and Wilhite, 1988

Groundwater beneath the site has been monitored since 1956 (Ryan, 1983) by a series of wells within the SWDF and by perimeter wells surrounding the enclosed area. Two areas of this site have had groundwater contamination by Plutonium as a result of activity incidental to plant operations. According to Ryan (1983), approximately 200 gallons of contaminated TBP-Kerosine were released to the groundwater in 1971 when a dry monitoring well was mistaken for a solvent storage tank header. To clean-up the groundwater, about 250,000 gallons of water were pumped from a nearby contaminated well to H-Area seepage basins.

A second potential source of plutonium in groundwater beneath the Old Burial Grounds was a decontamination station that was operated in the

northwestern corner of the site. Phosphate detergents and complexing agents such as EDTA were used to wash and decontaminate burial ground equipment (Ryan, 1983).

Follow up studies by Ryan (1983) and by McIntyre and Wilhite (1988) have shown continuing evidence of minor amounts of plutonium in the groundwater beneath the SWDF (see Table 4-4). Elevated levels of ²³⁹Pu in monitoring wells C-15 and C-17 were attributed to the contaminated solvent spill by McIntyre and Wilhite (1988). Samples from wells near the decontamination station (wells A-3 and C-1) show decreased levels of ²³⁸Pu in 1986 compared to samples taken in 1980.

General Separations Area Seepage Basins

During the period of 1954 to 1988, seepage basins were used on the Savannah River Site for the disposal of waste water that contained low concentration levels of chemicals and radionuclides. Several of these basins were located in the General Separations area near the F- and H-Area facilities (see Figure 4.20). The first seepage basin on site was constructed in 1954 just north of the F Area; however, the seepage rate was inadequate to handle the increasing volume of wastewater coming from the F-Area facilities. Three additional basins were constructed south of F Area and received effluent during the period of 1954 to 1988.

F Area Seepage Basins

Water infiltrating from the F-Area seepage basins encounters a perched water table 15 to 25 feet below the surface and then a normal water table at a depth of 60 to 65 feet below the land surface. Flow of water at the watertable aquifer is toward Four Mile Branch at a rate estimated to be about 0.5 feet/day (Stone and Christensen, 1983). The water infiltrating from these basins produces a plume that can be identified in monitor wells by its high conductivity and tritium values.

Stone and Christensen (1983) reviewed the then available groundwater data and found only tritium, ⁹⁰Sr, and uranium to be notably mobile in the subsurface at this site. Studies have been conducted on the accumulation of metals and radionuclides in the soils beneath the seepage basins (Corbo et al., 1987). Plutonium appeared to be relatively tightly bound to soil constituents and largely confined to the upper 20 cm (8 inches) of soil beneath the basins (Gordon et al., 1987).

The H Area Seepage Basins

The four seepage basins in this area covered an area of 42,700 m² and were in use between 1955 and 1988. The majority of the liquids discharged to the basins contained low-level radioactivity and chemicals from the H-Area Separations facility. The purpose of the basins was to use the soil columns to delay the release of tritium, allowing for longer decay, and to retard the migration of other radionuclides. In addition to the low-level radioactivity, the effluents to the basins contained metals, including mercury and cadmium nitrate in the form of HNO₃ and NaOH (Killian et al., 1987).

Release of plutonium to the basins is estimated at 2.4 Ci of ²³⁸Pu and 2 Ci of ²³⁹Pu (Cummins et al., 1991). In 1984, 1 meter soil cores were taken from the bottoms of the basins and analyzed (Carbo, et al., 1985). The plutonium concentration ranged from less than detection limits to 2,200 pCi/g ²³⁸Pu and 11,000 pCi/g ²³⁹Pu. Over 90% of the radioactivity, excluding tritium, was found in the upper 30 cm of the soils, indicating that the soils were effectively trapping the low-level wastes and plutonium. The basins were closed in 1988 and have since been capped.

Though in close proximity to the F-Area basins, the hydrogeology at the H-Area basins is distinct. The depth of the water table beneath the H-Area basins is only about 20 feet, and the basins are located closer to the groundwater discharge zone along Four Mile Branch. Much of the groundwater flow in this area appears to occur in narrow, high permeability channels in the sediments. While a small percentage of the seepage basin waters penetrate into a deeper aquifer, the majority migrate to an outcrop of the water table, or "seep line" above Four Mile Branch (Figure 4.20).

Groundwater monitoring in H Area for radioactive parameters has been conducted since the basins were placed into operations. The level of gross alpha activity in the ground water is generally less than 15 pCi/L, the drinking water standard. Detectable levels of ²³⁸Pu and ^{239/240}Pu are sporadically reported from monitoring wells near the seepage basins. These reported values are generally well below the proposed drinking water standards for ²³⁸Pu and ^{239/240}Pu and usually do not show up in subsequent quarterly reports.

Data on water discharging at the seep line along Fourmile Branch, down gradient from the basins, were collected in 1988 (Haselow et al., 1990). ²³⁸Pu and ^{239/240}Pu values were less than 1 pCi/L. Transport of Plutonium to surface waters via the groundwater

path from the seepage basins thus appears to be extremely limited, based on current information.

TNX Seepage Basins-CMX/TNX Seepage Basins

The primary purpose of the TNX area is to run pilot-scale testing of chemical processes and related activities. Several waste disposal sites have been active in the TNX area. Two seepage basins that are no longer used lie near the area boundaries and there exists an old burial ground (Figure 4.21). The old seepage basin operated from 1958 to 1980. This basin ceased receiving waste water in 1980. In 1981, a breach was opened in the western wall of the basin and the impounded water in the basin was drained into the adjacent wet lands (Christensen and Gordon, 1983). The old basin was then backfilled with a sand and clay mix and capped with clay.

Figure 4.21. Location of the Old TNX Seepage Basins

Plutonium is not known to have been discharged into any of the TNX Area seepage basins. Plutonium activities above the detection limits have been reported occasionally for groundwater samples taken from the vicinity of the basins. This data is not consistent and no conclusions can be drawn for the reported occurrences.

SRTC Seepage Basins

The four Savannah River Technology Center seepage basins are located in the northwestern section of the site about 3,200 feet from the nearest site boundary

(see Figure 4.22). The first two basins were placed into service in 1954 and augmented with two additional basins in 1958 and 1960, respectively (Christensen and Gordon, 1983). The four basins are connected via overflow channels. While in operation, they received low-level waste effluents not exceeding 100 d/m/ml alpha from the SRTC. Liquid wastes exceeding 100 d/m/ml were diverted for holding tank and transported to the F-Area evaporators (Stone & Christensen, 1983). Cummins, et al., 1991, estimated that approximately 8.9×10^{-3} Ci of ^{238}Pu and 2.95×10^{-3} Ci of $^{239/240}\text{Pu}$ were discharged to these basins. Shallow cores and grab samples taken from the bottoms of the SRTC basins indicate that most of the plutonium in the basins is retained in the upper two feet, especially in Basins 1 and 2 (Bransford et al., 1988).

Figure 4.22. Location of the M-Area Settling Basin and the SRTC Seepage Basins

The water table is more than 100 feet below the level of the seepage basins and below the level of the nearby, unnamed dry tributary channel of Tims Branch. The confining beds found in the shallow aquifers elsewhere on the site are either absent or ineffectual in this locality and recharge to the underlying Cretaceous formations is probably occurring in the vicinity of SRTC (Strom and Kaback, 1992).

Although monitor wells installed around the basins have detected evidence of migration of contaminants from the basins during the first and second quarters of 1989, the activities of plutonium were low. The maximum ^{238}Pu activity was 4.4 ± 1.4 pCi/L and for $^{239/240}\text{Pu}$, 12 ± 1.0 pCi/L. Both values were below proposed drinking water standards and were not confirmed in later sampling of the wells.

There are several plausible explanations for these observations including capture of colloidal plutonium-bearing particles during sampling, migration of a "front" of plutonium-bearing water past the sampling point, or even laboratory or sampling error. More recent sampling at the same wells indicate plutonium activities below detection limits in groundwater near the SRTC basins.

Groundwater Samples

Reactor Areas Seepage Basins

In the five reactor areas on the site, earthen basins were used both as seepage basins and containment basins. The historical use of these basins is described in Chapter 3, Table 4-5 shows the number of each type of basin at the five reactor areas. The seepage basins received low-level radioactive purge waters from the reactor disassembly buildings. Originally, the purge waters were pumped directly to the basins before the use of sand filters and mixed-bed deionizer were introduced during the 1960s. While approximately 20 different types of radionuclides have been sent to these basins, the bulk of radioactivity is from decay of ^3H , ^{90}Sr , and ^{137}Cs (Stone and Christensen, 1983). Alpha activity was determined on discharges though, with exception of R-Area basins, specific alpha emitters were not routinely determined. Table 4-5 shows the activity of radionuclides estimated to have been discharged to the reactor area seepage basins.

Table 4-5. Alpha Activity Discharged to Reactor Seepage Basins. Data on Activities from Hetrick and Martin (1989).

Reactor	Seepage Basins	Containment Basins	Alpha Emitters	$^{239/240}\text{Pu}$ (Ci)
C-Area	3	1	3.8×10^{-3}	—
K-Area	1	1	2.2×10^{-2}	—
L-Area	1	1	2.3×10^{-3}	—
P-Area	3	1	1.0×10^{-2}	—
R-Area	6	0	—	3.0×10^{-1}

In R Area, the majority of alpha activity sent to the basins resulted from the failure of an experimental fuel element during a calorimeter test during the fall of 1957. An estimated 3×10^{-1} Ci of ^{239}Pu was discharged to basin No. 1 as a result of the accident. This basin was backfilled, covered with asphalt and a clay dike constructed around the perimeter to contain the lateral migration of the radionuclides from the site.

Alpha radioactivity in groundwater monitoring-well samples around the retention basins is low usually below 1 pCi/L, even in the R Area. Isolated spikes in gross alpha activity have been reported in the annual environmental reports; however, these appear to be analytical artifacts and not attributable to transport of plutonium to groundwater from the R-Area basins.

Summary and Environmental Assessment

Release of plutonium to the groundwater environment has largely been through discharges of low activity liquid wastes to seepage basins; the majority to F- and H-Area seepage basins. In the case of plutonium, seepage basins appear to have trapped and retained the majority of the radionuclides in the upper 2 feet of soil. Monitoring plutonium activity in the groundwater in the vicinity of the seepage basins has yielded very inconsistent results. ^{238}Pu or $^{239/240}\text{Pu}$ above detection limits have been

sporadically reported for samples both near basins where plutonium has been discharged, such as at the TNX seepage basins.

Plutonium is reliably reported in groundwater beneath the Old Burial Grounds. This plutonium is apparently related to the 1971 solvent spill or to operations at the decontamination station. There is some evidence to believe that even at this site, plutonium is closely associated with, or sorbed to, soil particles or suspended colloids.

Table 4-4 shows both the 1980 gross alpha and the results of the alpha spectroscopy analyses. In several cases, the alpha activity is lower than the plutonium activity. The gross alpha measurements were made after the samples had been left undisturbed for 48 hours and solids and colloids had been allowed to settle from the solution, presumably removing plutonium or other alpha emitters from solution in the process. Alpha spectroscopy was performed by contrast on unfiltered acidified aqueous samples (McIntyre and Wilhite, 1988). Acidification has the effect of dissolving colloids, such as iron and aluminum oxyhydroxides, and of desorbing metals from sorption or exchange sites on solids. These differences in sample preparation methods may explain the disparities in the analytical results and confirm to the expected high degree of retention by soil particles.

References

- Aadland, R.K., P.A. Thayer, and A.D. Smits, 1992, "Hydrostratigraphy of the Savannah River Site Region, South Carolina and Georgia", Wallace Fallaw and Van Price Eds: Geological Investigations of the Central Savannah Area, South Carolina and Georgia, Carolina Geological Society Field Trip Guide Book, Nov. 13-15, 1992, South Carolina Geological Survey, Harbison Forest Road, Columbia, SC 29210-40898, p. CSG-B-X-1 to 6.
- Alberts, J.J., J.E. Halverson, and K.A. Orlandini, 1986. "The Distribution of Plutonium, Americium and Curium Isotopes in Pond and Stream Sediments of the Savannah River Plant, South Carolina, USA", J. Environ. Radioactivity 3:249-271.
- Bledsoe, H.W., 1984, SRP Baseline Hydrogeologic Investigation-Phase, DPST-84-833, E. I. du Pont de Nemours and Company, Savannah River Technology Center, Aiken, SC.
- Bransford, J.L., H. W. Bledsoe, and R.V. Simmons, 1988, Chemical Characterization of Sediments and Groundwater at the Savannah River Technology Center Seepage Basins, DPSTD-84-110, Rev 1, E. I. du Pont de Nemours and Company, Savannah River Technology Center, Aiken, SC.
- Carlson, D.C., A.J. Garrett, D.D. Gay, and C.E. Murphy, 1983. "Comparison of Simulated to Actual Plutonium Deposition at the Savannah River Site" in: Precipitation Scavenging, Dry Deposition, and Resuspension, Pruppacher, H.R., R.G. Semonin, and W.G.N. Slinn, Eds., Elsevier, New York, pp 1,121-1,129.
- Carlton, W.H., L.R. Bauer, A.G. Evans, L.A. Geary, C.E. Murphy, Jr., J.E. Pinder, and R.N. Strom, 1992. "Cesium in the Savannah River Site Environment", WSRP-RP-92-250, Westinghouse Savannah River Company, Savannah River Site, Aiken, SC.

- Christensen, E.J., and D.E. Gordon, 1983, Technical Summary of Groundwater Quality Protection Program at Savannah River Site, v.1, Site Geohydrology and Solid and Hazardous Waste, DPST-83-829, E. I. du Pont de Nemours and Company, Savannah River Technology Center, Aiken, SC.
- Corbo, P., M.V. Kantelo, and C.B. Fliermans, 1985, Analytical Results, Database Management and Quality Assurance for Analysis of Soil Cores from the F- and H-Area Seepage Basins, DPST-85-921, E. I. du Pont de Nemours and Company, Savannah River Technology Center, Aiken, SC.
- Corey, J.C., J.E. Pinder III, J.R. Watts, D.C. Adriano, A.L. Boni, and K.W. McLeod, 1981. "Stack-Released Plutonium in the Terrestrial Environment of a Chemical Separations Facility", *Nuclear Safety*, 23: 310-319.
- Cummins, C.L., C.S. Hetrick, and D.K. Martin, 1991, "Radioactive Releases at the Savannah River Site 1954-1989 (U)", WSRC-RP-91-684, Westinghouse Savannah River Company, Aiken, SC.
- Gay, D.D. and J.R. Watts, 1981. "Particle Size Distribution of Airborne Plutonium Near a Chemical Separations Facility", DP-1610, Savannah River Laboratory, Aiken, SC 29808, pp. 1-19.
- Gladden, J.B., M.W. Lower, H.E. Mackey, W.L. Specht, and E.W. Wilde, 1985. "Comprehensive Cooling Water Study Annual Report, Volume IV, Radionuclide and Heavy Metal Transport", DP-1697-4, E.I. du Pont de Nemours & Company, Savannah River Technology Center, Aiken, SC.
- Gohn, G.S., 1988, Late Mesozoic and Early Cenozoic Geology of the Atlantic Coastal Plains; North Carolina to Florida, in, Sheridan, R.E., and Grow, J.A., eds., *The Geology of North America*, v. 1-2, Geol. Soc. Am., p 107-130.
- Goldberg, E.D., J.J. Griffin, V. Hodge, and M. Koide, 1979. "Pollution History of the Savannah River Estuary", *Environ. Sci. Technol.* 13: 588-594.
- Gordon, D.E., W.F. Johnson, D.S. Kaback, B.B. Looney, R.L. Nichols, and C.B. Shedrow, 1987, Characterization Recommendations for Waste Sites at the Savannah River Site, DPST-87-667, E.I. du Pont de Nemours and Company, Savannah River Technology Center, Aiken, SC.
- Haselow, J.S., M. Harris, B.B. Looney, N.V. Halverson, and J.B. Gladden, 1990, Analysis of Soil and Water at the Four Mile Creek Seep Line Near the F & H Areas of SRS (U), WSRC-RP-89-737, Westinghouse Savannah River Company, Aiken, SC.
- Hayes, D.W., J.H. LeRoy, and F.A. Cross, 1975. "Plutonium in Atlantic Coastal Estuaries in the Southeastern United States", DP-MS-75-28, E.I. du Pont de Nemours & Company, Savannah River Technology Center, Aiken, SC.
- Hayes, D.W., and J.H. Horton, 1980. "Plutonium and Americium Behavior in the Savannah River Marine Environment" in *Transuranic Elements in the Environment*, edited by W.C. Hanson, DOE/TIC-22800.
- Hayes, D.W., and W.M. Sackett, 1987. "Plutonium and Cesium Radionuclides in Sediments of the Savannah River Estuary", *Estuar. Coast. Shelf Sci.*, 25:169-174.
- Holloway, R.W., and D.W. Hayes, 1981. "Transuranics in a Stream Near a Nuclear Fuel Chemical Separations Plant", DP-1592, E.I. du Pont de Nemours & Company, Savannah River Technology Center, Aiken, SC.
- Horton, J.H., and D.D. Gay, 1982. "Deposition of Airborne ²³⁸Pu Near a Chemical Separation Facility", DP-1585, E.I. du Pont de Nemours & Company Savannah River Technology Center, Aiken, SC 29808 pp 1-9.
- Killian, T.H., N.L. Kolb, P. Corbo, and I.W. Marine, H-Area Seepage Basins, Environmental Information Document, DPST-85-706, E.I. du Pont de Nemours and Company, Savannah river Technology Center, Aiken, SC.
- Marine, I.W., 1974, Geohydrology of the Buried Triassic Basin at the Savannah River Site, South Carolina, *Am. Assoc. Petrol. Geol. Bull.*, v. 58, p 1825.
- McIntyre, F.F., and E.L. Wilhite, 1988, Radionuclide Analyses of Burial Ground Well Water, Technical Memorandum DPST-88-375, E.I. du Pont de Nemours and Company, Savannah River Technology Center, Aiken, SC.
- Murphy, C.E., Jr., 1991. "Estimating Deposition Velocity from Atmospheric Releases of Iodine", WSRC-TR-91-72, Westinghouse Savannah River Company, Savannah River Site, Aiken, SC 8 p.

Murphy, C.E., Jr., L.R. Bauer, D.W. Hayes, W.L. Marter, C.C. Zeigler, D.E. Stephenson, D.D. Hoel, and D.M. Hamby, 1991. "Tritium in the Savannah River Site Environment", WSRC-RP-90-424-1, Revision 1, Savannah River Site, Aiken, SC.

Olsen, C.R., M. Thein, I.L. Larsen, P.D. Lowry, P.J. Mulholland, N.H. Cutshall, J.T. Byrd, and H.L. Windom, 1989. "Plutonium, Lead-210, and Carbon Isotopes in the Savannah Estuary: Riverborne versus Marine Sources", *Environ. Sci. Technol.* 23: 1475-1481.

Perkin, R.W., and C.W. Thomas, 1980. "World Fallout" in: *Transuranic Elements in the Environment*. W.C. Hanson, Ed. DOE/TIC-22800, Technical Information Center, UDDC, Springfield, VA, pp 53-82.

Pinder, J.E., and D. Paine, 1980. "Sources of Variation in Soil Plutonium Concentrations" in: *Transuranic Elements in the Environment*, W.C. Hanson, Ed. DOE/TIC-22800, Technical Information Center, UDDC, Springfield, VA, pp 165-172.

Ryan, J.P., 1983, *Groundwater Monitoring in the Savannah River Site Low-level Waste Burial Ground: a Summary and Interpretation of the Analytical Data*, DPST-83-209, E.I. du Pont de Nemours and Company, Savannah River Technology Center, Aiken, SC.

Sanders, S.M., and A.L. Boni, 1980. "The Detection and Study of Plutonium Bearing Particles Following the Reprocessing of Reactor Fuel", in: *Transuranic Elements in the Environment*, W.C. Hanson, Ed. DOE/TIC-22800, Technical Information Center, UDDC, Springfield, VA, pp 107-144.

Siple, G.E., 1967, "Geology and Ground Water of the Savannah River Site and Vicinity, South Carolina, U.S. Geological Survey Water Supply Paper 1841, U.S. Government Printing Office, Washington, DC.

Stone, J.A., and E.J. Christensen, 1983, *Technical Summary of Groundwater Quality Protection Program at Savannah River Site, v. II, Radioactive Waste*, DPST-83-829 (vol. 2), E.I. du Pont de Nemours, Aiken, SC.

Strom, R.N., and D.S. Kaback, 1992, *Tritium Migration in A/M-Area Groundwater*, WSRC-TR-92-8, Westinghouse Savannah River Company, Savannah River Technology Center, Aiken, SC.

This page intentionally left blank.

Chapter 5. Environmental Plutonium Research by the Savannah River Ecology Laboratory

Plutonium releases to the SRS environment provide opportunities to study the environmental behavior of this element. Before 1974, little was known about the transport and fate of Pu in the environment. Starting in 1974, extensive studies of Pu in the environment were begun at SRS, at other DOE sites, and at several universities. These studies were coordinated through DOE's Office of Health and Environmental Research. Studies at the SRS involved staff from the Savannah River Technology Center, the Savannah River Ecology Laboratory, Argonne National Laboratory, and Lawrence Livermore National Laboratory. The SRS studies were mostly involved with Pu behavior in terrestrial agroecosystems and aquatic environments, such as Pond B. These studies are described in greater detail in the following sections.

This page intentionally left blank.

Plutonium Behavior in Agroecosystems

Most studies of plutonium transport in terrestrial systems have considered only a single transport process (e.g., root uptake) or have occurred several years after the airborne release of plutonium when atmospheric deposition no longer was occurring. Few studies have determined the relative importance of root uptake, atmospheric deposition, and resuspension for instances of ongoing plutonium release. Studies designed to compare the relative importance of these processes were conducted by Savannah River Technology Center and Savannah River Ecology Laboratory at field sites near the H-Area nuclear fuel chemical separations facility. The main objective of these studies was to compare and contrast the relative importances of root uptake, atmospheric deposition, and resuspension in determining the plutonium contents of grain in wheat, soybean, and corn crops.

These comparisons were made using a model of ^{239}Pu transfers in agroecosystems (Table 5-1) that summarizes the data from different crops into several simple and easily estimated parameters which may be compared among crops. Plutonium transport is modeled for processes which occur in the field (see Figure 5.1), during the growth of the crop, and those which occur in the combine, during the mechanical

harvesting of the grains. Processes occurring in the field include root uptake and translocation to grain and the interception and retention of deposition on vegetation surfaces, such as leaves. Processes occurring in the combine include the transfer of plutonium from vegetation surfaces to grain surfaces, and the resuspension of plutonium-bearing soil particles to grain surfaces.

This simple model reduces the relatively complex behavior of plutonium in agroecosystems to a set of four parameters that may be easily estimated and compared among systems. These four parameters are: 1) I_v , the fraction of the yearly atmospheric deposition of plutonium retained on the surface of the vegetation at harvest; 2) T_{vg} , the fraction of the retained plutonium transferred from vegetative surfaces to grain surfaces during combining; 3) U_{sg} , the fraction of the soil inventory absorbed by roots and translocated to grain; and 4) R_{sg} , the fraction of the soil inventory of plutonium transferred to grain surfaces by resuspension. Atmospheric deposition is expressed as $\text{mCi m}^{-2} \text{d}^{-1}$, and the soil inventory and quantity of plutonium harvest are expressed as mCi m^{-2} . The effects of radioactive decay are negligible for ^{239}Pu and were omitted from the model.

Table 5-1. Estimates of parameter values for the plutonium transfer model presented in Figure 5.1. The model parameters are

- I_v , the fraction of the yearly deposition retained on the vegetation at harvest
- T_{vg} , the fraction of the plutonium on vegetation attributed to atmospheric deposition transferred to grain during combining
- U_{sg} , the fraction of the soil inventory absorbed by roots and translocated to grain; and
- R_{sg} , the fraction of the soil inventory of plutonium resuspended to grain surfaces

The parameter values for wheat and soybeans are the means $\pm$ standard errors for values computed for data from Fields 1 and 2 (Pinder et al., 1989). The values for corn represent means and standard errors of values from Fields 2 and 3.

Parameter	Crop		
	Wheat	Soybeans	Corn
I_v	0.030 ± 0.001	0.020 ± 0.013	0.037 ± 0.011
T_{vg}	0.0045 ± 0.0002	0.0021 ± 0.0001	0.0010 ± 0.0001
U_{sg}	$9.9(\pm 0.3) \times 10^{-11}$	$5.7(\pm 0.2) \times 10^{-10}$	$7.3(\pm 4.1) \times 10^{-10}$
R_{sg}	$1.6(\pm 0.1) \times 10^{-7}$	$7.4(\pm 2.3) \times 10^{-8}$	$6.2(\pm 6.2) \times 10^{-9}$

Figure 5.1. A model of plutonium transport in agroecosystems involving processes occurring while the crop is growing in the field and when the crop is mechanically harvested using a combine.

To estimate the parameters in the model, wheat, soybeans, and corn were grown in agricultural fields more than 0.5 hectare in size and located within 1 km of H Area. Samples of soils, plant biomass, and grains obtained by harvesting the crops with commercial combines were analyzed for their contents of ^{238}Pu and $^{239,240}\text{Pu}$. Detailed presentations of methods and results for wheat, soybeans, and corn are given by McLeod et al. (1980), Adriano et al. (1982), and Pinder et al. (1989a), respectively. The atmospheric

deposition rates of ^{238}Pu and $^{239,240}\text{Pu}$ for the fields were measured using tacky paper collectors (see Corey et al., 1982, for details). The contributions of resuspension and atmospheric deposition on the plutonium content of crops and grains were determined using the isotopic ratio (ISR) of ^{238}Pu to $^{239,240}\text{Pu}$. Atmospheric releases were primarily ^{238}Pu , whereas the plutonium content of soil and resuspension were primarily $^{239,240}\text{Pu}$.

A comparison of model parameters for wheat, soybeans, and corn is presented in Table 5-1. Some parameters, notably I_v , are similar among crops, whereas others, such as T_{vg} and R_{sg} , appear to differ among crops. The estimate of T_{vg} for corn is less than for wheat and soybeans and probably reflects differences in the types of combines used to obtain grain. For wheat and soybeans, the combines clip plants near the ground surface, and almost all the vegetation and surface plutonium inventories are taken into the combine. In contrast, a corn combine usually removes only the upper portion of the plants, where the ears are located. As a result, only a portion of the corn biomass and surface plutonium inventory enters the combine. Thus, not all of the surface Pu contamination is available to be transferred to grain, and the T_{vg} values are smaller. The mechanics of combining also result in relatively low R_{sg} for corn grain. More resuspended soil and plutonium is taken into the combine when the combine head is nearer the soil surface. Thus, more plutonium occurs on the surface of grains of wheat and soybeans than on the surface of corn grain.

Table 5-2. The inventories of $^{239,240}\text{Pu}$ in components of the Pond B ecosystem, the percent of the total inventory of 11.6 mCi of $^{239,240}\text{Pu}$ in the various components, and the ratio of concentration in biota to that in filtered water.

Ecosystem Component	Inventory (mCi per pond)	Percent of Total	Concentration Ratio
Sediments	11.6	99.9	
Water			
Seston	3.0×10^{-3}	2.6×10^{-2}	
Filtered	9.0×10^{-4}	7.9×10^{-3}	
Macrophytes	1.1×10^{-3}	9.1×10^{-3}	4200
Benthic			
Invertebrates	2.7×10^{-5}	2.3×10^{-4}	19000
Zooplankton	2.2×10^{-6}	1.9×10^{-5}	2200
Fish ¹	4.9×10^{-7}	4.2×10^{-8}	1200

¹ Computed assuming that all fish have the same concentration as largemouth bass

Despite the differences in parameter values, the relative contributions of atmospheric deposition, resuspension, and root uptake to the ^{239}Pu concentration for grains were similar for wheat, soybean, and corn agroecosystems. The relative importances of atmospheric deposition, resuspension, and root uptake are compared in Figure 5.2, where the ^{239}Pu concentration in wheat, soybean, and corn grains are shown for a hypothetical scenario. The hypothetical scenario involves a nuclear facility that operates for 30 years and deposits $2.7 \text{ pCi } ^{239}\text{Pu m}^{-2} \text{ d}^{-1}$ onto fields that already contain $2,000 \text{ pCi } ^{239}\text{Pu m}^{-2}$ because of global fallout. The values in Table 5-2 are computed using the model described in Figure 5.1 and the parameter values listed in Table 5-2. Atmospheric deposition is much most important for all crops. Resuspension is more important than root uptake for each crop. This occurs because I_v was >0.01 , whereas R_{vg} and U_{vg} were <0.000001 . Resuspension was more important than root uptake because R_{vg} was greater than U_{vg} . However,

Figure 5.2. The ^{239}Pu Concentrations for grains from wheat, soybean, and corn agroecosystems as a result of atmospheric deposition, resuspension, and root uptake for a hypothetical scenario in which a nuclear facility operates for 30 years and deposits $2.7 \text{ pCi } ^{239}\text{Pu m}^{-2} \text{ d}^{-1}$ onto areas already containing $2,000 \text{ pCi m}^{-2}$ from global fallout.

deposition likely will be the principal contamination mechanism. Where Pu releases and deposition have occurred in the past, resuspension is likely to be the predominant mechanism in moving Pu to grain crops.

These results imply some general conclusions concerning plutonium mobility in agroecosystems. Where plutonium releases to the atmosphere are ongoing, atmospheric differences occur in the amount that resuspension exceeds root uptake because of changes in the relative magnitudes of R_{vg} and T_{vg} . Resuspension is much more important than uptake for wheat where R_{vg} is much greater than U_{vg} . The R_{vg} for corn is only slightly greater than the U_{vg} ; consequently, resuspension for corn is only slightly greater than uptake.

In addition to these large-scale studies of agroecosystems, other agricultural studies were performed to measure 1) adherence of plutonium-bearing soil particles to tuber crops (Corey et al., 1983); 2) the deposition and resuspension of plutonium to other crops such as tobacco (McLeod et al., 1984b), and various broad-leaf crops, such as lettuce, cabbage, turnips, and broccoli (McLeod et al., 1984a); and 3) root uptake of plutonium isotopes (Hersloff and Corey, 1978; Adriano, et al., 1981, 1986; McLeod et al., 1981). Other studies at H Area have 1) measured the retention time of plutonium particles on plant surfaces (Pinder and Doswell, 1985), the relationship between canopy biomass and the fraction of plutonium deposition intercepted (Pinder et al., 1988), and the inhalation dose to agricultural workers disturbing and resuspending soil (Milham et al., 1976); 2) evaluated the accuracy of NRC computer codes and other models to predict Pu transport in agroecosystems (Pinder et al., 1989a); and 3) used plutonium as a tracer to quantify the mass of soil present on plant surfaces as a function of height above the ground surface (Pinder and McLeod, 1988, 1989b; Pinder et al., 1991). These studies were supported by research on the identification of sizes and compositions of plutonium-bearing particles (Sanders and Boni, 1980; Gay, 1982) and rates of resuspension of soil particles (Shinn et al., 1983).

The Behavior of Plutonium in Pond B

Although comprehensive studies of plutonium in aquatic systems have occurred in settling ponds and containment basins, relatively few studies have been performed on the dynamics of plutonium in the water columns of natural or semi-natural lakes. Settling ponds and containment basins usually are too small,

too shallow, or too impacted by continuing operations of nuclear facilities to be representative of more natural, large-scale aquatic systems. Where studies have occurred in natural and semi-natural systems, changes in the distribution of plutonium with time or water depth have been attributed to particle dynamics

or remobilization of plutonium from the sediments during periods of anoxia. Anoxia occurs in lakes, ponds, and reservoirs, especially in the southeastern United States, during the summer, when the water column is thermally stratified into isolated zones of warmer surface waters termed the epilimnion and colder deeper waters termed the hypolimnion. Biological activity in the isolated hypolimnion depletes the oxygen supply and results in anoxia. The absence of oxygen and the occurrence of reducing conditions allows remobilization of Fe, Mn, ^{137}Cs , and other elements from the sediments to the waters of the hypolimnion.

Because of its size and depth (12 m), Pond B shows an annual pattern of thermal stratification and anoxia typical for southeastern reservoirs (Chimney et al., 1985). This pattern of stratification and anoxia makes Pond B an ideal location for analyses of plutonium behavior in aquatic systems. Stratification and isolation of

surface and deep waters develops in March. Surface water temperatures in summer months approach 30°C , whereas temperatures at 12 m seldom exceed 15°C . The waters below 9 m become anoxic in mid-April. The waters from 6 - 9 m deep become anoxic in late April. Turnover and remixing of the pond occurs in late October and early November. Studies of plutonium behavior in Pond B have been concerned primarily with

- an inventory of the plutonium isotopes in the sediments, water column, and biota (Whicker et al., 1990)
- the seasonal variability in the plutonium contents of the water column.

The studies of seasonal variability in plutonium contents were conducted in conjunction with the staff of Argonne National Laboratory and concerned the possible role of anoxic remobilization in determining plutonium abundance in the water column.

Inventory of Plutonium in Pond B

In 1983, studies were begun to determine the amount and distribution of $^{239,240}\text{Pu}$ and ^{238}Pu in Pond B. The basic objectives of these studies, as presented in Whicker et al., (1990) were to

- determine the inventory of plutonium isotopes in Pond B (i.e., the Ci of $^{239,240}\text{Pu}$)
- determine the fraction of the inventory present in the sediments, water, and biotic components of the ecosystem
- compare the relative mobility of plutonium in foodchains in Pond B to that in other aquatic habitats.

Concentrations of plutonium were measured in the sediments and the water. To determine the inventory of plutonium in the biota, plutonium concentrations were measured in samples of plants (primarily floating-leaved macrophytes), zooplankton; benthic invertebrates, such as insect larvae, and fish. The mass of these biotic components also was measured by different sampling procedures (see Whicker et al., 1990, for details). Table 5-2 presents a summary of the biomass and $^{239,240}\text{Pu}$ data.

The inventory of $^{239,240}\text{Pu}$ in Pond B was determined to be 11.6 mCi. Almost all of this amount, >99%, was present in the sediments. Sediment cores suggested that most of the $^{239,240}\text{Pu}$ in the sediments was contained in the upper 15 cm. The inventory for ^{238}Pu

was 0.9 mCi, and more than 99% of this also was in the upper 15 cm of the sediments.

Of the $^{239,240}\text{Pu}$ that was not in the sediments, approximately 80% was in the water column and 20% was associated with the biota. The majority of the $^{239,240}\text{Pu}$ in the water column was associated with seston (i.e., particles with diameters $>0.45\text{ }\mu\text{m}$). Within the biota, most of the $^{239,240}\text{Pu}$ was associated with extensive beds of floating-leaved macrophytes that surround the pond in waters less than 5 m deep. Because of the limited absorption of plutonium isotopes by plants, it is likely that the plutonium associated with the plants was present as sediment or seston particles adhered to the surface of the vegetation.

The distributions for ^{238}Pu not in the sediments generally were similar to those for $^{239,240}\text{Pu}$ (Whicker et al., 1990) except

- a smaller fraction of the ^{238}Pu in the water column was associated with seston particles and
- a greater fraction of the ^{238}Pu was associated with floating-leaved macrophytes.

Both of these exceptions appeared to be consistent with ongoing atmospheric deposition of small ^{238}Pu -bearing particles onto the pond surface (Corey et al., 1982). These small particles appear to accumulate on

leaf surfaces (Whicker et al., 1990) and are retained in the filtered fraction of the water column (Pinder et al., in press).

There appears to be greater mobility of $^{239,240}\text{Pu}$ into the biota of Pond B than other aquatic ecosystems. This is indicated by the concentration ratios in Table 5-2, which express the ratio of the concentration in components in the biota to that in the filtered water. All of the ratios for Pond B were near or above the

range of concentration ratios previously reported in the literature. The concentration ratios for ^{137}Cs in Pond B were also greater than those observed elsewhere, which may be explained by the relatively low concentrations of its analog element K in Pond B waters (Whicker et al., 1990). There is no similar analog element for plutonium, and the reasons for the relatively large $^{239,240}\text{Pu}$ concentration ratios are unknown.

Seasonal Variation in the Plutonium Contents of the Water Column

To determine the seasonal variability of the plutonium content of the water column and to examine the possible role of anoxic remobilization of plutonium from the sediments to the water, an extensive sampling of plutonium concentrations in the water column was begun from February 1983 through June 1987. The plutonium concentrations were measured in the seston and filtered components of the water at depths of 1, 4, 8, and >9 m during various seasons of the year, and the data were expressed as inventories of plutonium.

Figure 5.3. Inventories are computed from determinations of $^{239,240}\text{Pu}$ concentrations in seston and filtered water collected at 1, 4, 8, and >9m depths and plotted as a function of the time since November 1, the nominal date of turnover. Vertical lines demark the usual dates for the development of stratification (March 10) and the onset of anoxia in waters >9m deep (April 15). Standard errors (vertical bars) are presented for means when data are available from both stations 1 and 2.

The annual cycle of the $^{239,240}\text{Pu}$ inventories is summarized in Figure 5.3, where inventories (i.e., Ci) are presented for the combined seston and filtered components for the entire water column. The

inventories are plotted as a function of the time since November 1, which is taken as the nominal date of turnover. The typical dates for the development of stratification, March 10, and the onset of anoxia below 9 m, April 15, are also depicted. The inventories demonstrated a consistent annual cycle with maximum values occurring near the time of stratification in March and minimum values occurring near turnover. The consistency of the annual cycle is demonstrated by the similarities in inventories among different years.

If remobilization of plutonium occurred at high rates during periods of summer anoxia in a manner similar to that for ^{137}Cs (Alberts et al., 1979; Evans, et al., 1983; Alberts et al., 1987), then the plutonium inventory of the water column would be expected to show an annual cycle similar to that for ^{137}Cs , with a minimum in early spring and a maximum in late summer or fall following the period of remobilization. Rather than showing the annual cycle expected for anoxic remobilization, the $^{239,240}\text{Pu}$ inventories demonstrated a cycle with a maximum in spring and a minimum in late summer and fall. Instead of showing increases in inventories in anoxic waters during the summer, the cycle is initiated by increases in the plutonium contents of oxic waters during winter months. More detailed analyses of the remobilization (see Pinder et al., in press) from turnover to stratification indicated that it occurred to both surface and deep waters and involved an increase in inventories of approximately 2.7 $\mu\text{Ci } ^{239,240}\text{Pu}$. This represents the remobilization of 0.02 of the sediment inventory.

There are several possible causes for the winter remobilization of plutonium. The timing of the remobilization suggests that resuspension of small plutonium-bearing sediment particles by bottom currents or wave action in near-shore sediments may be important. Greater bottom currents occur in winter, when ponds are well mixed. Greater resuspension may occur near shore in winter because of greater wave action when floating-leaved

macrophytes are less abundant (Kelly, 1989). Greater remobilization in winter could result from greater sediment-water exchanges in the low-pH waters (Burton, 1986) that occur in the bottom of the pond in winter, or greater photo-oxidation (Mudge, et al., 1988) of Pu (III, IV) associated with deeper light penetration in winter months. Although the remobilization processes occurring in Pond B have not been identified, the net remobilization of plutonium in winter months suggests that processes other than anoxic remobilization are important in determining the dynamic behavior of plutonium in the water column.

Although anoxic remobilization is not important in determining the annual cycle of $^{239,240}\text{Pu}$ in the water column, there is some evidence that it is occurring. The plutonium inventories of anoxic waters in summer do not decline. The large declines in the plutonium inventories in Figure 5.3 in the summer months are limited to the surface oxic waters. The relatively constant plutonium inventories occur in anoxic waters in the summer, suggesting some form of continuing plutonium input. Possible processes include

- particle settling from surface waters where inventories are declining and
- anoxic remobilization.

Anoxic remobilization is suggested by observations that the $^{239,240}\text{Pu}$ concentrations in water 9m deep are greater than those at 8m. The greater concentration in deeper waters suggests remobilization and diffusion from the sediments.

The model is defined by

- I_v , the fraction of the yearly deposition retained on vegetation surfaces at harvest
- T_{vg} , the fraction of plutonium on vegetation surfaces transferred to grain during combining
- U_{sg} , the fraction of the soil inventory absorbed by roots and translocated to grain
- R_{sg} , the fraction of the soil inventory of plutonium resuspended to grain.

Although resuspension is indicated by a single vector, it probably involves two separate processes, which are described in the text. Atmospheric deposition is expressed as $\text{mCi m}^{-2} \text{ y}^{-1}$ and the soil inventory and quantity of plutonium harvest expressed as mCi m^{-2} .

References

Adriano, D.C., K.W. McLeod, and T.G. Ciravolo, 1981. Plutonium, curium and other radionuclide uptake from a naturally weathered, contaminated soil. *Soil Science*, 132: 83-88.

Adriano, D.C., J.E. Pinder, III, K.W. McLeod, J.C. Corey, and A.L. Boni, 1982. Plutonium contents and fluxes in a soybean crop ecosystem near a nuclear fuel chemical separations facility. *J. Environ. Qual.*, 11: 506-511.

Alberts, J.J., J.W. Bowling, and K.A. Orlandini, 1987. The effect of seasonal anoxia on the distribution of ^{238}Pu , $^{239,240}\text{Pu}$, ^{241}Am , ^{244}Cm , and ^{137}Cs in Pond Systems of the southeastern United States. In *Environmental Research on Actinide Elements*, ed. by J. E. Pinder III, J.J. Alberts, K. W. McLeod, and R. G. Schreckhize, 371-390, U.S. Department of Energy CONF-841142.

Alberts, J.J., L.J. Tilly, and T.J. Vigerstad, 1979. Seasonal cycling of ^{137}Cs in a reservoir. *Science*, 203: 649-651.

Burton, P.J., 1986. Laboratory studies on the remobilization of actinides from Ravensglass Estuary sediment. *The Science of the Total Environment*, 52:123-145.

Chimney, M.J., W.R. Cody, and W.M. Starkel, 1985. Final Report on the Water Quality, Phytoplankton and Zooplankton of Par Pond and Pond B: I. Water Quality. Aiken, SC: Environmental and Chemical Services, DPST-85-789-1.

Corey, J.C., A.L. Boni, J.R. Watts, D.C. Adriano, K.W. McLeod, and J.E. Pinder, III, 1983. The relative importance of uptake and surface adherence in determining the radionuclide contents of subterranean crops. *Health Phys.*, 44: 19-28.

Corey, J.C., J.E. Pinder, III, J.R. Watts, D.C. Adriano, A.L. Boni, and K.W. McLeod, 1982. Stack-released plutonium in the terrestrial environment of a chemical separations facility. *Nuclear Safety*, 23: 310-319.

Evans, D.W., J.J. Alberts, and R.A. Clark, III. 1983. Reversible ion-exchange fixation of ^{137}Cs leading to mobilization from reservoir sediments. *Geochimica et Cosmochimica Acta*, 47:1041-1049.

Gay, D.D. and J.R. Watts, 1981. Particle-size distribution of airborne plutonium near a chemical separations facility. DP-1610, E.I. du Pont de Nemours & Company Savannah River Laboratory, Aiken, SC 29808

Hersloff, J.W., and J.C. Corey, 1978. Uptake of three isotopes of plutonium by sweet corn grown in a growth chamber. In: Adriano, D. C. and I.L. Brisbin, Jr., eds. *Environmental Chemistry and Cycling Processes*. Springfield, Virginia: National Technical Information Service, CONF-760429; pp. 622-627.

Kelly, M.S., 1989. Distribution and biomass of aquatic macrophytes in an abandoned nuclear cooling reservoir. *Aquatic Botany*, 35: 133-152.

McLeod, K.W., D.C. Adriano, A.L. Boni, J.C. Corey, J.H. Horton, D. Paine, and J.E. Pinder, III., 1980. Influence of a nuclear fuel chemical separations facility on the plutonium contents of a wheat crop. *J. Environ. Qual.*, 9: 306-315.

McLeod, K.W., D.C. Adriano, and T.G. Ciravolo, 1981. Uptake of plutonium from soils contaminated by a nuclear fuel chemical separations facility. *Soil Sci.*, 132: 89-98.

Milham, R.C., J.F. Schubert, J.R. Watts, A.L. Boni, and J.C. Corey, 1976. Measured plutonium resuspension and resulting dose from agricultural operations on an old field at the Savannah River Plant in the southeastern United States of America. In *Transuranium Nuclides in the Environment*. Vienna: International Atomic Energy Agency; pp. 409-421.

Mudge, S., J. Hamilton-Taylor, M. Kelly, and K. Bradshaw, 1988. Laboratory studies of the chemical behavior of plutonium associated with contaminated estuarine sediments. *Journal of Environmental Radioactivity*, 8: 217-237.

Pinder, J.E., III, J.J. Alberts, J.W. Bowling, D.M. Nelson, and K.A. Orlandini, The annual cycle of plutonium in the water column of a warm, monomictic reservoir. *Journal of Environmental Radioactivity*, in press.

Pinder, J.E., III, T.G. Ciravolo, and J.W. Bowling, 1988. The interrelationships among plant biomass, plant surface area and the interception of particulate deposition by grasses. *Health Phys.*, 55: 51-58.

Pinder, J.E., III, and A.C. Doswell, 1985. Retention of ^{238}Pu -bearing particles by corn plants. *Health Phys.*, 49: 771-776.

Pinder, J.E., III, and K.W. McLeod, 1988. Contaminant transport in agroecosystems through retention of soil particles on plant surfaces. *J. Environ. Qual.*, 17:602-607.

Pinder, J.E., III, K.W. McLeod, and D.C. Adriano, 1989a. The accuracy of some simple models for predicting particulate interception and retention in agricultural systems. *Health Phys.*, 56: 441-450.

Pinder, J.E., III, and K.W. McLeod, 1989b. Mass loading of soil particles on plant surfaces. *Health Phys.*, 57: 935-942.

Pinder, J.E., III, K.W. McLeod, R.F. Lide, and K.C. Sherrod, 1991. Mass loading of soil particles on a pasture grass. *Journal of Environmental Radioactivity*, 13: 341-354.

Sanders, S.M., Jr., and A.L. Boni, 1980. The detection and study of plutonium-bearing particles following the reprocessing of reactor fuel. In: Hanson, W. C., ed. *Transuranic elements in the environment*. Washington, DC: Office of Science and Technical Information; TIC 22800; pp. 107-144.

Shinn, J.R., D.H. Homan, and D.D. Gay, 1983. Plutonium aerosol fluxes and pulmonary exposure rates during resuspension from bare soils near a chemical separation facility. In: Pruppacher, H.R.; R.G. Semonin, W.G.N. Slinn, eds. *Precipitation Scavenging, Dry Deposition, and Resuspension. II. Dry Deposition and Resuspension*. New York, NY: Elsevier Science Publishing Co., Inc.; pp. 1131-1143.

U.S. Nuclear Regulatory Commission, 1977. Calculation of Annual Doses to Man from Routine Releases of Reactor Effluents for the Purpose of Compliance with 10 CFR Part 50, Appendix I. Regulatory Guide 1.109, Revision 1. Available from the U.S. Government Printing Office, Washington, DC.

Whicker, F.W., J.E. Pinder, III, J.W. Bowling, J.J. Alberts, and I.L. Brisbin, Jr. 1990. The distribution of long-lived radionuclides in an abandoned reactor cooling reservoir. Ecological Monographs, 60: 471-496.

***Chapter 6. Assessment of Dose/Risk for Savannah River
Site Plutonium Releases***

This chapter describes the health impacts associated with exposure to plutonium. The methodology used to produce dose estimates is presented. The results of a dose assessment for plutonium releases during the 1954-1989 period are discussed.

This page intentionally left blank.

Relationship of Dose to Risk and Health Effects

Ionizing Radiation

Ionizing radiation is radiation that strips the electrons from the matter through which it passes. The interaction of ionizing radiation with biological systems can induce a series of physical and chemical reactions that can cause permanent changes in the genetic material of cells. These changes (mutations) may cause abnormal functioning within the cell or lead to cell death.

The nature of radiation-induced cellular changes depends on the magnitude of the dose and the rate at which it is received. For the low doses and dose rates encountered in the environment from SRS releases, the most significant effect, is cancer induction.

This is believed to be a stochastic effect; i.e., an increase in dose increases the probability of the effect, but the severity of the effect is independent of the dose.

A characteristic of stochastic risks is the absence of a threshold. In other words, it is conceivable that any

dose of radiation, no matter how small, might give rise to a cancer. On the other hand, there is no way to be certain that a given dose, no matter how large, has caused or ultimately will cause a cancer in an individual.

Cancer Risk Estimates

The most comprehensive estimates of cancer induction by exposure to ionizing radiation come from studies of the atomic bomb survivors at Hiroshima and Nagasaki. Less definitive studies include those of medical patients exposed to therapeutic and diagnostic radiation. Studies of laboratory animals have increased the understanding of dose effect relationships. The International Commission on Radiological Protection (ICRP) has evaluated all of these studies and concluded that the best estimate of lifetime risk of fatal cancer for members of the general population is approximately 500 cases per 1,000,000 person-rem. This is equivalent to one case per 2,000 person-rem (ICRP, 1991).

Plutonium Exposure and Dose to Man

Distribution and Retention of Plutonium in the Human Body

Plutonium is absorbed into the body through ingestion and inhalation. Absorption from the gastrointestinal tract is low and most ingested plutonium is excreted in the feces. Inhaled plutonium, which is deposited in the lungs, is slowly absorbed into the blood stream.

Ninety percent of plutonium in the blood is deposited equally in liver and bone. A tiny fraction, about 0.02 percent, is translocated to the gonads, where it contributes to the genetic dose. Plutonium remains in the liver, with a biological half life of 40 years, in the bone, with a biological half life of 100 years and in the gonads indefinitely.

Plutonium Dosimetry

In 1988, the Department Of Energy issued internal dose conversion factors to ensure that doses are calculated in a consistent manner at all DOE facilities (DOE, 1988). The factors are based on ICRP recommendations (ICRP, 1979). These dose factors are used in conjunction with the models described in the following section to calculate all the doses reported in this document.

Future changes are anticipated in the dose calculation methodology. The ICRP (ICRP, 1989), which recently issued age-specific dose factors for ingestion of some of the more common isotopes is developing age-specific dose factors for inhalation of radioisotopes. In this document all individuals are assumed to be adults.

Models of Plutonium Transport and Dose

With the exception of tritium, most of the radioactive materials currently released from SRS have such low concentrations in the offsite environment that they are not detectable by conventional monitoring techniques. Therefore, radiation doses to offsite individuals and populations are calculated with mathematical models. These models use known transport mechanisms for atmospheric and liquid releases and known major pathways of exposure to man. Atmospheric and aqueous dispersion models periodically are verified using environmental measurements of tritium released during normal SRS operations.

The first models used at SRS for calculating offsite doses were developed by the Savannah River Technology Center (Cooper, 1975). These models, MREM (atmospheric releases) and RIVDOSE (liquid releases), first were used in 1972. In 1982, MREM and RIVDOSE were replaced with the more technologically advanced models currently in use.

SRS annual offsite doses are calculated with the transport and dose models developed for the commercial nuclear industry (NRC, 1977a; NRC, 1977b). The models are implemented at SRS in the following computer programs:

Atmospheric Releases

- MAXIGASP: calculates maximum and average doses to offsite individuals
- POPGASP: calculates offsite population doses

Liquid Releases

- LADTAP XL: calculates both maximum and average doses to offsite individuals and collective dose to offsite populations

MAXIGASP and POPGASP are SRTC-modified versions of the Nuclear Regulatory Commission (NRC) programs XOQDOQ (Sagendorf et al., 1982) and GASPARG (Eckerman et al., 1980). The modifications were made to meet the requirements for input of physical and biological data that are specific to SRS. The basic calculations in the XOQDOQ and GASPARG programs have not been modified. LADTAP XL (Hamby, 1991a) utilizes the same basic dispersion and dosimetric models as the NRC version, LADTAP II (Simpson and McGill, 1980), and can be run on a personal computer in a user-friendly environment.

Modeling Atmospheric Dispersion of Radioactive Releases

The routine atmospheric transport of radioactive materials from SRS is evaluated on the basis of meteorological conditions measured continuously at seven onsite meteorological towers. The towers relay wind speed, direction, and atmospheric stability information at 1.5-second intervals to SRTC via the WIND (Weather INFORMATION and Display) system. A database of this information containing the 60-min average values for the period 1982-1986 is accessed by the dispersion codes to estimate downwind concentrations of released radionuclides.

The dispersion of an atmospheric release from the SRS is modeled using XOQDOQ, which computes concentrations at ground level as a function of downwind distance and compass sector. At the user's option, the plume can be depleted as a result of dry deposition and/or radioactive decay. Also at the user's option, plume concentrations can be reduced by taking into account the upward displacement of the effluent resulting from thermal buoyancy and/or momentum effects. This option is not used at the SRS; i.e., no credit is taken for plume rise.

The plume concentration information generated by XOQDOQ then is used by the dose modeling program GASPARG to estimate doses to offsite individuals and populations. GASPARG is used to estimate doses from a number of pathways, which are illustrated in a general sense in Figure 6.1.

The doses estimated by GASPARG are reported on a pathway-specific basis as follows:

Plume - external dose from radioactive materials suspended in the atmosphere

Ground - external dose from radioactive materials deposited on the ground

Inhalation - internal dose from inhalation of radioactive materials present in the plume

Vegetation - internal dose from consumption of contaminated crops

Milk - internal dose from consumption of milk produced in a contaminated area

Meat - internal dose from consumption of meat produced in a contaminated area.

Figure 6.1. Simplified Pathways Between Radioactive Materials Released to the Atmosphere and Man

MAXIGASP

The calculations required by XOQDOQ and GASP to estimate maximum and average individual doses are performed at the SRS using the computer program MAXIGASP. MAXIGASP calculates annual average ground-level air concentrations and 50-yr committed doses at a number of points along the site boundary in each of 16 compass sectors.

The main output from the program is the maximum dose equivalent to an individual along the SRS perimeter. The maximally-exposed individual is assumed to reside continuously at the location of highest exposure and to have living and eating habits which maximize his dose. These assumptions provide a ceiling on dose estimates from atmospheric releases, and no such "maximum individual" is believed to exist.

The parameters used to calculate doses with MAXIGASP are presented in Table 6-1.

POPGASP

The calculations required by XOQDOQ and GASP to estimate population dose from atmospheric releases are performed at the SRS using POPGASP. POPGASP calculates annual average ground-level air concentrations and annual doses for each of 160 regions (16 wind-direction sectors at 10 distances per sector) within an 80-kilometer radius of the release location.

In addition to compass-sector-specific meteorological information, POPGASP uses sector-specific data on population distribution. Comparable data on milk, meat, and vegetable production and consumption also are used in the code (Hamby, 1991b). These databases are quite extensive and are available for review in the SRS Environmental Report, published annually. With respect to the human parameters used in POPGASP, the key values are shown in Table 6-1.

Modeling Doses from Liquid Releases

The consequences of liquid releases from the SRS are modeled using LADTAP XL (Liquid Annual Doses To All Persons). The potential pathways of exposure from liquid releases to the environment are shown in Figure 6.2. The pathway-specific doses calculated by LADTAP XL are grouped into the following five categories:

Potable drinking water - internal dose from consuming drinking water of Savannah River origin

Sport fish and commercial fish - internal dose from consuming fish of Savannah River origin

Saltwater invertebrates - internal dose from consuming shellfish from estuaries of the Savannah River

Recreation - external dose from recreation activities in and along the Savannah River (boating, swimming, and shoreline activities)

Irrigation - internal dose from foods produced by irrigation with Savannah River water (there are no known users of the river for this purpose).

Figure 6.2. Simplified Pathways Between Radioactive Materials Released to Ground or Surface Waters and Man

LADTAP XL estimates individual doses at specific downstream locations. The only removal mechanism included in the transport model as it is used at the SRS is radioactive decay. No credit is taken for adsorption on stream sediments.

The major assumption inherent in the application of LADTAP XL to SRS releases is that liquid discharges undergo complete mixing in the Savannah River before reaching potentially exposed populations. This assumption is supported by repeated measurements indicating that complete mixing occurs in the river between SRS and the Highway 301 sampling station (Cummins et al., 1990a).

LADTAP XL generates maximum individual and population doses for all the exposure pathways identified above. LADTAP XL calculations are performed with SRS-specific information to the extent that it is available. Summary tables of principal input values used in LADTAP XL are shown in Table 6-2 and 6-3.

Verification of Models Using Monitoring Data

Atmospheric Releases

The radionuclide concentrations predicted by XOQDOQ are compared routinely with measured values of tritium concentrations in air to evaluate the code's performance. (Tritium is the only radionuclide released by SRS that can be routinely detected offsite using conventional measuring techniques.) Predicted values tend to exceed observed values, but not to a degree that would indicate an excessively conservative approach.

Other comparisons of predicted and measured concentrations have been made (Marter, 1984) and exhibited similar results. The available data suggests that calculated concentrations of tritium in air generally are conservative estimates of actual offsite values.

Liquid Releases

Throughout the period 1954-1989, drinking water doses from routine SRS releases have been dominated by tritium. Measured, rather than estimated, tritium concentrations therefore are used for the downriver locations most important in terms of dose calculations:

- just below SRS
- at the Beaufort-Jasper Water Treatment Plant, and
- at the Port Wentworth Water Treatment Plant.

In addition to supplying measured tritium concentrations, such data allows calculation of Savannah River dilution factors for these locations. The availability of accurate estimates of river dilution characteristics significantly enhances LADTAP's ability to predict downriver concentrations of other radionuclides, such as plutonium. The results are conservative because no credit is taken for removal of Pu by adsorption in sediments.

Impact of SRS Plutonium Releases on the Offsite Population

The computer codes MAXIGASP, POPGASP, and LADTAP XL have been used to calculate the effective dose equivalent theoretically received by segments of the offsite population from plutonium exposure over the course of site operations. Results are shown in Tables 6-4 and 6-5 for doses attributable to atmospheric and liquid releases, respectively.

Doses from Atmospheric Releases

As shown in Table 6-4, the largest annual effective dose equivalent from atmospheric releases theoretically received by an adult occurred in 1955. The effective dose equivalent from plutonium to the "maximum" adult at the site perimeter in 1955 was 10 mrem. "Maximum" individuals are hypothetical persons who lived at the SRS boundary and subsisted on diets of locally produced milk, meat, and vegetables during the year of release. No such individuals are known to exist. Nevertheless, if one examines the case of the maximum adult individual living continuously at the site perimeter throughout the period 1954-1989, the cumulative effective dose equivalent from atmospheric releases of plutonium has been estimated as 15 mrem (Table 6-4). This value is believed to present the bounding case and would make a minor contribution to the overall dose received during that time period from natural radiation.

A person living in the Central Savannah River Area would have received an effective dose of approximately 10,620 mrem from exposure to natural sources of radioactivity and an additional 2,340 mrem from medical practices and various consumer products during the 36-year period (Cummins et al., 1990b). Therefore, the cumulative dose contribution to this individual from SRS atmospheric plutonium releases can be estimated as 0.1%.

Because the contribution of SRS plutonium releases to any one individual's total radiation dose is so small, it is necessary to pool the radiation exposures from a given population if an assessment of potential health risks is desired. The population dose within an 80-kilometer radius is the figure-of-merit frequently used to make such an assessment.

The population doses reported in Table 6-4 are based on 1980 census data (555,100 people within 80 km) and current meteorological and dose factor data. If it is assumed that this population has lived in the SRS vicinity throughout the period of site operation, the

total collective dose received by that population through 1989 would be 733 person-rem.

Risks associated with this collective dose are quite small. The ICRP risk estimate for the number of excess fatal cancers potentially induced by a collective dose of 733 person-rem is 0.4. Conversely, in that same population, at the current fatal cancer frequency of 16% (EPA, 1989b), there will be on the order of 90,000 spontaneous fatal cancers from all other causes. Therefore, it is impossible that a relationship between any of the cancer deaths occurring in this population and the releases of plutonium to the atmosphere from SRS can be demonstrated.

Doses from Liquid Releases

Dose equivalents potentially received by downstream consumers of Savannah River water and fish are shown in Table 6-5. The dose calculations are based on the total number of curies of plutonium released directly to onsite streams from 36 years of SRS operations. The release levels reflect contributions from all known effluents. Doses have been calculated for a "maximum" individual living just below SRS who subsists on a diet of untreated Savannah River water and fish of Savannah River origin. Such doses are believed to represent the bounding case for plutonium releases to surface water. Drinking water doses have also been calculated for age-specific "maximum" individuals at both of the downstream water treatment plants and for the populations served by the water treatment plants.

The maximum doses occurred in 1955, a year of relatively high plutonium releases coupled with low river flow-rates. The effective dose equivalent to the maximum individual for that year has been estimated at 0.022 mrem. If the hypothetical "maximum" exposure conditions are used as the bounding case for the 36-year period of site operation considered here, the cumulative effective dose to such an individual would be on the order of 0.13 mrem.

Since this individual's dose from non-SRS sources of radiation for that same time period would have exceeded 12,000 mrem; it may be concluded that the contribution to downstream individuals' doses by SRS plutonium releases is insignificant. An effective dose equivalent of 31 mrem/yr has been termed a Negligible Individual Risk Level by the National Council on Radiation Protection and Measurements (NCRP, 1987).

With respect to the effect of liquid plutonium releases on the populations downstream of the SRS, drinking water doses for users of the Beaufort-Jasper, SC (50,000 consumers), and Port Wentworth, GA (15,000 effective consumers), water treatment plants have also been estimated. Different terminology is used to describe the two populations to reflect the difference in their compositions. The Beaufort-Jasper plant services residential areas and therefore provides full-scale domestic water service. The Port Wentworth facility serves a commercial complex in which contact with treated Savannah River water is limited to industrial workers who consume tap water

at work. In past years, however, a locally operated soft-drink bottling facility may have presented an additional pathway of exposure.

If the cumulative effective doses received by both of these populations are summed, the collective dose equivalent would be 3.2 person-rem. Using the ICRP risk factor, the predicted impact of this collective dose is an estimated 0.002 excess fatal cancers in a population of 65,000 people — 10,400 of whom, at the current fatal cancer rate, are projected to succumb to cancer from all other sources.

Comparison of Plutonium Doses with Applicable Regulations

Atmospheric Releases

The highest hypothetical effective dose received by the maximally exposed individual due to atmospheric releases of plutonium from SRS was 10 mrem in 1955 (Table 6.4). The current annual limits on doses to members of the public recommended by the ICRP and the DOE are 500 and 100 mrem, respectively. However, the EPA (EPA, 1989b) has established a 10 mrem/year limit on effective dose equivalent to members of the public via atmospheric releases. The only year that the dose equalled or exceeded 10 mrem was 1955.

Liquid Releases

The current standard for plutonium in drinking water is 4 mrem/yr (EPA, 1977). As shown in Table 6-5, at no time during site operations has the annual dose from SRS plutonium releases to the Savannah River exceeded 0.022 mrem.

It is important to note that all of the dose limits described above are meant to be applied to all releases of radioactivity — not just plutonium. SRS, based on plutonium or total releases, is consistently a minor contributor to radiation dose in the SRS environment.

Summary of Dosimetric Impacts

The overall radiological impact of SRS plutonium releases (1954-1989) on the offsite maximum individual can be characterized by total doses of 15 mrem (atmospheric) and 0.13 mrem (liquid). During this period, however, such an individual received a dose of approximately 12,600 mrem from other sources of ionizing radiation present in the environment.

The impact of SRS plutonium releases on offsite populations also has been evaluated. The total collective dose from atmospheric plutonium releases (1954-1989) is estimated as 733 person-rem

distributed among 555,100 individuals. The total collective dose from liquid plutonium releases for the same period was 11 person-rem distributed among 65,000 individuals. These collective doses are minor components of the doses received from other environmental sources.

Plutonium releases from SRS have decreased dramatically over the course of site operations. Based on data published in the annual environmental reports, routine plutonium releases from SRS present a negligible risk to the offsite environment and the population it supports.

Table 6-1. Site and Age-specific Parameters for Atmospheric Releases

Demographic Data				
Population Group	Population Size	Children	Age Distribution, Percent	
50-mile radius	555,100	18.6	Teens 11.1	Adults 70.3
Maximum Individual (MAXIGASP)				
Exposure Pathway	Infant	Child	Teen	Adult
Inhalation (m ³ /yr)	1400	3700	8000	8000
Ingestion				
Cow's milk (L/yr)	244	244	297	230
Meat (kg/yr)	0	30	48	81
Leafy vegetables (kg/yr)	0	17	28	43
Fruits, grains and other leafy vegetables (kg/yr)	0	276	334	276
External exposure transmission factor for shielding from buildings	0.7	0.7	0.7	0.7
General Population (POPGASP)				
Exposure Pathway	Infant	Child	Teen	Adult
Inhalation (m ³ /yr)	1400	3700	8000	8000
Ingestion				
Cow's milk (L/yr)	186	186	218	120
Meat (kg/yr)	0	17	27	43
Leafy vegetables (kg/yr)	0	8.5	14	21
Fruits, grains, and other leafy vegetables (kg/yr)	0	171	205	163
External exposure transmission factor for shielding from buildings	0.5	0.5	0.5	0.5

Table 6-2. Site- and Age-specific Parameters for Liquid Releases

Maximum Individual Dose Assessments (LADTAP XL).

Site Parameters

Savannah River flow rate, ft ³ /sec	6000 or measured average
Transit time from SRS to Savannah River, hr	24
Shore width factor	0.2

Maximum Individual

Human Parameters	Infant	Child	Teen	Adult
Water consumption (L/yr) (a)	260 (330)	260(510)	260(510)	370(730)
Fish consumption (kg/yr)	0	6	14	19
Shellfish consumption (kg/yr)	0	2.7	6.1	8
Shoreline recreation (hr/yr)	0	27	128	23
Swimming (hr/yr)	0	10	50	8.9
Boating (hr/yr)	0	25	117	21

(a) The values in parentheses are EPA parameters mandated for use when calculating maximum individual doses to Beaufort-Jasper and Port Wentworth water users.

Table 6-3. Additional Site- and Age-specific Parameters for Liquid Releases

Average Individual/Population Dose Assessments (LADTAP XL).				
Site Parameters				
Savannah River flow rate, cu. ft. ³ /sec				10,000 or measured average
Transit time from SRS to Savannah River, hr				24
Transit time from SRS to SRS water treatment plants, hr				72
Retention time in water treatment systems, hrs				24
Shore width factor				0.2
River dilution in estuary				3
Aquatic food harvest, edible portions (kg/yr)				
Sport fish				35,000
Commercial fish				2,700
Salt water invertebrates				390,000
Demographic Data		Age Distribution, Percent		
Population Group	Size	Children	Teens	Adults
50-mile radius	555,100	18.6	11.1	70.3
Beaufort-Jasper water users	50,000	21	10	69
Port Wentworth water users	15,000	0	0	100
		Average Individual		
Human Parameters	Infant	Child	Teen	Adult
Water Consumption (L/yr)	260 (330)	260(510)	260(510)	370(730)
Fish Consumption (kg/yr)	0	6	14	19
Shellfish Consumption (kg/yr)	0	2.7	6.1	8
		Usage (person-hr)		
Shoreline Recreation (hr/yr)				960,000
Swimming (hr/yr)				160,000
Boating (hr/yr)				1,100,000

Table 6-4. Offsite Doses from Atmospheric Releases of ^{238}Pu , ^{239}Pu

Year	Release Ci/yr (a)	CEDE (b) mrem		EDC (c) person-rem 80-km Pop
		Max Ind	Avg Ind	
1955	2.66×10^0	10.355	8.039	513.77
1956	3.10×10^{-2}	0.121	0.094	5.98
1957	4.28×10^{-2}	0.166	0.129	8.25
1958	2.09×10^{-2}	0.081	0.063	4.03
1959	2.39×10^{-2}	0.093	0.072	4.60
1960	7.10×10^{-2}	0.276	0.214	13.71
1961	1.20×10^{-2}	0.047	0.036	2.32
1962	1.14×10^{-2}	0.045	0.035	2.21
1963	3.74×10^{-3}	0.015	0.011	0.72
1964	5.56×10^{-3}	0.022	0.017	1.07
1965	6.83×10^{-2}	0.266	0.206	13.19
1966	3.07×10^{-2}	0.119	0.093	5.92
1967	1.09×10^{-2}	0.042	0.033	2.10
1968	7.17×10^{-3}	0.028	0.022	1.38
1969	6.19×10^{-1}	2.409	1.870	119.53
1970	3.03×10^{-2}	0.118	0.091	5.84
1971	3.03×10^{-2}	0.118	0.092	5.85
1972	2.04×10^{-2}	0.079	0.062	3.93
1973	2.35×10^{-2}	0.092	0.071	4.54
1974	7.75×10^{-3}	0.030	0.023	1.50
1975	2.52×10^{-3}	0.010	0.008	0.49
1976	1.65×10^{-2}	0.064	0.050	3.18
1977	5.15×10^{-3}	0.020	0.016	0.99
1978	7.18×10^{-3}	0.028	0.022	1.39
1979	1.78×10^{-3}	0.007	0.005	0.34
1980	4.02×10^{-3}	0.016	0.012	0.78
1981	7.38×10^{-3}	0.029	0.022	1.42
1982	5.71×10^{-3}	0.022	0.017	1.10
1983	3.35×10^{-3}	0.013	0.010	0.65
1984	1.84×10^{-3}	0.007	0.006	0.35
1985	1.06×10^{-3}	0.004	0.003	0.20
1986	2.35×10^{-3}	0.009	0.007	0.45
1987	2.37×10^{-3}	0.009	0.007	0.46
1988	1.57×10^{-3}	0.006	0.005	0.30
1989	2.56×10^{-3}	0.010	0.008	0.49
Σ	3.80×10^0	14.775	11.471	733.06

(a) Release data include contributions from ^{238}Pu , ^{239}Pu and Gross Alpha from Cummins, Hetrick, and Martin, 1991

(b) CEDE = committed effective dose equivalent assuming 100% ^{239}Pu .

(c) EDC = environmental dose commitment assuming 100% ^{239}Pu .

Table 6-5. Offsite Doses from Stream Releases of Plutonium

Year	Release Ci/Yr (a)	River Flow Rate @ 301 (cfs) (a)	B-J Derived Flow rate, (cfs) (a)(b)	PW Derived Flow rate (cfs) (a)	Max Ind Dose, mrem (c)			WTP Pop Dose person-rem (f)		Total Pop Dose, Person- rem (d)(f)
					Below SRS (d)	B-J WTP (c) (e)	PW WTP (e)	B-J WTP (e)	PW WTP (e)	
1955	4.635x10 ⁻²	5974	-	7528	0.016	-	0.022	-	0.166	1.083
1956	4.210x10 ⁻²	6309	-	7949	0.014	-	0.019	-	0.143	0.932
1957	4.000x10 ⁻³	8312	-	10473	0.001	-	0.001	-	0.010	0.067
1958	1.100x10 ⁻²	11038	-	13908	0.002	-	0.003	-	0.021	0.139
1959	1.300x10 ⁻²	9748	-	12283	0.003	-	0.004	-	0.029	0.186
1960	1.680x10 ⁻²	13112	-	16521	0.003	-	0.004	-	0.027	0.179
1961	1.680x10 ⁻²	10909	-	13745	0.003	-	0.004	-	0.033	0.215
1962	1.150x10 ⁻²	10580	-	13331	0.002	-	0.003	-	0.023	0.152
1963	1.600x10 ⁻²	11138	-	14034	0.003	-	0.004	-	0.031	0.201
1964	1.500x10 ⁻²	20497	-	25826	0.002	-	0.002	-	0.016	0.102
1965	1.100x10 ⁻²	12785	28254	16109	0.002	0.001	0.002	0.035	0.018	0.155
1966	1.410x10 ⁻²	11175	18376	14080	0.003	0.003	0.004	0.068	0.027	0.244
1967	1.570x10 ⁻²	10573	22066	13322	0.003	0.002	0.004	0.063	0.032	0.271
1968	1.190x10 ⁻²	9624	16615	12126	0.003	0.003	0.003	0.064	0.026	0.236
1969	1.060x10 ⁻²	10945	22034	13790	0.002	0.002	0.003	0.043	0.021	0.178
1970	2.060x10 ⁻²	8208	27280	10342	0.005	0.003	0.007	0.067	0.054	0.418
1971	4.190x10 ⁻²	10686	43977	13464	0.008	0.003	0.011	0.085	0.084	0.632
1972	7.171x10 ⁻²	11235	27385	14156	0.013	0.009	0.018	0.233	0.137	1.124
1973	4.070x10 ⁻²	14431	23462	16544	0.006	0.006	0.009	0.154	0.066	0.554
1974	1.567x10 ⁻²	11101	22598	13182	0.003	0.002	0.004	0.062	0.032	0.261
1975	1.860x10 ⁻²	15408	30978	18987	0.003	0.002	0.003	0.053	0.026	0.223
1976	8.310x10 ⁻³	13914	35172	16660	0.001	0.001	0.002	0.021	0.013	0.105
1977	8.302x10 ⁻³	11646	19841	15306	0.001	0.001	0.002	0.037	0.015	0.136
1978	5.751x10 ⁻³	10522	24332	11450	0.001	0.001	0.002	0.021	0.014	0.099
1979	8.821x10 ⁻³	13252	34937	17469	0.001	0.001	0.002	0.022	0.014	0.115
1980	5.774x10 ⁻³	13202	30464	17219	0.001	0.001	0.001	0.017	0.009	0.078
1981	7.635x10 ⁻³	6599	11698	8579	0.002	0.002	0.003	0.058	0.024	0.219
1982	9.243x10 ⁻³	7169	19594	10135	0.003	0.002	0.003	0.042	0.025	0.219
1983	6.743x10 ⁻³	12348	12760	14723	0.001	0.002	0.002	0.047	0.012	0.124
1984	3.116x10 ⁻²	12759	26368	17196	0.005	0.004	0.006	0.105	0.049	0.443
1985	7.004x10 ⁻³	7167	9290	8959	0.002	0.003	0.003	0.067	0.021	0.204
1986	8.469x10 ⁻³	6175	8305	7526	0.003	0.004	0.004	0.091	0.030	0.283
1987	1.825x10 ⁻²	8955	13219	12619	0.004	0.005	0.005	0.123	0.039	0.403
1988	5.536x10 ⁻³	5364	7463	7152	0.002	0.003	0.003	0.066	0.021	0.209
1989	1.418x10 ⁻²	7832	8462	8650	0.004	0.006	0.006	0.149	0.044	0.407
Σ	6.10x10 ⁻¹	10297	21797	1329C	0.13	0.07	0.18	1.79	1.35	10.59

(a) Release data for ^{238,239}Pu & Gross Alpha from Cummins, Hetrick, and Martin 1991. Flow rates based on USGS data at Highway 301 for the maximum individual below the Site. All other doses calculated from flow rates derived from tritium data.

(b) The Beaufort-Jasper water treatment plant began operation in 1965.

(c) Individual doses are CEDEs (committed effective dose equivalents) assuming 100% ²³⁹Pu.

(d) Total dose includes contribution from fish and invertebrate consumption, shoreline habitation, recreational use, and water consumption.

(e) WTP doses calculated from water consumption only.

(f) Population doses are CEDEs (committed effective dose equivalents) assuming 100% ²³⁹Pu.

2 of 2

References

- BEIR, 1980. "Health Effects of Exposure to Low Levels of Ionizing Radiation - BEIR III", Committee on the Biological Effects of Ionizing Radiations, Board of Radiation Effects Research, Commission on Life Sciences, National Research Council, National Academy of Sciences.
- BEIR, 1990. "Health Effects of Exposure to Low Levels of Ionizing Radiation - BEIR V", Committee on the Biological Effects of Ionizing Radiations, Board of Radiation Effects Research, Commission on Life Sciences, National Research Council, National Academy of Sciences.
- Cooper, R.E., 1975. "Computer Programs at SRL Evaluate Environmental Effects of SRP Operations and Postulated Accidental Releases", DPST-75-384, Savannah River Laboratory, Aiken, SC.
- Cummins, C.L., D.K. Martin, and J.L. Todd, 1990a. "Savannah River Site Environmental Report for 1989", WSRC-IM-90-60, Vol. II, Westinghouse Savannah River Company, Aiken, SC, p. 96.
- Cummins, C.L., D.K. Martin, and J.L. Todd, 1990b. "Savannah River Site Environmental Report for 1989", WSRC-IM-90-60, Westinghouse Savannah River Company, Aiken, SC, p. xv.
- DOE (U.S. Department of Energy), 1988. "Internal Dose Conversion Factors for Calculation of Dose to the Public", DOE/EH-0071, Washington, DC.
- DOE, 1990. "Radiation Protection of the Public and the Environment", DOE Order 5400.5, U.S. Department of Energy, Washington, DC.
- Eckerman, K.F., Congel, F.J., Roeklein, A.K., and W.J. Pasciak, 1980. "User's Guide to GASPAR Code", NUREG-0597, U.S. Nuclear Regulatory Commission, Washington, DC.
- EPA (U.S. Environmental Protection Agency), 1977. "National Interim Primary Drinking Water Regulations", EPA 570/9-76-003, Washington, DC.
- EPA, 1988. "Limiting Values of Radionuclide Intake and Air Concentration", EPA 520/1-88-020, Washington, DC.
- EPA, 1989a. "Environmental Impact Statement NESHAPS for Radionuclides - Risk Assessment Methodology", Volume 1, EPA 520/1-89-005, Washington, DC.
- EPA, 1989b. 40 CFR Part 61, "National Emission Standards for Hazardous Air Pollutants; Regulation of Radionuclides; Final Rule and Notice of Reconsideration", Federal Register, Vol. 54, No. 240.
- Hamby, D.M., 1991a. "LADTAP XL: An Improved Electronic Spreadsheet Version of LADTAP II", WSRC-RP-91-975, Westinghouse Savannah River Company, Aiken, SC.
- Hamby, D.M., 1991b. "Land and Water Use Characteristics in the Vicinity of the Savannah River Site (U)", WSRC-RP-91-17, Westinghouse Savannah River Company, Aiken, SC.
- ICRP (International Commission on Radiological Protection), 1979. "Limits for Intake of Radionuclides by Workers", ICRP Publication 30, Part 1, Annals of the ICRP.
- ICRP, 1989. "Age-Dependent Doses to Members of the Public from Radionuclides", ICRP Publication 56, Annals of the ICRP.
- ICRP, 1991. "Risks Associated with Ionizing Radiations", Vol. 22, No. 1, Annals of the ICRP.
- Marter, W.L., 1984. "Environmental Dosimetry for Normal Operations at SRP", DPST-83-270, Rev. 1, Savannah River Technology Center, Aiken, SC.
- NAS (National Academy of Sciences), 1980. "The Effects on Populations of Exposure to Low Levels of Ionizing Radiation", Washington, DC.
- NCRP (National Council on Radiological Protection and Measurements), 1987. "Recommendations on Limits for Ionizing Radiation Exposure", NCRP Report No. 91, Washington, DC.
- NRC (U.S. Nuclear Regulatory Commission), 1977a. "Methods for Estimating Atmospheric Transport and Dispersion of Gaseous Effluents in Routine Releases from Light-Water-Cooled Reactors", Regulatory Guide 1.111, Rev. 1, Washington, DC.

NRC, 1977b. "Calculation of Annual Doses to Man from Routine Releases of Reactor Effluents for the Purpose of Evaluating Compliance with 10 CFR Part 50, Appendix I", Regulatory Guide 1.109, Rev. 1, Washington, DC.

Sagendorf, J.F., J.T. Goll, and W.F. Sandusky, 1982. "XOQDOQ: Computer Program for the Meteorological Evaluation of Routine Effluent Releases at Nuclear Power Stations", NUREG/CR-2919, U.S. Nuclear Regulatory Commission, Washington, DC.

Simpson, D.B., and B.L. McGill, 1980. "Users Manual for LADTAP II - A Computer Program for Calculating Radiation Exposure to Man from Routine Releases of Nuclear Reactor Effluents", NUREG/CR-1276, ORNL/TDMC-1, Oak Ridge National Laboratory, Oak Ridge, TN.

Appendix A.

Physical Properties of Plutonium

All isotopes of plutonium are radioactive. Eleven radioactive isotopes of plutonium may be present at SRS due to site operations. Each isotope's half life is tabulated in Table A.1. Half lives range from seconds to millions of years. The isotopes can be present at SRS as activation products from either singular or multiple neutron capture.

Some of the isotopes may exist both in their lowest energy level and in an excited energy level. In the latter case, the isotope designation includes the letter "m" to indicate a metastable level. For example, ^{237m}Pu indicates that ^{237}Pu exists in an excited energy level.

^{238}Pu and ^{239}Pu are the isotopes with the greatest impact on the SRS environment.

This page intentionally left blank.

Appendix A. Physical Properties of Plutonium

Table A-1. Characteristics of Radioactive Plutonium Isotopes That May Be Present at SRS Due To Site Operations.

<u>Plutonium Isotope</u>	<u>Half-Life</u>
^{236}Pu	2.85 years
^{237}Pu	45 days
$^{237\text{m}}\text{Pu}$	0.2 seconds
^{238}Pu	86 years
^{239}Pu	2.4×10^4 years
^{240}Pu	6.6×10^3 years
^{241}Pu	13.2 years
^{242}Pu	3.8×10^5 years
^{243}Pu	5.0 years
^{244}Pu	7.6×10^7 years
^{245}Pu	10.1 hours
^{246}Pu	10.9 days

This page intentionally left blank.

Appendix B.
Environmental Monitoring

This page intentionally left blank

Air

Concentrations of plutonium (^{238}Pu and ^{239}Pu) in the air are measured at five monitoring stations on the site, 14 monitoring stations around the site perimeter, and 12 stations at distances of approximately 25 miles from the center of the site (called 25-mile radius stations). The stations at the site perimeter and the 25-mile-radius stations are strategically located to permit continuous sampling within each 30-degree sector around the Savannah River Site (SRS). The placement of each monitoring station increases the probability of detecting any routine or non-routine release of airborne radioactivity from the SRS regardless of wind direction. Figure B.1 shows the locations of the monitoring stations.

Figure B.1. Location of Air Monitoring Stations

Four additional air monitoring stations, located at Savannah, GA, Macon, GA, Columbia, SC and Greenville, SC (100-mile-radius stations), are so distant from the SRS that the effect of site operations at these locations is negligible. These stations serve as reference points for determining background radioactivity levels from natural sources and worldwide fallout. Samplers operate continuously at all 35 monitoring stations. Samples for plutonium analysis are collected by drawing air through a two-

inch diameter, high-efficiency glass fiber filter at approximately 70 L/min (2.5 cubic ft./min), and the total sampling time is recorded to calculate the activity per unit volume of air. The filters, located upstream of the charcoal cartridges, are changed weekly. Figure B.2 is a diagram of an air sampling station.

Figure B.2. Air Sampling Station and Component Diagram

Air filters collected at monitoring stations are spiked with ^{242}Pu , ashed, then leached with acid during preparation for ^{238}Pu and ^{239}Pu analysis. The leached solution is evaporated to dryness, dissolved in an acid solution and passed through an anion exchange resin, which extracts and holds the plutonium. The extracted plutonium then is chemically stripped from the resin column, evaporated to dryness and redissolved in a sulfate solution. The sulfate medium containing the plutonium is electrodeposited on a stainless steel disk and counted on a silicon surface barrier detector. The ^{242}Pu spike recovery is used to verify the efficiency of the chemical separation and to quantify the amount of ^{238}Pu and ^{239}Pu present in the sample.

Rainwater

Rainwater is collected at eight monitoring stations by a 2 ft x 2 ft collection pan. The collected water passes through an ion exchange resin column and into a collection bottle. The ion columns are collected every fourth week except the 100-mile stations which are collected quarterly. Rainwater in the sample bottles is analyzed for plutonium on a quarterly basis at all eight locations.

Total radioactive plutonium (^{238}Pu and ^{239}Pu) concentrations are determined from the eluate of the ion exchange column obtained after analysis for the gamma-emitting radionuclides. The analytical procedures for these analyses are the same as those described for air filter samples.

Surface Water

Surface water plutonium concentrations are determined by laboratory analysis of samples. Three types of liquid samples are routinely collected for plutonium analysis:

1. Effluent Outfalls
2. Site Streams and Seepage Basins
3. Savannah River

Effluent Outfalls

Samples are collected where effluents discharge into surface water and are analyzed using the same procedure that is used for rainwater.

Site Streams and Seepage Basins

The major streams on site that are routinely sampled:

- Upper Three Runs
- Lower Three Runs
- Fourmile Branch
- Steel Creek
- Pen Branch
- Beaver Dam Creek

Generally, routine stream samples are collected weekly with a paddlewheel sampler or a Brailsford pump. Samples are analyzed for total alpha radioactivity attributed to plutonium and uranium, without specific isotopic analysis. The alpha-emitting

radionuclides are extracted from 1 liter samples with triisooctylamine (TIOA) in xylene. Both uranium and plutonium are stripped from the TIOA with hydrochloric acid (HCL). The acid solution then is evaporated to dryness to remove the HCL. The residue is dissolved in nitric acid, transferred to a stainless steel planchet, and counted on a gas-flow proportional counter.

A 2-liter grab sample is collected quarterly from seepage basins in A, C, L, and P areas and monthly from the TNX Seepage Basin and the Solid Waste Disposal Facility Settling Basin. These samples also are analyzed for total alpha-emitting radionuclides by the same procedure used to analyze stream samples.

Savannah River

The Savannah River, which receives the outflow from all streams located on SRS, is the most critical sample location for determining population dose from SRS operations. Because of the importance of this parameter, the river is sampled constantly by paddlewheel samplers equipped with 26-liter

polyethylene jugs. The Savannah River is sampled at the following seven locations:

1. River 2 Control
2. River 3A above Plant Vogtle
3. River 3B below Plant Vogtle

4. River 8A below Steel Creek
5. River 8B
6. River 8C below Little Hell Landing
7. River 10A Highway 301 Bridge

These samples are collected weekly, and an additional grab sample is picked up at the River 2 location.

Total plutonium (^{238}Pu and ^{239}Pu) concentrations are determined from a portion of the eluate taken from the ion exchange column used for the gamma-emitting radionuclides. The analytical procedure is the same as the one used for air filters.

Groundwater

The Environmental Monitoring Section (EMS) conducts a routine groundwater monitoring program. Radioactive and nonradioactive monitoring programs are carried out for approximately 1,200 wells. The radioactive monitoring program, which began in the early 1950s, has primarily monitored for gross alpha, nonvolatile beta and tritium activities. The nonradioactive monitoring program began in 1982, and gross alpha, nonvolatile beta, total radium, and tritium activities also are monitored at wells in this program. All wells are analyzed biannually for gross alpha, nonvolatile beta, tritium, and total radium, and all new wells are analyzed for these parameters for

four consecutive quarters. Special studies are periodically conducted by the Savannah River Technology Center (SRTC).

Analytical results are reported in quarterly groundwater reports and in the annual SRS Environmental Report. A documented database is maintained for all groundwater data collected by EMS. The database can be queried to produce graphs and tables for reports or research projects. Specific plutonium isotopic analysis normally is not performed on groundwater samples.

Drinking Water

Drinking water samples are collected at onsite sampling locations and in communities surrounding the SRS. Samples are collected from faucets and drinking fountains. Some onsite samples are collected monthly, while others are collected quarterly. Offsite samples are collected semiannually except from

water treatment plants, where raw and finished drinking water samples are collected daily, composited, and analyzed monthly. These samples are analyzed for total alpha-emitting radionuclides using the same procedure to analyze stream samples.

Other Environmental Matrixes

Soil and Sediments

Soil samples are collected annually from four locations around F Area, four around H Area, four in S Area, and four around Z Area. Four samples also are collected at the site perimeter and at the 100-mile-radius locations. Ten soil plugs, each 8 cm deep, are taken 30 cm apart in a straight line at each sampling location.

EMS collects sediment samples annually from SRS streams and the Savannah River sampling locations. Sediment collection techniques for streams and rivers

are designed to obtain samples from the top 8 cm of sediment in areas where fine sediment accumulates. The samples are not intended to be representative of the entire stream bed.

Soil and sediment samples are analyzed for ^{238}Pu and ^{239}Pu following the procedure described for air filters. This procedure, however, does not provide complete separation of interfering radium daughter products found naturally in the soil and sediment. Therefore, the concentrations reported for soils and sediments reflect the presence of plutonium and radium in the samples.

Dairy Product and Food Stuffs

Dairy products are not analyzed specifically for plutonium, except for special studies. Figure B.3 shows the milk sample locations.

Figure B.3. Milk Sample Locations

Local foodstuffs, including fruits, grains, corn, eggs, chicken, beef, and pork, are obtained from farms located within a 25-mile radius of SRS. Collards are collected as control samples from Columbia, SC. All food samples are collected annually except eggs, which are collected quarterly. Analysts prepare food samples for analysis by separating and discarding the inedible portions, except for grains, which contain both grain and husk. The samples are chopped or blended, then dried or ashed. The residue is dissolved in a hydrochloric acid solution. Concentrations of ^{238}Pu and ^{239}Pu are determined by the same procedure described for air filter samples. Figure B.4 shows the food sample locations.

Figure B.4. Food Sample Locations

Vegetation

Vegetation samples are collected quarterly onsite, at the site perimeter, and at 25 km, and 100 km mile-radius locations. The locations are identical to those used for air monitoring. Additional samples are collected quarterly outside the Radioactive Waste Burial Grounds and annually inside the Burial Ground. Bermuda grass is sampled when available. If not available, other plant species are sampled. Sampling locations are shown in Figures B.1, B.5, and B.6. Before beginning the analysis, the samples are oven-dried for approximately 24 hours at 80 to 90 degrees C. Samples are analyzed for total alpha and nonvolatile beta-emitting radionuclides, without specific isotopic analysis for plutonium.

Figure B.5. Vegetation Sampling Locations Inside the Solid Waste Disposal Facility

To determine gross alpha and nonvolatile beta-emitting radionuclides, a portion of dried and ashed vegetation is dissolved in nitric acid, transferred to a stainless steel planchet, and dried. It then is counted in a gas-flow proportional counter.

Figure B.6. Vegetation Sampling Locations Outside the Solid Waste Disposal Facility

Wildlife

Fish

Fish are collected from the following locations monthly, except at Thurmond Lake and Cannuck Lake, which are sampled annually:

Thurmond Lake
River Mile 160
River Mile 140
River Mile 120
River Mouth
Par Pond
Pond B
Jacks Lake
Cannuck Lake
Steel Creek
Upper Three Runs
Fourmile Branch
Lower Three Runs at Patterson's Mill Rd.
Beaver Dam Creek
Pen Branch

Figure B.7 shows the fish sample locations.

Fish samples are analyzed for total alpha- and nonvolatile beta-emitting radionuclides, without specific isotopic analysis for plutonium.

Figure B.7. Fish Sample and Water Treatment Plant Locations along the Savannah River

Deer

Deer and hogs are collected throughout the site by hunters during deer hunts conducted during the fall of each year. Animals are not analyzed specifically for plutonium, except for special studies.

Ducks

Ducks which are collected by the Savannah River Ecology Laboratory at Par Pond, Pond B, and Steel Creek, are not analyzed specifically for plutonium, except for special studies.

Appendix B. Environmental Monitoring

This page intentionally left blank

**DATE
FILMED**

1 / 12 / 94

END