PRELIMINARY EVALUATION OF SELECTED
IN SITU REMEDIATION TECHNOLOGIES
FOR VOLATILE ORGANIC COMPOUND
CONTAMINATION AT ARID SITES

R. J. Lenhard
M. A. Gerber
J. E. Amonette

October 1992

Prepared for the
U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

MASTER

SUMMARY

To support the Volatile Organic Compounds-Arid Site (VOC-Arid) Integrated Demonstration (ID) in its technical, logistical, institutional, and economical testing of emerging environmental management and restoration technologies, Pacific Northwest Laboratory^(a) is evaluating several in situ remediation technologies for possible inclusion in the demonstration. The evaluations are made with respect to the initial focus of the VOC-Arid ID: the carbon tetrachloride contamination at the Hanford Site, where it was disposed to the vadose zone along with other volatile and nonvolatile organic wastes, heavy metals, acids, and radionuclides. The purposes of this report are 1) to identify candidate in situ technologies for inclusion in the program, 2) to evaluate the candidate technologies based on their potential applicability to VOC contamination at arid sites and geologic conditions representative of the ID host site (i.e., Hanford Site), and 3) to prioritize those technologies for future U.S. Department of Energy (DOE) support.

Several technological approaches to remediation were identified for potential DOE support. Of the technologies that manipulate subsurface physical properties to affect contaminant behavior and enhance cleanup, three were identified that warrant further investigation and/or investment: 1) subsurface heating to enhance VOC vaporization; 2) barriers; and 3) long-term, low-maintenance, low-energy in situ remediation methods. One technology that can potentially destroy contaminants by directly adding energy was also identified for consideration: in situ corona destruction. Technologies that require chemical reagents to be injected into the subsurface were not selected for consideration because of associated mass transport problems and/or uncertainties. In addition, the chemical injection technologies appear to be ineffective in treating the primary contaminants (i.e., carbon tetrachloride and

(a) Pacific Northwest Laboratory is operated for the U.S. Department of Energy by Battelle Memorial Institute.

related compounds). There are too many unresolved issues with these technologies that will need to be further addressed before these technologies can be deployed in the field. Technologies that stimulate subsurface microbiological activity for the purpose of degrading organic compounds were reviewed and evaluated only in general. It was concluded, however, that bioremediation is a sufficiently promising in situ technology to continue receiving DOE support.

ACKNOWLEDGMENTS

This research was supported by the Volatile Organic Compounds Arid Site Integrated Demonstration Program, Office of Technology Development, U.S. Department of Energy.

The authors thank J. K. Fredrickson and D. J. Workman for providing the information in the biological treatment section, and M. J. Fayer for providing information on barriers.

CONTENTS

SUMMARY	iii
ACKNOWLEDGMENTS	v
1.0 INTRODUCTION	1.1
2.0 REQUIREMENTS, CONSIDERATIONS, AND CONSTRAINTS	2.1
2.1 REQUIREMENTS AND CONSIDERATIONS	2.1
2.1.1 Spatial Distribution of Contaminants	2.3
2.1.2 Moisture Content of Soil	2.4
2.1.3 Composition of Soil Constituents	2.5
2.1.4 Distribution of Subsurface Void Spaces and Their Spatial Variability	2.6
2.2 CONSTRAINTS	2.7
3.0 EVALUATION OF SPECIFIC IN SITU REMEDIATION METHODS	3.1
3.1 PHYSICAL TECHNOLOGIES	3.1
3.1.1 Electrokinetics	3.1
3.1.2 In Situ Electrical Heating	3.4
3.1.3 Barriers	3.6
3.2 CHEMICAL TECHNOLOGIES	3.8
3.2.1 Corona Destruction	3.9
3.2.2 Ozonation	3.10
3.2.3 Redox Manipulation	3.12
3.2.4 Thermal Chemical Degradation	3.25
3.3 BIOLOGICAL TECHNOLOGIES	3.27
4.0 RECOMMENDATIONS FOR ARID SITE IN SITU REMEDIATION TECHNOLOGIES	4.1
4.1 PHYSICAL TECHNOLOGIES	4.2

4.1.1	Subsurface Heating	4.2
4.1.2	Barriers	4.3
4.1.3	Newer Technologies	4.4
4.2	CHEMICAL TECHNOLOGIES	4.4
4.2.1	Corona Destruction	4.5
4.2.2	Chemical Injection In Situ Destruction Technologies	4.5
4.3	BIOREMEDIATION	4.7
5.0	CONCLUSION	5.1
6.0	REFERENCES	6.1

FIGURES

1	Half-Lives of Ozone in Different Waters	2.4
2	Effect of Soil Moisture Content on the Vapor-Phase Sorption of Volatile Organic Compounds to Soil Mineral Surfaces	2.8
3	Effect of Actinide Oxidation State on Adsorption to Oxide Surfaces	2.10

TABLE

1	Theoretical Oxidizing Power of Selected Oxidants in Aqueous Solution	3.17
---	---	------

1.0 INTRODUCTION

The Volatile Organic Compounds-Arid Site (VOC-Arid) Integrated Demonstration (ID) has been established to aid in the cleanup of soils and groundwater contaminated with volatile organic compounds at U.S. Department of Energy (DOE) production facilities located in arid to semiarid climates. The program is designed to support technical, logistical, institutional, and economical testing of emerging environmental management and restoration technologies. The initial focus of the VOC-Arid ID is on the carbon tetrachloride that was disposed to the vadose zone (with other volatile and nonvolatile organic wastes, heavy metals, acids, and radionuclides) at the ID host site (i.e., Hanford Site). Characteristics of the ID host site have been reported by Last et al. (1991).

The purposes of the VOC-Arid ID are the demonstration, testing, and evaluation of characterization, monitoring, and cleanup technologies that address VOC contamination and associated cocontaminants in the vadose and groundwater zones. Regulatory and public concerns that may affect the acceptability of a technology will be factored into the VOC-Arid ID. A primary objective of the program is to transfer cost-effective technologies to the private sector so that they can be employed to mitigate subsurface contamination at DOE sites.

To accomplish the objectives of the VOC-Arid ID, funds are being allocated to support development and field testing of selected technologies. Specifically, in situ remediation technologies have been given a high priority in the VOC-Arid ID. Candidate in situ technologies will be chosen for support based on their potential for improved effectiveness (better, faster, and/or safer) and cost relative to available technologies and their likelihood for successful deployment, technology transfer, and public and regulatory acceptance. The baseline technology system at the Hanford Site for carbon tetrachloride removal from the vadose zone and destruction (which will be the basis for comparing the

cost-effectiveness of remediation technologies) is soil vapor extraction coupled with carbon tetrachloride adsorption on granular-activated carbon (GAC), where the GAC, is periodically regenerated offsite using thermal methods. Any remediation system that has the potential to be more cost-effective than the baseline system, or any technology/technologies that can either augment or replace technologies employed in the baseline system to enhance the cost-effectiveness of the baseline system, will be prime candidates for support. Those technologies receiving support will come from university, industry, and national laboratory proposals. The proposals will be evaluated by Technical Support Groups that will give their recommendations to the VOC-Arid ID.

A definition of in situ remediation technologies, which is in common usage, is remediation technologies that do not require the contaminated soil to be transported offsite. Under this broad definition, many different practices may be classified as in situ technologies. In a survey of the U.S. Environmental Protection Agency's (EPA) Records of Decision, the most frequently employed practice for remediating vadose zone VOC contamination is advectively moving gas through the subsurface to a collection point where the contaminant vapors are treated. This process or technology is commonly called vacuum extraction or in situ vaporization. Soil washing or flushing, chemical reagent injection, bioremediation, and vitrification were also listed as vadose zone in situ technologies. Pump-and-treat technologies were the most frequently employed practices for use in remediating contaminated groundwater in situ. Clearly, the above broad definition of in situ remediation methods encompasses a variety of disparate technologies. Other definitions of in situ remediation technologies are typically more restricted to referring to those technologies that treat the contaminants in place (i.e., the contaminants are not transported out of the subsurface).

A priority of the VOC-Arid ID is to demonstrate those technologies that destroy contaminants where they reside in the subsurface (i.e., in situ destruction technologies). Lesser emphasis is placed on technologies that involve transporting contaminants through the subsurface to a

collection and/or treatment point (i.e., contaminant recovery technologies). The distinctions between these two technologies are that 1) for in situ destruction practices, chemical reagents and/or energy must be transported from an injection point to the contaminants and 2) for contaminant recovery technologies, contaminants are being transported through the subsurface to a centralized location. In both cases, effectively transporting mass and/or energy is crucial for successful deployment of a technology.

Unfortunately, there are few in situ destruction technologies that are in an advanced stage of development. As a consequence, this report will evaluate the applicability of selected in situ remediation technologies, including in situ destruction and some contaminant recovery technologies, for mitigating subsurface VOC contamination at arid to semi-arid sites. A critical component of in situ destruction and contaminant recovery technologies is the transport of contaminants and/or reagents through the subsurface with its spatially variable structure. A focus of the evaluations in this report, therefore, will be transport-related phenomena. Vacuum extraction and/or in situ vaporization technologies will not be evaluated because these technologies are the cost and performance baselines from which other technologies will be compared. However, technologies that may enhance the performance of the baseline technologies will be evaluated in this report. Bioremediation technologies will be discussed only in general.

The information in this report is intended to assist the VOC-Arid ID in choosing appropriate in situ remediation technologies for support by identifying the requirements, considerations, and constraints (Section 2.0) for successful implementation. Selected in situ remediation technologies are evaluated based on their potential applicability to VOC contamination at arid sites and geologic conditions similar to those at the ID host site (Section 3.0). Promising in situ remediation technologies are prioritized for future DOE support (Section 4.0), and the main conclusions of the above exercises are given (Section 5.0). References cited are listed in Section 6.0.

2.0 REQUIREMENTS, CONSIDERATIONS, AND CONSTRAINTS

In situ remediation technologies should not induce adverse side effects and should be effective when spatial heterogeneities in subsurface properties exist. For example, the technologies should not increase the mobility of contaminants unless it is accounted for in the remediation design. Furthermore, the technologies should not create more hazardous and/or refractory compounds. The technologies must also be able to operate in a remote, unconfined setting, and the costs to transport reagents and/or to supply the necessary energy to treat the contaminants must be favorable when compared to costs associated with the baseline remediation system. Using these guidelines, this section discusses general requirements, considerations, and constraints of VOC in situ remediation technologies in arid and semiarid sites.

2.1 REQUIREMENTS AND CONSIDERATIONS

The applicability and regulatory acceptability of any technology for the destruction of a specific compound depend on achieving suitable reaction rates under the existing operating conditions. If reagents are added to the subsurface, they 1) should react primarily with the contaminants, 2) should not be consumed by soil constituents, 3) should not inhibit natural microbiological activity, and 4) should not enhance the mobility of any contaminants and/or cocontaminants that are not being specifically treated.

After reagents are injected, they will need to be transported through the subsurface from the point of injection to the contaminants. This distance can be variable, depending on site characteristics and contamination history. Reagents, therefore, should be stable under subsurface conditions, because their lifetime expectancies need to be considerably longer than their transport time to the contaminants. Developing a multitude of injection wells to shorten transport distances would be uneconomical because of the high drilling costs.

Transporting reagents, heat, and/or electricity through the subsurface can be nonuniform. Because of spatial heterogeneity in subsurface properties, preferred migration pathways may exist that yield irregular distribution patterns. These patterns are difficult, if not impossible, to predict a priori. The result may be spotty and incomplete treatments. Treatment technologies need to consider the effects that spatial heterogeneity may have on the effectiveness and cost of their processes. Transport issues may be the most critical component of in situ destruction and contaminant recovery strategies.

Consideration also needs to be given to subsurface microorganisms. Ecological and geologic evidence suggests that by changing subsurface properties, either by human-induced or natural mechanisms, microorganisms will likely be impacted. Before deploying any subsurface remediation technology, synergistic and antagonistic effects of that technology on the subsurface ecology should be considered. Treatment methods should be concerned with stimulating biological activity near injection or treatment areas because the natural flow channels could become clogged with biological growth, which may adversely affect the ability to transport chemicals or to treat the contaminants.

Clearly, constraints placed on the in situ application of remediation technologies are large. In situ restoration of aquifers and deep vadose zone sediments to their original state may not be technically feasible because of the tremendous difficulty in achieving contact between the treating agent and the contaminant (Mackay and Cherry 1989; Travis and Doty 1990). Furthermore, any hope of successful in situ remediation will require thorough site characterization before, during, and after treatment because of the complexity of the subsurface. Decisions as to which technology is appropriate, if any, will depend on the site-specific nature and distribution of the subsurface voids (i.e., flow channels), solid-phase surface chemistry, fluids, and contaminants.

Some of the more important considerations are 1) location and accessibility of the contaminants, 2) moisture content of the soil,

3) composition of the soil constituents, and 4) distribution of subsurface void spaces and their spatial variability.

2.1.1 Spatial Distribution of Contaminants

The spatial distribution of the contaminants affects a technology's ability to be effective. For treatment technologies where the addition of reagents to the soil is required, it may not be practical to physically mix the soil to bring reagents into contact with the contaminants. Techniques that are commonly employed to bring injected reagents into contact with contaminants include imposing concentration and hydraulic (pneumatic) gradients. Concentration gradients will cause chemicals (i.e., reagents) to diffuse, which will tend to produce uniform concentrations in time. However, chemical diffusion can be very slow in porous media, particularly in arid soils where the compounds must migrate through a myriad of tortuous water pathways because of low water contents. Gaseous diffusion in arid soils will be significantly more rapid in the vadose zone. Another consideration is that the rate of reagent diffusion needs to be much faster than the rate of reagent depletion by autodecomposition. Furthermore, the reagent should not be consumed by or adsorbed on the soil constituents. Relying on diffusion processes, rather than physical mixing, to achieve remediation means that the use of relatively short-lived reagents such as ozone may not be effective. For example, the hydroxyl-catalyzed decomposition of ozone in groundwater can decrease the ozone concentration by 90% in less than 2 hours (Figure 1). Maintaining a hydraulic gradient under high moisture contents for water-dissolved reagents or imposing a gaseous pressure gradient for gaseous reagents can decrease the time required to transport a dissolved reagent a given distance because chemical movement occurs via advective and dispersive fluid flow, not just chemical diffusion. However, variations in soil-pore structure and the presence of manmade channels (e.g., drill holes) may result in uneven and ineffective reagent distribution.

FIGURE 1. Half-Lives of Ozone in Different Waters
(after Staehelin and Hoigne 1982)

2.1.2 Moisture Content of Soil

The low moisture content of unsaturated soils introduces several constraints to in situ treatment. The first of these constraints is that technologies that operate at ambient pressure and temperature were, in large part, developed from water-treatment processes and, consequently, require an aqueous environment. The lack of moisture, therefore, may adversely affect the efficiency of these techniques, with the possible exception of gaseous reagents. The second constraint is that the lack of water impedes aqueous reagent transport. Chemicals move through dry soils at rates orders of magnitude slower than those in wet soils. Injecting water to enhance movement of dissolved chemicals is, however, somewhat risky. The addition of water might compound the contamination problem by flushing some of the contaminants deeper into

the subsurface. Aqueous-phase treatment of the vadose zone could be critically linked to the development and demonstration of effective subsurface barriers and containment structures.

Chemical reagents can be transported via advective and/or diffusive mechanisms. In advective transport, the compounds are carried along with the flowing gas and/or the water. Movement of the fluids is effected by imposing a pressure gradient within a fluid phase. Because fluid velocities in soil pores vary according to pore sizes, dispersive chemical mixing occurs. For arid sites, where water contents tend to be low, gaseous flow is likely to be more effective and economical in transporting reagents. In diffusive transport, the difference in concentration gradients is the driving mechanism for chemical migration. Typically, diffusive transport also occurs in dispersive mixing. Diffusion of chemicals dissolved in water will be very slow in the subsurface; it could take years for chemicals to move several meters at arid sites. Diffusion of chemicals in the gaseous phase will be more rapid.

2.1.3 Composition of Soil Constituents

The mineral composition and organic matter content of the soil can also have potentially significant effects on all chemical treatment processes. Many soil minerals can either catalyze or inhibit oxidation, reduction, free-radical, and hydrolytic reactions. For example, structural iron in oxides and layer silicates can catalyze the decomposition of hydrogen peroxide, and they are reactive to oxidation and reduction processes. Calcite would be expected to inhibit free-radical reactions because of the scavenging action of the carbonate and bicarbonate ions. Humified organic substances are also highly reactive. Therefore, significant quantities of the redox reagents can be consumed by substances other than the target contaminants. These same soil constituents (i.e., organic matter, calcium carbonate, and iron-containing minerals) can act to buffer the soil pH and Eh, which will affect oxidation and hydrolysis reactions. To overcome these effects, an excess amount of reagent may be needed to treat target contaminants and could be uneconomical or impractical/deleterious.

2.1.4 Distribution of Subsurface Void Spaces and Their Spatial Variability

The movement of chemicals (i.e., reagents and contaminants) through the subsurface can occur in irregular patterns that cannot be accurately predicted a priori. This can result from instabilities in fluid flow but occurs more commonly because of spatial heterogeneities in flow-channel structure. Fluid flow is said to be unstable when a small disturbance imposed on the flow field grows and dominates the state of flow at later times (Yih 1988). There are several situations that cause fluid-flow instabilities to develop. For example, if an invading fluid is displacing another immiscible fluid downward and the invading fluid has a mass density higher than that of the displaced fluid, then the displacement is likely to be unstable. A large difference in viscosities between immiscible fluids may also promote instabilities where the less viscous fluid invades the region occupied by the more viscous fluid. Reviews of laminar flow instabilities can be found in books describing fluid flow (Bear 1972; White 1991).

Irregular flow, which bears a resemblance to unstable flow, can occur because of geologic layering and soil-property-dependent phenomena. The result is subsurface regions that possess different networks of voids or flow channels. The dimensions of these layers or regions are variable (i.e., from only a few millimeters to several hundred meters thick). Because of differences in porous media properties, even the smallest layers may have a significant influence on flow regimes. In addition, contaminants may be retained in some layers to a greater extent than in other layers. This is particularly true for many VOCs. In some layers, the majority of fluid flow will be conducted in only a few channels or preferred flow paths. In other regions, fluid flow will be uniformly distributed. It is very difficult to predict such behavior because the flow-channel structure (and, hence, its spatial distribution) is seldom known in advance and/or in sufficient detail. The uncertainty in predicting flow behavior suggests that the addition of appreciable quantities of fluids to the subsurface as part of remediation

efforts may be risky. Flow may occur very uniformly in a controlled manner or may be very irregular. The latter can transport contaminants deeper into the subsurface or into other layers where they may be more difficult to treat chemically or to extract.

2.2 CONSTRAINTS

In addition to the above considerations, contaminants possess properties that place additional constraints on in situ treatment. These include volatility, aqueous solubility, reactivity, and cocontaminants.

VOCs, by definition, are volatile. When in the vadose zone, a significant fraction of their mass may be in gaseous form at ambient temperatures. Technologies that address chemical destruction of VOCs dissolved in water may have only minor impact on the vadose zone VOC content. Technologies that increase subsurface temperatures will further promote the transfer of VOCs from a liquid to a gaseous state. However, in regions where the temperature is lower than that in adjacent regions, VOCs may condense out of the vapor phase and there could be a migration of VOCs from regions of higher temperature to regions of lower temperature. Potential VOC migration patterns need to be considered before any VOC remediation technology is employed or else deleterious results may occur.

The combination of volatility and low water solubility makes the transport of the alkyl-halide compounds in unsaturated soil systems very difficult to predict. Thorough site characterization and careful assessment of the possible secondary effects of reagent additions need to be conducted. One particularly critical factor is the amount of water that is adsorbed to soil surfaces. If the soil is very dry, the partition coefficients of VOCs on soil mineral surfaces may be several orders of magnitude larger than when the soil is moister (Peterson et al. 1988; Ong and Lion 1991). The addition of bulk water to a dry soil that is contaminated with alkyl halides would be expected to result in the desorption of nearly all the alkyl halides by a competitive process. Of

the desorbed compounds, a small fraction would be solubilized and carried along in the water, while a larger amount would be released into the vapor phase. In both instances, further transport of the compounds would occur. On the other hand, if enough alkyl halide were present to form a separate bulk phase, it may be retained by capillary forces in a manner similar to a trapped air bubble in water (Cary et al. 1989).

The relation between vapor adsorption and moisture content is summarized in Figure 2. From this relationship, it can be deduced that the optimum moisture content (from the standpoint of simultaneously minimizing VOC transport in the aqueous phase and VOC adsorption to the solid phase) would be about 25 to 35% of field capacity, which is hypothesized

FIGURE 2. Effect of Soil Moisture Content on the Vapor-Phase Sorption of Volatile Organic Compounds to Soil Mineral Surfaces. Moisture content for Region 1 ranges from an oven-dried mineral surface to a single monolayer of adsorbed water, Region 2 from a single monolayer to about five monolayers of adsorbed water, and Region 3 from five monolayers of water to field capacity (after Ong and Lion 1991).

to correspond to a film of water about five monolayers thick (Foth 1990; Ong and Lion 1991). This water content or water-film thickness, however, would be a function of the particle-size distribution of the subsurface strata. Clearly, coupling enhanced recovery technologies with effective chemical destruction technologies at appropriate subsurface moisture contents would minimize the transport of the alkyl halides to groundwater.

In many of the contaminated DOE sites, there will be inorganic cocontaminants that will need special consideration. Inorganic chemicals such as chromium, cesium, strontium, and the actinides (uranium, plutonium, and americium) may be as or more hazardous than the VOCs. Reagents that are added to the subsurface to treat alkyl halides may react with these inorganic chemicals and/or soil constituents to alter their speciation and, consequently, their mobility in geologic media. This is a very important regulatory issue that will need to be addressed. Increased mobility of radionuclides as a secondary effect of VOC chemical treatment could be catastrophic unless such mobility is carefully considered and designed in the remediation strategy. Processes that alter the redox state of these elements are of particular concern. For example, oxidation of chromium and the actinides to the hexavalent state would increase their solubility and mobility in soils. Reduction of chromium would likely produce a relatively insoluble hydroxide, which would tend to immobilize it. Effects of actinide reduction in soils are more difficult to predict. If, in the actinide reduction, the soil constituents that are largely responsible for chemical adsorption (i.e., iron oxides and layer-silicate edge sites) were not adversely altered, the actinide mobility would be expected to decrease because of increased adsorption affinity at lower pH (Figure 3). However, reductive dissolution of soil iron oxides would decrease the number of adsorption sites and thus lower the soil's capacity to attenuate actinides. Furthermore, remediation techniques that raise the dissolved carbon content (organic and inorganic) would increase the mobility of actinide species by

FIGURE 3. Effect of Actinide Oxidation State on Adsorption to Oxide Surfaces (gamma-alumina). Solid lines refer to thorium(IV), americium(III), and neptunium(V) adsorption, and open circles are data for plutonium(V) (from Bidoglio et al. 1989).

forming soluble complexes. This may occur if calcium carbonate, which is a common secondary mineral at arid sites, dissolves as a result of treatment.

The physical effects of remediation treatments on cocontaminant mobility also need to be considered. For example, the frothing action of hydrogen peroxide might encourage the mobilization of colloids that have contaminants adsorbed to their surfaces. Most of the concerns about cocontaminant mobilization arise when aqueous reagents are used for remediation in saturated or near-saturated soils. When gaseous reagents are used to remediate unsaturated soils, the potential for mobilizing other contaminants present is relatively small, regardless of changes in speciation.

3.0 EVALUATION OF SPECIFIC IN SITU REMEDIATION METHODS

The requirements, considerations, and constraints described in Section 2.0 were factored into the evaluation of specific in situ remediation technologies in this section. For simplicity, the technologies are grouped into three categories: physical, chemical, and biological. The placement of a given technology into one of these three groups was subjective because some technologies can be characterized as relating to more than one category. The evaluations are based on conditions likely to be encountered for VOC contamination at arid to semiarid sites. Because the technologies reviewed in this report are not meant to be inclusive of all the technologies that may be applicable, omission of a technology does not imply that the omitted technology will be unsuccessful in mitigating VOC contamination at arid to semiarid sites.

Where appropriate, applicability to carbon tetrachloride subsurface contamination is given because it is the initial priority at the ID host site. Carbon tetrachloride and other alkyl-halide cocontaminants at the ID host site are largely unreactive. They have low heats of combustion, have no flash points, and are classified as nonflammable.

3.1 PHYSICAL TECHNOLOGIES

The physical technologies evaluated in this subsection are electrokinetics, electrical heating, and barriers.

3.1.1 Electrokinetics

Electrokinetics involve inducing an electrical field through the subsurface whereby electrically charged ions and/or particles (i.e., colloids) migrate toward electrodes of opposite charge. A low direct current is passed through the soil between the positive and negative electrodes. This causes ions, water molecules, and charged particles to move in response to the imposed electrical field. Positively charged mobile substances will migrate toward the cathode, and negatively charged mobile substances will migrate toward the anode. There are

several types of electrokinetic phenomena. The one that appears to have the greatest applicability to organic chemical treatment in the vadose zone (Gerstl et al. 1989) is electro-osmosis, which applies to water migration induced by an imposed electrical field.

It has been proposed that electrokinetics can be used to direct contaminant movement within the vadose zone to certain localities where they may be removed or treated, to facilitate treatment or removal of adsorbed contaminants, and to create barriers to contaminant flow. Contaminant movement can be directed in the vadose zone by injecting water at the anode and extracting water at the cathode. Water will move in an electrical field toward the negatively charged electrode. This will establish a flow field where contaminants between the electrodes are leached toward the cathode. The injection procedure, however, needs to be carefully controlled or the contaminants may migrate beyond the electrical field, resulting in contaminant escapement from the treatment area. This is important particularly if some of the contaminants are radionuclides. Another possible procedure would be to develop an electrical field whose direction and intensity will counter prevailing hydraulic gradients. This can serve as a barrier to contaminant flow.

The success of using electrokinetics to treat contaminated sites will depend greatly on the subsurface moisture content (i.e., on the ability to establish and maintain an electrical field) and on the chemical structure of the contaminants. Electrokinetics appear to be more successful in conditions where the resistance to electrical current is low, which would occur in water-saturated soils. If the subsurface moisture content is low, then contaminants will have to follow a very tortuous route to the electrode and the resistance to electrical current will be high. The travel path length of a charged contaminant depends on the moisture content. For lower moisture contents, the path length can be as high as an order of magnitude greater than for moister soils. A longer path length implies a longer remediation period. A high electrical resistance will also tend to generate more heat and be less effective in mobilizing charged contaminants. Furthermore, the moisture content is likely to be highly variable because of subsurface spatial

heterogeneity in pore structure. This might result in preferred pathways for the flow of electrical current and might affect the cost of supplying the necessary electrical energy. Spatial heterogeneity might also affect how contaminants are distributed in the subsurface (i.e., where the contaminants are likely to be found). Hence, the cost of maintaining an effective electrical field for contaminant movement in drier sites is likely to be significantly higher than for moister sites.

For an electrical field to induce movement of ions and/or particles, those substances need to be charged and/or polar. The dipole moments for VOCs, which are measures of the polar nature of compounds, are typically low. Therefore, VOC migration induced by a direct electrical field is likely to be negligible. Nonpolar molecules can have an induced polarity; however, it is short lived. The polarization of electrons in an atom depends on how tightly the electrons are held by the nucleus. Most chlorinated hydrocarbons can be slightly to moderately polarized. Electrokinetics appear to be promising only for charged chemicals such as metals or polar compounds, and may also be successful in mobilizing radionuclides and polar organic compounds. Nonpolar organic compounds can be mobilized indirectly by creating a water-flow pattern between the electrodes as previously discussed.

The migration of the charged compounds and/or particles because of an induced direct current largely occurs within the aqueous phase. The conducting medium under a low current would principally be the aqueous phase. Compounds in the gaseous phase would be negligibly affected by the direct current. Hence, the contaminants of interest need to be dissolved in the aqueous phase and have an electrical charge for electrokinetics to be effective.

In summary, because VOCs typically 1) have a significant amount of their mass in the gaseous phase, 2) have low solubilities, and 3) are relatively nonpolar, the use of electrokinetics to remediate VOCs is questionable. Further investigations are needed to evaluate the suitability of electrokinetics for remediating VOCs in the vadose zone.

3.1.2 In Situ Electrical Heating

It has long been known that heat will be generated when a current is passed through an electrically conductive material. This is commonly termed resistive heating. If the current is increased, more heat will be generated. Very high temperatures can be obtained in this manner by regulating an electrical current through a material. The two principal factors in producing heat via electricity are the electrical current (i.e., amperage) and the resistance of the material. As either of these variables is held constant while the other is increased, a greater amount of heat will be generated.

In electrokinetics, a small amount of heat is created because a low current is passed through the soil between the two electrodes. In in situ electrical heating, the potential difference between the two electrodes is greater than in electrokinetics, producing a larger current. Assuming the soil resistance to be the same under both practices (i.e., electrokinetics and in situ electrical heating), the effect would be an increase in the amount of heat being transferred to the subsurface for the in situ electrical heating technique. Assuming that the soil remains electrically conductive, the current can be increased to yield high subsurface temperatures. In in situ electrical heating, alternating current is commonly employed in lieu of direct current. The application of alternating current will have a negligible effect on the movement of charged ions and/or particles any appreciable distances.

The underlying motives for increasing subsurface temperatures are 1) to affect chemical reaction rates and changes in equilibrium concentrations, 2) to influence fluid phase behavior, and 3) to increase biological activity. Chemical reaction rates almost invariably increase with a rise in temperature. The rate constants increase exponentially with temperature. Equilibrium concentrations also change with temperature. An increase in temperature typically increases the equilibrium constant for endothermic reactions and decreases the equilibrium constant for exothermic reactions. Consequently, VOCs adsorbed on solid surfaces may partition to a greater extent in water when the temperature

is increased. Organic liquid- and aqueous-phase VOCs will also volatilize more readily when the temperature is increased. This can significantly aid in removing VOCs from the subsurface via enhanced contaminant recovery technologies such as vacuum extraction. Greater biological activity is also likely when subsurface temperatures are increased. This may result in increased biodegradation of contaminants if electron donors and acceptors, nutrients, and substrates are available. However, if the temperatures become too high, biota may be destroyed. Generally, in situ heating is used to complement other remediation technologies to make them more efficient.

The successful application of electrical current to heat subsurface strata largely depends on maintaining an electrically conductive medium. A critical factor in this regard is the subsurface moisture content. In sandy geologic material, the electrical current is primarily conducted by the aqueous phase. In clayey material, more of the current is carried by the solid phase because clays, through isomorphic chemical substitution, have a net negative surface charge. Nevertheless, the water content needs to be such that the strata are electrically conductive in all geologic media. The ability to conduct electricity or heat in soils generally decreases exponentially with decreasing moisture content. This has practical implications at arid sites because the subsurface moisture contents are typically low, except near the water table. More energy will be required to maintain an electrical current in porous media with lower moisture contents. Research and development are currently in progress to resolve distributing electrical currents uniformly through dry geologic material. Recent electrode design features appear to be promising; however, they have not been fully field tested under varying conditions.

Subsurface heterogeneity may play an important role in successfully conducting an electrical current through unsaturated soils. Very rarely are natural geologic formations uniform. With regard to in situ heating, electrical current may flow only through subsurface regions with higher moisture contents. This may produce irregular heating patterns and could result in spotty treatment. Subsurface heterogeneity or

spatial variability needs to be evaluated for site-specific locations. Effects of spatial variability on conducting electricity through porous media need to be better understood; more fundamental investigations are needed before accurate predictions can be synthesized.

Any additions of water to make the soil more conductive need to be effected very carefully. Because of spatial heterogeneity, supplemental water may by-pass the treatment area and transport contaminants deeper into the subsurface, where they may be more difficult to remediate. Studies of enhanced radionuclide mobility need to be conducted before electrical heating is applied to sites that have radionuclides as cocontaminants.

In summary, further studies are warranted at field sites to delineate water contents necessary for economic deployment of in situ electrical heating and to evaluate the effects that soil heterogeneity has on electrical current and heat propagation. In situ electrical heating can be an effective technology that can promote partitioning of liquid and adsorbed VOCs to the gaseous phase, where they may be removed from the subsurface via enhanced contaminant recovery technologies. An in situ heating project is currently funded by the VOC-Arid and Nonarid IDs. In the in situ heating project, some of the outstanding issues discussed above are being investigated.

3.1.3 Barriers

In the context of environmental restoration and waste management, barriers are physical, chemical, and/or biological impediments to the movement of water, gas, heat, contaminants, plants, animals, or humans. Barriers can be used to stabilize contaminants in place, direct contaminant movement, enhance treatment, immobilize or destroy contaminants, or prevent biological access to the contaminants. Barriers that have been incorporated into the design of the disposal site prior to disposal typically function more effectively than barriers constructed following site contamination. An example is a landfill liner, which is a barrier that can prevent the downward movement of water and can serve as a flow diverter or collection device. The types of barriers that can be

incorporated into an already contaminated zone in a manner that expedites in situ remediation or stabilization are addressed in the following discussion.

The appropriate barrier(s) to use will depend on the site, contaminant(s), and goal of barrier emplacement. For vadose zone contaminants, a surface barrier could be emplaced to prevent water recharge to groundwater. This will minimize aqueous-phase advective contaminant transport below the barrier, which will reduce the contaminant flux to the groundwater. Although natural water recharge at arid to semiarid sites is small, over time a significant contaminant influx to groundwater could result without a surface barrier. However, a surface barrier may not affect the migration of gaseous-phase contaminants, which may be a major transport mechanism for VOCs in the vadose zone.

Contaminants in the vadose zone might also be isolated using walls such as grout curtains, vitrified sediments, or slurry walls, which might enhance vapor extraction technologies. In some situations, it may be feasible to vitrify (i.e., fuse into glass) the sediment beneath the waste site, thus creating an impermeable zone that would prevent additional downward movement of the contaminants. In the same manner, vertical walls of vitrified sediment could serve the same function as a grout curtain. For sites with significant groundwater contamination, bentonite slurry walls or grout curtains could be emplaced to either contain the contaminated water or divert it toward a collection system. Water could be pumped into surrounding wells to create a hydraulic wall to control the direction of contaminated groundwater flow. Also, temporary barriers could be constructed to direct contaminant flow.

Barriers can be constructed of, or impregnated with, material to which the contaminants preferentially bind. Clay mats, used as liners, serve as locations for contaminant sorption because clays have a very high sorption capacity. Slurry walls or grout curtains might be made to contain components that neutralize specific contaminants, either chemically or biologically.

The determination of which barriers are most appropriate for the VOC-Arid ID depends on an evaluation of the feasibility of construction, cost, expectation of effectiveness, and value. To some degree, all of the barriers discussed are conceptually feasible, but none have been demonstrated at the scale of the vadose zone at the Hanford Site (i.e., 70 m thick and with an unknown lateral extent of contamination).

All of the permanent subsurface barriers involve significant construction expense and entail much concern about spreading of contaminants as a result of construction. Barriers are generally expected to be effective, except when the barrier must be constructed in discrete units such that the seams between units might be failure points. Examples are clay mats, vitrified barriers, and geotextiles. Temporary barriers (e.g., high water or pressure zones) could be formed using infiltration ponds or new or existing wells. However, the effectiveness of temporary barriers would be difficult to ensure given the heterogeneous nature of the subsurface. A hydraulic barrier for directing groundwater flow might be an option. Past practices at the Hanford Site have shown that surface ponds raise the water table and significantly alter groundwater flow paths and rates.

In summary, the ability to form large-scale subsurface barriers that are impermeable to contaminants has not been demonstrated. Rather, the greatest utility of subsurface barriers lies in their ability to control flow rates and directions, which could complement other remediation technologies. An impermeable surface barrier, such as an asphalt layer, could be used to enhance vapor extraction while minimizing downward water movement. Studies of groundwater contamination by VOCs beneath surface barriers at arid to semiarid sites are needed to evaluate the benefits of surface barrier emplacement.

3.2 CHEMICAL TECHNOLOGIES

The specific chemical technologies evaluated in this section are corona destruction, ozonation, redox manipulation, and thermal chemical

degradation. Hydrolysis, oxidation, reduction, and free-radical degradation processes are considered under redox manipulation technologies.

3.2.1 Corona Destruction

In situ corona destruction is similar in many respects to in situ electrical heating. In both, an alternating current is passed through the subsurface. With in situ corona destruction, however, a plasma (i.e., ionized gases that have unusual physical and chemical properties) develops from electrons being accelerated in the induced electrical field. As the electrons attain sufficient energy, they ionize gas molecules. This causes a progressive effect where extensive breakdown of the gas occurs. The plasma consists of charged positive ions and electrons, which are continuously forming free radicals that are highly reactive. The plasma, however, is considered to be neutral.

The initiation of the plasma occurs after water near the electrodes vaporizes because of resistive heating. This reduces the moisture content and increases the electrical resistance in this region. The net result is the development of a large potential voltage difference with distance over this area. It is this potential voltage gradient, or electrical field, that produces a plasma. High-voltage equipment, therefore, is required to generate plasmas.

The mechanism for subsurface plasma propagation is believed to be associated with the movement of the large voltage gradient away from the electrodes. The drift of the electrons, however, is ultimately responsible for the conductivity of the plasma (McTaggart 1967). As water farther from the electrodes vaporizes, the spatial position of the large voltage gradient that produces the plasma also migrates away from the electrode. In this manner, it is conjectured that a highly reactive cloud of ionized gases can be transported through the subsurface. It is hypothesized that organic compounds (i.e., contaminants) will also vaporize and will be broken down into elemental units (e.g., carbon dioxide, water, etc.) by the plasma. For chlorinated organic compounds, either hydrochloric acid or chlorine gas may be produced. It is unclear at this time what compounds may be produced from contact with a plasma

in the subsurface because of the complex chemistry of contaminated sites. More quantitative studies are needed to assess the stoichiometry and kinetics of possible chemical reactions.

The successful deployment of a plasma to treat VOCs in situ depends on several factors. Of these factors, two are critical as they address the uniform treatment of an area and regulatory concerns: 1) the economical maintenance of the corona in the subsurface in heterogeneous geologic strata and 2) the effects the corona may have on the mobility of heavy metals and/or radionuclide cocontaminants. For this technology to be effective, the corona needs to be economically transported through structurally heterogeneous subsurfaces so that a uniform, not patchy, treatment results. Furthermore, the mobility of heavy metals and/or radionuclides should not be enhanced unless methods for recovering the radionuclides are considered. Finally, in situ corona destruction needs to be employed in conjunction with an enhanced recovery technology. Contaminant vapors that do not contact the plasma need to be removed from the subsurface so they will not escape to the atmosphere or partition back into the aqueous and/or solid phases and be sources for groundwater contamination. A disadvantage of this technology is that the processes may adversely impact biological organisms, particularly microorganisms that degrade contaminants. This is true for any remediation technology that generates high temperatures.

In summary, in situ corona destruction is a promising technology that can be used in conjunction with an enhanced recovery technology to treat vadose zone VOC contamination at arid sites. Plasma development, propagation through the subsurface, and the effects of these processes on heavy metal/radionuclide mobility are not well understood. Further research and development are needed for the technology to be employed at contaminated sites where regulatory acceptance is required.

3.2.2 Ozonation

Ozone can be used to oxidize organic compounds. It is a strong, but unstable, oxidant and is used to sterilize surgical instruments. It is also used in Europe to disinfect drinking water in lieu of chlorine.

For ozone to be effective in an in situ destruction technology, it will need to be injected into the subsurface, via drilled injection wells, and be transported to the contaminants. The ozone can be injected as a dissolved reagent in the aqueous phase or as a gaseous-phase reagent. Assuming spatial heterogeneities will not be a problem, it will take some time to transport ozone to the contaminants, particularly if they are located any appreciable distance from the injection point. If the lifetime expectancy of either dissolved ozone or gaseous ozone is short, then the method is not likely to be effective. Considering costs associated with drilling near contaminated sites, the number of injection wells needs to be minimized.

A major limitation of using ozone as an in situ oxidation reagent is that it decomposes rapidly when dissolved in aqueous solutions. Up to 90% of the ozone would be expected to decompose in less than 2 hours in typical carbonatic subsurface water. The decomposition of ozone in gaseous form is not as rapid as when dissolved in water but is still unstable.

Another important consideration of applying chemical oxidation methods to natural subsurface geologic material is that subsurface strata may contain significant quantities of inorganic and naturally occurring organic constituents. These naturally occurring constituents can be as easily oxidized by injected oxidizing agents as can the target compounds. For example, ferrous iron in soil minerals can consume any oxidant, which can make any oxidation treatment of contaminants relatively inefficient. Furthermore, cocontaminants may be oxidized into a more mobile state and be transported deeper into the subsurface.

In summary, injecting ozone to oxidize carbon tetrachloride does not appear to be effective at ambient conditions. Additional studies of lifetime expectancies and oxidizing power of ozone, oxidation effects on cocontaminants and microorganism populations, and economical in situ ozone synthesis are warranted. Although ozonation does not appear to be

an effective in situ remediation technology, it may be an effective and economical ex situ technology, where its life expectancy and mixing are not likely to be problems.

3.2.3 Redox Manipulation

In situ remediation of VOCs by alteration of the redox environment can be achieved either directly, by adding suitable chemical agents (oxidants or reductants), or indirectly, by fostering the growth of specific types of microorganisms. Direct chemical redox manipulation is discussed in this section, wherein the overall premise is that a reagent can be added to the subsurface and be transported to the contaminants. The reagents then react with the contaminants, either to alter their mobilities or to destroy them. However, seldom do subsurface conditions exist that lend themselves to uniform chemical mixing. Subsurface physical and chemical spatial heterogeneities will strongly affect chemical mixing and the effectiveness of the process. In the following subsections, hydrolysis, oxidation, reduction, and free-radical degradation processes with regard to VOCs are discussed. The applicability of the processes to chlorinated hydrocarbons at the ID host site will be discussed where appropriate.

3.2.3.1 Hydrolysis

In the strict sense, hydrolysis is a reaction between a compound and water that results in a splitting of the water molecule and the decomposition or alteration of the compound. Organic hydrolysis, however, is more broadly defined to include reactions in which components of water (i.e., protons and hydroxyl ions), rather than the complete water molecule, may be reactants. For example, the addition of a base to a solution and the subsequent formation of the alkali salt of an organic acid are described as hydrolysis. The use of hydrolysis as a remediation treatment is specific to compounds that are relatively reactive with water. Commonly encountered reactive compounds include metal alkoxides, metal amides, carbides, cyanates, halides, hydrides, oxyhalides, reactive metals, silanes, sulfides, nitriles, amides, esters, and some organic halides (Unterberg et al. 1987; Freeman 1989). In general,

hydrolysis of organic compounds results in the formation of intermediate products rather than a complete decomposition to innocuous compounds.

All the alkyl-halide compounds of the ID host site are susceptible to hydrolysis to varying extent. Maskarinec et al. (1990) conducted experiments to determine the maximum length of time that ground- and surface-water samples could be held prior to analysis without significant changes in concentrations of various contaminants, including alkyl-halide VOCs. Although this work was not specifically directed toward the determination of the rates of hydrolysis of these compounds, the results do indicate measurable rates of degradation caused by hydrolysis. At room temperature, 1,1,2-trichloroethane had the fastest decomposition rate and carbon tetrachloride the slowest of the alkyl-halide VOCs of interest in this report. In fact, after starting with a concentration of $65 \mu\text{g L}^{-1}$, almost complete decomposition of trichloroethane in distilled water was observed in 1 year. In general, slower rates of decomposition were observed with lower alkyl-halide concentrations. Lower decomposition rates were also recorded for natural water samples. Maskarinec et al. (1990) noted that the slower rates in the natural water samples could have been caused by the inhibitory mass-action effect of chloride ions in the waters but that differences in pH, carbonate content, and possibly microbial activity could have been factors. Also in their studies, Maskarinec et al. (1990) observed the production of intermediate products. For example, the hydrolysis of tetrachloroethane produced trichloroethylene, and hydrolysis of trichloroethane produced a concomitant increase in the concentration of dichloroethylene.

The Hazardous Materials Control Research Institute (HMCRI 1987) summarized data developed by Radding et al. (1977), Mabey and Mill (1978), and Callahan et al. (1979), which showed the half-lives of a number of alkyl halides in water at a pH of 7. Half-lives reported for some of the alkyl halides of concern are:

- carbon tetrachloride (1000 ppm) 7 years
- carbon tetrachloride (1 ppm) 7000 years

- chloroform 3500 years
- 1,1,1-trichloroethane 0.5 year
- methylene chloride 704 years.

Hydrolysis of less-reactive compounds can be accelerated by increasing heat and pressure, by adding metallic or enzymatic catalysts, or by altering the pH to more favorable conditions. Alkyl halides, which include the above hydrocarbons, generally react according to the equation

where R is the hydrocarbon radical and X is the halide. In some instances, a parallel reaction can also occur according to the equation

where M is a metal such as sodium.

Application of mass-action principles to Equations (3.1) and (3.2) suggests that alkyl-halide hydrolysis reactions are more favorable at high pH than at low pH. Experimental results support this hypothesis for some of the alkyl halides. For example, the HMCRI (1987) summary confirms that chloroform hydrolysis is accelerated by increasing pH but methylene chloride hydrolysis is not. Conversely, the addition of hydrochloric acid or sodium bisulfate to achieve a pH of 2 consistently decreased the hydrolysis rate for the alkyl halides studied by Maskarinec et al. (1990).

Alkaline-earth and transition-metal cations (e.g., magnesium, copper, manganese, and cobalt) have been reported to catalyze hydrolysis

reactions, presumably by affecting hydroxyl ion concentrations (Mabey and Mill 1978; HMCRI 1987). If so, then relatively high concentrations of these metals would be required to produce a significant increase in the reaction rate.

Increasing the temperature may also increase the rate of hydrolysis. Techniques that have merit are microwave heating, electrical heating, and hot-gas convection through the subsurface. These methods, however, should result in significant volatilization of VOCs, which would require a vapor collection system to be incorporated into the remediation plan. As a general rule, the reaction rates in solutions near room temperature increase approximately 2.5 times for an increase in solution temperature of 10°C. This trend was observed by Maskarinec et al. (1990) for the hydrolysis of several alkyl halides in distilled water and surface-water samples at 4°C and 25°C. Similar experiments by these investigators with groundwater samples, however, did not produce conclusive trends, suggesting the presence of other countervailing factors. Accelerating hydrolysis reactions by one or more orders of magnitude, however, could make such a scheme attractive.

One of the greatest areas of uncertainty in applying hydrolysis to contaminated soil systems is that the effects of the soil-surface chemistry are not fully known. Factors that may affect the hydrolysis rates are the pH at the soil-particle surfaces, the presence of metal oxides in the soil, the adsorption of the organic chemical to soil surfaces, and the soil-water content. For example, in an acid soil, the pH at the soil surface can be as much as 4 pH units lower than in the bulk water phase (Dragun 1988). On the other hand, an unsaturated soil will tend to concentrate the organics at soil mineral surfaces, which may act to catalyze the hydrolysis reaction.

In summary, in situ remediation technologies that incorporate hydrolysis of the alkyl halides have not been proposed or applied (though hydrolysis undoubtedly occurs in natural aqueous systems), most likely because of the relatively slow reaction rates for these compounds. To make the process attractive, methods for accelerating the in situ

reaction need to be developed and applied. It is likely that specific aqueous reagents will need to be added or the temperature of the subsurface increased. For the addition of metal catalysts such as copper, low solubility and potential toxicity will be primary constraints. Solubility is less of a constraint for the addition of pH modifiers. Increasing the pH of the soil solution may be the best way to accelerate the hydrolysis reaction rates (HMCRI 1987) if the soil-buffering capacity can be overcome.

3.2.3.2 Oxidation

In general, the chlorinated hydrocarbons considered at the ID host site are difficult to oxidize. The chlorine atoms that are associated with these compounds are relatively strong oxidants; therefore, a stronger oxidant would be needed to displace the chlorine from the carbon atoms.

Table 1 lists the theoretical oxidizing power (i.e., standard reduction potential) and half-cell reaction for a number of strong oxidizing species. However, the actual oxidizing power (i.e., formal reduction potential) will vary according to the conditions encountered. Particularly important in this regard are the solution pH, ionic strength, and relative concentrations of reactants and products. For example, a 10% hydrogen peroxide solution at pH 8 would exert an actual reduction potential of 1.32 V, even though the standard reduction potential of hydrogen peroxide is 1.78 V. At the same pH and with negligible chloride concentrations, chlorine gas would have more oxidizing power (i.e., 1.70 V) than would hydrogen peroxide because the reduction potential of chlorine gas is independent of pH. Fluorine is also a strong oxidant. It is not, however, a promising reagent for the oxidation of chlorinated compounds because it is very difficult to handle and the reaction products include undesirable fluorocarbons. Water may also be oxidized by fluorine, suggesting that significant quantities of fluorine will be consumed by nontarget compounds.

In addition to oxidizing power, factors such as stability of the oxidant and the speed with which it reacts will help determine its

TABLE 1. Theoretical Oxidizing Power of Selected Oxidants in Aqueous Solution

<u>Species</u>	<u>Half-Cell Reactions</u>	<u>Standard Reduction Potential^(a) (V)</u>	<u>Formal Reduction Potential at pH 8^(b) (V)</u>
Fluorine (F ₂)	$F_2 + 2e^- = 2F^-$	(2.87)	---
Ozone (O ₃)	$O_3 + 2H^+ + 2e^- = O_2 + H_2O$	2.08	1.47
Hydroxyl Radical (OH·)	$OH· + e^- = OH^-$	2.02	1.84
Hydrogen Peroxide (H ₂ O ₂)	$H_2O_2 + 2H^+ + 2e^- = 2H_2O$	1.78	1.32
Permanganate Ion (MnO ₄ ⁻)	$MnO_4^- + 4H^+ + 3e^- = MnO_2(s) + 2H_2O$	1.68	1.05
Perhydroxyl Radical (HO ₂ ·)	$HO_2· + H^+ + e^- = H_2O_2$	1.50	0.46
Hypochlorous Acid (HClO)	$HClO + H^+ + 2e^- = Cl^- + H_2O$	1.48	0.98
Chlorine (Cl ₂)	$Cl_2 + 2e^- = 2Cl^-$	1.36	1.70

(a) Weast et al. (1984).

(b) Additional assumptions: F₂ oxidizes H₂O; (O₃) saturated = 0.023 M, (O₂) saturated = 0.0013 M; (OH·) = (HO₂·) = 10⁻⁹ M; (H₂O₂) = 4.2 M (10%); (MnO₄⁻) = 1 M; (OCl⁻) = 0.7 M, (Cl⁻) = 10⁻⁹ M.

effectiveness. Free-radical oxidants, for example, are generally much more reactive than are ionic species. The hydroxyl free radical (OH·) is usually produced when ozone or hydrogen peroxide is exposed to ionizing radiation (beta or gamma) or ultraviolet (UV) light and has been shown to decompose many of the alkyl halides under ambient conditions. Free-radical oxidation is discussed in more detail in Subsection 3.2.3.4. Thus, the formal reduction potentials shown in Table 1 provide only an estimate of the actual performance of the oxidants.

Hydrogen peroxide is a strong and relatively stable oxidant that is often used to destroy organic compounds. Hydrogen peroxide can be sold and stored at concentrations as high as 70%, if measures are taken to prevent exposure to heat, light, and certain metals that catalyze its decomposition. Under proper storage conditions, hydrogen peroxide decomposes at a rate of 1 to 2% per year. High concentrations of hydrogen peroxide must be treated carefully because considerable amounts of heat and oxygen gas are released during decomposition. Hydrogen peroxide has about the same oxidizing power as do the perhydroxyl radical and permanganate (see Table 1). However, several studies have shown that at ambient or near-ambient conditions hydrogen peroxide does not react significantly with any of the chlorinated compounds being considered at the ID host site. In fact, research conducted at the University of Connecticut (Sundstrom et al. 1986), which was reported by Breton et al. (1988), showed hydrogen peroxide would not decompose trichloroethylene, which is the most reactive compound of the group. Oxidation with hydrogen peroxide, as well as its autodecomposition, can be accelerated by adding catalysts such as iron. This effect is attributed to the catalytic production of the hydroxyl free radical.

Ozone is a strong but unstable oxidant (see Table 1) that is generated by passing air or oxygen through a discharge gap between two electrodes maintained at a 5- to 30-kV potential difference (Ardon 1965). One of the electrodes is typically coated with a high-dielectric substance such as glass to stabilize the discharge density, yielding a silent discharge. The ozone-containing gas is then passed through water to solvate the ozone. Typical aqueous concentrations of ozone produced in this manner are 10 to 20 mg L⁻¹, though the aqueous solubility of ozone is about 1100 mg L⁻¹ at 0°C and 1 atm.

Like hydrogen peroxide, ozone has not been an effective oxidant for alkyl hydrocarbons under ambient aqueous conditions, even though ozone's oxidation potential is higher than hydrogen peroxide's. Breton et al. (1988) ranked various organic chemicals, including a number of halogenated compounds, according to their susceptibility to oxidation by ozone. In this ranking, carbon tetrachloride, chloroform, and

1,1,2-trichloroethane were classified as "unreactive" and trichloroethylene was classified as "very slow." Laboratory studies by Hoigne and Bader (1983) support this observation: they obtained reaction rate constants of $\leq 0.005 \text{ M}^{-1}\text{s}^{-1}$ for carbon tetrachloride, $\leq 0.1 \text{ M}^{-1}\text{s}^{-1}$ for methylene chloride and chloroform, and $17 \text{ M}^{-1}\text{s}^{-1}$ for trichloroethylene. Their research showed that the ethylene and methane derivatives were less susceptible to oxidation by ozone as the number of chlorine substitutions for hydrogen increased. For example, reaction rate constants ranging from 110 to $5700 \text{ M}^{-1}\text{s}^{-1}$ were obtained for various dichloroethylene isomers, in contrast to a rate constant of $< 0.1 \text{ M}^{-1}\text{s}^{-1}$ obtained for tetrachloroethylene.

An important limitation to using ozone as an in situ oxidation reagent is that it decomposes relatively rapidly in aqueous solutions (see Figure 1). The decomposition rate is slower in highly acidic, oxygenated solutions but increases with pH in the presence of organic, metallic, and oxide surfaces (Ardon 1965; Sehested et al. 1991). The decomposition of ozone may be slowed somewhat by the presence of free-radical scavengers such as carbonate and phosphate species (Hoigne and Bader 1978). For a typical carbonatic groundwater at arid sites, almost all of the ozone would be expected to decompose in less than 2 hours (see Figure 1). In the gaseous phase, ozone is more stable (half-life is approximately 12 hours). Gaseous-phase ozone might be suitable for in situ chemical oxidation of contaminants if the gaseous ozone molecules can be transported uniformly through the unsaturated zone at an adequate rate.

As with hydrolysis, increasing the temperature of the reactants should produce a corresponding increase in the oxidation rate. Therefore, it is possible that acceptable reaction rates can be obtained in situ if the soil is adequately heated. No specific data, however, were found to indicate the sensitivity of the oxidation of alkyl halides to temperature. It should be noted that increasing the temperature will decrease the aqueous solubility of these VOCs and promote release of these compounds to the soil atmosphere. Temperature will also increase the decomposition rate of ozone and hydrogen peroxide (Schumb et al.

1955; Ardon 1965; Breton et al. 1988; Lin et al. 1991; Sehested et al. 1991). Therefore, success with in situ heating and oxidation treatments depends on the relative effects of heating on the rates of the oxidation, aqueous solubility, and decomposition reactions.

The pH of the aqueous phase also affects the oxidation rates for both ozone and hydrogen peroxide. In general, oxidation by ozone and hydrogen peroxide is enhanced under basic conditions, though this rule may not apply to specific compounds. As with increasing temperature, however, the decomposition rate of these compounds increases at high pH and may serve to offset the improved oxidation rates (Schumb et al. 1955; Duke and Haas 1961; Ardon 1965; Breton et al. 1988; Sehested et al. 1991).

In summary, important considerations in the application of chemical oxidation technologies to the in situ treatment of soil are the potential for interaction of the oxidants with soil constituents, the reactive nature of the contaminants, and the subsurface chemical environment. Important factors in the subsurface chemical environment are solution pH, ionic strength, temperature, and relative concentrations of reactants and products. Both ozone and hydrogen peroxide are strong oxidants and, consequently, are capable of oxidizing a large number of inorganic and nontoxic organic constituents of the soil, as well as the target compounds. This creates several possible problems. First, the oxidation of constituents such as ferrous iron in soil minerals can consume a significant portion of the oxidant and decrease the efficiency of the process. Second, the oxidation of non-alkyl-halide constituents can lead to the formation of new hazardous species or make existing hazardous species more mobile in the soil. Third, the use of strong oxidants at relatively high concentrations will kill many organisms in the soil; thus, any subsequent biological treatment might require re inoculation of the treated area.

3.2.3.3 Reduction

Organic compounds containing chlorine are not easily reduced at the chlorine-carbon bond because chlorine is a strong oxidant and carbon is

a strong reductant. Only very strong reductants can break chlorine-carbon bonds. Two such reductants are elemental sodium (dissolved along with naphthalene in tetrahydrofuran) and an alkali alkoxide, which is produced by the reaction of glycol with an alkali hydroxide (Breton et al. 1988). Using elemental sodium is limited to anhydrous, air-free reaction conditions because of the reactivity of metallic sodium with water and oxygen. This method, consequently, is not suitable for applications in soils or groundwater. The alkali alkoxide, however, can be used in the presence of air and water. Therefore, it may be applicable to soils and sediments. Both methods, which were originally developed for the destruction of polychlorinated biphenyls and other halogenated aromatic and cyclic hydrocarbons, usually involve heating the reactants to about 100°C to achieve reasonable reaction rates. Reaction products include dehalogenated organic compounds.

In summary, because only very strong reductants can break the chlorine-carbon bonds, and these reductants either cannot be used safely in aerated conditions or cannot be used effectively at temperatures below 100°C, application of chemical reduction technologies for the in situ treatment of soils does not appear promising.

3.2.3.4 Free-Radical Degradation

Free radicals are formed by exciting a chemical bond in a molecule to the point where it breaks to form two unpaired electron fragments. These highly reactive free-radical species may then recombine to form various possible combinations of the original fragments. They may also react with other compounds that are present by either donating or accepting an electron. For example, free radicals may induce polymerization if unsaturated organic compounds are present. If hydrogen donors or oxidants are present, the free radicals may react to oxidize or reduce them, respectively.

Free radicals may be generated thermally, photolytically, acoustically, electrically, and chemically. Thermal excitation involves

raising the temperature to the point where molecules begin to decompose and results in free radicals. This process usually occurs during pyrolysis or calcining of organic materials.

Photolytic excitation can be accomplished with radiation sources such as gamma or UV radiation. In soils, however, gamma and UV radiation is attenuated within a relatively short distance. Soil treatment using UV radiation can be accomplished only by continuously turning the soil over to expose new soil surfaces to the light. This would require soil to be excavated. Gamma radiation has a much greater penetrating distance than does UV radiation; however, the penetration is only on the order of about 1 m, which is still too short for large-scale in situ applications. Furthermore, gamma radiation is more hazardous.

Ultrasonic or cavitation techniques are other methods for generating free radicals. In these methods, a liquid forms a temporary vapor phase, which releases energy on collapse. The effect of this energy production is increased localized temperatures that are sufficient to fragment certain molecules. Application of cavitation techniques in the subsurface, however, is considered impractical because of the high energy required to create cavitation conditions. Furthermore, it is unlikely that cavitation conditions can be induced in an unsaturated soil because of the presence of other gases.

Electrical excitation is accomplished using an electric arc or a corona discharge. Beta radiation may also be used to achieve electrical excitation. A disadvantage of in situ applications of an electrical arc is that very high localized temperatures are generated that can fuse the soil. Beta radiation is also impractical because, like UV radiation, it attenuates very rapidly. Laboratory tests have demonstrated the feasibility of creating a corona discharge in soil (Oma and Buel 1988), but this technology has not yet been applied to in situ remediation. A project is currently being funded under the VOC-Arid ID to evaluate the applicability of corona discharge as an in situ remediation technology.

Free-radical formation can also be induced by certain chemical reactions, particularly in the presence of a catalyst that lowers the

excitation energy required to break the bond. One such catalyst is Fenton's reagent, which is a slightly acidic solution of ferrous iron salts in hydrogen peroxide. In Fenton's reagent, the ferrous iron reacts with hydrogen peroxide to produce both a hydroxyl ion and a hydroxyl radical (Bove et al. 1983). Other catalysts for this reaction include ferric iron, aluminum, cupric ion, and divalent chromium (EPA 1983).

The most noteworthy free-radical reaction method for decomposing organics is the combination of free-radical formation and organic oxidation. Both ozone and hydrogen peroxide can be made to form the hydroxyl free radical, which is a very strong oxidant (see Table 1). Because the hydroxyl free radical is very reactive, it must be generated in situ rather than applied to the waste. The most common method of generating the hydroxyl free radical in aqueous solutions is by irradiating solutions of ozone or hydrogen peroxide with UV light. Another method is to use a catalyst, such as Fenton's reagent, to promote the formation of the hydroxyl free radical from hydrogen peroxide. A third method that has shown promise is to react ozone with hydrogen peroxide to form the hydroxyl free radical according to the equation

The hydroxyl free radical that is produced will react with oxidizable compounds.

Several researchers have studied the feasibility of free-radical oxidation in aqueous solutions. Research at the University of Connecticut (Sundstrom et al. 1986) showed that UV radiation was more effective in decomposing trichloroethylene than hydrogen peroxide. However, the irradiation of hydrogen peroxide solutions with UV light yielded faster decomposition rates. Up to 98% of the trichloroethylene decomposed in less than 50 minutes with the irradiated hydrogen peroxide solutions as reported by Breton et al. (1988). Estimated reaction rate

constants were 320, 60, and 10 μs^{-1} for trichloroethylene, chloroform, and carbon tetrachloride, respectively, at 20°C. Similar results were reported by Bellamy et al. (1991), who observed decomposition rate constants of 680 to 5850 μs^{-1} for trichloroethylene and 240 to 800 μs^{-1} for carbon tetrachloride. This was for a range of contaminant and ozone concentrations and hydrogen peroxide:ozone molar ratios. The removal of carbon tetrachloride, however, was attributed largely to volatilization effects rather than to oxidation. Zeff and Barich (1989) conducted research on the decomposition of methylene chloride in aqueous solutions and showed that the combination of UV radiation with either hydrogen peroxide or ozone improved decomposition over that achieved with only UV radiation. Combining hydrogen peroxide and ozone in the absence of UV radiation yielded results similar to those obtained when the individual gases were used in combination with UV radiation. Combining UV radiation, ozone, and hydrogen peroxide resulted in the greatest decomposition efficiency.

In implementing these free-radical degradation techniques, ozone and hydrogen peroxide must be delivered separately to the contaminated soil region and thoroughly mixed for the hydroxyl free radical to be accessible to the contaminants. A critical limitation is the short half-lives of ozone and the hydroxyl free radical in aqueous solutions.

In summary, free radicals are very reactive species that can be employed to destroy organic compounds. Free radicals can be generated by several different techniques; however, these methods are generally not suitable for in situ treatment. Either a large energy input, gamma or UV radiation, or chemical mixing of reagents and a catalyst is required. The latter two methods would require controlled conditions, which would not likely occur in the subsurface because of spatial heterogeneities and subsurface properties. Creating free radicals via electrical excitation, however, may be applicable. Further investigations are needed.

3.2.4 Thermal Chemical Degradation

In situ applications of high-temperature processes for the destruction of organics have not been investigated to any great extent. There are four methods by which soil temperatures can be raised to the levels required to destroy organic contaminants: electrical heating, microwave heating, hot-gas injection, and in situ combustion. In the Physical Technologies section (see Section 3.1), electrical heating was evaluated as a technology to transfer VOCs from a liquid to a gaseous state, which does not require the high temperatures needed to destroy compounds. In this subsection, the destruction of organic contaminants is considered.

Electrical heating involves the application of a current between electrodes inserted in the soil. Heat is generated as a result of the electrical resistance of the soil and soil gases. An extreme example is in situ vitrification, in which the soil is heated to the melting point. As the soil moisture content decreases because of water evaporation, electrical heating becomes less efficient because the conductive paths are diminished. Alternating current arcing techniques can be used to create a conducting path through the soil by ionizing soil gases. Laboratory tests with soil samples as large as 9.7 kg have achieved temperatures of 305°C using alternating current arcing techniques (Oma and Buel 1988).

In microwave (or radio-wave) heating, electromagnetic radiation in the frequency range of 2 to 45 MHz is applied to the soil by an array of excitor and ground electrodes either placed on the soil surface or inserted in boreholes drilled through the contaminated region. As the soil attenuates the electromagnetic energy, it is heated. This process has been used successfully to heat more than 30 tons of soil to 385°C (Johnson and Cosmos 1989). In microwave heating, the subsurface moisture or porosity is not a critical factor. Radio-frequency heating is being pursued collaboratively between the U.S. Air Force and DOE. Close collaboration is being established between the In Situ Heating Project of the VOC-Arid and Nonarid IDs and the Air Force-initiated radio-frequency heating technology demonstration.

Injection of a hot gas can also be used to heat the soil. Hot gas or steam is injected into the subsurface and flows through the contaminated region via an imposed gaseous-phase pressure gradient. Vacuum pumps and/or blowers, which are connected to boreholes, are commonly used to direct the gas flow. Surface barriers may also be used to control the flow regime. Because of the high specific volume, low density, and low specific heat capacity of gases, the injection method is limited. Temperatures normally associated with high-temperature processes are generally not obtained via conductive heat transfer. Furthermore, it is questionable whether large subsurface volumes can be heated in this manner because of spatial heterogeneities in soil properties. However, this technology may be suitable for limited heating in localized areas.

In situ combustion or incineration requires the addition of oxidants (i.e., air or oxygen) and fuel such as natural gas or a liquid hydrocarbon to the subsurface. The mixture is then ignited and maintained by the addition of more oxidant and fuel. In situ combustion of soil has not been used to treat VOC-contaminated sites; however, it may be feasible. A similar technique has been investigated for in situ heating of oil shale and in situ gasification of coal. The technique differs, however, in that nonvolatile liquid fuel is injected to the contaminated zone prior to ignition. The fuel is then ignited, and the combustion front is hypothesized to move through the subsurface consuming the fuel. A disadvantage is that if the combustion process is not complete, the remaining injected fuel becomes a contaminant. The petroleum industry has employed these techniques in petroleum reservoirs to enhance oil recovery (Latil 1980).

In summary, in situ techniques for high-temperature destruction of organics have not been tested in any detail. Creating high temperatures in the subsurface may melt soil constituents and kill microorganism populations. Because of the relatively low thermal conductivity of porous media, particularly after liquids vaporize, large amounts of energy may be required to produce the high temperatures, which may be uneconomical. Furthermore, as subsurface temperatures increase from ambient conditions

to the high temperatures needed for contaminant destruction, contaminant vapors will be produced. To prevent these vapors from moving into the atmosphere or to other regions of the subsurface, the vapors will have to be collected by a contaminant recovery technology. VOC vapors will migrate from higher- to lower-temperature regions. However, it may be possible to form a thermal barrier around the contaminated zone. By carefully designing the in situ heating system, thermal gradients can direct the VOCs to migrate toward the collection system. Although volatilization properties of VOCs appear to preclude the use of high-temperature-destruction technologies, it must be recognized that high temperatures may be required to remove and/or destroy all contaminants, because some VOCs may not volatilize at or near ambient temperatures.

3.3 BIOLOGICAL TECHNOLOGIES

In this section, bioremediation methods are discussed in general, but particular attention is given to carbon tetrachloride biodegradation.

Bioremediation is a very attractive in situ technology. If indigenous microorganisms are present in the vadose and/or groundwater zones, they may be stimulated to degrade contaminants; however, not all compounds are easily degraded. The current understanding of carbon tetrachloride microbial degradation is limited, but more is known about other chlorinated aliphatic compounds such as trichloroethylene. Recent studies have focused on identifying microorganisms and on understanding mechanisms of carbon tetrachloride biodegradation. Bouwer and McCarty (1983a) made some of the initial observations on the microbial transformation of carbon tetrachloride in groundwater under denitrifying conditions in batch microcosms. Degradation of carbon tetrachloride to carbon dioxide and chloroform in the microcosms was observed after 3 weeks of incubation. Bouwer and McCarty (1983b) also observed that carbon tetrachloride was completely degraded to carbon dioxide under methanogenic conditions. In another microcosm study, Wilson et al. (1987) observed carbon tetrachloride biodegradation in unamended aquifer sediments. In their study, considerable differences in carbon

tetrachloride degradation were observed in samples that were identical in appearance. This observation suggests that microbial populations and their associated activities can be heterogeneous.

Biodegradation of carbon tetrachloride has been demonstrated with a number of different bacteria. Conditions that favor carbon tetrachloride biodegradation are predominantly anaerobic. The biodegradation of carbon tetrachloride to carbon dioxide and other metabolites has been demonstrated in pure cultures and in consortia. Pseudomonas sp. (Criddle et al. 1990a; Hansen 1990), Acetobacterium woodii (Egli et al. 1988), and Clostridium sp. (Galli and McCarty 1989) have been found to degrade carbon tetrachloride. Escherichia coli (Criddle et al. 1990b) has been found to degrade carbon tetrachloride under anaerobic and microaerophilic conditions. Because carbon tetrachloride biodegradation appears to require anaerobic or microaerophilic conditions, biodegradation may be ineffective in unsaturated soils. To be effective, vadose zone biodegradation would probably require injection of water and nutrients to induce a low-oxygen environment. Injection of water, however, could cause problems similar to those previously discussed (i.e., contaminant mobilization). Oxygen-free gases may also be injected to displace native oxygen to create anaerobic conditions. The injected gases could also serve as a usable carbon source for the organisms; however, it may be economically prohibitive. Furthermore, there is currently no evidence that gaseous organic substrates will stimulate carbon tetrachloride-degrading microorganisms. In addition, the diversity and numbers of indigenous microorganisms within the vadose zone are typically limited. This may require the emplacement of nonindigenous populations to remediate the vadose zone, which might be unacceptable from a regulatory perspective. Because of the potential problems associated with producing an anaerobic environment in the vadose zone and introducing substrates and microorganisms, it is unlikely that vadose zone carbon tetrachloride bioremediation will be effective unless the indigenous microorganisms can be stimulated by other means. However, bioremediation of groundwater contaminants may be feasible.

The primary technical issues associated with contaminated groundwater in situ bioremediation are similar to those discussed for other in situ remediation processes. The complex subsurface heterogeneity may preferentially impede biological stimulation within certain zones and result in spotty treatment. Injecting nutrients to stimulate microorganisms may simply displace the aquifer contaminants. Therefore, groundwater recirculation may be necessary to ensure adequate contact between contaminants and microbially active zones, which may reduce the overall cost effectiveness of in situ bioremediation. In addition, injecting carbon sources to stimulate the organisms is likely to promote rapid biological growth. Clogging of subsurface flow channels from microbial growth has been previously shown to impede bioremediation effectiveness (Shaw et al. 1985). Methods are needed to minimize microbial growth while maximizing the distribution of nutrients to the microorganisms.

In summary, bioremediation may be a promising technology; however, issues concerning transporting nutrients and substrates to stimulate indigenous microorganisms need to be resolved. Furthermore, research on the ability of microorganisms to degrade specific compounds needs to be continued. Currently, biodegradation of carbon tetrachloride in the upper regions in the vadose zone, where it is relatively dry, does not appear to be promising. However, biodegradation of dissolved carbon tetrachloride in aquifers (i.e., the water-saturated zone) may be possible. Because new research and applied information are continually appearing in the literature, this evaluation of biodegradation is not inclusive.

4.0 RECOMMENDATIONS FOR ARID SITE IN SITU REMEDiation TECHNOLOGIES

Based on the information given in the previous sections, there are several technological remediation areas that warrant consideration for DOE support. Their likelihood for successful implementation, as it relates to the priority contaminants of the ID host site and to VOCs at arid to semiarid sites in general, is discussed in this section. The promising physical technological areas are

- subsurface heating
- barriers

and the promising chemical technological area is

- corona destruction.

A physical technological area that was not discussed in the previous sections but may be more cost-effective than vacuum extraction (which is part of the baseline remediation system) when contaminant transport becomes very limiting is longer-term, low-maintenance, low-energy technologies. These methods will be discussed briefly in the Newer Technologies Subsection 4.1.3.

Unfortunately, most of the above technologies are still in a research-and-development stage, and many unresolved issues need investigation before they will likely receive regulatory approval and be ready for field deployment. Many of the in situ destruction technologies will also need to be employed with contaminant recovery technologies to be effective.

Bioremediation is considered to be promising but was not extensively reviewed in this report. It is recognized as an in situ technology that deserves continued support and investment.

4.1 PHYSICAL TECHNOLOGIES

Physical technologies refer to in situ remediation practices that focus on manipulating physical properties of the subsurface to affect contaminant behavior. Physical technologies can be important in controlling the contaminant phase behavior and the contaminant flux rate to groundwater. The technologies reviewed in this report included electrokinetics, subsurface electrical heating, and barriers. Of these technological areas, subsurface heating and barriers warrant further investigation. A technological area that was not reviewed but warrants further investigation and possible investment is longer-term, low-maintenance, low-energy, in situ remediation methods.

The following subsections contain recommendations and brief summaries of subsurface heating and barriers, and recommendations and justifications for investigating/investing in longer-term, low-maintenance, low-energy, in situ remediation methods (i.e., new technologies).

4.1.1 Subsurface Heating

A major constraint in using electricity in remediation technologies at arid sites is the subsurface moisture content, which is typically very low near the soil surface. The moisture content affects the electrically conductive pathways in a porous medium. For some electrode pattern designs, a low water content can make using electricity impractical. For other designs, it may be economical.

Other issues of concern are the propagation of electricity in a spatially variable porous medium and the subsurface volume that can be treated from a single network of electrodes. It is unknown whether a uniform or spotty treatment will result from passing an electrical current through a heterogeneous subsurface at arid sites. Assuming the above issues are not a problem, modifying subsurface temperatures may aid in the mitigation of VOC contamination. The vapors that are produced from in situ heating and other related technologies, however, will have to be collected via vapor extraction or another form of contaminant recovery. The captured vapors would then be treated by a technology at

the soil surface. It would be unacceptable from a regulatory perspective if untreated contaminant vapors were discharged to the atmosphere.

Increasing subsurface temperatures will accelerate partitioning of VOCs to the gaseous phase, where the contaminants can be readily removed via vapor extraction. Therefore, the economical deployment of in situ heating technologies should be supported. Both electrical and radio-frequency heating should be evaluated. Additionally, any in situ heating technology should be interwoven with an enhanced recovery technology to form an efficient and effective in situ remediation strategy.

4.1.2 Barriers

The construction of surface barriers could also enhance contaminant recovery technologies by creating conditions that will affect how fluids move throughout the subsurface. The barriers may reduce the downward contaminant flux in the aqueous phase by minimizing the amount of precipitation the contaminated area receives. Inexpensive surface barriers can be constructed with crushed rock and asphalt material. A feasibility question, however, is the size of the surface barrier that will need to be constructed. If the barrier is not of sufficient size, water may migrate to the contaminated area by lateral water- and vapor-pressure gradients. If the surface barrier needs to be very large to prevent water migration, then it may become uneconomical to construct such a barrier.

Barriers may be helpful when used in conjunction with other in situ remediation and contaminant recovery technologies. Modeling activities associated with the VOC-Arid ID can provide valuable information concerning the expected behavior of subsurface contaminants when a barrier is emplaced. The effects of barrier emplacement and barrier sizes can be determined by simulating contaminant behavior with a computer program. If the computer simulations suggest that barriers may be beneficial, then a project should be solicited that will evaluate the economic emplacement of barriers to assist in subsurface remediation.

4.1.3 Newer Technologies

A technological area that has not received much attention is longer-term, low-maintenance, low-energy, in situ remediation/enhanced recovery methods. Typically, newer in situ remediation technologies require a large energy input or a large investment of personnel, supplies, and facilities. Furthermore, high-energy remediation systems may not be efficient at all times. When transport processes are diffusion controlled, contaminants will move slowly through the subsurface, regardless of energy input. For diffusion-controlled transport processes, longer-term methods that are less energy, maintenance, and personnel demanding appear attractive. For example, solar energy may be used to induce a gaseous-phase pressure gradient by which contaminant vapors can be collected and treated. A small temperature gradient may also be established that may cause contaminants to move in a controlled manner. These methods have been called passive by some researchers. Investment in developing such methods appears to be judicious. A network of low-maintenance, low-energy remediation systems may be economically advantageous and may reduce worker exposure to hazardous compounds.

4.2 CHEMICAL TECHNOLOGIES

Chemical technologies refer to in situ remediation practices that require chemical reagents to be added to the subsurface. They also include technologies that destroy contaminants by chemical reactions such as in corona destruction. At its current developmental stage, chemical in situ destruction does not appear to be an effective or proven method of destroying compounds such as carbon tetrachloride or related chemicals in the vadose zone. Of the chemical treatment technologies evaluated in Section 3.0, corona destruction appears to be the most promising; however, it has not been field tested. Further investigation and investment are warranted to evaluate its success in remediating VOC contamination at arid sites.

4.2.1 Corona Destruction

A plasma of highly reactive ionized gases (i.e., free radicals) that can destroy contaminants is produced in corona-destruction technologies. The corona discharges can be induced by passing a large voltage gradient through porous media. This will create very high localized temperatures that will vaporize liquids, including VOCs, and may melt solids. A technological issue is the propagation of the plasma through the subsurface, particularly in heterogeneous porous media, so that the free radicals can react with the contaminants. The economic deployment of the technology is also another issue because high-voltage equipment is used. Additional investigations/evaluations are needed to better understand plasma development and propagation through spatially heterogeneous subsurfaces. The propagation of a corona in a spatially heterogeneous porous medium is a critical element of the technology that needs to be resolved before it can be universally deployed. Furthermore, effects of corona-destruction technologies on heavy metal/radionuclide mobility need to be better understood to obtain regulatory acceptance. Investment in the better understanding of corona-destruction technologies is prudent because the technology may be very effective in destroying hard-to-reach contaminants in the subsurface.

4.2.2 Chemical Injection In Situ Destruction Technologies

For chemical in situ destruction technologies to be effective, injected reagents need to be stable and effective in destroying or immobilizing contaminants, and should be easy to transport through the subsurface. The reagents also should not be consumed by soil constituents, inhibit biological activity, or create compounds that are hazardous. A critical aspect of in situ chemical remediation technologies is obtaining a uniform and thorough mixing of reagents and contaminants in the subsurface. Overcoming the effects of spatial heterogeneity in soil properties will be paramount for universal application of the technologies.

At arid sites, injecting reagents in aqueous solutions does not seem advisable because of concerns about longevity of the reagents and potential for further contaminant mobilization. Injecting gas-phase reagents appears to be more promising because they can be transported through the subsurface at arid sites faster than when in the aqueous phase. However, suitable reagents and/or processes will need to be identified and/or developed.

Most of the target contaminants at the ID host site can exist in gaseous and aqueous forms in amounts above regulatory limits. This will require treating the contaminants in both the gaseous and the aqueous phase. Problems of identifying suitable reagents and obtaining thorough mixing of reagents and contaminants in the subsurface appear to be unresolved at this time. Because of the large depth to groundwater generally encountered at arid sites, this will be a challenging task. If chemical reagents are identified that can destroy or immobilize contaminants, the following three critical questions must be answered before any reagent is used:

1. How will the reagent react with contaminants a) in the aqueous phase, b) in the gaseous phase, and c) adsorbed onto mineral and organic solid materials?
2. How long will the reagent remain active in the subsurface?
3. How will the reagent affect other subsurface phenomena?

Because the target contaminants of the ID host site appear to be chemically unreactive at ambient conditions, redox manipulation technologies may not be suited for in situ treatment. Chemical technologies appear to be more suited for ex situ treatment methods, where reagent-contaminant mixing and the chemical environment can be more carefully controlled. However, where it is undesirable to transport contaminants to the surface, reaction chambers could be developed that can fit inside a borehole to treat contaminated vapors and/or groundwater. Reagents that have short lifetime expectancies could be synthesized at the ground

surface and pumped into the reaction chamber, where the contaminants would be destroyed. Contaminants could be transported to the reaction chamber via contaminant recovery technologies. This technique may have merit when cocontaminants may be radionuclides or when the transport and ex situ treatment costs become restrictive.

4.3 BIOREMEDIATION

Biological in situ technologies refer to those methods that stimulate subsurface microbiological activity for the purpose of degrading organic compounds. Bioremediation was not a focus of this report; it was reviewed only in general. The following paragraphs are recommendations and a brief summary of conditions necessary for successful implementation of bioremediation technologies for mitigating subsurface VOC contamination, with special attention given to the priority contaminants of the ID host site.

The success of bioremediation is very sensitive to the specific contaminant. It appears that indigenous microorganisms will degrade the primary target compounds of the ID host site only anaerobically. This suggests that bioremediation in the vadose zone is likely to be ineffective for these contaminants. Furthermore, microorganism populations in the vadose zone also appear to be relatively small because of the low moisture contents.

Biodegradation of the priority contaminants at the ID host site in groundwater, however, may be technologically feasible. In situ treatment may be possible if indigenous microorganisms can be supplied with nutrients and substrates. Nonindigenous microorganisms may also be effectively introduced into the aquifer to biodegrade contaminants. The introduction of nonindigenous species, however, raises some regulatory questions. A critical concern with either indigenous or nonindigenous approaches is obtaining a thorough and uniform mixing of nutrients, substrates, and microorganisms, which may be difficult because of subsurface soil-property heterogeneities. Another concern is clogging of porous medium pore spaces with biomass. As the microorganisms are

stimulated to grow, they might obstruct the movement of nutrients, substrate, and contaminants through the subsurface. This could result in ineffective treatment.

Regulator and public acceptance of bioremediation strategies, particularly the introduction of nonindigenous microorganisms, is likely to be more difficult than with other in situ technologies. Ex situ bioremediation, where acceptance is not generally an issue, could be very effective because the conditions/environment can be more easily controlled. A bioremediation project supported by the VOC-Arid ID is currently investigating conditions necessary for successful biodegradation of target contaminants.

Further research and development are needed. Studies are warranted to investigate the feasibility of vadose and groundwater zone carbon tetrachloride biodegradation. The ability to distribute nutrients and substrates uniformly without clogging soil pores is critical for effective bioremediation. Continued support for bioremediation research and development is important for developing cost-effective and efficient methods.

5.0 CONCLUSION

There are few in situ remediation technologies, as defined by the VOC-Arid ID, that are ready for field deployment. Issues such as low moisture contents, spatially heterogeneous soil properties, and enhanced mobility of cocontaminants are not resolved. It is doubtful that any given in situ remediation technology will completely mitigate all subsurface contamination. Contaminants can partition among gaseous, liquid, and solid phases. No one reagent or remediation technology is likely to treat all of the contaminants in their respective forms.

Remediating subsurface contamination will involve using several technologies that need to be interwoven. Instead of approaching the problem as one of developing remediation technologies, the approach should be on synthesizing remediation strategies where several in situ remediation, enhanced contaminant recovery, and ex situ treatment technologies can be employed. Typically, a given remediation technology will be addressing only a few of the possible fate paths for the contaminants.

Because many regulatory, engineering, and scientific issues are unresolved, further research-and-development support is required. All technologies should be first tested, in a controlled manner, on the scale of several meters before being conducted in the field. There are too many unknowns in the field to employ incompletely tested technologies. The result could be a further exacerbation of the existing contamination, which may yield increased hazards to the public or the environment. An energetic format is needed to address contamination at DOE sites. Only through cycles of testing and evaluation will newer, effective remediation technologies evolve that can be safely transferred to the private sector.

6.0 REFERENCES

- Ardon, M. 1965. Oxygen: Elementary Forms and Hydrogen Peroxide. W. A. Benjamin, New York, pp. 52-61.
- Bear, J. 1972. Dynamics of Fluids in Porous Media. American Elsevier Publishing, New York.
- Bellamy, W. D., G. T. Hickman, P. A. Mueller, and N. Ziemba. 1991. "Treatment of VOC-Contaminated Groundwater by Hydrogen Peroxide and Ozone Oxidation." Res. J. Water Pollut. Control Fed. 63(2):120-128.
- Bidoglio, G., A. De Plano, and L. Righetto. 1989. "Interactions and Transport of Plutonium-Humic Acid Particles in Groundwater Environments." Mater. Res. Soc. Symp. Proc. 127:823-830.
- Bouwer, E. J., and P. L. McCarty. 1983a. "Transformations of Halogenated Organic Compounds Under Denitrification Conditions." Appl. Environ. Microbiol. 45:1295-1299.
- Bouwer, E. J., and P. L. McCarty. 1983b. "Transformations of 1- and 2-Carbon Halogenated Aliphatic Organic Compounds Under Methanogenic Conditions." Appl. Environ. Microbiol. 45:1286-1294.
- Bove, L. J., W. P. Lambert, L.Y.H. Lin, D. E. Sullivan, and P. J. Marks. 1983. Installation Restoration General Environmental Technology Development - Final Report - Development of New Technology for the Removal of Contaminants from Groundwater Identification and Evaluation of Technologies. DRXTH-TE-CR-84270, Roy F. Weston, Inc., Westchester, Pennsylvania.
- Breton, M., P. Frillici, S. Palmer, C. Spears, M. Arienti, M. Kravett, A. Shayer, and N. Suprenant. 1988. Treatment Technologies for Solvent Containing Wastes. Noyes Data Corporation, Park Ridge, New Jersey.
- Callahan, M. A., M. W. Slimak, N. W. Gabel, I. P. May, C. F. Fowler, J. R. Freed, P. Jennings, R. L. Durfee, J. C. Whitmore, B. Maestri, W. R. Mooney, B. R. Holt, and C. Gould. 1979. Water-Related Environmental Fate of 129 Priority Pollutants. EPA-440/4-029a and b, 2 vols.. Office of Water Planning and Standards and Office of Water and Water Management, U.S. Environmental Protection Agency, Washington, D.C.
- Cary, J. W., J. F. McBride, and C. S. Simmons. 1989. "Trichloroethylene Residuals in the Capillary Fringe as Affected by Air-Entry Pressures." J. Environ. Qual. 18:72-77.
- Criddle, C. S., J. T. DeWitt, D. Grbic-Galic, and P. L. McCarty. 1990a. "Transformation of Carbon Tetrachloride by Pseudomonas sp. Strain KC Under Denitrification Conditions." Appl. Environ. Microbiol. 56:3240-3246.

Criddle, C. S., J. T. DeWitt, and P. L. McCarty. 1990b. "Reductive Dehalogenation of Carbon Tetrachloride by *Escherichia coli* K-12." Appl. Environ. Microbiol. 56:3247-3254.

Dragun, J. 1988. The Soil Chemistry of Hazardous Materials. Hazardous Materials Control Research Institute, Silver Spring, Maryland.

Duke, F. R., and T. W. Haas. 1961. "The Homogeneous Base-Catalyzed Decomposition of Hydrogen Peroxide." J. Phys. Chem. 65:304-306.

Egli, C., T. Tschan, R. Scholtz, A. M. Cook, and T. Leisinger. 1988. "Transformation of Tetrachloromethane to Dichloromethane and Carbon Dioxide by *Acetobacterium woodii*." Appl. Environ. Microbiol. 54:2819-2824.

EPA. 1983. Technology for Control/Removal of Pollutants. Volume 3 of Treatability Manual. EPA/600/2-82-001c, U.S. Environmental Protection Agency, Washington, D.C.

Foth, H. D. 1990. Fundamentals of Soil Science. 8th ed. John Wiley and Sons, New York, pp. 55-56.

Freeman, H. M., ed. 1989. Standard Handbook of Hazardous Waste Treatment and Disposal. McGraw-Hill, New York.

Galli, R., and P. L. McCarty. 1989. "Biotransformation of 1,1,1-Trichloroethane, Trichloromethane, and Tetrachloromethane by a *Clostridium* sp." Appl. Environ. Microbiol. 55:837-844.

Gerstl, Z., Y. Chen, U. Mingelgrin, and B. Yaron. 1989. Toxic Organic Chemicals in Porous Media. Springer-Verlag, New York.

Hansen, F. 1990. The Transformation of Tetrachloromethane Under Denitrifying Conditions by a Subsurface Bacterial Consortium and Its Isolates. M.S. thesis, Washington State University, Pullman, Washington.

HMCRI. 1987. "Special Method of Delivery and Recovery Enhancement (Electro-osmosis)." Section 1.4 in Superfund Series, Hazardous Materials In Situ Stabilization. Hazardous Materials Control Research Institute, Silver Spring, Maryland.

Hoigne, J., and H. Bader. 1978. "Ozonation of Water: Kinetics of Oxidation of Ammonia by Ozone and Hydroxyl Radicals." Environ. Sci. Technol. 12:79-84.

Hoigne, J., and H. Bader. 1983. "Rate Constants of Reactions of Ozone with Organic and Inorganic Compounds in Water - Part I: Non-Dissociating Organic Compounds." Water Res. 17:173-183.

Johnson, N. P., and M. G. Cosmos. 1989. "Thermal Treatment Technologies for Haz Waste Remediation." Pollut. Eng., October, pp. 66-85.

Last, G. V., R. J. Lenhard, B. N. Bjornstad, J. C. Evans, K. R. Roberson, F. A. Spane, J. E. Amonette, and M. L. Rockhold. 1991. Characteristics of the Volatile Organic Compounds-Arid Integrated Demonstration Site. PNL-7866, Pacific Northwest Laboratory, Richland, Washington.

Latil, M. 1980. Enhanced Oil Recovery. Gulf Publishing Company, Houston.

Lin, C. C., F. R. Smith, N. Ichikawa, T. Baba, and M. Itow. 1991. "Decomposition of Hydrogen Peroxide in Aqueous Solutions at Elevated Temperatures." Int. J. Chem. Kinetics 23:971-987.

Mabey, W., and T. Mill. 1978. "Critical Review of Hydrolysis of Organic Compounds in Water Under Environmental Conditions." J. Phys. Chem. Ref. Data 7(2):383-415.

Mackay, D. M., and J. A. Cherry. 1989. "Groundwater Contamination: Pump-and-Treat Remediation." Environ. Sci. Technol. 23:630-636.

Maskarinec, M. P., L. H. Johnson, S. K. Holladay, R. L. Moody, C. K. Bayne, and R. A. Jenkins. 1990. "Stability of Volatile Organic Compounds in Environmental Water Samples During Transport and Storage." Environ. Sci. Technol. 24(11):1665-1670.

McTaggart, F. K. 1967. Plasma Chemistry in Electrical Discharges. Elsevier Publishing Company, New York.

Oma, K. H., and J. L. Buelte. 1988. "In Situ Heating to Detoxify Organic Contaminated Soils." In Proceedings of the 5th National Conference on Hazardous Wastes and Hazardous Materials, pp. 154-157. Hazardous Materials Control Research Institute, Silver Spring, Maryland.

Ong, S. K., and L. W. Lion. 1991. "Mechanisms of Trichloroethylene Vapor Sorption onto Soil Minerals." J. Environ. Qual. 20:180-188.

Peterson, M. S., L. W. Lion, and C. A. Shoemaker. 1988. "Influence of Vapor-Phase Sorption and Diffusion on the Fate of Trichloroethylene in an Unsaturated Aquifer System." Environ. Sci. Technol. 22(5):571-578.

Radding, S. B., D. H. Liu, H. L. Johnson, and T. Mill. 1977. Review of the Environmental Fate of Selected Chemicals. EPA/560/5-77-033, U.S. Environmental Protection Agency, Washington, D.C.

Schumb, W. C., C. W. Satterfield, and R. L. Wentworth. 1955. "Stability." In Hydrogen Peroxide. ACS Monograph Series, Reinhold Publishers, Baltimore.

Sehested, K., H. Corfitzen, J. Holcman, C. H. Fischer, and E. J. Hart. 1991. "The Primary Reaction in the Decomposition of Ozone in Acidic Aqueous Solutions." Environ. Sci. Technol. 25:1589-1596.

Shaw, J. C., B. Bramhill, N. C. Wardlaw, and J. W. Costerton. 1985. "Bacterial Fouling in a Model Core System." Appl. Environ. Microbiol. 49:693-701.

Staehelin, J., and J. Hoigne. 1982. "Decomposition of Ozone in Water: Rate of Initiation by Hydroxide Ions and Hydrogen Peroxide." Environ. Sci. Technol. 16:676-681.

Sundstrom, D. W., H. E. Klei, T. A. Nalette, D. J. Reidy, and B. A. Weir. 1986. "Destruction of Halogenated Aliphatics by Ultra-violet Catalyzed Oxidation with Hydrogen Peroxide." Haz. Waste and Haz. Mater. 3(1):101-110.

Travis, C. C., and C. B. Doty. 1990. "Can Contaminated Aquifers at Superfund Sites Be Remediated?" Environ. Sci. Technol. 24:1464-1466.

Unterberg, W., R. W. Melvold, S. L. Davis, F. J. Stephens, and F. G. Bush III. 1987. Reference Manual of Countermeasures for Hazardous Substances Releases. EPA/600/2-87-069, U.S. Environmental Protection Agency, Cincinnati (or PB87-232252, National Technical Information Service, Springfield, Virginia).

Weast, R. C., M. J. Astle, and W. H. Beyer, eds. 1984. CRC Handbook of Chemistry and Physics. 64th ed. CRC Press, Boca Raton, Florida, pp. D156-D163.

White, F. M. 1991. Viscous Fluid Flow. McGraw-Hill, New York.

Wilson, J. T., G. B. Smith, J. W. Cochran, J. R. Barker, and P. V. Roberts. 1987. "Field Evaluation of a Simple Microcosm Simulating the Behavior of Volatile Organic Compounds in Subsurface Materials." Water Resour. Res. 23:1547-1553.

Yih, Chia-Shun. 1988. Fluid Mechanics. West River Press, Ann Arbor, Michigan.

Zeff, J. D., and J. T. Barich. 1989. "A Review of Ultrox Ultraviolet Oxidation Technology as Applied to Industrial Groundwater, Wastewater and Superfund Sites." Presented at the Summer National Meeting of the American Institute of Chemical Engineers, Philadelphia, Pennsylvania, August 20-23, 1989. AIChE, New York.

DISTRIBUTION

No. of
Copies

No. of
Copies

OFFSITE

12 DOE/Office of Scientific and
Technical Information

6 U.S. Department of Energy
12800 Middlebrook Road
Germantown, MD 20874
T. D. Anderson, EM-551
D. Biancosino, EM-551
M. K. Harmon, EM-442
J. C. Lehr, EM-442
S. C. T. Lien, EM-54
M. W. Shupe, EM-541

C. W. Frank, EM-50
U.S. Department of Energy
1000 Independence Ave. S.W.
Washington, D.C. 20585

2 Argonne National Laboratory
9700 S. Cass Ave.
Argonne, IL 60439-4837
J. E. Helt
R. Peters

2 U.S. Department of Energy
Savannah River Field Office
P.O. Box A
Aiken, SC 29808
D. Kaback
J. L. Steele

6 EG&G Idaho, Inc.
Idaho National Engineering
Laboratory
P.O. Box 1625
Idaho Falls, ID 83415
T. Chalwin
J. Conner
K. Koller
R. MacKinnon
W. Shutte
R. R. Stiger

2 EG&G Inc.
Rocky Flats Plant
P.O. Box 464
Golden, CO 80402
J. Blakeslee
T. Greengard

2 Lawrence Livermore National
Laboratory
University of California
P.O. Box 808
Livermore, CA 94550
R. Aines
J. L. Yow

2 Los Alamos National
Laboratory
Los Alamos, NM 87545
J. P. Shipley, Jr.
E. Springer

2 Massachusetts Institute of
Technology
Plasma Fusion Center
167 Albany Street, NW16-140
Cambridge, MA 02139
L. Bromberg
D. R. Cohn

3 Oak Ridge National Laboratory
P.O. Box 2008
Oak Ridge, TN 37831-6273
R. Jenkins
A. Malinauskas
R. Siegrist

2 Sandia National Laboratories
P.O. Box 5800
Albuquerque, NM 87185-5800
D. Berry
L. D. Tyler

No. of
Copies

2 Westinghouse Materials Co.
of Ohio
P.O. Box 398704
Cincinnati, OH 45239-8704
J. P. Hopper
K. Nuhfer

J. Barich
U.S. Environmental
Protection Agency
Region 10, ES-098
1200 Sixth Avenue
Seattle, WA 98101

Jeff Breckel
State of Washington
Department of Ecology
M/S PV-11
Olympia, WA 98504

P. Colombo
Brookhaven National Laboratory
Building 703-50 Rutherford
Upton, NY 11973

J. Corones
Ames Laboratory
329 Wilhelm Hall
Iowa State University
Ames, IA 50011

R. L. Crawford
University of Iowa
Iowa City, IA 52242

G. Dawson
ICF Technology Incorporated
601 Williams Blvd., 4th Floor
Richland, WA 99352

R. B. Evans
Environmental & Health
Division
Reynolds Electrical &
Engineering
P.O. Box 98521
Las Vegas, NV 89193-8521

No. of
Copies

D. P. Eyman
Associate Professor
Department of Chemistry
The University of Iowa
Iowa City, IA 52242

S. Gorelick
Department of Applied Earth
Sciences
Stanford University
Stanford, CA 94305-2225

R. Jacobson
Assistant Operations Manager
Remote Sensing Laboratory
University of Nevada
P.O. Box 1912, MS D-12
Las Vegas, NV 89125

J. Koger
Martin Marietta Energy Systems
P.O. Box 2009
Oak Ridge, TN 37831-8097

B. Looney
Environmental Sciences Division
Savannah River Laboratory
773-42A
Aiken, SC 29808

T. McEvilly
50E-111
Lawrence Berkely Laboratory
1 Cyclotron Road
Berkeley, CA 94720

L. Rogers
EG&G Energy Measurements, Inc.
P.O. Box 1912, MS RLS-11
Las Vegas, NV 89125

No. of
Copies

R. Snipes
Hazardous Waste Remedial
Actions Program
Martin Marietta Energy
Systems
P.O. Box 2003
Oak Ridge, TN 37831-7606

H. D. Stensel
University of Washington
Seattle, WA 98105

T. R. Thomas
Westinghouse Idaho Nuclear
Company, Inc.
P.O. Box 4000
Idaho Falls, ID 83403-4000

K. Vogel
HQ AFCESA/RAVW
Tyndall AFB, FL 32403-6001

R. Walker
Chem-Nuclear Geotech,
Inc.
P.O. Box 14000
Grand Junction, CO 81502-
2567

ONSITE

3 DOE Richland Field Office

R. P. Carter
J. D. Goodenough
J. M. Hennig

14 Westinghouse Hanford Company

M. R. Adams
J. D. Berger
K. R. Fecht
R. L. Gilchrist
M. C. Hagood
G. W. Jackson

No. of
Copies

W. L. Johnson
C. V. King
K. J. Koegler
R. E. Lerch
D. J. Moak
V. J. Rohay
J. L. Scott
J. G. Wollard

26 Pacific Northwest Laboratory

M. P. Bergeron
B. N. Bjornstad
T. M. Brouns
M. A. Chamness
P. G. Doctor
J. C. Evans
W. O. Heath
E. C. Korstad (2)
G. V. Last
R. J. Lenhard (2)
R. E. Lewis
R. G. Riley
R. R. Roberson
R. Schalla
S. C. Slate
S. L. Stein
J. A. Stottlemire
Publishing Coordination
Technical Report Files (5)

Routing

R. M. Ecker
J. M. Falco
M. J. Graham
P. Irving
R. L. Skaggs
P. C. Hays (last)

END

**DATE
FILMED**

2 / 10 / 93