Modeling VOC Transport in Simulated Waste Drums

Kevin J. Liekhus
Garold L. Gresham
Eric S. Peterson
Cathy Rae
Norman J. Hotz
Mike J. Connolly

Published June 1993

Idaho National Engineering Laboratory
EG&G Idaho, Inc.
Idaho Falls, Idaho 83415

Prepared for the
U.S. Department of Energy
Assistant Secretary for ER&WM
Under DOE Idaho Field Office
Contract DE-AC07-76ID01570

MASTER

FIGURES

1.	Automated VOC transport experimental configuration	10
2.	Simulated lab-scale waste drum	11
3.	NFT-020 Carbon-composite filter	13
4.	Feedthrough for small polyethylene bags	14
5.	Feedthroughs for large polyethylene bags	15
6.	Feedthroughs for drum lid	16
7.	Large-mouth polyethylene bottle configuration	18
8.	Environmental chamber	19
9.	Automated gas sampling system	20
10.	Configuration of 10-port gas sampling valve	21
11.	Automated calibration sequence	25
12.	Automated sampling sequence	26
13.	Single-component pressure change experimental configuration	32
14.	Mixed-component chromatographic detection method experimental configuration	34
15.	Model predictions and experimental data of average methylene chloride (MC), TCA, and TCE concentration in small bag void volumes of waste drum in variable-temperature environment (Trial 1.1)	46
16.	Model predictions and experimental data of average methylene chloride (MC), TCA, and TCE concentration in small bag void volumes of waste drum in constant-temperature environment (Trial 2.3)	47
17.	Model predictions and experimental data of methylene chloride (MC), carbon tetrachloride (CCl_4), and Freon-113 concentration in large bag void volume of waste drum in variable-temperature environment (Trial 2.1)	48
18.	Model predictions and experimental data of methylene chloride (MC), carbon tetrachloride (CCl_4), and Freon-113 concentration in the large bag void volume of waste drum in constant-temperature environment (Trial 3.4)	49
19.	Mean absolute relative deviation of VOC concentration in small bags	51

20.	Mean absolute relative deviation of VOC concentration in large bags	52
21.	Mean absolute relative deviation of VOC concentration in drum headspace	53
22.	Average methylene chloride (MC) and 1,1,1-trichloroethane (TCA) concentration in drum headspace for constant-temperature (○,□) and variable-temperature (●,■) experiments	54
23.	Predicted methylene chloride (MC) concentration in small bags as a function of available permeable small and large bag surface area	56
24.	Predicted average TCA concentration difference between large bag and drum headspace void volumes in waste drums maintained at a constant temperature (Trial 2.3) as a function of diffusion lengths (x_d) between void volumes	58
25.	Comparison of experimental data (Trial 2.3) and model predictions of TCA concentration in large bags (LB) and drum headspace (DH) void volumes with and without ($\eta = 0$) VOC accumulation in polyethylene drum liner	59

TABLES

1.	Experimental design for simulated waste drum VOC transport experiments	9
2.	Experimental design for polyethylene bottles VOC transport experiments	9
3.	Gas standard mixtures	23
4.	Sampling scheme for simulated waste drums	28
5.	Permeability, diffusivity and solubility of VOC-air mixtures in yellow polyethylene bag ..	38
6.	Measured VOC permeability from mixed-component chromatographic detection method	39
7.	VOC transfer coefficients used in eqn (3)	44

Table C-3. Percent relative error for continuing calibration standard analytes for test period II.

CCS Day		MeOH	Hexane	TCA	Toluene	Xylene	MeCl2	Freon	TCA	CCl4	TCE
Day 2	Conc. (ppm)	500.8	396.6	536.6	209.6	49.2	497.4	439.5	480.0	158.6	149.9
	%Rec	100.4	105.2	105.6	99.3	84.4	104.7	97.5	96.8	106.4	98.0
	Rel. % Error	0.4	5.2	5.6	-0.7	-15.6	4.7	-2.5	-3.2	6.4	-2.0
Day 5	Conc. (ppm)	519.5	383.9	520.2	219.9	55.4	507.6	436.0	480.9	158.7	146.5
	%Rec	104.1	101.8	102.4	104.2	95.0	106.9	96.7	97.0	106.5	95.8
	Rel. % Error	4.1	1.8	2.4	4.2	-5.0	6.9	-3.3	-3.0	6.5	-4.2
Day 7	Conc. (ppm)	515.0	382.6	520.1	211.7	52.7	513.4	451.2	497.2	162.3	158.0
	%Rec	103.2	101.5	102.4	100.3	90.4	108.1	100.0	100.2	108.9	103.3
	Rel. % Error	3.2	1.5	2.4	0.3	-9.6	8.1	0.0	0.2	8.9	3.3
Day 9	Conc. (ppm)	510.1	373.5	507.5	212.0	58.0	506.4	452.5	492.6	156.4	155.8
	%Rec	102.2	99.1	99.9	100.5	99.5	106.6	100.3	99.3	105.0	101.8
	Rel. % Error	2.2	-0.9	-0.1	0.5	-0.5	6.6	0.3	-0.7	5.0	1.8
Day 12	Conc. (ppm)	469.7	361.0	482.9	199.6	48.3	456.9	423.3	448.5	138.7	143.4
	%Rec	94.1	95.8	95.1	94.6	82.8	96.2	93.9	90.4	93.1	93.7
	Rel. % Error	-5.9	-4.2	-4.9	-5.4	-17.2	-3.8	-6.1	-9.6	-6.9	-6.3
Day 14	Conc. (ppm)	465.8	347.6	470.0	199.0	51.9	468.6	421.3	434.0	116.3	136.3
	%Rec	93.3	92.2	92.5	94.3	89.0	98.7	93.4	87.5	78.1	89.1
	Rel. % Error	-6.7	-7.8	-7.5	-5.7	-11.0	-1.3	-6.6	-12.5	-21.9	-10.9
Day 16	Conc. (ppm)	477.0	363.0	489.3	200.9	52.5	479.3	437.1	451.7	124.4	144.1
	%Rec	95.6	96.3	96.3	95.2	90.1	100.9	96.9	91.1	83.5	94.2
	Rel. % Error	-4.4	-3.7	-3.7	-4.8	-9.9	0.9	-3.1	-8.9	-16.5	-5.8
Day 19	Conc. (ppm)	472.2	363.0	491.7	198.3	49.8	486.6	436.2	460.4	129.7	144.1
	%Rec	94.6	96.3	96.8	94.0	85.4	102.4	96.7	92.8	87.0	94.2
	Rel. % Error	-5.4	-3.7	-3.2	-6.0	-14.6	2.4	-3.3	-7.2	-13.0	-5.8
Day 22	Conc. (ppm)	467.2	356.9	484.7	188.9	47.3	489.8	436.1	465.5	135.3	144.1
	%Rec	93.6	94.7	95.4	89.5	81.1	103.1	96.7	93.9	90.8	94.2
	Rel. % Error	-6.4	-5.3	-4.6	-10.5	-18.9	3.1	-3.3	-6.1	-9.2	-5.8
Mean % Error		-2.1	-1.9	-1.5	-3.1	-11.4	3.1	-3.1	-5.7	-4.5	-4.0
Std. Dev.		4.5	4.1	4.3	4.5	5.9	4.0	2.3	4.3	11.5	4.4

MeOH - Methanol, Hexane - Cyclohexane, TCA - 1,1,1-Trichloroethane, Xylene - para Xylene, MeCl2 - Methylene Chloride

Freon - Freon 113 (1,1,2-trichloro-1,2,2-trifluoroethane), CCl4 - Carbon Tetrachloride, TCE - Trichloroethylene

% Rec - Percent Recovery, Rel. % Error - Relative Percent Error

Table C-4. Percent relative error for continuing calibration standard analytes for test period III.

CCS Day		MeOH	Hexane	TCA	Toluene	Xylene	MeCl2	Freon	TCA	CCl4	TCE
Day 2	Conc. (ppm)	525.2	394.3	522.4	212.4	57.0	511.9	463.8	503.7	157.1	161.0
	%Rec	105.3	104.6	102.8	100.7	97.8	107.8	102.8	101.6	105.4	105.2
	Rel. % Error	5.3	4.6	2.8	0.7	-2.2	7.8	2.8	1.6	5.4	5.2
Day 3	Conc. (ppm)	531.3	378.8	507.8	200.2	58.7	505.7	457.7	498.2	160.7	158.5
	%Rec	106.5	100.5	100.0	94.9	100.7	106.5	101.5	100.4	107.9	103.6
	Rel. % Error	6.5	0.5	0.0	-5.1	0.7	6.5	1.5	0.4	7.9	3.6
Day 5	Conc. (ppm)	519.6	369.9	497.4	193.0	54.7	494.5	444.1	482.2	151.3	152.8
	%Rec	104.1	98.1	97.9	91.5	93.8	104.1	98.5	97.2	101.5	99.9
	Rel. % Error	4.1	-1.9	-2.1	-8.5	-6.2	4.1	-1.5	-2.8	1.5	-0.1
Day 8	Conc. (ppm)	527.4	326.2	439.5	187.2	56.8	461.9	425.0	455.0	142.6	145.4
	%Rec	105.7	86.5	86.5	88.7	97.4	97.2	94.2	91.7	95.7	95.0
	Rel. % Error	5.7	-13.5	-13.5	-11.3	-2.6	-2.8	-5.8	-8.3	-4.3	-5.0
Day 10	Conc. (ppm)	514.7	342.6	456.4	202.4	61.8	459.2	422.8	453.7	142.1	144.6
	%Rec	103.1	90.9	89.8	95.9	106.0	96.7	93.7	91.5	95.4	94.5
	Rel. % Error	3.1	-9.1	-10.2	-4.1	6.0	-3.3	-6.3	-8.5	-4.6	-5.5
Day 12	Conc. (ppm)	510.5	364.5	484.7	194.2	53.9	463.9	424.6	459.1	146.0	145.3
	%Rec	102.3	96.7	95.4	92.0	92.5	97.7	94.1	92.6	98.0	95.0
	Rel. % Error	2.3	-3.3	-4.6	-8.0	-7.5	-2.3	-5.9	-7.4	-2.0	-5.0
Day 16	Conc. (ppm)	514.8	362.5	483.1	196.3	57.0	464.5	422.0	455.9	148.4	142.9
	%Rec	103.2	96.2	95.1	93.0	97.8	97.8	93.6	91.9	99.6	93.4
	Rel. % Error	3.2	-3.8	-4.9	-7.0	-2.2	-2.2	-6.4	-8.1	-0.4	-6.6
Day 19	Conc. (ppm)	494.1	353.9	468.4	194.1	53.9	441.9	409.6	439.6	139.7	140.9
	%Rec	99.0	93.9	92.2	92.0	92.5	93.0	90.8	88.6	93.8	92.1
	Rel. % Error	-1.0	-6.1	-7.8	-8.0	-7.5	-7.0	-9.2	-11.4	-6.2	-7.9
Day 22	Conc. (ppm)	515.3	367.7	484.4	212.9	62.3	450.3	419.3	452.4	155.9	144.6
	%Rec	103.3	97.5	95.4	100.9	106.9	94.8	93.0	91.2	104.6	94.5
	Rel. % Error	3.3	-2.5	-4.6	0.9	6.9	-5.2	-7.0	-8.8	4.6	-5.5
Mean % Error		3.6	-3.9	-5.0	-5.6	-1.6	-0.5	-4.2	-5.9	0.2	-3.0
Standard Deviation		2.2	5.3	5.0	4.2	5.3	5.3	4.1	4.5	5.0	4.7

MeOH - Methanol, Hexane - Cyclohexane, TCA - 1,1,1-Trichloroethane, Xylene - para Xylene, MeCl2 - Methylene Chloride

Freon - Freon 113 (1,1,2-trichloro-1,2,2-trifluoroethane), CCl4 - Carbon Tetrachloride, TCE - Trichloroethylene

% Rec - Percent Recovery, Rel. % Error - Relative Percent Error

Table C-5. Percent relative error for continuing calibration standard analytes for test period IV.

CCS Day		MeOH	Hexane	TCA	Toluene	Xylene	MeCl2	Freon	TCA	CCl4	TCE
Day 2	Conc. (ppm)	447.6	405.1	504.5	214.3	52.8	362.1	446.2	531.3	264.2	166.5
	%Rec	89.7	107.5	99.3	101.6	90.6	76.2	98.9	107.1	177.3	108.8
	Rel. % Error	-10.3	7.5	-0.7	1.6	-9.4	-23.8	-1.1	7.1	77.3	8.8
Day 3	Conc. (ppm)	417.6	350.6	463.8	197.9	56.7	387.9	447.9	457.3	136.3	140.2
	%Rec	83.7	93.0	91.3	93.8	97.3	81.7	99.3	92.2	91.5	91.6
	Rel. % Error	-16.3	-7.0	-8.7	-6.2	-2.7	-18.3	-0.7	-7.8	-8.5	-8.4
Day 5	Conc. (ppm)	444.1	375.9	503.0	205.5	59.1	418.6	485.8	509.6	155.1	155.4
	%Rec	89.0	99.7	99.0	97.4	101.4	88.1	107.7	102.7	104.1	101.6
	Rel. % Error	-11.0	-0.3	-1.0	-2.6	1.4	-11.9	7.7	2.7	4.1	1.6
Day 8	Conc. (ppm)	451.4	379.1	504.9	214.9	63.2	416.5	484.6	508.6	152.1	155.2
	%Rec	90.5	100.6	99.4	101.8	108.4	87.7	107.5	102.5	102.1	101.4
	Rel. % Error	-9.5	0.6	-0.6	1.8	8.4	-12.3	7.5	2.5	2.1	1.4
Day 10	Conc. (ppm)	473.2	380.4	509.4	213.3	65.0	420.8	495.1	525.7	160.1	162.9
	%Rec	94.8	100.9	100.3	101.1	111.5	88.6	109.8	106.0	107.4	106.5
	Rel. % Error	-5.2	0.9	0.3	1.1	11.5	-11.4	9.8	6.0	7.4	6.5
Day 12	Conc. (ppm)	473.8	381.4	507.3	217.7	66.8	420.1	495.2	527.9	164.3	162.4
	%Rec	94.9	101.2	99.9	103.2	114.6	88.4	109.8	106.4	110.3	106.1
	Rel. % Error	-5.1	1.2	-0.1	3.2	14.6	-11.6	9.8	6.4	10.3	6.1
Day 16	Conc. (ppm)	488.0	404.7	546.0	231.9	68.7	447.0	522.4	543.0	155.7	164.8
	%Rec	97.8	107.3	107.5	109.9	117.8	94.1	115.8	109.5	104.5	107.7
	Rel. % Error	-2.2	7.3	7.5	9.9	17.8	-5.9	15.8	9.5	4.5	7.7
Day 19	Conc. (ppm)	473.1	388.4	527.2	226.0	67.9	445.2	516.9	536.7	162.4	164.0
	%Rec	94.8	103.0	103.8	107.1	116.5	93.7	114.6	108.2	109.0	107.2
	Rel. % Error	-5.2	3.0	3.8	7.1	16.5	-6.3	14.6	8.2	9.0	7.2
Day 22	Conc. (ppm)	476.3	395.7	530.9	229.9	67.3	434.3	511.0	531.7	153.1	165.1
	%Rec	95.5	105.0	104.5	109.0	115.4	91.4	113.3	107.2	102.8	107.9
	Rel. % Error	-4.5	5.0	4.5	9.0	15.4	-8.6	13.3	7.2	2.8	7.9
Mean % Error		-7.7	2.0	0.5	2.8	8.2	-12.2	8.5	4.7	4.0	4.3
Std. Dev.		4.4	4.5	4.5	5.3	9.6	5.7	6.1	5.2	5.8	5.5

MeOH - Methanol, Hexane - Cyclohexane, TCA - 1,1,1-Trichloroethane, Xylene - para Xylene, MeCl2 - Methylene Chloride

Freon - Freon 113 (1,1,2-trichloro-1,2,2-trifluoroethane), CCl4 - Carbon Tetrachloride, TCE - Trichloroethylene

% Rec - Percent Recovery, Rel. % Error - Relative Percent Error

Table C-6. Relative percent difference (RPD) for duplicate sample analyses during test period I.

(Concentrations in ppm)

Sample Location	MeOH	Hexane	TCA	Toluene	Xylene	MeCl ₂	Freon	TCA	CCl ₄	TCE
102-3SB4						774.6	228.9	303.2	68.0	49.0
102-3SB4D						758.7	225.2	291.7	65.1	48.4
RPD						2.07	1.63	3.87	4.36	1.23
103-3SB2						615.4	195.0	206.6	48.6	42.6
103-3SB2D						601.7	192.2	202.9	47.9	42.1
RPD						2.25	1.45	1.81	1.45	1.18
105-1SB2						248.7	162.9	156.7	39.3	34.4
105-1SB2D						247.0	162.7	163.3	41.3	37.5
RPD						0.69	0.12	-4.13	-4.96	-8.62
108-2SB2	No Data	No Data	No Data	No Data	No Data					
108-2SB2D	No Data	No Data	No Data	No Data	No Data					
RPD										
110-4SB2	108.3 *	65.7	101.5 *	18.6 *	6.4					
110-4SB2D	108.4 *	65.5	101.1 *	18.5 *	6.4					
RPD	-0.09	0.30	0.39	0.54	0.00					
112-2SB3	* 83.7 *	62.1	93.5 *	19.8 *	6.7					
112-2SB3D	* 83.3 *	70.4	101.3 *	24.3 *	7.6					
RPD	0.48	-12.53	-8.01	-20.41	-12.59					
116-1SB4						102.3 *	67.3 *	79.9 *	19.5 *	14.7
116-1SB4D						104.5 *	68.7 *	88.2 *	22.7 *	17.6
RPD						-2.13	-2.06	-9.88	-15.17	-17.96
119-4SB3	* 79.6 *	57.0 *	86.0 *	16.7 *	6.1					
119-4SB3D	* 79.5 *	57.1 *	86.1 *	16.6 *	6.1					
RPD	0.13	-0.18	-0.12	0.60	0.00					
122-3SB3						110.6 *	65.4 *	82.0 *	20.2 *	13.5
122-3SB3D						111.0 *	65.3 *	81.9 *	19.4 *	13.6
RPD						-0.36	0.15	0.12	4.04	-0.74

MeOH - Methanol, Hexane - Cyclohexane, TCA - 1,1,1-Trichloroethane, Xylene - para Xylene, MeCl₂ - Methylene Chloride

Freon - Freon 113 (1,1,2-trichloro-1,2,2-trifluoroethane), CCl₄ - Carbon Tetrachloride, TCE - Trichloroethylene

RPD - Relative Percent Difference, * - Outside Linear Dynamic Range

Table C-7. Relative percent difference (RPD) for duplicate sample analyses during test period II.

(Concentrations in ppm)

Sample Location	MeOH	Hexane	TCA	Toluene	Xylene	MeCl2	Freon	TCA	CCl4	TCE
202-3SB4						579.2	180.4	203.3	48.3	35.5
202-3SB4D						568.0	179.0	198.8	48.2	35.2
RPD						1.95	0.78	2.24	0.21	0.85
203-3SB2						389.0	161.5	160.6	41.1 *	32.0
203-3SB2D						380.3	160.1	159.0	40.3 *	31.7
RPD						2.26	0.87	1.00	1.97	0.94
205-1SB2						240.3	138.7	143.7	36.9 *	29.6
205-1SB2D						213.4	127.7	135.5	36.5 *	29.8
RPD						11.86	8.26	5.87	1.09	-0.67
208-2SB2	106.7 *	59.3	96.8 *	16.5 *	4.9					
208-2SB2D	106.0	75.5	112.8 *	16.4 *	7.4					
RPD	0.66	-24.04	-15.27	0.61	-40.65					
210-4SB2	107.4 *	61.8	100.7 *	14.9 *	4.8					
210-4SB2D	107.6 *	61.8	100.7 *	14.9 *	4.8					
RPD	-0.19	0.00	0.00	0.00	0.00					
212-2SB3	* 73.0 *	47.8 *	77.1 *	15.0 *	5.0					
212-2SB3D	* 74.1 *	56.9 *	86.4 *	19.4 *	5.8					
RPD	-1.50	-17.38	-11.38	-25.58	-14.81					
216-1SB4						* 89.0 *	* 64.3 *	* 76.6 *	* 19.9 *	* 17.4
216-1SB4D						* 78.8 *	* 58.2 *	* 74.3 *	* 19.7 *	* 18.5
RPD						12.16	9.96	3.05	1.01	-6.13
219-4SB3	* 74.2 *	46.0 *	76.6 *	10.9 *	4.3					
219-4SB3D	* 74.2 *	46.0 *	76.6 *	10.9 *	4.3					
RPD	0.00	0.00	0.00	0.00	0.00					
222-3SB3						95.9 *	* 65.1 *	* 75.2 *	* 20.3 *	* 15.4
222-3SB3D						95.3 *	* 64.6 *	* 75.1 *	* 20.6 *	* 15.4
RPD						0.63	0.77	0.13	-1.47	0.00

MeOH - Methanol, Hexane - Cyclohexane, TCA - 1,1,1-Trichloroethane, Xylene - para Xylene, MeCl2 - Methylene Chloride
 Freon - Freon 113 (1,1,2-trichloro-1,2,2-trifluoroethane), CCl4 - Carbon Tetrachloride, TCE - Trichloroethylene
 RPD - Relative Percent Difference, * - Outside Linear Dynamic Range

Table C-8. Relative percent difference (RPD) for duplicate sample analyses during test period III.

(Concentrations in ppm)

Sample Location	MeOH	Hexane	TCA	Toluene	Xylene	MeCl ₂	Freon	TCA	CCl ₄	TCE
302-3SB4	286.5	128.5	229.0 *	26.6 *	9.6					
302-3SB4D	271.1	123.6	219.5 *	26.2 *	9.5					
RPD	5.52	3.89	4.24	1.52	1.05					
305-3SB2	149.7	80.5	129.8 *	18.6 *	8.7					
305-3SB2D	144.3	78.5	126.5 *	18.3 *	8.6					
RPD	3.67	2.52	2.58	1.63	1.16					
307-1SB2						168.5	112.2	118.0 *	28.9 *	22.4
307-1SB2D						* 86.6	* 65.3	* 72.8	* 17.8	* 16.3
RPD						64.21	52.85	47.38	47.54	31.52
309-2SB2	108.9 *	67.5	103.3 *	16.2 *	8.5					
309-2SB2D	104.4	74.7	109.7 *	21.5 *	9.6					
RPD	4.22	-10.13	-6.01	-28.12	-12.15					
312-4SB2						119.6 *	70.8 *	80.4 *	17.6 *	14.0
312-4SB2D						119.1 *	71.2 *	80.4 *	17.7 *	14.0
RPD						0.42	-0.56	0.00	-0.57	0.00
314-2SB3	* 51.9	* 35.2	* 49.4	* 11.4	9.1					
314-2SB3D	No Data	No Data	No Data	No Data	No Data					
RPD										
316-1SB4						No Data	No Data	No Data	No Data	No Data
316-1SB4D						* 83.7	* 59.4	71.1	* 14.7	* 16.1
RPD										
319-4SB3						* 76.5	* 52.4	* 62.5	* 11.5	* 10.9
319-4SB3D						* 48.8	* 38.5	* 45.6	* 7.8	* 8.7
RPD						44.21	30.58	31.27	38.34	22.45
322-3SB3	* 59.3	* 41.3	* 67.3	* 8.0	* 7.9					
322-3SB3D	* 57.4	* 41.2	* 67.2	* 8.0	* 7.6					
RPD	3.26	0.24	0.15	0.00	3.87					

MeOH - Methanol, Hexane - Cyclohexane, TCA - 1,1,1-Trichloroethane, Xylene - para Xylene, MeCl₂ - Methylene ChlorideFreon - Freon 113 (1,1,2-trichloro-1,2,2-trifluoroethane), CCl₄ - Carbon Tetrachloride, TCE - Trichloroethylene

RPD - Relative Percent Difference, * - Outside Linear Dynamic Range

Table C-9. Relative percent difference (RPD) for duplicate sample analyses during test period IV.

(Concentrations in ppm)

Sample Location	MeOH	Hexane	TCA	Toluene	Xylene	MeCl2	Freon	TCA	CCl4	TCE
402-3SB4						562.8	142.3	226.9	88.3 *	33.7
402-3SB4D						554.8	140.0	219.5	84.5 *	33.3
RPD						1.43	1.63	3.32	4.40	1.19
403-3SB2						447.0	120.7	132.8	35.8 *	24.9
403-3SB2D						439.2	119.3	130.6	34.8 *	24.7
RPD						1.76	1.17	1.67	2.83	0.81
405-1SB2						337.9	130.8	142.1	40.2 *	29.9
405-1SB2D						326.7	130.9	150.1	43.9	35.2
RPD						3.37	-0.08	-5.48	-8.80	-16.28
408-2SB2	* 81.0	* 64.2	105.8	* 3.3	ND					
408-2SB2D	* 79.9	74.8	116.9	* 10.6	ND					
RPD	1.37	-15.25	-9.97	-105.04						
410-4SB2	* 72.2	* 66.3	108.7	* 3.4	ND					
410-4SB2D	* 72.4	* 66.0	108.2	* 3.3	ND					
RPD	-0.28	0.45	0.46	2.99						
412-2SB3	* 65.3	* 53.3	88.1	* 0.7	ND					
412-2SB3D	* 65.0	* 60.8	95.5	* 6.1	ND					
RPD	0.46	-13.15	-8.06	-158.82						
416-1SB4						193.1 *	56.4 *	81.7 *	25.0 *	20.0
416-1SB4D						195.0 *	57.7 *	89.8 *	27.7 *	23.1
RPD						-0.98	-2.28	-9.45	-10.25	-14.39
419-4SB3	* 46.7	* 42.3	* 71.9	ND	ND					
419-4SB3D	* 46.8	* 42.2	* 71.9	ND	ND					
RPD	-0.21	0.24	0.00							
422-3SB3						186.1 *	40.8 *	67.7 *	19.1 *	13.5
422-3SB3D						185.7 *	40.8 *	67.9 *	19.1 *	13.6
RPD						0.22	0.00	-0.29	0.00	-0.74

MeOH - Methanol, Hexane - Cyclohexane, TCA - 1,1,1-Trichloroethane, Xylene - para Xylene, MeCl2 - Methylene Chloride

Freon - Freon 113 (1,1,2-trichloro-1,2,2-trifluoroethane), CCl4 - Carbon Tetrachloride, TCE - Trichloroethylene

RPD - Relative Percent Difference, * - Outside Linear Dynamic Range, ND - Not Detected

Appendix D

Computer Program of VOC Transport Model for Lab-Scale Simulated Waste Drums


```

c
c program calculates the VOC concentration as a function of time
c in a simulated waste drum. The drum contains small poly bags initially
c filled with VOC-containing air. These bags were placed in a large poly
c bag inside a 90-mil rigid polyethylene liner, inside a vented metal drum.
c-----
c allows user to specify different model parameters for one small bag
c the parameters for other three small bags are the same. this allows user
c to describe situations where one bag may be smaller, have a leak, etc.
c-----
c model accounts for VOC accumulation in poly bags and liner
c-----
c model allows user to specify if drum temperature is constant or variable
c-----
c The program utilizes an IMSL routine to solve a series of first-order
c ordinary differential equations.
c
character*32 test,ifname,ofname,vocid(9)
real aa(1,1),yy(5,5),yz(9),sb1(5,21),sb2(5,21),lb(5,21),dh(5,21)
real param(50),p,d,ap(5),ad(5),v(5),xp(5),xd(5),mw
integer ivoc(5)
common/qq/p,d,ap,ad,v,xp,xd,pi,patm,pHg,dfh,c0,mw,temp0,
#vpb,vpc,y0,s0c0,nft,thr1
common/ss/s6,s7,s8,s9
external fcn,ivpag,sset
c-----
c input
c-----
write(*,9)
9 format(1x,'Enter name of input data file ')
read(*,*)ifname
open(unit=3,file=ifname,status='unknown')
c-----
c User provided input
c nvoc - number of VOCs in drum
c y(i,n) - i-th VOC concentration in n-th layer of confinement, (mol/cm3)
c n=1, small bag headspace (for 3 identical bags)
c n=2, small bag headspace (for 4th small bag)
c** allows user to specify unique conditions of one of four small bags
c n=3, large bag headspace
c n=4, drum liner headspace
c n=5, drum headspace
c ap(n) - permeation surface area around n-th layer of confinement (cm2)
c ad(n) - cross-sectional area for diffusion out of n-th layer
c of confinement (cm2)
c xp(n) - thickness of permeable surface (cm)
c xd(n) - length of diffusional path between layers of confinement (cm)
c v(n) - void volume in n-th layer of confinement (cm3)
c *****
c ivoc - VOC identification number
c 1 - CC14 2 - cyclohexane 3 - methanol 4 - CH2Cl2
c 5 - toluene 6 - TCA 7 - TCE 8 - Freon-113 9 - p-xylene
c *****
vocid(1)='carbon tetrachloride'
vocid(2)='cyclohexane'
vocid(3)='methanol'
vocid(4)='methylene chloride'
vocid(5)='toluene'
vocid(6)='1,1,1-trichloroethane'
vocid(7)='trichloroethylene'
vocid(8)='Freon-113'
vocid(9)='p-xylene'

```

```

c yvoc(i) - concentration of VOC i in drum headspace, ppmv
c nft - if = 1, temperature = constant
c       if = 2, temperature = f(t)
c thr1 - approximate number of hours after t=0 when heating cycle begins
c thr2 - approximate number of hours after t=0 when small bags first sampled
c temp - drum temperature, C
c pHg - atmospheric pressure, cm Hg
c dfh - carbon composite filter H2-diffusion constant, mol/s/mol fraction
c-----
c initial conditions
  read(3,*)test,ofname
  open(unit=2,file=ofname,status='unknown')
  read(3,*)nvoc
c neq - number of layers of confinement inside waste drum
  neq=5
  do 8 i=1,nvoc
    read(3,*)ivoc(i),(yy(i,j),j=1,neq)
  8 continue
  read(3,*)(ap(j),ad(j),v(j),xp(j),xd(j),j=1,neq)
  read(3,*)nft,thr1,thr2,temp,pHg,dfh
c-----
c r0 - gas constant (cm3 atm/mol K)
c patm - atmospheric pressure (atm)
  r0=82.06
  pi=3.141592654
c convert pHg (cm Hg) to patm (atm)
  patm=pHg/76.0
c temp0 - initial drum temperature, K
  temp0=temp+273.2
c c0 - initial gas concentration in each layer of confinement (mol/cm3)
  c0=patm/(r0*temp0)
cccccc*****
cccccc  calculate concentration throughout waste drum for each VOC
cccccc*****
  nv=nvoc
  do 43 i=1,nv
c-----
c convert VOC gas concentration from ppmv to mol/cm3
  do 37 j=1,neq
    yz(j)=yy(i,j)*c0*1.e-6
  37 continue
c VOC conc. in polymer walls (6(3); 9(1) -small bag, 7 -large bag, 8 - liner)
c (cm3 VOC/cm3 polymer)
  yz(6)=0.
  yz(7)=0.
  yz(8)=0.
  yz(9)=0.
  nq=9
c y0 - initial VOC concentration in gas feed, mol/cm3
  y0=yz(1)
c-----
c set param to default values
  mxparm=50
  CALL SSET(mxparm,0.0,param,1)
  param(4)=150000
  param(10)=2
c param(12): 1=Adams' method; 2=Gear's backward difference method
  param(12)=2
c-----
c initialization of other variables
c t - time (sec)
  t=0.

```