DOE/PC/91040--T3

**ADVANCED DIRECT LIQUEFACTION CONCEPTS
for PETC GENERIC UNITS**

DOE/PC/91040--T3

DE92 041281

**Quarterly Technical Progress Report
for Period April 1992 through June 1992**

by

**University of Kentucky
Center for Applied Energy Research**

Sandia National Laboratories

Consolidation Coal Company

LDP Associates

August 1992

Prepared for

The U. S. Department of Energy

Under Contract No.

DE-AC22-91PC91040

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISSEMINATION OF THIS DOCUMENT IS UNLIMITED

AUG 28 1992

INDEX

INDEX	ii
LIST OF TABLES	iii
LIST OF FIGURES	iv
SUMMARY	
Task 1 - Laboratory Support	1
Task 2 - Pretreatment Work	2
WORK PERFORMED	
Task 1.1 - Laboratory Support UK/CAER	4
Coal Analysis	5
Wilsonville Product Samples	7
Task 1.2 - Laboratory Support Consol	10
Task 1.3 - Laboratory Support Sandia	11
Task 2.1.1 Pretreatment Work UK/CAER	13
Experimental	14
Procedures	14
Effect of CO and Water Loading	16
Elemental Analysis of Products	19
Integrated Water Insoluble Product	21
Mechanistic Considerations	23
Effect of Coal Concentration	24
Fate of Sodium	26
Characterization of CO Pretreated	
Products	26
Physical Properties	26
Fluorescence Microscopy	27
FTIR Spectrometry	28
Coal and Pretreated Coal	31
Humic Acid Material	32
Pyridine Extraction of Raw and	
CO Pretreated Coal	33
Conclusions	36
Task 2.1.3 - Pretreatment Work Consol	36
Task 2.1.3/2.3.3 - Solvent Pretreatment and	
Catalyst Studies	39
Background	40
Experimental	41
Results from Tests with CoMo Cat	41
Results from Tests with NiMo Cat	43
Feed Rate Effects	45
Conclusions	45
Task 2.3.1 - Iron Based Dispersed Catalysts	47
Reactivity of Black Thunder Coal	47
Liquefaction with Wilsonville	
Composite Solvent	50
Liquefaction Solvent Composition	52
Material Balance and Product	
Yield Computational Methods	54

Ash Balance	55
Product Yields	57
Reactivity of Wilsonville Solvent	58
Coal Conversion in Wilsonville	
Composite Solvent	64
Thermal Runs	64
Wilsonville Fe ₂ O ₃	66
Nanometer Size Iron Oxide	67
Molybdenum Catalysts	69
Mass Transfer Characteristics of	
Microautoclave Reactor	71
REFERENCES	77

LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page</u>
1	Wilsonville Samples Stored at UK	4
2	Black Thunder Coal Analysis	5
3	Run 262: Black Thunder Mine Coal Analysis	
	Wilsonville Data	6
4	Wilsonville Run 262 Product Stream Analysis	7
5	Solvent Separation of Wilsonville Run 262	
	Product Streams	8
6	Analysis Methods Comparison	9
7	Metals Contents in Wilsonville Prod Fractions	10
8		13
9	Analyses of Wyodak and Black Thunder Coals	15
10	Effect of CO and Water on Wyodak Pretreatment	17
11	Elemental Analysis of THF Insolubles	19
12	Elemental Analysis of PA+A	20
13	Yield and Analysis of Total Water	
	Insoluble Products	22
14	Effect of Coal Concentration on CO Pretreat	25
15	Liquefaction of CO Pretreated Coal	34
16	Results of Ketone Dewaxing of Wilsonville	
	9/16/91 V-1074 Heavy Distillate	38
17	Proton Distribution of Feed and Product	
	Samples from Dewaxing Runs	39
18	Potassium Promotion of Water Gas Shift Rx	42
19	Catalyst Hydrogenation Activities in WGS Rx	44
20	Synthetic Solvent Hydrogenation	45
21	Liquefaction of Black Thunder Coal	
	in Tetralin	48
22	Liquefaction of Wyodak and Black	
	Thunder Coals	49
23	Analyses of Primary Oil Samples from	
	Wilsonville Run 262	53

24	Liquefaction Solvent Composition	54
25	Forced Ash Balance	56
26	Product Yield Calculation	57
27	Thermal Conversion of Composite Wilsonville Solvent	59
28	Catalyst Precursors	61
29	Effect of Catalyst on Wilsonville Solvent Conversion	61
30	Conversion of Wilsonville Ashy Resid	63
31	Coal Conversion in Wilsonville Composite Solv	64
32	Liquefaction with Wilsonville Fe ₂ O ₃	66
33	Effect of Ashy Resid on Liquefaction with Iron Oxide	68
34	Nanometer Iron Oxide Catalysis	69
35	Black Thunder Liquefaction with Molybdenum	70
36	Liquefaction in Horizontal Tubing-Bomb Reac	73
37	Mean and Standard Deviations for Product Fractions	74
38	ANOVA Results: Effects of Reactor Balls	75

LIST OF FIGURES

<u>Figure</u>	<u>Title</u>	<u>Page</u>
1	Capillary Gas Chromatograms of Wilsonville Heavy Distillate Fractions	12
2	FTIR spectra of Raw and Water Insoluble Coal	29
3	FTIR Spectra of Humic Acid from Coal Reaction	30
4	Concentration vs Time	46
5	Microautoclave Reactor Drawing	72

SUMMARY

TASK 1 - Laboratory Support

CAER/UK: Detail coal and starting solvents from Wilsonville were analyzed to develop the data necessary to conduct process studies in the CO Pretreatment and Catalyst Evaluation segment of this program. A comparison of the solvent separation analysis with the distillation/separation used at Wilsonville showed that the residual solvent components contained a large amount of residual pentane soluble products. This caused the quantities of the solubility classifications to differ significantly from the distillation separation fractions such that the oils contents of the composite solvent did not approach the 1050°F fraction. The metals concentrations in the residual fractions showed that a significant amount of molybdenum and iron were contained in these fractions. The ashy resid contained 3% iron and 400 ppm molybdenum. Although the iron content in the distillate and deashed resid was much less, namely about 200 ppm., the molybdenum concentrations in these fractions were not significantly reduced over the concentration in the ashy resid, i.e., 200 ppm in each.

Consol: Consol has provided samples and background information on Wilsonville Run 262 to UK and Sandia. Additional ashy resid (V-1082) from Run 262 was requested from Wilsonville but was not available; however, a drum of atmospheric flashed bottoms (V-1067) from Run 260 was obtained which can serve as a back-up source of ashy resid from Black Thunder coal for this project. Three gallons of this V-1067 oil were shipped to Dr. Bogdan Slomka at Ames Laboratory to test in an emulsification process for deashing such oils which may be useful in the planned agglomeration work under this contract.

Sandia: Heavy distillate from Wilsonville was separated into aliphatic and aromatic fractions using column chromatography. Elemental analysis and capillary chromatography of the V1074 fractions illustrate the waxy nature of this solvent.

TASK 2 - Pretreatment and Catalyst Work

UK/CAER: The pretreatment of coal with CO/H₂O in the presence of NaOH and Na₂CO₃ has been shown to give a product which is lower in oxygen content and higher in hydrogen content compared to the raw coal. The atomic H/C ratios of the H₂O-insolubles, THF insolubles and the PA+A fractions of the products together with the hydrogen consumption data suggested that the raw coal has been substantially depolymerized and hydrogenated via the WGS reaction during the pretreatment process. The extensive amount of molecular reconstruction that has occurred in the solid product was evident from the ease of solubilization of the product into pyridine. The result of the pretreatment process is a product which is highly reactive under hydroliquefaction conditions at 400°C. Reaction rates seem to be much faster than the raw coal, especially at shorter reaction times, providing the opportunity for major reductions in plant vessel sizes, and preliminary data has led us to believe that better efficiency in hydrogen utilization is achieved.

Liquefaction of Black Thunder coal was evaluated in both tetralin and the Wilsonville composite solvent which contains the distillate and ashy resid components. Conversion in tetralin indicated conversions were quite similar to Wyodak. Results in Wilsonville were much more complicated since the solvent undergoes considerable conversion itself under reaction conditions showing from 40 to 50% conversion for the catalysts that were tested. Catalyzed coal conversions in this solvent were regularly over 100% due to this extraordinary reactivity of

the solvent. A significant catalytic effect was observed with nanometer sized iron oxide catalysts which gave the highest coal conversion we observed being the same as for Mo. The lower oil conversion versus the Mo suggests a combination co-metal could significantly improve the performance of this system. A mass transfer evaluation of the horizontal tubing bomb reactor showed that a statistically significant affect was observed upon adding reactor balls to the reactor while shaking rate had no effect. Adding balls decreased IOM thereby improving coal conversion as well as increased PA+A and gas make. No effect was observed on oils make or hydrogen consumption.

Sandia: Solvent pretreatment tests using the combined water-gas shift solvent hydrogenation reaction were performed with a potassium doped cobalt molybdenum (CoMo) catalyst which was supported on alumina and a hydrous titanium oxide (HTO) thin film catalyst prepared with multiple coats of nickel and molybdenum on a porous silica support. These were compared with a commercially available NiMo catalyst, supported on alumina. These catalysts were tested in a fixed bed microflow reactor by concurrently flowing carbon monoxide, hydrogen, steam and a synthetic donor solvent (9.5 wt% aromatics in hexadecane) at 275°C.

Tests with CoMo catalysts promoted with potassium have shown enhanced water-gas shift activity but decreased hydrogenation activity. Combined water-gas shift solvent hydrogenation experiments have shown that sulfided NiMo catalysts are very effective at 275°C. Shell 324 was slightly more active than the thin-film HTO catalyst on a catalyst weight basis, however the thin film HTO was more active on a catalyst metal basis.

WORK PERFORMED

TASK 1.1 - Laboratory Support (UK/CAER)

Starting Materials - Five Wilsonville stream samples to be used in this program were received from CONSOL were further divided for subsequent use in liquefaction studies. Description of these fractions and how they are stored is shown in Table 1.

Table 1. Wilsonville Samples Stored at UK

Coal		Ground Black Thunder
	Sample No.	1621-22-1-B
	Quantity	16 lbs
	Date Sample Taken	9/14/91
	Handling at UK	Riffled under nitrogen
	Storage	Stored under nitrogen in Marvelseal bags
Ashy Resid		Wilsonville V-1082
	Sample No.	1621-22-4-A
	Quantity	26.4 lbs
	Date Sample Taken	9/16/91 at 16:15
	Handling	Mixed, ground and screened to -8 mesh
	Storage	Stored under nitrogen in Marvelseal bags
Deashed Resid		Wilsonville V-130
	Sample No.	1621-22-3-A
	Quantity	8.6 lbs
	Date Sample Taken	9/16/91 at 13:00
	Handling	Mixed, ground and screened to -8 mesh
	Storage	Stored under nitrogen in Marvelseal bags
Distillate		Wilsonville V-1074
	Sample No.	1621-22-5
	Quantity	7.4 lbs
	Date Sample Taken	9/16/91 at 13:00
	Handling	None
	Storage	Stored as received

Coal Analysis - The sample of Black Thunder coal received from CONSOL had been ground to -200 mesh. To assure uniformity in this 16 pound sample it was riffled under nitrogen using a glove box and then separated into smaller quantities and stored in a refrigerator in sealed Marvelseal pouches under nitrogen. Proximate and ultimate analyses of the coal are presented in Table 2.

Table 2. Black Thunder Coal Analysis

	wt%
Proximate Analysis	
Moisture	21.2
Ash	6.11
Volatile Matter	35.36
Fixed Carbon	38.29
Ultimate Analysis	
Carbon	68.99
Hydrogen	4.78
Nitrogen	1.22
Sulfur	0.56
Oxygen (diff)	18.34
Sulfur Types	
Total	0.39
Pyritic	0.07
Sulfate	0.09
Organic	0.23

These data can be compared with the ultimate analyses in Table 3 from Wilsonville taken over a series of several balance periods using this coal.

Because of the significant water contents in Black Thunder coal and the impact this value has on the overall data calculation

Table 3

Run 262: Black Thunder Mine Coal Analysis (wt % MF)

	262A	262B	262C1	262C2	262D	262E	262F
Carbon	69.6	69.3	68.7	68.7	69.5	68.4	68.8
Hydrogen	5.3	5.2	4.7	4.7	5.0	4.8	5.1
Nitrogen	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Sulfur	0.6	0.4	0.5	0.5	0.5	0.5	0.5
Oxygen (by diff.)	17.1	17.8	18.5	18.5	17.6	18.8	18.0
Ash	6.4	6.3	6.5	6.5	6.4	6.3	6.5

SOURCE: Wilsonville Handouts

and interpretation moisture measurements are made generally each day runs are performed. During this reporting period a number of repeats of this measurement were made. From this series of 14 moisture measurements a value at the 95% confidence level of 21.89 ± 0.72 wt% was determined which supports the proximate moisture measurement above.

Wilsonville Product Samples - Analyses of the Run 262 Wilsonville product fractions that are being used in this program were provided by CONSOL from data developed at Wilsonville using their standard product characterization methods. This includes vacuum distillation to define the 1050 F distillate fraction and cresol as a solvent for defining the insoluble organic matter. The data for these product fractions are shown in Table 4.

Table 4. Wilsonville Run 262 Product Stream Analysis

		1050F DIST	Cresol Soluble Residue	Cresol Insol	Ash
Heavy Distillate	V-1074	100	0	0	0
Deashed Resid	V-130	16.0	83.9	0.01	0.11
Ashy Resid	V-1082	2.5	58.8	18.3	20.4
Recycle Solvent	V-131B	43.8	36.6	19.3 (includes ash)	
Calc Solvent	V-131B	45.0	35.3	9.3	10.4

There is excellent agreement between the observed composition of the recycle solvent and the composition calculated from the individual component streams.

In the microautoclave experiments that are being run at UK, a solvent separation method is being used to characterize both

reactants and products. This method, which is described in the second quarterly progress report, involves the use of tetrahydrofuran (THF) and pentane as the primary solvents. In this procedure the products are separated into a THF insoluble fraction (includes insoluble organic matter (IOM) and ash), a THF soluble-pentane insoluble fraction (includes the asphaltene and preasphaltene content), and a pentane soluble fraction (includes the oils). Included in the oil fraction is the water produced in the dissolution which results in a small error. Gases and hydrogen consumption are determined separately.

Analysis of each of the fractions of the Wilsonville produced starting materials using the our standard solvent separation scheme were performed. The results are shown in Table 5.

Table 5. Solvent Separation of Wilsonville Run 262 Product Streams

	Pentane Solubles	PA + A	THF Insol	Ash
H e a v y V-1074 Distillate	95.9	0.7	3.1	0.3
D e a s h e d V-130 Resid	63.5	32.6	3.4	0.4
Ashy Resid V-1082	29.8	31.9	18.3	20.0
Recycle Solv (calculated)	60.8	18.4	10.7	10.2

Comparing the Wilsonville distillation data with the solvent separation data presented here in Table 5, the pentane solubles are noticeably greater than the 1050 F distillation cut reported from Wilsonville. Earlier work had shown that for products from thermal liquefaction, solvent extraction techniques are comparable with vacuum distillation in describing the yield of the oil fraction, specifically when pentane is the extracting fluid.¹ Therefore the 1050 F fraction is surprisingly different

from thermally generated products which showed very little pentane solubles in the residual fraction. The high level of pentane solubles in this Wilsonville distillate fraction is consistent with the results reported from Sandia, on this same fraction which are discussed below. Although the oil fraction differs considerably from the distillate fraction, the total THF solubles from these fractions, as determined in our laboratory, are surprisingly similar to the sum of the cresol solubles plus 1050 F fraction in the Wilsonville analysis as shown in Table 6.

Table 6. Analysis Methods Comparison

		Dist+Cresol Solubles	THF Solubles	Δ
Heavy Distillate	V-1074	100	96.6	3.4
Deashed Resid	V-130	99.9	96.1	3.8
Ashy Resid	V-1082	61.3	61.7	-0.4
Recycle Solvent	V-131B	80.4	79.1 ^a	1.3

a. Calculated

Most of the difference between these two methods exists in the analysis of the heavy distillate and deashed resid which have extremely small ash contents and low levels of their respective solvent insolubles. For the fraction having a very high ash and solids contents, i.e. the ashy resid, the agreement between the values are excellent.

Because in Wilsonville Run 262 both molybdenum and iron catalysts were being fed to the process unit, each of the fractions were analyzed to determine the amount of metals present. This data are shown in Table 7.

Table 7
Metals Contents in Wilsonville Product Fractions (wt%)

	Ashy Resid	Heavy Distillate	Deashed Resid
Fe	3	0.02	0.01
Mo	0.04	0.02	0.02
Ni	<.01	<.01	<.01
Co	<.01	<.01	<.01

The ashy resid contained a significant concentration of both iron and molybdenum, e.g. 30,000 and 400 ppm, respectively. In the distillate the iron concentration is reduced significantly while the molybdenum remains much closer to the concentration in the ashy resid suggesting that the Mo is present in these fractions in a highly dispersed state rather than being agglomerated with the ash material. Neither nickel or cobalt were found in these fractions at detectable levels.

Overall, the very high oil levels in the residual fractions, the high molybdenum concentration in all the fractions as well as the very high iron content in the ashy resid are of concern in conducting experimental evaluations in reaction mixtures containing these components. The complications related to the use of these materials in our research program will be discussed below in relationship to results that have been obtained using these fractions.

TASK 1.2 - Laboratory Support (CONSOL)

Two iron oxide (Fe_2O_3) catalyst samples were received from Wilsonville Run 263. A 2 kg aliquot of one of these, Wilsonville No. 30290, was sent to T. Hager at the University of Kentucky. The remaining material is being stored, together with the Run 262

materials, for future experimental studies. Background information and Wilsonville data for Run 262 were sent to H. Stephens (Sandia) and T. Hager (UK-CAER). This completes the provision by CONSOL of all subbituminous-coal-related samples to UK and Sandia.

F. Burke and R. Winschel participated in the quarterly project review meeting in Albuquerque, New Mexico. At this meeting, DOE suggested that we request additional ashy resid (V-1082) material from Wilsonville Run 262 as a back-up. No ashy resid from subbituminous coal was available; however, Wilsonville sent us a drum of atmospheric flashed bottoms (V-1067) from Run 260. This oil contains distillate in addition to ashy resid, but can serve as a back-up source of ashy resid from Black Thunder coal for this project. Three gallons of this V-1067 oil were shipped to Dr. Bogdan Slomka at Ames Laboratory. Dr. Slomka intends to test this material in an emulsification process for deashing such oils. The results from this study may be useful in the planned agglomeration work under this contract. The remainder of this material will be held in reserve and used only if our supply of ashy resid from Wilsonville Run 262 is depleted.

Task 1.3 Laboratory Support (SANDIA)

Wilsonville Run 262E Heavy Distillate V 1074 was previously analyzed by column chromatography according to a modified separation scheme reported by Later² and found to have 61 wt% paraffinic material. This result suggests that this material is an excellent candidate for solvent studies involving dewaxing by CONSOL. Capillary chromatograms from the aliphatic and neutral aromatic portions of this separation are shown in Figure 1, and demonstrate the waxy nature of this solvent. The concentration and elemental analysis of each of these fractions are given in Table 4 along with the elemental analysis of the original V1074.

FIGURE 1 Capillary Gas Chromatograms of Wilsonville Heavy Distillate Fractions

Aliphatic Fraction of Run 262 (V1074)

Aromatic Fraction of Run 262 (V1074)

Table 8

Fraction	Wt%	Carbon wt%	Hydrogen wt%	Nitrogen wt%
V1074	100	89.5	9.9	0.4
Aliphatic	61	88.0	11.4	0.0
Aromatic	23.5	91.4	7.1	0.7
N-containing	9.3	83.8	7.4	1.2
Balance	6.2	NA	NA	NA

Laboratory support experiments will continue to evaluate solvent quality. Future tests will include donor solvent tests with coal in batch microautoclave reactors.

Task 2.1.1 Pretreatment Work (UK/CAER)

The work plan for CO pretreatment of coal was outlined in the first quarterly report (January-March 1992). Most of the work that is being presented here was carried out with Wyodak coal although work with Black Thunder coal is progressing and the results will be presented in a forthcoming quarterly report.

Initial studies were carried out to gauge the effect of carbon monoxide, water, coal, catalyst (NaOH, Na_2CO_3) and catalyst loadings on the pretreatment process at 300°C. The temperature selection for this initial study was based on the literature survey carried out in the first quarter³ which indicated that there is a significant impact of CO pretreatment on coal in the 250-350°C temperature regime. Moreover, a key consideration has been to quickly scope out the effect of residence time on the process before moving into lower or higher temperature regimes. Longer reaction times may be required due to slower reaction kinetics at lower temperatures, while at higher temperatures

pressure considerations and product handling may pose additional problems. The recovered products from the pretreatment process were characterized using a range of techniques including elemental analysis, FTIR (Fourier Transform-Infra-Red spectroscopy), Fluorescence Microscopy, TGA (Thermogravimetric Analysis) and pore size/surface area analysis.

At this stage of the study, the effectiveness of the pretreatment process was ascertained by the following criteria; (1) the extent of oxygen removal from the coal in the process, (2) the quality of the recovered product and its suitability for subsequent liquefaction, and (3) the level of reactivity of the pretreated product compared to that of the raw coal under liquefaction conditions.

Experimental

Coals - The analyses of both the Wyodak (no.91684, 1985) and Black Thunder coals, the latter which is shown in Table 2, are presented in Table 9 on a dry, ash free basis. Both coals have very similar chemical compositions and H/C ratios. The Wyodak coal sample, which had undergone oxidation due to exposure to air during storage over the years, had a higher oxygen content compared to the Black Thunder coal. The preparation and handling of this sample was discussed above.

Procedures - In a typical experiment a predetermined weight of water soluble salt (NaOH , Na_2CO_3) at a concentration of 2.5 wt% Na on maf coal was charged to a 25 ml vertical reactor and combined with the required amount of distilled water (2 to 6 ml). From 2.0-5.0 g of coal were added to the reactor, as required, and the reactor was sealed and pressurized with CO to between 200-800 psig and then leak tested. For some reactions, N_2 was substituted for CO .

Table 9. Analyses of Wyodak and Black Thunder Coals

	Wyodak	Black Thunder
Composition, wt % maf		
Carbon	71.0	73.9
Hydrogen	4.9	5.2
Nitrogen	1.3	1.3
Sulfur	1.1	0.6
Oxygen ^a	21.7	19.0
Ash, wt% mf	6.94	6.12
H/C Ratio	0.83	0.84
Number	No. 91684 (1985)	-

a. Oxygen by difference

Reactions were carried out in a fluidized sandbath set at 300°C while the reactor was being shaken at a rate of 400 cycles per minute. At the end of the reaction period, the reactor was quenched to room temperature in a bucket of water. The gaseous products were collected in a gas bomb and analyzed by gas chromatographic analysis. The solid-liquid products were scrapped from the reactor using THF and the mixture was placed in a thimble in a Soxhlet apparatus and extracted for 18 hours. The THF insoluble material, which was comprised of IOM and ash, was dried (80°C/25 mm Hg) and weighed. The THF solubles were concentrated by removing excess THF in a rotary evaporator. A 50:1 excess volume of pentane was added to the THF concentrate to precipitate the preasphaltenes and asphaltenes (PA+A). The mixture was placed in an ultrasonic bath for 3 min to facilitate the precipitation process before filtering off the PA+A. The PA+A fraction was dried and weighed. The oils were collected, concentrated and stored in sample bottles.

During the course of this investigation, it was found that the high concentration of water used (up to 6 ml.) in the

pretreatment process caused the THF soluble/insoluble mixture to tar and retard the extraction and filtration process. Furthermore, the high water concentration interfered with the precipitation of the preasphaltenes and asphaltenes. This resulted in poor experimental reproducibility in some of the earlier experiments that were performed. To overcome this problem, the products in the reactor are now scrapped and washed from the reactor using distilled water. The water is filtered and the product 'freeze dried' and stored in a refrigerator to prevent any undesirable retrograde reactions from occurring. The water insoluble material which is isolated is representative of the 'whole' pretreated coal. The water soluble portion, which is listed separately as humic acids, are recovered by acidifying the aqueous filtrate with hydrochloric acid. The precipitated humic acid was centrifuged, collected and dried. The acidified aqueous layer was extracted with ether.

In order to determine the IOM, PA+A and oils the water insoluble products are after drying at 80°C/25 mm Hg for 60 min. are further separated and categorized as THF insolubles (IOM + ash), PA+A and oils. Conversion results are expressed on a wt.% moisture and ash free (maf) coal basis.

The Effect of Carbon Monoxide and Water Loading

There were a series of 5 runs made to determine this effect. In order to see the maximum effect of the alkali salt on the pretreatment process, a high loading of NaOH (2-3 % wt. Na⁺ dry, ash free (maf) coal basis) was used in this study. The pH of the starting solution ranged from 11-12 and at the end of the reaction, the pH of the aqueous layer was between 5 and 6. The experimental plan was to study the effect of the initial CO pressure at two levels; 200 psig (low) and 800 psig (high) and examine how this parameter interacts with the water loading at

two levels (2 ml. (low). and 6 ml. (high)). A middle point (400 psig CO, 4 ml. H₂O) was included in the set. The results are presented in Table 10.

Table 10. Effect of CO and Water on Wyodak Pretreatment

	Temperature Pressure Coal NaOH	300°C 800 psig CO 2 g 2.5% on coal			
CO, psig	200	200	400	800	800
H ₂ O, ml	2.0	6.0	4.0	2.0	6.0
NaOH, Moles/L	1.0	1.0	0.67	0.33	0.33
THF Conv	21.4	30.8	27.2	25.9	30.0
Products, wt% maf coal					
PA+A	2.2	5.5	17.7	17.6	18.8
Oil+Gas+H ₂ O	13.0	19.3	6.8	8.3	11.2
Ether Extract	1.1	0.5			
Humic Acids	5.1	5.5	2.7		
WGS Conv ^a	78	82	47	33	5.0
H ₂ Consumed, mg/g maf coal ^b	NA	NA	13.0	21.7	25.7
Run No.	52	48	46	49	45

a. WGS Conv calculated as $[\text{CO}_{\text{in}} - \text{CO}_{\text{out}}] / \text{CO}_{\text{in}} \times 100\%$

b. H₂ Consumed is $[\text{H}_2(\text{from WGS}) - \text{H}_2(\text{final})] / \text{maf coal}$

At low CO partial pressure (200 psig), increasing the water concentration from 2 to 6 ml. increased THF coal conversion from 21% to 31% (cf. Run 52 with 48). The corresponding PA+A yields were both very low, i.e. 2% and 5%, respectively, and the water soluble coal product, which is a combination of the acid insoluble humic acids and the ether extract, was ca. 6 wt%.

In these runs at 200 psig CO pressure the WGS reaction was from 78-82% complete within the reaction time indicating that the WGS reaction is quite rapid relative to the coal liquefaction rate.

This suggests rapid depletion of carbon monoxide (at low CO pressure charge) forming CO₂ and H₂ before any significant coal upgrading/conversion can take place. This may explain the low PA+A yields and the seemingly high yields of water soluble products plus oil+gas+water. This may be largely attributed to thermal processes which, in a hydrogen deficient environment, dominate over competing hydrogenation reactions. The hydrogen consumption data when it becomes available should provide some insight to the reaction processes occurring at these low CO partial pressures.

At high CO pressures (800 psig), there is a 4% difference in THF conversions between reactions in the high and low water concentration runs (see Runs 45 and 49). In both runs more than 50% of the THF soluble products report to the PA+A fraction, i.e., 17.6 and 18.8 wt% maf coal, respectively. The corresponding oil+gas+water yield is more modest for these two reactions and there is an absence of humic acid material in the reaction product, which includes both the acid insoluble and ether extracted (EE) material. This is consistent with the picture of portions of the coal structure breaking down into smaller fragments and being stabilized and hydrogenated by the active WGS intermediates. In these runs the WGS reaction is only 33 and 50% converted in the low and high water concentration runs, respectively, compared to the much higher conversion values in the lower 200 psig runs.

In a 400 psig CO pressure run made at 4 ml water loading, the THF conversion, PA+A yield, and WGS reaction completion were comparable to the higher CO pressure reactions. The amount of humic acids (2.7%) produced was half that formed in the 200 psig CO pressure runs while there was no ether extract produced.

The effect of water on these reactions is seen in higher coal

conversions at the higher water concentrations. At both 200 and 800 psig the conversion is higher at the 6 g water level versus the 2 g level. This corresponds to a higher conversion at the lower initial base concentration, i.e., 1 M and 0.33 M at 2 ml and 6 ml water charge levels, respectively.

Elemental Analysis of Products - Chemical compositional analysis of the different product components, which are presented in a series of tables, provide insight into the pretreatment process.

IOM Product - The elemental analysis of the THF insoluble products, which ranged between 69 and 79 wt% (maf basis) of the original coal, are shown in Table 11. The composition of the THF insoluble product giving the highest THF conversion of 30.8% was not determined.

Table 11. Elemental Analysis of THF Insolubles

CO, psig	200	400	800	800
Water, ml	2	4	6	2
IOM Yield, wt maf coal	78.6	72.8	70	74.1
Analysis, wt% maf				
Carbon	78.9	76.7	78.4	78.3
Hydrogen	4.9	5.1	5.6	5.3
Nitrogen	1.3	1.5	1.4	1.4
Sulfur	0.8	0.9	1.1	1.0
Oxygen	14.1	15.8	13.5	14.0
Hydrogen/Carbon	0.75	0.80	0.86	0.82
H ₂ consumed, mg/g maf coal	NA	13	25.9	21.7

NA = not available

The oxygen contents over this series differed by a maximum of 2.3% ranging from 13.5 to 15.8 wt% (maf coal) while the atomic hydrogen/carbon ratio ranged from 0.75-0.82. The hydrogen

consumption values, which range between 13 and 26 mg/g coal, appear to increase as both the hydrogen content in the IOM product as well as the hydrogen to carbon ratio increases. Both decreasing oxygen content and increasing H/C ratio requires a hydrogen source. Therefore, one of the factors in evaluating the effectiveness of the pretreatment process is determining the hydrogen consumption by the coal. As hydrogen consumption increases, better products, defines as having lower oxygen and higher combined hydrogen contents are obtained. The IOM products obtained at low CO partial pressures are poorly hydrogenated and have higher oxygen levels suggesting they are poorer quality materials for subsequent hydroprocessing because they have undergone mainly thermal conversions involving decarboxylation and pyrolysis reactions.

PA+A Products - The elemental analysis of PA+A products were determined for only runs made with 400 psig CO/4 ml H₂O and 800 psig CO/2 ml H₂O as shown in Table 12. In both these runs the PA+A yields were ca. 18 wt% (maf basis) of coal. The oxygen contents are similar to the values of the THF insolubles from the corresponding runs while the H/C ratios are much higher.

Table 12. Elemental Analysis of PA+A

CO, psig	400	800
Water, ml	4	2
PA+A Yield, wt%	17.7	17.6
Analysis, wt% maf		
Carbon	79.0	77.7
Hydrogen	6.2	6.4
Nitrogen	1.8	1.4
Oxygen + Sulfur	13.0	14.5
Hydrogen/Carbon	0.94	0.98

Water Soluble Products - In this series of runs insufficient water soluble products were isolated to provide sufficient sample to make a detailed analysis. Some discussion of these materials will be provided in the following sections.

Integrated Water Insoluble Product

Since it is likely that any liquefaction process would involve feeding the total water insoluble material from a CO pretreatment process this type of material was prepared and evaluated in a series of runs. In this set, the water insoluble products were obtained from the following reactions of Wyodak coal at 300°C with 2.5% Na loading (dry coal basis); 200 psig CO/2 ml H₂O, 400 psig CO/4 ml H₂O and 800 psig CO/6 ml H₂O. For comparison purposes, a reaction was carried out with 800 psig N₂/6 ml.H₂O. The results are presented in Table 13.

In absence of CO 80 wt% of H₂O-insoluble product was obtained which had a lower oxygen (13.6%) and lower H/C ratio (0.72) relative to the starting coal which were 21.7% and 0.83, respectively. When N₂ is replaced with 200 psig CO gas, the H₂O-insoluble yield increased and had a higher oxygen content and a slightly higher H/C ratio than the N₂ products. This result supports the contention that the low CO pressure system is a hydrogen deficient system. As the initial CO pressure increases to 800 psig, the oxygen content of the H₂O-insolubles drops to ca. 14.4% and the H/C ratio rises to 0.92 (compare 21.7% oxygen and H/C=0.83 for the coal). This represented a 1/3 reduction in the oxygen content and a 20% increase in the hydrogen content of the raw coal. In these higher CO pressure cases no humic acid was produced from the reaction.

Table 13. Yield and Analysis of Total Water Insoluble Product

	N ₂	N ₂	CO	CO	CO	CO
Pressure, psig	800	800	200	400	400	800
H ₂ O, ml	6	6	2	4	4	6
Product	WI	HA	WI	WI	HA	WI
Yield, wt% maf coal	80	7	85	81	2.7	74
Composition, wt % maf coal						
Carbon	79.5	75.0	77.1	75.6	72.6	77.7
Hydrogen	4.7	3.3	4.8	5.2	2.1	5.9
Nitrogen	1.5	4.2	1.2	1.3	5.5	1.33
Sulfur	0.7	-	0.8	0.8	-	1.2
Oxygen	13.6	17.5	16.1	17.1	19.8	14.4
Hydrogen/ Carbon	0.72	0.52	0.75	0.83	0.35	0.92

WI = Water insoluble

HA = Humic Acids

When the coal is reacted in the presence of N₂, a humic acid component forms (7 wt% maf coal) which had a reasonably high oxygen content (17.5 wt%) and a low H/C ratio (0.52). The corresponding product when formed in the presence of CO had a chemical composition that was directionally the same as found in nitrogen, even though it was produced at 400 psig CO. The quantity produced in nitrogen was somewhat more than produced in

CO at 400 psig, which is as expected based upon the decreased yields that were observed at the higher CO partial pressures above.

Therefore, it is clear that in either low pressures of CO or in the N₂ case, the low oxygen content in the water insolubles can be attributed, in part, to the partitioning of oxygen into the humic acid in the aqueous phase.

Mechanistic Considerations in CO Pretreatment

Examination of all the results preceding this section gave some insight into the pretreatment process:

The amount of CO charged into the reactor system has a strong bearing on the outcome of the pretreatment process. Adding a high concentration of water tends to drive the WGS reaction further to the right. This can be a dubious exercise if the CO pressure is low to start with as it will be depleted fairly rapidly in a closed reactor system. Under these conditions, a large amount (up to 25% wt. maf coal) of thermally generated product is formed which represents wastage because this material will likely end up either in the processing effluent or the gas phase.

The results in Table 10 suggest that higher CO pressures are needed to convert and hydrogenate the coal. Unlike the low CO pressure runs, the proportion of "waste products", e.g., oil+gas+water and humic acids, relative to amount of THF soluble products was lower. It appears that controlling the WGS reaction is critical to promoting the coal conversion and hydrogenation reactions. This is consistent with a mechanism in which the coal obtains its hydrogen from a WGS intermediate such as a formate ion or related precursor which decomposes to CO₂ and H₂.⁴ It is

likely that the coal reaction is the limiting step in the reaction scheme. Thus, compared to the coal reaction, the WGS reaction is so fast that in a closed system a significant portion of the CO is wasted. Therefore, the implication is that the same level of pretreatment may be accomplished, and even perhaps enhanced, in a well stirred reactor system where using a continuous flowing stream of low pressure CO. Controlling water concentration also can result in maintaining reasonable WGS activity and possibly lead to an overall lower system pressure.

Effect of Coal Concentration on CO Pretreatment

The efficient use of the water-gas-shift reaction is fundamental to the success of the CO pretreatment process. Del Bianco et al.⁵ showed that there was a linear correlation between the hydrogen consumed and the amount of coal present in the reaction (0.5-2.0 g) for three sets of experiments carried out with different initial CO pressures between 3-6 MPa. They noted that the amount of hydrogen consumed in the reaction per gram of coal was constant (16-17 mg/g maf coal) suggesting an upper limit to coal reactivity.

A set of experiments were run in this program to study the effect of coal loading on the extent of the water-gas-shift reaction, hydrogen consumption, product yields and distribution. Coal loadings ranging from 1.8-3.7 g maf were studied under the following conditions; 800 psig CO, 6 ml of 0.17 M Na_2CO_3 solution, and 300°C for a period of one hour. The results are presented in Table 14.

By increasing the coal loading from 1.85 g to 3.7 g did not affect the total conversion into THF soluble products but did alter the distribution of products. The PA+A yield ranged from 23 to 33 wt% (maf coal) and oil+gas+water ranged from 4-13 %wt

Table 14. Effect of Coal Concentration on CO Pretreatment

	Pressure	800 psig CO	
	Base	6 ml 0.165 M Na ₂ CO ₃	
	Temperature	300°C	
	Time	1 hour	
Coal, grams	1.85	2.76	3.70
Na loading, wt% maf coal	2.54	1.6	1.27
THF Conv, wt%	37.2	37.2	36.8
Products			
PA+A	29.5	33.1	23.3
Oil+Gas+H ₂ O	7.7	4.1	13.5
WGS Conv (%)	47	48	46
H ₂ Consumed, mg/g maf Coal	22	15	9
Run Number	87	93	88/94

(maf coal, calculated by difference). The hydrogen consumption from the WGS reaction dropped from 22 mg/g maf coal at the lower 1.87 g coal loading to 9 mg/g maf coal at the higher 3.7 g coal loading. The result in Run 88/89 where higher oil+gas+water yields were observed is similar to the earlier data in Runs 52 and 48 where similar high oil+gas+water yields were observed under depleted CO reaction conditions. In Run 88/94 the 'pool' of available hydrogen source (WGS intermediate) had to be shared by a larger amount of coal compared to run 87 and 93. These results seem suggest that the concentration of WGS intermediate available in Run 88/94 is adequate to satisfy the conversion of coal to THF soluble products but not sufficient to prevent some

of the reactive fragments from undergoing further thermal processes and ending up in the oil+gas+water phase. There are still additional analytical data on these products that are not yet available which may provide a clearer picture of this reaction.

Fate of Sodium in CO Pretreatment

From an applications point of view, it is important to know the fate of minerals, inorganics or catalyst/promoters after the reaction. Del Bianco et al.⁶ reported that X-ray diffraction of residues obtained from reactions of CO/H₂O/KOH and Na₂CO₃ at 400°C indicate that all of the potassium from the KOH and part of the sodium from Na₂CO₃ not in the aqueous phase had converted kaolinite to illite and part of the sodium had formed Natrodavine Na₅(AlSiO₄)₃CO₃, a cancrinite mineral group.

In our case, it is important to find out the fate of the Na⁺ (from NaOH and Na₂CO₃ promoted experiments) under our reaction conditions at 300°C. A representative solid product that was recovered from the reactor was washed with distilled water and freeze dried. Atomic absorption and ash analysis of the raw and CO pretreated coal indicated that greater than 90% of the Na⁺ charged to the reactor ended up in the aqueous layer. From the low pH value (5-6) observed in the aqueous layer after the reaction, it was inferred, based upon the literature⁷ that the Na⁺ species is present are a mixture of Na₂CO₃ and NaHCO₃. Our X-ray diffraction analysis data showed no evidence for incorporation of Na⁺ into the mineral matter of the starting coal.

Characterization of CO Pretreated Products

Physical Properties and Surface Area/Pore Volume Analysis - The H₂O-insoluble material recovered from the pretreatment

experiments are physically different. In reactions where low CO pressures were used the recovered products were agglomerated to a greater extent than when the reaction was carried out at high CO pressures. The texture of these low CO pressure agglomerates resembled a charred material. The corresponding material produced at high CO pressures consists mainly of finely divided particles and has a light orange/yellowish color on the surface but also contains some agglomerates.

Pore volume analysis using N₂-BET technique of the material generated at 800 psig CO with 6 ml of 0.33 M NaOH solution at 300°C for an hour indicated that the micropores in the raw coal (ca. 2 m²/g dry coal) had been destroyed. Further analysis using Mercury Porosimetry technique revealed that additional mesopores were generated during the reaction in both the finely divided particles as well as the agglomerates. The total surface area of the mesopores in the finely divided product was 38 m²/g dry coal and for the agglomerates it was 51 m²/g of dry coal. This compares to 17 m²/g dry coal for the raw coal. The significance of this is not immediately clear but it is reasonable to suggest that the higher porosity or opening up of the coal structure that result from the pretreatment should aid catalyst dispersion. It also may help swelling the coal through facilitating solvent interaction and subsequent liquefaction.

Fluorescence Microscopy - A pretreated sample generated from the reaction of 6 ml of 0.33 M NaOH solution, 800 psig CO, at 300°C for an hour was analyzed by Fluorescence Microscopy. It showed significant morphological changes in the coal structure after the pretreatment process. The treated sample showed mostly structureless agglomerates and rounded fragments (vitroplast) derived primarily from vitrinite macerals as compared to the raw coal which showed a distinct banding or layering of plant cell structures, pores etc. The surface of these treated fragments

seemed to indicate that the coal particles have undergone a transition 'melting phase' as opposed to carbonization during the pretreatment process. Staining of these pretreated samples with Safranin-O indicated that some of the oxygen functional groups in the original coal had been removed during the pretreatment process. This is in agreement with the elemental analysis results discussed earlier. FTIR analysis of the pretreated and raw coal and gas data from the liquefaction experiments of these samples indicated that at least half of the oxygen removed from the pretreatment process came from the carboxylic functional groups. These results satisfy one of our primary objectives in the CO pretreatment project since Solomon et al.⁸ have presented evidence to suggest that the route to improved reactivity and product yields may depend on the success of minimizing CO₂ production which has been associated with cross-linking/retrograde reactions.

FTIR Spectroscopy - For this method of characterization, the water insoluble portion of the product, which constitute between 74-85 wt% (maf coal), was analyzed. Similarly, for reactions where humic acid material was produced (up to 7 wt% maf coal), this component of the product was analyzed by recovering it from the aqueous phase after the pretreatment process. Figures 2 and 3 show the spectra of the original coals and various pretreated coal products from the 300°C reaction.

The main region of interest in the spectra are the C-H aliphatic stretching vibrations at 2850-2960 cm⁻¹ and the carboxylic/carboxylate bond stretching modes at 1600-1800 cm⁻¹.

seemed to indicate that the coal particles have undergone a transition 'melting phase' as opposed to carbonization during the pretreatment process. Staining of these pretreated samples with Safranin-O indicated that some of the oxygen functional groups in the original coal had been removed during the pretreatment process. This is in agreement with the elemental analysis results discussed earlier. FTIR analysis of the pretreated and raw coal and gas data from the liquefaction experiments of these samples indicated that at least half of the oxygen removed from the pretreatment process came from the carboxylic functional groups. These results satisfy one of our primary objectives in the CO pretreatment project since Solomon et al.⁸ have presented evidence to suggest that the route to improved reactivity and product yields may depend on the success of minimizing CO₂ production which has been associated with cross-linking/retrograde reactions.

FTIR Spectroscopy - For this method of characterization, the water insoluble portion of the product, which constitute between 74-85 wt% (maf coal), was analyzed. Similarly, for reactions where humic acid material was produced (up to 7 wt% maf coal), this component of the product was analyzed by recovering it from the aqueous phase after the pretreatment process. Figures 2 and 3 show the spectra of the original coals and various pretreated coal products from the 300°C reaction.

The main region of interest in the spectra are the C-H aliphatic stretching vibrations at 2850-2960 cm⁻¹ and the carboxylic/carboxylate bond stretching modes at 1600-1800 cm⁻¹.

Fig. 2(a-c). FTIR spectra of (a) Raw Coal (b) H₂O-insoluble product from coal reaction with CO/H₂O/NaOH and (c) H₂O-insoluble product from coal reaction with N₂/H₂O/NaOH

Fig. 3(a-b). FTIR spectra of (a) Humic Acid from coal reaction with CO/H₂O/NaOH and (b) Humic acid from coal reaction with N₂/H₂O/NaOH

The -OH and -C-O-C- stretching modes are of interest but these regions are often masked by moisture and coal mineral matter respectively so that interpretation of the data may be difficult.

Coal and Pretreated Coal

Aliphatic Region - The spectra of the pretreated coal (400 psig/4 ml H₂O, 2.5 wt% Na maf basis, 300°C, 1 h.) showed an increment in relative intensity^a in the aliphatic region at 2844 cm⁻¹ (-CH₃ stretching), 2915 cm⁻¹ (-CH₂-, -CH- stretching) and 1440 cm⁻¹ (-CH₂-, -CH₃ bending) compared to the original coal (cf. Fig 2a with 2b). This is consistent with the findings of previous studies⁹ which have shown that the long chain aliphatic material present in coals (up to C₄₀ in low rank coals) tend to remain in the residue after a CO/H₂O/base treatment at 320°C.

The spectrum of the H₂O insolubles from the reaction of coal with 200 psig N₂, 2 ml H₂O and 2.5 wt% Na (maf coal basis) at 300°C for 1 hour is shown in Fig. 2c. The intensity of the 2915 and 2844 cm⁻¹ stretching vibrations relative to the aromatic ring stretching vibration in this sample indicated that these long chain materials are also present (cf. Fig. 2a-c). These long chain hydrocarbons are removed when coal is heated with either CO/H₂O or N₂/H₂O in the absence of a base according to Stray.

These results infer that the high H/C ratios obtained for the pretreated coals are not necessarily due to the enrichment of hydrogen-rich aliphatic hydrocarbons inherent in the raw coal.

Carbonyl Region - For both the pretreated and raw coals, the carbonyl absorption appeared as a shoulder at 1703 cm⁻¹ and it can be seen that the intensity of this absorption relative to the

^a As related to the intensity of the 1600 cm⁻¹ aromatic stretching vibration

1600 cm^{-1} aromatic stretching vibration is less in the pretreated coal (either with CO or N_2) compared to the raw coal (Fig. 2(a-c)). This observation is supported by the elemental analysis data which indicated that up to a third of the oxygen was removed during the pretreatment process. Coal liquefaction data also showed that there was less CO_2 being produced during liquefaction of the CO pretreated coal at 400°C compared to the raw coal (1.7 % vs 4.9 wt% maf coal, respectively). Thus, the lower oxygen content of pretreated coal could be attributed to one or a combination of the two following factors: (1) partial thermal decarboxylation of the coal during processing and (2) the formation of oxygen-rich humic acid material when low CO pressures (200 or 400 psig) were used (see below).

Humic Acid Material

Aliphatic region - Figures 3a and 3b. showed the spectra of humic acid material generated from low pressure CO/ H_2O and N_2 / H_2O in the presence of NaOH. The aliphatic stretching peaks at 2915 and 2844 cm^{-1} are very weak and this is consistent with its low H/C ratio.

Carbonyl Region - These spectra showed a sharp, strong carbonyl peak at 1700 cm^{-1} . The intensity of this peak relative to the 1600 cm^{-1} peak in the CO generated humic acid spectrum is more intense than that of the N_2 generated humic acid spectrum. This is consistent with the higher oxygen content of the CO generated humic acid material. It is also interesting to observe the presence of a moderately defined peak in the 1100-1300 cm^{-1} region which indicates possibly the presence of various ether type functions in these material.

Pyridine Extraction of Raw and CO Pretreated Coal

It is not uncommon to use pyridine extraction as a qualitative gauge for the degree of cross-linking that might have occurred during a process treatment. In this test 1.0 g of pretreated coal generated from the reaction of Wyodak coal with 800 psig of CO, 6 ml. H₂O, 1 mole NaOH/kg dry coal (equivalent to 6 ml. of 0.33 M NaOH solution) at 300°C for 1 hour was extracted with 300 ml. of pyridine in a Soxhlet extraction apparatus for 18 hours. The raw coal was similarly extracted and the results compared. For the pretreated coal 60 wt% (maf basis) of the starting material was extracted at the completion of the experiment while only ca. 5 wt% of the raw coal was extracted. These results together with the hydrogen consumption data presented earlier suggested that during the pretreatment process the coal structure had depolymerized into smaller fragments and they had been stabilized by the *in-situ* hydrogen generated by the WGS reaction.

Liquefaction of CO Pretreated Coal

The results presented in the preceding sections indicated that it is possible to upgrade the raw coal to a liquefaction feedstock which has a lower oxygen content, a higher hydrogen content and is not conducive to retrogressive reactions during thermal processing. The implications from these data should result in a feedstock that is highly amenable to hydroliquefaction leading to the production of a better quality product slate at less severe processing conditions. To test this thesis the raw and pretreated coal (H₂O-insoluble fraction derived from the raw coal at 300°C/1 h, 800 psig CO, 6 ml of 0.33 M NaOH solution) were reacted with 1:1 tetralin:coal ratio, 800 psig H₂ at 400°C for 15 and 60 minutes. Tetralin was chosen for this initial study because it afforded a simpler reaction system than the

Wilsonville resid and distillates. However, the latter reactants will be tested at a later date.

The results presented in Table 15 showed that the pretreatment process has a positive effect on the raw coal. For the pretreated coal, conversion to THF soluble products and gases reached 61 wt% (maf basis) at 15 min compared to 45% for the raw coal for the same reaction time. This represented a 36% improvement over the raw coal. At 60 min, the THF conversions were 83% and 75%, respectively; an improvement of 10% over the raw coal.

Table 15. Liquefaction of CO Pretreated Coal

	Temperature	400°C		
	Pressure	800 psig H ₂		
	Charge	2 g coal		
		2 g tetralin		
Coal	Raw	Pretreated	Raw	Pretreated
Time, min	15	15	60	60
THF Conv, wt%	44.8	60.8	74.8	83.2
Products, wt% maf coal				
PA+A	36.7	47.0	42.8	41.8
Oils	2.5	11.6	26.3 ^a	38.9 ^a
CO+CO ₂	5.3	2.0	5.4	1.9
HC Gases	0.3	0.2	-	-
H ₂ Consumed, mg/g maf coal	11.4	18.7	17.0	18.0
Run Number	79	81/82	85	86

a. Pretreatment: 800 psig CO, 6 ml of 0.33 M NaOH, 300°C, 1 hr.

b. Represents oils+gas+water; HC gases analysis in progress.

The improvement in THF conversion for the 15 min. reaction was manifested equally in the PA+A and oil fraction. For such a short reaction time the water yield is not anticipated to be more than a couple of percent thereby not affecting the oil yield

significantly. The improvement in conversion for the 60 min run is reflected in the increase in the sum of the oil plus hydrocarbon gases but at present there is insufficient data to estimate how much is in the oil yield or to absolutely know how much water is made.

However, it is interesting to note that the amount of hydrogen consumed by the pretreated coal from the gas phase for the 15 min. reaction was similar to that of the 60 min. reaction (18.7 vs. 18.0 mg/g maf coal, respectively) despite the big difference in THF conversion (61% vs. 83% respectively). Assuming that the total hydrogen consumption is similar in both cases^b it is improbable that the 60 min. reaction would produce more than a few percent hydrocarbon gases and water so that the oil yield for the 60 min run is probably significantly higher than that of the 15 min reaction. A similar argument may be applied when comparing the reactions of raw coal with pretreated coal for the 60 min. reaction (see Table 15). Accordingly it is tempting to suggest that hydrogen utilization has been significantly improved by the pretreatment process but further work is needed to unequivocally confirm this thesis.

The CO+CO₂ gas yield seems to reach a plateau early in the reaction for both the raw and pretreated coal (see Table 15). It is noteworthy that the total carbon oxide gas yields produced in the reactions of raw coal were approximately 2.5 times that of the pretreated coal reactions, i.e., 5.3% vs. 2% at 15 min and 5.4% vs. 1.9% at 60 min, respectively. In recent studies Solomon, et al. 1990, tied the production of carbon oxide gases, particularly CO₂, to possible retrogressive reactions which led

^b Although the hydrogen consumption from tetralin has yet to be determined, it is not unreasonable to suggest that the values would be similar in both cases since no catalyst is present in the reaction.

to low liquid yields and a low product quality slate. Currently the liquefaction products from these experiments are being analyzed to ascertain the product quality.

Conclusions

The pretreatment of coal with CO/H₂O in the presence of NaOH and Na₂CO₃ has been shown to give a product which is lower in oxygen content and higher in hydrogen content compared to the raw coal.

The atomic H/C ratios of the H₂O-insolubles, THF insolubles and the PA+A fractions of the products together with the hydrogen consumption data suggested that the raw coal has been substantially depolymerized and hydrogenated via the WGS reaction during the pretreatment process. The extensive amount of molecular reconstruction that has occurred in the solid product was evident from the ease of solubilization of the product into pyridine.

The result of the pretreatment process is a product which is highly reactive under hydroliquefaction conditions at 400°C. Reaction rates seem to be much faster than the raw coal, especially at shorter reaction times, providing the opportunity for major reductions in plant vessel sizes, and preliminary data has led us to believe that better efficiency in hydrogen utilization is achieved.

Task 2.1.2 - Pretreatment Work (CONSOL)

NEPA approval was received from DOE. Preliminary experiments to dewax the V-1074 oil from Wilsonville Run 262, 9/16/91, were begun. GC/MS analysis of this material showed it to have a high concentration of n-paraffins. This suggests it should be a good dewaxing feedstock.

It was found that the starting V-1074 heavy distillate contains 0.10 wt % tetrahydrofuran (THF) insolubles (0.05 wt % insoluble organic matter (IOM), 0.05 wt % ash). For the initial set of dewaxing tests, this small quantity of insolubles is being ignored in the material balances.

Four ketone dewaxing runs were made at 0, -10, -20, and -35°C. For each run, 100 mL of sample was mixed with 300 mL of HPLC grade acetone in a beaker. The mixture was gradually cooled, with stirring, to the test temperature using a bath of dry ice and acetone. At the desired temperature, the precipitated wax was suction-filtered and washed with cold acetone. The filter cake then was dissolved and washed through the filter into a separate container with THF, which was at room temperature or higher (warmed on a hot plate). The wax and dewaxed oil fractions were recovered by rotary evaporation, followed by drying overnight in an oven at about 100°C or in a vacuum oven at 90°C. Yields of each fraction and the total recovered material were calculated from the weights of feed oil and recovered fractions (Table 16). Each sample was analyzed by ¹H-NMR for proton distribution (Table 17), and the feed and dewaxed oils were tested for liquefaction donor solvent quality by a standard assay in use in CONSOL's laboratory (Table 16). Test conditions were: 9 g oil, 6 g Old Ben Coal (Indiana V seam), 30 minutes, 750°F.

The results in Tables 16 and 17 show a progression in yield and oil and wax properties as the dewaxing temperature was decreased. With decreasing temperature, wax yield was higher, wax purity was lower, and donor solvent quality of the dewaxed oil increased (levelling off at about 83% at -10°C and lower). Decreasing wax purity with decreasing dewaxing temperature was expected from prior dewaxing experience in this laboratory.¹⁰ This trend was evident in the filter cake color (darker), and the increasing

proportions of aromatic and alpha protons and decreasing proportion of alkyl beta protons in the proton distribution of the wax. Material balances were 99.8 to 100.0 wt % for the runs completed to date. GC-MS analysis, performed on the set of feed and product samples from the -20°C run, showed the wax to be highly aliphatic, but not purely paraffinic. It also showed that virtually all of the n-paraffins were removed from the oil at -20°C.

The results show that significant improvement in donor solvent quality (microautoclave coal conversions increased from 62 to 83%) was achieved by dewaxing the heavy distillate solvent. A dewaxing run at -5°C is planned, to determine more precisely the dewaxing temperature at which the donor solvent quality of the dewaxed oil levels off. We also plan to measure the performance of the solvent in converting Black Thunder Coal. The dewaxing work is progressing toward the production of a large batch of dewaxed oil for Sandia to use as a hydrogenation feedstock.

**TABLE 16 RESULTS OF KETONE DEWAXING OF WILSONVILLE 9/16/91
V-1074 HEAVY DISTILLATE**

Run	Temperature, °C	Yield of Dewaxed Oil, %	Yield of Wax, %	Material Balance, %	Donor Solvent Quality Assay, %
Baseline	NA	NA	NA	NA	62.4
4	0	90.47	9.30	99.78	71.2
3	-10	79.14	20.83	99.98	82.9
1	-20	70.94	29.04	99.97	84.1
5	-35	44.33	55.69	100.02	82.5

**TABLE 17 PROTON DISTRIBUTIONS OF FEED AND PRODUCT SAMPLES FROM
DEWAXING RUNS**

Run	°C	Sample	Proton Distribution, %						
			Cond Arom	Uncond Arom.	Cyclic Alpha	Alkyl Alpha	Cyc Beta	Alkyl Beta	Gamma
Base line	NA	Feed	11.3	3.6	14.7	7.6	15.8	34.6	12.3
4	0	Dewaxe d Oil	12.4	4.9	15.8	8.7	17.1	27.3	13.7
3	-10	Dewaxe d Oil	15.3	4.8	18.4	9.5	18.0	21.7	12.3
1	-20	Dewaxe d Oil	18.1	4.9	20.3	9.8	18.0	18.8	10.1
5	-35	Dewaxe d Oil	20.3	6.0	21.6	8.1	17.3	17.0	9.6
4	0	Wax	0.3	0.3	3.0	2.6	7.1	75.0	11.7
3	-10	Wax	1.3	0.6	4.5	3.2	13.0	61.4	16.0
1	-20	Wax	1.9	1.4	5.5	4.6	14.7	56.9	15.1
5	-35	Wax	4.0	1.4	8.1	5.3	15.8	50.1	15.3

Task 2.1.3/2.3.3 Solvent Pretreatment and Catalyst Studies

Solvent pretreatment tests using the combined water-gas shift solvent hydrogenation reaction were performed with two different types of supported catalysts. These catalysts were tested in a fixed bed microflow reactor by concurrently flowing carbon

monoxide, hydrogen, steam and a synthetic donor solvent (9.5 wt% aromatics in hexadecane) at 275°C.

- The first series of tests used a potassium doped cobalt molybdenum (CoMo) catalyst which was supported on alumina. This catalyst has 5.8% Mo and 1.7% Co with a surface area of 300 m²/g. Potassium addition to the catalyst promoted the water-gas shift reaction but inhibited the solvent hydrogenation reaction.

- A second series of tests were performed to evaluate nickel molybdenum (NiMo) catalysts. A hydrous titanium oxide (HTO) thin film catalyst was prepared with multiple coats of nickel and molybdenum on a porous silica support. This catalyst was compared with a commercially available NiMo catalyst, supported on alumina. These catalysts were tested in a larger catalyst bed so that they could be evaluated in their engineered forms (bead and extrudate). Both catalysts were quite active for the combined reaction at 275°C. Hydrogenation rates for fluoranthene were markedly higher than for pyrene and phenanthrene.

- Heavy distillate from Wilsonville was separated into aliphatic and aromatic fractions using column chromatography. Elemental analysis and capillary chromatography of the V1074 fractions illustrate the waxy nature of this solvent.

Background

In this program Sandia is studying the solvent hydrogenation pretreatment using the water-gas shift reaction. The aim of the work is to reduce reaction temperature and pressure for donor solvent hydrogenation and to remove the requirement for purified hydrogen. The use of water and CO mixtures involves two classes of coupled catalytic reactions:

Water-gas shift:

Hydrogenation of donor species, for example:

Hydrogenation of the donor solvent species is illustrated here by the hydrogenation of pyrene, a donor solvent precursor.

Equilibrium concentrations of hydrogen and $H_2\text{Py}$ are greatly increased at lower temperatures due to the greater K_p for the above reactions. The ability to lower the coupled reaction temperature allows the total system pressure to be reduced and still achieve adequate solvent hydrogenation. Currently, catalyst testing at Sandia involves hydrogenation of a synthetic solvent containing 9.5 wt% aromatic compounds (phenanthrene, fluoranthene, pyrene) in hexadecane at temperatures near 300°C.

Experimental

The microflow reactor used for these tests consists of a fixed bed tubular reactor supported inside of a thermostatically controlled oven. The catalyst bed was presulfided for two hours at 390°C with a 9% H_2S in hydrogen mixture before each reaction series. Synthesis gas and steam were fed in equimolar amounts ($CO:H_2:H_2O = 1:1:1$) to hydrogenate the solvent using the in situ water-gas shift reaction. All reactants were fed downward over the catalyst bed concurrently and total reaction pressure was maintained at 1000 psig.

Results from Tests with CoMo Catalyst

A commercially available cobalt molybdenum catalyst supported on

alumina was used to test water-gas shift promotion using potassium. This catalyst has a surface area of 300m²/g with 5.8% Mo and 1.7% Co. The catalyst was ground to a -30/+40 mesh particle size, packed in the reactor and sulfided before starting reactant flow. Weight Hourly Space Velocity (WHSV) was 0.5 hr⁻¹ (WHSV = wt aromatic feed/ wt catalyst per hour). Comparative results for the potassium loaded and potassium free catalysts are given in Table 18.

Table 18

Catalyst	Temp °C	%CO conv	PHEN %hyd	FLUOR %hyd	PYRENE %hyd
CoMo	275	60	21	38	34
CoMo/pota	275	94	0	6	4
CoMo	300	76	12	33	26
CoMo/pota	300	94	0	14	9

The addition of potassium increased the carbon monoxide conversion but greatly reduced the aromatic hydrogenation rate. The water-gas shift results are in general agreement with studies which report alkali metal promotion of sulfided CoMo catalysts.^{11,12} The high potassium concentration (8 wt%) on the potassium loaded catalyst inhibited the hydrogenation reaction and low potassium concentrations (0.1%, tested previously) proved ineffective in enhancing the shift reaction. The optimum potassium/molybdenum ratio for water-gas shift promotion should be approximately 0.4 which corresponds to approximately 1 wt% potassium for this catalyst. However, potassium inhibition of the hydrogenation reaction made further study of this catalyst unprofitable.

Results from Tests with NiMo Catalysts

Two series of flow reactor experiments were conducted with catalysts used in their engineered form (extrudate and bead). These tests were performed to evaluate two of the more active catalyst formulations in the larger reactors (0.5" O.D.), which will be used for coal-derived solvent hydrogenation experiments. The reaction series is outlined below:

Series	Catalyst Description	%Mo	%Ni	Catalyst wt
A	Thin film HTO on silica	5.6	1.8	2.00g
B	NiMo on alumina	12.4	2.8	1.99g

The first catalyst was a hydrous titanium oxide (HTO) thin film catalyst which had been coated multiple times with nickel and molybdenum. The support for this catalyst was a porous silica bead. The second catalyst was Shell 324, a commercially available, alumina supported catalyst. Water-gas shift and solvent hydrogenation results are given in Table 19.

For each test the large (12 cm³) reactor was packed with catalyst and a catalyst diluent (α -alumina) and then sulfided. Catalyst activity results are shown in Table 19 along with data showing the effect of gas treat rates on CO conversion and solvent hydrogenation. The gas treat rates are listed as Gas Hourly Space Velocity (GHSV= cubic centimeters gas/cubic centimeters reactor per hour at 1 atm).

Table 19

Catalyst	Temp °C	WHSV hr ⁻¹	GHSV hr ⁻¹ CO/H ₂	%CO Conv	PHEN % hyd	FLUOR %hyd	PYRENE %hyd
Shell 324	275	.44	300/300	78	47	95	67
Shell 324	275	.44	200/200	86	48	96	68
Shell 324	275	.44	100/100	93	48	96	68
Thin film	275	.44	300/300	78	42	89	53
Thin film	275	.44	200/200	88	45	88	57
Thin film	275	.44	100/100	95	43	85	55
Shell 324	275	.89	100/100	95	27	84	54
Thin film	275	.89	100/100	95	25	65	36
Thin film	300	.89	100/100	95	45	82	49

The effect of gas treat rate on the solvent hydrogenation reaction was negligible; however the gas velocity did affect the water-gas shift reaction. The carbon monoxide conversion decreased with increasing gas treat rate, showing a kinetic effect for this reaction under these conditions.

In addition, on a weight of catalyst basis the Shell 324 catalyst proved to be somewhat more active for solvent hydrogenation. On a catalyst metal basis, however, the thin film catalyst showed greater activity.

Feed Rate Effects

After some catalyst deactivation, the thin film HTO catalyst (series A) was used to test the effects of feed rate on solvent hydrogenation rate. The WHSV of the synthetic solvent was varied between 0.44 and 1.11 hr⁻¹. Feed rate effects are shown in Table 20.

Table 20

WHSV hr ⁻¹	Temp °C	%CO conv	PHEN %hyd	FLUOR %hyd	PYRENE %hyd
.44	275	94	31	80	46
.67	275	94	29	76	44
1.11	275	96	14	57	23

The water-gas shift reaction was unaffected by the increase in aromatic feed rate to the reactor. Preliminary analysis of the liquid products, however, indicates that fluoranthene hydrogenation rates are much faster than those for either phenanthrene or pyrene. A plot of concentration vs time (Figure 4) shows the dramatic difference between these rates. Indeed, the high initial rate for fluoranthene hydrogenation seems to repress the other two hydrogenation reactions, possibly by competing for the available hydrogen.

Conclusions

Tests with CoMo catalysts promoted with potassium have shown enhanced water-gas shift activity but decreased hydrogenation activity.

Combined water-gas shift solvent hydrogenation experiments have shown that sulfided NiMo catalysts are very effective at 275°C.

Figure 4 Concentration vs Time

Shell 324 was slightly more active than the thin-film HTO catalyst on a catalyst weight basis, however the thin film HTO was more active on a catalyst metal basis. Future experiments will include coal-derived solvent hydrogenation using V1074 and dewaxed V1074 provided by CONSOL.

Task 2.3.1 Iron Based Dispersed Catalysts

The objective of this task is to develop iron based catalysts which will significantly improve first stage liquefaction performance through either incorporating the catalyst into the feed slurry to the first stage unit or combining with the coal during a pretreatment step. The experimental approach formulated in the program plan includes evaluating performance of candidate catalysts by using reconstituted recycle solvent from Wilsonville in order to simulate a process configuration involving recycle of ash, unconverted coal and residual fractions. Fractions of the relevant streams from Wilsonville have been supplied to UK by Consol and work with these materials began in earnest during this past reporting period. Since these materials were not available in the earlier phases of this program because of not having received NEPA clearance from DOE, most of the earlier work reported in previous quarterly reports involved liquefying Wyodak coal with tetralin as solvent. The work has now switched to using the Wilsonville derived materials along with Black Thunder coal, on which the Wilsonville plant was operating when those materials were generated.

Reactivity of Black Thunder Coal

Upon receipt of the Black Thunder coal from CONSOL several liquefaction runs were made with the coal in tetralin to check its relative performance versus the earlier runs with Wyodak coal. These runs were made at three different time intervals in tetralin at 415°C at solvent to coal ratios of 2.3/1 and 1000 psig cold

hydrogen pressure. This ratio of solvent to coal was increased over the previous runs in anticipation of switching to the higher ratio used at Wilsonville in Run 262. The workups were done in THF/pentane using a Soxhlet extraction technique coupled with sonication. Results from those runs are shown in Table 21.

Table 21. Liquefaction of Black Thunder Coal in Tetralin

Run Temperature	415°C		
H ₂ Pressure	1000 psig		
Moisture in coal	21.9 wt %		
Tetralin / Dried Coal (wt/wt)	2.3		
	15 min	30 min	60 min
Yields, wt% MAF coal			
Gases	4.6	5.1	5.9
Oils	20.7	28.0	43.4
PA + A	40.9	43.6	35.8
IOM	33.7	23.3	14.9
THF Conversion	66.3	76.7	85.1
H ₂ Consump, mg/g maf coal	30.0	28.0	36.1
Run Number	R2-154-2	R2-154-1	R2-160-2

In these runs the THF conversion increased steadily from 66.3% at 15 minute residence time up to 85.1% at one hour. In addition, oils and gases both increased; the oils from 20.7 at 15 minutes up to 43.4 wt% at 60 minutes. The maxima observed in the PA + A lump is as expected for a sequential conversion to preasphaltenes and then asphaltenes. Although numbers reported for the hydrogen gas consumption are tentative, 30 mg/gram maf coal appears reasonable based upon hydrogen gas consumption for the first stage liquefaction of Wyodak coal at Wilsonville, which was on the order of 40 mg per gram maf coal.¹³ Consumptions for bituminous coals in a thermal process would be on the order of 1-3 wt % of maf coal, which corresponds to consumptions from about 15 to 30 mg/gram maf coal. Since these values are quite recent and are certainly directionally

correct they are being re-evaluated and corrected values will be reported as they become available.

In the previous quarterly report results from liquefaction runs on Wyodak coal in tetralin for 15 minute reaction periods over a broad temperature range were reported. Although the temperatures and other conditions were not exactly the same as those used for the Black Thunder data reported in Table 21, they provide an interesting comparison as shown in Table 22.

Table 22. Liquefaction of Wyodak and Black Thunder Coals

Solvent	Black Thunder	Wyodak
	Tetralin	Tetralin
Temperature, °C	415	391
Time, min	15	15
Hydrogen, psig cold	1000	800
Tetralin/Dried Coal wt/wt	2.3	1.66
Yields, wt% MAF coal		
Gases	4.6	2.8
Oils	20.7	24.0
PA + A	40.9	25.7
IOM	33.7	47.5
THF Conversion	66.3	---
Pyridine Conv	---	52.5
Run Number	R2-154-2	---

Even though the Wyodak coal sample used in the above comparison may have been less than optimum, because of the possibility of being quite severely oxidized, the direction of the data suggests that the Black Thunder is as reactive if not slightly more reactive than the Wyodak coal. The level of conversion, one being based upon THF solubility and the other being in pyridine, suggests the Black

Thunder was somewhat more reactive. Directionally the gas make agrees with this conclusion. Additional comparisons have been run but the data are not as yet available.

These results observed in these runs in tetralin provide confidence that Black Thunder can be expected to behave in a predictable manner in runs made in the Wilsonville ashy resid containing solvents. This is significant in light of the initial difficulty and the subsequent interpretational complexity experienced in the runs made in solvents containing ashy resid which will be addressed below.

Liquefaction with Wilsonville Composite Solvent

The approach being used in this program to improve upon first stage processing performance is to conduct coal liquefaction studies in solvents having compositions comparable to those in the feed to the first stage in the Wilsonville operation. These solvents are comprised of heavy distillate from the vacuum flash tower, deashed resid from the Rose critical solvent deashing unit and ash containing residual material that is the feed to the Rose unit. This composite stream then is comprised of significant amounts of material that can be converted during subsequent processing. At Wilsonville, in a continuous, steady-state process operation, the conversion of these residual and insoluble ash components was not a factor since conversion and product yields were calculated based upon fresh coal. In a once through laboratory experimental program, conversion of the solvent stream is a complicating factor.

In most types of once-through liquefaction studies the use of distillate solvent eliminates any problem with defining the conversion to distillate material since retrogressive reaction of the distillate to residual fractions is essentially insignificant.¹⁴ Use of residual fractions, however, creates added complexity to the interpretation of the data. In continuous, once-through process

studies Kang and Givens¹⁵ showed that substitution of 25% deashed resid from the second stage settler of the Kerr McGee CSD unit into the distillate solvent led to an ~8% increase in coal conversion accompanied by an ~3% increase in oil yield at 450°C. In the absence of coal approximately 15% of the deashed resid was observed to convert under the same condition at 450°C. In these cases interpretation of the coal conversion characteristics was complicated by the competing conversion of the solvent. Although these runs were all non-catalyzed thermal runs, it is likely that conducting this same type of reaction in a catalyzed system would result in higher levels of conversion which would further complicate interpretation of the data since conversion of the "inert" solvent would compete in magnitude with the coal conversion itself.

Other data have shown that the partitioning of the residual feed in the Kerr McGee ROSE solvent deashing unit at Wilsonville resulted in an ash concentrate that contained easily converted IOM and preasphaltenes.¹⁶ An ash concentrate that contained 71% pyridine insolubles along with 25% of a pyridine soluble/benzene insoluble fraction (preasphaltenes) was observed to undergo considerable conversion under thermal reaction conditions. At 450°C, 17% of the IOM and 51% of the preasphaltenes were converted. When the ash concentrate was added to a coal slurry a significant increase in coal conversion and oil make resulted which was a combined effect of the conversion of the coal and ash concentrate. By comparison, reactions conducted with slurries containing filter cake from Wilsonville showed no statistically significant change in coal conversion versus runs made without solids addition. In these cases the IOM is essentially inert in this reaction environment.

The highly reactive nature of the ash concentrate from the ROSE critical solvent deashing unit was considered to be a characteristic of process and its effect on the composition of the materials separated in that process. It was thought that during solids

partitioning from of the bulk liquid in the ROSE unit that some of the residual hydrocarbon phase was carried with the solids. During this processing some of these materials underwent mild retrograde reactions forming material that was no longer soluble in pyridine or cresol. However, exposing these materials to liquefaction conditions resulted in a reaction of those retrograde products converting them into solubilized material. Since this type of behavior was not seen in filter cake materials, these retrograde materials were assumed to be primarily the result of reactions occurring in the ROSE unit.

These earlier results suggested that the use of Wilsonville process stream samples containing residual material would create added complexity to conducting experimental runs and interpreting the effect of catalyst on coal conversion. Unquestionably, the components of the solvent fraction will react at varying rates being converted to both distillate and other residual products. Even further conversion of distillate to still lighter molecular weight distillate product is expected as well as the occurrence of competing retrograde reactions. Interpreting data from reactions run in this type of starting solvent with the objective of determining coal conversion and product distribution from the coal feed requires knowing the composition of the solvent.

Liquefaction Solvent Composition - The decision on the composition of the ashy resid containing solvent to be used in the liquefaction runs was based upon compositional data for Run 262 at Wilsonville on 9/16/91 and supplied by Consol, as shown in Table 23.

The workup procedure that will be used in our lab to separate the products will involve a solvent separation scheme. The composition of the solvent, which is made up of the ashy resid, deashed resid and the heavy distillate, was determined using the solvent separation method. The data are shown in Table 24.

Table 23

ANALYSES OF PRIMARY OIL SAMPLES
WILSONVILLE RUN 262, 9/16/91

stream	V-1074 heavy distillate	V-130 deashed resid	V-1082 ashy resid	V-131B recycle solvent	calcu- lated V-131B
fraction of recycle solvent blend, wt%	42.7	6.6	50.7	100.0	100.0
Composition, wt%					
solvent (~1050°F dist.)	N.D. (assume 100.0)	16.0	2.5	43.8	45.0
soluble resid (diff.)	N.D. (assume 0.0)	83.9	58.8	36.6	35.3
cresol insoluble organics	N.D. (assume 0.0)	0.01	18.3	19.6	9.3
ash	N.D. (assume 0.0)	0.11	20.4		10.4
analysis, wt%					
C	89.6	90.5	72.4	80.8	80.9
H	10.0	7.4	5.5	7.5	7.5
N	0.45	1.1	1.0	0.8	0.8
O (diff)	-0.1	0.8	-1.5	N.D.	-0.7
S	0.04	0.1	2.2	N.D.	1.1
ash	N.D. (assume 0.0)	0.11	20.4	N.D.	10.4

Note: Data supplied by C. Cantrell, letter to G.A. Robbins, Feb.21, 1992. N.D.= not determined. Assumed and calculated values supplied by CONSOL.

Table 24. Liquefaction Solvent Composition

	Distillate	Deashed Resid	Ashy Resid	Combined Calculated
Ash	0.26	0.43	20.03	10.29
Oils	95.91	63.51	29.78	60.22
PA + A	0.74	32.63	31.89	18.66
IOM	3.09	3.43	18.31	10.83
Total	42.7	6.6	50.7	100

It is assumed that the calculated and actually separated solvent fractions are additive when mixed. We are currently doing the separation to verify that the combined solvent gives the expected result.

Material Balance and Product Yield Computational Methods - The calculation of the yield of products from the small autoclave runs being done in this program differ somewhat from those reported elsewhere in that the solvent is comprised of several different fractions. Therefore the calculations are somewhat more complicated as illustrated by the series of four runs shown in Table 25. In these runs the reactor is typically charged with about 5.4 grams of the Wilsonville combined solvent along with 3 grams of wet coal. The weights of the individual solvent fractions are combined with the coal plus the catalyst, if any, to make up the combined feed to the reactor as shown in the table. From the compositions of the individual components the weights of each of the individual fractions, broken down as oils, preasphaltene plus asphaltenes (PA+A), insoluble organic matter (IOM), and ash, are combined to give a gross weight for each fraction, which agrees with the weight of the fractions as added to the reactor. After reaction, the product is removed from the reactor and separated in the following manner. The gaseous product is isolated, measured and analyzed by

gas chromatography to give a total weight, composition, and weight of consumed hydrogen. The remainder of the sample is subjected to solvent separation which provides direct weights of the combined PA+A fraction and the total weight of THF insolubles. The THF insolubles are comprised of IOM and inorganic matter plus the final form of the catalyst. By assuming complete recovery of the ash plus catalyst the weight of insoluble organic matter (IOM) can be calculated. By this method the overall conversion of coal and distribution of the solubility fractions are calculated. Errors due to formation of water during liquefaction are included in the oils fraction which makes for a small error in this number.

Ash Balance - Since this procedure assumes complete recovery of ash and catalyst, data for several experiments are shown in Table 25 to illustrate the validity of this approach. Data from a thermal run, R2-140-2 shown in the first data column, to which no catalyst was added, illustrate that the ash content in the recovered THF insoluble fraction conforms with the amount in the feed which complies with complete recovery of the ash. Data from three runs in which catalyst was added to the reaction mixture are shown in the remaining columns of the table. In each of these runs catalysts were added to the reaction mixture in the form of their precursors. In two, an iron oxide used at Wilsonville was added and presumed to convert to pyrrhotite. The weight of catalyst reporting to the ash fraction was then calculated based upon the weight of FeS that was formed. In the third case Shell 324 catalyst was added and the weight of the final catalyst was based upon the transformation of the nickel and molybdenum being present as their corresponding sulfides. From these data the weight of ash plus catalyst that theoretically should report to the THF insolubles was calculated. These values are essentially the same as the experimentally determined values.

Table 25 Forced Ash Balance
415°C, 60 min, 1000 psi H₂ cold

Catalyst	none	Fe ₂ O ₃	Fe ₂ O ₃	Shell 324
Reactant, grams				
Coal	3.001	2.998	3.000	3.002
Ashy Resid	2.954	2.757	2.759	2.957
Deashed Resid	0.385	0.360	0.359	0.393
Distillate	2.489	2.323	2.323	2.489
Catalyst	0	0.054	0.054	0.266
Total	8.829	8.491	8.496	9.106
React Solvent, g				
Ash in Solvent	0.600	0.560	0.560	0.600
Wt Oils	3.512	3.277	3.278	3.517
PA + A (af)	1.086	1.014	1.014	1.089
IOM (af)	0.631	0.589	0.589	0.632
Moisture in Coal	0.656	0.634	0.657	0.673
Coal, Maf	2.192	2.209	2.190	2.175
Coal Ash	0.153	0.154	0.153	0.155
Catalyst	0.000	0.054	0.054	0.266
Total	8.829	8.491	8.496	9.106
Product, grams				
Coal Gas	0.136	0.148	0.146	0.123
PA + A	2.872	1.936	2.086	1.482
THF Insol	1.221	1.211	1.222	1.470
Forced Ash Balance				
IOM, Calc ^a	0.468	0.443	0.455	0.450
Ash, Calc from feed	0.753	0.714	0.713	0.755
Ash in THF Insol				
Calculated ^a	61.7	63.4	62.8	69.4
Experimental	62.0	63.0	61.0	69.0
Run Number	140-2	189-1	142-2	114-1

a. Calculated based on forced ash balance.

Product Yields - Product yields reported here reflect the conversion of coal into its component solubility classifications based upon a forced mass balance. In determining product yields the first step is to calculate the total amount of each component that is present in the product versus the amount that was charged to the reactor. In Table 26 these values are tabulated for run R2-167-1 which was a thermal liquefaction run in which the Wilsonville solvent was used and to which no catalyst was added. The total feed to the reactor is tabulated in its component parts as shown in the table. Total feed coal is broken down into maf coal, ash and moisture while the feed solvent is separated into oils, PA+A, IOM and ash. In the product, PA+A is a directly measured value while both the ash and moisture contents in the product are assumed to be equal to their respective quantities in the feed. IOM is calculated by subtracting the amount of ash present in the feed from the total THF insolubles determined in the product. The oil value is calculated based upon 100% mass recovery of the reactants.

Table 26 Product Yield Calculation

Run Number R2-167-1
 Temperature 415°C
 Run Time 60 min.
 Catalyst None

	Feed	Product	Net Yield	% Yield
Gases		0.154	0.154	7.1
Wt Oils	3.276	4.303	1.026	44.2
Wt PA + A (af)	1.014	2.136	1.122	51.6
Wt IOM (af)	0.589	0.462	-0.127	-5.8
Moisture in Coal	0.669	0.669	0	
Coal, Maf	2.175		-2.175	
Total Ash	0.712	0.712	0	
Catalyst	0.000		0	
Total	8.436	8.436	0	
Coal Conversion				105.8

Net product yields are then calculated by subtracting the amount of material contained in the feed from the corresponding amount found in the product. The total of the net products equals the amount of maf coal in the feed. These values reflect the net make (or loss) of each of the solubility fractions versus the amount contained in the charge to the reactor while coal conversion equals 100 minus the yield of IOM.

Although this procedure is very straightforward and identical to that commonly used to express product distribution and coal conversion, we felt it was necessary to point this out in light of the very unusual product distributions that have been observed in this study. In short, as discussed below, we regularly observe coal conversions in excess of 100% in the runs in which Wilsonville solvent has been used.

Reactivity of Wilsonville Solvent

During this reporting period it became apparent that the solvent was significantly altering the reaction product composition routinely giving coal conversions in excess of 100% and oil yields which were exceptionally large. In order to understand the magnitude of this change a detailed examination of the behavior of the liquefaction solvent was undertaken. A series of runs were made on the solvent itself without any added catalyst at 415°C at residence times of 30 and 60 minutes under conditions as shown in Table 27.

The most noticeable change in the solvent after reaction was the decrease in IOM content dropping from 12.1 wt% in the starting mix to between 8.1-8.8 wt%, on a maf basis, in the product. This yield corresponds to an IOM conversion of between 27 and 33 wt%. On a total mass basis the PA+A values change very little from the starting solvent with the difference showing up primarily in the oil yield which increased from 3 to 5% over the starting material.

Table 27. Thermal Conversion of Composite Wilsonville Solvent

	Temperature	415°C		
	Solvent	5.4 grams		
	Reactor Volume	50 ml		
	H ₂ Pressure	1000 psig		
	Solvent	Solvent	30 min	60 min
	wt%(mf)	wt%(maf)	wt%(maf)	wt%(maf)
Composition, wt%				
Gases			0.2	0.4
Oils	60.2	67.1	72.8	69.7
PA + A	18.6	20.8	18.2	21.8
IOM	10.8	12.1	8.8	8.1
Ash in Total Solvent	10.3			
Fe, wt% maf	1.71			
Mo, wt% maf	0.03			
IOM Conv wt%			27	33
Run Number			155-2	140-1

The data suggests that at extremely short residence times an immediate drop in IOM occurs which is accompanied by a corresponding immediate re-distribution within the product framework. By extrapolating this data to zero time provides an estimate of the level of conversion that occurs immediately upon subjecting the solvent mix to high temperature. We are currently in the process of getting additional data to do this extrapolation.

Recognizing the sizable amount of iron and molybdenum that is present in the starting solvent immediately suggests that these metals may have an effect on the initial reaction as well as may catalyze the overall conversion that occurs over the longer times. However an immediate change in the IOM was also observed in solvents containing ash concentrate taken from the ROSE critical solvent

deashing unit when the Wilsonville plant was running in a non-catalytic thermal mode.¹⁷ In the thermal mode no iron or molybdenum catalysts were added to the reaction system and therefore were not present in the ash concentrate other than iron that was originally present in the coal ash feed. Although the ash concentrate is apparently an entirely different material from that used in the study here, this data suggests that the quite significant amount of iron and molybdenum in the ashy resid containing solvent may exert little significant catalytic influence on the reaction.

Similar runs were also made using both iron and molybdenum containing catalysts described in Table 28. In the iron containing catalysts the amount of metal added to the system was small compared to the amount of iron already in the system, namely 1.7% based on feed. In those runs in which iron was added to the system, it was only an additional 0.5% in each case, which comprised only about 1/4 of the iron present in the system, excluding the amount of iron contained in the mineral matter in the coal. In the case of the molybdenum catalysts the amount of molybdenum already present in the system was quite small relative to the amount that was added either as molybdenum naphthenate or as the NiMo catalysts. In all these metal addition runs sulfur as dimethyl disulfide was added to the system to provide for the transformation of the precursor to the active form of the catalyst, namely, pyrrhotite for the iron oxide and molybdenum and nickel disulfides for the Mo and Ni, respectively. In each case the level of sulfur addition was equivalent to a 2.4 molar ratio of sulfur to metal.

The results of these catalyzed runs, which were all made at 60 minutes under conditions identical to those described for the thermal runs above, are shown in Table 29.

Table 28. Catalyst Precursors

Type	Source	Handling	BET Surface m ² /g	Metal Content wt%
Nickel Moly on Alumina	Shell 324	Ground to <100 mesh; calcined @500°C	N/A	12.4 % Mo, 2.8% Ni
Molybdenum Naphthenate	K&K Labs	None	N/A	6.07 % Mo
Fe ₂ O ₃	Wilsonville	None	8.6	69.9 % Fe (calc)
Fe ₂ O ₃ - Nanometer size	Mach I, Inc.	Stored under dry N ₂	318	69.9 % Fe (calc)

Table 29. Effect of Catalyst on Wilsonville Solvent Conversion^a

	Solvent	Iron Oxide	Iron Oxide	Mo Naphthenate	NiMo
		WV Sample	nanometer	6 wt% Mo	Shell 324
wt % maf					
Gases	-	0.5	0.7	0.6	0.5
Oils	67.1	75.7	75.7	78.8	79.9
PA + A	20.8	16.4	17.5	13.7	11.6
IOM	12.1	7.4	6.0	7.0	8.1
Fe, wt% maf ^b	1.71	2.2	2.2	1.7	1.7
Mo, wt% maf	0.03	0.03	0.03	1.1	0.60
IOM Conv wt%	-	39	50	42	37
PA+A Conv wt%	-	22	16	43	48
Run Number		R2-142-1	R2-156-2	R2-149-1	R2-126-2

a. For conditions see previous table.

b. Excludes iron in mineral matter in coal.

In run 142-1 the results from the addition of 0.5 wt% of an iron oxide sample that was obtained from Wilsonville show an increase in IOM conversion over that observed in the thermal runs above. The 39% conversion for the Wilsonville iron oxide is significantly greater than for the thermal runs. The nanometer sized iron oxide catalyst gave the highest IOM conversion (50%) of any of the catalysts tested in the solvent conversion mode while the two molybdenum catalysts were closer to the IOM conversion level of the Wilsonville iron oxide sample. Since the addition of the 0.5 grams of iron oxide for each of the iron cases has a significantly higher IOM conversion than the thermal runs which already contained the 1.7 grams present in the original solvent mix, it is apparent that the catalytic activity of the iron already present in the sample is not equivalent to the catalyst generated from the added iron precursor.

Although the PA+A concentrations show little change in the thermal runs, in the catalytic runs quite sizable decreases occur with all the product showing up in the oils fraction. In the two cases where iron oxides were added the decrease in PA+A corresponded to conversions from 16-22%. For the molybdenum cases these conversions jumped to 43 and 48%, with the latter being for the NiMo catalyst.

A comparative experiment was performed with ashy resid and NiMo catalyst in absence of any added distillate or deashed resid. In this run shown in Table 30 the ratios of Mo to ashy resid and added sulfur to Mo were the same as in the previous case using the composite solvent.

The level of IOM and PA+A conversion for these two runs are very nearly the same. The slightly higher PA+A conversion probably reflects the higher concentration of the PA+A in the feed due to the contribution made by the presence of the deashed resid in the composite solvent.

Table 30. Conversion of Wilsonville Ashy Resid

Temperature	415°C			
Time	60 min			
Catalyst	Shell 324			
Reactor Volume	50 ml			
H ₂ Pressure	1000 psig			
	Composite Solvent		Ashy Resid	
	Feed	Product	Feed	Product
Composition (ash free wt %)				
Gases		0.5		0.7
Oils	67.1	79.9	41.0	67.1
PA + A	20.8	11.6	38.9	19.0
IOM	12.1	8.1	20.2	13.1
Fe, wt% maf		1.71		3.2
Mo, wt% maf		0.60		1.1
IOM Conv, wt%		37		35
PA+A Conv, wt %		47		51
Run Number		R2-126-2		R2-126-1

Clearly these data show that significant conversion of the solvent occurs under thermal liquefaction conditions. Catalysts likewise accelerates conversion. The iron catalysts give higher conversion of the IOM while the molybdenum catalysts give higher conversion of PA+A. Although the significant concentrations of iron in the ashy resid may contribute to background thermal conversion added fresh iron, which makes up about 1/4 of the total iron present, is far more active. Addition of molybdenum also shows significant catalytic action toward increasing the conversion of the PA+A fraction. As with the iron, the molybdenum present in the ashy resid may contribute to the thermal conversion but its contribution is rather insignificant compared to the levels of conversion observed with the added molybdenum catalysts.

Coal Conversion in Wilsonville Composite Solvent

A series of liquefaction experiments of Black Thunder coal were performed in the Wilsonville composite solvent at 415°C for various reaction periods from 15 to 60 minutes. In all of these runs approximately 5.4 grams of solvent was mixed with 3 grams of coal in a 50 ml horizontal tubing bomb reactor described above. The iron and molybdenum concentrations due to the presence of the metals in the starting solvent calculated on a moisture free basis were 3.8 and 0.08 wt %, respectively. The iron in the coal mineral matter is not included in this value. In cases where catalysts were added those values were separately calculated.

Thermal Runs - A series of runs with reaction times between 15 and 60 minutes were run without any added catalysts. The yields from those runs, which are shown in Table 31, were calculated in the manner discussed above.

Table 31. Thermal Liquefaction in Wilsonville Composite Solvent

	Temperature	415° C		
	Pressure	1000 psig cold		
	Charge			
	Solvent	5.4 grams		
	Coal	3.0 grams		
	Metals Conc on maf Coal			
	Fe	3.8 wt %		
	Mo	0.08 wt %		
	15 min	30 min	60 min	
Yields, wt %				
Gases	5.1	6.1	6.9	
Oils	21.4	36.6	48.7	
PA + A	57.5	56.1	52.1	
IOM	16.1	1.3	-7.7	
Coal Conv, wt %	83.9	98.7	107.7	
Run Number	R2-148-2	R2-167-2	R2-139-1/ R2-167-1	

In these runs conversion of coal increased from 84 to 108% in going from 15 to 60 minute reaction times. The 100%+ conversion of the coal is a reflection of the negative yield of IOM which results from the conversion of the IOM present in the Wilsonville composite feed solvent, specifically the conversion of the IOM in the ashy resid component of the solvent. These values compared with those obtained in tetralin, as shown in Table 21, are directionally the same but considerably different in magnitude.

Interestingly, the gases yields between these runs in Wilsonville solvent and those in tetralin are essentially identical which is probably a reflection of the minimal gas make from the Wilsonville composite solvent in these reaction regimes. At the present time we have no hydrogen consumption numbers to compare between the two series.

Oil yields increased over this reaction period from 21 to 49% in the presence of the Wilsonville solvent whereas in tetralin these values increased from 21 to 43%. This difference is consistent with a the thermal conversion of the starting solvent to give modest increases in oil yield. Correspondingly, the PA+A yield fluctuated modestly over the range in the runs with the Wilsonville solvent as did these values for the runs made in tetralin. This probably reflects the small fluctuations observed in this value for the Wilsonville solvent conversions.

Other than the magnitudes of the conversions and particular fractional yields, the data for the Black Thunder conversion in Wilsonville composite solvent is quite consistent with what was directionally found in tetralin. Whether the iron or molybdenum present in these Wilsonville composite solvent runs caused any catalytic effect isn't evident from the data presented here. As data on hydrogen consumption become available, these values will be examined for any differences which might show an apparent catalytic

In these runs conversion of coal increased from 84 to 108% in going from 15 to 60 minute reaction times. The 100%+ conversion of the coal is a reflection of the negative yield of IOM which results from the conversion of the IOM present in the Wilsonville composite feed solvent, specifically the conversion of the IOM in the ashy resid component of the solvent. These values compared with those obtained in tetralin, as shown in Table 21, are directionally the same but considerably different in magnitude.

Interestingly, the gases yields between these runs in Wilsonville solvent and those in tetralin are essentially identical which is probably a reflection of the minimal gas make from the Wilsonville composite solvent in these reaction regimes. At the present time we have no hydrogen consumption numbers to compare between the two series.

Oil yields increased over this reaction period from 21 to 49% in the presence of the Wilsonville solvent whereas in tetralin these values increased from 21 to 43%. This difference is consistent with a the thermal conversion of the starting solvent to give modest increases in oil yield. Correspondingly, the PA+A yield fluctuated modestly over the range in the runs with the Wilsonville solvent as did these values for the runs made in tetralin. This probably reflects the small fluctuations observed in this value for the Wilsonville solvent conversions.

Other than the magnitudes of the conversions and particular fractional yields, the data for the Black Thunder conversion in Wilsonville composite solvent is quite consistent with what was directionally found in tetralin. Whether the iron or molybdenum present in these Wilsonville composite solvent runs caused any catalytic effect isn't evident from the data presented here. As data on hydrogen consumption become available, these values will be examined for any differences which might show an apparent catalytic

effect.

Wilsonville Fe₂O₃ - The iron oxide used at Wilsonville in Run 262 that provided the source of iron contained in the ashy resid was tested for its catalytic activity for liquefying the Black Thunder coal. The level of iron addition was small compared to the amount already contained in the Wilsonville composite mixture. The runs were made at the same conditions as used for the thermal runs above except for the added iron oxide plus addition of dimethyl disulfide to convert the oxide to its active sulfided form. The data are given in Table 32.

Table 32. Liquefaction with Wilsonville Fe₂O₃

Temperature	415° C	
Pressure	1000 psig cold	
Charge		
Solvent	5.4 grams	
Coal	3.0 grams	
Sulfur/Fe	2.4 mole/mole	
Metals Conc, wt% on maf Coal		
Total Fe	4.9 wt %	
Added Fe	1.1 wt %	
Mo	0.08 wt %	
	30 min	60 min
Yields, wt% maf coal		
Gases	6.4	6.7
Oils	36.2	54.3
PA + A	59.1	45.3
IOM	-1.7	-6.4
THF Conv wt%	101.7	106.4
Run Numbers	R2-169-1	R2-142-2/ R2-189-1

As in the thermal runs above coal conversion was again over 100%. For the 60 minute run the value was almost identical to that observed in the thermal run while the 30 minute data were somewhat lower. As with the thermal runs the gas make was essentially equal

being unaffected by the presence of the added iron. The most noticeable difference between the thermal runs and the added iron runs was the higher oil make in the 60 minute run, e.g., 54.3% for the added iron run versus 48.7% for the thermal runs. Whether this difference is statistically significant isn't known at present. As additional data are developed that type of evaluation will be possible.

Another run was made with the Wilsonville iron oxide using only Wilsonville distillate material without any added ashy or deashed resid. Since most of the iron in the Wilsonville composite solvent is carried in the ashy resid, the run made with distillate contained much less iron, namely 1.2 wt% versus 4.9 wt% in the composite solvent. Molybdenum, on the other hand was not significantly affected since the concentrations in all the fractions were similar. The data from the distillate run at 60 minutes are shown in Table 33.

The conversions in the absence of the ashy resid component show coal conversions of 95% which is somewhat higher than observed in tetralin without the added iron oxide. On the other hand, the oil make is somewhat lower. The specific influence of solvent and iron oxide in this reaction isn't known at present.

Nanomneter Size Iron Oxide - Samples of the nanometer size iron oxide discussed above was tested for liquefaction of the Black Thunder with the Wilsonville composite solvent. The concentration of the added iron on coal was the same as used with the Wilsonville iron oxide above. As in that case sufficient dimethyl disulfide was added to provide 120% of the sulfur necessary to convert the iron to the disulfide. Data for both 15 minute and 60 minute residence times are presented in Table 34.

Table 33. Effect of Ashy Resid on Liquefaction with Iron Oxide

Temperature	415° C	
Pressure	1000 psig cold	
Charge		
Solvent	5.4 grams	
Coal	3.0 grams	
Sulfur/Fe	2.4 mole/mole	
	Ashy Resid	Distillate
	60	60
Metals Conc (wt% maf coal)		
Fe	4.9	1.2
Fe Added	1.1	1.1
Mo	0.07	0.05
Mo Added	0	0
Yields, wt% maf coal		
Gases	6.7	7.3
Oils	54.3	35.7
PA + A	45.3	52.0
IOM	-6.4	5.0
THF Conv wt%	106.4	95.0
Run Numbers	R2-142-2/ R2-189-1	R2-169-2

Compared to the Wilsonville iron oxide at the same iron loading much higher coal conversion was obtained with the nanometer sized iron oxide, namely 114 wt % for the nanometer sized catalyst versus 106 wt % for the Wilsonville iron oxide, while the gases make was again nearly the same for both runs. The higher coal conversion is consistent with the runs in solvent where the nanometer iron oxide gave the highest coal conversion of any of the catalysts that were tested. Accompanying this higher coal conversion was an oils yield of 60 wt% for the nanometer sized oxide versus 54% for the Wilsonville iron oxide case. The higher oils yield was somewhat surprising in that the data from the solvent only runs did not

indicate a particular capacity for catalyzing the conversion of the PA+A fraction. It is obvious that these smaller particle iron materials are significantly more catalytic than the larger sized type of material used at Wilsonville in Run 262.

Table 34. Nanometer Iron Oxide Catalysis

	15 min	60 min
Metals Conc (wt% maf coal)		
Fe	4.9	4.9
Fe Added	1.1	1.1
Mo	0.07	0.08
Mo Added	0	0
Yields, wt% maf coal		
Gases	5.5	7.0
Oils	20.8	60.2
PA + A	58.1	47.1
IOM	15.6	-14.3
THF Conv, wt%	84.4	114.3
Run Number	R2-176-1	R2-162-1

Molybdenum Catalysts - Both supported as well as a molecularly dispersed molybdenum catalysts were tested with the Black Thunder coal in the Wilsonville composite solvent. Molybdenum naphthenate solution containing 6% solubilized molybdenum was added to coal at a ratio of 1 wt % on as received coal. In addition several runs were made with a nickel molybdena catalyst (Shell 324) at a concentration also at the same molybdenum concentration of 1 wt% on as received coal. In this case the data were averaged as presented in Table 35 for comparison with the molybdenum naphthenate. In both cases the molybdenum in the Wilsonville composite solvent was insignificant to the amount that was added for both these catalysts. The amount of iron present in the system was quite significant, however.

Table 35. Black Thunder Liquefaction with Molybdenum Catalysts

		Temperature	415° C
		Pressure	1000 psig cold
		Charge	
		Solvent	5.4 grams
		Coal	3.0 grams
		Sulfur/Mo	2.4 mole/mole added metal
Catalysts		Shell 324	Mo Naphthenate
Metals Conc (wt % maf coal)			
Fe		4.2	3.8
Fe Added		0	0
Mo		1.5	1.5
Mo Added		1.4	1.4
Yields, wt% MAF coal			
Gases		5.3	-
Oils		82.5	75.6 ^a
PA + A		19.7	39.2
IOM		-7.4	-14.8
THF Conv, wt%		107.4	114.8
Run Number		Avg 3 Runs ^b	R2-150-1
a. Combined oils plus gas yield.			
b. Runs made without mixing balls.			

The coal conversion for the molybdenum naphthenate catalyst was comparable to the result with the nanometer size iron oxide which was the highest observed in all these runs. The corresponding yields from the NiMo catalyst was somewhat less, but still significantly higher than for the thermal or Wilsonville iron oxide runs. The PA+A yield for the NiMo was the smallest observed in any of these runs with the corresponding oils yield being correspondingly larger than any of the other runs at 82%. The data for the gas yield from the Mo naphthenate run is not currently available but it would be expected to be about the same as for the other runs which were all between 5-6%, which indicates the thermal nature of the gas formation process.

The data on the Wilsonville composite solvent conversion in the presence of the molybdenum naphthenate did not suggest that it would have a coal conversion number among the highest observed for any of the catalysts tested in this study. In fact, its conversion was lower than for the nanometer iron oxide catalyst, namely 42% versus 50% for the nanometer iron oxide. Likewise the magnitude of the oils make from the solvent only runs showed the molybdenum naphthenate was almost as good as the NiMo catalyst. Both of the above observations on coal conversion and oils yield suggest that the main catalytic effect being observed in these runs with molybdenum is an effect on the coal itself and cannot be ascribed to a higher catalytic specificity for the solvent conversion. This overall question of reactivity of solvent versus coal will be addressed more extensively later.

Mass Transfer Characteristics of Microautoclave Reactor

During this reporting period, we began use of a new reactor design having a 1-inch diameter horizontal configuration shown in Figure 5. Based upon the higher mass transfer rates observed in the horizontal configuration versus the vertical configuration used earlier in this program and the anticipated higher viscosity of the solvents, this configuration was chosen to minimize any problems associated with limited hydrogen mass transfer.¹⁸ The volume of the reactor and gas sample line is nominally 60 ml and the dimensions are as shown in the drawing.

A series of experiments were conducted to evaluate the mass transfer characteristics of this new reactor configuration. Black Thunder coal was liquefied in the Wilsonville composite solvent in the presence of a NiMo catalyst. Everything was held constant over this series of experiments except the shaking rate (or dasher speed) was varied between 300 and 450 rpm and runs were made with and without two 12 mm steel mixing balls being present in the reactor. The

Figure 5. Microautoclave Reactor Drawing

Microautoclave
Reactor

Univ. of Ky.
CAER

6/10/92

SHI

results from this study are shown in Table 36.

Table 36. Liquefaction in Horizontal Tubing-Bomb Reactor

Temperature	415°C					
H ₂ Pressure	1000 psig cold					
Catalyst	NiMo, Shell 324					
Charge						
Solvent	5.4 grams					
Coal	3 grams					
Catalyst	0.24 grams					
Metals, wt % maf coal						
Fe	4.1					
Mo	1.4					
Shaking rate, rpm	300	300	400	400	440	440
Shaker balls	N	Y	N	Y	N	Y
Yields, wt% maf coal						
Gases	6.2	6.2	5.7	6.6	5.5	6.6
Oils	79.9	78.1	84.6	79.2	81.3	83.0
PA + A	21.3	24.8	18.0	23.4	19.7	21.2
IOM	-7.4	-9.1	-8.4	-9.2	-6.5	-10.7
THF Conv, wt%	107.4	109.1	108.4	109.2	106.5	110.7
H ₂ Cons., mg/g coal	67	63	66	65	67	77
Run Number	111-1	112-1	114-1	120-1	120-2	133-1

Although runs were made at 440 rpm, this rate is not experimentally feasible since it cannot be routinely achieved without excessive wear to the dasher equipment. In the runs with the reactor balls being present the THF conversions tend to be higher than those runs made at the same shaker rate without the reactor balls. However, the overall range in THF conversion for all the runs varies between a low of 106.5 up to 110.7 wt%, which were both at 440 rpm.

The PA+A values vary similarly with the runs in the presence of reactor balls giving higher values. In this case, the lowest value is at 400 rpm without reactor balls while the highest value is at 440 rpm with the reactor balls. The oil yields, which includes the

water yields, appear to show no clear trend within the data. The lowest value is at 300 rpm in the presence of shaker balls while the highest is at 400 rpm in the absence of shaker balls.

The hydrogen consumption numbers, which from the standpoint of mass transfer limitations may be the most significant values in this data set, show no clear trend in the data. Other than the value at 440 rpm all the values are between 63 and 67 mg H₂ per gram of coal.

A review of the data suggests that total THF conversion might be a function of the presence of mixing balls, but not of dasher speed. The means and standard deviations for each group, one with and the other without the presence of the reactor balls, were calculated. These values are shown in Table 37.

Table 37. Mean and Standard Deviations for Each Product Fraction

	With Reactor Balls		No Reactor Balls	
	Mean	Std Deviation	Mean	Std Deviation
Product Yields, wt % maf coal				
Gases	6.5	0.2	5.8	0.3
Oils	80.1	2.1	81.9	2
PA+A	23.1	1.5	19.7	1.3
IOM	-9.7	0.7	-7.4	0.8

Comparison of the values and the standard deviations suggests that for one or more of the product classifications the data sets may be statistically different. For each product classification, to determine if the two sets are reliably different, a one-way analysis of variance, or ANOVA, was calculated by dividing the data into two sets for each product class. This provides a simple model with one independent variable. This technique tests the hypothesis that for each product class there no differences exist between the two sets of data. This is referred to as the null hypothesis.

The procedure generates a pooled estimate of the experimental variance within the sets which are used to calculate the "within group mean square variance" which provides an estimate of the internal consistency of the data. A grand average of all data can be determined by dividing the sum of all observations by the total number of observations. The variation of the set averages about this grand average is used to determine the "between group mean square variance". The degree of variation of the "within group variance" and "between group variance" is used to either substantiate or discard the null hypothesis. If the null hypothesis is true, the ratio of the mean squares of the "within group" and "between group" variances should approach one. This ratio is then used to determine the F-distribution. This value provides the confidence level that the two sets of data are indeed distinguishable.

Applying the ANOVA analysis to the data provides the values shown in Table 38.

Table 38. ANOVA Results: Effects of Reactor Balls

	F Value	α	Within Group Std Deviation
Gases	7.27	0.054	0.30
Oils	0.81		2.5
PA+A	5.99	0.078	1.7
IOM	8.77	0.044	0.92

These calculations show that the probability of the reactor balls not affecting the IOM yields is 0.044. Restated, the data has a 96% confidence level and that it would be very unlikely the deviations between treatments could be accounted for by variations within the sets. The root mean square error or deviation in variance within treatments calculated for this analysis was 0.92%.

Applying the same model to PA&A yield shows an α value of .078 with

root mean square error of 1.7%. The oils value has an F value which is less than one which means the variance within the group is greater than the variance between groups. Therefore, the data cannot distinguish an effect of reactor balls on the oils yields.

Therefore, in each of the products, except for oils, there is only a 4 to 8% probability that the null hypothesis is true, and consistency of the data within treatments is good. The data then discredit the null hypothesis and supports a difference in the sets for gases, PA+A and IOM.

Why the presence of reactor balls results in an increase in gases, PA+A and coal conversion isn't clear? One obvious possibility is the grinding effect the balls have on the catalyst making more surface available for reaction. Although there appears to be no affect on hydrogen consumption rate, the major amount of hydrogen consumption could possibly occur early in the reaction and may not be impacted by the added fresh surface generated in the grinding operation. Alternatively, the effect of added surface area due to adding two metal balls should have little effect on the overall reaction since the added balls increases the surface by only about 10%.

It seems at present that adding reactor balls will create complications in evaluating catalyst performance. Therefore, it seems unlikely that we will alter our standard run procedure followed thus far in this program of not using reactor ball.

REFERENCES

1. F. K. Schweighardt, I. S. Kingsley, F. E. Cooper, A. Z. Kamzelski and D. M. Parees, "Development of SRC-1 Product Analysis, 1983, DOE/OR/03054-61 (See p 5 and Table 4).
2. D W. Later, M.L. Lee, K.D. Bartle, R.C. Kong, D.L. Vassilaros. Anal. Chem. 1981, 53, 1612-1.
3. Quarterly Technical Progress Report, Jan-Mar 1992, DE-AC22-91PC91040, pp 5-16.
4. See Figure 1, Quarterly Report, "Advanced Direct Liquefaction Concepts for PETC Generic Units," Jan-Mar 1992, p 16.
5. Del Bianco, et. al., Fuel Processing Technology, 1989, 23 , p.205
6. Del Bianco et al. Fuel, 67,198 , p.874
7. D. C. Elliott and L. J. Sealock, Ind. Eng. Chem. Prod. Res. Dev., 1983, 22, 426.
8. P. R. Solomon, et. al., Energy Fuels, 1990, 4, p42.
9. Stray, PhD. Thesis, Monash University, 1988
10. Winschel, R. A.; Robbins, G. A.; Burke, F. P. Fuel 1987, 66, 654-660.
11. A.D. Overstreet, "A Screening Study of a New Water-Gas Shift Catalyst," M.S. Thesis, July 1974; Virginia Polytechnic Institute and State University, Blacksburg, Virginia.
12. V. Berispek, "Studies of an Alkali Impregnated Cobalt-Molybdate Catalyst for the Water-Gas Shift and Methanation Reactions," M.S. Thesis, March 1975; Virginia Polytechnic Institute and State University, Blacksburg, Virginia.
13. Catalytic, Inc.. Technical Progress Report Run 251, DOE/PC/50041-88, April 1988.
14. R. R. Anderson and B. C. Bockrath, Fuel 1984, 63, 329.
15. D. Kang and E. N. Givens, Chem. Eng. Prog., 1984 (11), p38.
16. R. W. Skinner, "Effects of Accumulated Solids and Solvent Initial Boiling Point on Dissolver Performance," 1983, DOE/OR/03054-29.

17. R. W. Skinner, "Effects of Accumulated Solids and Solvent Initial Boiling Point on Dissolver Performance," DOE/OR/03054-29, Sept 1983.

18. Y. W. Rhee, J. A. Guin and C. W. Curtis, Fuel Process. Tech., 1989, 22, p 97.

END

**DATE
FILMED**

12 / 14 / 92