DOE/ER/45445--4

DE93 001986

SURFACE PHYSICS WITH COLD AND
THERMAL NEUTRON REFLECTOMETRY

Progress Report
for Period April 1, 1991 - March 31, 1992

A. Steyerl

University of Rhode Island
Kingston, Rhode Island 02881-0817

November 1991

Prepared for

THE U. S. DEPARTMENT OF ENERGY
AGREEMENT NO. DE-FG02-91ER45445

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

ds
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

Three aspects of the research project "Surface physics with cold and ultracold neutron reflectometry" were stressed during the present first year:

(1) Setup of the reflectometer facility at the research reactor of the Rhode Island Nuclear Science Center. The installation provides a narrow "pencil beam" analyzed by time of flight using a chopper system. Following beam characterization and a test measurement of the total cross section of copper single crystal first reflectivity measurements are currently performed using a supermirror.

(2) Design study for the ultracold neutron imaging system, with involvement of the relevant industry. Bids are available for several components indicating that it will be very difficult to build the entire system unless further funds become available.

(3) Analysis of features of neutron reflection from surfaces with special emphasis on the effect of surface roughness both on the specular beam and the diffusely reflected and refracted intensity. Previous theoretical studies were supplemented by further numerical calculations of diffuse scattering distributions using different models. Application of ultracold and cold neutron reflectometry to the study of liquid-vapor phase transition were discussed. The theoretical work also includes the development of tentative ideas for novel fundamental physics experiments.

November, 1991

Annual Research Report for Project "Surface Physics with Cold and Thermal Neutron Reflectometry", period April 1, 1991 to March 31, 1992

This report covers the three main aspects of the present project:

(I) Development of a thermal neutron reflectometer facility at the research reactor of the Rhode Island Nuclear Science Center (RINSC), to be used for surface studies, especially in preparation for experiments utilizing national high-flux neutron facilities.

(II) Development of a prototype of very high resolution two-mirror imaging device for ultracold neutrons for fundamental and surface physics studies, to be prepared for tests at the Institute Laue-Langevin and with the option of building a full-fledged system for the Advanced Neutron Source planned at Argonne.

(III) Furthermore, ongoing analysis work in the areas of neutron reflectivity on rough surfaces and of phase transitions on surfaces, as well as on proposals of novel fundamental physics experiments is described.

I. Development of a Thermal Neutron Reflectometer at RINSC

The first stage of the reflectometer setup has been completed. The system comprises a rotatable collimator in the beam tube R1, providing a "pencil-like" beam of 2 mm in diameter. A rotation of the collimator allows a variation of the angle of beam slanting downward or upward in the range up to 0.03 radians, allowing measurements on horizontal surface to be made from "above" and from "below" (e.g., through the sample substrate). Using a disk chopper a time of flight resolution of about 4% is achieved for a flight path of length 4 m and a wavelength of 1.8 Å. Data are accumulated using a NUCLEUS computer equipped with options for multiscaling and pulse height analysis applications. So far mainly a single detector has been used but a linear position sensitive detector has also been tested.

Test experiments were performed to characterize the beam line. They included total cross section measurements on copper single crystal (see the data of figure 1) and first surface reflectivity measurements for a supermirror reflector on the basis FeCo - Al (figure 2).

The data indicate that relevant information can be obtained at this facility, in spite of the low flux available.

We plan to adapt a borrowed UHV sample chamber to the reflectometer needs (control of sample position as well as temperature control up to 700 K) during the remainder of this year. Vibration

isolation and tests of a position sensitive detector and its installation are foreseen for 1992. Provision of a second chopper disk with more than one slit will accelerate data accumulation.

We hope that actual utilization of the new setup can begin during the second funding period (1992/93). Presently, a postgraduate fellow (Lowell Crow, on a partial basis), two graduate students (Steve Quagliato and User Jeng) and a technician (Joseph Micciche) are involved in the technical setup as well as in the preparation of experiments. Following further test experiments on liquid surfaces like D₂O and "Fomblin" oil (a fully fluorinated polyester) we plan to work on supermirrors and on polymer solutions deposited on silicon substrate. Further, if the low intensity permits, first diffraction experiments on a reflection grating will be performed.

In addition to these "in-house" activities it is planned to utilize the reflectometer setup at the Brookhaven HFBR facility. Our intention to take part in the PRT program at this instrument has been expressed in a letter of intent.

II. Design and Development of a High-Resolution Imaging Device for Ultracold Neutrons

In an attempt to reconcile the requirements of the proposed two-mirror imaging system for ultracold neutrons with the reduced budget for this project a number of possibilities were studied:

- (i) Further reduction of the prototype size would eliminate the possibility to demonstrate the very feature of extreme resolution.
- (ii) Attempts to procure used equipment, for instance for the vacuum chamber, were unsuccessful; the combined requirements with respect to cleanliness, reduction of magnetic field, vibration aspects and geometrical conditions could not be met.
- (iii) In-house fabrication of major components of the system does not appear feasible. Although technical support is available at the University of Rhode Island industrial facilities will have to be utilized for fabrication of the imaging mirrors, the vacuum chamber with pumping system, the vibration isolation system and the mu-metal shielding.

The following new bids are available:

- (a) Mirrors: Two curved mirrors: k\$ 84
One flat mirror: k\$ 10.5 to 61
- (b) Vacuum chamber + pumping: k\$ 79.2 to 150
- (c) Vibration isolation system: k\$ 31
- (d) Three-layer magnetic shield: k\$ 34

It is intended to utilize the major part of the budget available for 1991/92 and foreseen for 1992/93 for partial orders for the imaging system.

A part of the collaborative work with ultracold neutrons at the ILL reactor source is summarized in ref. [3]. In spite of the present technical problems of the high flux reactor, Grenoble, preparation for new experiments is being continued, e.g., by the international group setting up the upgraded system designed for a further improvement in the search for an electric dipole moment of the neutron. Arrangements for a test of the two-mirror UCN imaging system upon restart of the reactor (tentatively expected for 1994) have been made.

(III) Theoretical Work Related to Reflectivity and Fundamental Physics

Our work on the theoretical analysis of reflection and refraction at rough surfaces [1] was continued by a graduate student (L. Iyengar) who obtained numerical data on diffuse scattering distributions for a variety of parameters characterizing the surface roughness. An example is given in figure 3. Furthermore, an analysis of reflectivities of magnetic multilayers in the vicinity of a critical point was initiated, and it was proposed to measure the exponent β for a liquid-vapor interface near the critical point with minimal gravity correction, using very slow neutron reflectometry [2].

Furthermore, an attempt was made to quantify a specific type of possible non-linearity in wave mechanics (known as the "logarithmic Schrödinger equation"). First numerical work was described in [3]. An approach of this kind might, possibly, serve as a guideline for the planning of new experiments probing fundamental aspects of matter waves. A detailed report is in preparation.

The principal investigator has devoted, and will devote, 100% of the summer and approximately 60% of time to the various aspects of this project. Support by faculty members is available. The position (1/2) of postdoctoral fellow contained in the grant for the second and third year will be filled by the present postdoctoral fellow (L. Crow) or by one of several candidates who have already shown interest in this position. Dedicated technical support is available from a technician III position currently filled by J. Micciche.

References

- [1] A. Steyerl, S.S. Malik and L.R. Iyengar: "Specular and diffuse reflection and refraction at surfaces", Physics B 173 (1991) 47-64 (Invited paper, Workshop "Methods of Analysis and Interpretation of Neutron Reflectivity Data", Argonne, 23-25 Aug., 1990)
- [2] F.G. Ludecke, S.S. Malik and A. Steyerl: "Possible investigation of liquid-vapor phase transition with a realistic interface using long-wavelength neutrons", Physica B 174 (1991) 177-181.
- [3] A. Steyerl: "Research using ultracold neutrons at the ILL", VI International School on Neutron Physics, Alushta (U.S.S.R.), 8-19 Oct., 1990; will appear in the Proceedings.

Fig. 1: Total cross section for copper single crystal measured using the RINSC reflectometer setup (open circles). The data is compared to a previous measurement (given by the crosses) performed by Grabcev (J. Appl. Cryst. 12 (1979) 399). The solid curve shows a simplified calculation using the incoherent approximation for phonon scattering.

Fig. 2: First reflectivity data (full circles) for a magnetized Fe-Co - Al supermirror with 80 bilayers. The data show the two reflection edges due to the total reflection of one spin state and the diffractive reflection due to the layer system, respectively. General agreement with previous data (triangles) on supermirrors of this type by H.A. Mook and J.B. Hayter (Appl. Phys. Lett. 53 (1988)) was observed.

Fig. 3: Angular distribution of diffuse neutron reflection on a surface with slight roughness, for the following parameters: incident angle = 5 times the critical value; mean square roughness = 10 Å; lateral correlation length for roughness = 1000 Å; $\gamma = 1/2$ corresponds to a fractal dimension of 2.5. The data show that even for fairly large incident angles the diffuse scattering distribution is very broad and that a considerable fraction of diffuse scattering is concentrated near the critical angle for total reflection (the sharp "Yoneda peak").

END

**DATE
FILMED**

12 / 4 / 92