118
1-23-76
LA-3067-MS, Rev.

Informal Report

DL-1907

UC-46

Reporting Date: November 1975

Issued: December 1975

Los Alamos Critical-Mass Data

by

H. C. Paxton

los alamos
scientific laboratory

of the University of California

LOS ALAMOS, NEW MEXICO 87545

An Affirmative Action/Equal Opportunity Employer

MASTER

UNITED STATES
ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION
CONTRACT W-7405-ENG. 36

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

In the interest of prompt distribution, this report was not edited by the Technical Information staff.

Printed in the United States of America. Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22151
Price: Printed Copy \$5.50 Microfiche \$2.25

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.

PAGES i to ii
WERE INTENTIONALLY
LEFT BLANK

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

TABLE OF CONTENTS

	Page
ABSTRACT	1
INTRODUCTION	2
TABLES	
IA1 Highly Enriched U Metal, Unreflected.	4
IA2 U(93.4) - U(N) Metal Cylinders, Unreflected	5
IA3 U(93.3) - U(N) Metal Cylinders, 15.00" Diameter, Unreflected.	6
IA4 U(93.3) - U(N) Metal Cylinders, 21" Diameter, Unreflected	7
IB1 Enriched U Metal Sphere or Pseudosphere, U(N) Reflector.	8
IB2 Enriched U Metal Cylinder, Pseudocylinder or Parallelepiped, U(N) Reflector	9
IB3 Miscellaneous Enriched U Metal, U(N) Reflector.	10
IC1 Highly Enriched U Metal, Reflector of Th, W, WC, Mo or Mo ₂ C	11
IC2 Highly Enriched U Metal, Reflector of Zn, Cu, Ni, Co, or Fe	12
IC3 Highly Enriched U Metal, Reflector of Ti, Al, Al ₂ O ₃ , Mg, Be, or BeO	13
IC4a Highly Enriched U Metal, Complete Graphite Reflector.	14

TABLES (Continued)

	Page
IC4b Highly Enriched U Metal, Partial Graphite Reflector.	15
IC5 Highly Enriched U Metal, Reflector of D ₂ O (99.8%)	16
IC6a Highly Enriched U Metal, Complete Reflector of H ₂ O or Polyethylene.	17
IC6b Highly Enriched U Metal, Complete Reflector of Paraffin	18
IC6c Highly Enriched U Metal, Partial Reflector of H ₂ O, Polyethylene, Lucite, or Paraffin	19
IC7 Highly Enriched U, Mixed Reflector.	20
IIA1 U(93.3) Metal Cylinders Diluted with Fe, Ni, Cu, or Zn, 15" Diameter, Unreflected.	21
IIA2 U(93.3) Metal Cylinders Diluted with Mo, Ta, or W, 15" Diameter, Unreflected	22
IIA3 U(93.3) Metal Cylinders Diluted with Al, Zr, or Hf, 15" Diameter, Unreflected.	23
IIB1 U(93.3) - Graphite Cylinders, Unreflected	24
IIB2a Graphite-Moderated Highly-Enriched U, Reflector of Graphite	25
IIB2b Graphite-Moderated Highly-Enriched U, Reflector of Be (Plus some Graphite).	26
IIC1 Lucite Moderated U(93.16), Unreflected.	27
IIC2a Lucite Moderated U(93.16), $\geq$ 6" Thick Lucite Reflector.	28
IIC2b Lucite Moderated U(93.16) Slabs, 6" Thick Lucite Reflectors on Two Large Surfaces Only.	29
IIC3 Polyethylene Moderated U(93.15) Parallel-epipeds, Beryllium Reflector.	30

	Page
IID1 Lucite-Graphite Moderated U(93.16), Unreflected.	31
IID2a Lucite-Graphite Moderated U(93.16), Lucite Reflected	32
IID2b Lucite-Graphite Moderated U(93.16) Slabs, 6" Thick Lucite Reflectors on Two Large Surfaces Only.	33
IIIE1 Diffuse U(93.1) Reflected by Thick D ₂ O or Be (Cavity Assemblies).	34
IIIE2 U(93.65)O ₂ F ₂ -D ₂ O Solutions, Bare, D ₂ O or Graphite Reflected	35
IIIF1a U(14.67)O ₂ SO ₄ -H ₂ O Solution, Sphere	36
IIIF1b U(93.5)-Phosphate Aqueous Solution Cylinders, 3.0" Thick Fe Reflector	37
IIIF2 Enriched-Uranium Hydride Composition	38
IIIF3 Lattices of U(94) Metal Units, H ₂ O Moderated, H ₂ O Reflected	39
IIIA1 Plutonium-Metal Spheres.	40
IIIA2 Plutonium in Metal-Polyethylene Reflector, Spherical Geometry	41
IIIA3 Plutonium-Metal Cylinders.	42
IIIB1 Diluted Pu Cylinders, 6.0" Diameter, Unreflected.	43
IIIB2 Diluted Pu Cylinders, 6.0" Diameter, 2.0" Thick U(~0.3) Reflector	44
IIIB3 Diluted Pu Cylinders, 6.0" Diameter, 4.5" Thick U(~0.3) Reflector	45
IIIB4 Diluted Pu Cylinders, 6.0" Diameter, 7.5" Thick U(~0.3) Reflector	46
IIIB5 Diluted Pu Cylinders, 6.0" Diameter, 2.0" Thick Th Reflector.	47
IIIB6 Diluted Pu Cylinders, 6.0" Diameter, 4.5" Thick Th Reflector.	48

TABLES (Continued)

	Page
IIIB7 Diluted Pu Cylinders, 6.0 Diameter 7.5" Thick Th Reflector.	49
IV U-233 Metal Spheres.	50
VA Pu or U-233 Metal Spheres Within U(~93) Metal Spheres	51
VB Pu Metal Cylinder Within U(93.2) Metal Cylinder, Thick U(N) Reflector	52
REFERENCES.	53

LOS ALAMOS CRITICAL-MASS DATA

by

H. C. Paxton

ABSTRACT

The original version of this report tabulates critical masses of simple systems, which have been measured through the year 1963. This revision adds data through October 1975, and modifies some of the old critical specifications that have been reevaluated. The old format and symbolism are retained to simplify reproduction.

INTRODUCTION

Numerous Los Alamos critical mass data have been published only as points on curves, frequently after adjustment to "standard" conditions (e.g., to uniform values of U^{235} enrichment and density), and usually without indication of reliability. Under these conditions, original data tend to become lost. It is the purpose of this compilation to retrieve original critical masses and to give some means of judging the quality of measurements.

Indexes of accuracy are probable error, if it has been estimated, the maximum mass of fissile material used in the measurement, or the maximum central-source neutron multiplication attained. For nonhydrogenous systems a multiplication of 10 usually corresponds to a core mass that is 70% to 80% of critical, 20 corresponds to 85% to 90% of the critical mass, 50 corresponds to 93% to 97%, and 100 corresponds to 96-1/2% to 98-1/2%. Generally, the probable error in critical mass is about one-quarter of the difference between the critical mass value and the maximum mass employed. This estimate may be valid down to an indicated probable error of 1% to 2%, beyond which the probable error is usually controlled by the precision with which the composition and geometry of the system can be described. Maximum multiplication is not a reliable index of accuracy for hydrogen-moderated assemblies because of the severe influence of neutron-spectral distortion.

Not included in this compilation are numerous critical assemblies such as reactor mockups, which cannot be described adequately by simple entries in tables. Also omitted are a few critical mass estimates for which the maximum mass used

was less than three-quarters of the critical value.

The following symbolism appears in the tables of critical masses.

m_c - critical mass of core

m_{max} - maximum mass used, in same units as m_c

M_{max} - maximum central source neutron multiplication attained

h_c - critical height of cylindric core

d - diameter of core

$L \times H \times W$ - length times height times width of parallelepiped

ρ - density

w/o - weight percent

v/o - volume percent

U(93) - enriched uranium containing 93 w/o U^{235}

U(N) - uranium with natural isotopic composition

TABLE IA1

HIGHLY ENRICHED U METAL, UNREFLECTED

Corrected empirically for influence of supports and small (~ 0.4 ") source cavity unless noted otherwise

reference	shape	components	material	$\bar{\rho}$ (total U) (g/cm ³)	h_c/d	m_c (kg U ²³⁵)	m_{max} (kg U ²³⁵)	M_{max}
(1)(55)	sphere ^a	thick sections	U(93.71)	18.74	-	49.12 $\pm$ 0.15	critical	
(2)(55)	sphere	thick shells	U(93.86)	18.81	-	48.75 $\pm$ 0.15		142
(3)	pseudosphere	~ 0.4 " rings ^b	U(93.9)	18.5 $\pm$ 0.1	-	50.9	49.8	150
(4)	psuedosphere	~ 0.4 " rings ^b	U(93.9)	18.5 $\pm$ 0.1	-	50.6	50.0	180
(4)	cyl 4.75" dia	~ 0.4 " rings ^b	U(93.8)	18.5 $\pm$ 0.1	-	>94	70.8	13
(4)	cyl 5.50" dia	~ 0.4 " rings ^b	U(93.8)	18.5 $\pm$ 0.1	1.76	66.2	61.4	96
(4)	cyl 6.37" dia	~ 0.4 " rings ^b	U(94.0)	18.5 $\pm$ 0.1	0.95	55.3	52.6	85
(4)	cyl 7.00" dia	~ 0.4 " rings ^b	U(94.0)	18.5 $\pm$ 0.1	0.72	55.6	54.0	76
(4)	cyl 7.50" dia	~ 0.4 " rings ^b	U(94.0)	18.5 $\pm$ 0.1	0.61	58.2	55.9	54
(5)	cyl 15.00" dia	0.3 cm plates	U(93.3)	17.9	0.214	155.3 $\pm$ 0.6	151	67
(5)	cyl 21.00" dia	0.3 cm plates	U(93.2)	17.9	0.141	281.2 $\pm$ 0.7	270	68

^a Corrected for slight asphericity^b Uncorrected for 0.06 in.³ central source cavity; corrected empirically for effect of supports

TABLE IA2

U(93.4) - U(N) METAL CYLINDERS, UNREFLECTED

Indicated layers are combinations of 10.5" diameter, 0.8 cm thick U(93.4), and 0.6 cm thick U(N)

Corrected from partial terminating sandwich to fractional sandwich of proper composition

Corrected for reflection effect of support

All systems critical

References (6), (55)

average composition	repeated layers, thickness (cm)		$\bar{\rho}$ (total U) (g/cm ³)	diameter (in.)	h_c (in.)	h_c/d	m_c (kg U ²³⁵)
	U(93.4)	U(N)					
U(53.6)	0.8 ^a	0.6	18.7	10.50	5.10	0.581	86.8 ± 1/2%
U(37.7)	0.8	1.2 ^b	18.75	10.50	10.04	0.956	100.7 ± 1/2%
U(29.0)	0.8	1.8 ^b	18.8	11.42 av ^c	13.45	1.178	123.0 ± 1%

^a Starts with 0.8 cm U(93.4) at base of stack

^b Starts with 0.6 cm U(N) at base of stack

^c Basic stack of plates extended by blocks of U(94) and U(N) in proper proportion

TABLE IA3

U(93.3) - U(N) METAL CYLINDERS, 15.00" DIAMETER, UNREFLECTED

Indicated layers, combinations of 0.3 cm thick U(93.3) and U(N), 0.6 cm U(N) or 1.5 cm U(N), start with U(N) at bottom and end with portion of sandwich at top

Average composition is that of final stack

Corrected for influence of supports of split stack

Communicated by G. A. Jarvis

average composition	repeated layers, thickness (cm)		$\bar{\rho}$ (total U) (g/cm ³)	h_c (in.)	h_c/d	m_c (kg U ²³⁵)	m_{max} (kg U ²³⁵)
	U(93.3)	U(N)					
U (93.3)	0.3	0	18.06	3.18	0.212	155.2 ^a	151
U (86.4)	3.6	0.3	18.08	3.36	0.224	152.1	146
U (83.4)	2.4	0.3	17.95	3.50	0.233	151.6	146
U (80.5)	1.8	0.3	17.98	3.60	0.240	150.8	146
U (77.7)	1.5	0.3	17.98	3.70	0.247	149.8	146
U (75.1)	1.2	0.3	18.19	3.77	0.252	149.1	146
U (70.5)	0.9	0.3	18.16	4.00	0.266	148.2	146
U (65.5)	3.6	1.5	18.33	4.05	0.270	140.8	136
U (64.4)	0.6	0.3	18.21	4.34	0.289	147.6	142
U (56.6)	2.4	1.5	18.37	4.60	0.306	138.5	136
U (57.1) ^c	2.1	1.5	18.34	4.66	0.311	141.2	137
U (50.5)	1.8	1.5	18.35	5.25	0.350	140.9	137
U (50.7) ^c	1.5	1.5	18.44	5.25	0.350	142.2	141
U (47.0)	0.6	0.6	18.42	5.53	0.369	138.8	134
U (47.1)	0.3	0.3	18.25	5.61	0.374	139.8	134
U (44.2)	1.2	1.5	18.49	5.92	0.394	140.1	137
U (38.0)	0.9	1.5	18.49	7.02	0.468	142.9	140
U (31.6)	0.3	0.6	18.51	8.23	0.548	139.2	135
U (28.9)	0.6	1.5	18.32	9.63	0.642	147.5	144
U (23.9)	(0.3) (0.3)	(1.5) (0.3) ^b	18.65	11.73	0.782	151.6	149
U (21.3)	(0.3) (0.3)	(1.5) (0.6) ^b	18.62	14.15	0.943	162.6	155
U (19.3)	(0.3) (0.3)	(1.5) (0.9) ^b	18.66	17.85	1.190	185.8	175

^a Corrections not as detailed as those for next-to-last item in Table IA1

^b The 1.5 cm U(N) plate was at base of stack; it alternates with the thinner U(N) in successive sandwiches

^c Extra U(93.3) plates at top of stack

TABLE IA4

U(93.3)-U(N) METAL CYLINDERS, 21" DIAMETER, UNREFLECTED

Repeated layers of interleaved U(93.3) and U(N)

References (55), (57)

<u>average composition</u>	<u>repeated layers, thickness (in.)</u>	<u>mass/layer (kg U)</u>	<u>$\bar{\rho}$(total U) (g/cm³)</u>	<u>m_c (kg U²³⁵)</u>	<u>m_{max} (kg U²³⁵)</u>
U(16.01)	0.591 U(N) 0.118 U(93.3)	76.1	18.68	232 $\pm$ 2	224
U(14.11)	0.709 U(N) 0.118 U(93.3)	87.0	18.41	258 $\pm$ 2	252
U(12.32)	0.591 U(N) 0.118 U(93.3) 0.236 U(N)	100.4	18.64	312 $\pm$ 2	307
U(10.90)	0.709 U(N) 0.118 U(93.3) 1.182 U(N) 0.118 U(93.3)	224.8	18.63	540 $\pm$ 13	412

TABLE IB1

ENRICHED U METAL SPHERE OR PSEUDOSPHERE, U(N) REFLECTOR

reference	core				reflector			m_c (kg U^{235})	M_{max}
	shape	components	material	$\bar{\rho}$ (total U) (g/cm ³)	shape	thickness (in.)	$\bar{\rho}$ (g/cm ³)		
(7)(55)	sphere	hemispheres	U(93.24)	18.62	sphere	7.09	19.0	16.63 ± 0.04	critical
(2)(55)	sphere	nesting shells	U(93.9)	18.69	sphere	3.93	19.00	18.61 ± 0.09	167
(2)	sphere	nesting shells	U(93.9)	18.75	sphere	3.52	19.0	19.2 ± 0.2	53
(2)(55)	sphere	nesting shells	U(93.99)	18.67	sphere	1.742	18.67	24.96 ± 0.12	141
(2)(55)	sphere	nesting shells	U(93.91)	18.70	sphere	0.683	19.00	34.31 ± 0.17	156
(4)	pseudosphere	~0.4" rings	U(93.8)	18.5 ^a	pseudosphere	1.87	18.7	24.6	160
(4)	pseudosphere	~0.4" rings	U(93.8)	18.5 ^a	pseudosphere	0.99	18.7	32.4	34
(8)	pseudosphere	1/2" min blocks	U(94)	18.7	pseudosphere	11 av	19.0	16.2	critical
(9)	pseudosphere	1/2" min blocks	U(94.13)	18.7	pseudosphere	9 av	19.0	16.39 ± 0.07	critical
(9)	pseudosphere	1/2" min blocks	U(80.5) ^b	18.7	pseudosphere	8-3/4 av	19.0	18.3	critical
(9)	pseudosphere	1/2" min blocks	U(67.6) ^b	18.75	pseudosphere	8-1/2 av	19.0	20.8	critical
(9)	pseudosphere	1/2" min blocks	U(66.6) ^b	18.75	pseudosphere	8-1/2 av	19.0	21.2	critical
(9)	pseudosphere	1/2" min blocks	U(47.3) ^b	18.8	pseudosphere	7-3/4 av	19.0	27.1	critical
(9)	pseudosphere	1/2" min blocks	U(94)	16.0 ^c	pseudosphere	8-3/4 av	19.0	19.7	critical
(9)	pseudosphere	1/2" min blocks	U(94)	15.8 ^c	pseudosphere	8-3/4 av	19.0	20.1	critical
(9)	pseudosphere	1/2" min blocks	U(94)	13.1 ^c	pseudosphere	8-1/4 av	19.0	25.3	critical
(9)	pseudosphere	1/2" min blocks	U(94)	9.35 ^c	pseudosphere	7-1/4 av	19.0	37.0	critical
(10)	pseudosphere	1/2" min blocks	U(78.7)	~17.8	sphere	19 o.d.	19.0	21.9	critical

^a Uncorrected for 0.06 in.³ central source cavity^b Average concentration of mixed 1/2" cubic units of U(94) and U(N)^c Average density with 1/2" cubic voids distributed throughout core; corrected experimentally for effect of tubular Al spacers within voids

TABLE 1B2

ENRICHED U METAL CYLINDER, PSEUDOCYLINDER OR PARALLELEPIPED, U(N) REFLECTOR (LAST ITEM DEPLETED U)

reference	core				reflector			m_c (kg U ²³⁵)	m_{max} (kg U ²³⁵)	M_{max}
	shape	dimensions (in.)	material	$\bar{\rho}$ (total U) (g/cm ³)	shape	av thickness (in.)	$\bar{\rho}$ (g/cm ³)			
(8)	pseudocylinder ^a	4.00 x ~4.5 av dia	U(94)	18.7	pseudosphere	~9 av	19.0	16.9	critical	
(8)	parallelepiped ^a	4.00 x 4.00 x ~3.5	U(94)	18.7	pseudosphere	~9 av	19.0	16.9	critical	
(8)	parallelepiped ^a	5.00 x 5.00 x ~2.5	U(94)	18.7	pseudosphere	~8-3/4 av	19.0	18.2	critical	
(8)	parallelepiped ^a	7.50 x 7.50 x ~1.5	U(94)	13.7	pseudosphere	~8-1/4 av	19.0	25.4	24.3	
(8)	parallelepiped ^a	7.50 x 3.00 x ~3.0	U(94)	18.7	pseudosphere	~8-1/2 av	19.0	19.6	critical	
(8)	parallelepiped ^a	6.00 x 3.50 x ~3.0	U(94)	18.7	pseudosphere	~8-3/4 av	19.0	18.2	critical	
(4)	cylinder ^b	3.98 dia, $h_c/d = 3.51$	U(93.7)	18.5	cylinder	1.12	18.7	49.5	~43	67
(4)	cylinder ^b	3.98 dia, $h_c/d = 2.15$	U(93.7)	18.5	cylinder	1.87	13.7	30.4	~30	200
(4)	cylinder ^b	4.75 dia, $h_c/d = 1.38$	U(93.8)	18.5	cylinder	1.12	18.7	33.0	~31.5	59
(4)	cylinder ^b	4.75 dia, $h_c/d = 1.03$	U(93.8)	18.5	cylinder	2.00	18.7	24.6	~24	100
(4)	cylinder ^b	5.50 dia, $h_c/d = 0.84$	U(93.8)	18.5	cylinder	1.12	18.7	31.3	~31	96
(4)	cylinder ^b	5.50 dia, $h_c/d = 0.67$	U(93.8)	18.5	cylinder	2.00	18.7	25.0	~24	96
(4)	cylinder ^b	6.37 dia, $h_c/d = 0.565$	U(94.0)	18.5	cylinder	1.12	18.7	32.4	~31.5	66
(4)	cylinder ^b	6.37 dia, $h_c/d = 0.47$	U(94.0)	18.5	cylinder	2.00	18.7	27.4	~26	43
(4)	cylinder ^b	7.00 dia, $h_c/d = 0.46$	U(94.0)	18.5	cylinder	1.12	18.7	35.3		38
(4)	cylinder ^b	7.50 dia, $h_c/d = 0.41$	U(94.0)	18.5	cylinder	1.12	18.7	38.0		107
(4)	pseudocylinder ^a	3.0 av dia, $h_c/d = 3.08$	U(94)	18.7	pseudosphere	~8 av	18.9	21.3	20.7	
(4)	pseudocylinder ^a	4.0 av dia, $h_c/d = 1.00$	U(94)	18.7	pseudosphere	~9 av	18.9	16.66	critical	
(4)	pseudocylinder ^a	6.5 av dia, $h_c/d = 0.31$	U(94)	18.7	pseudosphere	~8-1/2 av	18.9	20.3	19.6	
(4)	pseudocylinder ^a	8.3 av dia, $h_c/d = 0.18$	U(94)	18.7	pseudosphere	~7-3/4 av	18.9	25.7	24.9	
(11)	cylinder ^c	5.25 dia, $h_c/c = 1.25$	U(93.3)	18.75	cylinder	0.500	13.8	40.7 ± 0.1		1000
(11)	cylinder ^c	5.25 dia, $h_c/c = 0.965$	U(93.3)	18.75	cylinder	1.000	13.8	31.4 ± 0.1		500
(12)	cylinder ^d	15.00 dia, $h_c/d = 0.91$	U(93.4)	17.7	cylinder	3.00	13.9	65.4 ± 1.0		52
(12)	cylinder ^e	3.24 dia, $h_c/d = 8.6$	U(93.2)	18.7	cylinder	2.75	18.9	65.5 ± 1.0		52
(13) (55)	cylinder ^f	15.00 dia x 12.75	U(16.19)	18.75	cylinder	3.00	19.0	110.6 ± 0.6	critical	

^a Core of 1/2" min blocks^b Core of ~0.4" nesting rings; uncorrected for 0.06 in.³ central source cavity^c Core of discs 1.20" to 0.075" thick; m_c corrected empirically for incidental reflection, diaphragm supporting part of assembly, and 0.05 in.³ central cavity^d Core of 0.3 cm discs of U(93.4), m_c corrected for influence of support structure^e Core of thick plates; reflector U depleted to ~0.3% U²³⁵^f Core of alternating 0.3 cm discs of U(93.36) and 1.5 cm discs of U(N)

TABLE IB3

MISCELLANEOUS ENRICHED U METAL, U REFLECTOR^a

reference	core	reflector	$\frac{m_c}{\text{kg U}^{235}}$
(14)	annulus, 12.25" o.d. x 6.00" i.d. x 3.01" high, stack of 1/2" and 1/4" thick rings U(93.4), $\bar{\rho}(U) = 18.7 \text{ g/cm}^3$	1.00" thick, U(N), $\bar{\rho} = 19.0$ g/cm ³ , completely envelops core	77.2 ± 0.3 ($m_{\text{max}} > m_c$) ^b
(14)	annulus, 12.25" o.d. x 6.00" i.d. x 2.03" high, stack of 1/2" and 1/4" thick rings U(93.4), $\bar{\rho}(U) = 18.7 \text{ g/cm}^3$	3.00" thick, U(N), $\bar{\rho} = 19.0$ g/cm ³ , completely envelops core	52.2 ± 0.3 ($m_{\text{max}} = 51.6$)
(15)	pseudocylinder, 13.74" av diam x 12.00", av compo- sition: ^c 18.1 v/o U(93.6), $\bar{\rho} = 3.38 \text{ g/cm}^3$; 13.6 v/o U(N), $\bar{\rho} = 2.58 \text{ g/cm}^3$; 11.8 v/o Fe, $\bar{\rho} = 0.92 \text{ g/cm}^3$; 52.3 v/o Al, $\bar{\rho} = 1.40 \text{ g/cm}^3$; 4.2 v/o void	pseudocylinder 5.0" av thickness, $\bar{\rho} = 18.9 \text{ g/cm}^3$	93.0 ($m_{\text{max}} = 225$)
(56)	cylinder, 21.00" diam x 22.00" long, av composition U(10.15), $\bar{\rho}(U) = 18.78 \text{ g/cm}^3$ (homogeneous metal on axis surrounded by interleaved 0.118" thick U(93.3) and U(N) to average same U ²³⁵ enrichment)	U(0.30), 6.00" thick on periphery, 8.00" thick on ends	238 ± 1 (critical)

^aUnlisted, is a nonuniform assembly of mixed plates and rings of U(93.4) and U(N) that enclose a near-central cylindrical cavity, 15.0" diam x 11.8"; outside dimensions of the assembly are 21.0" diam x ~21" high (S. J. Balestrini, G. A. Jarvis, J. D. Orndoff, December 1961). Average composition bounding cavity is U(27), ~1-1/2" thick U(N) rings form top and bottom of cylinder. At critical, the total mass is ~1400 kg U(N) and 339 kg U(93.4). Uncorrected for 1/4" thick steel plate supporting portion above cavity.

^bCorrected for small gap between assembly halves.

^cAverage thickness of core discs, blocks, and shaped Al fillers: U(93.6) ~0.4", U(N) ~0.3", Fe ~0.25", Al ~0.9".

TABLE IC1

HIGHLY ENRICHED U METAL, REFLECTOR OF Th, W, WC, Mo OR Mo₂C

ref	core				reflector				m_c (kg U ²³⁵)	m_{max} (kg U ²³⁵)	M_{max}
	shape	dimensions (in.)	material	$\bar{\rho}$ (total U) (g/cm ³)	material	shape	thickness (in.)	$\bar{\rho}$ (total) (g/cm ³)			
(11)	sphere	(nesting shells)	U(93.9)	18.6	Th	sphere	1.81	11.48	34.7 ± 0.2	34.2	162
(16) (57)	cylinder	5.967 dia, $h_c/d = 0.59$	U(93.16)	18.75	Th	(21.0" equi-lateral cyl)		11.58	28.0 ± 0.3	26.9	
(11)	sphere	(nesting shells)	U(93.9)	18.75	W-alloy ^a	sphere	2.00	17.35	24.1 ± 0.2		159
(11)	sphere	(nesting shells)	U(93.9)	18.75	W-alloy ^a	sphere	4.00	17.35	19.4	18.3	44
(11)	cylinder	5.25 dia, $h_c/d = 1.25^b$	U(93.3)	18.75	W-alloy ^c	cylinder	0.500	17.3	40.6 ± 0.1		1250
(11)	cylinder	5.25 dia, $h_c/d = 0.97^b$	U(93.3)	18.75	W-alloy ^c	cylinder	1.000	17.3	31.75 ± 0.1		128
(17)	cylinder	4.25 dia	U(93.5)	18.7	W-alloy ^d	cylinder	2.00, but one end 3.00	17.3	27.36	critical	
(8)	sphere	(shells) 0.83 i.d.	U(93.9)	18.45	WC	pseudosphere	2.9 av	~14.7	18.7	15.1	13
(8)	sphere	(shells) 0.83 i.d.	U(93.9)	18.45	WC	pseudosphere	4.5 av	~14.7	16.6	15.1	29
(8)	sphere	(shells) 0.83 i.d.	U(93.9)	18.45	WC	pseudosphere	6.5 av	~14.7	16.3	15.1	36
(10)	pseudosphere	(1/2" min blocks)	U(78.5)	17.8	WC	(14" cube)		14.7	20.8 ^e	critical	
(17)	cylinder	4.25 dia	U(93.5)	18.7	WC	cylinder	2.00	~14.7	24.4	23.6	80
(11)	cylinder	5.25 dia, $h_c/d = 1.29^b$	U(93.3)	18.75	Mo (99.8 w/o)	cylinder	0.500	10.43	41.7		210
(11)	cylinder	5.25 dia, $h_c/d = 1.01^b$	U(93.3)	18.75	Mo (99.8 w/o)	cylinder	1.000	10.43	32.9		141
(11)	cylinder	5.25 dia, $h_c/d = 1.23^b$	U(93.3)	18.75	Mo ₂ C ^f	cylinder	0.500	9.57	39.9		270
(11)	cylinder	5.25 dia, $h_c/d = 0.95^b$	U(93.3)	18.75	Mo ₂ C ^f	cylinder	1.000	9.57	30.9		110

^a Composition 90 w/o W, 7 w/o Ni, 3 w/o Cu^b Core of discs 1.2C" to 0.075" thick; m_c corrected empirically for incidental reflection, diaphragm supporting part of assembly, and 0.05 in.³ central cavity^c Composition 91.3 w/o W, 5.5 w/o Ni, 2.5 w/o Cu, 0.7 w/o Zr^d Composition 92 w/o W, 5.5 w/o Ni, 2.5 w/o Cu^e For cylinders in this reflector, m_c/m_c (sphere) = 0.98, 0.96, 0.93 when $h_c/d = 0.92, 0.63, 1.60$, respectively^f Composition 95 to 96 w/o Mo₂C, 4 to 5 w/o Ni

TABLE IC2

HIGHLY ENRICHED U METAL, REFLECTOR OF Zn, Cu, Ni, Co, OR Fe

ref	core				reflector				m_c (kg U ²³⁵)	m_{max} (kg U ²³⁵)	M_{max}
	shape	dimensions (in.)	material	$\bar{\rho}$ (total U) (g/cm ³)	material	shape	thickness (in.)	$\bar{\rho}$ (total) (g/cm ³)			
(11)	sphere	(nesting shells)	U(93.9)	18.7	Zn	sphere	2.00	7.04	30.0	28.5	52
(11)	sphere	(nesting shells)	U(93.9)	18.5	Zn	sphere	4.075	7.04	25.4 ± 0.3	23.9	46
(11) (55)	sphere	(nesting shells)	U(93.8)	18.38	Cu	sphere	1.980	8.88	26.4 ± 0.2		118
(11) (55)	sphere	(nesting shells)	U(94.0)	18.43	Cu	sphere	4.158	8.88	20.8 ± 0.2		141
(11)	cylinder	5.25 dia, $h_c/d = 1.29^a$	U(93.3)	18.75	Cu ^b	cylinder	0.500	8.87	42.16 ± 0.1		330
(11)	cylinder	5.25 dia, $h_c/d = 1.03^a$	U(93.3)	18.75	Cu ^b	cylinder	1.000	8.87	33.44 ± 0.1		190
(8)	pseudosphere	(1/2" min blocks)	U(94.0)	18.7	"A"-Ni	pseudosphere	8-3/4 av	8.88	19.9	critical	
(11) (55)	sphere	(nesting shells)	U(93.8)	18.38	"A"-Ni	sphere	1.945	8.80	27.5 ± 0.4	25.9	42
(11)	cylinder	5.25 dia, $h_c/d = 1.29^a$	U(93.3)	18.75	Ni (elect)	cylinder	0.500	8.79	42.0		170
(11)	cylinder	5.25 dia, $h_c/d = 1.04^a$	U(93.3)	18.75	Ni (elect)	cylinder	1.000	8.79	34.0		190
(11)	cylinder	5.25 dia, $h_c/d = 1.27^a$	U(93.3)	18.75	Co (reag)	cylinder	0.500	8.72	41.5		102
(11)	cylinder	5.25 dia, $h_c/d = 1.02^a$	U(93.3)	18.75	Co (reag)	cylinder	1.000	8.72	33.3		117
(11)	sphere	(nesting shells)	U(93.9)	18.6	Fe (cast)	sphere	2.00	7.16	29.7 ± 0.3	28.5	59
(11)	sphere	(nesting shells)	U(93.9)	18.4	Fe (cast)	sphere	4.00	7.16	26.0 ± 0.2		143
(18)	sphere	(thick shells)	U(93.9)	18.52	steel	(60" cube)		~7.7	23.4		64
(11)	cylinder	5.25 dia, $h_c/d = 1.42^a$	U(93.3)	18.75	Fe ^c	cylinder	0.500	7.78	46.3 ± 0.2		105
(11)	cylinder	5.25 dia, $h_c/d = 1.18^a$	U(93.3)	18.75	Fe ^c	cylinder	1.000	7.78	38.38 ± 0.1		340
(17)	cylinder	4.25 dia	U(93.5)	18.7	Fe ^c	cylinder	4.00	7.78	33.6	26.9	13

^a Core of discs 1.20" to 0.075" thick; m_c corrected empirically for incidental reflection, diaphragm supporting part of assembly, and 0.05 in.³ central cavity

^b Cast Cu, 1/2 to 1 w/o impurity

^c Steel, SAE 1020

TABLE IC3

HIGHLY ENRICHED U METAL, REFLECTOR OF Ti, Al, Al₂O₃, Mg, Be, OR BeO

ref	core				reflector				m_c (kg U ²³⁵)	N_{max}
	shape	dimensions (in.)	material	$\bar{\rho}$ (total U) (g/cm ³)	material	shape	thickness (in.)	$\bar{\rho}$ (total) (g/cm ³)		
(11)	cylinder	5.25 dia, $h_c/d = 1.61^a$	U(93.3)	18.75	Ti ^b	cylinder	0.500	4.50	52.4 ± 0.6	16
(11)	cylinder	5.25 dia, $h_c/d = 1.38^a$	U(93.3)	18.75	Ti ^b	cylinder	1.000	4.50	45.0 ± 0.1	125
(19)	sphere	(nesting shells)	U(93.18)	18.40	Al (2014)	sphere	2.610 ± 0.03	2.82	34.71 ± 0.1	170
(11)	cylinder	5.25 dia, $h_c/d = 1.59^a$	U(93.3)	18.75	Al (2S)	cylinder	0.500	2.70	52.0 ± 0.6	17
(11)	cylinder	5.25 dia, $h_c/d = 1.35^a$	U(93.3)	18.75	Al (2S)	cylinder	1.000	2.70	44.1 ± 0.1	200
(11)	cylinder	5.25 dia, $h_c/d = 1.40^a$	U(93.3)	18.75	Al ₂ O ₃	cylinder	0.500	2.76	45.5	~100
(11)	cylinder	5.25 dia, $h_c/d = 1.14^a$	U(93.3)	18.75	Al ₂ O ₃	cylinder	1.000	2.76	37.2	~150
(11)	cylinder	5.25 dia, $h_c/d = 1.66^a$	U(93.3)	18.75	Mg (FS-1)	cylinder	0.500	1.77	54.2 ± 0.7	13
(11)	cylinder	5.25 dia, $h_c/d = 1.46^a$	U(93.3)	18.75	Mg (FS-1)	cylinder	1.000	1.77	47.7 ± 0.3	34
(11)	sphere	(nesting shells)	U(93.9)	18.5	Be	sphere	1.85	1.84	22.2 ± 0.2	100
(11)	sphere	(nesting shells)	U(93.9)	18.75	Be	sphere	1.89	1.84	21.6	24
(11)	sphere	(nesting shells)	U(93.6)	18.6	Be	sphere	4.64	1.84	13.1 ± 0.2 ^c	143
(11)	cylinder	5.25 dia, $h_c/d = 1.19^a$	U(93.3)	18.75	Be (QMV)	cylinder	0.500	1.84	38.89 ± 0.1	480
(11)	cylinder	5.25 dia, $h_c/d = 0.90^a$	U(93.3)	18.75	Be (QMV)	cylinder	1.000	1.84	29.28 ± 0.1	210
(12)	cylinder	15.00 dia, $h_c/d = 0.131$	U(93.4)	17.7	Be	cylinder	1.00	1.80	93.9 ± 0.9	25
(12)	cylinder	15.00 dia, $h_c/d = 0.090$	U(93.4)	17.7	Be	cylinder	2.00	1.80	64.9 ± 1.0	23
(12)	cylinder	15.00 dia, $h_c/d = 0.068$	U(93.4)	17.7	Be	cylinder	3.00	1.80	49.0 ± 1.0	35
(12)	cylinder	15.00 dia, $h_c/d = 0.053$	U(93.4)	17.7	Be	cylinder	4.00	1.80	37.8 ± 0.5	13
(12)	cylinder	15.00 dia, $h_c/d = 0.042$	U(93.4)	17.7	Be	cylinder	5.00	1.80	30.4 ± 0.5	15
(11)	pseudosphere	(1/2" min blocks) ^d	U(94)	18.7	BeO	pseudosphere	2.35 av	2.69	19.7	85
(11)	pseudosphere	(1/2" min blocks) ^d	U(94)	18.7	BeO	pseudosphere	3.5 av	2.69	16.5	105
(10)	pseudosphere	(1/2" min blocks)	U(82.7)	17.8	BeO	(24" cube)		~2.69	10.3	critical

^a Core of discs 1.20" to 0.075" thick; m_c corrected empirically for incidental reflection, diaphragm supporting part of assembly, and 0.05 in.³ central cavity

^b Composition 96.5 w/o Ti, 2.5 w/o Cr, 1 w/o Fe

^c With 0.010" Cd between core and reflector, $m_c = 14.0$ kg U²³⁵ ($N_{max} = 31$)

^d Uncorrected for 0.06 in.³ central source cavity

TABLE IC4a

HIGHLY ENRICHED U METAL, COMPLETE GRAPHITE REFLECTOR

Graphite is grade CS-312 except as noted

ref	core				reflector				M_{max}
	shape	dimensions (in.)	material	$\bar{\rho}$ (total U) (g/cm ³)	shape	thickness (in.)	$\bar{\rho}$ (g/cm ³)	m_c (kg U ²³⁵)	
(20)	sphere	(nesting shells) ^a	U(93.9)	18.7	sphere	2.00	1.67	29.6 ± 0.3	58
(20)	sphere	(nesting shells) ^a	U(93.9)	18.7	sphere	4.00	1.67	24.3 ± 0.2	150
(20)	sphere	(nesting shells) ^a	U(93.9)	18.45	sphere	6.00	1.67	21.5 ± 0.2	150
(20)	sphere	(nesting shells) ^a	U(93.9)	18.75	sphere	8.00	1.67	19.5 ± 0.3	42
(20)	sphere	(nesting shells) ^a	U(93.9)	18.5	pseudosphere ^b	17 av	1.66	17.0	48
(20)	cylinder	3.25 dia, h _c /d = 2.95 ^c	U(93.7)	18.5	pseudosphere ^b	17 av	1.66	22.5	17
(20)	pseudocylinder	3.62 av dia, h _c /d = 1.85 ^d	U(94)	18.7	pseudosphere ^b	17 av	1.66	20.1	40
(20)	cylinder	3.98 dia, h _c /d = 1.30 ^c	U(93.7)	18.5	pseudosphere ^b	17 av	1.66	18.3	109
(20)	cylinder	4.75 dia, h _c /d = 0.815 ^c	U(93.7)	18.5	pseudosphere ^b	17 av	1.66	17.5	82
(20)	cylinder	5.50 dia, h _c /d = 0.495 ^c	U(93.8)	18.5	pseudosphere ^b	17 av	1.66	18.5	78
(20)	cylinder	6.375 dia, h _c /d = 0.345 ^c	U(94.0)	18.5	pseudosphere ^b	17 av	1.66	20.0	107
(20)	cylinder	7.50 dia, h _c /d = 0.235 ^c	U(94.0)	18.5	pseudosphere ^b	17 av	1.66	22.7	150
(20)	pseudocylinder	h = 1.50, h _c /d = 0.177 ^d	U(94.0)	18.7	pseudosphere ^b	17 av	1.66	24.6	90
(20)	pseudocylinder	h = 1.00, h _c /d = 0.081 ^d	U(94.0)	18.7	pseudosphere ^b	17 av	1.66	34.8	200
(11)	cylinder	5.25 dia, h _c /d = 1.42 ^e	U(93.3)	18.75	cylinder	0.500	1.67	46.35 ± 0.2	51
(11)	cylinder	5.25 dia, h _c /d = 1.16 ^e	U(93.3)	18.75	cylinder	1.000	1.67	37.71 ± 0.1	>500
(12)	cylinder	3.24 dia, h _c /d = 6.78	U(93.2)	18.7	cylinder	4.85	1.60	51.7 ± 0.9	233
(12)	cylinder	3.24 dia, h _c /d = 4.97	U(93.2)	18.7	cylinder	5.75	1.60	37.9 ± 0.7	1350
(12)	cylinder	3.24 dia, h _c /d = 4.41	U(93.2)	18.7	cylinder	6.25	1.60	33.6 ± 0.7	460
(12)	cylinder	15.00 dia, h _c /d = 0.073 ^f	U(93.4)	17.7	cylinder	7.00	1.60	52.1 ± 1.0	20
(21)	cylinder	10.50 dia, h _c /d = 0.192 ^g	U(93.4)	18.7	cylinder	2.00	1.68	50.0	18
(14)	annulus	12.25 o.d. x 6.00 i.d. x 2.86	U(93.4)	18.7	(envelops core)	2.00	~1.67	73.3 ± 0.3	(m_{max} = 71.0)

^a Uncorrected for 0.05 in.³ central source cavity^b Pile-grade graphite surrounds ~5" thick CS-312^c Interlocking rings; uncorrected for 0.06 in.³ central source cavity^d Formed of 1/2" min blocks^e Core of discs 1.20" to 0.075" thick; m_c corrected empirically for incidental reflection, diaphragm supporting part of assembly, and 0.05 in.³ central cavity^f Core of 0.3 cm thick plates; empirical correction for diaphragm supporting part of assembly^g Core of 0.315" thick plates; empirical correction for diaphragm supporting part of assembly

TABLE IC4b

HIGHLY ENRICHED U METAL, PARTIAL GRAPHITE REFLECTOR

Reflector same diameter as core where on ends only

Corrected empirically for diaphragm supporting part of assembly, for incidental reflection, and for small source cavity (no correction required for last item)

ref	core				reflector			m_c (kg U^{235})	M_{max}
	shape	dimensions (in.)	material	$\bar{\rho}$ (total U) (g/cm ³)	surfaces reflected	thickness (in.)	$\bar{\rho}$ (g/cm ³)		
(5)	cylinder	15.00 dia	U(93.3)	17.9 $\pm$ 0.2	top plane	1.00	1.79	135.5 $\pm$ 0.5	123
(5)	cylinder	21.00 dia	U(93.2)	18.2 $\pm$ 0.2	top plane	1.00	1.73	242.3 $\pm$ 0.7	60
(5)	cylinder	15.00 dia	U(93.3)	17.9 $\pm$ 0.2	top plane	2.00	1.79	125.4 $\pm$ 0.5	46
(5)	cylinder	21.00 dia	U(93.2)	18.2 $\pm$ 0.2	top plane	2.00	1.73	222.3 $\pm$ 0.6	140
(5)	cylinder	15.00 dia	U(93.3)	17.9 $\pm$ 0.2	top plane	6.00	1.70	114.9 $\pm$ 0.4	135
(5)	cylinder	21.00 dia	U(93.2)	18.2 $\pm$ 0.2	top plane	6.00	1.76	192.3 $\pm$ 0.6	98
(5)	cylinder	15.00 dia	U(93.3)	17.9 $\pm$ 0.2	both planes	6.00	1.7	75.4 $\pm$ 0.3	37
(5)	cylinder	21.00 dia	U(93.2)	18.2 $\pm$ 0.2	both planes	6.00	1.7	103.5 $\pm$ 0.3	46
(5)	cylinder	15.00 dia	U(93.3)	17.9 $\pm$ 0.2	top plane	7.00	1.71	113.9 $\pm$ 0.4	43
(5)	cylinder	21.00 dia	U(93.2)	18.2 $\pm$ 0.2	top plane	7.00	1.76	190.2 $\pm$ 0.6	95
(5)	cylinder	15.00 dia	U(93.3)	17.9 $\pm$ 0.2	both planes	7.00	1.7	73.0 $\pm$ 0.3	107
(5)	cylinder	21.00 dia	U(93.2)	18.2 $\pm$ 0.2	both planes	7.00	1.7	99.4 $\pm$ 0.3	48
(5)	cylinder	15.00 dia	U(93.3)	17.9 $\pm$ 0.2	top plane	8.00	1.72	113.2 $\pm$ 0.4	55
(5)	cylinder	21.00 dia	U(93.2)	18.2 $\pm$ 0.2	top plane	8.00	1.75	188.4 $\pm$ 0.6	101
(5)	cylinder	15.00 dia	U(93.3)	17.9 $\pm$ 0.2	top plane	12.00	1.70	113.4 $\pm$ 0.4	52
(5)	cylinder	21.00 dia	U(93.2)	18.2 $\pm$ 0.2	top plane	12.00	1.76	185.7 $\pm$ 0.6	67
(5)	cylinder	15.00 dia	U(93.3)	17.9 $\pm$ 0.2	top plane	14.00	1.71	113.3 $\pm$ 0.4	54
(5)	cylinder	21.00 dia	U(93.2)	18.2 $\pm$ 0.2	top plane	14.00	1.76	185.3 $\pm$ 0.6	76
(21)	cylinder	10.50 dia, $h_c/d = 0.226$	U(93.4)	18.7	both planes	2.00	1.68	58.7	20
(22)	annulus	21.00 o.d. x 15.00 i.d. x 3.44	U(93.16)	17.9	(across both planes)	6.00	1.7	164.6	330
(23)	annulus	6.14 o.d. x 3.85 i.d. x 6.36	U(93.15)	18.7	top, bottom, wall (none inside)	9.5 8.9	1.67	32.7 $\pm$ 0.3	28

TABLE IC5

HIGHLY ENRICHED U METAL, REFLECTOR OF D₂O (99.8%)⁽²⁴⁾

shape	core		$\bar{\rho}$ (total U) (g/cm ³)	reflector (sphere)		m_c (kg U ²³⁵)	M_{max}
	dimensions (in.)	material		thickness (in.)	container		
sphere	(nesting shells)	U(93.9) ^a	18.5	3.28	0.04" ss	23.3	36
sphere	(nesting shells)	U(93.9) ^a	18.5	4.59	0.10" Al	20.5	22
sphere	(nesting shells)	U(93.9) ^a	18.5	5.50	0.04" ss	19.0	55
sphere	(nesting shells)	U(93.9) ^a	18.5	6.84	0.04" ss	17.1	40
sphere	(nesting shells)	U(93.7) ^a	18.5	15.3	0.2" ss	13.4	>400
sphere surrounded by 0.010" Cd	(nesting shells)	U(93.9) ^a	18.5	6.7	0.04" ss	20.9	$m_{max} = 18.0$
sphere surrounded by 0.010" Cd	(nesting shells)	U(93.9) ^a	18.5	15.1	0.2" ss	20.2	$m_{max} = 18.0$
hollow sphere, filled with D ₂ O	3.60 i.d.	U(93.9)	18.5	14.9	0.2" ss	16.4	16
hollow sphere, filled with D ₂ O	4.08 i.d.	U(93.7)	18.5	14.7	0.2" ss	17.2	32
hollow sphere, filled with D ₂ O	4.97 i.d.	U(93.7)	18.5	14.4	0.2" ss	18.3	18

^a Empirical correction for small central source cavity

TABLE 1C6a

HIGHLY ENRICHED U METAL, COMPLETE REFLECTOR OF H₂O OR POLYETHYLENE
See also first item of Table 1IF3

ref	core				reflector					
	shape	dimensions (in.)	material	$\bar{\rho}$ (total U) (g/cm ³)	material	shape	thickness (in.)	$\bar{\rho}$ (g/cm ³)	m_c (kg U ²³⁵)	k_{max}
(25)	sphere	(shells) 0.83 i.d.	U(93.9)	18.5	H ₂ O	cylinder	>12	1.00	23.4	49
(25)	sphere surrounded by 0.010" Cd	(shells) 0.83 i.d.	U(93.9)	18.4	H ₂ O	cylinder	>12	1.00	32.9	32
(20)	sphere	(nesting shells) ^a	U(93.9)	18.5	H ₂ O	cylinder	>12	1.00	23.2	154
(24)	sphere	(nesting shells) ^a	U(93.9)	18.5	H ₂ O	sphere	3.25	1.00	23.5	35
(24)	hollow sphere, filled with H ₂ O	7.60 i.d.	U(93.9)	18.5	H ₂ O	sphere	14.6	1.00	25.1	40
(24)	hollow sphere, filled with H ₂ O	4.08 i.d.	U(93.9)	18.5	H ₂ O	sphere	14.4	1.00	26.3	80
(24)	hollow sphere, filled with H ₂ O	4.68 i.d.	U(93.8)	18.5	H ₂ O	sphere	14.3	1.00	27.7	19
(20)	cylinder	3.98 dia, $h_c/d = 1.90^a$	U(93.7)	18.5	H ₂ O	cylinder	>12	1.00	26.7	200
(20)	cylinder	4.75 dia, $h_c/d = 0.98^a$	U(93.8)	18.5	H ₂ O	cylinder	>12	1.00	23.7	101
(20)	cylinder	5.50 dia, $h_c/d = 0.66^a$	U(93.8)	18.5	H ₂ O	cylinder	>12	1.00	24.4	200
(20)	cylinder	6.375 dia, $h_c/d = 0.46^a$	U(94.0)	18.5	H ₂ O	cylinder	>12	1.00	25.9	150
(20)	cylinder	7.00 dia, $h_c/d = 0.365^a$	U(94.0)	18.5	H ₂ O	cylinder	>12	1.00	27.7	108
(20)	cylinder	7.50 dia, $h_c/d = 0.300^a$	U(94.0)	18.5	H ₂ O	cylinder	>12	1.00	29.0	53
(23)	annulus	6.14 o.d. x 3.85 i.d. x 5.75 ^b	U(93.15)	18.75	H ₂ O	cylinder	>12	1.00	29.6 ± 0.5	35
(26)	hemishell, segmented	12.0 o.d., 10.0 i.d.	U(93.5)	18.75	H ₂ O	cylinder	>6	1.00	56	20
(12)	cylinder	3.24 dia, $h_c/d = 12.2$	U(93.2)	18.7	H ₂ O	cylinder	>12	1.00	93.2 ± 5	43
(12)	cylinder	15.00 dia, $h_c/d = 0.082^c$	U(93.4)	17.7	H ₂ O	cylinder	>12	1.00	59.0 ± 0.5	170
(11)	cylinder	5.25 dia, $h_c/d = 1.34^d$	U(93.3)	18.75	polyethylene	cylinder	0.500	0.921	43.7	140
(11)	cylinder	5.25 dia, $h_c/d = 1.00^d$	U(93.3)	18.75	polyethylene	cylinder	1.000	0.921	32.7	140
(12)	cylinder	3.24 dia, $h_c/d = 8.0$	U(93.2)	18.7	polyethylene	cylinder	4.00	0.92	61.3 ± 0.9	161
(12)	cylinder	15.00 dia, $h_c/d = 0.095^c$	U(93.4)	17.7	polyethylene	cylinder	2.00	0.92	68.4 ± 0.9	79
(14)	annulus	12.25 o.d. x 6.00 i.d. x 2.20	U(93.4)	18.7	polyethylene (envelops core)		3.00	0.92	56.6 ± 0.3	$k_{max} > k_c$

^a Uncorrected for 0.05 in.³ central source cavity

^b Water fills annulus

^c Core of 0.3 cm plates; empirical correction for small source cavity and diaphragm supporting part of assembly (not used with H₂O reflector)

^d Empirical correction for small central cavity and support effects

^e Corrected for small gap in final configuration

TABLE IC6b

HIGHLY ENRICHED U METAL, COMPLETE REFLECTOR OF PARAFFIN

Paraffin reflector cylindrical, >8" thick, $\bar{\rho} = 0.89 \text{ g/cm}^3$

ref	shape	core		$\bar{\rho}$ (total U) (g/cm ³)	m_c (kg U ²³⁵)	$M_{\max}$
		dimensions (in.)	material			
(20)	sphere	(nesting shells) ^a	U(93.9)	18.5	22.2	62
(25)	sphere	(shells), 0.83 i.d.	U(93.9)	18.5	22.8	69
(20)	cylinder	3.25 dia, $h_c/d = 4.4^b$	U(93.7)	18.5	35	11
(20)	cylinder	3.98 dia, $h_c/d = 1.80^b$	U(93.7)	18.5	25.0	77
(20)	cylinder	4.75 dia, $h_c/d = 0.915^b$	U(93.8)	18.5	22.2	108
(20)	cylinder	5.50 dia, $h_c/d = 0.605^b$	U(93.8)	18.5	22.4	123
(20)	cylinder	6.375 dia, $h_c/d = 0.45^b$	U(94.0)	18.5	24.5	200
(20)	cylinder	7.50 dia, $h_c/d = 0.280^b$	U(94.0)	18.5	26.9	86

^a Uncorrected for 0.05 in.³ central source cavity^b Interlocking rings ~0.4" thick, uncorrected for 0.05 in.³ central source cavity

TABLE 1C6c

HIGHLY ENRICHED U METAL, PARTIAL REFLECTOR OF H₂O, POLYETHYLENE, LUCITE, OR PARAFFIN (5)

Reflector same diameter as core

Core of 0.3 cm plates and rings; m_c corrected empirically for diaphragm supporting part of assembly, for incidental reflection, and for small central source cavity

cylinder dia (in.)	core		reflector				m_c (kg U ²³⁵)	M_{max}
	material	$\bar{\rho}$ (total U) (g/cm ³)	material	surfaces reflected	thickness (in.)	$\bar{\rho}$ (g/cm ³)		
15.00	U(93.3)	17.9 ± 0.2	H ₂ O ^a	top plane	6.00	1.00	109.6 ± 0.4	250
21.00	U(93.2)	18.2 ± 0.2	H ₂ O ^a	top plane	6.00	1.00	188.5 ± 0.7	99
15.00	U(93.3)	17.9 ± 0.2	polyethylene	top plane	1.00	0.925	129.0 ± 0.5	167
21.00	U(93.2)	18.2 ± 0.2	polyethylene	top plane	1.00	0.925	228.4 ± 0.6	125
15.00	U(93.3)	17.9 ± 0.2	polyethylene	top plane	2.00	0.925	113.6 ± 0.4	57
21.00	U(93.2)	18.2 ± 0.2	polyethylene	top plane	2.00	0.925	198.5 ± 0.6	35
15.00	U(93.3)	17.9 ± 0.2	polyethylene	both planes	2.00	0.925	73.1 ± 0.3	73
21.00	U(93.2)	18.2 ± 0.2	polyethylene	both planes	2.00	0.925	117.4 ± 0.3	90
15.00	U(93.3)	17.9 ± 0.2	polyethylene	top plane	3.00	0.925	109.3 ± 0.4	77
21.00	U(93.2)	18.2 ± 0.2	polyethylene	top plane	3.00	0.925	190.3 ± 0.6	280
15.00	U(93.3)	17.9 ± 0.2	polyethylene	top plane	4.00	0.925	108.5 ± 0.4	75
21.00	U(93.2)	18.2 ± 0.2	polyethylene	top plane	4.00	0.925	188.5 ± 0.6	160
15.00	U(93.3)	17.9 ± 0.2	polyethylene	top plane	6.00	0.925	108.7 ± 0.4 ^b	99
21.00	U(93.2)	18.2 ± 0.2	polyethylene	top plane	6.00	0.925	187.9 ± 0.6 ^c	195
15.00	U(93.3)	17.9 ± 0.2	polyethylene	top plane	8.00	0.925	108.5 ± 0.4	110
21.00	U(93.2)	18.2 ± 0.2	polyethylene	top plane	8.00	0.925	187.8 ± 0.6	245
15.00	U(93.3)	17.9 ± 0.2	polyethylene	top plane	10.00	0.925	108.5 ± 0.4	120
21.00	U(93.2)	18.2 ± 0.2	polyethylene	top plane	10.00	0.925	187.6 ± 0.6	102
15.00	U(93.3)	17.9 ± 0.2	lucite	top plane	6.00	1.18	106.4 ± 0.4	52
21.00	U(93.2)	18.2 ± 0.2	lucite	top plane	6.00	1.18	182.1 ± 0.6	74
15.00	U(93.3)	17.9 ± 0.2	paraffin	top plane	6.00	0.87	109.2 ± 0.4	130
21.00	U(93.2)	18.2 ± 0.2	paraffin	top plane	6.00	0.87	188.5 ± 0.6	49

^a Empirical correction for effect of 1/16" Al tank containing water, via influence of the tank containing lucite^b Critical mass 129.0 ± 0.5 (M_{max} = 170) when 0.015" Cd between core and reflector^c Critical mass 228.4 ± 0.6 (M_{max} = 38) when 0.015" Cd between core and reflector

TABLE IC7

HIGHLY ENRICHED U, MIXED REFLECTOR^a

ref	core				reflector				m_c (kg U ²³⁵)	M_{max}
	shape	dimensions (in.)	material	$\bar{\rho}$ (total U) (g/cm ³)	shape	thickness (in.)	material	$\bar{\rho}$ (g/cm ³)		
(27)	sphere	(nesting shells) ^b	U(93.9)	18.4	sphere	1.88	40 w/o Cu 32 w/o Ni 28 w/o Zn	8.55	26.7	89
(27)	sphere	(nesting shells) ^b	U(93.9)	18.75	sphere	2.02	40 w/o Cu 32 w/o Ni 28 w/o Zn	8.55	25.7	46
(28)	sphere	(shells) 0.83 i.d.	U(93.9)	18.45	inside: sphere outside: sphere	(9.00 o.d.) (18.5 o.d.)	U(N) Al	19.0 2.7	20.2	22
(29)	sphere	(shells) 0.83 i.d.	U(93.9)	18.5	inside: sphere outside: sphere	(9.00 o.d.) (13.7 o.d.)	U(N) Al	19.0 2.7	21.8	65
(29)	sphere	(shells) 0.83 i.d.	U(93.9)	18.5	inside: sphere outside: sphere	(9.00 o.d.) (13.7 o.d.)	U(N) Be	19.0 1.84	17.7	300
(30)	sphere	(thick shells)	U(93.2)	18.4	inside: sphere outside: sphere	0.50 1.30 ₅	U(N) Be	19.0 1.84	23.0	$m_{max} > m_c$
(11)	sphere	(nesting shells) ^b	U(93.5)	18.8	inside: sphere outside: sphere	2.00 2.00	W-alloy ^c cast iron	17.39 7.16	21.0 ± 0.5	20
(11)	cylinder	5.25 dia, $h_c/d = 0.99$	U(93.3)	18.75	inside: cylinder outside: cylinder	0.500 0.500	Be Fe	1.84 7.78	32.4	102
(14)	annulus	12.25 o.d., 6.00 i.d., $h_c = 1.98$	U(93.4)	18.7	inside: (envelops outside: core)	1.00 2.00	U(N) polyethylene	19.0 0.92	50.9	$m_{max} > m_c$
(31)	cylinder	15.00 dia	U(93.3)	17.7	(cyl, top plane only)	2.0 (31 lb)	concrete ^e	~2.3	127.9 ^f	96
(31)	cylinder	15.00 dia	U(93.3)	17.7	(cyl, top plane only)	4.0 (58 lb)	concrete ^e	~2.3	119.5 ^f	10
(31)	cylinder	15.00 dia	U(93.3)	17.7	(cyl, top plane only)	6.0 (89 lb)	concrete ^e	~2.3	117.5 ^f	20
(31)	cylinder	15.00 dia	U(93.3)	17.7	(cyl, top plane only)	8.0 (116 lb)	concrete ^e	~2.3	116.4 ^f	29
(31)	cylinder	15.00 dia	U(93.3)	17.7	(cyl, top plane only)	12.0 (178 lb)	concrete ^e	~2.3	116.1 ^f	35
(31)	cylinder	15.00 dia	U(93.3)	17.7	(cyl, top plane only)	28.0 (406 lb)	concrete ^e	~2.3	115.8 ^f	40

^a Note: Hansen, G. E., Wood, D. P., Geer, W. U., "Critical Masses of Enriched-Uranium Cylinders with Multiple Reflectors of Medium-Z Elements," Nuclear Sci. and Eng. 8, 588-594 (1960). Reported critical masses are not included in this tabulation.

^b Uncorrected for 0.05 in.³ central source cavity

^c Composition 90 w/o W, 7 w/o Ni, 3 w/o Cu

^d Corrected for small gap in final configuration

^e Class A concrete: 1548 lb 3/4" rock, 1563 lb sand, 517 lb Portland cement, 40.3 gal water

^f Unreflected, $m_c = 152.8$ ($M_{max} = 168$); curves of $1/M$ vs mass paralleled for this series

TABLE IIA1

U(93.3) METAL CYLINDERS DILUTED WITH Fe, Ni, Cu, OR Zn, 15" DIAMETER, UNREFLECTED

Thickness of U(93.3) plates 0.3 cm

Plate of diluent at base, portion of sandwich at top, unless noted otherwise

Average composition is that of final stack

Corrected for influence of supports of split stack

Communicated by G. A. Jarvis

diluent (A)	vol % U(93.3)	repeated layers, thickness (cm)		$\bar{\rho}(U)$ (g/cm ³)	$\bar{\rho}(A)$ (g/cm ³)	b_c (in.)	$h_c/\bar{c}$	m_c (kg U ²³⁵)	m_{max} (kg U ²³⁵)
		U(93.3)	A						
Fe	72.8	2.4	0.95	13.28	2.08	4.33	0.289	155.3	151
Fe	62.3	1.5	0.95	11.36	2.88	5.21	0.347	159.9	157
Fe	49.0	0.9	0.95	8.97	3.91	7.02	0.468	170.0	169
Fe	49.0	0.9 ^a	0.95	8.97	3.91	7.00	0.467	169.6	163
Fe	39.1	0.6	0.95	7.18	4.68	9.84	0.656	190.8	187
Fe	38.4	0.6 ^a	0.95	7.01	4.70	9.96	0.654	188.7	182
Ni	72.4	2.4	0.95	13.15	2.35	4.33	0.283	153.7	151
Ni	61.8	1.5	0.95	11.33	3.29	5.14	0.343	157.5	157
Ni	48.1	0.9	0.95	8.82	4.47	6.82	0.455	162.6	157
Ni	39.1	0.6	0.95	7.28	5.26	9.20	0.611	178.8	175
Ni	38.3	0.6 ^a	0.95	7.07	5.34	9.28	0.613	177.3	169
Cu	79.4	3.6	0.95	13.96	1.775	3.85	0.253	150.2	145
Cu	72.3	2.4	0.95	12.56	2.40	4.26	0.284	151.8	145
Cu	66.4	1.8	0.95	12.13	2.92	4.68	0.312	153.4	151
Cu	61.2	1.5	0.95	11.21	3.37	5.06	0.338	153.5	151
Cu	57.4	1.2	0.95	10.50	3.70	5.54	0.369	157.1	151
Cu	50.9	0.9	0.95	9.33	4.28	6.39	0.426	161.1	157
Cu	39.2	0.6	0.95	7.22	5.33	8.33	0.555	162.5	157
Cu	31.8	0.9	1.90	5.93	6.03	10.92	0.728	175.0	169
Zn	38.5	0.6	0.95	7.09	4.32	9.43	0.629	180.7	175

^a U(93.3) plate at base of stack (sandwiches inverted)

TABLE IIA2

U(93.3) METAL CYLINDERS DILUTED WITH Mo, Ta, OR W, 15" DIAMETER, UNREFLECTED

Thickness of U(93.3) plates 0.3 cm

U plate at base, portion of sandwich at top

Average composition is that of final stack

Corrected for influence of supports of split stack

Communicated by G. A. Jarvis

diluent (A)	vol % U(93.3)	repeated layers, thickness (cm)		$\bar{\rho}(U)$ (g/cm ³)	$\bar{\rho}(A)$ (g/cm ³)	h_c (in.)	h_c/d	m_c (kg U ²³⁵)	m_{max} (kg U ²³⁵)
		U(93.3)	A						
Mo	89.2	0.6	0.08	16.18	1.080	3.56	0.238	155.8	151
Mo	79.1	0.3	0.08	15.15	2.09	3.96	0.264	155.1	151
Ta	74.5	0.3	0.1	13.43	4.08	4.43	0.295	160.7	151
Ta	59.4	0.3	0.2	10.77	6.52	5.73	0.382	166.7	157
Ta	49.2	0.3	0.3	8.94	8.16	7.31	0.487	176.5	169
W	73.1	0.3	0.1	13.21	4.92	4.33	0.288	154.4	151
W	57.4	0.3	0.2	10.40	7.83	5.55	0.370	155.8	151
W	47.3	0.3	0.3	8.63	9.72	6.74	0.480	157.2	151
W	40.2	0.3	0.4	7.29	10.99	8.31	0.554	163.7	157
W	35.0	0.3	0.5	6.46	12.15	9.85	0.656	171.9	169
W	30.9	0.3	0.6	5.64	12.80	12.23	0.815	186.5	181

TABLE IIA3

U(93.3) METAL CYLINDERS DILUTED WITH Al, Zr, OR Hf, 15" DIAMETER, UNREFLECTED

Thickness of U(93.3) plates 0.3 cm

U plate at base, portion of sandwich at top

Average composition is that of final stack

Corrected for influence of supports of split stack

Communicated by G. A. Jarvis

diluent (A)	vol % U(93.3)	repeated layers, thickness (cm)		$\bar{\rho}(U)$ (g/cm ³)	$\bar{\rho}(A)$ (g/cm ³)	h_c (in.)	h_c/d	m_c (kg U ²³⁵)	m_{max} (kg U ²³⁵)
		U(93.3)	A						
Al	78.6	0.3	0.08	14.20	0.555	4.14	0.276	159.0	157
Al	64.8	0.3	0.16	11.68	0.912	5.22	0.348	164.9	163
Al	55.2	0.3	0.24	9.97	1.166	6.39	0.426	172.2	169
Al	48.0	0.3	0.32	8.70	1.358	7.67	0.512	180.4	175
Al	42.6	0.3	0.40	7.75	1.502	9.23	0.615	193.2	187
Zr	71.3	0.3	0.1	13.18	1.810	4.44	0.296	158.2	157
Zr	56.6	0.3	0.2	10.31	2.70	5.84	0.389	162.5	157
Zr	46.5	0.3	0.3	8.45	3.32	7.42	0.495	169.4	163
Zr	39.6	0.3	0.4	7.18	3.74	9.22	0.614	178.7	175
Hf	97.3	(3.6) ^a (3.9)	0.1	17.55	0.349	3.27	0.218	155.1	151
Hf	93.4	1.5	0.1	16.80	0.837	3.45	0.230	156.6	151
Hf	85.1	0.6	0.1	15.31	1.904	3.82	0.255	158.1	157
Hf	74.1	0.3	0.1	13.30	3.30	4.48	0.299	161.2	157

^a The two thicknesses of U alternate in successive sandwiches

TABLE IIB1

U(93.3) - GRAPHITE CYLINDERS, UNREFLECTED

Thickness of U(93.3) plates 0.3 cm

U plate at base, portion of sandwich at top

Average composition is that of final stack

Corrected for influence of supports of split stack

Communicated by G. A. Jarvis

vol % U(93.3)	repeated layers, thickness (cm)		$\bar{\rho}(U)$ (g/cm ³)	$\bar{\rho}(C)$ (g/cm ³)	h_c (in.)	h_c/d	m_c (kg U ²³⁵)	m_{max} (kg U ²³⁵)
	U(93.3)	graphite						
15" diameter cylinders:								
86.0	2.4	0.40	15.56	0.222	3.67	0.245	154.5	145
82.2	1.8	0.40	14.78	0.282	3.88	0.258	155.0	145
79.2	1.5	0.40	14.28	0.330	4.00	0.267	154.7	150
75.5	1.2	0.40	13.97	0.399	4.14	0.276	156.3	150
69.7	0.9	0.40	12.70	0.485	4.54	0.303	156.0	145
60.7	0.6	0.40	11.06	0.631	5.23	0.349	156.5	150
53.6	0.9	0.80	9.97	0.758	5.86	0.390	157.7	153
43.5	0.3	0.40	8.07	0.921	7.48	0.499	163.1	157
33.8	0.6	1.20	6.22	1.075	10.24	0.683	172.3	169
28.0	0.3	0.80	5.26	1.188	13.61	0.908	193.6	187
21" diameter cylinders:								
47.7	0.3	0.32	8.94	0.830	5.46	0.260	267	259
31.8	0.3	0.64	5.97	1.123	7.81	0.372	260	247
23.7	0.3	0.95	4.44	1.248	10.48	0.499	258	247
19.00	0.3	1.27	3.56	1.345	13.08	0.623	258	247
15.79	0.3	1.59	2.96	1.392	16.49	0.785	263	259
13.53	0.3	1.90	2.54	1.434	20.1	0.958	274	270
11.89	0.3	2.22	2.23	1.467	23.9	1.138	292	282
10.47	0.3	2.54	1.965	1.540	28.3	1.345	303	294
9.44	0.3	2.86	1.770	1.551	36.4	1.734	350	341
32" square cross section, U(93.2) foil (0.002", 0.003", 0.005" thicknesses):								
2.93	0.021 av	0.71	0.539	1.573	35.9	-	303	285
48" cube in Al matrix at $\bar{\rho} = 0.165$ g/cm ³ , U(93.15) foil (0.002", 0.004" thicknesses), Ref. (58):								
0.0083	0.0076 av	0.74 av	0.1558	1.348	48.0	-	263 ± 1	critical

TABLE IIB2a

GRAPHITE-MODERATED HIGHLY-ENRICHED U, REFLECTOR OF GRAPHITE

ref	core						reflector			m_c (kg U ²³⁵)	m_{max} (kg U ²³⁵)
	dimensions (in.)	U spec	layer thickness U (total)	thickness graphite	$\bar{\rho}$ (U) (g/cm ³)	$\bar{\rho}$ (C) (g/cm ³)	surfaces reflected	thickness (in.)	$\bar{\rho}$ (g/cm ³)		
(22)	21.00 dia, $h_c/d = 0.112$	U(93.3) (47.7 v/o)	0.30 cm	0.32 cm	8.94	0.83	both planes (21.0" dia)	6.00	1.7	112.1 ^a	105.8
(22)	21.00 dia, $h_c/d = 0.185$	U(93.3) (31.8 v/o)	0.30 cm	0.64 cm	5.97	1.12	both planes (21.0" dia)	6.00	1.7	123.3 ^a	117.5
(22)	21.00 dia, $h_c/d = 0.373$	U(93.3) (19.0 v/o)	0.30 cm	1.27 cm	3.56	1.34	both planes (21.0" dia)	6.00	1.7	148.4 ^a	141.1
(22)	21.00 dia, $h_c/d = 0.64$	U(93.3) (13.5 v/o)	0.30 cm	1.91 cm	2.54	1.43	both planes (21.0" dia)	6.00	1.7	182.7 ^a	176.3
(22)	21.00 dia, $h_c/d = 1.04$	U(93.3) (10.47 v/o)	0.30 cm	2.54 cm	1.96	1.54	both planes (21.0" dia)	6.00	1.7	228.5 ^a	222.7
(22)	21.00 dia, $h_c/d = 1.35$	U(93.3) (9.44 v/o)	0.30 cm	2.86 cm	1.77	1.55	both planes (21.0" dia)	6.00	1.7	276.0 ^a	258.6
(22)	21.00 dia, $h_c/d = 2.10$	U(93.3) (8.76 v/o)	0.30 cm	3.18 cm	1.62	1.57	both planes (21.0" dia)	6.00	1.7	377.6 ^a	364.4
(21)	10.50 dia, $h_c/d = 0.402$	U(93.4)	0.03"	0.50"	10.43	0.72	complete	2.00	1.68	58.4 ^b	($m_{max} = 29$)
(32)	48.0 x 48.0 x 48.0	U(93.2)	0.001"	(C/U ²³⁵ = 7135)		1.50	complete	12.00	1.55	7.44 ^c	critical
(32)	48.0 x 39.0 x 42.0	U(93.2)	0.001"	(C/U ²³⁵ = 5297)		1.50	complete	12.00	1.55	7.11 ^c	critical
(32)	40.0 x 36.0 x 36.0	U(93.2)	0.001"	(C/U ²³⁵ = 3369)		1.50	complete	12.00	1.55	7.38 ^c	critical
(32)	40.0 x 33.0 x 33.0	U(93.2)	0.001"	(C/U ²³⁵ = 2538)		1.50	complete	12.00	1.55	8.24 ^c	critical
(32)	48.0 x 48.0 x 45.6 ^d	U(93.2)	0.001"	(C/U ²³⁵ = 4685)		1.34	complete	12.00	1.55	9.07 ^c	critical
(32)	42.0 x 39.0 x 40.0	U(93.2)	0.001"	(C/U ²³⁵ = 2972)		1.34	complete	12.00	1.55	9.52 ^c	critical

^a No correction for 0.020" thick ss diaphragm across median plane of assembly^b Empirical correction for 0.063" ss diaphragm supporting part of assembly^c Core and reflector contain 0.061 v/c Al (1100F) as matrix of 3" square tubes^d Three extra 3" square tubes are averaged into this dimension of core

TABLE IIB2b

GRAPHITE-MODERATED HIGHLY-ENRICHED U, REFLECTOR OF Be (PLUS SOME GRAPHITE)

Core and reflector contain Al (1100) at $\bar{\rho} = 0.165 \text{ g/cm}^3$ as matrix of 3" square tubes; forms are pseudocylinders

One-inch thick unloaded graphite across face 1 of core

Core uranium is U(93.2); $\bar{\rho}$ (Be) = 1.66 g/cm^3

U foil in core 0.002" thick up to 16.3 kg U^{235} , beyond which 0.005" thick foil intermixed

All assemblies critical

ref	Core			reflector				
	dimensions (in.)	C/U ²³⁵	$\bar{\rho}$ (C) (g/cm ³)	Be thickness (in.)			graphite thickness against core face 2 (in.)	m_c (kg U ²³⁵)
				wall	face 1	face 2		
(33)	24.6 av dia x 30.6	125	1.42	4.88 av	4.00	8.00	0.40	53.6
(33)	24.6 av dia x 30.6	125	1.42	5.39 av	4.00	4.00	0.40	53.6
(33)	31.9 av dia x 31.0	395	1.42	5.10 av	4.50	3.20	0.00	28.7
(33)	36.3 av dia x 31.0	395	1.29	5.51 av	3.00 (1.27" C outside both faces of Be)	3.00	0.00	33.5
(33)	38.4 av dia x 31.0	398	1.30	5.04 av	3.35	3.35	0.00	37.6
(33)	38.4 av dia x 30.0	1022	1.48	4.72 av	3.85	0.00 9.1 C	1.00	16.2
(33)	38.4 av dia x 30.0	1022	1.48	4.72 av	3.85	3.85	1.00	16.2
(34)	55.0 av dia x 52.0	1350	1.17	inside: C, 2.00 av outside: Be, 6.50 av	0.00 (no C on face)	0.00	0.00	32.0

TABLE IIC1

LUCITE MODERATED U(93.16), UNREFLECTED

Al matrix throughout core and as incidental reflector, $\bar{\rho}$ (Al) = 0.165 g/cm³Probable error in m_c about $\pm 1\%$ for critical systems

Communicated by J. C. Hoogterp

thicknesses of alternating layers (in.)	$\bar{\rho}$ (U ²³⁵) (g/cm ³)	av atomic ratio		dimensions (in.)	m_c (kg U ²³⁵)	M_{max}
		H/U ²³⁵	C/U ²³⁵			
0.012 U, 1/16 lucite	2.12	5.99	3.74	23.5 x 12 x 10.87	106.5	critical
0.012 U, 1/16 lucite	2.31	5.99	3.74	23.5 x 12 x 9.26	98.8	critical
0.006 U, 1/16 lucite	1.317	12.12	7.57	15 x 11.4 x 12	44.2	critical
0.002 U, 1/16 lucite	0.491	35.4	22.1	15 x 12 x 11.46	16.61	critical
0.004 U, 1/8 lucite	0.476	35.6	22.3	15 x 12 x 12	16.83	128
0.008 U, 1/4 lucite	0.477	35.4	22.1	15 x 12 x 12	16.89	critical
0.012 U, 3/8 lucite	0.489	35.3	22.2	15 x 12 x 11.65	16.78	critical
0.016 U, 1/2 lucite	0.484	35.2	22.0	15 x 12 x 12.06	17.22	critical
0.022 U, 11/16 lucite	0.494	35.1	22.0	15 x 12 x 12	17.48	critical
0.030 U, 15/16 lucite	0.495	35.1	22.0	15 x 12 x 12.47	18.22	critical

TABLE IIC2a

LUCITE MODERATED U(93.16), ≥ 6 " THICK LUCITE REFLECTORAl matrix throughout core and reflector, $\bar{\rho}$ (Al) = 0.165 g/cm³Probable error in m_c about $\pm 1\%$ for critical systems

Communicated by J. C. Hoogterp

thicknesses of alternating layers (in.)	core				reflector		m_c (kg U ²³⁵)	M_{max}
	$\bar{\rho}$ (U ²³⁵) (g/cm ³)	av atomic ratio		critical size (L x H x W-in.)	$\bar{\rho}$ (lucite) (g/cm ³)	thickness/face (L ^a x H x W-in.)		
		H/U ²³⁵	C/U ²³⁵					
0.006 U, 1/16 lucite	1.311	12.2	7.6	15 x 6 x 8.23	1.007	8.25 x $\left(\frac{6}{9}\right)$ x 9	15.90	critical
0.006 U, 1/16 lucite	1.213	13.3	8.3	15 x 6 x 8	1.048	8.25 x 6 x 6	14.32	critical
0.006 U, 1/16 lucite	1.109	12.1	7.6	15 x 9 x 7.5	1.037	8.25 x 6 x 6	18.41	critical
0.006 U, 1/16 lucite	0.950	12.0	7.5	15 x 9 x 10.5	1.036	8.25 x 6 x 6	22.06	critical
0.002 U, 1/16 lucite	0.363	35.6	22.3	15 x 9 x 10.5	1.036	8.25 x 6 x 6	8.43	critical
0.002 U, 1/16 lucite	0.452	35.3	22.0	15 x 6 x 10.5	1.044	8.25 x 6 x 6	7.00	critical
0.002 U, 1/16 lucite	0.517	34.3	21.5	15 x 6 x 8	1.040	8.25 x 6 x 6	6.10	254
0.004 U, 1/8 lucite	0.518	34.3	21.5	15 x 6 x 8.03	1.040	8.25 x 6 x 6	6.14	725
0.008 U, 1/4 lucite	0.518	34.3	21.4	15 x 6 x 8.10	1.048	8.25 x 6 x 6	6.19	critical
0.012 U, 3/8 lucite	0.518	34.3	21.5	15 x 6 x 8.13	1.048	8.25 x 6 x 6.12	6.21	critical
0.016 U, 1/2 lucite	0.521	34.3	21.5	15 x 6 x 8.39	1.050	8.25 x 6 x 6.06	6.45	critical
0.024 U, 3/4 lucite	0.532	33.5	20.9	15 x 6 x 9.11	1.035	8.25 x 6 x 6.06	7.14	critical
0.030 U, 15/16 lucite	0.509	35.3	22.0	15 x 6 x 10.26	1.031	8.25 x 6 x 6.09	7.70	critical
0.030 U, 13/16 lucite	0.582	30.6	19.1	15 x 6 x 9.48	1.031	8.25 x 6 x 6.26	8.13	519
0.030 U, 11/16 lucite	0.685	26.0	16.2	15 x 6 x 8.04	1.030	8.25 x 6 x 6.98	8.12	893
0.030 U, 9/16 lucite	0.818	21.2	13.2	15 x 6 x 8.34	1.031	8.25 x 6 x 6.83	10.06	critical
0.030 U, 7/16 lucite	1.021	16.6	10.4	15 x 6 x 7.89	1.030	8.25 x 6 x 7.05	11.89	170
0.008 U, 15/16 lucite	0.138	133.3	83.2	15 x 6 x 17.09	1.001	8.25 x 6 x 6.04	3.47	critical
0.008 U, 11/16 lucite	0.186	97.8	61.1	15 x 6 x 12.35	1.000	8.25 x 6 x 8.33	3.38	critical
0.008 U, 9/16 lucite	0.229	79.4	49.6	15 x 6 x 10.79	1.000	8.25 x 6 x 9.11	3.65	28

^a Reflector thickness on ends averaged to allow for 1/2" irregularity

TABLE IIC2b

LUCITE MODERATED U(93.16) SLABS, 6" THICK LUCITE REFLECTORS ON TWO LARGE SURFACES ONLY

Alternating layers of 0.002" U and 1/16" lucite in core

Al matrix throughout core and reflector, $\bar{\rho}$ (Al) = 0.165 g/cm³

Probable error in m_c about $\pm 1\%$ for critical systems

Communicated by J. C. Hoogterp

core				reflector		
$\bar{\rho}$ (U ²³⁵) (g/cm ³)	av atomic ratio		dimensions (in.)	$\bar{\rho}$ (lucite) (g/cm ³)	m_c (kg U ²³⁵)	M_{max}
	H/U ²³⁵	C/U ²³⁵				
0.488	35.3	22.1	15 ^a x 6 x 14.53	0.977	10.45	2320
0.422	36.0	22.5	32 x 6 x 13.06	1.007	17.34	critical
0.372	35.7	22.3	32 x 6 x 17.03	1.006	19.96	2320
0.478	35.0	22.5	32 x 5.24 x 12	1.022	15.79	102
0.491	35.9	22.4	32 x 5 x 12	1.022	15.44	1821
0.479	37.3	23.3	32 x 3 x 23.03	1.041	17.37	critical
0.479	35.6	22.2	32 x 3 x 28.5	1.002	21.5	critical
0.431	35.7	22.3	32 x 3 x 54	1.041	36.6	critical
0.474	36.2	22.6	32 x 2.71 x 48	1.040	32.4	187
0.473	36.1	22.6	32 x 2.69 x 52.8	1.037	35.2	critical
0.498	36.2	22.6	32 x 2.50 x 58.9	1.041	38.5	38.6

^a Reflector overhangs fuel 1/2" on both sides

TABLE IIC3

POLYETHYLENE-MODERATED U(93.15) PARALLELEPIPEDS,
BERYLLIUM REFLECTOR

CORE: U(93.15) foil interleaved with polyethylene slabs

Reflector: Brush QMV S-200-C beryllium, $\bar{\rho} = 1.85 \text{ g/cm}^3$

Reference (59)

<u>nominal</u> <u>L x W x H (in.)</u>	<u>core</u> <u>atomic ratio</u> <u>H/U²³⁵</u>	<u>m_c</u> <u>(kg U²³⁵)</u>	<u>m_{max}</u> <u>(kg U²³⁵)</u>
Be reflector 12.5" thick, 0.0012" thick U, polyethylene $\bar{\rho} = 0.961 \text{ g/cm}^3$:			
6.0 x 6.125 x 5.75	375 ^a	0.299	0.291
6.0 x 6.125 x 4.75	316 ^a	0.292	0.291
6.0 x 6.125 x 3.75	242 ^a	0.301	0.297
Be reflector 12.0" thick, 0.0012" thick U, polyethylene $\bar{\rho} = 0.947 \text{ g/cm}^3$:			
6.5 x 6.625 x 4.75	340	0.313	0.311
Be reflector 11.5" thick, 0.0020" thick U, polyethylene $\bar{\rho} = 0.888 \text{ g/cm}^3$:			
8.0 x 8.125 x 7.75	540	0.456	0.451
8.0 x 8.125 x 6.50	489	0.422	0.414
8.0 x 8.125 x 5.00	411	0.386	0.376
8.0 x 8.125 x 3.63	318	0.360	0.339
8.0 x 8.125 x 2.75	248	0.352	0.339
8.0 x 8.125 x 2.25	190	0.376	0.339

^aU foil on all six sides of core.

TABLE IID1

LUCITE-GRAPHITE MODERATED U(93.16), UNREFLECTED

Lucite thickness 1/16" per indicated thicknesses of U and graphite

Al matrix throughout core and as incidental reflector, $\bar{\rho}$ (Al) = 0.165 g/cm³Probable error in m_c about $\pm 1\%$ for critical systems

Communicated by J. C. Hoogterp

thicknesses of layers with 1/16" lucite (in.)	$\bar{\rho}$ (U ²³⁵) (g/cm ³)	av atomic ratio		dimensions (in.)	m_c (kg U ²³⁵)	M_{max}
		H/U ²³⁵	C/U ²³⁵			
0.012 U, 0.120 graphite	0.916	6.02	24.1	23.5 x 18.14 x 18	115.2	critical
0.012 U, 0.280 graphite	0.518	6.04	48.7	23.5 x 28.02 x 24	134.2	317
0.006 U, 0.280 graphite	0.258	12.41	98.2	32 x 24.70 x 24.70	82.4	critical
0.006 U, 0.280 graphite	0.258	12.41	98.2	32 x 13.61 av radius ^a	78.6	critical
0.006 U, 0.280 graphite	0.258	12.27	98.7	23.5 x 28.5 x 28.79	81.4	critical
0.002 U, 0.120 graphite	0.337	35.2	51.8	15 x 15 x 15.69	19.51	critical
0.002 U, 0.120 graphite	0.337	35.2	48.2	15 x 15 x 16.69	20.7	critical
0.002 U, 0.280 graphite	0.224	35.0	101.5	15 x 21 x 21	24.2	critical

^a Pseudocylinder with 3" nodule

TABLE IID2a

LUCITE-GRAPHITE MODERATED U(93.16), LUCITE REFLECTED

U thickness 0.006" and lucite thickness 1/16" per indicated thickness of graphite in core

Al matrix throughout core and reflector, $\bar{\rho}$ (Al) = 0.165 g/cm³All systems critical, probable error in m_c about $\pm 1\%$

Communicated by J. C. Hoogterp

graphite thickness (in.) per 0.006" U, 1/16" lucite	core				reflector			m_c (kg U ²³⁵)
	$\bar{\rho}$ (U ²³⁵) (g/cm ³)	av atomic ratio		critical size (L x H x W-in.)	$\bar{\rho}$ (lucite) ends	(g/cm ³) sides	thickness/face (L ^a x H x W-in.)	
0.280	0.255	12.46	100.3	23.5 x 24 x 24	1.021	0.938	~6 x 1.50 x 1.50	43.2
0.280	0.223	12.48	100.6	23.5 x 21 x 21	1.021	0.969	~6 x 4 x 4	37.8
0.280	0.252	12.12	101.2	23.5 x 18 x 18	1.042	0.984	~6 x 3.75 x 3.75	31.5
0.280	0.244	12.12	101.2	23.5 x 18 x 18	1.042	1.021	~6 x 7.50 x 7.50	30.5
0.280	0.252	12.05	101.5	23.5 x 17.25 x 17.4	1.042	0.982	~6 x 6.38 x 6.32	29.0
0.280	0.251	12.10	101.6	23.5 x 9.57 av radius ^b	1.042	0.980	~6 x 7.10 av ^b	27.8
0.004 av ^c	0.934	12.05	8.89	15 x 9 x 10.5	1.036	1.036	8.25 x 6 x 6	21.7

^a Low-density 1.5" extension of 6" thick reflector; 8.25" end reflector thickness is averaged over 1/2" irregularity^b Pseudocylinder with 3" module^c Average of nonuniformly-distributed 0.120"-thick graphite

TABLE IID2b

LUCITE-GRAPHITE MODERATED U(93.16) SLABS, 6" THICK LUCITE REFLECTORS ON TWO LARGE SURFACES ONLY

Core consists of the successive layers: 0.006" U, 1/16" lucite, 0.280" graphite

Al matrix throughout core and reflector, $\bar{\rho}$ (Al) = 0.165 g/cm³

All systems critical, probable error in m_c about $\pm 1\%$

Communicated by J. C. Hoogterp

ρ (U ²³⁵) (g/cm ³)	core		dimensions (in.)	reflector $\bar{\rho}$ (lucite) (g/cm ³)	m_c (kg U ²³⁵)
	av atomic ratio H/U ²³⁵	ratio C/U ²³⁵			
0.239	13.0	106.2	32 x 13.5 x 29.8	1.001	50.4
0.239	13.2	105.4	32 x 12 x 35.4	1.032	53.3
0.239	13.2	106.9	32 x 9 x 110	1.029	124.0
0.254	12.4	99.1	64 x 9 x 39.1	1.042	93.8
0.254	12.5	99.2	64 x 8.25 x 52.6	1.033	115.9

TABLE IIE1

DIFFUSE U(93.1) REFLECTED BY THICK D₂O OR Be (CAVITY ASSEMBLIES)U²³⁵ enrichment of all uranium is 93.15 w/o; detailed descriptions in Ref. (80)

ref	core		cylindric reflector			m_c (kg U ²³⁵)	m_{max}
	cavity cylinder dimensions (in.)	fuel	material	thickness (in.)	interior liner		
(35)	40 dia x 40	0.003" U foil covering cavity surface, on av 0.05" Al support	D ₂ O (99.2 w/o)	20	1/8" Al, av	6.00 ^a	critical
(35)	same except 4" dia axial channel through bottom reflector					6.06	critical
(35)	same except 6" dia axial channel through bottom reflector					6.09	critical
(35)	same except 8" dia axial channel through bottom reflector					6.19	critical
(35)	same except 9" dia axial channel through bottom reflector					6.26	critical
(35)	same except 10" dia axial channel through bottom reflector					6.40	critical
(35)	same except 23.8 kg D ₂ O (12" x 12" cyl) at cavity center (no channel)					5.60 ^b	critical
(35)	40 dia x 40	six 40" discs of 0.035" av U foil 8" apart along cavity axis, on 1/16" Al plates	D ₂ O (99.2 w/o)	20	1/8" Al, av	7.97 ^c	critical
(36)	15-1/2 dia x 31	0.022" av U foil covering cavity sur- face, on 1/16" Al support	Be ($\bar{\rho} = 1.77$ g/cm ³)	14 wall, 18 top, 15 bottom	-	11.0 ^d	56
(36)	15-1/2 dia x 31	0.015" av U foil covering cavity sur- face, on 1/16" Al support	Be ($\bar{\rho} = 1.79$ g/cm ³)	18.5 wall, 18 top, 15 bottom	-	7.7 ^e	100
(36)	15-1/2 dia x 31	0.6 o.d., 0.25 i.d. graphite - 22 w/o U rods, distributed uniformly within cavity, parallel to axis	Be ($\bar{\rho} = 1.79$ g/cm ³)	18.5 wall, 18 top, 15 bottom	1/16" Al	7.6 ^{e,f}	130
(36)	15-1/2 dia x 16	0.6 o.d., 0.25 i.d. graphite - 22 w/o U rods, distributed uniformly within cavity, parallel to axis	Be ($\bar{\rho} = 1.77$ g/cm ³)	14 wall, 18 top, 30 bottom	1/16" Al	9.9 ^g	138

^a After correction for Al cavity liner and fuel support, $m_c = 5.33$ kg; 6.93 kg of 0.003" foil covers the cavity completely^b Corrected for effect of Al container for central D₂O^c After correction for Al cavity liner and fuel support, $m_c \sim 7.0$ kg^d Corrected (-0.04 kg) for Al fuel support^e Corrected (-0.03 kg) for Al cavity liner^f $m_c = 7.30$ kg when fuel concentrated toward outside of cavity, $m_c = 8.60$ kg when fuel concentrated along axis; with 14" reflector wall, $m_c = 8.99$ kg when fuel concentrated toward outside of cavity^g Corrected (-0.02 kg) for Al cavity liner

TABLE IIE2

U(93.65)O₂F₂-D₂O SOLUTIONS, BARE, D₂O OR GRAPHITE REFLECTED

All systems critical

ref	core					reflector			m_c (kg U ²³⁵)
	c (U ²³⁵) (g/cm ³)	atomic ratio D/U ²³⁵	shape	solution dimensions (in.)	container	shape	dimensions (in.)	composition	
(37)	0.1094	230 ^a	cylinder	24.9 dia x 28.1	1/8" ss		none		24.5
	1" o.d. x 7/8" i.d.	ss	"dry" axial glory hole						
(37)	0.0610	419 ^a	cylinder	24.9 dia x 31.0	1/8" ss		none		15.04
	1" o.d. x 7/8" i.d.	ss	"dry" axial glory hole						
(37)	0.0301	856 ^a	cylinder	30.0 dia x 24.1	1/8" ss		none		8.37
	1" o.d. x 7/8" i.d.	ss	"dry" axial glory hole						
(37)	0.0301	856 ^a	cylinder	30.0 dia x 24.0	1/8" ss		none		8.33
	1-1/8" o.d. x 1" i.d.	Al	"dry" axial glory hole						
(37)	0.0124	2081 ^a	cylinder	30.0 dia x 33.4	1/8" ss		none		4.78
	1-1/8" o.d. x 1" i.d.	Al	"dry" axial glory hole						
(37)	0.679	34.2 ^b	sphere	~13.5 dia	0.04" ss (321)	sphere ^c	10.7 thick D ₂ O	~99.5% D ₂ O	14.19
(37)	0.443	53.7 ^b	sphere	~14.5 dia	0.04" ss (321)	sphere ^c	10.2 thick D ₂ O	~99.5% D ₂ O	11.56
(37)	0.302	81.2 ^b	sphere	~15.5 dia	0.04" ss (321)	sphere ^c	9.7 thick D ₂ O	~99.5% D ₂ O	9.57
(37)	0.185	135.3 ^b	sphere	~16.5 dia	0.04" ss (321)	sphere ^c	9.2 thick D ₂ O	~99.5% D ₂ O	7.05
(37)	0.104	243 ^b	sphere	~17.5 dia	0.04" ss (321)	sphere ^c	8.7 thick D ₂ O	~99.5% D ₂ O	4.77
(37)	0.0595	431 ^b	sphere	~18.5 dia	0.04" ss (321)	sphere ^c	8.2 thick D ₂ O	~99.5% D ₂ O	3.20
(38)	1.051	19.56 ^a	cylinder	12.5 dia x 12.1	ss, 1/16" wall, 1/8" top, bottom	cylinder	32 dia x 31.75 9.67 wall, 10 base, 8.5 top	graphite (CS-312) ρ = 1.67 g/cm ³	25.51
	0.9" thick space above solution								
(38)	0.595	39.4 ^a	cylinder	14 dia x 13.4	ss, 1/16" wall, 1/8" top, bottom	cylinder	32 dia x 31.75 8.92 wall, 10 base, 7 top	graphite (CS-312) ρ = 1.67 g/cm ³	20.11
	1.1" thick space above solution								

^a No correction for ~1 mole percent H₂O^b No correction for ~0.3 mole percent H₂O^c Stainless steel container 35" i.d., ~0.1" thick

TABLE IIF1a

U(14.67)O₂SO₄-H₂O SOLUTION, SPHERE

Solution volume 14.95 liters, container 12" dia, 1/32" thick, type 347 ss sphere

reference	critical core		reflector				m_c (kg U ²³⁵)	m_{max} (kg U ²³⁵)
	ρ (U ²³⁵) (g/cm ³)	atomic ratio H/U ²³⁵	material	ρ (g/cm ³)	shape	outside dimension (in.)		
(39)	0.0378	647	BeO supported on ~12" thick graphite plate	2.7	pseudosphere	~36 dia	0.565 ₅	critical
(39)	0.0383	638	BeO supported on ~12" thick graphite plate	2.7	pseudosphere	~36 dia	0.572 $\pm$ 2 ^a	critical
(39)	0.0383	638	BeO (inside) graphite	2.7 1.67	cube cube	24 18 thick	0.573 $\pm$ 2 ^a	critical
(39)	0.0492	497	graphite (inside) BeO	1.67 2.7	cube cube	18 12 thick	0.735 $\pm$ 10 ^a	0.66
(39)	0.0508	481	graphite	1.67	cube	48	0.760 $\pm$ 10 ^a	0.66
(39),(40)	0.0803	~300	water	1.0	cylinder	60 dia x 60	1.20 $\pm$ 0.05 ^a	0.72 ^b

^a Large detector displacing reflector near core, re-entrant tube in core^b Although this measurement does not satisfy the criterion $m_{max}/m_c \geq 0.75$, multiplication curves with several detector types and locations lead to greater reliability than usual

TABLE IIF1b

U(93.5)-PHOSPHATE AQUEOUS SOLUTION, CYLINDERS, 3.0" THICK Fe REFLECTOR^aSolutions of UO₃ dissolved in 4.26 molar H₃PO₄

Solution cylinder 12.4" dia; 1/8" ss (347) container included in thickness of mild steel reflector

reference	ρ (U ²³⁵) of solution (g/cm ³)	atomic ratio H/U ²³⁵	$\bar{\rho}$ (347 ss) in core (g/cm ³) ^b	solution h _c (in.)	core h _c /d	m _c (kg U ²³⁵)	m _{max} (kg U ²³⁵)
(41),(42)	0.112	212	0	6.5	0.52	1.43 ± 0.02	1.35
(42)	0.112	212	0.725	10.0	0.81	2.02 ± 0.02	1.93
(42)	0.112	212	1.140	17.1	1.38	3.26 ± 0.03	3.10
(41),(42)	0.101	235	0	6.8	0.55	1.36 ± 0.02	1.27
(42)	0.101	235	0.725	10.8	0.87	1.97 ± 0.02	1.85
(41),(42)	0.090	265	0	7.1	0.57	1.25 ± 0.02	1.23
(42)	0.090	265	0.725	12.1	0.97	1.95 ± 0.04	1.85
(41),(42)	0.075	321	0	7.7	0.62	1.14 ± 0.02	1.10
(42)	0.075	321	0.725	15.6	1.26	2.10 ± 0.12 0.03	1.83

^a Reflector nearly in contact with top of solution^b Plates of 1/16" thick type 347 stainless steel distributed throughout the solution as vertical grids

TABLE IIF2

ENRICHED-URANIUM HYDRIDE COMPOSITION^a

Cores are homogeneous except that of last entry

ref	core			reflector				m_c (kg U ²³⁵)	M_{max}
	effective composition	$\bar{\rho}$ (U ²³⁵) (g/cm ³)	shape ^b	material	ρ (g/cm ³)	shape	thickness (in.)		
(43)	U(93.15)H _{2.97} C _{1.11} O _{0.25}	6.36	pseudosphere	U(N)	19.0	pseudosphere	~8-1/2	12.61	critical
(43)	U(93.15)H _{2.97} C _{1.11} O _{0.25}	6.36	pseudosphere	Ni	8.8	pseudosphere	~8-1/2	12.63	critical
(43)	U(93.15)H _{2.97} C _{1.11} O _{0.25}	6.36	pseudosphere	Ni (inside) U(N)	8.8 19.0	pseudosphere pseudosphere	~1/2 ~8	11.81	critical
(43)	U(93.15)H _{2.97} C _{1.11} O _{0.25}	6.36	pseudosphere	Ni (inside) U(N)	8.8 19.0	pseudosphere pseudosphere	~1 ~7-1/2	11.64	critical
(43)	U(93.15)H _{2.97} C _{1.11} O _{0.25}	6.36	approx. cube	U(N)	19.0	pseudosphere	~8-1/2	12.98	critical
(44)	U(73.8)H ₁₀ C ₄	2.09	pseudoellipsoid	U(N)	18.6	sphere	~6-1/2	6.95 ± 0.12	critical
(44)	U(75.0)H ₁₀ C ₄	2.17	pseudosphere	WC	~14.7	cube	~4-1/2	7.00 ± 0.05	critical
(44)	U(75.0)H ₁₀ C ₄	2.17	approx. cube	WC	~14.7	cube	~4-1/2	7.53 ± 0.12	critical
(44)	U(73.5)H ₁₀ C ₄	2.06	pseudoellipsoid	Pb	11.2	sphere	~6-1/2	9.2 ± 0.2	14.5
(44)	U(73.5)H ₁₀ C ₄	2.06	pseudoellipsoid	Fe	7.8	sphere	~6-1/2	8.29 ± 0.17	critical
(44)	U(75.2)H ₁₀ C ₄	2.18	approx. cube	BeO	2.69	cube	~6	3.52 ± 0.05	critical
(44)	U(75.2)H ₁₀ C ₄	2.18	approx. cube	BeO	2.69	cube	~12	2.80 ± 0.06	critical
(44)	U(73.8)H ₁₀ C ₄	2.07	approx. cube			none		16.5 ± 1.2	13.7
(45)	av U(94.5)H _{3.8} C _{1.9} ^c (heterogeneous)	5.32	pseudosphere	U(N)	19.0	pseudosphere	~8	11.35	critical

^a Heterogeneous mixtures of U(72)H₁₀C₄ and polyethylene extending to the average composition UH₈₀C₃₉ have not been tabulated because of imperfect reflector assemblies and deficient core densities^b All cores built of 1/2" cubic units^c Core composed of 1/2" cubes of U(94.5) metal and of polyethylene, intermixed to average 30 v/o U

TABLE IIF3

LATTICES OF U(94) METAL UNITS, H₂O MODERATED, H₂O REFLECTOR

Centered in water cylinder, 35-1/2" dia x 23" deep

Reference (46)

U ²³⁵ enrich- ment, w/o	dimensions of metal unit (in.)	lattice		center-center spacing (in.)	critical no. of units	m _c (kg U ²³⁵)	m _{max} (kg U ²³⁵)	M _{max}
		structure	form					
94.0	4.0 x 4.0 x 4.5	(solid core)		-	1	22.5	20.8	110
94.3	1 cube	cubic	approx. cube	1.25	33.4	24.1	22.0	100
94.3	1 cube	cubic	approx. cube	1.50	75.0	21.7	18.5	58
94.3	1 cube	cubic	approx. cube	1.75	73.0	21.1	18.5	81
94.3	1 cube	cubic	approx. cube	2.00	79.9	23.1	19.7	74
94.52	1/2 cube	cubic	approx. cube	0.75	469	17.0	12.4	22
94.52	1/2 cube	cubic	approx. cube	1.00	378	13.7	12.4	90
94.52	1/2 cube	cubic	approx. cube	1.17	372	13.5	12.4	124
94.52	1/2 cube	cubic	approx. cube	1.50	522	18.9	12.4	34
94.52	1/2 cube	body-center cubic	approx. cube	1.50 in any horiz. plane	368	13.3 ^a	12.4	143
93.61	1/8 dia x 12 rod	square	pseudocylinder	0.50	171	7.13	6.55	86
93.61	1/8 dia x 12 rod	square	pseudocylinder	0.625	149	6.22 ^b	5.91	125
93.61	1/8 dia x 12 rod	square	pseudocylinder	0.750	152	6.33	6.01	170
93.61	1/8 dia x 12 rod	square	pseudocylinder	0.875	173	7.21	6.55	139
93.61	1/8 dia x 12 rod	square	pseudocylinder	1.00	>203	>8.4	6.55	52

^a With alternate horizontal planes of cubes translated 3/4" to vertical face-center positions, m_c = 13.6 kg^b Non uniform arrays of 1/8" rods gave minimum observed m_c = 6.08 kg with spacing graded from 1/2" near axis to 1" near periphery

TABLE IIIA1

PLUTONIUM-METAL SPHERES

Hemispheres of Pu(1.0w/o Ga) are coated with ~0.005" thick Ni, unless otherwise noted

ref	core		reflector				m_c (kg Pu)	M_{max}
	w/o Pu ²⁴⁰	$\bar{\rho}$ (total Pu) (g/cm ³)	material	shape	thickness (in.)	$\bar{\rho}$ (g/cm ³)		
(47) (55)	4.5	15.45		none			16.85 ± 0.10 ^a	critical
(55)	20.2	15.57		none			19.26 ± 0.15 ^b	critical
(47) (55)	1.5	15.63	U(N)	pseudosphere	9-1/2 av	19.0	5.73 ± 0.02 ^c	critical
(7) (55)	4.82	15.36	U(N)	sphere	7.72	19.0	5.99 ± 0.03 ^c	critical
(2)	1.35	15.58	U(N)	sphere	4.60	19.0	6.22	94
(48)	4.9	15.62	U(N)	sphere	1.625 ± 1%	18.92	8.39	$m_{max} > m_c^e$
(49) (57)	5.1	15.25	Th	cylinder (21" diam x 21")	8.4 min	11.58	9.24 ^a	critical
(48)	4.9	15.62	W ^f	sphere	1.850 ± 1%	17.21	8.39	$m_{max} > m_c^e$
(50)	1.35	15.58	Cu	sphere	5.00	8.88	6.88 ^g	25
(19)	4.9	15.74	Al (2014)	sphere	3.12 ± 0.03	2.82	11.04	$m_{max} > m_c^e$
(48)	4.9	15.62	Be (98 w/o)	sphere	1.452 ± 1%	1.83	8.39	$m_{max} > m_c^e$
(25)	1.35	15.58	water	cylinder	>12	1.00	7.9 ^h	15
(55)	5.20	19.74	water	cylinder	>10	1.00	5.79 ± 0.3 ⁱ	critical
(10)	1.0	15.6	inside: U(N) outside: Al	sphere sphere	(1.0 o.d.) (18.5 o.d.)	19.0 2.7	6.46 ^h	$M_{max} = 6.15$
(10)	1.35	15.58	inside: U(N) outside: WC	sphere parallelepiped (12.75" x 12.75" x 10.62")	0.45	19.0 ~14.7	6.13 ^h	critical

^aThree major parts; corrected empirically to unreflected, uniform sphere; 0.3 w/o Pu²⁴¹.^bThree major parts; corrected empirically to unreflected, uniform sphere; 3.1 w/o Pu²⁴¹, 0.4 w/o Pu²⁴².^cTwo major parts, corrected empirically for effects of Ni and cavities.^d0.30 w/o Pu²⁴¹.^eEffect of a small compensating gap was extrapolated to zero.^fComposition 91.3 w/o W, 5.5 w/o Ni, 2.5 w/o Cu, 0.7 w/o Zr.^gNo correction for 0.41" central source cavity.^hNo correction for 0.83" central source cavity.ⁱ0.30 w/o Pu²⁴¹, 0.02 w/o Pu²⁴²; no Ga.

TABLE IIIA2

PLUTONIUM IN METAL-POLYETHYLENE REFLECTOR, SPHERICAL GEOMETRY

Ball of Pu(94.54 w/o Pu²³⁹, 5.11 w/o Pu²⁴⁰, 0.35 w/o Pu²⁴¹) in three major Ni-coated parts, 0.95 w/o Ga

Close-fitting metal or graphite shell, 5.335-cm nominal i.d., 6.335-cm o.d., polyethylene shell 6.342-cm i.d.

Critical mass 9.76 kg Pu in each case

Reference (61)

metal or graphite shell		polyethylene critical parameters ^a		<u>M_{max}</u>
<u>material</u>	<u>mass (kg)</u>	<u>density (g/cm³)</u>	<u>mass (kg)</u>	
beryllium	0.783	0.926 av	1.261	549
graphite	0.738	0.926 av	1.960	critical
aluminum	1.140	0.937 av	2.507	critical
iron	3.414	0.960	2.807	critical
molybdenum	4.291	0.924	1.739	274

^a Measured when temperature at center of Pu was 30°C.

TABLE IIIA3

PLUTONIUM-METAL CYLINDERS

Cores of Pu(1w/o Ga) containing ~5% Pu²⁴⁰; no correction for Ni coating

Reference (12)

See also the last item of Table VB

core			cylindric reflector			m_c (kg Pu)	m_{max} (kg Pu)
cylinder dia (in.)	h_c/d	$\bar{\rho}$ (total Pu) (g/cm ³)	material	$\bar{\rho}$ (g/cm ³)	thickness (in.)		
2.25 ^a	8.75	15.44	U(~0.3) ^b	18.7	3.0	20.0 ± 0.1	19.2
2.25 ^a	7.13	15.44	graphite ^b	1.60	7.0	16.3 ± 0.1	15.7
2.21 ^a	12.52	15.44	water	1.00	>12	27.1 ± 1.5	21.3
6.0 ^c	0.258	14.3	U(N)	18.7	3.0	10.14 ± 0.07	9.9
6.0 ^c	0.390	14.3	graphite	1.60	1.0	15.44 ± 0.07	15.4
6.0 ^c	0.273	14.3	graphite	1.60	7.0	10.8 ± 0.07	10.7
6.0 ^c	0.280	14.3	water ^d	1.00	>12	11.1 ± 0.2	9.9
11.0 ^{c,e}	0.095	13.1 ^e	water ^d	1.00	>12	21.4 ± 0.8	20.0
16.0 ^{c,e}	0.049	13.1 ^e	water ^d	1.00	>12	34.1 ± 1.2	26.5

^a Pu pieces 0.5" to 3.0" thick, each coated with 0.005" thick Ni

^b Reflector wall lined with 0.030" thick steel

^c Pu pieces 5.934" dia x 0.123" in thin Ni cans with outside dimensions 5.967" x 0.135"

^d Core sealed in lucite container before immersion in water

^e Average diameter and density of cylinders constructed of overlapping layers of close-packed plates

TABLE IIIB1

DILUTED Pu CYLINDERS, 6.0" DIAMETER, UNREFLECTED

Pu (1w/o Ga), ~5% Pu²⁴⁰, as discs 5.934" dia x 0.123", in thin Ni cans of outside dimensions 5.967" dia x 0.135", ρ (Pu) = 15.61 g/cm³.

Diluent plates 5.967" dia x 1/8" or 1/4"

Reference (51)

diluent (A)	vol % Pu	repeated layers, nom thickness (in.)		core-average ρ (g/cm ³) ^a			h_c (in.)	h_c/d^a	m_c (kg Pu)	m_{max} (kg Pu)
		Pu	A	$\bar{\rho}$ (Pu)	$\bar{\rho}$ (A)	$\bar{\rho}$ (Ni)				
none	91.4	1/8	-	14.27	-	0.65	3.23	0.54	21.4 ^b	20.2
U(0.28)	63.0	1/4	1/8	9.83	5.97	0.45	6.07	1.01	27.3	25.2
steel ^c	62.7	1/4	1/8	9.78	2.50	0.45	7.32	1.22	32.8	27.1
Th	62.7	1/4	1/8	9.78	3.62	0.45	7.85	1.31	35.2	27.1

^a Based on 6.00" diameter

^b Also reported in (51) are reflector saving values for 1/2" thick discs of polyethylene, Be, graphite, Mg, Al, Ti, Fe, Co, Ni, Cu, Mo, W, Th, U(N), and U(0.28), on the top of this Pu stack

^c Stainless steel, type 304

TABLE IIIB2

DILUTED Pu CYLINDERS, 6.0" DIAMETER, 2.0" THICK U(~ 0.3) REFLECTOR

Pu(1w/o Ga), $\sim 5\%$ Pu²⁴⁰, as discs 5.934" dia x 0.123", in thin Ni cans of outside dimensions 5.967" dia x 0.135"; ρ (Pu) = 15.61 g/cm³

Diluent plates 5.97" dia x 1/8" or 1/4"

Steel guide sleeve, 0.030" thick, within reflector cylinder; $\bar{r}$ (U) = 19.0

Reference (51)

diluent (A)	vol % Pu	repeated layers, nom thickness (in.)		core-average ρ (g/cm ³) ^a			h_c (in.)	h_c/d^a	m_c (kg Pu)	m_{max} (kg Pu)
		Pu	A	$\bar{\rho}$ (Pu)	$\bar{\rho}$ (A)	$\bar{\rho}$ (Ni)				
none	90.8	1/8	-	14.18	-	0.65	1.72	0.29	11.1 ₅	10.7
U(0.28)	62.2	1/4	1/8	9.71	5.95	0.45	2.92	0.49	13.0	12.5
steel ^b	62.5	1/4	1/8	9.75	2.51	0.45	3.15	0.52 ₅	14.1	13.9
Th	62.4	1/4	1/8	9.74	3.63	0.45	3.29	0.55	14.7	14.4
Al ^c	62.3	1/4	1/8	9.72	0.84	0.45	3.23	0.54	14.4	14.15
space	64.0	1/4	1/8	9.97	-	0.45	3.29	0.55	15.0 ₅	14.4
U(0.28)	47.8	1/8	1/8	7.46	9.03	0.34	4.56	0.76	15.6	15.4
steel ^b	47.6	1/8	1/8	7.43	3.78	0.34	5.58	0.93	19.0	18.7
Th	48.0	1/8	1/8	7.49	5.55	0.34	6.02	1.00	20.6 ₅	19.8
Al ^c	48.0	1/8	1/8	7.49	1.28	0.34	5.78	0.96	19.9	19.6
space	48.7	1/8	1/8	7.60	-	0.35	6.43	1.07	22.4	21.7
U(0.28)	32.4	1/8	1/4	5.05	12.22	0.23	12.49	2.08	28.9	27.1

^a Based on 6.00" diameter to include reflector clearance^b Stainless steel, type 304^c Aluminum, type 1100F

TABLE IIIB3

DILUTED Pu CYLINDERS, 6.0" DIAMETER, 4.5" THICK U($\sim$ 0.3) REFLECTORPu (w/o Ga), $\sim$ 5% Pu²⁴⁰, as discs 5.934" dia x 0.123", in thin Ni cans of outside dimensions 5.967" dia x 0.135"; ρ (Pu) = 15.51 g/cm³

Diluent plates 5.97" dia x 1/8" or 1/4"

Steel guide sleeve, 0.030" thick, within reflector cylinder; $\bar{\rho}$ (U) = 19.0

Reference (51)

diluent (A)	vol % Pu	repeated layers, nom thickness (in.)		core-average ρ (g/cm ³) ^a			h_c (in.)	h_c/d^a	m_c (kg Pu)	m_{max} (kg Pu)
		Pu	A	$\bar{\rho}$ (Pu)	$\bar{\rho}$ (A)	$\bar{\rho}$ (Ni)				
none	91.4	1/8	-	14.26	-	0.65	1.42	0.24	9.3	9.0
U(0.28)	61.8	1/4	1/8	9.65	5.88	0.44	2.40	0.40	10.6	9.0
steel ^b	60.6	1/4	1/8	9.46	2.48	0.44	2.59	0.43	11.2	10.6
Th	62.5	1/4	1/8	9.75	3.65	0.45	2.62	0.44	11.7	10.8
Al ^c	62.5	1/4	1/8	9.75	0.84	0.45	2.58	0.43	11.5 ₅	10.8
space	63.7	1/4	1/8	9.95	-	0.45	2.59	0.43	11.8	10.8
U(0.28)	47.5	1/8	1/8	7.42	9.08	0.34	3.72	0.62	12.6 ₅	12.55
steel ^b	47.5	1/8	1/8	7.42	3.81	0.34	4.26	0.71	14.5	14.35
Th	47.7	1/8	1/8	7.44	5.55	0.34	4.51	0.75	15.4	15.2
Al ^c	47.5	1/8	1/8	7.42	1.27	0.34	4.34	0.72	14.8	14.35
space	49.0	1/8	1/8	7.65	-	0.35	4.46	0.74	15.7	15.4
U(0.28)	32.4	1/8	1/4	5.06	12.28	0.23	7.99	1.33	18.5 ₅	18.0
steel ^b	32.3	1/8	1/4	5.04	5.14	0.23	10.97	1.83	25.3	24.3
Th	32.5	1/8	1/4	5.07	7.70	0.23	12.90	2.15	30.0	28.0
Al ^c	32.4	1/8	1/4	5.05	1.75	0.23	11.42	1.90	26.4	26.1
space	32.7	1/8	1/4	5.11	-	0.23	12.84	2.14	30.1	27.0

^a Based on 6.00" diameter to include reflector clearance^b Stainless steel, type 304^c Aluminum, type 1100F

TABLE IIIB4

DILUTED Pu CYLINDERS, 6.0" DIAMETER, 7.5" THICK U(~ 0.3) REFLECTORPu(1w/o Ga), $\sim 5\%$ Pu²⁴⁰, as discs 5.934" dia x 0.123", in thin Ni cans of outside dimensions 5.967" dia x 0.135"; ρ (Pu) = 15.61 g/cm³

Diluent plates 5.97" dia x 1/8" or 1/4"

Steel guide sleeve 0.030" thick, within reflector cylinder; $\bar{\rho}$ (U) = 19.0

Reference (51)

diluent (A)	vol % Pu	repeated layers, nom thickness (in.)		core-average ρ (g/cm ³) ^a			h_c (in.)	h_c/d^2	m_c (kg Pu)	m_{max} (kg Pu)
		Pu	A	$\bar{\rho}$ (Pu)	$\bar{\rho}$ (A)	$\bar{\rho}$ (Ni)				
none	91.2	1/8	-	14.23	-	0.65	1.37	0.23	8.9 ₅	8.0
U(0.28)	62.6	1/4	1/8	9.77	5.94	0.45	2.31	0.38 ₅	10.3 ₅	10.3
steel ^b	62.5	1/4	1/8	9.76	2.51	0.45	2.43	0.40 ₅	10.9	10.8
Th	62.5	1/4	1/8	9.76	3.63	0.45	2.49	0.41 ₅	11.1	10.8
Al ^c	62.5	1/4	1/8	9.76	0.84	0.45	2.47	0.41	11.0 ₅	10.8
space	63.5	1/4	1/8	9.92	-	0.45	2.47	0.41	11.2 ₅	10.8
U(0.28)	47.7	1/8	1/8	7.44	9.05	0.34	3.51	0.58 ₅	11.9 ₅	11.7
steel ^b	47.7	1/8	1/8	7.45	3.80	0.34	3.97	0.66 ₅	13.5 ₅	13.3
Th	48.1	1/8	1/8	7.51	5.57	0.34	4.14	0.69	14.2 ₅	14.2
Al ^c	48.0	1/8	1/8	7.50	1.28	0.34	3.98	0.66 ₅	13.7	13.5
space	48.8	1/8	1/8	7.62	-	0.35	4.18	0.70	14.6	14.4
U(0.28)	32.4	1/8	1/4	5.06	12.27	0.23	7.29	1.22	16.9	16.7
steel ^b	32.1	1/8	1/4	5.01	5.11	0.23	9.49	1.58	21.8	21.7
Th	32.5	1/8	1/4	5.07	7.49	0.23	10.83	1.80	25.1 ₅	25.0
Al ^c	32.4	1/8	1/4	5.05	1.75	0.23	9.65	1.61	22.3 ₅	22.3
space	32.8	1/8	1/4	5.12	-	0.23	10.58	1.76	24.8 ₅	24.4
U(0.28)	24.4	1/8	3/8	3.81	13.87	0.17	17.24	2.87	30.1	27.0

^a Based on 6.00" diameter to include reflector clearance^b Stainless steel, type 304^c Aluminum, type 1100F

TABLE III B5

DILUTED Pu CYLINDERS, 6.0" DIAMETER, 2.0" THICK Th REFLECTOR

Pu(1w/o Ga), ~5% Pu²⁴⁰, as discs 5.934" dia x 0.123", in thin Ni cans of outside dimensions 5.967" dia x 0.135"; ρ (Pu) = 15.61 g/cm³

Diluent plates 5.97" dia x 1/8" or 1/4"

Steel guide sleeve, 0.030" thick, within reflector cylinder; $\bar{\rho}$ (Th) = 11.9 g/cm³

Reference (51)

diluent (A)	vol % Pu	repeated layers, nom thickness (in.)		core-average ρ (g/cm ³) ^a			h_c (in.)	h_c/d^a	m_c (kg Pu)	m_{max} (kg Pu)
		Pu	A	$\bar{\rho}$ (Pu)	$\bar{\rho}$ (A)	$\bar{\rho}$ (Ni)				
none	91.3	1/8	-	14.25	-	0.65	2.25	0.37 ₅	14.7	14.5
U(0.28)	63.1	1/4	1/8	9.85	5.29	0.45	3.90	0.65	17.6	16.3
steel ^b	62.8	1/4	1/8	9.81	2.51	0.45	4.32	0.72	19.4	18.1
Th	62.8	1/4	1/8	9.81	3.63	0.45	4.44	0.74	20.0	18.1
Al ^c	62.8	1/4	1/8	9.81	0.84	0.45	4.46	0.74	20.0 ₅	18.1
space	64.0	1/4	1/8	9.99	-	0.45	4.80	0.80	22.0	19.9
U(0.28)	47.5	1/8	1/8	7.41	9.01	0.34	6.55	1.09	22.2 ₅	21.65
steel ^b	50.4	1/8	1/8	7.87	4.01	0.36	8.50	1.42	30.6	26.1
Th	47.9	1/8	1/8	7.48	5.54	0.34	9.78	1.63	33.5	26.1
Al ^c	48.1	1/8	1/8	7.51	1.29	0.34	10.15	1.69	34.9	26.1

^a Based on 6.00" diameter to include reflector clearance^b Stainless steel, type 304^c Aluminum, type 1100F

TABLE IIIB6

DILUTED Pu CYLINDERS, 6.0" DIAMETER, 4.5" THICK Th REFLECTOR

Pu(1w/o Ga), ~5% Pu²⁴⁰, as discs 5.934" dia x 0.123", in thin Ni cans of outside dimensions 5.967" dia x 0.135"; ρ (Pu) = 15.61 g/cm³

Diluent plates 5.97" dia x 1/8" or 1/4"

Steel guide sleeve, 0.030" thick, within reflector cylinder; $\bar{\rho}$ (Th) = 11.9 g/cm³

Reference (51)

diluent (A)	vol % Pu	repeated layers, nom thickness (in.)		core-average ρ (g/cm ³) ^a			h_c (in.)	h_c/d^a	m_c (kg Pu)	m_{max} (kg Pu)
		Pu	A	$\bar{\rho}$ (Pu)	$\bar{\rho}$ (A)	$\bar{\rho}$ (Ni)				
none	91.8	1/8	-	14.33	-	0.66	2.02	0.34	13.2 ₅	12.6
U(0.28)	62.5	1/4	1/8	9.75	5.94	0.45	3.42	0.57	15.3	14.4
steel ^b	63.1	1/4	1/8	9.85	2.52	0.45	3.74	0.62 ₅	16.9	16.2
Th	63.0	1/4	1/8	9.83	3.67	0.45	3.90	0.65	17.5 ₅	16.2
Al ^c	63.1	1/4	1/8	9.85	0.84	0.45	3.88	0.64 ₅	17.5	16.2
space	63.9	1/4	1/8	9.97	-	0.45	3.99	0.66 ₅	18.2	16.2
U(0.28)	47.7	1/8	1/8	7.45	9.06	0.34	5.52	0.92	18.9	18.0
steel ^b	47.3	1/8	1/8	7.39	3.77	0.34	6.85	1.14	23.5	22.5
Th	47.9	1/8	1/8	7.47	5.52	0.34	7.35	1.22 ₅	25.2	24.4
Al ^c	47.8	1/8	1/8	7.46	1.28	0.34	7.35	1.22 ₅	25.1 ₅	24.4
space	48.8	1/8	1/8	7.62	-	0.35	8.36	1.39	29.2	27.9

^a Based on 6.00" diameter to include reflector clearance

^b Stainless steel, type 304

^c Aluminum, type 1100F

TABLE IIIB7

DILUTED Pu CYLINDERS, 6.0" DIAMETER, 7.5" THICK Th REFLECTOR

Pu(1w/o Ga), ~5% Pu²⁴⁰, as discs 5.934" dia x 0.123", in thin Ni cans of outside dimensions 5.967" dia x 0.135"; ρ (Pu) = 15.61 g/cm³

Diluent plates 5.97" dia x 1/8" or 1/4"

Steel guide sleeve, 0.030" thick, within reflector cylinder; $\bar{\rho}$ (Th) = 11.9 g/cm³

Reference (51)

diluent (A)	vol % Pu	repeated layers, nom thickness (in.)		core-average ρ (g/cm ³) ^a			h_c (in.)	h_c/d^a	m_c (kg Pu)	m_{max} (kg Pu)
		Pu	A	$\bar{\rho}$ (Pu)	$\bar{\rho}$ (A)	$\bar{\rho}$ (Ni)				
none	92.9	1/8	-	14.50	-	0.66	1.92	0.32	12.7 ₅	11.8
U(0.28)	63.5	1/4	1/8	9.91	5.99	0.45	3.23	0.54	14.6 ₅	12.6
steel ^b	62.5	1/4	1/8	9.76	2.50	0.45	3.58	0.60	16.0	14.4
Th	62.9	1/4	1/8	9.82	3.63	0.45	3.69	0.61 ₅	16.6	16.2
Al ^c	63.7	1/4	1/8	9.95	0.85	0.45	3.61	0.60	16.4 ₅	16.2
space	63.7	1/4	1/8	9.95	-	0.45	3.80	0.63	17.3 ₅	16.2
U(0.28)	47.5	1/8	1/8	7.42	9.04	0.34	5.16	0.86	17.5 ₅	17.1
steel ^b	47.6	1/8	1/8	7.43	3.80	0.34	6.33	1.06	21.5 ₅	20.7
Th	47.7	1/8	1/8	7.45	5.52	0.34	6.78	1.13	23.2	22.5
Al ^c	48.6	1/8	1/8	7.59	1.30	0.35	6.55	1.09	22.8	21.6
space	49.0	1/8	1/8	7.65	-	0.35	7.34	1.22	25.7 ₅	25.2
U(0.28)	32.4	1/8	1/4	5.06	12.27	0.23	13.28	2.21	30.8	27.0

^a Based on 6.00" diameter to include reflector clearance

^b Stainless steel, type 304

^c Aluminum, type 1100F

TABLE IV

U-233 METAL SPHERES

Reflected cores consist of hemispheres coated with 0.005" thick Ni

ref	core				spheric reflector			m_c (kg U ²³³)	m_{max}
	composition			$\bar{\rho}$ (U) (g/cm ³)	material	$\bar{\rho}$ (g/cm ³)	thickness (in.)		
	w/o U ²³³	w/o U ²³⁴	w/o U ²³⁸						
(1)(55)	98.11	1.25	0.61	18.42		none		16.22 ± 0.06 ^a	critical
(52)(55)	98.11 ^b	1.25	0.61	18.42	U(N)	19.0	7.84	5.63 ± 0.03 ^c	critical
(48)	98.2	1.1	0.7	18.64	U(N)	18.92	2.09 ± 1%	7.47 ^d (3.622" dia)	> m_c^e
(48)	98.2	1.1	0.7	18.62	U(N)	18.92	0.906 ± 1%	9.84 ^d (3.972" dia)	> m_c^e
(48)	98.2	1.1	0.7	18.64	W-alloy ^f	17.21	2.28 ± 1%	7.47 ^d (3.622" dia)	> m_c^e
(48)	98.2	1.1	0.7	18.62	W-alloy ^f	17.21	0.960 ± 1%	9.84 ^d (3.972" dia)	> m_c^e
(48)	98.2	1.1	0.7	18.64	Be (98%)	1.83	1.652 ± 1%	7.47 ^d (3.622" dia)	> m_c^e
(48)	98.2	1.1	0.7	18.62	Be (98%)	1.83	0.805 ± 1%	9.84 ^d (3.972" dia)	> m_c^e

^a Corrected for effects of Ni coating, supports and small asphericity; 0.03 w/o U²³⁵^b Analysis available for one hemisphere only, 0.03 w/o U²³⁵^c Corrected for effects of Ni coating, oversize core and compensating gap between core and reflector^d Corrected for effects of Ni and clearances between assembly parts^e Effect of small compensating gap was adjusted to zero; reflector thickness modified^f Composition 91.3 w/o W, 5.5 w/o Ni, 2.5 w/o Cu, 0.7 w/o Zr

TABLE VA

Pu OR U-233 METAL SPHERES WITHIN U(93) METAL SPHERES

ref	central ball			U(93) shell, $\bar{\rho} = 18.8 \text{ g/cm}^3$		U(N) reflector sphere	m_c		$M_{\max}$
	composition	$\bar{\rho}$ (Pu, U) (g/cm ³)	diam (in.)	enrichment w/o U ²³⁵	critical thickness (in.)	$\bar{\rho} = 19.0 \text{ g/cm}^3$ thickness (in.)	kg Pu or U ²³³	kg U ²³⁵	
(48) (55)	Pu(1 w/o Ga), 4.9% Pu ²⁴⁰	15.62	3.970	93.2	0.655 ± 1%	none	8.386	12.73 ± 0.18 ^a	$m_{\max} > m_c^b$
(53)	Pu(1 w/o Ga), 1.5% Pu ²⁴⁰	15.56	3.510 0.42 i.d.	93.18	1.006	none	5.72	18.8 ± 0.3 ^a	65
(53) (57)	Pu(1 w/o Ga), 4.7% Pu ²⁴⁰	15.13	2.506	93.17	1.939	none	2.02 ₂	36.7 ± 0.1 ^a	130
(53) (57)	Pu(1 w/o Ga), 1.5% Pu ²⁴⁰	15.14	2.506	93.17	1.929	none	2.02 ₄	36.3 ₅ ± 0.1 ^a	118
(53) (57)	Pu (100%), 4.8% Pu ²⁴⁰	18.80	2.502	93.17	1.644	none	2.52 ₇	26.8 ± 0.1 ^c	233
(54)	Pu (100%), 2.34% Pu ²⁴⁰	19.48	2.130	93.2	0.974	7.45	1.615	8.87 ^d	critical
(54)	Pu (100%), 4.73% Pu ²⁴⁰	19.42	2.130	93.2	0.988	7.43	1.610	9.09 ^d	critical
(54)	Pu (100%), 16.1% Pu ²⁴⁰	19.43	2.130	93.2	1.039	7.38	1.611	9.90 ^d	$m_{\max} = 9.75 \text{ kg U}^{235}$
(48) (55)	U ²³³ (98.11 w/o) ^e	18.62	3.972	93.2	0.481 ± 1%	none	9.83	8.64 ± 0.11 ^a	$m_{\max} > m_c^b$
(48) (55)	U ²³³ (98.11 w/o) ^e	18.64	3.622	93.2	0.783 ± 1%	none	7.46	13.84 ± 0.19 ^a	$m_{\max} > m_c^b$
(53) (57)	U ²³³ (97.9 w/o) ^f	17.78	2.504	93.17	1.886	none	2.37 ₁	34.8 ± 0.1 ^a	138

^aCorrected for effects of 0.005" thick Ni on Pu or U²³³ hemispheres and for clearances between assembly parts^bEffect of small compensating gap was adjusted to zero; reflector thickness modified^cCorrected for effects of 0.005" thick Cu about Pu sphere and for clearances between assembly parts^dNo correction for 0.012" thick gap containing 0.010" thick Ni between Pu and U(93.2)^e1.25 w/o U²³⁴, 0.03 w/o U²³⁵, 0.61 w/o U²³⁸^f0.9 w/o U²³⁴, 0.2 w/o U²³⁸, 0.95 w/o W

TABLE VB

Pu METAL CYLINDER WITHIN U(93.2) METAL CYLINDER, THICK U(N) REFLECTOR

The Pu(lw/o Ga) contains ~6% Pu²⁴⁰; Pu pieces coated with 0.005" thick Ni

Dimensions of Pu and outside dimensions of U(93.2) are such that h/d values are the same

Cores are approximately centered in a U(N) cylinder, 18.0" dia x 10", of density 19.0 g/cm³

Reference (53)

h_c/d (Pu and U ²³⁵)	Pu cavity dimensions (in.)	$\bar{\rho}$ (Pu) (g/cm ³)	$\bar{\rho}$ (U-93.2) (g/cm ³)	m_c^a		m_{max}
				kg Pu	kg U ²³⁵	
0.20	4.315 dia x 0.875	14.98	18.66	3.14 (fixed)	13.0 $\pm$ 0.2	11.9 kg U ²³⁵
0.30	4.315 dia x 1.290	15.29	18.30	4.73 (fixed)	5.3 $\pm$ 0.2	4.2 kg U ²³⁵
1.00	2.235 dia x 2.231	14.83	18.58	2.13 (fixed)	9.7 $\pm$ 0.2	8.2 kg U ²³⁵
0.44	4.315 dia cyl	15.34	none	6.91 $\pm$ 0.04	-	6.47 kg Pu

^a No correction for effect of Ni or 0.06 in.³ central source cavity

REFERENCES

- (1) G. E. Hansen, Status of Computational and Experimental Correlations for Los Alamos Fast-Neutron Critical Assemblies, Physics of Fast and Intermediate Reactors, IAEA, Vienna (1962).
- (2) G. E. Hansen and D. P. Wood, Precision Critical-Mass Determinations for Oralloy and Plutonium in Spherical Tuballoy Tampers, LA-1356 Revised (to be issued).
- (3) J. D. Orndoff and H. C. Paxton, Measurements on Untamped Oralloy Assembly, LA-1209 (February 1951).
- (4) V. Josephson, R. W. Paine, Jr. and L. L. Woodward, Oralloy Shape Factor Measurements, LA-1155 (August 1950).
- (5) G. E. Hansen, D. P. Wood and B. Peña, Reflector Savings of Moderating Materials on Large Diameter U(93.2%) Slabs, LAMS-2744 (June 1962).
- (6) H. C. Paxton, Bare Critical Assemblies of Oralloy at Intermediate Concentrations of U-235, LA-1671 (May 1954).
- (7) Private communication, D. M. Barton (September 1958).
- (8) V. Josephson, Critical Mass Measurements on Oy in Tu and WC Tampers, LA-1114 deleted (May 1950).
- (9) J. D. Orndoff, H. C. Paxton and G. E. Hansen, Critical Masses of Oralloy at Reduced Concentrations and Densities, LA-1251 (May 1951).
- (10) Private communication, C. P. Baker (December 1947).
- (11) G. E. Hansen, H. C. Paxton and D. P. Wood, Critical Masses of Oralloy in Thin Reflectors, LA-2203 (July 1958).

REFERENCES (Continued)

- (12) G. E. Hansen, H. C. Paxton and D. P. Wood, Critical Plutonium and Enriched-Uranium-Metal Cylinders of Extreme Shape, Nuclear Sci. and Eng. 8, 570-577 (1960).
- (13) J. J. Neuer, Critical Assembly of Uranium Metal at an Average U²³⁵ Concentration of 16-1/4%, LA-2085 (January 1957).
- (14) Private communication, J. J. Neuer, G. A. Newby, H. C. Paxton and T. F. Wimett (March 1954).
- (15) Private communication, H. C. Paxton and C. B. Stewart (May 1953).
- (16) Private communication, D. P. Wood, L. C. Osborn and B. Peña (April 1960).
- (17) Private communication, V. Josephson and R. W. Paine, Jr. (March 1951).
- (18) Private communication, J. C. Hoogterp and D. P. Wood (September 1955).
- (19) D. P. Wood and B. Peña, Critical Mass Measurements of Oy and Pu Cores in Spherical Aluminum Reflectors, LAMS-2579 (June 1961).
- (20) E. C. Mallary, Oralloy Cylindrical Shape Factor and Critical Mass Measurements in Graphite, Paraffin, and Water Tampers, LA-1305 (October 1951).
- (21) J. C. Hoogterp, Critical Masses of Graphite-Tamped Heterogeneous Oy-Graphite Systems, LA-1732 (May 1954).
- (22) Private communication, G. A. Jarvis (November 1961).
- (23) Private communication, D. P. Wood (October 1961).
- (24) Private communication, F. F. Hart and C. B. Stewart (December 1953).
- (25) Private communication, R. W. Paine, Jr., D. P. Wood and R. S. Dike (April 1951).

REFERENCES (Continued)

- (26) F. F. Hart, Safety Tests for Melting and Casting Oralloy, LA-1623 (December 1953).
- (27) Private communication, K. Gallup, G. E. Hansen (July 1951).
- (28) Private communication, R. E. Schreiber (September 1951).
- (29) Private communication, E. C. Mallary (March 1952).
- (30) Private communication, J. J. Neuer, H. C. Paxton, R. H. White and T. F. Wimett (March 1954).
- (31) Private communication, G. A. Jarvis (June 1963).
- (32) H. Iskenderian and C. C. Byers, Physics Calculations on Four Los Alamos Graphite Moderated Critical Assemblies, Trans. ANS 1, No. 1, p. 149 (June 1958); also private communication, C. C. Byers (September 1957).
- (33) G. E. Hansen, J. C. Hoogterp, J. D. Orndoff and H. C. Paxton, Beryllium-Reflected, Graphite-Moderated Critical Assemblies, LA-2141 (October 1957).
- (34) Private communication, S. J. Balestrini (November 1963).
- (35) Private communication, C. C. Byers (March 1962).
- (36) Private communication, G. A. Jarvis and C. C. Byers (October 1961).
- (37) R. N. Olcott, Homogeneous Heavy Water Moderated Critical Assemblies, Part 1, Experimental, Nuclear Sci. and Eng. 1, 327-341 (1956).
- (38) G. E. Hansen and W. H. Roach, Interpretation of Neutron Resonance Detector Activities in Critical Uranyl Fluoride - Heavy Water Solutions, Proc. Brookhaven Conf. on Resonance Absorption of Neutrons in Nuclear Reactors, Upton, New York, BNL 433 (C-24), pp. 13-25 (September 1956); also private communication, C. C. Byers (January 1956).

REFERENCES (Continued)

- (39) Los Alamos Scientific Laboratory of the University of California, An Enriched Homogeneous Nuclear Reactor, RSI 22, 489-499 (July 1951); also L. D. P. King, Water Boilers, LA-1034 (December 1947).
- (40) R. E. Carter and J. C. Hinton, Water Tamper Measurements, LA-241 (March 1945).
- (41) J. C. Allred, P. J. Bendt and R. E. Peterson, Critical Measurements on $\text{UO}_3\text{-H}_3\text{PO}_4$ Solutions, Nuclear Sci. and Eng. 4, 498-500 (1958).
- (42) Private communication, J. C. Allred, P. J. Bendt, H. C. Paxton and R. E. Peterson (April 1953).
- (43) G. A. Linenberger, J. D. Orndoff and H. C. Paxton, Enriched-Uranium Hydride Critical Assemblies, Nuclear Sci. and Eng. 7, 44-57 (1960).
- (44) Private communication, M. G. Holloway and C. P. Baker (December 1947).
- (45) H. C. Paxton and G. A. Linenberger, Polythene-25 Critical Assembly and Neutron Distribution Studies, LA-749 (September 1949).
- (46) J. C. Hoogterp, Critical Masses of Oralloy Lattices Immersed in Water, LA-2026 (November 1955).
- (47) G. A. Jarvis, G. A. Linenberger, J. D. Orndoff and H. C. Paxton, Two Plutonium-Metal Critical Assemblies, Nuclear Sci. and Eng. 8, 525-531 (1960).
- (48) E. A. Plassmann and D. P. Wood, Critical Reflector Thicknesses for Spherical U^{233} and Pu^{239} Systems, Nuclear Sci. and Eng. 8, 615-620 (1960).
- (49) Private communication, D. P. Wood and C. C. Byers (December 1960).
- (50) Private communication, H. C. Paxton (October 1951).
- (51) D. P. Wood, C. C. Byers and L. C. Osborn, Critical Masses of Plutonium Diluted with Other Metals, Nuclear Sci. and Eng. 8, 578-587 (1960).

REFERENCES (Continued)

- (52) Private communication, G. E. Hansen (October 1963).
- (53) Private communication, H. C. Paxton, G. E. Hansen, D. P. Wood and E. A. Plassmann (May 1960).
- (54) D. M. Barton, W. Bernard and G. E. Hansen, Critical Masses of Composites of Oy and Pu-239-240 in Flat-top Geometry, LAMS-2489 (December 1960).
- (55) G. E. Hansen and H. C. Paxton, Reevaluated Critical Specifications of Some Los Alamos Fast-Neutron Systems, LA-4208 (September 1969).
- (56) L. J. Sapir, H. H. Helmick and J. D. Orndoff, BIG TEN, a 10% Enriched Uranium Critical Assembly: Kinetic Studies, ANS Trans., 15, No. 1, 312 (June 1972); also private communication, G. E. Hansen and H. C. Paxton (December 1974).
- (57) Private communication, G. E. Hansen (November 1966).
- (58) J. C. Hoogterp, G. E. Hansen and H. C. Paxton, Bare U(93)C₁₇₀ Assembly, LA-4798-MS (May 1974).
- (59) G. A. Jarvis and C. B. Mills, Critical Mass Reduction, LA-3651 (March 1967).
- (60) H. C. Paxton, G. A. Jarvis and C. C. Byers, Reflector-Moderated Critical Assemblies, LA-5963 (July 1975).
- (61) Private communication; E. A. Plassmann (October 1975).