Screening of Processing and Upgrading Schemes Task 3

Topical Report

October 1991

Work Performed Under Contract No.: DE-AC21-88MC25020

For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
Morgantown, West Virginia

Reproduced by OSTI

NOV 02 1992

By
Lummus Crest, Inc.
Bloomfield, New Jersey

MASTER

RP

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

**Screening of Processing and Upgrading Schemes
Task 3**

Topical Report

Work Performed Under Contract No.: DE-AC21-88MC25020

**For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P.O. Box 880
Morgantown, West Virginia 26507-0880**

**By
Lummus Crest, Inc.
1515 Broad Street
Bloomfield, New Jersey 07003**

October 1991

TABLE OF CONTENTS

	<u>Page No.</u>
List of Tables	iv
List of Figures	ix
 1.0 <u>EXECUTIVE SUMMARY</u>	 1
1.1 Background & DOE Perspective	1
1.2 Contract Objectives	2
1.3 Task Breakdown Structure	2
1.4 Feedstocks	6
1.5 High Energy Density Fuels (HEDF)	6
1.6 Process Screening Alternatives	8
1.7 Experimental Procedures	9
1.8 Summary of Results of COALITE Operations	9
1.9 Summary of Results of Colorado Shale Oil Operations	13
 2.0 <u>EXPERIMENTAL PROCEDURES</u>	 18
2.1 Overview	18
2.2 Bench-Scale Fixed-Bed Hydrotreating Unit	18
2.3 Bench-Scale Fixed-Bed Hydrocracking Unit	21
2.4 Bench-Scale LC-Fining Unit	23
2.5 Continuous Bench Coking Unit	26
2.6 Laboratory Extraction Unit	28
2.7 4-in Batch Fractionation Unit	28
2.8 Equilibrium Flash Vaporization Pilot Unit	28
2.9 Laboratory Batch Distillation Units	28
2.10 Laboratory Clay Treating Unit	30
2.11 Calculation Procedures and Analytical Methods	30

TABLE OF CONTENTS

	<u>Page No</u>
3.0 <u>FEEDSTOCK ANALYSES</u>	35
3.1 COALITE Feedstock	35
3.2 Colorado Shale Oil Feedstock	43
4.0 <u>SCREENING PROGRAM OPERATING CHRONOLOGY</u>	73
4.1 Overview	73
4.2 COALITE Operations	73
4.2.1 Feedstock Preparation	73
4.2.2 Virgin Distillate Hydrotreating Campaigns	74
4.2.3 Virgin Atmospheric Resid Cracking Campaigns	76
4.2.3.1 LC-Fining (Hydrocracking)	86
4.2.3.2 Delayed Coking	86
4.2.4 Cracked Distillate Hydrotreating Campaigns	86
4.2.4.1 Hydrotreating of LC-Finate Distillates	86
4.2.4.2 Hydrotreating of Coker Distillates	86
4.2.5 Two-Step Selective Hydrocracking Campaigns	86
4.3 Colorado Shale Oil Operations	104
4.3.1 Feedstock Preparation	104
4.3.2 Virgin Distillate Hydrotreating Campaigns	104
4.3.3 Virgin Atmospheric Resid Cracking Campaigns	111
4.3.3.1 LC-Fining (Hydrocracking)	111
4.3.3.2 Delayed Coking	111
4.3.4 Cracked Distillate Hydrotreating Campaigns	111
4.3.4.1 Hydrotreating of LC-Finate Distillates	116
4.3.4.2 Hydrotreating of Coker Distillates	116
4.3.5 Two-Step Selective Hydrocracking Campaigns	116
4.3.6 Extraction Studies	127

TABLE OF CONTENTS

	<u>Page No</u>
5.0 <u>SUMMARY OF RESULTS OF COALITE OPERATIONS</u>	130
5.1 Overview	130
5.2 Virgin Distillate Hydrotreating	131
5.3 Virgin Atmospheric Resid Cracking	173
5.3.1 LC-Fining	173
5.3.2 Delayed Coking	173
5.4 Cracked Distillate Hydrotreating	179
5.4.1 Hydrotreating of LC-Finate Distillates	179
5.4.2 Hydrotreating of Coker Distillates	179
5.5 Two-Step Selective Hydrocracking of Vacuum Gas Oil (VGO)	179
5.5.1 Overview of Early Results	179
5.5.2 Subtask 3.1/3.2 Scope	195
5.5.3 Subtask 3.1/3.2 Results	197
5.5.3.1 LC-Fining Studies	199
5.5.3.2 Fixed-Bed HDN Studies	200
5.5.3.3 Fixed-Bed Selective Hydrocracking Studies	200
5.5.3.4 Hydrotreating Studies	208
5.5.3.5 HEDF Finishing	208
6.0 <u>SUMMARY OF RESULTS OF COLORADO SHALE OIL OPERATIONS</u>	214
6.1 Overview	214
6.2 Virgin Distillate Hydrotreating	214
6.3 Virgin Atmospheric Resid Cracking	245
6.4 Cracked Distillate Hydrotreating	245
6.5 Two-Step Selective Hydrocracking of Vacuum Gas Oil (VGO)	245
6.6 Extraction Studies	254
7.0 <u>REFERENCES</u>	259
8.0 <u>ACKNOWLEDGEMENTS</u>	260

LIST OF TABLES

<u>Table No.</u>	<u>Title</u>	<u>Page #</u>
1.8-1	Task 3 Screening Program Results	14
2.11-1	Formulas for Selected Hydroprocessing Parameters	32
3.1-1	Analyses of Narrow-Boiling COALITE Distillates	38
3.1-2	G.C./M.S. Analysis of 200-550F COALITE	40
3.1-3	NMR Spectroscopy of 390-650F COALITE	50
3.2-1	Analyses of Narrow-Boiling Colorado Shale Oil Distillates	63
4.2.1-1	Hydrotreating Feedstock Analyses of Raw COALITE Mid-Distillate	75
4.2.2-1	Summary of Operating Conditions for Fixed-Bed COALITE Hydrotreating Tests(FB17A1-49)	77
4.2.2-2	Summary of Operating Conditions for Fixed-Bed COALITE Hydrotreating Tests(FB30-36)	81
4.2.2-3	Summary of Operating Conditions for Fixed-Bed COALITE Hydrotreating Tests(FB169-177)	82
4.2.2-4	Summary of Operating Conditions for Fixed-Bed COALITE Hydrotreating Tests(FB94-104)	83
4.2.2-5	Summary of Operating Conditions for Fixed-Bed COALITE Hydrotreating Tests(FB146-147)	84
4.2.2-6	Summary of Operating Conditions for Fixed-Bed COALITE Hydrotreating Tests(FB135-138)	85
4.2.3.1-1	Feedstock Assays for LC-Fining of COALITE Residua	87
4.2.3.1-2	Summary of Operating Conditions for LC-Fining Tests (BLCF86-101)	88
4.2.3.1-3	Summary of Operating Conditions for LC-Fining Tests (BLCF90-95)	89
4.2.3.2-1	Assays of Delayed Coking COALITE Feedstocks	90
4.2.3.2-2	Summary of Operating Conditions for Delayed Coking of COALITE	91
4.2.4.1-1	Assays of COALITE Mid-distillate LC-Finate Feeds to Hydrotreating	93
4.2.4.1-2	Summary of Operating Conditions for Fixed-Bed Hydrotreating of Hydrocracked COALITE Distillate (FB44-105)	94
4.2.4.1-3	Summary of Operating Conditions for Fixed-Bed Hydrotreating of Hydrocracked COALITE Distillate (FB156-158)	95
4.2.4.2-1	Assays of COALITE Coker Mid-distillate Feeds to Hydrotreating	96
4.2.4.2-2	Summary of Operating Conditions for Fixed-Bed Hydrotreating of Thermally Processed COALITE Distillate (FB45-127)	97
4.2.5-1	Assays of COALITE VGO Feedstocks To Fixed- Bed Hydrocracking	99
4.2.5-2	Summary of Operating Conditions for Fixed-Bed Hydrocracking of COALITE(FBHC1-17)	100
4.2.5.-3	Summary of Operating Conditions for Fixed-Bed Hydrocracking of COALITE(FBHC18-27)	101
4.2.5-4	Assays of Selectively Hydrocracked COALITE Mid- Distillate Feed to Hydrotreating	102

LIST OF TABLES

<u>Table No.</u>	<u>Title</u>	<u>Page #</u>
4.3.1-1	Assay of Raw Colorado Shale Oil Mid-Distillate Feedstock to Hydrotreating	105
4.3.2-1	Summary of Operating Conditions for Fixed-Bed Colorado Shale Oil Hydrotreating (FB106-130)	106
4.3.2-2	Summary of Operating Conditions for Fixed-Bed Colorado Shale Oil Hydrotreating (FB148-155)	109
4.3.2-3	Summary of Operating Conditions for Fixed-Bed Colorado Shale Oil Hydrotreating (FB159-164)	110
4.3.3.1-1	Summary of Operating Conditions for LC-Fining of Colorado Shale Oil (BLCF89-1/89-5)	112
4.3.3.1-2	Summary of Operating Conditions for LC-Fining of Colorado Shale Oil (BLCF91-99)	113
4.3.3.2-1	Assay of Delayed Coking Colorado Shale Oil-Derived Feedstock	114
4.3.3.2-2	Summary of Operating Conditions for Delayed Coking of Colorado Shale Oil (CBC65-66)	115
4.3.4.1-1	Assay of Colorado Shale Oil LC-Finate Mid-Distillate to Hydrotreating	117
4.3.4.1-2	Summary of Operating Conditions for Fixed-Bed Hydrotreating of Hydroprocessed Colorado Shale Oil Distillate (FB143-145)	118
4.3.4.2-1	Assay of Colorado Shale Oil Delayed Coker Mid-Distillate to Hydrotreating	119
4.3.4.2-2	Summary of Operating Conditions for Fixed-Bed Hydrotreating of Thermally Processed Colorado Shale Oil Distillate (FB131-134)	120
4.3.5-1	Assay of Colorado Shale Oil VGO Feedstocks To Fixed-Bed Hydrocracking	122
4.3.5-2	Summary of Operating Conditions for Fixed-Bed Colorado Shale Oil Hydrocracking(FBHC5-12)	123
4.3.5-3	Summary of Operating Conditions for Fixed-Bed Colorado Shale Oil Hydrocracking(FBHC28-35)	124
4.3.5-4	Summary of Operating Conditions for Fixed-Bed Hydrotreating of Hydroprocessed Colorado Shale Oil Distillate (FB186-187)	125
4.3.5-5	Summary of Operating Conditions for Fixed-Bed Hydrotreating of Hydrocracked Colorado Shale Oil Distillate (FB188-189)	126
4.3.6-1	Results of Extraction of Hydrotreated Colorado Shale Oils	129
5.2.1-1	Key Specifications for Military Turbine Fuels	133
5.2.1-2	Assays of Distillate Hydrotreating Catalysts	135
5.2.1-3A	Summary of Operating Results for Fixed-Bed COALITE Hydrotreating (FB17A1-49)	137
5.2.1-3B	Summary of Properties of Full-Range Hydrotreated COALITE From Fixed-Bed Hydrotreating (FB17A1-49)	141
5.2.1-4A	Summary of Operating Results for Fixed-Bed COALITE Hydrotreating (FB30/36-2)	145
5.2.1-4B	Summary of Properties of Full-Range Hydrotreated COALITE From Fixed-Bed Hydrotreating (FB30/36-2)	146

LIST OF TABLES

<u>Table No.</u>	<u>Title</u>	<u>Page #</u>
5.2.1-5A	Summary of Operating Results for Fixed-Bed COALITE Hydrotreating (FB169-177)	147
5.2.1-5B	Summary of Properties of Full-Range Hydrotreated COALITE From Fixed-Bed Hydrotreating (FB169-77)	148
5.2.1-6A	Summary of Operating Results for Fixed-Bed COALITE Hydrotreating (FB94-104)	149
5.2.1-6B	Summary of Properties of Full-Range Hydrotreated COALITE From Fixed-Bed Hydrotreating (FB94-104)	150
5.2.1-7A	Summary of Operating Results for Fixed-Bed COALITE Hydrotreating (FB146-47)	151
5.2.1-7B	Summary of Properties of Full-Range Hydrotreated COALITE From Fixed-Bed Hydrotreating (FB146-47)	152
5.2.1-8A	Summary of Operating Results for Fixed-Bed COALITE Hydrotreating (FB135-38)	153
5.2.1-8B	Summary of Properties of Full-Range Hydrotreated COALITE From Fixed-Bed Hydrotreating (FB135-38)	154
5.3.1-1	Summary of Operating Conditions for LC-Fining of COALITE (BLCF86-1/90)	175
5.3.1-2	Summary of Operating Conditions for LC-Fining of COALITE (BLCF92-101)	176
5.3.1-3	Summary of Properties of Full-Range LC-Finates COALITE (BLCF86-90)	177
5.3.1-4	Summary of Properties of Full-Range LC-Finates COALITE (BLCF92-101)	178
5.4.1-1A	Summary of Operating Results for Fixed-Bed Hydrotreating of Hydrocracked COALITE Distillate (FB44-105)	180
5.4.1-1B	Summary of Properties of Full-Range Hydrotreated COALITE From Fixed-Bed Hydrocracking (FB44-105)	181
5.4.1-2A	Summary of Operating Results for Fixed-Bed Hydrotreating of Hydrocracked COALITE Distillate (FB156-158)	182
5.4.1-2B	Summary of Properties of Full-Range Hydrotreated COALITE From Fixed-Bed Hydrocracking (FB156-58)	183
5.4.1-3A	Summary of Operating Results for Fixed-Bed Hydrocracking of COALITE (FBHC1-17)	184
5.4.1-3B	Summary of Properties of Hydrocrackates From Fixed-Bed COALITE Hydrocracking (FBHC1-17)	185
5.4.1-4A	Summary of Operating Results for Fixed-Bed Hydrocracking of COALITE (FBHC18-27)	186
5.4.1-4B	Summary of Properties of Hydrocrackates From Fixed-Bed COALITE Hydrocracking (FBHC18-27)	187
5.4.1-5A	Summary of Operating Results for Fixed-Bed Hydrotreating of Hydrocracked COALITE Distillate (FB165-168)	188
5.4.1-5B	Summary of Properties of Full-Range Hydrotreated COALITE From Fixed-Bed Hydrocracking (FB165-68)	189
5.4.2-1A	Summary of Operating Results for Fixed-Bed Hydrotreating of Thermally Processed COALITE (FB45/126/127)	190

LIST OF TABLES

<u>Table No.</u>	<u>Title</u>	<u>Page #</u>
5.4.2-1B	Summary of Properties of Full-Range Hydrotreated COALITE From Delayed Coking(FB45/126-7)	191
5.5-1	Comparison of COALITE-Derived HEDF Fuels Produced Via Two Hydroprocessing Schemes	194
5.5.3.1-1	Summary Results for LC-Fining Run 6LCF-11	201
5.5.3.2-1	Results of Fixed-Bed Hydrotreating of 975F-COALITE LC-Finate	202
5.5.3.3-1	Summary of Fixed-Bed Hydrocracking Run FBHC-37	205
5.5.3.3-2	Summary of Fixed-Bed Hydrocracking Run FBHC-38	206
5.5.3.3-3	Summary of Fixed-Bed Hydrocracking Run FBHC-39	207
5.5.3.3-4	Summary of Fixed-Bed Hydrocracking Run FBHC-40	209
5.5.3.3-5	Comparison of Run FBHC-40F with FBHC-41	210
5.5.3.4-1	Summary of Fixed-Bed Hydrotreating Run FB-214	211
5.5.3.5-1	COALITE Derived HEDF Fuel Properties for Subtask 3.2 Screening Program	212
6.2-1A	Summary of Operating Results for Fixed-Bed Colorado Shale Oil Hydrotreating(FB148-64)	215
6.2-1B	Summary of Properties of Full-Range Hydrotreated Colorado Shale Oil From Fixed-Bed Hydrotreating (FB148-164)	217
6.2-2A	Summary of Operating Results for Fixed-Bed Colorado Shale Oil Hydrotreating(FB106-130)	219
6.2-2B	Summary of Properties of Full-Range Hydrotreated Colorado Shale Oil From Fixed-Bed Hydrotreating (FB106-130)	222
6.2-3A	Summary of Operating Results for Fixed-Bed Hydrotreating of Hydroprocessed Colorado Shale Oil Distillate(FB186-87)	225
6.2-3B	Summary of Properties of Fixed-Bed Hydrotreated Products from Hydroprocessed Colorado Shale Oil Distillate(FB186-87)	226
6.2-4A	Summary of Operating Results of Fixed-Bed Hydrotreated Products from Hydroprocessed Colorado Shale Oil Distillate(FB143-45)	227
6.2-4B	Summary of Properties of Fixed-Bed Hydrotreated Products from Hydroprocessed Colorado Shale Oil Distillate(FB143-145)	228
6.2-5A	Summary of Operating Results for Fixed-Bed Colorado Shale Oil Hydrocracking(FBHC28-35)	229
6.2-5B	Summary of Properties of Hydrocrackates from Fixed-Bed Colorado Shale Oil Hydrocracking(FBHC28-35)	230
6.2-6A	Summary of Operating Results for Fixed-Bed Colorado Shale Oil Hydrocracking(FBHC5-12)	231
6.2-6B	Summary of Properties of Hydrocrackates from Fixed-Bed Colorado Shale Oil Hydrocracking(FBHC5-12)	232
6.3-1A	Summary of Operating Results for LC-Fining of Colorado Shale Oil (BLCF89-1/89-5)	246
6.3-1B	Summary of Properties of LC-Finates from Colorado Shale Oil(BLCF89-1/89-5)	247

LIST OF TABLES

<u>Table No.</u>	<u>Title</u>	<u>Page #</u>
6.3-2A	Summary of Operating Results for LC-Fining of Colorado Shale Oil (BLCF91-99)	248
6.3-2B	Summary of Properties of LC-Finates from Colorado Shale Oil(BLCF91-99)	249
6.3-3A	Summary of Operating Results for Fixed-Bed Hydrotreating of Thermally Processed Colorado Shale Oil Distillate(FB131-134)	250
6.3-3B	Summary of Properties of Hydrotreated Products from Fixed-Bed Hydrotreating of Thermally Processed Colorado Shale Oil Distillates(FB131-34)	251
6.4-1A	Summary of Operating Results for Fixed-Bed Hydrotreating of Hydrocracked Colorado Shale Oil Distillate(FB188-189)	252
6.4-1B	Summary of Properties of Fixed-Bed Hydrotreated Products from Hydrocracked Colorado Shale Oil Distillate(FB188-189)	253
6.6-1	Results of Solvent Extraction of Hydrotreated Colorado Shale Oils	257
6.6-2	Lab Extraction Study Results	258

LIST OF FIGURES

<u>Figure No.</u>	<u>Title</u>	<u>Page #</u>
1.8-1	Effect of H Content & API Gravity on Energy Density	15
2.2-1	Schematic Flow Diagram of Fixed-Bed Hydroprocessing Pilot Unit	19
2.3-1	Schematic of Bench-Scale Fixed-Bed Hydrocracking Unit	22
2.4-1	Schematic of Autoclave-Based LC-Fining Unit	24
2.5-1	Schematic of Continuous Bench Coking Unit	27
2.7-1	Schematic of Four-in Batch Fractionation Unit	29
3.1-1	Consolidated ASTM D86/D1160 Distillations of Dewatered COALITE	36
3.1-2	ASTM Distillations of Synfuel Feedstocks	37
3.1-3	Wt% Distillate Yield As a Function of VABP of Cut	39
3.1-4	H/C Atomic Ratio of COALITE Distillate Cuts As A Function of VABP of Cut	44
3.1-5	API Gravity of COALITE Distillates As A Function of VABP of Cut	45
3.1-6	Nitrogen Content As A Function of VABP Of Cut	46
3.1-7	Wt% Oxygen Content As A Function of VABP Of Cut	47
3.1-8	Wt% Sulfur Content As A Function of VABP Of Cut	48
3.1-9	PONA Analysis of Selected COALITE Distillates As A Function of VABP Of Cut	49
3.1-10	Hydrogen Distribution by HNMR Spectroscopy As A Function of VABP Of Cut	51
3.1-11	Calculated Carbon Distributions From HNMR As A Function of VABP Of Cut	52
3.1-12	H/C Ratios From HNMR Spectroscopy As A Function of VABP Of Cut	53
3.1-13	Bromine No As A Function of VABP Of Cut	54
3.1-14	Refractive Index @20C As A Function of VABP Of Cut	55
3.1-15	API Gravity As A Function of Refractive Index	56
3.1-16	H/C Atomic Ratio As A Function of Refractive Index	57
3.1-17	Hydrogen Aromaticity As A Function of Refractive Index of Distillate Cuts	58
3.1-18	Carbon Aromaticity As A Function of Refractive Index of Distillate Cuts	59
3.2-1	Consolidated ASTM Distillation of Raw Colorado Shale Oil Feedstock	61
3.2-2	ASTM Distillations of Synfuel Feedstocks	62
3.2-3	H/C Atomic Ratio of Synfuel Distillates As a Function of VABP	64
3.2-4	API Gravity of Synfuel Distillates As a Function of VABP	65
3.2-5	Nitrogen Content of Synfuel Distillates As a Function of VABP	66
3.2-6	Wt% Sulfur of Synfuel Distillates as a Function of VABP	67
3.2-7	PONA Analysis of Synfuel Distillates as a Function of VABP	68
3.2-8	NMR Carbon Distribution for COALITE and Colorado Shale Oil as a Function of Distillate VABP	69
3.2-9	Refractive Index of Synfuel Distillates as a Function of VABP	70

LIST OF FIGURES

<u>Figure No.</u>	<u>Title</u>	<u>Page #</u>
3.2-10	NMR Carbon Distribution for COALITE & Colorado Shale Oil as a Function of Refractive Index	71
4.2.5-1	Hydrocracking/Hydrogenation Routes To HEDF	98
4.3.5-1	Processing Approaches to Colorado Shale Oil HEDF	121
5.2.1-1	Volumetric Heat Content vs Hydrogen Content of Model Compounds	134
5.2.1-2	Hydrotreating Severity vs VHLV for Hydrotreated COALITE Distillates	155
5.2.1-3	Hydrotreating Severity vs Hydrogen Content For COALITE Distillates Over K-550	156
5.2.1-4	Hydrotreating Severity vs FIA Aromatics For COALITE Distillates Over K-550	157
5.2.1-5	Hydrotreating Severity vs API Gravity For COALITE Distillates Over K-550	158
5.2.1-6	Hydrotreating Severity vs Aniline Pt For COALITE Distillates Over K-550	159
5.2.1-7	Hydrotreating Severity vs Cetane Index For COALITE Distillates Over K-550	160
5.2.1-8	Hydrotreating Severity vs Smoke Pt For COALITE Distillates Over K-550	161
5.2.1-9	Hydrotreating Severity vs Refractive Index For COALITE Distillates Over K-550	162
5.2.1-10	Effect of Aromatics on VLHV of Coal-Derived Diesel/Jet Fuels	163
5.2.1-11	Effect of Aromatics on Cetane Quality of Coal-Derived Diesel Fuels	164
5.2.1-12	Effect of Aromatics on Smoke Point of Coal-Derived Turbine Fuels	165
5.2.1-13	Predicted Net Heat of Combustion of COALITE vs R.I. and API Gravity	166
5.2.1-14	Distillate Hydrogen Content as a Function of R.I. of COALITE Distillates	167
5.2.1-15	Predicted API Gravity as a Function of R.I. of Hydrotreated COALITE	168
5.2.1-16	Watson K Factor As a Function of R.I. of Hydrotreated COALITE	169
5.2.1-17	Smoke Pt and Luminometer No vs R.I. of COALITE	170
5.2.4-1	Relative Hydroprocessing Performance for 350-550F COALITE: Sp. Gr Reduction	171
5.2.4-2	Relative Hydroprocessing Performance for 350-550F COALITE: Aromatics Conversion	172
5.2.4-3	Relative Hydroprocessing Performance for 350-550F COALITE: Hydrogen Uptake	174
6.2-1	Hydrotreating Severity vs VHLV for COALITE & Shale Derived Jet Fuels	233
6.2-2	Hydrotreating Severity vs FIA Aromatics for Coal & Shale Derived Jet Fuels	234
6.2-3	Hydrotreating Severity vs Hydrogen Content for Coal & Shale Derived Jet Fuels	235
6.2-4	Hydrotreating Severity vs API Gravity for Coal & Shale Derived Jet Fuels	236

LIST OF FIGURES

<u>Figure No.</u>	<u>Title</u>	<u>Page #</u>
6.2-5	Hydrotreating Severity vs Smoke Pt for Coal & Shale Derived Jet Fuels	237
6.2-6	Hydrotreating Severity vs Refractive Index for Coal & Shale Derived Jet Fuels	238
6.2-7	Effect of Aromatics on VLHV of Coal & Shale Derived Jet Fuels	239
6.2-8	Effect of Aromatics on Smoke Pt of Coal & Shale Derived Jet Fuels	240
6.2-9	API Gravity vs Refractive Index of Coal & Shale Derived Distillates	241
6.2-10	Smoke Pt vs Refractive Index of Coal & Shale Derived Jet Fuels	242
6.2-11	Distillate Hydrogen Content vs Refractive Index of Coal & Shale Derived Jet Fuels	243
6.6-1	Extraction/Hydrogenation Route to HEDF From Colorado Shale Oil	255

1.0 EXECUTIVE SUMMARY

1.1 Background and DOE Perspective

In April 1988, the Department of Energy (DOE) Morgantown Energy Technology Center (METC) issued a request for proposal (RFP) soliciting a research effort for the "Development of High Energy Density Fuels from Mild Gasification of Coal". ABB Lummus Crest Inc. (then a subsidiary of Combustion Engineering Inc and currently a subsidiary of Asea Brown Boveri Inc.) and Amoco Oil Company (AOC) as key subcontractor successfully responded to the RFP and entered into a contract (No. DE-AC22-88MC25020) with the DOE on September 30, 1988.

The RFP was predicated on DOE's desire to enhance the development of advanced transportation fuels made from coal via a program to process mild coal gasification (MCG) liquids into high volumetric energy density (HEDF) test fuels. The desired product fuels were to be cost effectively manufactured, have high volumetric energy density, and be hydrocarbon-based for existing and prototype turbine and diesel engines. The sources for these special fuels consist of the abundant and secure indigenous energy resources of coal. Comparison studies were also to be made using other non-petroleum fossil fuels such as shale oil and tar sands bitumen.

METC has concluded that MCG technology has the potential to simultaneously satisfy the transportation and power generation fuel needs in the most cost-effective manner. MCG is based on low temperature pyrolysis, a technique known to the coal community for over a century. Most past pyrolysis developments were aimed at maximizing the liquids yield which results in a low quality tarry product requiring significant and capital intensive upgrading.

By properly tailoring the pyrolysis severity to control the liquid yield-liquid quality relationship, it has been found that a higher quality distillate-boiling liquid can be readily "skimmed" from the coal. The resultant liquids have a much higher H/C ratio than conventional pyrolytic tars and therefore can be hydroprocessed at lower cost. These liquids are also extremely enriched in 1-, 2-, and 3-ring aromatics. The co-product char material can be used in place of coal as a pulverized fuel(pf) for power generation in a coal combustor. In this situation where the original coal has a high sulfur content, the MCG process can be practiced with a coal-lime mixture and the calcium values retained on the char can tie up the unconverted coal sulfur upon pf combustion of the char. Lime has also been shown to improve the yield and quality of the MCG liquids.

The development of advanced fuels will provide increased range of volume-limited aircraft/missiles/vehicles and possibly provide a better heat sink than existing liquid fuels for high-speed aircraft. These special fuels would also provide desired characteristics for aircraft/vehicle operations in extreme conditions. Development of these fuels would have civilian and military applications in turbine and/or diesel engines for extended range and uses in remote areas where fuel supply may be difficult to sustain.

1.0 EXECUTIVE SUMMARY

1.1 Background and DOE Perspective

In April 1988, the Department of Energy (DOE) Morgantown Energy Technology Center (METC) issued a request for proposal (RFP) soliciting a research effort for the "Development of High Energy Density Fuels from Mild Gasification of Coal". ABB Lummus Crest Inc. (then a subsidiary of Combustion Engineering Inc and currently a subsidiary of Asea Brown Boveri Inc.) and Amoco Oil Company (AOC) as key subcontractor successfully responded to the RFP and entered into a contract (No. DE-AC22-88MC25020) with the DOE on September 30, 1988.

The RFP was predicated on DOE's desire to enhance the development of advanced transportation fuels made from coal via a program to process mild coal gasification (MCG) liquids into high volumetric energy density (HEDF) test fuels. The desired product fuels were to be cost effectively manufactured, have high volumetric energy density, and be hydrocarbon-based for existing and prototype turbine and diesel engines. The sources for these special fuels consist of the abundant and secure indigenous energy resources of coal. Comparison studies were also to be made using other non-petroleum fossil fuels such as shale oil and tar sands bitumen.

METC has concluded that MCG technology has the potential to simultaneously satisfy the transportation and power generation fuel needs in the most cost-effective manner. MCG is based on low temperature pyrolysis, a technique known to the coal community for over a century. Most past pyrolysis developments were aimed at maximizing the liquids yield which results in a low quality tarry product requiring significant and capital intensive upgrading.

By properly tailoring the pyrolysis severity to control the liquid yield-liquid quality relationship, it has been found that a higher quality distillate-boiling liquid can be readily "skimmed" from the coal. The resultant liquids have a much higher H/C ratio than conventional pyrolytic tars and therefore can be hydroprocessed at lower cost. These liquids are also extremely enriched in 1-, 2-, and 3-ring aromatics. The co-product char material can be used in place of coal as a pulverized fuel(pf) for power generation in a coal combustor. In this situation where the original coal has a high sulfur content, the MCG process can be practiced with a coal-lime mixture and the calcium values retained on the char can tie up the unconverted coal sulfur upon pf combustion of the char. Lime has also been shown to improve the yield and quality of the MCG liquids.

The development of advanced fuels will provide increased range of volume-limited aircraft/missiles/vehicles and possibly provide a better heat sink than existing liquid fuels for high-speed aircraft. These special fuels would also provide desired characteristics for aircraft/vehicle operations in extreme conditions. Development of these fuels would have civilian and military applications in turbine and/or diesel engines for extended range and uses in remote areas where fuel supply may be difficult to sustain.

While little R&D has been conducted on the treatment of coal-derived MCG liquids to produce advanced fuels, significant R&D efforts have been carried out to produce specification fuels from shale oil and tar sands bitumen. The major technical challenge in this program is the development of effective methods for treating MCG liquids and in increasing volumetric energy density while still meeting the essential features of the operational fuel specifications.

Processing and upgrading methods are needed to produce good yields of advanced fuels while minimizing overall processing costs. Advanced test fuels of interest must be produced to meet operational requirements reflected in the DOD fuel specifications but may vary in chemical composition so as to increase the volumetric energy density and/or reduce the processing severity.

1.2 Contract Objectives

The overall objective of the research effort is the determination of the minimum processing requirements to produce high energy density fuels (HEDF) having acceptable fuel specifications. The program encompasses assessing current technology capability; selecting acceptable processing and refining schemes; and generating samples of advanced test fuels.

The specific objectives are:

- o Conduct a technical and economic assessment of promising processing and upgrading methods to convert raw products from mild coal gasification into advanced high volumetric energy density test fuels for aviation turbines and diesel engines;
- o Conduct screening tests of alternative processing methods; and
- o Generate and deliver gallon-size test quantities of advanced fuels from mild coal gasification liquids and other sources.

1.3 Task Breakdown Structure

The Phase I Baseline Program is intended to explore the processing alternatives for producing advanced HEDF from two raw synfuel feedstocks, one from Mild Coal Gasification as exemplified by the COALITE process and one from Colorado shale oil derived from the UNOCAL retorting process. Eight key tasks were initially identified as follows:

<u>Task I.D. No.</u>	<u>Task Definition</u>
1	Planning and Environmental Permitting
2	Transporting and Storage of Raw Fuel Sources and Products
3	Screening of Processing and Upgrading Schemes
4	Proposed Upgrading Schemes for Advanced Fuel
5	Upgrading of Raw Oil into Advanced Fuel

6 Packaging and Shipment of Advanced Fuels
7 Updated Technical and Economic Assessment
8 Final Report of Phase I Efforts

This topical report summarizes the operations and results of the Phase I Task 3 screening program. The specific objectives of Task 3 were to:

- o characterize the two synfuel feedstocks supplied by DOE with regard to their processability for conversion to advanced HEDF; and
- o perform laboratory screening tests of candidate processing methodologies.

The characterization tests were to consist of performing analytical assays of each of the two synfuel feeds and the processed test materials. Each candidate feed was to be analyzed with the following minimal tests being performed:

1. Ultimate Analyses
2. Distillation
3. Specific Gravity
4. Hydrocarbon Type Analyses including % Aromatics
5. Viscosity
6. Aniline Point
7. Bromine Number
8. Heating Value
9. Conradson Carbon Residue (CCR)
10. Solubility in heptane, toluene, quinoline
11. Pour Point
12. Flash Point
13. Diene Number
14. Accelerated Thermal Stability (D-2274)
15. Metals including arsenic

The feeds were to be fractionated into at least three cuts, an IBP-300°F naphtha; a 300-650°F mid-distillate; and a 650°F+ residue. The naphtha was to be analyzed for:

1. Ultimate Analysis
2. Specific Gravity
3. Distillation
4. RI
5. Hydrocarbon Type Analysis
6. Flash Point
7. Octane Number
8. Bromine Number
9. Diene Number

The mid-distillate cut was to be analyzed for:

1. Ultimate Analyses
2. Specific Gravity
3. Distillation
4. Hydrocarbon Type Analyses

5. Flash Point
6. Smoke Point
7. Cetane Number
8. Heating Value
9. ASTM D-873 Residue
10. Freeze Point

The resid cut was to be analyzed for ultimate analysis, CCR content, specific gravity, solubilities, distillation, viscosity, and metals content.

Upon a critical review of the analytical characterization data with regard to processability options for production of advanced HEDF, Lummus was to determine if the current two-step heteroatom removal-ring saturation concept is still feasible. Lummus was then to notify the COTR if the screening test plan submitted under Task 1 needs to be modified to reflect the latest analytical data. The screening tests will consist of checking those points of uncertainty in which little or no data exist to be able to completely define the processing/upgrading requirements. The following sections describe the initial screening study proposed based on the two-step processing concept and the alternative studies in the event that the two-step cat hydrotreating route is found to be discouraging with respect to achievement of the 130,000 Btu/gal LHV spec at attractive HEDF yields.

Initial screening was to consist of the catalytic two-step hydrotreatment in a fixed-bed bench-scale unit. Initially the whole-range feedstock was to be processed and upon review of the analyses of the products, further screening tests with selected distillate feed cuts may be warranted. The objective of this catalytic hydrotreatment was to convert heteroatoms, namely, S, N, and O, at high conversion rates and under conditions that will preserve the integrity of the 2-ring and 3-ring aromatics. It is also a desire of the catalysis to minimize undesirable side reactions such as hydrocracking that might also result in significant gas formation and high hydrogen consumption rates.

The catalytic hydrotreatment screening studies were to be analyzed by comparing performance as a function of operating severity. Severity will be varied as a function of reaction temperature, space velocity, hydrogen partial pressure, hydrogen recycle rate and catalyst type. Catalyst types that were to be considered include commercial petroleum refining catalysts such as NiMo; NiCoMo; NiWS/SiO₂-Al₂O₃. Development catalysts that are being specifically tailored for nitrogen removal (both the UCCR and METC Mild Gasification liquids have very high basic nitrogen contents) might also be considered.

Performance will be measured by depth of removal of the heteroatoms. Additionally, hydrocarbon type analyses will be performed to determine the aromatics/naphthenes ratio with the objective of elucidating the interrelated effects of severity on heteroatom removal and degree of aromaticity. The volumetric energy density (VLHV) of the hydrotreated

material will also be determined to assess the degree of improvement in the HEDF target energy density during the catalyst hydrotreatment step.

From the subsequent analyses of these data, a preferred catalytic hydrotreatment severity was to be selected. The fixed-bed screening unit would then be operated at this preferred condition to generate sufficient hydrotreated product for the second-stage HEDF production studies. The objective of the second-stage operation was to saturate the aromatic ring structures sufficiently to achieve the minimal calorific value requirement namely, 130,000 Btu/gal LHV. This value is within a few percent of the LHV of decalin, a totally saturated 2-ring cycloparaffin with desirable HEDF properties. Thus, significant aromatics saturation will be required to process the aromatics-rich Mild Coal Gasification liquids to meet the LHV spec for HEDF.

In order to overcome equilibrium constraints, it is desirable to saturate the aromatic rings at the lowest possible reaction temperature. This will necessitate the use of very active and selective catalysts which generally are intolerant of basic nitrogen and sulfur compounds. Thus, the deep heteroatom removal step is needed. Typical catalysts that might be evaluated include platinum, palladium or ruthenium. Non-noble metal catalysts to be evaluated include nickel on silica-alumina and cobalt/chromium/molybdenum on mol sieve/alumina supports. If heteroatoms can't be readily removed to the required levels for these active catalyst types, then more conventional base metal catalysts will be tested. The latter can be achieved but at higher hydrogen partial pressures necessary to effect aromatic ring saturation at the higher reaction temperatures required by these less active catalysts.

The second reaction step will explore the effects of temperature, pressure, space velocity and catalyst type. Screening will be carried out in the same fixed-bed bench-scale unit as that used for the cat hydrotreatment step. This unit is of small enough scale and designed such that removal of exothermic heat will not be an operational problem. Performance will be monitored by the achievement of the 130,000 Btu/gal LHV spec as a function of reaction severity. For each hydrogenated product, analytical testing of the aviation turbine fuel specs represented by JP-4, JP-8, JP-7 and JP-10 fuels will also be carried out. In particular, the following tests will be performed: JFTOT stability, smoke point, cetane number, luminometer number, copper corrosion, potential gum, specific gravity, aniline point, freeze point, color, flash point and viscosity.

While it is believed that the two-step heteroatom removal-ring saturation process will generate favorable results with respect to processing requirements and achievement of the high energy density spec, there are alternative processing routes that can be investigated should the results of the initial screening program prove to be discouraging.

The fraction boiling above the aviation turbine fuel range, namely 650°F+, would have to be cracked, either via thermal (e.g., coking, steam cracking); thermal-catalytic (e.g., FCC) or hydrocracking (e.g. LC-Finingsm) technologies. The cracking operation might be preceded by a catalytic hydrotreating step, similar to that proposed for the two-step, heteroatom removal-ring saturation process.

These screening operations can be carried out in several test units available at Lummus. Thermal cracking can be evaluated in either a batch bench thermal cracking unit or in a multi-drum coker unit. Key parameters in this operation include temperature, pressure, residence time and steam rate. Hydrocracking can be evaluated in either a batch LC-Finingsm process simulation unit or in a continuous stirred autoclave unit. In either operation, the key parameters are hydrogen pressure, temperature, contact time or space velocity and catalyst type. Significant catalyst research has been performed for the hydroprocessing of coal-derived residual oils and Lummussm has a large database from which to compare and assess the LC-Finingsm performance potential of Mild Coal gasification liquids and shale oils. These data can be extended to the upgrading of LC-Finates to advanced HEDF.

1.4 Feedstocks

The two candidate synfuel feedstocks selected for the Phase I program by DOE consisted of a mild coal gasification liquid and a shale oil. The coal liquid consists of a nominal 160-1000F boiling range product from the British COALITE carbonization process. The COALITE process was developed in the early 1900's (1) based on the use of a vertical retort. A COALITE plant built in 1936 at the Bolsover Works of Coalite and Chemical Products Ltd is still in operation and the 1000-gal sample was procured and delivered to Lummus by United Coal Company Research Corporation of Bristol, VA. The COALITE was produced from a medium coking British coal and is expected to have properties similar to those of U.S. Eastern bituminous coals.

The shale oil is derived from Green River oil shale and was produced at the Unocal plant in Colorado. The 1000-gal sample was provided to Lummus by the Western Research Institute of Laramie, WY.

1.5 High Energy Density Fuels (HEDF)

Conventional petroleum-based aviation turbine fuels (e.g., JP-4) generally contain about 20 volume percent aromatics (25% max.) and 30% paraffinics with the balance being naphthenics. If these conventional fuels were severely hydrogenated to convert all the aromatics to naphthenes, the total saturated cyclic content would still only be about 70%. In order to convert the paraffinic compounds, which characteristically have low energy density because of their high H/C ratios and low specific gravities, to cycloparaffins would require complex and expensive processing techniques such as isomerization and aromatization.

Naphthenic hydrocarbons having two or three rings represent the optimal density-calorific value relationship of any hydrocarbon fuel currently produced. Thee two-ring (and three-ring) saturates can be readily produced by hydrogenation of their unsaturated or aromatic precursors. Coal liquids produced by mild coal gasification are known to have in excess of 90-95% 2-ring and 3-ring polynuclear aromatics content. Thus, by hydroprocessing techniques to insure the integrity of 2- and 3-ring hydrogenated products, these mild gasification products can be converted to advanced high energy density fuels at high yields.

Three advanced HEDF types have been defined for this RFP as discussed below.

Category I - Aviation Turbine Fuel

This advanced fuel is defined as one having a Lower Heating Value (LHV) in excess of 130,000 Btu/gal and preferably on the order of 135,000 Btu/gal and having high thermal stability. For comparison, conventional JP-4 turbine fuel has an LHV of only 119,400 Btu/gal and typical kerosene has a value of about 123,000. Decalin, an unsubstituted 2-ring cycloparaffin, has an LHV of 135,400 Btu/gal and an alkylated decalin has an LHV of 134,950 Btu/gal. This Category I advanced fuel must conform to the operational requirements reflected in the DOD fuel specifications for JP-4 and JP-8 but with necessary chemical composition variations required to achieve the desired higher volumetric energy densities and/or to reduce the required processing severity.

Category II - Endothermic Turbine Fuel

This advanced fuel must have a high energy density value but also must have those properties to make it a satisfactory fuel for use in advanced hypersonic aircraft. At hypersonic speeds, significant thermal problems arise due to the effect of stagnation temperature, the latter being the resultant temperature due to the resistance of the air molecules impeding the motion of the vehicle. Heat can be removed by either a mechanical refrigeration system; a non-combustible coolant; or by the fuel itself, the latter being the most preferred. Three types of endothermic processes can be used depending upon fuel type: a) catalytic dehydrogenation of naphthenes; b) thermal cracking of various hydrocarbons; and c) depolymerization of polymers. All of these systems have varying heat sink limits and the prior R&D reported in the literature has pinpointed the naphtha dehydrogenation route as a preferred endothermic mechanism. Typical compounds having good heat sinks include methylcyclohexane(MCH), methycyclopentane(MCP), decalin, dicyclohexyl, etc. Compounds of these types or their unsaturated precursors might exist in the Mild Coal Gasification liquids at some appreciable concentrations to result in the production of a reasonable yield of the Category II advanced fuel.

Category III - High Energy Diesel Fuel

This advanced fuel must meet DOD's diesel spec VV-F-800D(this spec supersedes the VV-F-800C spec shown in the RFP) and have an energy

density comparable to that of the Category I turbine fuel thus allowing extended driving range for military vehicles such as tanks. This spec has no volumetric energy density limitation per se, but the Cetane No. spec can be effected by hydrocarbon type, in particular, aromatics, and the latter will affect the resultant energy density of the fuel. The three grades of VV-F-800D diesel fuel, namely, DF-A, DF-1 and DF-2 have varying operability characteristics pursuant to the climactic specification. Grade DF-A, Arctic grade, has the lowest viscosity requirement and distillation end point limit. Back-end diesel cut blending to achieve the desired high volumetric energy density will have to be balanced against front-end blending to insure that the Distillation End Point, Viscosity and Carbon Residue specs are not violated.

1.6 Process Screening Alternatives

Our overall approach to processing Mild Coal Gasification liquids and shale oils consists of integrated hydrofining technology using catalysts tailored to the heteroatom removal and ring hydrogenation functions. In order to perform the optimization of maximum yield of the desired HEDF products at minimal processing costs, there will have to be a tradeoff of product yield vs. hydrogen consumption requirements. Consideration will have to be given to the handling of the light end and the heavier end of the synfuel feedstocks which can not completely be incorporated into the desired mid-distillate advanced fuel products. Based on in-house hydroprocessing experience with these type of synfuel feedstocks together with Amco's Refinery LPT model, preliminary flowschemes were developed to serve as the basis for initiating the screening studies of Task 3.

The initial screening consisted of the catalytic two-step hydrotreatment, i.e., heteroatom removal followed by ring saturation, in a fixed-bed, downflow bench-scale unit. Tests were performed with selected distillate fractions of the feeds. The heavier fraction boiling above the aviation turbine fuel range was cracked either via thermal (e.g., coking); or hydrocracking (e.g., LC-Fining, VGO hydrocracking) technologies.

A contract modification for extending the Task 3 screening studies was approved by DOE. The emphasis of this modification was to deemphasize the Colorado shale oil feedstock (since the early screening data indicated that it did not have the high energy density potential as that of the MCG liquids) and to concentrate on the production of HEDF components via selective hydrocracking of the gas oil and resid components of the raw COALITE feedstock. An enhanced screening program was implemented to evaluate alternative catalysts for the selective hydrocracking steps and to relate hydroprocessing severities to the thermal stability properties of the finished HEDF test fuels.

1.7 Experimental Procedures

At Lummus's Research & Development Center (formerly the Engineering Development Center-EDC), process screening is carried out in either laboratory-scale, bench-top or pilot plant equipment. The processing and upgrading schemes for producing HEDF from synfuel feedstocks under the subject program include the following unit operations:

- o Fixed-bed Distillate Hydrotreating
- o Fixed-bed Distillate Hydrocracking
- o Expanded-bed Resid Hydrocracking
- o Delayed Coking
- o Fractionation
- o Solvent Extraction
- o Clay Treating

The screening of these process operations was carried out in the following test units:

1. Bench-Scale Fixed-Bed Hydrotreating Unit
2. Bench-Scale Fixed-Bed Hydrocracking Unit
3. Bench-Scale Expanded-Bed LC-Fining^{cm} Unit
4. Continuous Bench Coking Unit
5. Laboratory Extraction Unit
6. 4-in Batch Fractionation Unit
7. Equilibrium Flash Vaporization Pilot Unit
8. Laboratory Batch Distillation Units
9. Laboratory Clay Treating Unit

1.8 Summary of Results of COALITE Operations

The raw COALITE feedstock was fractionated in the 4-in Batch Distillation unit in four different campaigns. The initial fractionation, referred to as CC-1, resulted in the collection of sixteen successive distillate cuts and a vacuum resid fraction. The bulk of these materials was used for the analytical characterization tests (described in Section 3), the delayed coking evaluation of the 650F+ resid, and the LC-Fining evaluation of the 650F+ (343C+) resid.

Batch fractionation CC-2 resulted in the collection of 24 distillate fractions and a 670F+ (354C) resid fraction. Two composite blends for distillate hydrotreating were made: a nominal 350-650F (177-343C) blend of distillate fractions 5 through 22 to simulate a Category III boiling-range fuel; and a nominal 350-550F (177-288C) blend of distillate fractions 5 through 14 to simulate a Category I boiling-range fuel. Two additional blends were made with heavier end points (i.e., 750F and 820F) to determine whether the addition of the heavier gas oil components could increase energy densities above and beyond the 130,000 Btu/gal specification.

It should be kept in mind that the final Initial Boiling Point and End Point of the finished HEDF product is set in a post-hydrogenation topping and tailing operation. The nominal ranges of the feeds could not be fine-tuned in advance of and during the screening test work

until sufficient information was acquired on the interaction of the process variables on all of the specified HEDF properties. Thus, the approach taken was to use the post-hydrogenation distillation operations to fine tune the critical distillation temperatures controlling the volatility (i.e., flash point spec) and the back-end viscosity/freeze point spec. Of course, in a commercial operation, the design of the fractionation systems would be optimized to reduce the cost of any unnecessary towers.

Six virgin distillate hydrotreating campaigns were made with the COALITE distillates to study the effects of catalyst type, distillate boiling range, single-stage vs two-stage, recycle of first-pass hydrotreated product and severity as controlled by space velocity, hydrogen partial pressure and reactor temperature. A total of 59 material balance tests were made of durations extending from 2-hours to 36-hours. The following table summarizes the salient features of each campaign and the summary table reference number.

<u>CAMPAIGN #</u>	<u># STAGES</u>	<u>CATALYST TYPE</u>	<u>FEED BOILING RANGE</u>	<u>#TESTS</u>
1	1	K-550	350-650F	30
2	1	K-550	350-550F	8
3	2	K-550/K-550	350-750F;350-820F	8
4	2	K-550/K-599	350-650F	7
5	1	K-599	350-650F	2
6	1	Ca-doped K-550	350-650F	4

Campaign 5 was also used for the production of liter-size samples of finished HEDF samples required as a Task 3 deliverable. The specific objectives of each of these six campaigns are summarized below:

- Campaign 1: Initial scans to evaluate the effects of space velocity, reaction temperature, hydrogen partial pressure and single-pass product recycle with a candidate NiWS hydrotreating catalyst in a single-stage reactor using the 350-650F COALITE distillate.
- Campaign 2: Initial scans to evaluate the effects of space velocity, reaction temperature and single-pass product recycle with a candidate NiWS hydrotreating catalyst in a single-stage reactor using the 350-550F COALITE distillate.
- Campaign 3: Initial scans to evaluate the effects of temperature and space velocity with higher end point COALITE distillates using a two-stage NiWS catalyst reaction system.
- Campaign 4: Initial scans to evaluate the effects of temperature and space velocity with the 350-650F COALITE distillate in a two-stage reactor system comprising a NiWS catalyst in the first-stage and a high moly nickel catalyst in the second-stage reactor.

- Campaign 5: Production run to produce liter size samples of HEDF materials in a single-stage reactor with the high moly nickel catalyst using the 350-650F COALITE distillate.
- Campaign 6: Scans of the effects of temperature and space velocity with a calcium-doped NiWS catalyst using the 350-650F COALITE distillate.

There is a considerable yield of atmospheric resid in the raw COALITE. HEDF products are end-point limited because of viscosity and freeze point specifications. Therefore, it is necessary to crack the heavier components to the mid-distillate range comprising the desired HEDF turbine fuel products. Three cracking methods were considered: 1) Resid hydrocracking using the LC-Finingtm process; 2) Delayed Coking; and 3) VGO fixed-bed hydrocracking.

LC-Finingtm is a commercial technology for upgrading heavy oils. In the context of the COALITE HEDF application, LC-Finingtm has been used to hydrotreat long residues (ca., 300F+) and to hydrocrack the 650F+ (343C+) components into the HEDF boiling ranges. Three feedstocks were considered: 1) a virgin or raw 650F+ (343C+) atmospheric resid fraction of the raw COALITE; 2) a virgin 300F+ (148C+) long resid fraction; and 3) a hydrotreated 575F+ (301C+) atmospheric resid fraction. The objectives of these three campaigns were as follows:

- o Evaluate the first-pass reactivity of the virgin 650F+ atmospheric resid fraction towards hydrocracking and the production of hydrocracked HEDF-boiling range materials;
- o Evaluate the hydrocracking reactivity of the first-pass unconverted (575F+) atmospheric resid recovered from the virgin 650F+ LC-Finingtm tests of the above campaigns; and
- o Prepare hydrotreated gas oil (650-975F) for downstream selective fixed-bed hydrocracking campaigns by subjecting the 300F+ long resid to mild LC-Finingtm.

Delayed Coking is another alternative technology for upgrading heavy oils to lighter products, such as HEDF materials. However, Delayed Coking is not as selective as hydrocracking and results in the production of a variety of byproducts, the predominant one being coke. On the other hand, Delayed Coking is much less capital intensive than hydrocracking and the differential HEDF yield losses are modulated by lower capital and operating costs.

Three Delayed Coking tests were made in the Continuous Bench Coker (CBC) unit, two with virgin 650F+ atmospheric residua and one with a hydrotreated resid. Two delayed coking severities were investigated: a) 100 psig coke drum pressure; and b) 25 psig coke drum pressure, all other conditions kept constant.

The above two cracking operations, namely, LC-Finingtm and Delayed Coking, are primarily conversion processes to produce HEDF precursor materials that boil within the HEDF boiling range. They therefore do

not result in the production of finished HEDF products and a post-cracking hydrogenation operation is required for upgrading the cracked precursor materials. In a true commercial process, a fractionator would be installed between the cracking unit(s) with the cracked distillate fed continuously to the distillate hydrotreater and the heavier unconverted residuum being recycled back to the cracking unit. In this Task 3 screening program with the COALITE feedstock, the bench-scale cracking and hydrotreating units were not integrated and thus only first-pass crackates, either, delayed coker distillates or hydrocrackates (LC-Finates), were evaluated. Three distillate hydrotreating runs were made with delayed coker distillates and eleven distillate hydrotreating runs were made with LC-Finate (hydrocracked) distillates.

The objective of the eleven hydrotreating tests made with the LC-Finate mid-distillates produced was to evaluate the effects of hydrocracked distillate end point, catalyst type, space velocity, reactor temperature, and single-stage vs two-stage distillate hydrotreating. The objective of the hydrotreating tests made with the coker mid-distillates was to evaluate the effects of coker severity, coker distillate end point, reactor temperature, and single-stage vs two-stage distillate hydrotreating.

During the early phases of the screening program, it was determined that the raw atmospheric resid fraction of COALITE was very reactive towards undesirable cracking and condensation reactions. Thus, it was postulated that a pretreatment based on hydrogenation would provide some degree of stabilization of reactive species and thereby allow better performance during subsequent cracking operations. Since the atmospheric COALITE resid contains some coal char particles, it was felt that hydrotreating in a fixed-bed unit would pose significant operability problems. The expanded-bed hydrocracking process of LC-Fining[™] offers the capability to perform the hydrogen addition process in the presence of solids and other contaminants under commercially feasible conditions.

The two-step selective hydrocracking (TSSH) of COALITE consists of a hydrotreating pretreatment step using an LC-Fining[™] reaction system followed by fractionation to recover a hydrotreated vacuum gas oil (HVGO) fraction and a hydrotreated middle distillate fraction, the latter of which can be directed to the HEDF pool. The HVGO fraction is then catalytically hydrocracked over a fixed-bed hydrocracking catalyst to convert the heavier gas oil-boiling species to HEDF precursors. The thus hydrocracked LC-Finate HVGO, is then subjected to distillate hydrotreating to produce the final HEDF product.

In the screening program, the fixed-bed hydrocracker and the hydrocracked distillate hydrotreater were not integrated and therefore hydrotreating of only the first-pass hydrocracked HVGO fraction was evaluated. Finally, in order to minimize fractionation equipment costs in a commercial plant, it was decided to perform the initial LC-Fining[™] pretreatment step with a 300F+ atmospheric resid fraction rather than with a 650F+ atmospheric resid fraction. Two hydrocracking campaigns were made: 1) hydrocracking of virgin COALITE

VGO; and 2) hydrocracking of hydrotreated LC-Finate VGO. The objective of these tests was to evaluate the effects of space velocity, reactor temperature and VGO feedstock type. All nineteen tests were made with a proprietary fixed-bed hydrocracking catalyst supplied by Amoco Oil Company. The hydrocracked LC-Finate VGO was fractionated to recover a mid-distillate fraction for distillate hydrotreating.

A contract modification was approved by DOE to perform further screening studies of the two-stage selective hydrocracking route with the goal of exceeding the 130,000 Btu/gal energy density target of the finished HEDF test fuels. It was further expanded to also consider the impact of the energy density-JFTOT fuel stability relationships. A proprietary zeolitic hydrocracking catalyst from Zeolyst Enterprises was found to have dual functionality and be able to selectively hydrocrack VGO materials and saturate the cracked aromatic rings in the mid-distillate range simultaneously while generating a HEDF test fuel having a volumetric energy density on the order of 133 KBtu/gal. Although this did not meet the revised target of 135,000, it did exceed the original work statement target of 130,000 Btu/gal. Tables 1.8-1 and Figure 1.8-1 summarize the energy density achievements for the four Subtask 3.2 campaigns.

1.9 Summary of Results of Colorado Shale Oil Operations

Unlike the MCG liquids, the Colorado shale oil distillates are less concentrated in the cyclics and more concentrated in the aliphatic materials as seen in the table below:

	<u>Colo. Shale Oil</u>	<u>COALITE</u>
% Olefins	39.9	11.8
% Saturates (cyclic+aliphatic)	32.9	<13.7
%Aromatics	27.2	>74.5

The COALITE olefins are primarily cyclic in structure, e.g., cyclooctene, cyclodecene, whereas the shale-derived olefins are primarily aliphatic, e.g., n-octene/iso-octene, n-decene/iso-decene. The saturates types, naphthenes vs. paraffins, for these raw synfuels were not readily differentiated by the sulfonation/R.I. procedure of the ASTM FIA analysis.

For the case of the Colorado shale oil, the raw 300-600F distillate had a volumetric heat content of only about 127 KBtu/gal, some 3000 Btu/gal below the target. Upon hydrotreatment, the volumetric energy content decreases significantly away from the target. Thus, the K-550 NiWS and K-599 NiMo catalysts do not appear to have the right functionality to preserve and/or form the desirable cyclic structures. It may be possible to obviate this situation by extending the end point of the distillates beyond 600F and the initial point beyond 300F in order to increase the concentration of the denser 2- and 3-ring cyclics.

TABLE 1.8-1
COALITE DERIVED
HEDF FUEL PROPERTIES

TASK 3 SCREENING PROGRAM RESULTS

DESIGNATION	FBHC-41	FB-214D	FB-214E	FB-214F
BOILING RANGE, DEG. F	300-600	300-610	300-620	300-600
GRAVITY, SP. @60	0.8560	0.8745	0.8571	0.8702
GRAVITY, DEG. API	33.8	30.3	33.6	31.1
ELEMENTALS:				
CARBON, WT.%	86.36	86.84	86.55	86.78
HYDROGEN, WT.%	13.64	13.16	13.45	13.22
NITROGEN, ppm	<1	<1	<1	<1
SULFUR, ppm	5	4	1	<1
VISCOSITY @ -4F, cst.	9.1	14.1	9.3	11.0
FLASH POINT, DEG. F	>120	>145	>140	>150
FREEZE POINT, DEG. F	<-50	<-50	<-50	<-50
SMOKE POINT, mm	22	18	20	20
ANILINE POINT, DEG. C	61.9	58.0	62.0	54.9
F.I.A.:				
AROMATICS, VOL.%	4.6	3.7	6.6	15.2
OLEFINS, VOL.%	0.5	0.5	0.5	0.5
SATURATES, VOL.%	94.9	95.8	92.9	84.3
COPPER CORROSION, @ 212F	3A	1A	1A	1A
POTENTIAL GUM, mg/100ml	7.0	NA	7.4	16.4
THERMAL STABILITY (JFTOT):				
TUBE DEPOSIT RATING	0	0	0	2
TUBE DEPOSIT RATING, MAX.	0.5	1.0	1.5	8.0
DIFF. PRESS. MAX., mm Hg	3.0	3.0	3.0	3.0
ENERGY DENSITY, BTU/GAL	130,860	133,992	131,622	132,901

FIGURE 1.8-1

Two campaigns of resid hydrocracking via LC-Fining technology were made. One campaign of resid thermal cracking via delayed coking was completed. Only one test campaign was completed for the hydrotreating of cracked distillates. We previously found that volumetric energy densities of 300-600F raw Colorado shale oils after fixed-bed hydrotreating were limited to about 125,000 Btu/gal. While this value is some 5000 Btu/gal below the spec, it still represents a 5000-10,000 Btu/gal energy density premium above that of conventional jet fuels. Nevertheless, a campaign was initiated with the heavy (550F+) Colorado shale oil fraction following parallel processing routes that successfully generated a 132,000+ Btu/gal energy density HEDF from the 550F+ COALITE feedstock.

The selective hydrocracking route, as successfully implemented with the COALITE feedstock, basically consists of mild expanded-bed hydrofining (LC-Fining) of the 300F+ dewatered feed; fractionation to recover the 550-975F LC-Finate vacuum gas oil (VGO); selective hydrocracking of the VGO over the Amoco proprietary fixed-bed hydrocracking catalyst; and fixed-bed hydrogenation of the VGO hydrocrackate.

In the current campaign with the Colorado shale oil feedstock, the selective hydrocracking route followed the steps delineated below:

- o The whole (IBP to end point), undewatered Colorado shale oil was subjected to the mild LC-Fining (test BLCF-102) step. The water collected in the LC-Finate product receivers was phase separated by decanting. The LC-Finate full-range product was fractionated to generate a 575-975F VGO fraction for downstream hydrocracking/hydrogenation.
- o Since the nitrogen content of the LC-Finate VGO was still very high, ca., 15000 ppm, a subsequent fixed-bed hydrotreating (test FB-186/187) step using a NiW/NiMo two-stage catalyst system was used to reduce nitrogen content to 200 ppm.
- o The thus hydrotreated LC-Finate VGO was then subjected to fixed-bed hydrocracking (test FBHC-32/35) over the Amoco proprietary hydrocracking catalyst. The resultant full-range hydrocrackate was then subjected to fixed-bed hydrotreating (FB-188/189) over a NiW/NiMo two-stage catalyst system without fractionating out the unconverted 575-975F gas oil fraction.
- o The hydrogenated hydrocrackate was fractionated to recover a 275-550F HEDF product that met flash point and freeze point specs.

The measured energy density of this latter product was still only about 125,000 Btu/gal, comparable to that generated when hydrotreating the raw 300-600F Colorado shale oil distillate. Thus, the selective hydrocracking of the 575F+ fraction of the Colorado shale oil did not

improve energy density quality as was observed with the COALITE feedstock. Furthermore, the per pass conversions during the LC-Fining (BLCF-102) and the fixed-bed hydrocracking (FBHC-32/35) were very low indicating the relative refractory nature of the gas oil fraction of the Colorado shale oils.

The plan for the evaluation of the extraction/hydrogenation route consists of: a) collection of basic equilibrium solvent selectivity data for the two candidate solvents, namely, dimethylformamide (DMF) and tetraethylene glycol (TEG); b) analytical evaluation of the extracts and raffinates with respect to energy density improvements; and c) recommendations for preparation of bench-scale quantities of extracts for demonstration of the potential of fixed-bed hydrotreating (and hydrocracking) to upgrade extracted HEDF precursors to the 130,000 min. Btu/gal energy density spec.

The four feedstocks selected for the initial evaluation include:

- o mildly LC-Fined vac gas oil (BLCF-102 product)
- o severely hydrotreated LC-Finate vac gas oil (FB-186/187)
- o selectively hydrocracked mid-distillate (FB-188/189)
- o hydrotreated raw mid-distillate (FB-130)

The first two feedstocks represent the evaluation of heavier extracts boiling above the HEDF boiling range prior to hydrocracking. The latter two feedstocks to extraction represent HEDF products having nominal 125,000 Btu/gal energy densities.

The test equipment consists of a stirred, externally heated, glass extraction vessel. Testing consisted of three stages of contact using fresh solvent in each stage. Conditions held constant in these initial tests were as follows:

- o Nominal temperature of 195F
- o Atmospheric pressure
- o Stirrer speed of 5 rpm
- o 1 hour extraction contact time per stage
- o Fresh solvent to feed ratio of 1.5 gm/gm

Raffinate and solvent-rich extract phases were separated by decanting in a separatory funnel. The extract was separated from the solvent by introduction of water which dissolved the solvent and freed the hydrocarbon-rich extract. The two solvents selected were premised on separation from the extract by distillation. The initial testing indicated that the DMF solvent demonstrated a good degree of effectiveness in extracting some species from the heavier feedstock. The TEG solvent appeared to have no specificity for any of the components in the lighter distillate feedstock. Since the DMF solvent is soluble in water, it may be separated from the extract in a commercial-scale application by introduction of a third phase, namely, water or an aqueous-rich recycle stream, instead of distillation.

The DMF extraction of a hydrotreated 300-650F distillate can increase the energy density of the extract by some 2335 Btu/gal over that of the feed but at the expense of a reduction in the energy density of the raffinate.

2.0 EXPERIMENTAL PROCEDURES

2.1 Overview

The Task 3 Work Statement called for the screening of processing and upgrading schemes using laboratory-scale screening equipment. At Lummus's Research & Development Center (formerly the Engineering Development Center-EDC), process screening is carried out in either laboratory-scale, bench-top or pilot plant equipment. The processing and upgrading schemes for producing HEDF from synfuel feedstocks under the subject program include the following unit operations:

- o Fixed-bed Distillate Hydrotreating
- o Fixed-bed Distillate Hydrocracking
- o Expanded-bed Resid Hydrocracking
- o Delayed Coking
- o Fractionation
- o Solvent Extraction
- o Clay Treating

The screening of these process operations was carried out in the following test units:

1. Bench-Scale Fixed-Bed Hydrotreating Unit
2. Bench-Scale Fixed-Bed Hydrocracking Unit
3. Bench-Scale Expanded-Bed LC-Fining^{cm} Unit
4. Continuous Bench Coking Unit
5. Laboratory Extraction Unit
6. 4-in Batch Fractionation Unit
7. Equilibrium Flash Vaporization Pilot Unit
8. Laboratory Batch Distillation Units
9. Laboratory Clay Treating Unit

2.2 Bench-Scale Fixed-Bed Hydrotreating Unit

The Bench-Scale Fixed-Bed Hydrotreating Unit (see Figure 2.2-1) consists of a two-stage, close-coupled, fixed-bed reactor system equipped with high pressure liquid and gaseous (hydrogen) feed systems and a product recovery system. The reactors can be piped in series or in parallel with or without vapor/liquid separation between stages. The following describes each unit operating system.

o Liquid Feed System

The oil feed is charged to a feed tank that is continuously stirred and circulated through a transfer line at about 5-10 psig back into

FIGURE 2.2-1

SCHEMATIC FLOW DIAGRAM OF FIXED-BED HYDROPROCESSING PILOT UNIT

the feed tank using a Tuthill lobe pump. A high pressure piston-type metering pump (Wallace-Tiernan) takes suction from the circulating loop and pumps the oil forward to the first stage reactor preheater. The feed rate is monitored by the rate of weight loss of the feed tank which is installed on a sensitive electronic weigh scale. Changes in the feed rate can be made by adjusting the plunger displacement on the Wallace-Tiernan pump.

o Hydrogen Feed System

A continuous supply of hydrogen is available from high pressure hydrogen trailers. The hydrogen is regulated to a low pressure (ca., 100 psig) and then recompressed to about 2500 psig with a diaphragm compressor. A high pressure piping manifold splits the compressed hydrogen and delivers it to the inlet of the preheater and the inlet of the fixed-bed reactors.

Each hydrogen flow is metered with a high pressure Brooks rotameter. The total hydrogen flow is also continuously metered by use of a precalibrated differential pressure monitor. System pressure is monitored at several locations including the discharge of the Wallace-Tiernan feed pump; inlet and outlet of the fixed-bed reactor; heavy oil product separator and the light oil receiver. System pressure is controlled by a diaphragm type back-pressure regulator.

o Reaction Systems

The preheater consists of a 0.245-in. inside diameter tube electrically heated with Calrod electric heaters providing for two separate controlled heating circuits. A separate transfer line heater controls the temperature of the stage I effluent. The fixed-bed reactors consist of a 1-in. i.d. pipe having an internal volume of about 192-cc. Each reactor is immersed in a sand bath serving as the reactor heater. The bath can be fluidized in the event isothermal operation is desired. Each reactor is equipped with four internal thermocouples. A 25-cc layer of 3-mm glass beads is positioned at the top of each catalyst bed. Each bed contains about 165-cc of catalyst.

o Product Collection System

The recovery system consists of four high pressure separators, each one operated at sequentially lower skin temperatures. In the first vessel, liquid products are separated from the uncondensed hydrocarbons and heteroatoms. This separator is steam traced and operated at system pressure. The resultant product is depressurized to ambient pressure, and then drained into an appropriate storage container.

The overhead vapor stream is further separated in three consecutive high pressure separators, and operated at sequentially lower temperatures. The pressure of the uncondensed vapors from the last separator is reduced to atmospheric, and cooled further in an ambient water-cooled condenser. Light uncondensed gases and hydrogen are then

metered by a wet test meter and sampled for subsequent gas chromatographic analysis.

The basic operating procedure is summarized below:

1. The unit is pressurized with hydrogen and brought up to operating temperatures and flow rates using the oil feed. No external startup oil is required.
2. The unit is then lined out with the feed for a period of time to insure at least 95 percent displacement of the existing system inventory. At this point, a material balance period of 6 hour duration is initiated. Gas and liquid product samples are collected.
3. Operating conditions are then changed for the next test and the new line-out period is established prior to initiating a new material balance period.

2.3 Bench-Scale Fixed-Bed Hydrocracking Unit

The Bench-Scale Fixed-Bed Hydrocracking Unit (see Figure 2.3-1) consists of a single-stage, fixed-bed reactor system equipped with high pressure liquid and gaseous (hydrogen) feed systems and a product recovery system. The following describes each unit operating system.

o Liquid Feed System

The liquid feed to the Bench-Scale Fixed-Bed Hydrocracker is generally a vacuum or atmospheric gas oil having a relatively high pour point. The feed system has been designed to provide heating to reduce feed viscosity and to provide circulation/agitation to prevent possible settling of contained solids (e.g., coal char fines as the case for COALITE feedstocks or oil shale fines as the case for Colorado shale oil feedstocks). The feed tank is continuously stirred and circulated through a transfer line at about 5-10 psig back into the feed tank using a Tuthill lobe pump. A high pressure piston-type metering pump (Wallace-Tiernan) takes suction from the circulating heavy oil loop and pumps the feed forward to the high pressure autoclave reaction system. The feed rate is monitored by the rate of weight loss of the feed tank which is installed on a sensitive electronic weigh scale. Changes in the feed rate can be made by adjusting the plunger displacement on the Wallace-Tiernan pump.

o Hydrogen Feed System

A continuous supply of hydrogen is available from high pressure hydrogen trailers. The hydrogen is regulated to a low pressure (ca., 100 psig) and then recompressed to about 2500 psig with a diaphragm compressor. A high pressure piping manifold splits the compressed hydrogen and delivers it to the inlet of the preheater, the inlet of the autoclave, and the drive assembly of the autoclave.

FIGURE 2.3-1
SCHEMATIC OF BENCH-SCALE FIXED-BED HYDROCRACKING UNIT

Each hydrogen flow is metered with a high pressure Brooks rotameter. The total hydrogen flow is also continuously metered by use of a precalibrated differential pressure monitor. System pressure is monitored at several locations including the discharge of the Wallace-Tiernan feed pump; outlet of the autoclave; heavy oil product separator and the light oil receiver. System pressure is controlled by a diaphragm type back-pressure regulator.

o Reaction System

The preheater consists of a 0.245-in. inside diameter tube electrically heated with Calrod electric heaters providing for two separate controlled heating circuits. The fixed-bed reactor consists of a 1-in. i.d. pipe having an internal volume of about 192-cc. The reactor is wrapped with calrod electric heaters and an insulation laminate to provide some degree of adiabaticity. The reactor is equipped with four internal thermocouples. A 25-cc layer of 3-mm glass beads is positioned at the top of the catalyst bed which contains about 165-cc of catalyst.

o Product Collection System

The recovery system consists of four high pressure separators, each one operated at sequentially lower skin temperatures. In the first vessel, liquid products are separated from the uncondensed hydrocarbons and heteroatoms. This separator is steam traced and operated at system pressure. The resultant product is depressurized to ambient pressure, and then drained into an appropriate storage container.

The overhead vapor stream is further separated in three consecutive high pressure separators, and operated at sequentially lower temperatures. The pressure of the uncondensed vapors from the last separator is reduced to atmospheric, and cooled further in an ambient water-cooled condenser. Light uncondensed gases and hydrogen are then metered by a wet test meter and sampled for subsequent gas chromatographic analysis.

2.4 Bench-Scale Expanded-Bed LC-Finingtm Unit

As a co-licensor of the proprietary expanded-bed hydrocracking process known as LC-Finingsm, Lummus has the responsibility of providing the process design package to LC-Finingsm licensees. In support of this effort, several LC-Finingsm test units are available at EDC. The unit utilized in the Task 3 screening study is a continuous bench-scale system containing an autoclave reactor system to simulate the commercial expanded-bed reactors. Data from this unit can be readily utilized to develop the test conditions of the larger pilot plant reactor system planned for use in Task 5.

Figure 2.4-1 is a schematic of the autoclave-based LC-Finingsm bench-scale unit. The unit consists of a liquid feed system; a

FIGURE 2.4-1

SCHEMATIC OF AUTOCLAVE-BASED LC-FINING UNIT

hydrogen feed system; a reaction system; and product collection system as described below.

o Liquid Feed System

The liquid feed to the autoclave-based LC-FinerSM is generally a vacuum or atmospheric resid having a relatively high pour point. The feed system has been designed to provide heating to reduce feed viscosity and to provide circulation/agitation to prevent possible settling of contained solids (e.g., coal char fines as the case for COALITE feedstocks or oil shale fines as the case for Colorado shale oil feedstocks). The feed tank is continuously stirred and circulated through a transfer line at about 5-10 psig back into the feed tank using a Tuthill lobe pump. A high pressure piston-type metering pump (Wallace-Tiernan) takes suction from the circulating heavy oil loop and pumps the feed forward to the high pressure autoclave reaction system. The feed rate is monitored by the rate of weight loss of the feed tank which is installed on a sensitive electronic weigh scale. Changes in the feed rate can be made by adjusting the plunger displacement on the Wallace-Tiernan pump.

o Hydrogen Feed System

A continuous supply of hydrogen is available from high pressure hydrogen trailers. The hydrogen is regulated to a low pressure (ca., 100 psig) and then recompressed to about 2500 psig with a diaphragm compressor. A high pressure piping manifold splits the compressed hydrogen and delivers it to the inlet of the preheater, the inlet of the autoclave, and the drive assembly of the autoclave.

Each hydrogen flow is metered with a high pressure Brooks rotameter. The total hydrogen flow is also continuously metered by use of a precalibrated differential pressure monitor. System pressure is monitored at several locations including the discharge of the Wallace-Tiernan feed pump; outlet of the autoclave; heavy oil product separator and the light oil receiver. System pressure is controlled by a diaphragm type back-pressure regulator.

o Reaction System

Two autoclave reaction systems are available: a 300 cc stirred autoclave having a 240 cc internal liquid volume; and a 1000 cc stirred autoclave having an 800-cc volume. Preheated feed is fed directly to the inlet of the autoclave at the bottom and exits at the top of the autoclave. Two impellers each consisting of six-bladed turbines are attached to the stirrer shaft. Typical stirring speeds utilized in the screening program were 175-250 rpm. Use of more violent mixing could possibly result in excessive breakage of the catalyst extrudates. Temperature control was excellent with internal autoclave temperatures not varying by more than 3-4F from set point.

o Product Collection System

The recovery system consists of four high pressure separators, each one operated at sequentially lower skin temperatures. In the first vessel, liquid products are separated from the uncondensed hydrocarbons and heteroatoms. This separator is steam traced and operated at system pressure. The resultant product is depressurized to ambient pressure, and then drained into an appropriate storage container.

The overhead vapor stream is further separated in three consecutive high pressure separators, and operated at sequentially lower temperatures. The pressure of the uncondensed vapors from the last separator is reduced to atmospheric, and cooled further in an ambient water-cooled condenser. Light uncondensed gases and hydrogen are then metered by a wet test meter and sampled for subsequent gas chromatographic analysis.

2.5 Continuous Bench Coking Unit

Lummus, as a licensor of commercial delayed coking technology, maintains several delayed coking test units at its R&D Center. The Continuous Bench Coking (CBC) Unit, while somewhat smaller than the Delayed Coking Pilot Plant, matches commercial delayed coking operations with respect to coking time, heavy liquids recycle, coke drum temperature and coke drum pressure.

A schematic flow sheet of the CBC Unit is shown in Figure 2.5-1. The CBC unit can be operated with fresh liquid feed rates from 400 to 1400 gm/hr and with recycle/fresh feed ratios as desired, typically from 0 to 1.5 vol/vol. Coke drum pressures up to 100 psig and coking temperatures from about 800F (426C) to 1000F (538C) can be evaluated. The operating pressure and key temperatures are controlled automatically within a relatively narrow range. The coking cycle is generally conducted up to a 20-24 hour period and depending upon the coke yield for a given feedstock, the coke drum can hold about 1300 to 4500 gm of green coke product.

Fresh feed is pumped from the steam-heated feed tank and is joined with the heavy oil recycle stream. The combined streams flow through the preheater and through the heater coil. From the heater, the fresh feed/recycle stream is fed to the coke drum. The devolatilized products from the coke drum flow through a pressure control valve and into the heavy oil separator. In this vessel, the recycle portion is condensed and pumped back to the inlet of the preheater. The coker "distillate" product is taken overhead into the light oil separator. The overhead vapor stream from this vessel is subsequently scrubbed in water and caustic scrubbers and then the non-condensibles are metered in a wet test meter.

FIGURE 2.5-1
SCHEMATIC OF CONTINUOUS BENCH COKING UNIT

2.6 Laboratory Extraction Unit

The initial approach to assessing the technical feasibility and amenability of the Colorado shale oil-derived products to HEDF energy density improvement consisted of equilibrium solubility studies in an ambient pressure glass contacting unit. The contactor consisted of a 1-L jacketed flask containing a glass stirring rod. Hot water is circulated through the jacket. Three stages of solvent contact were employed using the raffinate recovered from the preceeding stage in a subsequent extraction with fresh solvent. Contact time was maintained sufficiently to insure equilibrium. Shale oil-derived extracts were recovered from the separated solvents by water extraction.

2.7 4-in Batch Fractionation Unit

The 4-in Batch Fractionation Unit (see Figure 2.7-1) contains a 4-in diameter by 20-ft SS column containing 20 SS decks of bubble caps, 2 bubble caps per deck equivalent to 8-10 theoretical plates; an automatic variable range reflux head; and an 85-gal reboiler. A vacuum system is capable of operation at reflux head pressures of 5-10 mm Hg abs.

2.8 Equilibrium Flash Vaporization Pilot Unit

The Equilibrium Flash Vaporization pilot unit is a continuous system for performing single-stage equilibrium flash operations. The unit consists of an 8-in diameter by 14-in long flash chamber and can process 5-7 gal/hr of liquid feed to a 600F (315C) maximum temperature. At the operating vacuum limits (ca., 3-4 mm Hg abs), this temperature corresponds to a maximum atmospheric equivalent temperature of about 975F (524C). The unit is a true simple flash with essentially no reflux as the flash chamber walls are electrically heated to at or above the flash temperature.

2.9 Laboratory Batch Distillation Units

In the course of the screening work, it is necessary to tailor distillate product boiling ranges to meet certain jet/diesel fuel specs. As a result of the exploratory nature of the screening program, it is not always possible to prepare the hydroprocessing feedstocks to meet the exact boiling ranges of the final HEDF products. Therefore, there is a need for intermediate distillation for tailing front-end and back-end distillation temperatures.

This work is facilitated in a variety of laboratory glass distillation columns. Two general types of distillation units were used: ASTM distillations and true boiling point distillations. The ASTM distillations were based on the use of either the D-86; D-1130 (Vac Engler); or modified D-1130 (Herzog) units. The true boiling distillation units consisted of either a 2-in diameter by 2-ft long glass column packed with 1/6-in Cannon stainless steel packing, or a 1-in diameter by 18-in long vacuum-jacketed Vigreux column. Both units are equipped with variable reflux heads and a vacuum system capable of 1 mm Hg abs pressure at the reflux head.

2.10 Laboratory Clay Treating Unit

Final purification of finished HEDF products is accomplished by clay treating. A simple laboratory glass column, 1-in diameter by 5-ft long, was charged with adsorbent and feed was allowed to percolate through the column under gravity flow. A second pass can be used to obtain further reduction in trace impurities affecting color, corrosion and other jet fuel specifications.

2.11 Analytical Methods and Calculation Procedures

The characterization tests will consist of performing analytical assays of the COALITE liquids and the Colorado shale oil. Each feedstock was analyzed for the following minimal tests:

1. Elemental Analyses
2. Distillation
3. Specific Gravity
4. Hydrocarbon Type Analyses including % Aromatics
5. Viscosity
6. Aniline Point
7. Bromine Number
8. Heating Value
9. Conradson Carbon Residue (CCR)
10. Solubility in heptane, toluene, quinoline
11. Pour Point
12. Flash Point
13. Diene Number
14. Accelerated Thermal Stability (D-2274)
15. Metals including arsenic
16. Basic Nitrogen

The feeds were also be fractionated into at least three cuts: an IBP-300°F naphtha; a 300-650°F mid-distillate; and a 650°F+ residue. Several mid-distillate cuts were also taken with end-points varying about the nominal 650°F value. The naphtha cuts were analyzed for:

1. Ultimate Analysis
2. Specific Gravity
3. Distillation
4. RI
5. Hydrocarbon Type Analysis
6. Flash Point
7. Octane Number
8. Bromine Number
9. Diene Number
10. Basic Nitrogen

The mid-distillate cuts were be analyzed for:

1. Ultimate Analyses
2. Specific Gravity
3. Distillation

4. Hydrocarbon Type Analyses
5. Flash Point
6. Smoke Point
7. Cetane Number
8. Heating Value
9. ASTM D-873 Residue
10. Freeze Point
11. Basic Nitrogen

The resid cuts were analyzed for ultimate analysis, CCR content, specific gravity, solvent solubilities, distillation, viscosity, and metals content.

The finished HEDF materials were analyzed for the following properties:

1. Elemental Analyses
2. Specific Gravity
3. Heating Value
4. Distillation
5. Hydrocarbon Type Analysis
6. Flash Point
7. Smoke Point
8. Pour Point
9. Aniline Point
10. Stability
11. Cetane Number
12. D-873 Residue
13. Luminometer Number
14. Copper Corrosion
15. Viscosity
16. Color
17. Existent Gum

Intermediate HEDF products were also analyzed for selected properties, such as, specific gravity, heating value, hydrocarbon type analysis and elemental analysis.

The calculation procedures basically consist of determining performance criteria for hydroprocessing operations. These typically include percent removal of heteroatoms (hydrodesulfurization-HDS, hydrodenitrogenation-HDN, and hydrodeoxygenation-HDO); percent hydrocracking of 650F+ components; light gas yield; advanced HEDF yield; and hydrogen consumption. Other correlating parameters of importance include smoke point improvement; API gravity improvement; cetane number improvement; stability and viscosity improvement; percent aromatics reduction; kinetic activation energy and frequency factors. The formulas for some of these parameters are summarized in Table 2.11-1.

Data analysis consists of a combination of approaches. Trendwise correlations of hydroprocessing performance vs. operating conditions were generated from the test data. These are compared to correlations,

TABLE 2.11-1

FORMULAS FOR SELECTED HYDROPROCESSING PARAMETERS(1.) 650°F+ Conversion

This parameter represents the total conversion of the 650°F+ fraction in the synfuel feedstocks to 650°F minus material (liquid and gaseous products including NH₃, H₂S, H₂O, CO_x, etc).

650°F+ Conversion =

$$\frac{\left[\frac{(650^{\circ}\text{F+ in})_{\text{Feed}}}{(650^{\circ}\text{F+ in})_{\text{Feed}}} - \frac{(650^{\circ}\text{F+ out})_{\text{TLP}}}{(650^{\circ}\text{F+ in})_{\text{Feed}}} \right] \times 100}{(650^{\circ}\text{F+ in})_{\text{Feed}}}$$

(2.) Gas Yield

This is determined from wet gas test meter readings and gas analyses (corrected to a dry and H₂ free basis).

Gas Yield =

$$\left(\frac{\text{SCFH Dry Gas}}{379.5} \right) \times \left(\frac{100 - \text{H}_2 \text{ Conc Dry Gas}}{100} \right) \times \left(\frac{\text{Mol. Wt. H}_2 \text{ Free Dry Gas}}{\text{Feed Rate, lbs/hr}} \right)$$

(3.) Net Distillate Make

Net Distillate Make, $\frac{\text{Net make of C5 - 650}^{\circ}\text{F in product}}{100 \text{ lbs } 650^{\circ}\text{F+ in feed}}$

$$= \frac{\left[\frac{650^{\circ}\text{F- out}}{\text{lbs}} - \frac{650^{\circ}\text{F- in}}{650^{\circ}\text{F+}} \right] \times 100}{650^{\circ}\text{F+}}$$

(4.) Desulfurization

The sulfur removal includes the sulfur converted to H₂S as well as any sulfur absorbed by the catalyst.

$$\text{Percent Desulfurization} = \frac{\left[S_{\text{Feed}} - S_{\text{TLP}} \right] \times \frac{\text{Wt. TLP}}{\text{Wt. Feed}}}{S_{\text{Feed}}} \times 100$$

(5.) Denitrogenation

This parameter represents the percent nitrogen converted to NH_3 during a material balance period.

$$\text{Percent Denitrogenation} = \frac{\left[N_{\text{Feed}} - N_{\text{TLP}} \right] \times \frac{\text{Wt. TLP}}{\text{Wt. Feed}}}{(N)_{\text{Feed}}} \times 100$$

(6.) Deoxygenation

This parameter represents the percent oxygen converted to H_2O and CO_x during a material balance period.

$$\text{Percent Denitrogenation} = \frac{\left[O_{\text{Feed}} - O_{\text{TLP}} \right] \times \frac{\text{Wt. TLP}}{\text{Wt. Feed}}}{(O)_{\text{Feed}}} \times 100$$

both in-house as well as in the literature, for similar hydroprocessing operations with other synfuel feedstocks. Where applicable, pseudo-kinetics analyses were performed to help compare hydroprocessing performance for those cases where a constant set of base operating conditions is not readily available.

3.0 FEEDSTOCK ANALYSES

3.1 COALITE Feedstock

This feedstock consists of a nominal 160-1000F boiling range product from the British COALITE carbonization process. The COALITE process was developed in the early 1900's based on the use of a vertical retort. A COALITE plant built in 1936 at the Bolsover Works of Coalite and Chemical Products Ltd is still in operation and the 1000-gal sample was procured and delivered to Lummus in November 1988 by United Coal Company Research Corporation (presently Coal Technology Corporation) of Bristol, VA. The COALITE was produced from a medium coking British coal and is expected to have properties similar to those of U.S. Eastern bituminous coals.

Upon receipt of the 20-drums, 1-quart aliquot samples were taken from each drum and a composite sample of all 20 drums was made. Additionally, grab samples from several of the drums were taken to check the consistency of the liquids from drum to drum. One of the difficulties in analyzing the COALITE is related to its water content and relatively wide boiling range, ca., 160 to about 1000F (71-538C). We found it expedient to first dewater the sample using a rotavap apparatus and then performing the various whole oil and distillate fraction analyses on the dewatered COALITE.

Analytical distillation was accomplished in two steps: atmospheric distillation via the ASTM D-86 procedure followed by vacuum distillation of the atmospheric bottoms using the D-1160 procedure. The consolidated distillation curve for the composite sample is shown on Figure 3.1-1. Figure 3.1-2 shows the quality comparison of the MCG-based COALITE liquids with that of conventional COED pyrolysis (2) oils.

In order to assess the amenability of COALITE distillates to hydroconversion to HEDF materials, it was determined that analytical characterization data on narrow boiling distillate fractions would be of value in formulating a hydroconversion test matrix. One objective of this analytical study was the determination of whether or not there was a sharp break point in cyclic HEDF precursor content with distillate boiling point. The COALITE composite was fractionated in laboratory true boiling point distillation apparatus to recover 16 successive distillate fractions spanning the range of 300-650F (148-343C). The analyses of the individual fractions are shown in Table 3.1-1. Figure 3.1-3 shows the yield curve vs. the volumetric average boiling point (VABP) of the respective distillate fractions. The VABP parameter has also been used as the independent correlating variable in analyzing distillate properties as a function of boiling range.

A heart cut, i.e., 200-550F (93-288C), was also subjected to G.C./M.S. analysis using an SP-1000 column. The sample speciation, as provided by Professor Robert Baldwin of the Colorado School of Mines, is shown on Table 3.1-2.

FIGURE 3.1-1

CONSOLIDATED ASTM D86/D1160 DISTILLATIONS OF DEWATERED COALITE

FIGURE 3.1-2

ASTM DISTILLATIONS OF SYNFUEL FEEDSTOCKS

TABLE 3.1-1
ANALYSES OF NARROW-BOILING COALITE DISTILLATES

CUT #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
CUMULATE WEIGHT % DISTILLED	2.7	4.3	11.6	18.7	27.0	30.9	39.1	41.7	42.9	46.5	46.6	49.5	50.9	54.4	57.8	59.2
SP. GRAVITY	0.835	0.927	0.972	0.972	0.975	0.980	1.005	1.003	1.015	1.023	1.025	1.035	1.035	1.014	1.016	1.028
API GRAVITY	37.96	21.14	14.08	14.08	13.63	12.89	9.30	9.98	7.91	6.82	6.55	5.21	5.21	8.05	7.77	6.15
TBP (6.C.) DISTILLATION, wt %																
TBP	165	307	340	342	366	379	408	407	416	430	431	439	437	454	457	471
10 %	228	345	367	383	401	426	487	484	517	536	536	559	558	589	598	626
30 %	237	354	388	406	442	478	537	533	567	589	590	616	615	646	654	676
50 %	284	375	404	435	482	510	572	568	600	626	627	650	649	678	685	706
70 %	338	388	419	471	516	545	606	602	631	656	657	681	680	709	716	734
90 %	394	414	473	522	575	607	654	653	670	697	698	724	724	755	759	775
99 %	483	450	548	618	704	746	780	785	783	797	795	818	820	846	843	850
FBP	509	460	575	645	743	787	818	824	822	833	830	853	855	882	878	882
VABP	296	375	410	443	483	513	571	568	597	621	622	646	645	675	682	703
ELEMENTAL, wt %																
C	85.18	81.76	80.36	81.80	81.05	83.55	84.34	84.15	84.31	84.65	84.57	85.42	85.05	84.75	84.91	85.04
H	11.34	9.92	9.19	9.41	9.27	9.66	9.33	9.36	9.20	9.10	9.10	8.99	9.00	8.76	8.48	8.52
N	0.30	0.20	0.53	0.63	0.52	0.73	0.92	0.89	0.99	0.94	1.07	1.16	1.12	1.18	1.27	1.33
S	1.27	1.10	0.61	0.46	0.67	1.03	0.90	1.10	1.02	1.02	1.01	1.00	1.03	0.96	0.96	0.90
O (BY DIFF.)	1.91	7.02	9.31	7.70	8.49	5.03	4.51	4.50	4.48	4.29	4.25	3.43	3.80	4.35	4.38	4.21
WT % PARAFFINS	20.60	0.00	0.00	0.00	0.00	0.00	0.00									
WT % OLEFINS	17.50	22.40	20.60	17.60	14.40	15.60	5.30									
WT % NAPHTHENES	8.80	31.66	34.70	22.00	21.40	18.60	7.70									
WT % AROMATICS	53.20	46.10	54.70	60.30	65.50	65.30	87.20									
BROMINE NO.	42	88	83	94	81											
REFRACTIVE INDEX @ 20 C	1.4468	1.4988	1.5224	1.5273	1.5344	1.5400	1.5592	1.5573	1.5657	1.5734	1.5727	1.5815	1.5815	1.5929	1.5955	1.6026

FIGURE 3.1-3

WEIGHT PERCENT DISTILLATE YIELD
AS A FUNCTION OF VOLUMETRIC
AVERAGE BOILING POINT(VABP) OF CUT

TABLE 3.1-2

G.C./M.S. ANALYSIS OF 200-550F COALITE

COALITE MID DISTILLATE (200-550 F)
USING SP-1000 COLUMN

RET TIME	AREA%	COMPOUND NAME
2.077	0.11	paraffin or isoparaffin
2.215	0.14	heptane
2.287	0.06	paraffin or isoparaffin
2.387	0.14	paraffin or isoparaffin
2.491	0.13	octane
2.579	0.22	5-methyl-2-hexanone
2.672	0.06	paraffin or isoparaffin
2.742	0.07	paraffin or isoparaffin
2.788	0.10	paraffin or isoparaffin
2.981	0.36	nonane
3.135	0.05	paraffin or isoparaffin
3.237	0.21	paraffin or isoparaffin
3.356	0.16	paraffin or isoparaffin
3.633	0.09	paraffin or isoparaffin
3.772	0.33	decane
3.862	0.11	paraffin or isoparaffin
3.939	0.14	butyl ester of acetic acid
4.120	0.05	paraffin or isoparaffin
4.228	0.15	paraffin or isoparaffin
4.296	0.80	1,3,5-cycloheptatriene
4.489	0.08	paraffin or isoparaffin
4.716	0.10	paraffin or isoparaffin
4.881	0.55	undecane
5.094	0.07	paraffin or isoparaffin
5.246	0.03	paraffin or isoparaffin
5.357	0.02	big 91
5.459	0.38	big 91
5.559	0.60	dimethyl benzene
5.755	0.03	paraffin or isoparaffin
5.819	0.10	paraffin or isoparaffin
5.985	0.03	paraffin or isoparaffin
6.062	0.11	paraffin or isoparaffin
6.214	1.20	dodecane
6.485	0.07	big 91
6.539	0.17	paraffin or isoparaffin
6.724	0.45	ethyl methyl benzene
6.851	0.27	1-dodecene
6.903	0.24	7-methyl-tridecane
7.008	0.52	trimethyl benzene
7.167	0.09	paraffin or isoparaffin
7.256	0.20	ethyl methyl benzene
7.372	0.08	paraffin or isoparaffin
7.568	0.63	ethyl methyl benzene
7.644	0.86	tridecane
7.723	0.15	paraffin or isoparaffin
7.856	0.23	methyl propyl benzene
7.987	0.11	paraffin or isoparaffin
8.090	0.10	paraffin or isoparaffin
8.178	0.21	ethyl dimethyl benzene
8.251	0.18	paraffin or isoparaffin
8.305	0.50	C13 isoparaffin
8.393	0.28	trimethyl benzene

TABLE 3.1-2 (continued)

8.446	0.51	C13 isoparaffin
8.609	0.25	methyl phenyl pentadecane
8.710	0.43	trimethyl propyl benzene
8.818	0.20	methyl ethyl benzene
8.918	0.31	dihydro Indene
8.991	0.21	trimethyl pyrridine
9.101	1.14	tetradecane
9.212	0.08	paraffin or isoparaffin
9.275	0.28	dihydro-methyl-1H-Indene
9.413	0.42	benzaldehyde
9.634	0.83	5-methyl-5-ethyl decane
9.761	0.43	paraffin or isoparaffin
9.833	0.23	dimethyl benzene
9.890	0.16	paraffin or isoparaffin
9.961	0.24	paraffin or isoparaffin
10.213	0.18	paraffin or isoparaffin
10.308	0.07	paraffin or isoparaffin
10.422	0.15	paraffin or isoparaffin
10.308	0.15	paraffin or isoparaffin
10.422	0.39	benzene compound
10.521	1.16	2-methyl-heptadecane
10.605	0.28	tetramethyl benzene
10.712	0.34	dihydro-dimethyl-1H-Indene
10.788	1.01	dihydro-methyl-1H-Indene
10.986	0.28	paraffin or isoparaffin
11.088	0.30	dihydro-dimethyl-1H-Indene
11.164	0.51	paraffin or isoparaffin
11.284	0.21	paraffin or isoparaffin
11.342	0.10	paraffin or isoparaffin
11.469	0.31	paraffin or isoparaffin
11.558	0.09	paraffin or isoparaffin
11.632	0.11	paraffin or isoparaffin
11.679	0.21	paraffin or isoparaffin
11.754	0.17	paraffin or isoparaffin
11.825	0.14	Indene or benzene compound
11.881	1.49	hexadecane
12.146	0.60	pyrridine compound
12.239	0.70	dihydro-dimethyl-1H-Indene
12.372	0.11	paraffin or isoparaffin
12.426	0.22	Indene or naphthalene compound
12.518	0.40	paraffin or isoparaffin
12.621	0.28	paraffin or isoparaffin
12.698	0.13	paraffin or isoparaffin
12.765	1.01	5-propyl-tridecane
12.964	0.57	dihydro dimethyl-1H-Indene
13.113	0.22	paraffin or isoparaffin
13.194	0.94	9-octyl-heptadecane
13.359	0.70	paraffin or isoparaffin
13.534	0.50	pyrridine compound
13.607	0.42	dihydro-methyl-naphthalene
13.734	0.35	benzene or naphthalene compound
13.815	0.42	paraffin or isoparaffin
14.002	1.56	naphthalene
14.146	0.57	paraffin or isoparaffin
14.357	0.26	paraffin or isoparaffin
14.437	0.79	hexacosane

TABLE 3.1-2 (concluded)

14.583	0.47	triethyl-dihydro-Indene
14.673	0.28	paraffin or isoparaffin
14.800	0.33	nitrogen-containing compound
14.942	0.38	ethyl-propyl-benzimidazole
15.069	0.44	ethyl naphthalene
15.176	0.21	paraffin or isoparaffin
15.212	0.22	paraffin or isoparaffin
15.380	2.26	1-ethylidene-1H-Indene
15.702	1.66	dimethyl phenol
15.819	1.52	methyl naphthalene
16.102	0.52	Indenone compound
16.213	0.48	methyl ethyl phenol
16.313	0.54	paraffin or isoparaffin
16.457	0.56	ethyl naphthalene
16.700	9.61	methyl phenol
16.846	0.80	paraffin or isoparaffin
17.013	0.69	dimethyl naphthalene
17.112	1.52	dimethyl naphthalene
17.237	0.63	paraffin or isoparaffin
17.418	1.20	ethyl phenol
17.571	8.49	dimethyl phenol
17.675	5.22	methyl phenol
17.872	0.85	paraffin or isoparaffin
18.042	0.52	paraffin or isoparaffin
18.112	0.37	paraffin or isoparaffin
18.203	1.21	2-ethyl-4-methyl phenol
18.365	2.10	dimethyl phenol
18.548	1.70	2-ethyl-5-methyl phenol
18.696	4.09	ethyl phenol
18.780	2.20	ethyl phenol
18.982	0.64	phenol compound
19.147	1.15	phenol compound
19.323	2.87	dimethyl phenol
19.480	0.37	paraffin or isoparaffin
19.604	0.48	benzene compound
19.701	0.29	paraffin or isoparaffin
19.830	2.73	ethyl methyl phenol
20.163	0.23	paraffin or isoparaffin
20.289	0.61	paraffin or isoparaffin
20.434	0.48	ethyl methyl phenol
20.491	0.16	pyrrodine or sulfur-containing compound
20.524	0.45	sulfur-containing compound
20.678	0.19	paraffin or isoparaffin
20.818	0.20	paraffin or isoparaffin
20.985	0.52	paraffin or isoparaffin
21.111	0.23	nitrogen- or sulfur-containing compound
21.597	0.77	ar,ar,.alpha.-trimethyl benzenemethanol
21.837	0.19	benzene compound

Figure 3.1-4 shows the H/C atomic ratio of the COALITE distillates as a function of VABP. As expected, the H/C ratio decreases as VABP increases. Also shown on the figure is the H/C ratios required for the HEDF product. The H/C atomic ratio of the raw COALITE distillates has to be improved by approximately 40%.

Figure 3.1-5 shows the API Gravity of the COALITE distillates as a function of VABP. The API of the finished HEDF product should be about 20-40 degrees API higher than that of the raw COALITE 300-650F (148-343C) distillate.

Figures 3.1-6, 7, and 8 show the nitrogen, oxygen and sulfur contents of the COALITE distillates as a function of VABP. Nitrogen content increases linearly with VABP. Oxygen content, as determined by difference, appears to decrease almost linearly with VABP. Sulfur content shows an unusual minima at about 450F (232C) average boiling point and then lines out at a value of about 0.9-1.0 wt percent at higher VABP.

PONA analysis based on the F.I.A./Refractive Index method was used as a measure of hydrocarbon types. The resultant data are presented on Figure 3.1-9. It is to be cautioned that the method may not be accurate for non-petroleum, synfuel-derived distillates such as COALITE. The general trend indicates a continual increase in aromaticity as VABP increases.

Proton NMR spectroscopy was used as an additional analytical tool to assess the hydrogen and carbon distributions in COALITE distillates. Table 3.1-3 shows the NMR parameters for a 390-650F (198-343C) boiling distillate. Figures 3.1-10, 11, and 12 show the NMR hydrogen distributions, carbon distributions and H/C atomic ratios respectively as a function of VABP.

Bromine No., which is a measure of carbon-carbon double bond content, for four lighter COALITE distillates is plotted vs VABP in Figure 3.1-13. There is little effect of VABP on Bromine No. over the range evaluated.

Refractive Index (@ 20C) is a rapid analytical tool and a good measure of distillate quality. Figure 3.1-14 shows the effect of VABP on distillate Refractive Index. Refractive Index can also be used as an independent correlating variable similar to that of the VABP parameter. Figures 3.1-15, 16, 17, and 18 show the dependency of several distillate properties as a function of the Refractive Index. Also shown on the latter four graphs are data published by METC (3) for a variety of full-range coal liquids and shale oils. While the Lummus and METC correlations are not completely congruent, the Refractive Index parameter does show to be a widely usable correlating tool.

3.2 Colorado Shale Oil Feedstock

The programs being performed under this contract are co-funded by the

FIGURE 3.1-4

H/C ATOMIC RATIO OF COALITE DISTILLATE CUTS
AS A FUNCTION OF VOLUMETRIC
AVERAGE BOILING POINT(VABP) OF CUT

FIGURE 3.1-5

API GRAVITY OF COALITE DISTILLATES
AS A FUNCTION OF VOLUMETRIC
AVERAGE BOILING POINT(VABP) OF CUT

FIGURE 3.1-6

NITROGEN CONTENT
AS A FUNCTION OF VOLUMETRIC
AVERAGE BOILING POINT(VABP) OF CUT

FIGURE 3.1-7

WEIGHT PERCENT OXYGEN CONTENT
AS A FUNCTION OF VOLUMETRIC
AVERAGE BOILING POINT(VABP) OF CUT

FIGURE 3.1-8

WEIGHT PERCENT SULFUR CONTENT
AS A FUNCTION OF VOLUMETRIC
AVERAGE BOILING POINT(VABP) OF CUT

FIGURE 3.1-9

PONA ANALYSIS OF SELECTED COALITE DISTILLATES AS A FUNCTION OF VOLUMETRIC AVERAGE BOILING POINT(VABP) OF CUT

TABLE 3.1-3
NMR SPECTROSCOPY OF 390-650°F COALITE

HYDROGEN DISTRIBUTION

ELEMENTAL ANALYSIS %	
H	9.26
C	84.02
(H/C) ELEMENTAL ANALYSIS	1.31
(H/C) NMR	1.34
H AROM/C AROM	0.58
H SAT/C SAT.	2.26
H A POLY, %	12.8
H A MONO	11.3
H F	0
H A1	7.3
H A2	23.7
H B1	9.4
H B2	23.5
H G	12.0
TOTAL H	100.0
H AROM %	24.1
H SAT%	75.9

CARBON DISTRIBUTION

C A POLY	32.8
C A MONO	22.4
C F	0
C A1	4.9
C A2	10.5
C B1	8.4
C B2	15.7
C G	5.3
TOTAL C%	100.0
C AROM %	55.2
C SAT %	44.8
C A SUB %	27.9
C A UNS %	58.4
C A INT %	13.7
C A PER %	86.3
C A INT %	13.7
C NAPHT %	18.8
f AROM	0.552
% AS	32.4
CPER/CINT	6.29
B. I.	0.37
C/H SAT W	5.27
n CHAIN	2.5

FIGURE 3.1-10

HYDROGEN DISTRIBUTION BY HNMR SPECTROSCOPY AS A FUNCTION OF VOLUMETRIC AVERAGE BOILING POINT(VABP) OF CUT

FIGURE 3.1-11

CALCULATED CARBON DISTRIBUTIONS FROM HNMR AS A FUNCTION OF VOLUMETRIC AVERAGE BOILING POINT(VABP) OF CUT

VABP OF DISTILLATE CUT, DEG F

FIGURE 3.1-12

H/C RATIOS FROM PROTON NMR SPECTROSCOPY AS A FUNCTION OF VOLUMETRIC AVERAGE BOILING POINT(VABP) OF CUT

FIGURE 3.1-13

BROMINE NUMBER OF DISTILLATE CUT
AS A FUNCTION OF VOLUMETRIC
AVERAGE BOILING POINT(VABP) OF CUT

FIGURE 3.1-14

REFRACTIVE INDEX @ 20C
AS A FUNCTION OF VOLUMETRIC
AVERAGE BOILING POINT(VABP) OF CUT

FIGURE 3.1-15

API GRAVITY AS A FUNCTION OF REFRACTIVE INDEX OF COALITE DISTILLATE CUTS

FIGURE 3.1-16

H/C ATOMIC RATIO AS A FUNCTION OF REFRACTIVE INDEX OF COALITE DISTILLATE CUTS

FIGURE 3.1-17

HYDROGEN AROMATICITY AS A FUNCTION OF REFRACTIVE INDEX OF COALITE DISTILLATE CUTS

FIGURE 3.1-18

CARBON AROMATICITY AS A FUNCTION OF REFRACTIVE INDEX OF COALITE DISTILLATE CUTS

Coal Projects Management Division/Gasification Branch and by the Extraction Projects Management Division. Thus, there is interest in producing HEDF from both MCG liquids as well as shale oils, tar sands and other liquid synfuels. The Colorado shale oil feedstock is derived from the Unocal retorting facility at Parachute Creek. The 1000-gal sample was provided to Lummus by the Western Research Institute in Laramie, WY.

Upon receipt of the 19-drums, 1-quart aliquot samples were taken from each drum and a composite sample of all 19 drums was made. Additionally, grab samples from several of the drums were taken to check the consistency of the liquids from drum to drum.

Analytical distillation was accomplished in two steps: atmospheric distillation via the ASTM D-86 procedure followed by vacuum distillation of the atmospheric bottoms using the D-1160 procedure. The consolidated distillation curve for the composite sample is shown on Figure 3.2-1. As can be seen from the figure, there is a considerable vac resid component in this material approaching about 35% at 975F (524C) as well as a major quantity of atmospheric resid amounting to 63% at 650F+ (343C). The shale oil is somewhat heavier than the COALITE feed but lighter than a COED bituminous coal-derived pyrolysis oil as can be seen in Figure 3.2-2. Thus, considerable cracking, thermal or catalytic hydrocracking, is required to obtain significant yields of HEDF turbine fuels from this Colorado shale oil feedstock.

In order to assess the amenability of the turbine-range boiling distillates to hydroconversion to HEDF materials, it was determined that analytical characterization data on narrow boiling distillate fractions would be of value in formulating a hydroconversion test matrix. One objective of this analytical study was the determination of whether or not there was a sharp break point in cyclic HEDF precursor content with distillate boiling point. Therefore, the Colorado shale oil composite was fractionated in laboratory true boiling point distillation apparatus in a manner similar to that of the COALITE composite to recover 19 successive distillate fractions spanning the range of 300-700F (148-371C). The analyses of the individual fractions are shown in Table 3.2-1.

Figures 3.2-3 through -10 are presented to show the trends of volumetric average boiling point and refractive index with selected distillate properties. For comparative purposes, the analogous data for the COALITE distillates are also included on the figures.

Figure 3.2-3 shows the H/C atomic ratio of the Colorado shale oil distillate and the COALITE distillate as a function of VABP. As expected, the H/C ratios decrease as VABP increases. Also shown on the figure is the H/C ratios required for the HEDF product. The H/C atomic ratio of the raw Colorado shale oil distillates are essentially equal to that of the HEDF product.

FIGURE 3.2-1
 CONSOLIDATED ASTM DISTILLATION OF RAW
 COLORADO SHALE OIL FEEDSTOCK

FIGURE 3.2-2
ASTM DISTILLATIONS OF SYNFUEL FEEDSTOCKS

TABLE 3.2-1

ANALYSES OF NARROW-BOILING COLORADO SHALE OIL DISTILLATES

CUT #	1,2,3,4,5	7	9	11	12	13	15	17	19
WT % YIELD ON WHOLE OIL	5.5	1.9	3.5	3.5	3.6	3.6	3.7	1.9	1.2
SP.GRAV., g/m/cc	0.7905	0.8448	0.8463	0.8729	0.8805	0.8772	0.9052	0.9162	0.9203
A.P.I. GRAVITY	47.5	36.0	35.7	30.6	29.2	29.8	24.8	22.9	22.3
FBP DISTILLATION, wt %									
IBP F	109	331	397	440	449	474	513	514	498
10%	180	365	426	493	518	550	610	641	661
30%	235	383	447	510	540	572	633	663	685
50%	265	389	456	518	550	581	644	675	698
70%	300	395	464	526	564	588	656	685	707
90%	344	408	482	544	580	603	668	694	716
EBP	438	628	662	773	793	816	815	842	829
VABP	265	388	455	518	550	579	642	672	693
ELEMENTAL, wt %									
C	85.50	84.48	84.64	84.75	84.34	84.70	84.32	84.50	84.35
H	12.42	12.92	13.08	12.51	12.28	12.65	11.87	11.75	11.68
N	0.48	0.98	0.84	0.96	1.21	1.31	1.50	1.60	1.70
S	1.14	1.00	0.86	1.08	1.12	0.88	1.00	1.00	0.92
O (BY DIFF.)	0.46	0.62	0.56	0.70	1.05	0.46	1.31	1.15	1.35
WT % PARAFFINS	31.40	16.10	8.70	0.00	0.00	0.00			
WT % OLEFINS	32.80	33.30	39.10	37.30	40.90	37.50			
WT % NAPHTHENES	0.00	27.50	34.80	41.40	37.70	39.10			
WT % AROMATICS	35.80	23.10	17.40	21.30	21.40	23.40			
REFRACTIVE INDEX @20 C	1.4439	1.4555	1.4667	1.4822	1.4874	1.4840	1.5017	1.5084	1.5122

FIGURE 3.2-3

H/C ATOMIC RATIO OF SYNFUEL DISTILLATES AS A FUNCTION OF VOLUMETRIC AVERAGE BOILING POINT(VABP)

FIGURE 3.2-4

API GRAVITY OF SYNFUEL DISTILLATES AS A FUNCTION OF VOLUMETRIC AVERAGE BOILING POINT(VABP)

FIGURE 3.2-5

NITROGEN CONTENT OF SYNFUEL DISTILLATES AS A FUNCTION OF VOLUMETRIC AVERAGE BOILING POINT(VABP)

FIGURE 3.2-6

WEIGHT PERCENT SULFUR CONTENT OF SYN-FUEL DISTILLATES AS A FUNCTION OF VOLUMETRIC AVERAGE BOILING POINT(VABP)

VABP OF DISTILLATE CUT, DEG F

FIGURE 3.2-7

PONA ANALYSIS OF SYNFUEL DISTILLATES AS A FUNCTION OF VOLUMETRIC AVERAGE BOILING POINT(VABP)

VABP OF DISTILLATE CUT, DEG F

FIGURE 3.2-8

NMR CARBON DISTRIBUTION FOR COALITE AND COLO SHALE OIL AS A FUNCTION OF DISTILLATE VABP

VABP OF DISTILLATE CUT, DEG F

FIGURE 3.2-9

REFRACTIVE INDEX OF SYNFUEL DISTILLATES AS A FUNCTION OF VOLUMETRIC AVERAGE BOILING POINT(VABP)

FIGURE 3.2-10

NMR CARBON DISTRIBUTION FOR COALITE AND COLO SHALE OIL AS A FUNCTION OF REFRACTIVE INDEX

REFRACTIVE INDEX @ 20C

Figure 3.2-4 shows the API Gravity of the two synfuel distillates as a function of VABP. The Colorado shale oil has a considerably higher API gravity across the VABP range evaluated but its rate of decline with VABP is about 33% higher than that of the COALITE. Figures 3.2-5 and 6 show the nitrogen and sulfur contents of the two synfuel distillates as a function of VABP. Nitrogen content increases almost linearly with VABP for both distillates with the shale oil having about a 2000 ppmw higher N content than the COALITE. While the sulfur content of the COALITE distillates shows an unusual minima at about 450F (232C) average boiling point, the Colorado shale oil-derived sulfur exhibits a broad maxima at about 325-425F (163-218C). The heavier shale oil and COALITE distillates, ca., 600-700F (315-371C), have essentially the same sulfur content, namely, 0.8-1.0 wt percent.

PONA analysis based on the F.I.A./Refractive Index method was used as a measure of hydrocarbon types. The resultant data are presented on Figure 3.2-7. It is to be cautioned that the method may not be accurate for non-petroleum, synfuel-derived distillates such as shale oil or COALITE. While the COALITE aromatics exhibit an increasing trend with VABP, the shale oil aromatics first decrease and then line out at the higher VABP. As expected, the shale oil aromatics contents are significantly lower than those of the COALITE, especially for the higher boiling distillates.

Proton NMR spectroscopy was used as an additional analytical tool to assess the carbon distributions in the shale oil and COALITE distillates. Figure 3.2-8 shows the NMR carbon distributions as a function of VABP. The shale oil distillates have about a 10-15 mol percent lower cyclic content (naphthenes plus aromatics) than that of the COALITE. However, the desirable naphthenic content, with the latter being key components of HEDF fuels, of the shale oil distillates is some 15-30 mol percent higher than that of the COALITE.

Refractive Index (@ 20C) is a rapid analytical tool and a good measure of distillate quality. Figure 3.2-9 shows the effect of VABP on distillate Refractive Index for the two synfuel distillates. Refractive Index can also be used as an independent correlating variable similar to that of the VABP parameter. Figure 3.2-10 shows the dependency of NMR carbon distribution as a function of the Refractive Index. This type of plot illustrates the major difference in compositional variations between the two feedstocks reflecting a discontinuity at a refractive index level of about 1.520.

4.0 SCREENING PROGRAM OPERATING CHRONOLOGY

4.1 Overview

The major goals of the screening program were to: a) pinpoint those processing routes that would result in the production of high energy density turbine fuels (HEDF) meeting or exceeding the minimum energy density specification of 130,000 Btu/gal; and b) collect sufficient processing data on the alternative processing routes for use in the subsequent Task 4 economic modelling study. A third goal was the collection of liter size samples of HEDF products for transmittal to DOE-METC.

The methodology chosen was to perform process variable scans in selected existing test units for each of the candidate processing schemes identified in the project management plan. As with any exploratory R&D program, deviations from the original plan are to be expected as emerging test data are acquired. The direction taken during the course of the screening program was always towards the scanning of conditions that would result in achieving the maximum HEDF product energy density. The key processing routes evaluated are as follows:

- o Raw distillate hydrotreating (single and two-stage)
- o Raw atmospheric resid hydrocracking (LC-FiningSM)
- o Vacuum gas oil hydrocracking
- o Raw atmospheric resid delayed coking
- o Cracked distillate hydrotreating
- o Hydrotreated distillate extraction (shale oil only)

These tests were carried out in five different bench-scale facilities. Additionally, test data were collected for the ancillary HEDF manufacturing processes of fractionation and clay treating. In order to maximize the operating efficiency of our pilot plant/analytical staffs and thereby maximize the return on the research investment, the scheduling of the various tests did not follow any predetermined order. Thus, operating campaigns with the COALITE feedstocks were intermingled with the Colorado shale oil feedstock campaigns. By necessity, the cracked distillate hydrotreating campaigns had to follow the hydrocracking and the delayed coking campaigns since these latter operations produced the cracked distillate feedstocks.

4.2 COALITE Operations

4.2.1 Feedstock Preparation

The raw COALITE feedstock was fractionated in the 4-in Batch Distillation unit in four different campaigns. The initial fractionation, referred to as CC-1, resulted in the collection of

sixteen successive distillate cuts and a vacuum resid fraction. The bulk of these materials was used for the analytical characterization tests (described in Section 3), the delayed coking evaluation of the 650F+ resid, and the LC-Fining evaluation of the 650F+ (343C+) resid.

Batch fractionation CC-2 resulted in the collection of 24 distillate fractions and a 670F+ (354C) resid fraction. Two composite blends for distillate hydrotreating were made: a nominal 350-650F (177-343C) blend of distillate fractions 5 through 22 to simulate a Category III boiling-range fuel; and a nominal 350-550F (177-288C) blend of distillate fractions 5 through 14 to simulate a Category I boiling-range fuel. Two additional blends were made with heavier end points (i.e., 750F and 820F) to determine whether the addition of the heavier gas oil components could increase energy densities above and beyond the 130,000 Btu/gal specification.

It should be kept in mind that the final Initial Boiling Point and End Point of the finished HEDF product is set in a post-hydrogenation topping and tailing operation. The nominal ranges of the feeds could not be fine-tuned in advance of and during the screening test work until sufficient information was acquired on the interaction of the process variables on all of the specified HEDF properties. Thus, the approach taken was to use the post-hydrogenation distillation operations to fine tune the critical distillation temperatures controlling the volatility (i.e., flash point spec) and the back-end viscosity/freeze point spec. Of course, in a commercial operation, the design of the fractionation systems would be optimized to reduce the cost of any unnecessary towers.

Batch fractionations CC-3 and CC-4 were used to prepare 300F+ (149C+) dewatered product for use in the selective hydrocracking campaigns and for use in preparing hydrotreated resid for a delayed coking test. Table 4.2.1-1 presents the properties of the raw mid-distillate cuts used as feedstocks in the distillate hydrotreating campaigns.

4.2.2 Virgin Distillate Hydrotreating Campaigns

Six virgin distillate hydrotreating campaigns were made with the COALITE distillates to study the effects of catalyst type, distillate boiling range, single-stage vs two-stage, recycle of first-pass hydrotreated product and severity as controlled by space velocity, hydrogen partial pressure and reactor temperature. A Severity function has been defined as follows:

$$\text{Severity} = 10^4 * \text{H2 Press, psig} * \text{LHSV}^{-1} * \exp\{-35000/[1.987 * T_{\text{avg}}, R]\}$$

A total of 59 material balance tests were made of durations extending from 2-hours to 36-hours. The following table summarizes the salient features of each campaign and the summary table reference number.

TABLE 4.2.1-1

HYDROTREATING FEEDSTOCK ANALYSES OF RAW COALITE MID-DISTILLATE

Nominal Boiling Range, °F	350-550 °F	350-650 °F	300-750 °F	300-820 °F
R. I. @ 20°C	1.5327	1.5469	1.5445	1.5561
Sp. Grav., g/cc	0.9772	0.9923	0.9902	1.0050
API Gravity	13.3	11.1	11.4	9.3
Distillation, °F				
IBP	D86/TBP-GC	D86/TBP-GC	TBP-GC	
10%	394/345	390/364	335	
30%	416/389	422/409	384	
50%	438/436	460/478	454	
70%	460/478	504/531	522	
90%	488/512	552/588	590	
EBP	518/562	616/658	685	
VABP	550/816	652/851	828	
	465/505	531/572	527	
Watson K, R	9.70/10.04	9.98/10.12	9.89	
Elemental, Wt. %				
C	83.11	84.00	82.55	
H	9.44	9.26	9.62	
N	0.60	0.81	0.81	
S	0.63	0.73	0.88	
O (By Diff.)	6.22	5.20	6.14	
F.I.A./R.I., Liq. Vol%				
Paraffins	0.0	0.0	---	
Olefins	13.4	11.8	---	
Naphthenes	22.5	11.7	---	
Aromatics	64.1	76.5	---	
WLHV, btu/lb	15880	16059	15793	
VLHV, btu/gal	129264	132741	130266	
Viscosity, cs @ -4 °F	---	4.0	---	
Pour Pt., °F	<20	5	---	
Aniline Pt., °F	28.0	34.5	---	
Diesel Index	3.7	3.8	---	
Smoke Pt.	9	7	---	
Luminometer No.	32.0	29.0		

<u>CAMPAIGN #</u>	<u># STAGES</u>	<u>CATALYST TYPE</u>	<u>FEED BOILING RANGE</u>	<u>#TESTS</u>	<u>TABLE #</u>
1	1	K-550	350-650F	30	4.2.2-1
2	1	K-550	350-550F	8	4.2.2-2
3	2	K-550/K-550	350-750F;350-820F	8	4.2.2-3
4	2	K-550/K-599	350-650F	7	4.2.2-4
5	1	K-599	350-650F	2	4.2.2-5
6	1	Ca-doped K-550	350-650F	4	4.2.2-6

Campaign 5 was also used for the production of liter-size samples of finished HEDF samples required as a Task 3 deliverable. The specific objectives of each of these six campaigns are summarized below:

- Campaign 1: Initial scans to evaluate the effects of space velocity, reaction temperature, hydrogen partial pressure and single-pass product recycle with a candidate NiWS hydrotreating catalyst in a single-stage reactor using the 350-650F COALITE distillate.
- Campaign 2: Initial scans to evaluate the effects of space velocity, reaction temperature and single-pass product recycle with a candidate NiWS hydrotreating catalyst in a single-stage reactor using the 350-550F COALITE distillate.
- Campaign 3: Initial scans to evaluate the effects of temperature and space velocity with higher end point COALITE distillates using a two-stage NiWS catalyst reaction system.
- Campaign 4: Initial scans to evaluate the effects of temperature and space velocity with the 350-650F COALITE distillate in a two-stage reactor system comprising a NiWS catalyst in the first-stage and a high moly nickel catalyst in the second-stage reactor.
- Campaign 5: Production run to produce liter size samples of HEDF materials in a single-stage reactor with the high moly nickel catalyst using the 350-650F COALITE distillate.
- Campaign 6: Scans of the effects of temperature and space velocity with a calcium-doped NiWS catalyst using the 350-650F COALITE distillate.

4.2.3 Virgin Atmospheric Resid Cracking Campaigns

There is a considerable yield of atmospheric resid in the raw COALITE. HEDF products are end-point limited because of viscosity and freeze point specifications. Therefore, it is necessary to crack the heavier components to the mid-distillate range comprising the desired HEDF turbine fuel products. Three cracking methods were considered: 1) Resid hydrocracking using the LC-Finingtm process; 2) Delayed Coking; and 3) VGO fixed-bed hydrocracking. The former two are discussed in

TABLE 4.2.2-1

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTB01.WK1

TEST # (FB-)	17A-1	17A-2	18A-1	18A-2	18A-3	19A-1	19A-2	19A-3
DATE (1989)	01-13	01-13	01-16	01-16	01-16	01-17	01-17	01-17
START TIME	14:30	16:30	12:30	14:45	19:00	12:30	15:00	18:20
END TIME	16:30	17:30	13:30	15:45	21:00	13:30	17:00	20:20
FEEDSTOCK	A	A	A	A	A	A	A	A
FEED RATE, cc/hr	1542	590	372	373	167	154	155	135
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H2 PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H2 TREAT RATE, scf/bbl	3000	3000	5000	5000	5000	5000	5000	5000
REACTOR 1 CONDITIONS								
LHSV, cc/hr/cc cat.	9.6	3.7	2.3	2.3	1.0	1.0	1.0	0.8
INLET BED TEMP., F	371	393	499	602	606	609	644	605
UPPER MID BED TEMP., F								
LOWER BED TEMP., F	396	404	507	672	654	628	704	667
AVERAGE BED TEMP., F	384	399	503	637	630	619	674	636
SAND BATH TEMP., F	399	404	579	606	577	606	534	481
REACTOR 2 CONDITIONS								
LHSV, cc/hr/cc cat.								
INLET BED TEMP., F								
UPPER MID BED TEMP., F								
LOWER BED TEMP., F								
AVERAGE BED TEMP., F								
SAND BATH TEMP., F								
SEVERITY STAGE 1	0.0018	0.0067	0.0992	0.9259	1.9210	1.6169	3.5959	2.6233
SEVERITY STAGE 2								
OVERALL SEVERITY	0.0018	0.0067	0.0992	0.9259	1.9210	1.6169	3.5959	2.6233

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

TABLE 4.2.2-1 (continued)

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTB01.WK1

TEST # (FB-)	20A-1	20A-2	21	22	23	24	25	26
DATE (1989)	01-18	01-18	01-19	01-20	01-20	01-23	01-23	01-24
START TIME	16:20	19:00	19:00	16:45	19:30	17:45	20:45	15:20
END TIME	18:20	21:00	21:00	17:45	20:30	18:45	21:45	16:30
FEEDSTOCK	A	A	A	A	A	A	A	A
FEED RATE, cc/hr	152	144	107	109	106	150	151	166
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2400	2400	1600
H2 PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2400	2400	1600
H2 TREAT RATE, scf/bbl	5000	5000	5000	5000	5000	5000	5000	5000
REACTOR 1 CONDITIONS								
LHSV, cc/hr/cc cat.	1.0	0.9	0.7	0.7	0.7	0.9	0.9	1.0
INLET BED TEMP., F	589	602	612	621	650	601	560	651
UPPER MID BED TEMP., F								
LOWER BED TEMP., F	696	617	660	691	659	602	684	678
AVERAGE BED TEMP., F	643	610	636	656	655	602	622	665
SAND BATH TEMP., F	541	599	559	579	643	601	544	654
REACTOR 2 CONDITIONS								
LHSV, cc/hr/cc cat.								
INLET BED TEMP., F								
UPPER MID BED TEMP., F								
LOWER BED TEMP., F								
AVERAGE BED TEMP., F								
SAND BATH TEMP., F								
SEVERITY STAGE 1	2.3072	1.5659	2.9981	3.9987	3.9146	1.6598	2.2729	2.5230
SEVERITY STAGE 2								
OVERALL SEVERITY	2.3072	1.5659	2.9981	3.9987	3.9146	1.6598	2.2729	2.5230

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

TABLE 4.2.2-1 (continued)

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTB02.WK1

TEST # (FB-)	27	28	29	37	38	39	40	41
DATE (1989)	01-24	01-24	01-25	02-02	02-02	02-03	02-03	02-03
START TIME	17:45	20:15	16:40	11:30	20:15	10:35	13:35	17:30
END TIME	18:45	21:15	17:40	19:00	21:45	12:05	15:05	18:45
FEEDSTOCK	A	A	A	A	A	B	B	A
FEED RATE, cc/hr	154	226	164	120	130	109	109	247
OPERATING PRESSURE, psig	1600	1600	2000	2000	2000	2000	2000	2000
H2 PARTIAL PRESSURE, psig	1600	1600	2000	2000	2000	2000	2000	2000
H2 TREAT RATE, scf/bbl	5000	5000	5000	5000	5000	5000	5000	5000
REACTOR 1 CONDITIONS								
LHSV, cc/hr/cc cat.	1.0	1.4	1.0	0.75	0.8	0.68	0.68	1.5
INLET BED TEMP., F	703	653	701	703	739	699	700	692
UPPER MID BED TEMP., F								
LOWER BED TEMP., F	713	699	696	718	743	701	705	753
AVERAGE BED TEMP., F	708	676	699	711	741	700	703	723
SAND BATH TEMP., F	698	657	681	697	724	696	703	714
REACTOR 2 CONDITIONS								
LHSV, cc/hr/cc cat.								
INLET BED TEMP., F								
UPPER MID BED TEMP., F								
LOWER BED TEMP., F								
AVERAGE BED TEMP., F								
SAND BATH TEMP., F								
SEVERITY STAGE 1	4.52	2.11	4.99	7.78	10.69	7.49	7.74	4.53
SEVERITY STAGE 2								
OVERALL SEVERITY	4.52	2.11	4.99	7.78	10.69	15.27	7.74	4.53

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

B: LIQUID PRODUCT FROM FB-37.

TABLE 4.2.2-1 (concluded)

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTB02.WK1

TEST # (FB-)	42	43	46	47	48	49
DATE (1989)	02-06	02-06	02-21/22	02-22	02-23	02-24
START TIME	12:05	18:45	03:45	05:45	02:00	00:00
END TIME	17:35	20:40	04:00	24:00	22:00	20:00
FEEDSTOCK	A	C	A	D	A	A
FEED RATE, cc/hr	104	104	113	114	113	140
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2000
H2 PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000
H2 TREAT RATE, scf/bbl	5000	5000	5000	5000	5000	5000
REACTOR 1 CONDITIONS						
LHSV, cc/hr/cc cat.	0.7	0.65	0.7	0.7	0.7	0.88
INLET BED TEMP., F	738	737	702	697	737	623
UPPER MID BED TEMP., F						
LOWER BED TEMP., F	739	735	716	708	741	615
AVERAGE BED TEMP., F	739	736	709	703	739	619
SAND BATH TEMP., F	739	729	695	606	724	602
REACTOR 2 CONDITIONS						
LHSV, cc/hr/cc cat.						
INLET BED TEMP., F						
UPPER MID BED TEMP., F						
LOWER BED TEMP., F						
AVERAGE BED TEMP., F						
SAND BATH TEMP., F						
SEVERITY STAGE 1	11.85	12.38	8.18	7.52	11.92	1.85
SEVERITY STAGE 2						
OVERALL SEVERITY	11.85	24.23	8.18	15.70	11.92	1.85

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

C: LIQUID PRODUCT FROM FB-42.

D: LIQUID PRODUCT FROM FB-46.

TABLE 4.2.2-2

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTB03.WK1

TEST # (FB-)	30	31	32	33	34	35	36-1	36-2
DATE (1989)	01-25	01-25	01-26	01-26	01-27	01-27	01-30	01-30
START TIME	19:00	20:55	12:55	16:15	13:25	16:45	13:40	14:10
END TIME	20:00	21:55	13:55	22:00	14:10	18:45	14:10	14:40
FEEDSTOCK	A	A	A	A	B	B	C	C
FEED RATE, cc/hr	160	159	157	156	136	104	108	102
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H2 PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H2 TREAT RATE, scf/bbl	5000	5000	5000	5000	5000	5000	5000	5000
REACTOR 1 CONDITIONS								
LHSV, cc/hr/cc cat.	1.0	1.0	1.0	1.0	0.85	0.65	0.67	0.64
INLET BED TEMP., F	709	659	606	700	701	699	698	698
UPPER MID BED TEMP., F								
LOWER BED TEMP., F	696	668	636	694	693	698	702	700
AVERAGE BED TEMP., F	703	664	621	697	697	699	700	699
SAND BATH TEMP., F	680	649	605	681	679	694	700	696
REACTOR 2 CONDITIONS								
LHSV, cc/hr/cc cat.								
INLET BED TEMP., F								
UPPER MID BED TEMP., F								
LOWER BED TEMP., F								
AVERAGE BED TEMP., F								
SAND BATH TEMP., F								
SEVERITY STAGE 1	5.2623	3.1100	1.6792	4.8966	5.7607	7.6832	7.6018	7.8546
SEVERITY STAGE 2								
OVERALL SEVERITY	5.2623	3.1100	1.6792	4.8966	10.6573	12.5798	20.1700	20.4300

FEEDSTOCK TYPE:

A: 350-550 F VIRGIN COALITE DISTILLATE.

B: LIQUID PRODUCT FROM FB-33.

C: LIQUID PRODUCT FROM FB-34/FB-35.

TABLE 4.2.2-3

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)/K-550 (2ND STAGE)		FILE ID: REPTB04.WK1						
TEST # (FB-)	169	172	170	173	174	175	176	177
DATE (1989)	06-27	06-29	06-28	06-29	06-30	06-30	06-30	06-30
START TIME	04:30	09:00	00:00	15:30	22:00	02:00	06:00	10:00
END TIME	20:00	10:00	12:00	20:00	24:00	04:00	08:00	20:00
FEEDSTOCK	A	A	B	B	B	B	B	B
FEED RATE, cc/hr	124	119	118	120	124	118	116	117
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H ₂ TREAT RATE, scf/bbl	8000	8000	8000	8000	8000	8000	8000	8000
REACTOR 1 CONDITIONS								
LHSV, cc/hr/cc cat.	0.75	0.72	0.72	0.73	0.75	0.72	0.70	0.71
INLET BED TEMP., F	720	683	720	662	648	625	600	632
UPPER MID BED TEMP., F	676	662	674	659	646	624	598	639
LOWER BED TEMP., F	660	649	662	643	634	615	593	629
AVERAGE BED TEMP., F	685	665	685	655	643	621	597	633
SAND BATH TEMP., F	651	638	655	630	620	607	586	613
REACTOR 2 CONDITIONS								
LHSV, cc/hr/cc cat.	0.75	0.72	0.72	0.73	0.75	0.72	0.70	0.71
INLET BED TEMP., F	713	695	717	658	644	616	593	627
UPPER MID BED TEMP., F	723	702	721	675	650	624	600	636
LOWER BED TEMP., F	713	720	705	643	655	625	600	621
AVERAGE BED TEMP., F	718	699	719	667	647	620	597	632
SAND BATH TEMP., F	715	693	715	659	643	617	595	629
SEVERITY STAGE 1	5.58	4.38	5.86	3.78	3.08	2.36	1.65	2.85
SEVERITY STAGE 2	8.55	6.92	9.10	4.46	3.28	2.31	1.64	2.77
OVERALL SEVERITY	14.13	11.31	14.96	8.24	6.35	4.67	3.29	5.62

FEEDSTOCK TYPE:

A: 350-750F RAW COALITE DISTILLATE
B: 350-820F RAW COALITE DISTILLATE

TABLE 4.2.2-4

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)/K-599 (2ND STAGE)

FILE ID: REPTB05.WK1

TEST # (FB-)	94-1	94-2	94-3	101	102	103	104
DATE (1989)	04-05	04-06	04-06	04-10	04-10	04-10	04-10
START TIME	21:00	01:00	05:00	05:00	09:30	14:00	18:00
END TIME	01:00	05:00	09:00	06:30	11:00	15:30	20:00
FEEDSTOCK	A	A	A	A	A	A	A
FEED RATE, cc/hr	116	116	115	124	110	118	119
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000
H2 PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000
H2 TREAT RATE, scf/bbl	7000	7000	7000	7000	7000	7000	7000
REACTOR 1 CONDITIONS							
LHSV, cc/hr/cc cat.	0.7	0.7	0.7	0.75	0.7	0.7	0.7
INLET BED TEMP., F	616	621	624	402	400	399	399
UPPER MID BED TEMP., F	671	692	696	402	400	400	399
LOWER BED TEMP., F	617	614	616	403	400	400	400
AVERAGE BED TEMP., F	635	642	645	402	400	400	399
SAND BATH TEMP., F	595	596	598	402	400	400	398
REACTOR 2 CONDITIONS							
LHSV, cc/hr/cc cat.	0.7	0.7	0.7	0.75	0.7	0.7	0.7
INLET BED TEMP., F	628	628	627	632	660	739	772
UPPER MID BED TEMP., F	623	625	624	653	705	704	701
LOWER BED TEMP., F	615	620	620	618	633	663	671
AVERAGE BED TEMP., F	622	624	624	634	666	702	715
SAND BATH TEMP., F	608	618	618	611	626	660	670
SEVERITY STAGE 1	2.9399	3.2880	3.4338	0.0360	0.0364	0.0362	0.0359
SEVERITY STAGE 2	2.4352	2.5220	2.4970	2.7305	4.6003	7.4687	8.7948
OVERALL SEVERITY	5.3752	5.8101	5.9307	2.7665	4.6367	7.5048	8.8307

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

TABLE 4.2.2-5

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-599 (1ST STAGE)

FILE ID: REPTB05.WK1

TEST # (FB-)	146	147
DATE (1989)	05-16/18	05-18/19
START TIME	18:30	08:30
END TIME	06:30	20:30
FEEDSTOCK	A	B
FEED RATE, cc/hr	118	115
OPERATING PRESSURE, psig	2000	2000
H2 PARTIAL PRESSURE, psig	2000	2000
H2 TREAT RATE, scf/bbl	8000	8000
REACTOR 1 CONDITIONS		
LHSV, cc/hr/cc cat.		
INLET BED TEMP., F		
UPPER MID BED TEMP., F		
LOWER BED TEMP., F		
AVERAGE BED TEMP., F		
SAND BATH TEMP., F		
REACTOR 2 CONDITIONS		
LHSV, cc/hr/cc cat.	0.7	1
INLET BED TEMP., F	744	717
UPPER MID BED TEMP., F	684	716
LOWER BED TEMP., F	663	714
AVERAGE BED TEMP., F	697	716
SAND BATH TEMP., F	643	714
SEVERITY STAGE 1	6.8966	8.9077
SEVERITY STAGE 2		
OVERALL SEVERITY	6.8966	8.9077

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.
 B: LIQUID PRODUCT FROM FB-146.

TABLE 4.2.2-6

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: CACIUM PROMOTED K-550

FILE ID: REPTCA1.WK1

TEST # (FB-)	135	136	137	138
DATE (1989)	04-26/27	04-27/28	04-28	04-28
START TIME	21:00	17:00	13:00	18:30
END TIME	13:00	09:00	15:00	20:30

FEEDSTOCK	A	A	A	A
FEED RATE, cc/hr	120	122	136	161
OPERATING PRESSURE, psig	2000	2000	2000	2000
H2 PARTIAL PRESSURE, psig	2000	2000	2000	2000
H2 TREAT RATE, scf/bbl	7000	7000	7000	7000

REACTOR 1 CONDITIONS

LHSV, cc/hr/cc cat.	0.7	0.7	0.8	1.0
INLET BED TEMP., F	708	712	641	615
UPPER MID BED TEMP., F	643	707	658	625
LOWER BED TEMP., F	634	691	657	621
AVERAGE BED TEMP., F	662	703	652	620
SAND BATH TEMP., F	623	680	616	591

REACTOR 2 CONDITIONS

LHSV, cc/hr/cc cat.	
INLET BED TEMP., F	
UPPER MID BED TEMP., F	
LOWER BED TEMP., F	

AVERAGE BED TEMP., F	
SAND BATH TEMP., F	

SEVERITY STAGE 1	4.1526	7.2872	3.2251	1.7138
SEVERITY STAGE 2				
OVERALL SEVERITY	4.1526	7.2872	3.2251	1.7138

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

the next two sections while the latter is discussed in Section 4.2.5.

4.2.3.1 LC-Finingtm (Residue Hydrocracking)

LC-Finingtm, a service mark of Lummus and its co-licensors for engineering, marketing and technical services relating to hydrocracking and hydrodesulfurization processes for reduced crude and residual oils, is a commercial technology for upgrading heavy oils. In the context of the COALITE HEDF application, LC-Finingtm has been used to hydrotreat long residues (ca., 300F+) and to hydrocrack the 650F+ (343C+) components into the HEDF boiling ranges. In the screening program, a stirred autoclave simulator of the LC-Finingtm process was used to collect the required data. Three feedstocks were considered: 1) a virgin or raw 650F+ (343C+) atmospheric resid fraction of the raw COALITE; 2) a virgin 300F+ (148C+) long resid fraction; and 3) a hydrotreated 575F+ (301C+) atmospheric resid fraction. The analyses of these three feedstocks are presented in Table 4.2.3.1-1. The objectives of these three campaigns were as follows:

- o Evaluate the first-pass reactivity of the virgin 650F+ atmospheric resid fraction towards hydrocracking and the production of hydrocracked HEDF-boiling range materials;
- o Evaluate the hydrocracking reactivity of the first-pass unconverted (575F+) atmospheric resid recovered from the virgin 650F+ LC-Finingtm tests of the above campaigns; and
- o Prepare hydrotreated gas oil (650-975F) for downstream selective fixed-bed hydrocracking campaigns by subjecting the 300F+ long resid to mild LC-Finingtm.

The summary of the operating conditions for these campaigns is presented in Table 4.2.3.1-2 and -3.

4.2.3.2 Delayed Coking

Delayed Coking is another alternative technology for upgrading heavy oils to lighter products, such as HEDF materials. However, Delayed Coking is not as selective as hydrocracking and results in the production of a variety of byproducts, the predominant one being coke. On the other hand, Delayed Coking is much less capital intensive than hydrocracking and the differential HEDF yield losses are modulated by lower capital and operating costs. The choice of Delayed Coking vs LC-Finingtm (residue hydrocracking) is an economic one and the preferred technology will be based on the results of the subsequent Task 4 economic optimization studies using a refinery linear programming computer model.

Three Delayed Coking tests were made in the Continuous Bench Coker (CBC) unit, two with virgin 650F+ atmospheric residua and one with a hydrotreated resid. Table 4.2.3.2-1 presents a summary of the feedstock properties. Two delayed coking severities were investigated: a) 100 psig coke drum pressure; and b) 25 psig coke drum pressure, all other conditions kept constant. The detailed operating conditions for the three tests are presented in Table 4.2.3.2-2.

TABLE 4.2.3.1-1

FEEDSTOCK ASSAYS FOR LC-FINING OF COALITE RESIDUA

<u>Coalite Type</u> <u>IBP, °F</u>	<u>Virgin</u> <u>300</u>	<u>Virgin</u> <u>650</u>	<u>Hydrotreated</u> <u>575</u>
Sp. Grav., g/cc	1.0513	1.1678	1.0143
A.P.I. Gravity	3.1	-10.3	8.0
Distillation, °F			
IBP	407	294	---
10%	447	703	
30%	512	753	
50%	657	812	
70%	776	946	
90%			
EBP	950 (84.8%)	950 (77%)	
Elemental, Wt.%			
C	85.10	85.47	88.25
H	8.53	7.75	9.18
N	1.06	1.18	0.87
S	0.81	0.75	0.09
Ash	0.01	0.01	0.01
O (By Diff.)	4.50	4.84	1.60

TABLE 4.2.3.1-2

SUMMARY OF OPERATING CONDITIONS FOR LC-FINING TESTS

CATALYST: SHELL 324 M (AGED)

TEST # (BLCF-)	86-1	86-2	87	88-1/2	88-3	88-4	88-5	100	101
DATE (1989)	01-31	02-01	02-08	02-27/28	02-28/03-01	03-1/2	03-2/3	05-17/19	06-13/16
START TIME	19:00	07:00	02:00	15:30	16:30	09:00	07:30	20:00	08:00
END TIME	23:00	15:00	16:00	16:30	09:00	07:30	18:00	19:30	02:30
FEEDSTOCK	A	A	A	A	A	A	A	B	B
FEED RATE, cc/hr	137	73	65	264	273	269	265	697	732
OPERATING PRESSURE, psig	2200	2200	2200	2200	2200	2200	2200	2000	2000
H2 PARTIAL PRESSURE, psig	2200	2200	2200	2200	2200	2200	2200	2000	2000
H2 TREAT RATE, scf/bbl	10000	10000	10000	10000	10000	10000	10000	7000	7000
LHSV, cc/hr/cc cat.	0.91	0.49	0.43	0.53	0.55	0.54	0.53	1.4	1.5
LHSV, cc/hr/cc react.vol.	0.54	0.29	0.26	0.26	0.27	0.27	0.27	0.70	0.73
INLET SLURRY TEMP., F	650	610	630	730	748	746	743	700	768
UPPER SLURRY TEMP., F	800	800	816	744	779	796	799		
LOWER SLURRY TEMP., F	793	795	809	566	604	616	617	550	532
AVERAGE SLURRY TEMP., F	746	735	752	680	710	719	720	625	650

FEEDSTOCK TYPE:

A: 650 F+ VIRGIN ATMOSPHERIC RESID.

B: 300 F+ VIRGIN ATMOSPHERIC RESID.

TABLE 4.2.3.1-3

SUMMARY OF OPERATING CONDITIONS FOR LC-FINING TESTS

CATALYST: SHELL 324 M (AGED)

TEST # (BLCF-)	90	92	93	94	95
DATE (1989)	04-04	04-10	04-11	04-11	04-12
START TIME	01:00	12:00	24:00	14:00	02:00
END TIME	09:00	20:00	08:00	22:00	10:00
FEEDSTOCK	A	A	A	A	A
FEED RATE, cc/hr					
OPERATING PRESSURE, psig	2200	2250	2250	2250	2250
H2 PARTIAL PRESSURE, psig	2200	2250	2250	2250	2250
H2 TREAT RATE, scf/bbl	7500	10000	10000	10000	10000
STIRRER SPEED, rpm					
LHSV, cc/hr/cc cat.					
LHSV, cc/hr/cc react.vol.					
INLET SLURRY TEMP., F	698	675	681	689	709
UPPER SLURRY TEMP., F	719	760	780	800	798
LOWER SLURRY TEMP., F	699	736	753	770	772
AVERAGE SLURRY TEMP., F	705	724	738	753	760

FEEDSTOCK TYPE:

A: HYDROTREATED S75 F+ PRODUCT FROM BLCF-88.

TABLE 4.2.3.2-1

ASSAYS OF DELAYED COKING COALITE-DERIVED FEEDSTOCKS

<u>Feedstock Type</u>	<u>Virgin</u>	<u>Mildly Hydrotreated</u>
Nominal IBP, °F	650	650
Specific Gravity @ 60°F	1.1678	1.1399
API Gravity	-10.3	-7.4
ASTM Distillation, °F		
5% distilled	650	675
10%	703	732
30%	753	760
50%	812	825
70%	946	928
90%	---	980
Watson K, R	---	9.50
Elementals, Wt%		
C	85.47	87.15
H	7.75	7.99
N	1.18	0.95
S	0.75	0.56
O + Ash (By diff)	4.85	3.35

TABLE 4.2.3.2-2

SUMMARY OF OPERATING CONDITIONS
FOR DELAYED COKING OF COALITE

<u>Test No. (CBC-)</u>	<u>62</u>	<u>63</u>	<u>64</u>	<u>67</u>
Feed Source	----- Virgin 650F+ Resid -----			Mildly Hydrotreated 650F+ Resid
Coke Drum Temp, °F	870	880	880	880
Coke Drum Pressure, psig	100	100	25	25
Coke Drum Preheater Temp, °F	700	700	700	700
Feed Rate, lb/hr	0.85	0.85	0.85	0.85
Run Length, hr.	24	24	24	24
Recycle/Fresh Feed Ratio	0.50	0.50	0.66	0.81

4.2.4 Cracked Distillate Hydrotreating Campaigns

The above two cracking operations, namely, LC-Finingtm and Delayed Coking, are primarily conversion processes to produce HEDF precursor materials that boil within the HEDF boiling range. They therefore do not result in the production of finished HEDF products and a post-cracking hydrogenation operation is required for upgrading the cracked precursor materials. In a true commercial process, a fractionator would be installed between the cracking unit(s) with the cracked distillate fed continuously to the distillate hydrotreater and the heavier unconverted residuum being recycled back to the cracking unit. In this Task 3 screening program with the COALITE feedstock, the bench-scale cracking and hydrotreating units were not integrated and thus only first-pass crackates, either, delayed coker distillates or hydrocrackates (LC-Finates), were evaluated. Three distillate hydrotreating runs were made with delayed coker distillates and eleven distillate hydrotreating runs were made with LC-Finate (hydrocracked) distillates.

4.2.4.1 Hydrotreating of LC-Finate Distillates

Table 4.2.4.1-1 presents the feedstock assays for the three LC-Finate distillates used in the hydrocracked distillate hydrotreating campaigns. Table 4.2.4.1-2 and -3 present the summary of the operating conditions for the eleven hydrotreating tests. The objective of these campaigns was to evaluate the effects of hydrocracked distillate end point, catalyst type, space velocity, reactor temperature, and single-stage vs two-stage distillate hydrotreating.

4.2.4.2 Hydrotreating of Coker Distillates

Table 4.2.4.2-1 presents the feedstock assays for the coker distillates used in the thermally cracked distillate hydrotreating campaigns. Table 4.2.4.2-2 presents the summary of the operating conditions for the three hydrotreating tests. The objective of these campaigns was to evaluate the effects of coker severity, coker distillate end point, reactor temperature, and single-stage vs two-stage distillate hydrotreating.

4.2.5 Two-Step Selective Hydrocracking Campaigns

During the early phases of the screening program, it was determined that the raw atmospheric resid fraction of COALITE was very reactive towards undesirable cracking and condensation reactions. Thus, it was postulated that a pretreatment based on hydrogenation would provide some degree of stabilization of reactive species and thereby allow better performance during subsequent cracking operations. Since the atmospheric COALITE resid contains some coal char particles, it was felt that hydrotreating in a fixed-bed unit would pose significant operability problems. The expanded-bed hydrocracking process of LC-Finingtm offers the capability to perform the hydrogen addition process in the presence of solids and other contaminants under commercially feasible conditions.

TABLE 4.2.4.1-1

ASSAYS OF COALITE MID-DISTILLATE
LC-FINATE (HYDROCRACKATE) FEEDS TO HYDROTREATING

<u>Nominal TBP</u> <u>End Pt., °F</u>	<u>650</u>	<u>600</u>	<u>575</u>
R.I. @ 20°C	1.5493	1.5201	1.5200
Specific Gravity, g/cc	0.9619	0.9396	0.9297
A.P.I. Gravity @ 60°F	15.6	19.1	20.7
Simulated Distillation, °F			
IBP	342	354	247
10%	396	398	363
30%	445	448	411
50%	502	491	453
70%	546	535	493
90%	604	580	546
EBP	680	761	729
VAPB	502	510	463
Watson K, R	10.19	10.35	10.31
Elemental, Wt.%			
C	89.38	86.26	87.97
H	9.60	10.52	10.40
N	0.45	0.57	0.69
S	0.05	0.05	0.03
O (By Diff.)	0.52	2.60	0.91
F.I.A/R.I., 1 Vol%			
Paraffins	N.D.	N.D.	N.D.
Olefins	0.6	2.5	5.3
Naphthenes	18.6	28.3	21.2
Aromatics	80.8	69.2	73.5
WLHV, Btu/lb	16031	---	17142
VLHV, Btu/gal	128451	---	132785
Aniline Pt., °F	-6.9	---	---
Diesel Index	-1.07	---	---
Smoke Pt., mm	7	---	---
Lum. No.	30.1	---	---

TABLE 4.2.4.1-2

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED HYDROTREATING TESTS OF

HYDROCRACKED COALITE DISTILLATE

CATALYST: K-550 (1ST STAGE), K-599 (2ND STAGE)

TEST # (FB-)	44	95	96	97	98	99	100	105
DATE (1989)	02-09	04-06	04-06	04-07	04-07	04-07	04-07	04-11
START TIME	11:35	12:20	18:00	22:30	12:00	17:00	20:00	01:00
END TIME	12:35	14:50	19:30	24:00	13:30	18:00	21:30	12:00
FEEDSTOCK	A	B	B	B	B	B	B	B
FEED RATE, cc/hr	113	108	112	113	110	120	117	111
OPERATING PRESSURE, psig	2000	2050	2000	2000	2000	2000	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H ₂ TREAT RATE, scf/dbl	5000	7000	7000	7000	7000	7000	7000	7000
REACTOR 1 CONDITIONS								
LHSV, cc/hr/cc cat.	0.66	0.66	0.68	0.69	0.67	0.73	0.70	0.67
INLET BED TEMP., °F	695	625	630	746	400	399	400	607
UPPER MID BED TEMP., °F		651	702	732	402	400	400	644
LOWER BED TEMP., °F	717	627	650	695	403	401	400	621
AVERAGE BED TEMP., °F	704	634	661	725	402	400	400	624
SAND BATH TEMP., °F	701	605	620	681	403	402	403	600
REACTOR 2 CONDITIONS								
LHSV, cc/hr/cc cat.					0.7	0.7	0.7	0.7
INLET BED TEMP., °F					647	715	742	694
UPPER MID BED TEMP., °F					640	667	701	699
LOWER BED TEMP., °F					643	672	699	690
AVERAGE BED TEMP., °F					643	684	714	696
SAND BATH TEMP., °F					617	645	679	684
SEVERITY STAGE 1	0.8910	3.1506	4.3959	10.1685	0.0396	0.0352	0.0364	2.6218
SEVERITY STAGE 2					3.3360	5.8840	8.7202	6.9340
OVERALL SEVERITY	0.8910	3.1506	4.3959	10.1685	3.3756	5.9192	8.7567	9.5558

FEEDSTOCK TYPE:

A: 300-650 °F HYDROCRACKED COALITE DISTILLATE, DERIVED FROM LC-FINING OF VIRGIN 650 °F+.

B: 300-575 °F HYDROCRACKED COALITE DISTILLATE, DERIVED FROM LC-FINING OF VIRGIN 650 °F+.

TABLE 4.2.4.1-3

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED HYDROTREATING TESTS OF

HYDROCRACKED COALITE DISTILLATE

CATALYST: K-599 (1ST STAGE)

TEST # (FB-)	156	157	158
DATE (1989)	05-30	05-30	05-31
START TIME	06:00	16:00	00:00
END TIME	10:00	20:00	04:00
FEEDSTOCK	A	A	A
FEED RATE, cc/hr	118	115	116
OPERATING PRESSURE, psig	2000	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000	2000
H ₂ TREAT RATE, scf/bbl	7000	7000	7000
REACTOR 1 CONDITIONS			
LHSV, cc/hr/cc cat.	0.70	0.70	0.70
INLET BED TEMP., F	625	691	740
UPPER MID BED TEMP., F	640	709	721
LOWER BED TEMP., F	649	705	731
AVERAGE BED TEMP., F	638	702	732
SAND BATH TEMP., F			
REACTOR 2 CONDITIONS			
LHSV, cc/hr/cc cat.			
INLET BED TEMP., F			
UPPER MID BED TEMP., F			
LOWER BED TEMP., F			
AVERAGE BED TEMP., F			
SAND BATH TEMP., F			
SEVERITY STAGE 1	3.0871	7.4363	10.9827
SEVERITY STAGE 2			
OVERALL SEVERITY	3.0871	7.4363	10.9827

FEEDSTOCK TYPE:

A: 300-600 F HYDROCRACKED COALITE DISTILLATE, DERIVED FROM LC-FINING OF VIRGIN 650 F.

TABLE 4.2.4.2-1

ASSAYS OF COALITE COKER MID-DISTILLATE
FEEDS TO HYDROTREATING

<u>Feed Type</u>	<u>100 psig Coke Drum Pressure</u>	<u>62 psig Average Coke Drum Pressure</u>
R.I. @ 20°C	1.5406	1.4785
Specific Gravity, g/cc	0.9679	0.8676
API Gravity	14.7	31.6
Simulated Distillation, °F		
IBP	347	300
10%	384	370
30%	436	409
50%	489	454
70%	547	497
90%	609	559
EBP	754	725
VABP	509	473
Watson K, R	10.15	11.17
Elemental, Wt%		
C	84.33	83.88
H	9.50	10.10
N	0.93	0.65
S	0.45	0.46
O (By Diff.)	4.79	4.91
F.I.A./R.I., 1 Vol%		
Paraffins	N.D.	N.D.
Olefins	14.6	25.2
Naphthenes	24.3	22.3
Aromatics	61.1	52.5
WLHV, btu/lb.	15972	16374
VLHV, btu/gal	128775	118337
Aniline Pt., F	37.4	---
Diesel Index	5.50	---
Smoke Pt., mm	5	---
Lum. No.	29.5	---

TABLE 4.2.4.2 - 2

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED HYDROTREATING TESTS OF

THERMALLY PROCESSED COALITE DISTILLATE

CATALYST: K-550 (1ST STAGE) K-599 (2ND STAGE)

TEST # (FB-1)	45	126	127
DATE (1989)	02-13	04-19	04-19
START TIME	10:50	07:30	13:30
END TIME	11:50	09:00	14:45
FEEDSTOCK	A	B	B
FEED RATE, cc/hr	108	117	109
OPERATING PRESSURE, psig	2000	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000	2000
H ₂ TREAT RATE, scf/bbl	7060	7000	7000
REACTOR 1 CONDITIONS			
LHSV, cc/hr/cc cat.	0.7	0.7	0.7
INLET BED TEMP., F		612	400
UPPER MID BED TEMP., F	706	650	403
LOWER BED TEMP., F	713	638	404
AVERAGE BED TEMP., F	710	632	403
SAND BATH TEMP., F			
REACTOR 2 CONDITIONS			
LHSV, cc/hr/cc cat.		0.7	0.7
INLET BED TEMP., F		680	747
UPPER MID BED TEMP., F		669	670
LOWER BED TEMP., F		671	666
AVERAGE BED TEMP., F		675	694
SAND BATH TEMP., F			
SEVERITY STAGE 1	8.2311	2.8406	0.0391
SEVERITY STAGE 2		5.2078	6.7534
OVERALL SEVERITY	8.2311	8.0484	6.7925

FEEDSTOCK TYPE:

A: THERMALLY PROCESSED COALITE DISTILLATE, 300-650 F @ 100 psig COKEDRUM PRESSURE.
 B: THERMALLY PROCESSED COALITE DISTILLATE, 300-575 F @ 62 psig AVERAGE COKEDRUM PRESSURE.

FIGURE 4.2.5-1

HYDROCRACKING/HYDROGENATION ROUTES TO HEDF

TABLE 4.2.5-1

ASSAYS OF COALITE VGO FEEDSTOCKS
TO FIXED-BED HYDROCRACKING

<u>Feed Type</u>	<u>Virgin</u>	<u>Hydrotreated</u>
Specific Gravity, g/cc	1.1159	1.0180
A.P.I. Gravity	-4.7	7.5
Simulated Distillation, °F		
IBP	561	530
10%	695	618
30%	750	663
50%	792	710
70%	835	765
90%	901	849
EBP	1001	965
VABP	791	729
Watson K, R	9.66	10.38
Elemental, Wt%		
C	85.34	88.02
H	7.79	9.29
N	1.28	0.67
S	0.85	0.30
O (By Diff.)	4.74	1.72
Ash	<0.01	---
Conradson Carbon	2.90	0.55
Q.I.	0.018	---

TABLE 4.2.5 - 2

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COALITE HYDROCRACKING TESTS

CATALYST: AMOCO PROPRIETARY

TEST # (FBHC-)	1	2	3	4	13	14	15	16	17
DATE (1989)	04-27	04-28	04-28	04-28	05-03	05-04	05-04	05-04	05-05
START TIME	21:30	03:30	13:00	18:30	15:30	21:30	03:30	11:00	19:00
END TIME	23:30	05:30	15:00	20:30	17:30	23:30	08:30	14:00	08:00
FEEDSTOCK	A	A	A	A	A	A	A	A	A
FEED RATE, cc/hr	179	170	107	125	143	179	103	60	167
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000	2000
H ₂ TREAT RATE, scf/bbl	7000	7000	7000	7000	7000	7000	7000	7000	7000
LHSV, cc/hr/cc cat.	1.1	1.0	0.7	0.8	0.9	1.1	0.6	0.4	1.0
INLET BED TEMP., F	654	682	693	675	714	724	732	729	727
UPPER MID BED TEMP., F	701	730	758	721	787	805	802	805	805
LOWER BED TEMP., F	723	754	756	710	782	793	773	764	801
OUTLET BED TEMP., F									
AVERAGE BED TEMP., F	694	724	736	702	761	774	769	772	777

FEEDSTOCK TYPE:

40-150-700 F VIRGIN VGL

TABLE 4.2.5 - 3

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COALITE HYDROCRACKING TESTS

CATALYST: AMOCO PROPRIETARY

TEST # (FBHC-)	18	19	20	21	22	23	24	25	26	27
DATE (1989)	05-24	05-25	05-25	05-25	05-26	05-26	05-26	05-26	05-30	06-05/06
START TIME	22:30	04:30	10:30	17:00	23:00	05:00	13:00	20:00	07:00	07:00
END TIME	24:30	06:30	12:30	19:00	01:00	09:00	17:00	21:00	09:00	07:00
FEEDSTOCK	B	B	B	B	B	B	B	B	B	B
FEED RATE, cc/hr	124	129	118	154	147	49	102	107	117	139
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
H ₂ TREAT RATE, scf/bbl	7000	7000	7000	7000	7000	7000	7000	7000	7000	7000
LHSV, cc/hr/cc cat.	0.9	0.9	0.8	1.1	1.1	0.4	0.7	0.8	0.8	1.0
INLET BED TEMP., F	665	684	705	707	699	718	690	724	685	701
UPPER MID BED TEMP., F	714	739	772	774	760	770	743	790	705	763
LOWER BED TEMP., F	722	758	792	799	780	765	760	756	720	740
OUTLET BED TEMP., F										
AVERAGE BED TEMP., F	700	727	756	760	746	751	731	771	697	751

FEEDSTOCK TYPE:

B. 650-975 F HYDROTREATED LC-FINATE VGO.

TABLE 4.2.5-4

ASSAY OF SELECTIVELY HYDROCRACKED
COALITE MID-DISTILLATE FEED TO HYDROTREATING

TBP Boiling Range °F	300-750
R.I. @ 20°C	1.5406
Specific Gravity, g/cc	0.9619
API Gravity	15.6
Distillation, °F	
IBP	362
10%	552
30%	631
50%	666
70%	697
90%	739
EBP	781
VABP	633
Watson K, R	10.62
Elemental, Wt%	
C	88.26
H	10.97
N	0.35
S	0.05
O (By Diff.)	0.37
F.I.A./R.I., 1 Vol%	
Saturates	6.3
Aromatics	93.7
WLHV, btu/lb	17339
VLHV, btu/gal	138931

The two-step selective hydrocracking (TSSH) of COALITE consists of a hydrotreating pretreatment step using an LC-Fining[™] reaction system followed by fractionation to recover a hydrotreated vacuum gas oil (HVGO) fraction and a hydrotreated middle distillate fraction, the latter of which can be directed to the HEDF pool. The HVGO fraction is then catalytically hydrocracked over a fixed-bed hydrocracking catalyst to convert the heavier gas oil-boiling species to HEDF precursors. The thus hydrocracked LC-Finate HVGO, is then subjected to distillate hydrotreating to produce the final HEDF product.

In a true commercial process, a fractionator between the fixed-bed hydrocracker and the hydrocracked distillate hydrotreater would allow for near extinction recycle of the heavy gas oil components. In the screening program, the fixed-bed hydrocracker and the hydrocracked distillate hydrotreater were not integrated and therefore hydrotreating of only the first-pass hydrocracked HVGO fraction was evaluated. Finally, in order to minimize fractionation equipment costs in a commercial plant, it was decided to perform the initial LC-Fining[™] pretreatment step with a 300F+ atmospheric resid fraction rather than with a 650F+ atmospheric resid fraction. The residual vacuum resid (975F+) fraction after the initial LC-Fining[™] pretreatment step can be used for power generation by combustion in a steam boiler or be recycled to extinction in the MCG pyrolysis reactor. Figure 4.2.5-1 is a schematic of the processing flow scheme for the TSSH approach.

Table 4.2.5-1 presents the feedstock assays for the two gas oil feeds to the fixed-bed hydrocracking step. Two hydrocracking campaigns were made: 1) hydrocracking of virgin COALITE VGO; and 2) hydrocracking of hydrotreated LC-Finate VGO. Table 4.2.5-2 summarizes the operating conditions for the nine tests made with the virgin VGO and Table 4.2.5-3 summarizes the conditions for the ten tests made with the hydrotreated LC-Finate VGO. The objective of these tests was to evaluate the effects of space velocity, reactor temperature and VGO feedstock type. All nineteen tests were made with a proprietary fixed-bed hydrocracking catalyst supplied by Amoco Oil Company.

The hydrocracked LC-Finate VGO was fractionated to recover a mid-distillate fraction for distillate hydrotreating. The assay of this selectively hydrocracked mid-distillate feedstock is presented in Table 4.2.5-4.

A contract modification was approved by DOE to perform further screening studies of the two-stage selective hydrocracking route with the goal of exceeding the 130,000 Btu/gal energy density target of the finished HEDF test fuels. It was further expanded to also consider the impact of the energy density-JFTOT fuel stability relationships. A new Subtask 3.2 test matrix was formulated and the details of this phase of Task 3 are presented in Section 5.5.3.

4.3 Colorado Shale Oil Operations

4.3.1 Feedstock Preparation

Western Research Institute (WRI) provided nineteen drums of Colorado shale oil produced at the Unocal plant in Parachute Creek. The drums were blanketed with nitrogen prior to and during shipment as well as during the storage time at Lummus. The drums were shipped from WRI's Laramie facility on November 7, 1988.

One drum of the raw Colorado shale oil feedstock was fractionated in the 4-in Batch Distillation unit in distillation campaign referred to as S01. Twenty-three successive distillate cuts were recovered as well as a nominal 650F+ (343C+) vac resid cut. The distillate cuts were consolidated into three composites: IBP-355F raw naphtha; 355-618F mid-distillate; and 618-650F heavy gas oil. The mid-distillate cut was used as the feedstock for the virgin distillate hydrotreating campaigns. The 650F+ bottoms was evaluated as a feedstock to LC-Finingtm and delayed coking. It was also fractionated in the Equilibrium Flash Vaporization (EFV) pilot plant to produce a vacuum gas oil (650-975F) feedstock for fixed-bed hydrocracking. The selective hydrocracking evaluations utilized the raw full-range shale oil in the initial LC-Finingtm hydrotreating campaign. The thus hydrotreated LC-Finate was then fractionated to recover the 575-975F VGO fractions for subsequent fixed-bed distillate hydrotreating evaluations. Table 4.3.1-1 summarizes the properties of the 355-618F mid-distillate feed to the hydrotreating test campaigns.

Based on the processing information and analyses developed during the COALITE campaigns, the test matrix for evaluation of the Colorado shale oil feedstock was readily downsized (relative to that of the COALITE feed) while still allowing the collection of sufficient data for engineering and economic analysis.

4.3.2 Virgin Distillate Hydrotreating Campaigns

Three virgin distillate hydrotreating campaigns were made with the 355-618F mid-distillate fraction to study the effects of catalyst type, single-stage vs two-stage, space velocity, reactor temperature and hydrogen partial pressure. A total of 37 material balance tests were made of durations extending from 2-hours to 15-hours. The specific objective of each campaign is summarized below:

<u>Campaign #</u>	<u>Test # (FB-)</u>	<u>Objective</u>
I	106-125; 128-130 (Table 4.3.2-1)	Initial scans of the effects of space velocity, temperature and number of stages using NiW (K-550) and NiMo (K-599) hydrotreating catalysts
II	148-155 (Table 4.3.2-2)	Initial scans of the dehydroisomerization of raw shale oil distillate using molybdena (Mo-1230) reforming catalyst
III	159-164 (Table 4.3.2-3)	Initial scans of the two-stage dehydroisomerization/distillate hydrotreating using the Mo-1230/K-599 catalyst system

TABLE 4.3.1-1

ASSAY OF RAW COLORADO SHALE OIL MID-DISTILLATE
FEEDSTOCK TO HYDROTREATING

TBP Boiling Range, °F	355-618
R.I. @ 20°C	1.4785
Specific Gravity, g/cc	0.8676
A.P.I. Gravity	31.6
Distillation, °F	
IBP	348
10%	411
30%	467
50%	521
70%	577
90%	630
EBP	787
VABP	521
Watson K, R	11.35
Elemental, Wt%	
C	84.32
H	12.68
N	1.10
S	0.92
O (By Diff.)	0.95
F.I.A./R.I., 1 Vol%	
Paraffins	N.D.
Olefins	39.9
Naphthenes	32.9
Aromatics	27.2
WLHV, btu/lb.	17527
VLHV, btu/gal.	126670

TABLE 4.3.2-1

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COLORADO SHALE OIL

HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)/K-599 (2ND STAGE)

FILE ID: REPTS01.WK1

TEST # (FB-)	106	107	108	109	110	111	112	113
DATE (1989)	04-11	04-11/12	04-12	04-12	04-12	04-13	04-13	04-13
START TIME	17:30	23:30	05:30	11:30	18:30	00:30	06:30	13:00
END TIME	19:30	01:30	07:30	13:30	20:30	02:30	08:30	15:00
FEEDSTOCK	A	A	A	A	A	A	A	A
FEED RATE, cc/hr	115	119	120	115	119	120	119	170
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H2 PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H2 TREAT RATE, scf/bbl	7000	7000	7000	7000	7000	7000	7000	7000
REACTOR 1 CONDITIONS								
LHSV, cc/hr/cc cat.	0.70	0.72	0.73	0.70	0.72	0.73	0.72	1.03
INLET BED TEMP., F	395	396	396	400	398	397	399	401
UPPER MID BED TEMP., F	395	396	395	400	398	397	399	401
LOWER BED TEMP., F	395	396	396	400	398	397	399	401
AVERAGE BED TEMP., F	395	396	396	400	398	397	399	401
SAND BATH TEMP., F	392	393	393	398	396	394	395	399
REACTOR 2 CONDITIONS								
LHSV, cc/hr/cc cat.	0.70	0.72	0.73	0.70	0.72	0.73	0.72	1.03
INLET BED TEMP., F	596	647	699	742	647	741	744	741
UPPER MID BED TEMP., F	589	635	679	704	732	702	697	720
LOWER BED TEMP., F	587	633	676	699	631	700	692	707
AVERAGE BED TEMP., F	591	638	685	715	670	714	711	723
SAND BATH TEMP., F	584	624	671	696	624	696	690	698
SEVERITY STAGE 1	0.0325	0.0321	0.0316	0.0366	—	—	—	—
SEVERITY STAGE 2	1.5052	3.0109	5.7143	8.8707	4.7192	8.4290	8.1446	6.6131
OVERALL SEVERITY	1.5377	3.0431	5.7459	8.9073	4.7192	8.4290	8.1446	6.6131

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 4.3.2-1 (contd)

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COLORADO SHALE OIL

HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)/K-599 (2ND STAGE)

FILE ID: REPTS01.WK1

TEST # (FB-)	114	115	116	117	118	119	120	121
DATE (1989)	04-13	04-14	04-14	04-14	04-17	04-17	04-18	04-18
START TIME	22:00	04:00	10:00	16:00	06:30	12:30	19:30	01:30
END TIME	24:00	06:00	12:00	18:00	08:30	14:30	21:30	03:30
FEEDSTOCK	A	A	A	A	A	A	A	A
FEED RATE, cc/hr	119	115	115	115	118	115	230	116
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H ₂ TREAT RATE, scf/bbl	7000	7000	7000	7000	7000	7000	7000	7000
REACTOR 1 CONDITIONS								
LHSV, cc/hr/cc cat.	0.72	0.70	0.70	0.70	0.72	0.70	1.39	0.70
INLET BED TEMP., F	599	651	700	738	650	739	724	740
UPPER MID BED TEMP., F	586	640	688	700	640	705	741	708
LOWER BED TEMP., F	578	626	671	691	627	695	707	695
AVERAGE BED TEMP., F	588	639	686	710	639	713	724	714
SAND BATH TEMP., F	574	618	659	688	617	689	679	692
REACTOR 2 CONDITIONS								
LHSV, cc/hr/cc cat.							1.39	0.70
INLET BED TEMP., F							731	738
UPPER MID BED TEMP., F							737	739
LOWER BED TEMP., F							742	740
AVERAGE BED TEMP., F							737	739
SAND BATH TEMP., F							737	740
SEVERITY STAGE 1	1.3864	3.1461	6.0977	8.2846	3.0661	8.6468	4.9706	8.7197
SEVERITY STAGE 2	—	—	—	—	—	—	5.8183	11.8714
OVERALL SEVERITY	1.3864	3.1461	6.0977	8.2846	3.0661	8.6468	10.7889	20.5911

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 4.3.2-1 (concl'd)

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COLORADO SHALE OIL

HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)/K-599 (2ND STAGE)

FILE ID: REPTS01.WK1

TEST # (FB-)	122	123	124	125	128	129	130
DATE (1989)	04-18	04-18	04-18	04-19	04-19/20	04-20/21	04-21
START TIME	07:30	13:30	19:30	01:30	18:30	12:30	07:30
END TIME	09:30	15:30	21:30	03:30	09:30	03:30	21:00
FEEDSTOCK	A	A	A	A	A	A	A
FEED RATE, cc/hr	118	116	117	117	116	117	115
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000
H2 PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000
H2 TREAT RATE, scf/bbl	7000	7000	7000	7000	7000	7000	7000
REACTOR 1 CONDITIONS							
LHSV, cc/hr/cc cat.	0.72	0.70	0.71	0.71	0.70	0.71	0.70
INLET BED TEMP., F	599	699	647	600	650	739	700
UPPER MID BED TEMP., F	589	689	637	590	646	709	691
LOWER BED TEMP., F	584	670	625	580	633	693	673
AVERAGE BED TEMP., F	591	686	636	590	643	714	688
SAND BATH TEMP., F	575	662	617	588	623	689	664
REACTOR 2 CONDITIONS							
LHSV, cc/hr/cc cat.	0.72	0.70	0.71	0.71	0.70	0.71	
INLET BED TEMP., F	740	691	643	598	647	736	
UPPER MID BED TEMP., F	728	695	645	600	650	737	
LOWER BED TEMP., F	727	698	647	603	653	739	
AVERAGE BED TEMP., F	732	695	645	600	650	737	
SAND BATH TEMP., F	723	695	645	600	650	742	
SEVERITY STAGE 1	1.4669	6.0161	2.9741	1.4638	3.3056	8.5718	6.2352
SEVERITY STAGE 2	10.6615	6.7540	3.3735	1.7238	3.6559	11.5317	—
OVERALL SEVERITY	12.1285	12.7721	6.3476	3.1876	6.9615	20.1036	6.2352

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 4.3.2-2

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COLORADO SHALE OIL

HYDROTREATING TESTS

CATALYST: K-599 (1ST STAGE)/MO-1230 (2ND STAGE)

FILE ID: REPTS02.WK1

TEST # (FB-)	148	149	150	151	152	153	154	155
DATE (1989)	05-24	05-25	05-25	05-25	05-26	05-26	05-26	05-26
START TIME	16:00	00:00	08:00	16:00	00:00	08:00	16:30	20:00
END TIME	20:00	04:00	12:00	20:00	04:00	12:00	17:30	21:00
FEEDSTOCK	A	A	A	A	A	A	A	A
FEED RATE, cc/hr	82	85	83	83	332	333	495	83
OPERATING PRESSURE, psig	500	500	500	500	500	500	500	500
H2 PARTIAL PRESSURE, psig	500	500	500	500	500	500	500	500
H2 TREAT RATE, scf/bbl	9000	9000	9000	9000	9000	9000	9000	9000
REACTOR 1 CONDITIONS								
LHSV, cc/hr/cc cat.	0.50	0.52	0.50	0.50	2.01	2.02	3.00	0.50
INLET BED TEMP., F	304	306	295	303	293	296	295	298
UPPER MID BED TEMP., F	304	306	294	302	294	299	292	290
LOWER BED TEMP., F	305	308	295	304	296	301	300	290
AVERAGE BED TEMP., F	304	307	295	303	294	299	296	293
SAND BATH TEMP., F	307	307	295	303	298	305	315	284
REACTOR 2 CONDITIONS								
LHSV, cc/hr/cc cat.	0.50	0.52	0.50	0.50	2.01	2.02	3.00	0.50
INLET BED TEMP., F	790	840	891	924	859	794	817	791
UPPER MID BED TEMP., F	778	833	886	922	914	831	880	791
LOWER BED TEMP., F	774	827	882	915	924	841	911	790
AVERAGE BED TEMP., F	781	833	886	920	899	822	869	791
SAND BATH TEMP., F	776	832	883	917	916	835	914	787
SEVERITY STAGE 1	0.0010	0.0011	0.0007	0.0010	0.0002	0.0002	0.0001	0.0006
SEVERITY STAGE 2	6.8760	11.8248	20.6993	28.5693	5.8459	2.6760	2.9361	7.6097
OVERALL SEVERITY	6.8770	11.8259	20.7001	28.5703	5.8461	2.6762	2.9363	7.6104

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 4.3.2-3

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED COLORADO SHALE OIL

HYDROTREATING TESTS

CATALYST: K-599 (1ST STAGE)/MO-1230 (2ND STAGE)

FILE ID: REPTS02.WK1

TEST # (FB-)	159	160	161	162	163	164
DATE (1989)	06-05/06	06-06/07	06-08	06-08	06-08	06-09
START TIME	16:00	18:00	00:00	08:00	16:00	00:00
END TIME	16:00	18:00	06:00	14:15	22:00	06:00
FEEDSTOCK	A	A	B	B	C	C
FEED RATE, cc/hr	87	84	80	78	82	82
OPERATING PRESSURE, psig	500	500	2000	2000	2000	2000
H ₂ PARTIAL PRESSURE, psig	500	500	2000	2000	2000	2000
H ₂ TREAT RATE, scf/bbl	9000	9000	7000	7000	7000	7000
REACTOR 1 CONDITIONS						
LHSV, cc/hr/cc cat.	0.53	0.51	0.48	0.47	0.50	0.50
INLET BED TEMP., F	300	300	599	694	699	600
UPPER MID BED TEMP., F	300	300	599	697	698	600
LOWER BED TEMP., F	300	300	600	700	702	602
AVERAGE BED TEMP., F	300	300	599	697	700	601
SAND BATH TEMP., F	302	302	602	698	699	604
REACTOR 2 CONDITIONS						
LHSV, cc/hr/cc cat.	0.53	0.51				
INLET BED TEMP., F	840	790				
UPPER MID BED TEMP., F	837	788				
LOWER BED TEMP., F	830	782				
AVERAGE BED TEMP., F	836	787				
SAND BATH TEMP., F	832	783				
SEVERITY STAGE 1	0.0008	0.0008	2.4818	10.3582	10.2039	2.4724
SEVERITY STAGE 2	11.8398	7.1870				
OVERALL SEVERITY	11.8406	7.1878	2.4818	10.3582	10.2039	2.4724

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

B: LIQUID PRODUCT FROM FB-159.

C: LIQUID PRODUCT FROM FB-160.

4.3.3 Virgin Atmospheric Resid Cracking Campaigns

Like the COALITE, there is also a considerable yield of atmospheric resid in the raw Colorado shale oil. Therefore, it is also necessary to crack the heavier components to the mid-distillate range comprising the desired HEDF turbine fuel products. In a manner similar to that when processing the COALITE, three cracking methods were considered: 1) Resid hydrocracking using the LC-Finingtm process; 2) Delayed Coking; and 3) VGO fixed-bed hydrocracking. The former two are discussed in the next two sections while the latter is discussed in Section 4.3.5.

4.3.3.1 LC-Fining (Residue Hydrocracking)

Two LC-Finingtm campaigns were made with atmospheric residues from the Colorado shale oil feedstock in the stirred autoclave simulator of the LC-Finingtm process. Campaign I included five material balance tests made with a virgin 650F+ atmospheric resid fraction which evaluated the effect of reactor temperature. A NiMo catalyst (Shell 324M) that had previously been aged on coal-oil service was used in the tests. Table 4.3.3.1-1 summarizes the operating conditions evaluated.

Campaign II also included five material balance tests made with a first-pass hydrotreated 575F+ fraction recovered by distillation from the liquids processed in LC-Finingtm Campaign I. This allowed a comparison of the hydrocracking processabilities of virgin and first-pass hydrotreated residua. Table 4.3.3.1-2 summarizes the operating conditions evaluated.

4.3.3.2 Delayed Coking

Two Delayed Coking tests were made in the Continuous Bench Coking unit with the virgin 650F+ atmospheric resid to study the effects of coke drum pressure at constant coke drum temperature. Table 4.3.3.2-1 presents the summary of the feedstock properties. The detailed operating conditions for the two tests are presented in Table 4.3.3.2-2.

4.3.4 Cracked Distillate Hydrotreating Campaigns

The above two cracking operations, namely, LC-Finingtm and Delayed Coking, are primarily conversion processes to produce HEDF precursor materials that boil within the HEDF boiling range. They therefore do not result in the production of finished HEDF products and a post-cracking hydrogenation operation is required for upgrading the cracked precursor materials. In a true commercial process, a fractionator would be installed between the cracking unit(s) with the cracked distillate fed continuously to the distillate hydrotreater and the heavier unconverted residuum being recycled back to the cracking unit.

In this Task 3 screening program with the Colorado shale oil feedstock, the bench-scale cracking and hydrotreating units were not integrated and thus only first-pass crackates, either, delayed coker

SUMMARY OF OPERATING CONDITIONS FOR LC-FINING (HYDROCRACKING) TESTS

CATALYST: SMELL 324 1AGED

TEST #	89-1	89-2	89-3	89-4	89-5
DATE (1994)	03-06	03-07	03-07/08	03-08	03-09
START TIME	11:30	21:30	14:00	04:10	15:00
END TIME	20:30	12:00	02:00	13:00	01:30
FEEDPOINT	4	4	4	4	5
FILL RATE (cc/min)	387	274	281	280	300
OPERATING PRESSURE (psid)	1150	1050	2150	2150	2150
IN-LET LINE PRESSURE (psid)	2150	2150	2150	2250	2150
OUT-LET LINE PRESSURE	10000	10000	10000	10000	10000
STYRENE FILL (cc)					
INLET DENSITY (cc/g)					
 

TABLE A.3.3.1 - 1

SUMMARY OF OPERATING CONDITIONS FOR LO-FINING + HYDROCRACKING TESTS

COLORADO SHALE OIL DISTILLATE

CATALYST: SHELL 324 (AGED)

TEST # (BLOF#)	91	96	97	98	99
DATE (1989)	04-05	04-12/13	04-13	04-13/14	04-14
START TIME	18:00	13:00	05:00	10:00	11:00
END TIME	24:00	04:00	16:00	08:00	20:00
FEEDSTOCK	B	B	B	B	B
FEED RATE (cc/hr)	107	99	89	91	187
OPERATING PRESSURE (psig)	2250	2250	2250	2250	2250
HYDROGEN PRESSURE (psig)	2150	2150	2150	2150	2250
HYDROGEN FLOW (cc/hr)	7500	10000	10000	10000	10000
COUPLER PRESS (psig)					
COUPLER TEMP (°C)					
COUPLER PRESS (psig)	0.3	0.4	0.3	0.4	0.6
COUPLER TEMP (°C)	668	671	671	673	680
COUPLER PRESS (psig)	600	600	600	600	600
COUPLER TEMP (°C)	680	700	740	760	780
COUPLER PRESS (psig)	680	700	700	700	700

FEDBACK TIME

FEED RATE (cc/hr) RATE (cc/hr)

FEED RATE (cc/hr) RATE (cc/hr)

FEED RATE (cc/hr) RATE (cc/hr)

TABLE 4.3.3.2-1

ASSAY OF DELAYED COKING COLORADO SHALE OIL - DERIVED FEEDSTOCK

<u>Feedstock Type</u>	<u>Virgin</u>
Nominal IBP, °F	650
Specific Gravity @ 60°F	0.9680
API Gravity	14.7
ASTM Distillation, °F	
5% Distilled	655
10% Distilled	763
30% Distilled	824
50% Distilled	889
70% Distilled	975
Elementals, Wt%	
C	84.41
H	11.05
N	2.69
S	0.75
O + Ash (By Diff.)	1.10

TABLE 4.3.3.2-2

SUMMARY OF OPERATING CONDITIONS
FOR DELAYED COKING OF COLORADO SHALE OIL

Test No. (CBC-)	<u>65</u>	<u>66</u>
Feed Source	--- Virgin 650F+ Resid ---	
Coke Drum Temp., °F	880	880
Coke Drum Pressure, psig	100	25
Coke Drum Preheater Temp., °F	700	600
Feed Rate, lb/hr	0.85	0.65
Run Length, hr.	24	24
Recycle/Fresh Feed Ratio	0.20	0.75

distillates or hydrocrackates (LC-Finates), were evaluated. Four distillate hydrotreating runs were made with delayed coker distillates and five distillate hydrotreating runs were made with LC-Finate (hydrocracked) distillates.

4.3.4.1 Hydrotreating of LC-Finate Distillates

One fixed-bed hydrotreating campaign was made to evaluate the effects of catalyst type, two-stage vs single-stage, feedstock boiling range, space velocity and reaction temperature. Table 4.3.4.1-1 presents the analyses of the LC-Finate feedstocks to distillate hydrotreating. The campaign included three fixed-bed tests (Table 4.3.4.1-2) made to evaluate the effect of reactor temperature using a 300-575F HEDF precursor-boiling stream.

4.3.4.2 Hydrotreating of Coker Distillates

Table 4.3.4.2-1 presents the feedstock assay for the coker distillate used in the four fixed-bed hydrotreating tests. The summary of the operating conditions for these tests is presented in Table 4.3.4.2-2. The objective of the hydrotreating tests was to evaluate the effects of space velocity, reactor temperature, and two-stage severity.

4.3.5 Two-Step Selective Hydrocracking Campaigns

The two-step selective hydrocracking (TSSH) approach used for the COALITE was also carried out for the Colorado shale oil feedstock. Three feedstocks were considered for the VGO fixed-bed hydrocracking step: 1) a virgin 650-975F VGO; 2) LC-Finate hydrocracked VGO; and 3) LC-Finate hydrocracked and hydrodenitrogenated VGO. The flowscheme with test number denotation for the latter two campaigns is presented in Figure 4.3.5-1. The feedstock assays for all three test campaigns are presented in Table 4.3.5-1. Eight fixed-bed hydrocracking tests were made with the virgin VGO (Table 4.3.5-2) to study the effects of space velocity and reactor temperature using the proprietary Amoco hydrocracking catalyst. Four tests were made with the LC-Finate hydrocrackates to study the effect of space velocity at constant temperature and hydrogen partial pressure. Four tests were made with hydrodenitrogenated LC-Finate VGO to study the effects of space velocity and reactor temperature. Table 4.3.5-3 presents the summary of the operating conditions for both of the latter fixed-bed hydrocracking campaigns. The summary of the operating conditions for the LC-Finate VGO hydrodenitrogenation campaigns is presented in Table 4.3.5-4.

The thus hydrocracked denitrogenated LC-Finate VGO product containing the 300-575F HEDF precursors was subjected to a final hydrogenation step to saturate aromatics to the low levels required for achieving high energy densities. A post-hydrogenation fractionation step was used to recover the final HEDF product meeting the front-end flash point and back-end freeze point specifications. Two distillate hydrotreating campaigns, made at two different space velocities and constant temperature/hydrogen partial pressure, were made to produce sufficient sample for detailed analytical evaluation. The summary of the operating conditions for these tests is presented in Table 4.3.5-5.

TABLE 4.3.4.1-1

ASSAY OF COLORADO SHALE OIL
LC-FINATE MID-DISTILLATE TO HYDROTREATING

T.B.P. Boiling Range, °F	300-575
R.I. @ 20°C	1.4715
Specific Gravity, g/cc	0.8504
API Gravity	34.9

Distillation, °F	
IBP	272
10%	364
30%	425
50%	467
70%	507
90%	570
EBP	767
VABP	467

Watson K, R	11.44
-------------	-------

Elemental, Wt%	
C	84.30
H	13.11
N	1.14
S	0.70
O (By Diff.)	0.75

F.I.A./R.I., 1 Vol%	
Paraffins	N.D.
Olefins	17.8
Naphthenes	53.9
Aromatics	28.3

TABLE 4.3.4.1-2

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED HYDROTREATING TESTS OF

HYDROPROCESSED COLORADO SHALE OIL DISTILLATE

CATALYST: K-599 (2ND STAGE)

FILE ID: REPTSLC1.WK1

TEST # (FB-)	143	144	145
DATE (1989)	05-15/16	05-16	05-16
START TIME	22:30	04:30	10:30
END TIME	00:30	06:30	12:30
FEEDSTOCK		A	A
FEED RATE, cc/hr	119	119	112
OPERATING PRESSURE, psig	2000	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000	2000
H ₂ TREAT RATE, scf/bbl	7000	7000	7000
REACTOR 1 CONDITIONS			
LHSV, cc/hr/cc cat.			
INLET BED TEMP., F			
UPPER MID BED TEMP., F			
LOWER BED TEMP., F			
AVERAGE BED TEMP., F			
SAND BATH TEMP., F			
REACTOR 2 CONDITIONS			
LHSV, cc/hr/cc cat.	0.72	0.72	0.68
INLET BED TEMP., F	701	750	793
UPPER MID BED TEMP., F	682	714	764
LOWER BED TEMP., F	680	710	762
AVERAGE BED TEMP., F	686	726	773
SAND BATH TEMP., F	675	707	760
SEVERITY STAGE 1			
SEVERITY STAGE 2	5.9988	9.8101	18.4357
OVERALL SEVERITY	5.9988	9.8101	18.4357

FEEDSTOCK TYPE:

A: 300-575 F HYDROPROCESSED COLORADO SHALE OIL DISTILLATE.

TABLE 4.3.4.2-1

ASSAY OF COLORADO SHALE OIL (CSO) DELAYED
COKER MID-DISILLATE FEED TO HYDROTREATING

Feed Source	Delayed Coking of 650°F+ CSO resid at 62.5 psig average coke drum pressure
R.I. @ 20°C	1.4780
Specific Gravity, g/cc	0.8591
A.P.I. Gravity	33.2
Simulated Distillation, °F	
IBP	245
10%	324
30%	383
50%	427
70%	478
90%	540
EBP	733
VABP	447
Watson K, R	11.26
Elemental, Wt%	
C	84.76
H	12.21
N	1.54
S	0.75
O (By Diff.)	0.74
F.I.A./R.I., Vol%	
Paraffins	N.D.
Olefins	40.4
Naphthenes	26.0
Aromatics	33.6

TABLE 4.3.4.2-2

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED HYDROTREATING TESTS OF

THERMALLY PROCESSED COLORADO SHALE OIL DISTILLATE

CATALYST: K-550 (1ST STAGE) K-599 (2ND STAGE)

FILE ID: REPTSC1.WK1

TEST # (FB-)	131	132	133	134
DATE (1989)	04-24	04-24	04-24	04-25
START TIME	10:00	16:00	21:00	01:30
END TIME	12:00	18:00	22:30	03:00
FEEDSTOCK	A	A	A	A
FEED RATE, cc/hr	116	90	184	157
OPERATING PRESSURE, psig	2000	2000	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000	2000	2000
H ₂ TREAT RATE, scf/bbl	7000	7000	7000	7000
REACTOR 1 CONDITIONS				
LHSV, cc/hr/cc cat.	0.70	0.55	1.12	0.95
INLET BED TEMP., F	404	641	415	397
UPPER MID BED TEMP., F	406	638	415	402
LOWER BED TEMP., F	404	620	415	401
AVERAGE BED TEMP., F	405	633	415	400
SAND BATH TEMP., F				
REACTOR 2 CONDITIONS				
LHSV, cc/hr/cc cat.	0.70	0.55	1.12	0.95
INLET BED TEMP., F	743	694	652	651
UPPER MID BED TEMP., F	689	698	634	650
LOWER BED TEMP., F	692	702	630	644
AVERAGE BED TEMP., F	708	698	639	648
SAND BATH TEMP., F				
SEVERITY STAGE 1	0.0405	3.6815	0.0325	0.0268
SEVERITY STAGE 2	8.0386	9.0959	1.9568	2.6375
OVERALL SEVERITY	8.0792	12.7774	1.9893	2.6643

FEEDSTOCK TYPE:

A: THERMALLY PROCESSED COLORADO SHALE OIL DISTILLATE, 300-575 F.

FIGURE 4.3.5-1

PROCESSING APPROCHES
TO COLORADO SHALE OIL HEDF

FILE ID: CSOHEDF

TABLE 4.3.5-1

ASSAYS OF COLORADO SHALE OIL VGO FEEDS
TO FIXED-BED HYDROCRACKING

<u>Feed Type</u>	<u>Virgin</u>	<u>Mildly Hydrocracked (LC-Finates)</u>
Specific Gravity, g/cc	0.9482	0.9030
A.P.I. Gravity	17.7	25.2
Distillation, °F		
IBP	604	600
10%	738	639
30%	790	688
50%	833	750
70%	879	812
90%	950	881
EBP	1044	1000
VABP	834	754
Watson K, R	11.49	11.71
Elemental, Wt%		
C	84.51	85.68
H	11.64	12.79
N	1.95	1.29
S	0.90	0.07
O (By Diff.)	1.00	0.17
Ash	<0.01	---
Conradson Carbon	0.78	---
Q.I.	0.007	---

TABLE 4.3.5-2

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED

COLORADO SHALE OIL HYDROCRACKING TESTS

CATALYST: AMOCO PROPRIETARY

FILE ID: REPTSHC1.WK1

TEST # (FBHC-)	5	6	7	8	9	10	11	12
DATE (1989)	05-01	05-01	05-01	05-01	05-02	05-02	05-02	05-03
START TIME	07:30	13:30	19:30	01:30	07:30	13:30	19:30	04:30
END TIME	09:30	15:30	21:30	03:30	09:30	15:30	24:30	09:30
FEEDSTOCK	A	A	A	A	A	A	A	A
FEED RATE, cc/hr	98	105	211	211	211	190	110	76
OPERATING PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000	2000	2000	2000	2000	2000	2000
H ₂ TREAT RATE, scf/bbl	7000	7000	7000	7000	7000	7000	7000	7000
LHSV, cc/hr/cc cat.	0.59	0.64	1.28	1.28	1.28	1.15	0.67	0.46
INLET BED TEMP., F	680	716	710	675	725	747	738	762
UPPER MID BED TEMP., F	721	763	758	714	779	803	785	804
LOWER BED TEMP., F	717	746	760	721	784	806	771	785
OUTLET BED TEMP., F								
AVERAGE BED TEMP., F	706	742	743	703	763	785	765	784

FEEDSTOCK TYPE:

A: 650-975 F COLORADO SHALE OIL VGO.

TABLE 4.3.5 - 3

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED

COLORADO SHALE OIL HYDROCRACKING TESTS

CATALYST: AMOCO PROPRIETARY

TEST # (FBHC-)	28	29	30	31	32	33	34	35
DATE (1989)	08-16	08-17	08-17/18	08-18/21	08-28/29	08-29/30	08-30/31	08-31/09-01
START TIME	06:00	00:00	12:00	13:00	21:00	20:00	20:00	12:00
END TIME	08:00	08:00	08:00	20:00	18:00	18:00	12:00	21:00
FEEDSTOCK	A	A	A	A	B	B	B	B
FEED RATE, cc/hr	177	144	108	88	111	79	119	139
OPERATING PRESSURE, psig	2000	2000	2000	2000	2400	2400	2400	2400
H ₂ PARTIAL PRESSURE, psig	2000	2000	2000	2000	2400	2400	2400	2400
H ₂ TREAT RATE, scf/dbl	7000	7000	7000	7000	6000	6000	6000	6000
LHSV, cc/hr/cc cat.	1.07	0.87	0.69	0.53	0.67	0.48	0.72	0.84
INLET BED TEMP., F	685	689	689	685	682	685	702	723
UPPER MID BED TEMP., F	757	760	760	758	724	730	751	766
LOWER BED TEMP., F	798	800	800	800	750	750	776	790
OUTLET BED TEMP., F	801	795	793	796	746	740	768	784
AVERAGE BED TEMP., F	746	750	750	749	719	722	743	760

FEEDSTOCK TYPE:

A: 575-1000 F LC-FINATE.

B: 575-1000 F HYDRODEMITROGENATED LC-FINATE.

TABLE 4.3.5 - 4

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED HYDROTREATING TESTS OF

HYDROPROCESSED COLORADO SHALE OIL DISTILLATE

CATALYST: K-550 (1ST STAGE) / K-599 (2ND STAGE)

TEST # (FB-)	186	187
DATE (1989)	08-22/23	08-23/25
START TIME	18:00	18:00
END TIME	18:00	17:00
FEEDSTOCK	A	A
FEED RATE, cc/hr	313	303
OPERATING PRESSURE, psig	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000
H ₂ TREAT RATE, scf/bbl	7000	7000
REACTOR 1 CONDITIONS		
LHSV, cc/hr/cc cat.	1.89	1.84
INLET BED TEMP., F	748	766
UPPER MID BED TEMP., F	764	780
LOWER BED TEMP., F	767	783
AVERAGE BED TEMP., F	760	776
SAND BATH TEMP., F	754	756
REACTOR 2 CONDITIONS		
LHSV, cc/hr/cc cat.	1.89	1.84
INLET BED TEMP., F	760	753
UPPER MID BED TEMP., F	773	773
LOWER BED TEMP., F	775	775
AVERAGE BED TEMP., F	769	762
SAND BATH TEMP., F	773	774
SEVERITY STAGE 1	5.0639	7.0681
SEVERITY STAGE 2	6.2449	6.3918
OVERALL SEVERITY	12.0088	13.4599

FEEDSTOCK TYPE:

A: 575-1000 F LC-FINATE VGO.

TABLE 4.3.5 - 5

SUMMARY OF OPERATING CONDITIONS FOR FIXED-BED HYDROTREATING TESTS OF

HYDROCRACKED COLORADO SHALE OIL DISTILLATE

CATALYST: K-550 (1ST STAGE) / KS99 (2ND STAGE)

TEST # (FB-)	188	189
DATE (1989)	09-05	09-05/07
START TIME	06:00	19:00
END TIME	15:00	13:00
FEEDSTOCK	A	A
FEED RATE, cc/hr	98	191
OPERATING PRESSURE, psig	2000	2000
H ₂ PARTIAL PRESSURE, psig	2000	2000
H ₂ TREAT RATE, scf/bbl	8000	8000
REACTOR 1 CONDITIONS		
LHSV, cc/hr/cc cat.	0.59	1.16
INLET BED TEMP., °F	679	671
UPPER MID BED TEMP., °F	680	680
LOWER BED TEMP., °F	680	684
AVERAGE BED TEMP., °F	681	678
SAND BATH TEMP., °F	681	684
REACTOR 2 CONDITIONS		
LHSV, cc/hr/cc cat.		1.16
INLET BED TEMP., °F		688
UPPER MID BED TEMP., °F		700
LOWER BED TEMP., °F		705
AVERAGE BED TEMP., °F		699
SAND BATH TEMP., °F		705
SEVERITY STAGE 1	6.6296	3.2956
SEVERITY STAGE 2		4.3237
OVERALL SEVERITY	6.6296	7.6193

FEEDSTOCK TYPE:

A: HYDROCRACKED & HYDRODENITROGENATED LC-FINATE VGO.

4.3.6 Extraction Studies

The initial results of the hydroprocessing campaigns summarized above indicated that HEDF volumetric energy densities were practically limited to several thousand Btu/gal below the minimum specification. It was accordingly theorized that this resulted from the relatively high aliphatics content of the shale oils relative to their cyclics content. Thus, it was hypothesized that a hydrocarbon type separation step, such as for example, solvent extraction, could be implemented to generate an extract and a raffinate stream, one being enriched in cyclics and having a significantly higher volumetric energy density than that of either the initial feed or the other reject stream. The disposition of the high energy density cyclics, i.e., in the extract or in the raffinate, would depend upon the choice of solvent and the extraction conditions. The aliphatics-rich stream, albeit in the extract or the raffinate, would represent a high cetane-quality diesel byproduct or alternatively could be further processed catalytically to "reform" the aliphatics to cyclic structures thereby increasing the yield of the desired HEDF.

In applying the solvent extraction approach, there are many parameters that can be considered. Firstly, the HEDF precursor stream (s) for extraction need to be identified. There are several combinations to consider here:

- o Prior to or subsequent to hydroprocessing operations. Prior to hydrogenation, the cyclics in the Colorado shale oil exist as a mixture of aromatics and naphthenics, with the ratios depending upon boiling range of the precursor. Also present prior to hydroprocessing are a considerable quantity of heteroatomic compounds (e.g., organic N, S & O) which could interfere with the solvents.
- o Use of HEDF boiling range precursors vs use of heavier ends. Separation of cyclics from aliphatics might be accomplished with the VGO fraction of the shale oil prior to hydrocracking. Conversely, solvent extraction might be applied after hydrocracking and prior to or after hydrocrackate hydrogenation. In either case, a different solvent would probably be considered from the points of view of solvent effectiveness and method of separation of the solvent from the extract.

In an optimized flowscheme for conversion of the full-range Colorado shale oils to HEDF products, one or more solvent extraction applications may be feasible.

The choice of solvent (s) is also a critical parameter affecting the technical and economic feasibility of the solvent extraction route. If the solvent is most effective above ambient temperature, separation would be achieved by decanting and solvent recovery would most likely be achieved by either distillation or water extraction followed by distillation, the latter occurring only if the solvent is totally

miscible in water. If the solvent is most effective at sub-ambient conditions, separation would be accomplished by fractional crystallization and the solvent recovery method would be either of the two methods identified above.

One of the most widely used commercial solvent extraction technologies is the dewaxing of petroleum lube oils. In this case, the lube oil feedstocks are heavy boiling fractions, relative to the 300-575F HEDF range. Solvents in use include for example, N-methylpyrrolidone (NMP), N,N-dimethylformamide (DMF), furfural, phenol, etc. These all boil below that of the lube oil feedstocks and are readily separated from the extracts by distillation with the solvent boiling overhead. Other lube oil dewaxing solvents in use include methyl ethyl ketone (MEK), methyl isobutyl ketone (MIBK), acetone, etc., the latter resulting in the initial paraffin separation via fractional crystallization. When applying solvent extraction to the Colorado shale oil HEDF precursor streams, the solvent should boil either below about 300F or above about 575F if it is to be readily separated by distillation from the extracts. In the initial evaluation studies completed as part of Task 3, two solvent candidates were identified: DMF, a low boiling solvent (B.P. = 307F); and TEG (tetraethylene glycol), a higher boiling solvent (B.P. = 597F).

Four HEDF precursor streams were examined in the initial solvent extraction evaluation campaigns:

1. LC-Finate VGO
2. Hydrodenitrogenated LC-Finate VGO
3. HEDF from selective hydrocracking of VGO
4. HEDF from hydrotreating of virgin mid-distillate

Table 4.3.6-1 summarizes the batch equilibrium extraction test cycles performed with the two candidate solvents at constant temperature, pressure, solvent/feed ratio, extraction time and stirrer speed.

RESULTS OF SOLVENT EXTRACTION ON HYDROTREATED COLORADO SHALE OILS

SOLVENT A: TETRAETHYLENE GLYCOL
SOLVENT B: N,N-DIMETHYLFORMAMIDE

129

5.0 SUMMARY OF RESULTS OF COALITE OPERATIONS

5.1 Overview

The Task 3 screening program is an experimental investigation of processing responses of COALITE feedstocks with regard to their conversion to HEDF fuels, namely, Category I high density aviation turbine (jet) fuel; Category II endothermic aviation turbine (jet) fuel; and Category III high density diesel fuel. The overall objectives and technical directions taken in the screening program are as follows:

- o Generate experimental processing data, analyze data and formulate processing strategies aimed at meeting the goal of producing COALITE-derived HEDF fuels meeting a minimum volumetric energy density specification of 130,000 Btu/gal as well as satisfying the other required turbine fuel properties. A secondary goal was the identification of processing strategies that would result in HEDF fuels achieving the energy density target of 135,000 Btu/gal; and
- o Collect sufficient data for use in the refinery LP computer model of Task 5 which is aimed at determining economically optimized process flowschemes for producing HEDF products in a conceptualized refinery processing facility.

The basic technical approach taken consisted of cracking the heavier ends of the COALITE boiling above the HEDF precursor range using thermal (delayed coking) cracking technology and catalytic (LC-Fining[™] and fixed-bed VGO hydrocracking) hydrocracking technology followed by fixed-bed distillate hydrotreating of both the virgin COALITE distillates as well as the cracked COALITE distillates. Since the experimental data are collected in small bench-scale or pilot-scale units, the scaleup interpretation of the resultant data to the HEDF processing requirements must not be underestimated. Although the screening tests could not be comprehensive enough to quantify every commercial processing parameter, including for example, catalyst deactivation, catalyst makeup requirements, extinction recycle requirements, etc., these parameters had to be considered in the execution and resultant analysis of the screening test matrix.

Commercial jet (and diesel) fuel products require a considerable number of detailed specifications that must be met. In this screening program, the major emphasis was on the analytical determination and evaluation of certain key fuel properties in addition to the volumetric energy density specification. These include:

1. Freeze Point
2. Flash Point
3. Viscosity
4. Smoke Point
5. Cetane Number

6. Hydrogen Content
7. Trace sulfur and nitrogen
8. Specific gravity
9. Aromatics

Those properties not investigated for most of the 73 distillate hydrotreating tests made with the COALITE feedstocks included existent gum, JFTOT (thermal stability), copper strip corrosion, naphthalenes content, Saybolt color, acid number, mercaptans, particulate matter, water separation index, inhibitor content, carbon residue and ash content. It was assumed that the high degree of hydrogenation required to meet the stringent hydrogen and aromatics content specifications for the finished HEDF products would result in the achievement of the specifications for the above chemical and physical tests.

The following sections sequentially summarize the analyses of the results of the four major processing approaches investigated during the Task 3 screening efforts with the COALITE feedstocks.

5.2 Virgin Distillate Hydrotreating

One of the key advantages of Mild Coal Gasification over those of conventional pyrolysis technologies is the production of coal liquids enriched in distillates having relatively high hydrogen/carbon ratios and leaner in the tarry residue materials. The COALITE sample used in this program contained more than about 50 weight percent boiling in the mid-distillate range. Accordingly, these materials were the first precursors considered for conversion of COALITE to HEDF fuels.

The category I (jet) and III (diesel) fuel specifications differ primarily on the basis of distillation end point, with the diesel allowing a higher end point. It was arbitrarily decided to select two raw mid-distillate fractions for distillate hydrotreating evaluation. The raw jet fraction to hydrotreating was specified as a nominal 350-550F (TBP) cut and the raw diesel fraction was specified as a nominal 350-650F (TBP) cut. In practice, the bulk of the testing was made with the 350-650F fraction, which included the jet precursors as well as the diesel precursors. This allowed for cut point (front-end as well as back-end) control by distillation after hydrotreating. This insured that any heavy materials, i.e., 550F+, boiling above the finished jet fuel range would, upon hydrogenation, be allowed to pass into the jet fuel range. Using model compounds as an example, the hydrogenation of the heteroatomic compound 2-ethylaminonaphthalene (B.P. = 591F) might result in the formation of 2-ethylnaphthalene which boils at 496F and 2-ethyldecahydronaphthalene, a 2-ring naphthene, which also boils within the HEDF range.

The resultant ammonia product of hydrogenation would be a byproduct of the process. There are analogous situations for the hydrotreating of the heavier boiling oxygenates and sulfur-containing compounds present in the 550F+ mid-distillate fractions. These would result in the byproduct formation of H_2O and H_2S . In addition to the heteroatom

conversion aspect of hydrotreating, there also exists some degree of hydrocarbon hydrocracking which would convert the heavier 550F+ hydrocarbons to the finished jet fuel range materials.

There is also an analogy to the front-end of the mid-distillate fraction. Front-end cut point is limited in part by the flash point specification. Heteroatom conversion such as hydrogenation of multi-phenols to alkylated aromatics coupled with ring saturation of the resultant alkylated aromatics would result in a fraction boiling below the 300F nominal HEDF initial boiling point. These materials, which include alkylcyclohexanes for example, represent excellent stocks for the Category II endothermic fuels.

Depending upon the particular aircraft requirements, there are several specifications for jet or aviation turbine fuels as defined by the respective JP- designations (Table 5.2.1-1). With the exception of JP-10, a missile fuel, the other JP fuels have volumetric energy density specifications of about 115 to 121 KBtu/gal. These latter values are ultimately limited by the hydrocarbon structures characteristic of the petroleum stocks used to produce these jet fuels, these being a predominance of aliphatics as opposed to naphthenics. The latter class of hydrocarbons is known to have a unique combination of desirable high specific gravity and high mass heat of combustion which translates to high (net) volumetric energy densities, ca., 130+ KBtu/gal. This is depicted in Figure 5.2.1-1 which shows the volumetric (gross) energy densities as a function of hydrogen content for the cyclics class of hydrocarbons and the conventional petroleum-derived JP- fuels. The difference between gross and net heat of combustion is the latent heat of vaporization of the water product generated during the combustion of the fuel.

Thus, the objective of the hydroprocessing operations with the coal-derived COALITE mid-distillate feedstock is to saturate the existing alkylated single and multi-ring aromatics to alkylated single and multi-ring naphthenics and to hydrotreat the contained heteroatomics sufficiently to achieve a thermally stable fuel product in such a way that the volumetric energy density is maximized. This is accomplished by using active and selective Group 6b and 8 transition metal-based hydrogenation catalysts. In this screening effort, two such commercially available catalysts were utilized: 1) K-550, a nickel-tungsten on alumina catalyst manufactured by Katalco Corporation; and 2) K-599, a nickel-molybdenum on alumina catalyst also manufactured by Katalco. Other competing catalyst vendors also make commercial products similar to the ones utilized in this study. In one series of tests, the K-550 catalyst was specially treated in our laboratories with a calcium promoter in an attempt to improve the catalyst selectivity towards suppression of ring-opening activity. Table 5.2.1-2 summarizes the properties of the fresh catalyst oxides as reported by the manufacturer. Catalyst activation via presulfiding with an H_2S/H_2 mixture was practiced prior to hydrotreating operations.

The results are summarized in a series of spreadsheet tables with the "A" tables presenting the run performance data and the "B" tables presenting the properties of the full-range hydrotreated distillates. The organization of the tabulated results is as follows:

Table 5.2.1-1

KEY SPECIFICATIONS FOR MILITARY TURBINE FUELS

	<u>JP-4</u>	<u>JP-8</u>	<u>JP-7</u>	<u>JP-10</u> 98.5%MIN C ₁₀ H ₁₆
I. VOLATILITY PROPERTIES				
<u>ASTM D-86 Distillation, °F</u>				
<u>IBP</u>	N.L.	N.L.	360	N.L.
<u>10% distilled (MAX)</u>	N.L.	401	385	N.L.
<u>20% distilled (MAX)</u>	293	N.L.	403	N.L.
<u>50% distilled (MAX)</u>	374	N.L.	N.L.	N.L.
<u>90% distilled (MAX)</u>	473	N.L.	500	N.L.
<u>EP (MAX) °F (MJN)</u>	518	572	550	N.L.
<u>Flash Point, °F</u>	N.L.	100	140	131
<u>Density, API @ 15 °C</u>				
<u>MAX</u>	57.0	51.0	50.0	20.0
<u>MIN</u>	45.0	37.0	44.0	18.5
<u>Vapor Pressure @ 100°F, psi</u>				
<u>MIN</u>	2.0	N.L.	N.L.	N.L.
<u>MAX</u>	3.0	N.L.	3.0 @300°F	N.L.
II. FLUIDITY PROPERTIES				
<u>Freezing Point, °F (MAX)</u>	-72	-53	-46	-110
<u>Viscosity @ -4°F (MAX)</u>	N.L.	8.0	8.0	9.0 @0°F
III. COMBUSTION PROPERTIES				
<u>Net Heat of Combustion (MIN)</u>				
<u>Btu/lb</u>	18,400	18,400	18,700	18,100
<u>Btu/gal</u>	115,261	118,944	121,508	141,500
<u>Smoke Point, mm (MIN)</u>	20.0	25.0	N.L.	N.L.
<u>Hydrogen Content, wt % (MIN)</u>	13.6	13.4	14.4	11.6
<u>Aromatics, vol % (MAX)</u>	N.L.	25.0	5.0	1.5
<u>Cetane No. (MIN)</u>	N.L.	N.L.	N.L.	N.L.
IV. CORROSION PROPERTIES				
<u>Copper Strip Corrosion, 2 hr @ 212°F, (MAX)</u>				
	1.0	1.0	1b	N.L.
V. THERMAL STABILITY PROPERTIES				
<u>JFTOT, mm Hg (MAX)</u>				
	25	25	25	10
VI. CONTAMINANTS				
<u>Existent Gum, mg/100 ml (MAX)</u>				
	7.0	7.0	5.0	N.L.
<u>Particulate Matter, mg/L (MAX)</u>				
	1.0	1.0	0.3	1.0
<u>Accelerated Stability, mg/100 ml (MAX)</u>				
	N.L.	N.L.	N.L.	N.L.

Figure 5.2.1-1

VOLUMETRIC HEAT CONTENT VS HYDROGEN CONTENT OF MODEL COMPOUNDS

TABLE 5.2.1-2

ASSAYS OF DISTILLATE HYDROTREATING CATALYSTS

Catalyst Designation (Oxided/calcined form)	<u>K-550</u>	<u>K-599</u>
B.E.T. Surface Area, m ² /gm	230	220
Crush Strength, lb	15	20
Compacted Bulk Density, lb/ft ³	49.92	57.41
<u>Bulk Chemical Analysis, wt% dry basis</u>		
WO ₃	20.0	0
NiO	5.0	6.7
MoO ₃	0	27.0
Al ₂ O ₃	Balance	Balance
<u>Trace Metals, ppmw on ashed catalyst*</u>		
Vanadium	434	480
Iron	191	100
Arsenic	<2	<2
Calcium	1600	1300
Copper	B.D.L.	B.D.L.
Sodium	633	842
Lead	286	192

* Via Atomic Absorption Spectrophotometry

<u>Table No</u>	<u>Catalyst Type</u>	<u>Feed Boiling Range (F)</u>	<u># Reaction Stages</u>
5.2.1-3A,B	K-550	350-650	1
5.2.1-4A,B	K-550	350-550	1
5.2.1-5A,B	K-550/K-550	350-750(820)	2
5.2.1-6A,B	K-550/K-599	350-650	2
5.2.1-7A,B	K-599	350-650	1
5.2.1-8A,B	K-550/Calcium	350-650	1

Several interesting correlations were developed for the hydrotreating of the raw 350-550F and 350-650F COALITE distillates. Correlations were developed of the HEDF properties vs the kinetic hydrotreating severity parameter (KSF described in Section 4). These are shown graphically in Figures 5.2.1-2 through -9. Cross-correlations of key HEDF properties vs aromatics contents are depicted in Figures 5.2.1-10 through -12. Cross-correlations of key HEDF properties vs Refractive Index are shown in Figures 5.2.1-13 through -17.

At a quarterly project review meeting held in Morgantown in November 1989, WRI presented some data on their efforts to evaluate the hydrotreating of COALITE. Two hydrotreating tests were made with the COALITE mid-distillate fraction at conditions not very dissimilar to tests made at Lummus during the early Task 3 screening operations. While an exact comparison of the operating procedures and analytical methodologies was not able to be made, some interesting relationships and correlations were observed based on a comparison of the major known parameters. These are summarized below:

- o Shell 424, a nickel-molybdenum on alumina catalyst, and Katalco 550, a nickel-tungsten on alumina catalyst, both demonstrated excellent activity for saturating COALITE aromatics in the presence of heteroatomic contaminants.
- o Both catalysts appear to result in comparable specific gravity reductions in the hydrotreated products as a function of the degree of aromatics conversion. Specific gravity reduction is important because it has a direct impact on the desired improvement of the HEDF volumetric energy densities. Approximately 85% of the ultimate specific gravity reduction occurs at aromatics conversions up to about 60-70 percent (Figure 5.2.4-1).
- o Average catalyst bed temperature appears to correlate the extent of aromatics conversion at constant space velocity and hydrogen partial pressure for both catalysts with no discernible differences for the two catalyst types (Figure 5.2.4-2).
- o The experimentally observed hydrogen uptake-average catalyst bed temperature correlation for the two catalysts are nearly parallel suggesting similar activation energies for the two catalyst types. The WRI data obtained with the Shell 424 catalyst appear to result in significantly higher absolute hydrogen uptake levels. However, this may have resulted from calculational and/or experimental precision differences

TABLE 5.2.1-3A 1 of 4

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTBE1.WK1

TEST # (FB-)	17A-1	17A-2	18A-1	18A-2	18A-3	19A-1	19A-2	19A-3
DATE (1989)	01-13	01-13	01-16	01-16	01-16	01-17	01-17	01-17
START TIME	14:30	16:30	12:30	14:45	19:00	12:30	15:00	18:20
END TIME	16:30	17:30	13:30	15:45	21:00	13:30	17:00	20:20
FEEDSTOCK	A	A	A	A	A	A	A	A
% NDS	9.36		22.97	87.25	94.08	91.93	95.68	97.04
% HDM	25.28		9.03	10.60	50.67	24.82	83.12	60.05
% HDO	25.51		-9.08	10.08	75.91	21.99	87.86	91.70
H2 UPTAKE, scf/bbl	3000	3000	5000	5000	5000	5000	5000	5000
% F.I.A. OLEFINS SATURATION			66.31		91.76		92.87	95.43
% F.I.A. AROMATICS SATURATION	24.26 *		13.18	31.57 *	50.17	38.88 *	53.25	48.96
API IMPROVEMENT	0.9	0.2	1.0	9.4	19.4	10.8	23.3	20.6
R.I. DEPRESSION	0.0015		0.0040	0.0339	0.0601	0.0385	0.0747	0.0657
EST. HEAT OF REACTION, Btu/lb			83		335		385	363

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

* ESTIMATED FROM REGRESSION ANALYSIS.

TABLE 5.2.1-3A 2 of 4

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTBE1.WK1

TEST # (FB-)	20A-1	20A-2	21	22	23	24	25	26
DATE (1989)	01-18	01-18	01-19	01-20	01-20	01-23	01-23	01-24
START TIME	16:20	19:00	19:00	16:45	19:30	17:45	20:45	15:20
END TIME	18:20	21:00	21:00	17:45	20:30	18:45	21:45	16:30
FEEDSTOCK	A	A	A	A	A	A	A	A
% HDS	94.48	90.33	91.79					
% HDN	68.89	12.82	48.21					
% HDO	80.03	20.65	55.05					
H2 UPTAKE, scf/bbl	5000	5000	5000	5000	5000	5000	5000	5000
% F.I.A. OLEFINS SATURATION	95.73	92.31						
% F.I.A. AROMATICS SATURATION	55.72	38.15	50.25 *	65.73 *	55.96 *	35.45 *	45.90 *	65.40 *
API IMPROVEMENT	21.0	9.6	15.0	22.4	19.8	10.3	15.7	21.0
R.I. DEPRESSION	0.0707	0.0344	0.0530	0.0723	0.0625	0.0361	0.0511	0.0685
EST. HEAT OF REACTION, Btu/lb	389	242						

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

* ESTIMATED FROM REGRESSION ANALYSIS.

TABLE 5.2.1-3A 3 of 4

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTBE2.WK1

TEST # (FB-)	27	28	29	37	38	39	40	41
DATE (1989)	01-24	01-24	01-25	02-02	02-02	02-03	02-03	02-03
START TIME	17:45	20:15	16:40	11:30	20:15	10:35	13:35	17:30
END TIME	18:45	21:15	17:40	19:00	21:45	12:05	15:05	18:45
FEEDSTOCK	A	A	A	A	A	B	B	A
% HDS								
% HDN								
% HDO								
H2 UPTAKE, scf/bbl	5000	5000	5000	5000	5000	5000	5000	5000
% F.I.A. OLEFINS SATURATION				57.97	97.66	100.00	100.00	93.36
% F.I.A. AROMATICS SATURATION	61.96 *	58.57 *	58.75 *	76.40	80.42	94.22	98.59	72.59
API IMPROVEMENT	22.90	19.90	19.90	27.21	27.39	28.01	28.61	26.20
R.I. DEPRESSION	0.0699	0.0625	0.0585	0.0867	0.0903	0.0933	0.0965	0.0853
EST. HEAT OF REACTION, Btu/lb								

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

B: LIQUID PRODUCT FROM FB-37.

* ESTIMATED FROM REGRESSION ANALYSIS.

TABLE 5.2.1-3A 4 of 4

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTBE2.WK1

TEST # (FB-)	42	43	46	47	48	49
DATE (1989)	02-06	02-06	02-21/22	02-22	02-23	02-24
START TIME	12:05	18:45	03:45	05:45	02:00	00:00
END TIME	17:35	20:40	04:00	24:00	22:00	20:00
FEEDSTOCK	A	C	A	D	A	A
% HDS			94.48		98.64	
% HDN			68.9		87.78	
% HDO			100.58		92.01	
H ₂ UPTAKE, scf/bbl	5000	5000	5000	5000	5000	5000
% F.I.A. OLEFINS SATURATION			96.58		96.65	
% F.I.A. AROMATICS SATURATION			70.63		78.92	
API IMPROVEMENT	8.5	28.5	24.6	28.2	27.2	9.1
R.I. DEPRESSION	0.0357	0.0947	0.0810	0.0943	0.0879	0.0325
EST. HEAT OF REACTION, Btu/lb			478		516	

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

C: LIQUID PRODUCT FROM FB-42.

D: LIQUID PRODUCT FROM FB-46.

* ESTIMATED FROM REGRESSION ANALYSIS.

TABLE 5.2.1-3B 1 of 4

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COALITE PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTBP1.WK1

TEST # (FB-)	17A-1	17A-2	18A-1	18A-2	18A-3	19A-1	19A-2	19A-3
DATE (1989)	01-13	01-13	01-16	01-16	01-16	01-17	01-17	01-17
START TIME	14:30	16:30	12:30	14:45	19:00	12:30	15:00	18:20
END TIME	16:30	17:30	13:30	15:45	21:00	13:30	17:00	20:20
FEEDSTOCK	A	A	A	A	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.9861	0.9909	0.9854	0.9309	0.8735	0.9224	0.8529	0.8670
API GRAVITY @ 60 F	12.0	11.3	12.1	20.5	30.5	21.9	34.4	31.7
REFRACTIVE INDEX @ 20 C	1.5454		1.5429	1.5130	1.4868	1.5084	1.4722	1.4812
ELEMENTALS, wt%								
C	84.30		83.42	84.04	86.17	84.28	86.51	86.89
H	9.33		9.39	10.65	12.26	10.91	12.73	12.39
SIMULATED DISTILLATION, F								
IBP			365		178	183	133	
10% DISTILLED			409		237	314	218	
30%			477		369	429	327	
50%			531		452	487	422	
70%			589		517	549	493	
90%			663		606	632	583	
VOLUM. AVG. BOIL. PT, F			534		436	482	409	
WATSON K			10.06		10.95	10.55	11.10	
F.I.A. ANALYSIS, 1vol%								
OLEFINS			4.1		0.9		0.8	0.5
SATURATES			27.4		63.8		65.2	63.3
AROMATICS	71.8		68.5	50.6	35.3	47.6	34.0	36.2
WLHV, Btu/lb	16046 *		16087	16820	17869	17021 *	18132	17934 *
VLHV, Btu/gal	131807 *		132048	130429	130019	130781 *	128822	129520 *
FLASH PT., F								
SMOKE PT., mm	3		7	3	7	7	8	5
FREZE PT., F								
ANILINE PT., F	36 *		38 *	61.3 *	81.8 *	64.9 *	93.2 *	86.2 *
CETANE INDEX	4		5	13	25	14	32	27
VISCOSITY, cst @ -4 F					6.5		5.3	

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

* ESTIMATED FROM REGRESSION ANALYSIS.

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COALITE PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-550 (1ST STAGE)

TEST # (FB-)	FILE ID: REPTBP1.WK1							
	20A-1	20A-2	21	22	23	24	25	26
DATE (1989)	01-18	01-18	01-19	01-20	01-20	01-23	01-23	01-24
START TIME	16:20	19:00	19:00	16:45	19:30	17:45	20:45	15:20
END TIME	18:20	21:00	21:00	17:45	20:30	18:45	21:45	16:30
FEEDSTOCK	A	A	A	A	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.8616	0.9297	0.8978	0.8576	0.8713	0.9254	0.8939	0.8649
API GRAVITY @ 60 F	32.7	20.7	26.1	33.5	30.9	21.4	26.8	32.1
REFRACTIVE INDEX @ 20 C	1.4762	1.5125	1.4939	1.4746	1.4844	1.5108	1.4958	1.4784
ELEMENTALS, wt%								
C	86.18	84.36	85.59				85.46	
H	12.50	10.78	11.59	12.61 *	12.15 *	10.90 *	11.63	12.43 *
SIMULATED DISTILLATION, F								
IBP	176			178			185	
10% DISTILLED	222			224			272	
30%	357			351			419	
50%	446			442			484	
70%	511			507			547	
90%	602			598			640	
VOLUM. AVG. BOIL. PT, F	428			424			472	
WATSON K	11.07			11.11			10.85	
F.I.A. ANALYSIS, 1vol%								
OLEFINS	0.5	0.9						
SATURATES	65.9	52.2						
AROMATICS	33.6	46.9	38.1	25.5	31.9	49.2	39.3	28.0
WLHV, Btu/lb	18051	16868	17440 *	18069 *	17786 *	17015 *	17465 *	17958 *
VLHV, Btu/gal	129554	130633	130430 *	129085 *	129088 *	131159 *	130047 *	129384 *
FLASH PT., F								
SMOKE PT., °	11	3	4	9	5	9	9	6
FREZE PT., F								
ANILINE PT., F	94.3	61.7 *	76.3 *	91.3 *	83.7 *	66.6	76.3	87.8
CETANE INDEX	31	13	20	31	26	14	20	28
VISCOSITY, cst @ -4 F	7.5				3.5		12.0	4.4

FEEDSTOCK TYPE:

A:350-650 F VIRGIN COALITE DISTILLATE.

* ESTIMATED FROM REGRESSION ANALYSIS.

TABLE 5.2.1-3B 3 of 4

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COALITED PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-550 (1ST STAGE)

FILE ID: REPT8P2

TEST # (FB-)	27	28	29	37	38	39	40	41
DATE (1989)	01-24	01-24	01-25	02-02	02-02	02-03	01-03	02-03
START TIME	17:45	20:15	16:40	11:30	20:15	10:35	13:35	17:30
END TIME	18:45	21:15	17:40	19:00	21:45	12:05	15:05	18:45
FEEDSTOCK	A	A	A	A	A	B	B	A
SPECIFIC GRAVITY, gm/cc	0.8550	0.8708	0.8708	0.8333	0.8324	0.8294	0.8265	0.8383
API GRAVITY @ 60 F	34.0	31.0	31.0	38.3	38.5	39.1	39.7	37.3
REFRACTIVE INDEX @ 20 C	1.4770	1.4844	1.4844	1.4602	1.4566	1.4536	1.4504	1.4616
ELEMENTALS, wt%								
C								
H	12.50 *	12.15 *	12.22 *	13.29 *	13.46 *	13.60 *	13.75 *	13.22 *
SIMULATED DISTILLATION, F								
IBP	175.0			166.0	150.0	174.0	177.0	157.0
10% DISTILLED	245.0			219.0	218.0	214.0	215.0	217.0
30%	365.0			325.0	309.0	312.0	321.0	329.0
50%	416.0			412.0	405.0	402.0	402.0	411.0
70%	508.0			482.0	474.0	473.0	472.0	483.0
90%	597.0			558.0	554.0	564.0	562.0	573.0
VOLUM. AVG. BOIL. PT., F	426			399	392	393	407	411
WATSON K	11.15			11.32	11.30	11.34	11.5	11.30
F.I.A. ANALYSIS, 1vol%								
OLEFINS				5.0	0.3	0.0	0.0	0.8
SATURATES				81.3	83.3	95.3	98.7	77.8
AROMATICS	27.0 *	31.9 *	31.9 *	18.2	16.3	4.7	1.3	21.4
WLHV, Btu/lb	18002 *	17786 *	17786 *	18489 *	18594 *			18446 *
VLHV, Btu/gal	128210 *	129014 *	129014 *	128339 *	128928 *			128808 *
FLASH PT., F								
SNOKE PT., °F	6	5	5	20	20	12	35	25
FREZE PT., F								
ANILINE PT., F	88.2	79.5	78.1	105.4	120.6	132.8	139.3	110.8
CETANE INDEX	30	25	24	40	46	52	55	41
VISCOSITY, cst @ -4 F	4.0	5.0						

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

B: LIQUID PRODUCT FROM FB-37

* ESTIMATED FROM REGRESSION ANALYSIS.

TABLE 5.2.1-3B 4 of 4

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COALITED PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTBP2

TEST # (FB-)	42	43	46	47	48	49
DATE (1989)	02-06	02-06	02-21/22	02-22	02-23	02-24
START TIME	12:05	18:45	03:45	05:45	02:00	00:00
END TIME	17:35	20:40	04:00	24:00	22:00	20:00
FEEDSTOCK	A	C	A	D	A	A
SPECIFIC GRAVITY, gm/cc	0.9365	0.8270	0.8462	0.8285	0.8333	0.9328
API GRAVITY @ 60 F	19.6	39.6	35.7	39.3	38.3	20.2
REFRACTIVE INDEX @ 20 C	1.5112	1.4522	1.4659	1.4526	1.4590	1.5144
ELEMENTALS, wt%						
C			86.6	85.8	86.0	83.8
H	10.88 *	13.67 *	13.10	14.0	13.50	10.8
SIMULATED DISTILLATION, F						
IBP		171.0	148.0	159.0	104.0	186.0
10% DISTILLED		215.0	219.0	219.0	218.0	354.0
30%		322.0	334.0	315.0	315.0	431.0
50%		402.0	419.0	403.0	405.0	490.0
70%		468.0	490.0	472.0	475.0	553.0
90%		560.0	577.0	561.0	569.0	635.0
VOLUM. AVG. BOIL. PT., F		393	408	394	396	493
WATSON K		11.4	11.2	11.4	11.3	10.5
F.I.A. ANALYSIS, 1vol%						
OLEFINS	5.4	0.0	0.4		0.4	
SATURATES	56.8	96.0	77.3		83.2	
AROMATICS	37.8	4.5	22.3		16.3	
WLHV, Btu/lb	17002 *					
VLHV, Btu/gal	132636 *					
FLASH PT., F			<74	50.0	30.0	70.0
SMOKE PT., mm	3	35	24			
FREZE PT., F						
ANILINE PT., F	135.3	133.5	113.9		103.5 *	60.2 *
CETANE INDEX	27	53	41		40	12
VISCOSITY, cst @ -4 F						

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

C: LIQUID PRODUCT FROM FB-42.

D: LIQUID PRODUCT FROM FB-46.

* ESTIMATED FROM REGRESSION ANALYSIS.

TABLE 5.2.1-4A

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTBE3.WK1

TEST # (FB-)	30	31	32	33	34	35	36-1	36-2
DATE (1989)	01-25	01-25	01-26	01-26	01-27	01-27	01-30	01-30
START TIME	19:00	20:55	12:55	16:15	13:25	16:45	13:40	14:10
END TIME	20:00	21:55	13:55	22:00	14:10	18:45	14:10	14:40
FEEDSTOCK	A	A	A	A	B	B	C	C
% HDS	98.39		91.90	95.18	98.55	97.94		98.62
% HDN	86.49		-3.72	100.00	78.68	89.18		100.00
% HDO	93.48		22.92	99.02	92.95	89.36		97.20
H2 UPTAKE, scf/bbl	5000	5000	5000	5000	5000	5000	5000	5000
% F.I.A. OLEFINS SATURATION	93.94	96.28	93.90			95.73		100.00
% F.I.A. AROMATICS SATURATION	37.48	46.47	33.87	65.90 *	79.07 *	85.13	87.75 *	97.83
API IMPROVEMENT	20.3	20.4	10.7	24.0	26.5	28.9	29.2	29.4
R.I. DEPRESSION	0.0552	0.0551	0.0328	0.0676	0.0778	0.0860	0.0864	0.0887
EST. HEAT OF REACTION, Btu/lb	23.60	26.80	16.00			51.90		57.60

FEEDSTOCK TYPE:

A: 350-550 F VIRGIN COALITE DISTILLATE.

B: LIQUID PRODUCT FROM FB-33.

C: LIQUID PRODUCT FROM FB-34/FB-35.

* ESTIMATED FROM REGRESSION ANALYSIS.

TABLE 5.2.1-4B

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COALITE PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-550 (1ST STAGE)

FILE ID: REPTBP3

TEST # (FB-)	30	31	32	33	34	35	36-1	36-2
DATE (1989)	01-25	01-25	01-26	01-26	01-27	01-27	01-30	01-30
START TIME	19:00	20:55	12:55	16:15	13:25	16:45	13:40	14:10
END TIME	20:00	21:55	13:55	22:00	14:10	18:45	14:10	14:40
FEEDSTOCK	A	A	A	A	B	B	C	C
SPECIFIC GRAVITY, gm/cc	0.8571	0.8565	0.9100	0.8383	0.8260	0.8146	0.8132	0.8123
API GRAVITY @ 60 F	33.6	33.7	24.0	37.3	39.8	42.2	42.5	42.7
REFRACTIVE INDEX @ 20 C	1.4775	1.4776	1.4999	1.4651	1.4549	1.4467	1.4463	1.4440
ELEMENTALS, wt%								
C	87.30		83.57	87.13	86.02	85.49		85.55
H	12.21	12.26	11.07	12.78	13.35	13.94	13.91	14.24
SIMULATED DISTILLATION, F								
IBP				173				174
10% DISTILLED				220				219
30%				296				274
50%				392				361
70%				461				419
90%				527				498
VOLUM. AVG. BOIL. PT. F				379				354
WATSON K				11.16				11.40
F.I.A. ANALYSIS, 1vol%								
OLEFINS	0.8	0.5	0.8			0.4		0.0
SATURATES	59.7	65.0	57.5			92.2		98.4
AROMATICS	39.6	34.5	41.6	21.6 *	14.7 *	7.4	8.9 *	1.6
WLHV, Btu/lb	17995	17605	16645	18072	18251	18600	18582	18512
VLHV, Btu/gal	128478	125609	126174	126197	125575	126211	125874	125261
FLASH PT., F								
SMOKE PT., °F	12	6 *	9	30		30		30
FREZE PT., F								
ANILINE PT., F	74.5	80.2	60.8	101.3 *		125.4		135.7
CETANE INDEX	25	27	15	38		53		58
VISCOSITY, cst @ -4 F								

FEEDSTOCK TYPE:

A: 350-550 F VIRGIN COALITE DISTILLATE.

B: LIQUID PRODUCT FROM FB-33.

C: LIQUID PRODUCT FROM FB-34/FB-35.

* ESTIMATED FROM REGRESSION ANALYSIS.

TABLE 5.2.1-5A

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)/K-550 (2ND STAGE)

TEST # (FB-)	FILE ID: REPTBE4.WK1							
	169	172	170	173	174	175	176	177
DATE (1989)	06-27	06-29	06-28	06-29	06-30	06-30	06-30	06-30
START TIME	04:30	09:00	00:00	15:30	22:00	02:00	06:00	10:00
END TIME	20:00	10:00	12:00	20:00	24:00	04:00	08:00	20:00
FEEDSTOCK	A	A	B	B	B	B	B	B
% HDS								
% HDN	90	75.4						
% HDO								
H2 UPTAKE, scf/bbl	8000	8000	8000	8000	8000	8000	8000	8000
%F.I.A. OLEFINS SATURATION								
%F.I.A. AROMATICS SATURATION								
API IMPROVEMENT	34.6	33.6	33.9	30.6	28.1	22.7	18.5	25.4
R.I. DEPRESSION	1.4699	1.4716	1.4703					
EST. HEAT OF REACTION, Btu/lb								

FEEDSTOCK TYPE:

A: 350-750 F VIRGIN COALITE DISTILLATE.

B: 350-820 F VIRGIN COALITE DISTILLATE.

TABLE 5.2.1-5B

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COALITE PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-550 (1ST STAGE)/K-550 (2ND STAGE)

FILE ID: REPT8P4.WK1

TEST # (FB-)	169	172	170	173	174	175	176	177
DATE (1989)	06-27	06-29	06-28	06-29	06-30	06-30	06-30	06-30
START TIME	04:30	09:00	00:00	15:30	22:00	02:00	06:00	10:00
END TIME	20:00	10:00	12:00	20:00	24:00	04:00	08:00	20:00
FEEDSTOCK	A	A	B	B	B	B	B	B
SPECIFIC GRAVITY, gm/cc	0.8519	0.8571	0.8555	0.8729	0.8866	0.9176	0.9433	0.9018
API GRAVITY @ 60 F	34.6	33.6	33.9	30.6	28.1	22.7	18.5	25.4
REFRACTIVE INDEX @ 20 C	1.4699	1.4716	1.4703	0.8729	0.8866	0.9176	0.9433	0.9018
ELEMENTALS, wt%								
C	86.49	86.60	86.64					86.27
H	13.49	13.37	13.30					11.86
SIMULATED DISTILLATION, F								
IBP								183
10% DISTILLED								262
30%								411
50%								488
50%								570
70%								676
90%								826
VOLUM. AVG. BOIL. PT. F								539
WATSON K								11.01
F.I.A. ANALYSIS, 1vol%								
OLEFINS	2.0	0.0	1.3					0.8
SATURATES	86.8	83.7	82.6					50.8
AROMATICS	11.3	16.3	16.1					48.4
WLHV, Btu/lb	18195	17876	18116					17563
VLHV, Btu/gal	129118	127564	129100					131933
FLASH PT., F								
SMOKE PT., °								15
FREZE PT., F	17.6		26.6					10.4
ANILINE PT., F								71.15
CETANE INDEX								
VISCOSITY, cst @ -4 F								13

FEEDSTOCK TYPE:

A: 350-750 F VIRGIN COALITE DISTILLATE.

B: 350-820 F VIRGIN COALITE DISTILLATE.

TABLE 5.2.1-6A

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE)/K-599 (2ND STAGE)

TEST # (FB-)	FILE ID: REPTBES.WK1						
	94-1	94-2	94-3	101	102	103	104
DATE (1989)	04-05	04-06	04-06	04-10	04-10	04-10	04-10
START TIME	21:00	01:00	05:00	05:00	09:30	14:00	18:00
END TIME	01:00	05:00	09:00	06:30	11:00	15:30	20:00
FEEDSTOCK	A	A	A	A	A	A	A
% HDS							
% HDN							
% HDO							
H2 UPTAKE, scf/bbl	7000	7000	7000	7000	7000	7000	7000
% F.I.A. OLEFINS SATURATION	94.1	90.1	100	91.4	95.7	95.2	95.2
% F.I.A. AROMATICS SATURATION	94.4	93.9	53.8	59.5	64.2	79.8	80.5
API IMPROVEMENT	34.4	34	20.7	32.4	34.6	37.3	37.5
R.I. DEPRESSION	1.4672	1.4686	1.468	1.4763	1.4696	1.4585	1.4583
EST. HEAT OF REACTION, Btu/lb							

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

TABLE 5.2.1-6B

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COALITE PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-550 (1ST STAGE)/K-599 (2ND STAGE)

FILE ID :REPTBP5.WK

TEST # (FB-)	94-1	94-2	94-3	101	102	103	104
DATE (1989)	04-05	04-06	04-06	04-10	4-10	04-10	04-10
START TIME	21:00	01:00	05:00	05:00	09:30	14:00	18:00
END TIME	01:00	05:00	09:00	06:30	11:00	15:30	20:00
FEEDSTOCK	A	A	A	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.8529	0.8550	0.8529	0.8633	0.8519	0.8383	0.8373
A.P.I. GRAVITY @ 60 F	34.4	34.0	34.4	32.4	34.6	37.3	37.5
REFRACTIVE INDEX @ 20 C	1.4672	1.4686	1.4680	1.4763	1.4696	1.4585	1.4583

ELEMENTAL, wt. %

C
H

DISTILLATION, F

IBP
10% IDSTILLED
30%
50%
70%
90%

VOLUM. AVG. BOIL. PT. F
WATSON K

F.I.A./R.I., vol. %

OLEFINS	1.0	1.2	0.0	1.0	0.5	0.6	0.6
SATURATES	92.9	94.0	64.0	68.5	72.4	82.9	83.7
AROMATICS	6.1	4.8	36.0	30.5	27.1	16.5	15.7

WLHV, btu/lb.
VLHV, btu/gal.

FLASH PT., F							
SNOKE PT., °F				25	15	20	25
FREZE TP., F							
ANILINE PT., F				98.6			
CETANE INDEX							
VISCOSITY, cst @ -4 F							

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

TABLE 5.2.1-7A

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: K-599 (1ST STAGE)

FILE ID: REPTBES.WK1

TEST # (FB-)	146	147
DATE (1989)	05-16/18	05-18/19
START TIME	18:30	08:30
END TIME	06:30	20:30
FEEDSTOCK	A	B
% HDS		
% HDN	89.9	
% HDO		
H2 UPTAKE, scf/bbl	8000	8000
% F.I.A. OLEFINS SATURATION	95.7	100
% F.I.A. AROMATICS SATURATION	89.1	97.2
API IMPROVEMENT	25.1	28.8
R.I. DEPRESSION	0.0826	0.0965
EST. HEAT OF REACTION, Btu/lb		

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

B: LIQUID PRODUCT FROM FB-146.

TABLE 5.2.1-7B

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COALITE PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-599 (1ST STAGE)

FILE ID :REPTBPS.WK

TEST # (FB-)	146	147
DATE (1989)	05-16/18	05-18/19
START TIME	18:30	08:30
END TIME	06:30	20:30
FEEDSTOCK	A	B
SPECIFIC GRAVITY, gm/cc	0.8438	0.8256
A.P.I. GRAVITY @ 60 F	36.2	39.9
REFRACTIVE INDEX @ 20 C	1.4643	1.4504
ELEMENTAL, wt. %		
C	86.49	85.08
H	13.33	14.12
DISTILLATION, F		
IBP	157	155
10% DISTILLED	217	216
30%	336	314
50%	426	403
70%	492	472
90%	579	563
VOLUM. AVG. BOIL. PT. F	410	394
WATSON K	11.23	11.40
F.I.A./R.I. vol. %		
OLEFINS	0.5	0.3
SATURATES	91.4	96.2
AROMATICS	8.1	3.5
WLHV, btu/lb.		18374
VLHV, btu/gal.		126363
FLASH PT., F		
SMOKE PT., °		
FREZE TP., F		
ANILINE PT., F		
CETANE INDEX		
VISCOSITY, cst @ -4 F		

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

B: LIQUID PRODUCT FROM FB-146.

TABLE 5.2.1-8A

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COALITE HYDROTREATING TESTS

CATALYST: CACIUM PROMOTED K-550

FILE ID: REPTCAS.WK1

TEST # (FB-)	135	136	137	138
DATE (1989)	04-26/27	04-27/28	04-28	04-28
START TIME	21:00	17:00	13:00	18:30
END TIME	13:00	09:00	15:00	20:30
FEEDSTOCK	A	A	A	A
% HDS				
% HDN				
% HDO				
H ₂ UPTAKE, scf/bbl	7000	7000	7000	7000
% F.I.A. OLEFINS SATURATION		96.5	86.3	85.7
% F.I.A. AROMATICS SATURATION		93.5	41.1	39.7
API IMPROVEMENT	20.4	27.1	27.8	12.1
R.I. DEPRESSION	0.0654	0.0926	0.0574	0.0009
EST. HEAT OF REACTION, Btu/lb				

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

TABLE 5.2.1-8B

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COALITE PRODUCTS

CATALYST: CACIUM PROMOTED K-550

FILE ID: REPTCA2

TEST # (FB-)	135	136	137	138
DATE (1989)	04-26/27	04-27/28	04-28	04-28
START TIME	21:00	17:00	13:00	18:30
END TIME	13:00	09:00	15:00	20:30

FEEDSTOCK	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.8681	0.8338	0.8822	0.9147
API GRAVITY @ 60 F	31.5	38.2	28.9	23.2
REFRACTIVE INDEX @ 20 C	1.4815	1.4543	1.4895	1.5460

ELEMENTALS, wt%

C	86.54	86.36	86.32	84.36
H	12.40	15.53	11.95	11.14

SIMULATED DISTILLATION, F

IBP
10% DISTILLED
30%
50%
70%
90%

VOLUM. AVG. BOIL. PT, F
WATSON K

F.I.A. ANALYSIS, 1vol%

OLEFINS	0.6	0.5	1.6	1.6
SATURATES	62.1	93.5	53.8	54.6
AROMATICS	37.3	6.0	44.6	43.8

WLHV, Btu/lb	18315	17553	17124
VLHV, Btu/gal	127208	128992	130475

FLASH PT., F
SMOKE PT., °F
FREEZE PT., F
ANILINE PT., F
CETANE INDEX
VISCOSITY, cst @ -4 F

FEEDSTOCK TYPE:

A: 350-650 F VIRGIN COALITE DISTILLATE.

FIGURE 5.2.1-2

HYDROTREATING SEVERITY VS. VLHV FOR HYDROTREATED COALITE DISTILLATES

FIGURE 5.2.1-3

HYDROTREATING SEVERITY VS. HYDROGEN CONTENT
FOR COALITE DISTILLATE OVER K-550 CATALYST

FIGURE 5.2.1-4

HYDROTREATING SEVERITY VS. F.I.A. AROMATICS
FOR COALITE DISTILLATE OVER K-550 CATALYST

HYDROTREATING SEVERITY, 10000*P/LHSV *e(-35000/RT)

FIGURE 5.2.1-5

HYDROTREATING SEVERITY VS. API GRAVITY
FOR COALITE DISTILLATE OVER K-550 CATALYST

HYDROTREATING SEVERITY, 10000*P/LHSV *e(-35000/RT)

FIGURE 5.2.1-6

HYDROTREATING SEVERITY VS. ANILINE POINT FOR COALITE DISTILLATE OVER K-550 CATALYST

HYDROTREATING SEVERITY, $10000 \cdot P / LHSV \cdot e(-35000/RT)$

FIGURE 5.2.1-7

HYDROTREATING SEVERITY VS. CETANE INDEX
FOR COALITE DISTILLATE OVER K-550 CATALYST

HYDROTREATING SEVERITY, 10000*P/LHSV *e(-35000/RT)

FIGURE 5.2.1-8

HYDROTREATING SEVERITY VS. SMOKE POINT FOR COALITE DISTILLATE OVER K-550 CATALYST

FIGURE 5.2.1-9

HYDROTREATING SEVERITY VS. REFRACTIVE INDEX
FOR COALITE DISTILLATE OVER K-550 CATALYST

HYDROTREATING SEVERITY, 10000*P/LHSV *e(-35000/RT)

FIGURE 5.2.1-10

EFFECT OF AROMATICS ON VOLUMETRIC LHV OF COAL-DERIVED DIESEL/JET FUELS

FIGURE 5.2.1-11

EFFECT OF AROMATICS ON CETANE QUALITY OF COAL-DERIVED DIESEL FUELS

FIGURE 5.2.1-12

EFFECT OF AROMATICS ON SMOKE POINT OF COAL-DERIVED TURBINE FUELS

FIGURE 5.2.1-13

PREDICTED NET HEAT OF COMBUSTION (LHV) OF COALITE VS R.I. AND API GRAVITY

FIGURE 5.2.1-14

DISTILLATE HYDROGEN CONTENT AS A FUNCTION OF REFRACTIVE INDEX OF COALITE DISTILLATES

FIGURE 5.2.1-15

PREDICTED API GRAVITY AS A FUNCTION OF REFRACTIVE INDEX OF HYDROTREATED COALITE

FIGURE 5.2.1-16

WATSON K FACTOR AS A FUNCTION OF REFRACTIVE INDEX OF HYDROTREATED COALITE

FIGURE 5.2.1-17

SMOKE POINT AND LUMINOMETER NO. VS. REFRACTIVE INDEX OF COALITE DISTILLATES

FIGURE 5.2.4-1

RELATIVE HYDROPROCESSING PERFORMANCE FOR 350--550F COALITE

FIGURE 5.2.4-2

RELATIVE HYDROPROCESSING PERFORMANCES OF 350-550F COALITE

between the two laboratories in their efforts to quantify the hydrogen uptake values rather than from catalyst type (Figure 5.2.4-3).

5.3 Virgin Atmospheric Resid Cracking

5.3.1 LC-Fining

The LC-Fining process utilizes an expanded-bed of hydrotreating catalyst to provide for backmixing and near isothermal operation during the hydrogenation of heavy oils and residua that contain significant catalyst poisons, e.g., trash metals, organometallics, coke precursors, etc. The process has been widely commercialized, especially for vacuum residua, and the continuous addition and withdrawal of catalysts allows for continuous operation without having to shutdown to replace poison or coked catalysts. While the raw COALITE does not contain much vac resid content, it does contain considerable atmospheric resid (650F+). LC-Fining is a potential technology for upgrading the atmospheric resid fraction of MCG liquids, especially as a means of inputting the high overall hydrogen uptakes required to convert the hydrogen-deficient liquids to hydrogen-rich HEDF.

Four LC-Fining test campaigns were made: two with virgin residua (300F+ and 650F+) and two with hydrotreated resid recovered from the first-pass LC-Fining operation with the 650F+ virgin resid. The performance results for these campaigns are presented in Tables 5.3.1-1 and -2. The summary of the properties of the full-range LC-Finate products from these campaigns is presented in Tables 5.3.1-3 and -4. The main objective of these tests was to produce feedstock for the cracked distillate hydrotreating campaigns in which the jet boiling range aromatics hydrocracked from the VGO material are saturated to high energy density cycloparaffins.

5.3.2 Delayed Coking

With very thermally reactive feedstocks such as pyrolysis oils from the COALITE process, processing in catalytic systems can result in relatively high levels of carbon on the catalysts. This can be ameliorated by operating at low thermal severities which in turn requires high catalyst inventories, i.e., operation at low space velocities, to achieve commercially feasible conversion levels. Another processing approach is based on the use of thermal processing technologies which produce lighter and hydrogen-enriched liquids by rejection of feed carbon as coke. Delayed coking is a mature commercial process for production of distillate fuels from heavy residua. The resultant coke byproduct generated can be upgraded to fuel gas via partial oxidation technology or in the case of MCG can be blended with the MCG char and upgraded to any of the premium solid products being targeted via Mild Coal Gasification.

All four tests made with the two feedstocks (virgin 650F+ and mildly hydrotreated 650F+ residua) gave similar yield structures: 41-49% coke yields, 31-43% liquids yields, and 14-20% gas yields. The mildly hydrotreated resid feed did result in the lowest coke make but the

FIGURE 5.2.4-3

RELATIVE HYDROPROCESSING PERFORMANCE FOR 350--550F COALITE

TABLE 5.3.1-1

SUMMARY OF OPERATING RESULTS FOR LC-FINING (HYDROCRACKING) TESTS

CATALYST: SHELL 324 (AGED)

FILE ID: REPTBLC2.WK1

TEST # (BLCF-)	86-1	86-2	87	88-1/2	88-3	88-4	88-5	90
DATE (1989)	01-31	02-01	02-08	02-27/28	02-28/03-01	03-1/2	03-2/3	04-04
START TIME	19:00	07:00	02:00	15:30	16:30	09:00	07:30	01:00
END TIME	23:00	15:00	16:00	16:30	09:00	07:30	18:00	09:00
FEEDSTOCK	A	A	A	A	A	A	A	B
% HDS								
% HDN								
% HDO								
H2 UPTAKE, scf/bbl				10000	10000	10000	10000	10000
API IMPROVEMENT				21.4	19.6	19.0	18.3	4.0
R.I. REGRESSION								
EST. HEAT OF REACTION, Btu/lb								

FEEDSTOCK TYPE:

A: COALITE ATM RESID, 650+ F.

B: HYDROPROCESSED COALITE DISTILL RESID, 575+ F.

TABLE 5.3.1-2

SUMMARY OF OPERATING RESULTS FOR LC-FINING (HYDROCRACKING) TESTS

CATALYST: SHELL 324 (AGED)

FILE ID: REPTBLC2.WK1

TEST # (BLCF-)	92	93	94	95	100	101
DATE (1989)	04-10	04-11	04-11	04-12	05-17/19	06-13/15
START TIME	12:00	24:00	14:00	02:00	20:00	08:00
END TIME	20:00	08:00	22:00	10:00	19:30	02:30
FEEDSTOCK	B	B	B	B	C	C
% HDS						
% HDN						
% HDO						
H2 UPTAKE, scf/bbl	10000	10000	10000	10000	7000	7000
API IMPROVEMENT			8.4	6.7	11.9	1.3
R.I. REGRESSION						
EST. HEAT OF REACTION, Btu/lb						

FEEDSTOCK TYPE:

B: HYDROPROCESSED COALITE DISTILL RESID, 575+ F.

C: COALITE DISTILLATE, 300+ F.

TABLE 5.3.1-3

SUMMARY OF PROPERTIES OF FULL-RANGE LC-FIMATE TESTS

TEST # (BLCF-)	CATALYST: SHELL 324 (AGED)							90
	86-1	86-2	87	88-1/2	88-3	88-4	88-5	
DATE (1989)	01-31	02-01	02-08	02-27/28	02-28/03-01	03-1/2	03-2/3	04-04
START TIME	19:00	07:00	02:00	15:30	16:30	09:00	07:30	01:00
END TIME	23:00	15:00	16:00	16:30	09:00	07:30	18:00	09:00
FEEDSTOCK	A	A	A	A	A	A	A	B
SPECIFIC GRAVITY, gm/cc				0.9923	1.0050	1.0093	1.0143	1.0306
API GRAVITY @ 60F				11.1	9.3	8.7	8.0	5.8
REFRACTIVE INDEX @ 20C								
ELEMENTALS, wt%								
C				87.33	88.24	88.81	87.05	
H				9.35	9.18	9.16	9.15	
SIMULATED DISTILLATION, F								
18P				184	209	196	194	
10% Distilled				368	399	400	405	
30%				489	539	543	565	
50%				583	628	636	657	
70%				666	697	704	712	
90%				760	783	791	800	
VOLUN. AVG. BOIL. PT., F				573	609	615	628	
WATSON K				340.4	348.0	348.4	350.9	
WLHV, Btu/lb								
VLHV, Btu/gal								

FEEDSTOCK TYPE:

A: COALITE ATM RESID, 650+ F.

B: HYDROPROCESSED COALITE DISTILL RESID, 575+ F.

TABLE 5.3.1-4

SUMMARY OF PROPERTIES OF FULL-RANGE LC-FINATE TESTS

CATALYST: SHELL 324 (AGED)

FILE ID: REPTBLC3.WK1

TEST # (BLCF-)	92	93	94	95	100	101
DATE (1989)	04-10	04-11	04-11	04-12	05-17/19	06-13/15
START TIME	12:00	24:00	14:00	02:00	20:00	08:00
END TIME	20:00	08:00	22:00	10:00	19:30	02:30
FEEDSTOCK	B	B	B	B	C	C
SPECIFIC GRAVITY, gm/cc			0.9986	1.0107	0.9659	1.0409
API GRAVITY @ 60F			10.2	8.5	15.0	4.4
REFRACTIVE INDEX @ 20C						
ELEMENTALS, wt%						
C						
H						
SIMULATED DISTILLATION, F						
IBP					216	393
10% Distilled					385	453
30%					479	535
50%					566	667
70%					600	791
90%					787	791
VOL. AVG. BOIL. PT., F					563	647
WATSON K					11.1	19.3
WLHV, Btu/lb						
VLHV, Btu/gal						

FEEDSTOCK TYPE:

B: HYDROPROCESSED COALITE DISTILL RESID, 575+ F.

C: COALITE DISTILLATE, 300+ F.

coke suppression did not lead to a concomitant increase in liquids yield. The test made with the virgin resid at 100 psig coke drum pressure had a mid-distillate product with more than 60% aromatics content and an energy density (before hydrogenation) of 128,775 Btu/gal. The mid-distillate product from the coker test made at 62 psig coke drum pressure had a higher olefins content and a lower aromatics content than that for the 100 psig drum pressure. In both cases, coke yields represented a significant loss of potential HEDF yield. However as pointed out previously the capital cost of the coker-derived liquids is relatively lower than that of the higher liquids producing, hydrocracking process-derived route.

5.4 Cracked Distillate Hydrotreating

Products from both the LC-Fining and Delayed Coking tests were fractionated to recover 650F- distillate fractions which served as the feedstocks for the final hydrogenation step necessary to convert aromatics to cycloparaffins, the latter being the high energy density components of the HEDF test fuels. Distillate hydrotreating was carried out in several campaigns to reflect the different sources of the distillate feeds to hydrotreating.

5.4.1 Hydrotreating of LC-Finate Distillates

The results of these campaigns are summarized in a series of spreadsheet tables with the "A" tables presenting the run performance data and the "B" tables presenting the properties of the full-range hydrotreated distillates. The organization of the tabulated results is as follows:

<u>Table No</u>	<u>Catalyst Type</u>	<u>Feed Boiling Range (F)</u>	<u># Reaction Stages</u>
5.4.1-1A,B	K-550/K-599	300-575(650)	2
5.4.1-2A,B	K-599	300-600	1
5.4.1-3A,B	Amoco Propr.	650-975Virgin	1
5.4.1-4A,B	Amoco Propr.	650-975HDT	1
5.4.1-5A,B	K-599/K-599	350-750	2

5.4.2 Hydrotreating of Coker Distillates

The results of the three hydrotreating tests with coker distillates are presented in Table 5.4.2-1A (run performance data) and 5.4.2-1B (properties data).

5.5 Two-Step Selective Hydrocracking of Vacuum Gas Oil (VGO)

5.5.1 Overview of Early Results

Early Task 3 screening tests were aimed at investigating the hydrocracking via expanded-bed LC-Fining (using a base metal hydrocracking catalyst) of the 650F+ COALITE feedstock. This was followed by an alternative hydrocracking route consisting of fixed-bed hydrocracking of a VGO fraction (650-975F) of the 650F+ COALITE over a more selective, proprietary, zeolite-based hydrocracking catalyst. The latter operation was somewhat hampered by temperature control/hot spot

TABLE 5.4.1-1A

SUMMARY OF OPERATING RESULTS OF FIXED-BED HYDROTREATED PRODUCTS FROM

HYDROCRACKED COALITE DISTILLATE

CATALYST: K-550 (1ST STAGE), K-599 (2ND STAGE)

TEST # (FB-)	44	95	96	97	98	99	100	105
DATE (1989)	02-09	04-06	04-06	04-07	04-07	04-07	04-07	04-11
START TIME	11:45	12:20	18:00	22:30	12:00	17:00	20:00	01:00
END TIME	12:35	14:50	19:30	24:00	13:30	18:00	21:30	12:00
FEEDSTOCK	A	B	B	B	B	B	B	B
% HDS								
% HDN	85.80	86.61	95.57	79.58	84.76	84.08	81.17	79.23
% HDO								
H2 UPTAKE, scf/bbl	5000	7000	7000	7000	7000	7000	7000	7000
% F.I.A. OLEFINS SATURATION	0.3	1.5	1.2	4.6	1.2		1.0	0.5
% F.I.A. AROMATICS SATURATION	2.9	29.2	11.1	3.3	16.2		4.4	9.8
API IMPROVEMENT	39.6	32	34.2	36.2	32.4	34.4	35.5	35.9
R.I. DEPRESSION	1.4516	1.4744	1.4644	1.4572	1.4727	1.4643	1.4608	1.4590
EST. HEAT OF REACTION, Btu/lb								

FEEDSTOCK TYPE:

A: 300-650 F HYDROCRACKED COALITE DISTILLATE. DERIVED FROM LC-FINING OF VIRGIN 650 F+.

B: 300-575 F HYDROCRACKED COALITE DISTILLATE. DERIVED FROM LC-FINING OF VIRGIN 650 F+.

TABLE 5.4.1-1B

SUMMARY OF PROPERTIES OF FIXED-BED HYDROTREATED PRODUCTS FROM

HYDROCRACKED COALITE DISTILLATE

CATALYST: K-550 (1ST STAGE), K-599 (2ND STAGE)

TEST # (FB-)	44	95	96	97	98	99	100	105
DATE (1989)	02-09	04-06	04-06	04-07	04-07	04-07	04-07	04-11
START TIME	11:35	12:20	10:00	20:30	12:00	17:00	20:00	01:00
END TIME	12:35	14:50	15:00	24:00	13:30	18:00	21:30	12:00
FEEDSTOCK	A	B	B	B	B	B	B	B
SPECIFIC GRAVITY, gm/cc	0.8270	0.8654	0.8540	0.8468	0.8633	0.8529	0.8473	0.8453
API GRAVITY @ 60 F	39.6	32.0	34.2	35.6	32.4	34.4	35.5	35.9
REFRACTIVE INDEX @ 20 C	1.4516	1.4744	1.4644	1.4572	1.4727	1.4643	1.4608	1.459
ELEMENTALS, wt%								
C	85.62	87.02	86.35	85.66	86.86	86.34	85.93	86.26
H	13.83	12.89	13.42	13.87	12.84	13.45	13.67	13.84
SIMULATED DISTILLATION, F								
IBP	178						187	
10% DISTILLED	227						294	
30%	330						365	
50%	402						405	
70%	471						457	
90%	556						512	
VOLUM. AVG. BOIL. PT., F	397						407	
WATSON K	11.40						11.16	
F.I.A. ANALYSIS, 1vol%								
OLIFINS	0.3	1.5	1.2	4.6	1.2		1.0	0.5
SATURATES	96.9	69.3	87.7	92.1	82.6		94.6	89.7
AROMATICS	2.9	29.2	11.1	3.3	16.6		4.4	9.8
WLHV, Btu/lb	18489	18157	17374	18183	17671	18285	18331	18352
VLHV, Btu/gal	127369	130890	123595	127807	127075	129910	129379	129223
FLASH PT., F								85
SMOKE PT., °F	35						25	25
FREEZE PT., F								26.6
ANILINE PT., F	138.9	95.2	115	129.2	94.6	115.7	119.6	
CETANE INDEX	55	30	39	46	31	40	42	
VISCOSITY, cst @ -4 F								

FEEDSTOCK TYPE:

A: 300-650 F HYDROCRACKED COALITE DISTILLATE. DERIVED FROM LC-FINING OF VIRGIN 650 F+.

B: 300-750 F HYDROCRACKED COALITE DISTILLATE. DERIVED FROM LC-FINING OF VIRGIN 650 F+.

TABLE 5.4.1-2A

SUMMARY OF OPERATING RESULTS OF FIXED-BED HYDROTREATED PRODUCTS FROM

HYDROCRACKED COALITE DISTILLATE

CATALYST: K-599 (1ST STAGE)

TEST # (FB-)	156	157	158
DATE (1989)	05-30	05-30	05-31
START TIME	06:00	16:00	00:00
END TIME	10:00	20:00	04:00
FEEDSTOCK	A	A	A
% HDS			
% HDN	84.82	82.02	92.80
% HDO			
H2 UPTAKE, scf/bbl	2000	2000	2000
% F.I.A. OLEFINS SATURATION	64.8	67.2	779.5
% F.I.A. AROMATICS SATURATION	45.2	74.7	76.3
API IMPROVEMENT	11.9	15.8	17.2
R.I. DEPRESSION	0.0406	0.0548	0.0594
EST. HEAT OF REACTION, Btu/lb			

FEEDSTOCK TYPE:

A: 300-600 F HYDROCRACKED COALITE DISTILLATE. DERIVED FROM LC-FINING OF 650 F+.

TABLE 5.4.1-2B

SUMMARY OF PROPERTIES OF FIXED-BED HYDROTREATED PRODUCTS FROM

HYDROCRACKED COALITE DISTILLATE

CATALYST: K-599 (1ST STAGE)

TEST # (FB-)	156	157	158
DATE (1989)	05-30	05-30	05-31
START TIME	06:00	16:00	00:00
END TIME	10:00	20:00	04:00
FEEDSTOCK	A	A	A
SPECIFIC GRAVITY, gm/cc	0.8708	0.8504	0.8433
API GRAVITY @ 60 F	31.0	34.9	36.3
REFRACTIVE INDEX @ 20 C	1.4795	1.4653	1.4607
ELEMENTALS, wt%			
C	87.13	85.50	86.46
H	12.76	13.42	13.54
SIMULATED DISTILLATION, F			
IBP			183
10% DISTILLED			269
30%			386
50%			433
70%			481
90%			541
VOLUM. AVG. BOIL. PT., F			422
WATSON K			11.29
F.I.A. ANALYSIS, 1vol%			
OLIFINS	0.9	0.8	0.5
SATURATES	60.3	82.1	83.5
AROMATICS	38.8	17.1	16.0
WLHV, Btu/lb			
VLHV, Btu/gal			
FLASH PT., F			
SHOKE PT., °			
FREEZE PT., F			
ANILINE PT., F			
CETANE INDEX			
VISCOSITY, cst @ -4 F			

FEEDSTOCK TYPE:

A: 300-600 F HYDROCRACKED COALITE DISTILLATE. DERIVED FROM LC-FINING OF VIRGIN 650 F+.

TABLE 5.4.1-3A

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COALITE HYDROCRACKING TESTS

CATALYST: AMOCO PROPRIETARY

TEST # (FBHC-)	1	2	3	4	13	14	15	16	17
DATE (1989)	04-27	04-28	04-28	04-28	05-03	05-04	05-04	05-04	05-05
START TIME	21:30	03:30	13:00	18:30	15:30	21:30	03:30	11:00	19:00
END TIME	23:30	05:30	15:00	20:30	17:30	23:30	08:30	14:00	08:00
FEEDSTOCK	A	A	A	A	A	A	A	A	A
% HDS							91.2		
% HDN							77.5		
% HDO							92.7		
H2 UPTAKE, scf/bbl	7000	7000	7000	7000	7000	7000	7000	7000	7000
% F.I.A. OLIFINS SATURATION									
% F.I.A. AROMATICS SATURATION									
API IMPROVEMENT	9.2	11.7	14.4	13.7	17.5	17.5	21.0	22.2	17.9
R.I. DEPRESSION									
EST. HEAT OF REACTION, Btu/lb									

FEEDSTOCK TYPE:

A: 650-975 F VIRGIN VGO.

TABLE 5.4.1-3B

SUMMARY OF PROPERTIES OF HYDROCRACKATES FROM FIXED-BED COALITE HYDROCRACKING

CATALYST: AMOCO PROPRIETARY

TEST # (FBHC-)	1	2	3	4	13	14	15	16	17
DATE (1989)	04-27	04-28	04-28	04-28	05-03	05-04	05-04	05-04	05-05
START TIME	21:30	03:30	13:00	18:30	15:30	21:30	03:30	11:00	19:00
END TIME	23:30	05:30	15:00	20:30	17:30	23:30	08:30	14:00	08:00
FEEDSTOCK	A	A	A	A	A	A	A	A	A
SPECIFIC GRAVITY, gm/cc	1.0404	1.0217	1.0021	1.0071	0.9806	0.9806	0.9574	0.9597	0.9797
API GRAVITY @ 60F	4.5	7.0	9.7	9.0	12.8	12.8	16.3	15.9	12.9
REFRACTIVE INDEX @ 20C									
ELEMENTALS, wt %									
C							88.2		
H							11.03		
SIMULATED DISTILLATION, F									
IBP	260	254	225	274	220	215	213	217	224
10% DISTILLED	560	527	495	523	465	446	419	418	452
30%	695	671	638	654	611	599	571	554	597
50%	758	744	719	728	695	688	661	639	682
70%	811	803	786	792	768	763	743	717	757
90%	883	880	868	873	857	856	843	829	849
VOLUM. AVG. BOIL. PT. F	741	725	701	714	679	670	647	631	667
WATSON K	11.00	10.75	10.47	10.56	10.18	10.15	9.85	9.82	10.14
WLHV, Btu/lb									
VLHV, Btu/gal									

FEEDSTOCK TYPE:

A: 650-975 F VIRGIN VGO.

TABLE 5.4.1-4A

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COALITE HYDROCRACKING TESTS

CATALYST: AMOCO PROPRIETARY

TEST # (FBHC-)	18	19	20	21	22	23	24	25	26	27
DATE (1989)	05-24	05-25	05-25	05-25	05-26	05-26	05-26	05-26	05-30	06-05/08
START TIME	22:30	04:30	10:30	17:00	23:00	05:00	13:00	20:00	07:00	07:00
END TIME	24:30	06:30	12:30	19:00	01:00	09:00	17:00	21:00	09:00	07:00
FEEDSTOCK	B	B	B	B	B	B	B	B	B	B
% HDS										
% HDN										93.2
% HDO										
H2 UPTAKE, scf/bbl	7000	7000	7000	7000	7000	7000	7000	7000	7000	7000
% F.I.A. OLIFINS SATURATION										
% F.I.A. AROMATICS SATURATION										
API IMPROVEMENT	5.5									
R.I. DEPRESSION										
EST. HEAT OF REACTION, Btu/lb										

FEEDSTCK TYPE:

B: 650-975 F HYDROTREATED LC-FINATE VGO.

TABLE 5.4.1-4B

SUMMARY OF PROPERTIES OF HYDROCRACKATES FROM FIXED-BED COALITE HYDROCRACKING

CATALYST: AMOCO PROPRIETARY

TEST # (FBHC-)	18	19	20	21	22	23	24	25	26	27
DATE (1989)	05-24	05-25	05-25	05-25	05-26	05-26	05-26	05-26	05-30	06-05-08
START TIME	22:30	04:30	10:30	17:00	23:00	05:00	13:00	20:00	07:00	07:00
END TIME	24:30	06:30	12:30	19:00	01:00	09:00	17:00	21:00	09:00	07:00
FEEDSTOCK	B	B	B	B	B	B	B	B	B	B
SPECIFIC GRAVITY, gm/cc	0.9792	0.9705	0.9574	0.9613	0.9672	0.9285	0.9765	0.9433	0.9674	0.9705
API GRAVITY @ 60F	13.0	14.3	16.3	15.7	14.8	20.9	13.4	18.5	11.6	14.3
REFRACTIVE INDEX @ 20C										
ELEMENTALS wt %										
C										88.8
H										10.76
SIMULATED DISTILLATION, F										
16F	310	244	213	217	218	215	251	217	353	234
10% DISTILLED	376	349	496	505	526	445	556	456	596	522
30%	639	631	613	616	624	570	636	558	650	624
50%	690	680	666	668	671	631	687	650	696	670
70%	751	740	727	729	737	690	748	710	757	730
90%	841	834	827	826	832	793	846	811	850	821
WATER AND BOIL. PT., F	710	688	666	669	677	626	695	643	709	676
WATER	10.23	10.10	9.90	9.95	10.04	9.48	10.18	9.69	10.34	10.10
WATER BOIL. PT.										
WATER BOIL. PT.										

FEEDSTOCK TYPE:

B: 650-975 F HYDROTREATED LC-FINATE VGO.

TABLE 5.4.1-5A

SUMMARY OF OPERATING RESULTS FOR FIXED-BED HYDROTREATING TESTS OF

HYDROCRACKED COALITE DISTILLATE

CATALYST: K-599 (1ST STAGE)/K-599 (2ND STAGE)

FILE ID: REPTBE6.WK1

TEST # (FB-)	165	166	167	168
DATE (1989)	06-12	06-13/14	06-15	06-15
START TIME	21:00	03:00	10:00	19:00
END TIME	23:00	06:00	15:00	06:00
FEEDSTOCK	A	A	A	A
% HDS				
% HDN				
% HDQ				
H ₂ UPTAKE, scf/bbl	7000	7000	7000	7000
% F.I.A. OLEFINS SATURATION				
% F.I.A. AROMATICS SATURATION				
API IMPROVEMENT	18.0	25.5	21.4	17.6
R.I. DEPRESSION	1.5239	1.4909	1.5088	1.5260
EST. HEAT OF REACTION, Btu/lb				

FEEDSTOCK TYPE:

A: 350-750 F CRACKED COALITE DISTILLATE.
FROM TWO-STEPS, 300 F+ COALITE LC-FINING
FOLLOWED BY FIXED-BED HYDROCRACKING OF
575-975 F LC-FINATE VGO.

TABLE 5.4.1-5B

SUMMARY OF PROPERTIES OF FIXED-BED HYDROTREATED PRODUCTS

FROM HYDROCRACKED COALITE DISTILLATE

CATALYST: K-599 (1ST STAGE)/K-599 (2ND STAGE)

FILE ID: REPTBP6

TEST # (FB-)	165	166	167	168
DATE (1989)	06-12	06-13/14	06-14	06-15
START TIME	21:00	03:00	10:00	19:00
END TIME	23:00	06:00	15:00	06:00
FEEDSTOCK	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.9465	0.9013	0.9254	0.9490
API GRAVITY @ 60 F	18.0	25.5	21.4	17.6
REFRACTIVE INDEX, @ 20 C	1.5239	1.4909	1.5088	1.5260
ELEMENTAL, wt. %				
C	88.44	87.16	88.02	
H	11.59	13.04	12.39	
SIMULATED DISTILLATION, F				
IBP		191		
10% DISTILLED		423		
30%		541		
50%		600		
70%		647		
90%		714		
VOLUM. AVG. BOIL. PT. F		585		
WATSON K		11.19		
F.I.A./R.I., vol. %				
OLEFINS				
SATURATES				
AROMATICS				
WLHV, btu/lb.		18070		
VLHV, btu/gal.		135666		
FLASH PT. F				
SMOKE PT., °F		15		
FREEZ. PT., F		57		
ANILINE PT., F		139		
CETANE INDEX *6		35.4		
VISCOSITY, cs @ -4 F		75		

FEEDSTOCK TYPE:

A: 350-750 F CRACKED COALITE DISTILLATE.
 FROM TWO-STEPS, 300 F+ COALITE LC-FINING
 FOLLOWED BY FIXED-BED HYDROCRACKING OF
 575-975 F LC-FINATE VGO.

TABLE 5.4.2-1A

SUMMARY OF OPERATING RESULTS HYDROTREATED PRODUCTS FROM FIXED-BED HYDROTREATING OF

THERMALLY PROCESSED COALITE DISTILLATE

CATALYST: K-550 (1ST STAGE) K-599 (2ND STAGE)

TEST # (FB-)	45	126	127
DATE(1989)	02-03	04-19	04-19
START TIME	10:50	07:30	13:30
END TIME	11:50	09:30	14:45
FEEDSTOCK	A	B	B
% HDS			89.9
% HDN			78.5
% HDG			
H2 UPTAKE, scf/bbl	7000	7000	7000
% F.I.A. OLEFINS SATURATION	96.2	98.0	98.2
% F.I.A. AROMATICS SATURATION	81.8	79.5	81.0
API IMPROVEMENT	34.9	40.6	41.0
R.I. DEPRESSION	1.4635	1.4496	1.4488
EST. HEAT OF REACTION, Btu/lb	18233	18109	18478

FEEDSTOCK TYPE:

A: THERMALLY PROCESSED COALITE DISTILLATE. 300-650 F @ 100 psig COKEDRUM PRESSURE.
 B: THERMALLY PROCESSED COALITE DISTILLATE. 300-575 F @ 62 psig AVERAGE COKEDRUM PRESSURE.

TABLE 5.4.2-1B

SUMMARY OF PROPERTIES OF HYDROTREATED PRODUCTS FROM FIXED-BED HYDROTREATING OF

THERMALLY PROCESSED COALITE DISTILLATE

CATALYST: K-550 (1ST STAGE) K-599 (2ND STAGE)

TEST # (FB-)	45	126	127
DATE(1989)	02-03	04-19	04-19
START TIME	10:50	07:30	13:30
END TIME	11:50	09:00	14:45
FEEDSTOCK	A	B	B
SPECIFIC GRAVITY, gm/cc	0.8504	0.8222	0.8203
API GRAVITY	34.9	40.6	41.0
REFRACTIVE INDEX @ 20 C	1.4635	1.4496	1.4486
ELEMENTAL, wt. %			
C	86.16		86.00
H	13.32		14.15
DISTILLATION, F			
1BP	184		188
10%	275		255
30%	360		350
50%	430		401
70%	489		430
90%	544		526
VOLUM. VAP. BOIL. PT., F	426		404
ANAL. ANALYSIS, 1vol. %			
OLEFINS	0.1	0.3	0.3
SATURATES	89.4	88.8	88.8
AROMATICS	10.1	10.7	10.7
NH ₃ , BTU/lb.	18233 *	18109	18478
VLHV, BTU/gal.	129158 *	124027	126262
FLASH PT., F			
SMOKE PT., °F			
FREEZ. PT., F			
ANILINE PT., F			
VISCOSITY, cs @ -4 F			

FEEDSTOCK TYPE:

A: THERMALLY PROCESSED COALITE DISTILLATE, 300-650 F @ 100 psig COKEDRUM PRESSURE.

B: THERMALLY PROCESSED COALITE DISTILLATE, 300-575 F @ 62 psig AVERAGE COKEDRUM PRESSURE.

* EXTRAPOLATED FROM REGRESSION ANALYSIS.

problems associated with the high hydrogen uptake rates. This problem would be magnified in a true adiabatic commercial unit necessitating multi-bed quenching operations.

As an alternative to the afore-mentioned approach, an initial hydrotreating step prior to the fixed-bed hydrocracking step would input some degree of hydrogen uptake and thus ameliorate the heat removal requirements in the subsequent downstream hydrocracker. In view of the various distillate fractions that will be required to process the raw COALITE, it was decided to hydrotreat a dewatered and essentially full-range (300F+) COALITE stream. This was carried out in the stirred autoclave simulator of the LC-Fining process at nominal conditions of 750F, 1950 psig hydrogen partial pressure and 0.8 liquid hourly space velocity. (The "standard" hydrocracking severity used in the earlier 650F+ COALITE LC-Fining studies included 800-820F temperature, 0.4 space velocity and 2000 psig).

The resultant hydrotreated 300F+ COALITE was then fractionated in the 4-in Batch Still and the Equilibrium Flash Vaporization units to produce a hydrotreated 300-600F distillate; a hydrotreated 600-975F HVGO; and a hydrotreated 975F+ vac resid.

The hydrotreated 600-975F vacuum gas oil (HVGO) was subjected to fixed-bed hydrocracking over the proprietary Amoco hydrocracking catalyst in a series of test scans to evaluate temperature, hydrogen partial pressure and space velocity. The thus hydrotreated hydrocrackates were distilled in a laboratory column to produce a nominal 300-750F distillate for subsequent fixed-bed hydrotreating and upgrading to HEDF product. The higher 750F cut point was selected to allow the continued evaluation of the effect of higher cut points on volumetric energy densities.

The two 300-750F distillates, namely, the raw COALITE and that recovered from the selective fixed-bed hydrocracking of a 650-975F LC-Finate derived from mild LC-Finingsm of the 300F+ COALITE, had similarities in physical properties as per the following:

<u>Feed Source</u>	<u>Raw COALITE</u>	<u>Selectively Hydrocracked LC-Finate-derived HVGO</u>
Refractive Index	1.5445	1.5406
API Gravity	11.4	15.6
Specific Gravity	0.9902	0.9619
Hydrogen Content, wt%	9.62	10.97
VLHV, Btu/gal	133,000	138,931

Of note is the fact that the selectively hydrocracked HVGO has a higher hydrogen content but a lower specific gravity than that of the comparable raw COALITE distillate.

Upon fixed-bed hydrogenation (test FB-166), the selectively hydrocracked LC-Finate HVGO appeared to generate a higher specific gravity product at comparable hydrotreating severity to that achieved with the raw COALITE distillate feedstock (test FB-172). Moreover, the volumetric energy density was significantly higher as can be seen from the following table:

<u>Product Source</u>	<u>HDT COALITE</u> (FB-172)	<u>Hydrotreated Selectively</u> <u>Hydrocracked LC-Finate</u> <u>Derived HVGO (FB-166)</u>
Specific Gravity	0.8571	0.9013
API Gravity	33.6	25.5
Refractive Index	1.4716	1.4909
Hydrogen Content, wt%	13.37	13.04
FIA Aromatics, wt%	16.3	-
VLHV, Btu/gal	130,050	135,666

It would appear that the hydrogenation of the HEDF precursors contained in the selectively hydrocracked LC-Finate derived HVGO retain their desirably higher specific gravity-energy content properties to a greater extent than that of the raw COALITE distillate counterparts.

It should be pointed out that in both cases, the product energy densities are based on the measurement of the total liquid product, unfractionated, recovered from the hydrotreating operations. In order to meet all of the required turbine fuel specifications, a fractionation post-treatment would be required to adjust volatility and viscosity/freeze point properties. In the case of the above two examples, the end points were extended to 750F as per DOE's suggestion in order to maximize product energy densities. Although this was achieved, as noted by the ca. 130,000+ Btu/gal values, the higher end points corresponded to unacceptably high freeze points.

The final distillation operations for adjustment of front-end volatiles (i.e., flash point) and back-end waxes (i.e., freeze point, viscosity) were completed for the HEDF product derived from the selective VGO hydrocracking route. Table 5.5-1 summarizes the properties of the final product. All specifications were met and all identified target properties were exceeded with the exception of smoke point. It appears that the F.I.A. aromatics content of 10% was a little high resulting in the adverse 15 mm smoke point. Thus, FB-166 should have been operated at a slightly higher hydrogenation severity to reduce the aromatics to below 10%, preferably between 5 and 7.5%. From the earlier data on the hydroprocessing of the raw 300-600F COALITE, it would appear that an increase in smoke point of 5 mm would require an aromatics reduction of about 5% suggesting that both the smoke point and the aromatics content specs can be met.

This small but finite incremental hydrogenation unfortunately will result in some further reduction in the volumetric energy density. On the positive side, the prior hydroprocessing data with the raw COALITE distillate indicated that at HEDF aromatics levels below about 20%, there was not a great effect of aromatics content on volumetric energy densities.

TABLE 5.5-1

COMPARISON OF COALITE-DERIVED HEDF FUELS

PRODUCED VIA TWO HYDROPROCESSING SCHEMES

Property	Specification	Selective HYC	Raw Dist. HD
VLHV, Btu/gal	130,000 (min)	132,915	129,095
FREEZE PT, F	-50	-60	-54
FLASH PT, F	100 (min)	115	115
% HYDROGEN	12.5 (min)	13.2	13.9
% AROMATICS	5 min; 25 max	10.0	5.0
SULFUR, ppmw	500 max	<2	<5
% OLEFINS	5 max	<0.5	<0.5
VISC, cst/-4F	8 min; 12 max	11.0	8.0

5.5.2 Subtask 3.1/3.2 Scope

In view of these promising results and DOE's desire to increase the target HEDF energy density from 130,000 Btu/gal to 135,000 Btu/gal, a contract modification was executed. A new Subtask 3.1/3.2 was formulated to concentrate on the selective hydrocracking route by investigating alternative catalysts that will simultaneously produce HEDF test fuels having the targetted high (ca., 135,000 Btu/gal) energy densities and acceptable thermal stability characteristics. The Colorado shale oil studies were to be deemphasized because of their apparent limited cyclics content that prevents the achievement of the 130,000+ Btu/gal energy densities.

It has been hypothesized that there is a set of operating conditions that exists in which a high density jet fuel fraction, derived from hydroprocessing of COALITE heavy distillates, will have an energy density of 135,000 Btu/gal or higher and meet some acceptable thermal stability criterion. Of the many parameters that might affect the achievement of these goals, those that are anticipated to have the greatest influence on energy density and stability include:

- o COALITE feedstock definition
- o Hydroprocessing steps including fractionation between steps to pinpoint preferred distillate compositions
- o Catalyst type
- o Thermal severity as measured by reaction temperature and space velocity

COALITE Feedstock Definition

From the prior Task 3 screening efforts, it was determined that hydrocracked heavy distillates had higher energy densities, by some 3000-4000 Btu/gal, than those of distillates boiling in the jet fuel range by virtue of being thermally cracked during the COALITE MCG process. By tailoring the selective hydrocracking operations to near optimal conditions, it might be possible to increase the energy density advantage over the as-produced jet fuel-range distillates by as much as 5000-6000 Btu/gal.

Assuming the end-point of the finished HEDF product will be 575F, the raw COALITE was fractionated to generate a 575F+ resid, more than 90% of which boils below 975F. The latter vacuum gas oil (VGO) cut, namely, 575-975F, is the candidate feedstock for the selective hydrocracking campaigns of Subtask 3.2.

Hydroprocessing Sequence

The hydroprocessing of the heavy COALITE fractions is carried out in several steps of hydrogen uptake, heteroatom removal, hydrocracking and aromatics saturation. The multi-step operation represents the best

approach from the points of view of reactor design, heat removal, and catalyst selectivity/activity. The stepwise process consists of:

1. LC-Fining of 575F+ resid
2. Flash vaporization to recover the 975F- LC-Finates
3. Fixed-bed hydrodenitrogenation of the 975F- LC-Finates
4. Fixed-bed hydrocracking of the hydrodenitrogenated 975F- LC-Finates
5. Fixed-bed hydrogenation (aromatics saturation) of the selectively hydrocracked LC-Finates
6. Fractionation to recover the Category I HEDF product (and Category II and III distillate byproducts)

LC-Fining

The LC-Fining step might commercially be substituted with a fixed-bed resid hydrotreating process. Its primary function is to perform some degree of hydrogen uptake in a manner that can cost effectively remove the corresponding exothermic heats of reaction. Along with HDN, olefins are saturated, some aromatics are saturated and much of the organic oxygen is removed. Additionally, there is some degree of hydrocracking, defined as conversion to 575F-. The LC-Finer also allows the hydroprocessing of the resid portion of the COALITE which contains some coal char fines and coal mineral matter that are normally poisons and deactivators in fixed-bed hydroprocessing units.

The LC-Finer is being used as a unit to prepare feedstock for downstream hydroprocessing technology evaluations and is operated at constant conditions of 2000 psig pressure, 760F reactor temperature, 0.8 LHSV (based on catalyst volume) and 6000 scf/bbl treat gas rate using Criterion 324M catalyst, a nickel-moly catalyst used extensively in coal hydroliquefaction operations.

Flash Vaporization

The LC-Finate product, containing hydrocracked 575F- distillates, hydrotreated 575-975F distillates, and hydrotreated 975F+ resid, is flashed in a continuous equilibrium flash vaporization (EFV) unit operated at 575F and 25 mm Hg absolute. These flashing conditions approximate a 975F atmospheric equivalent end point of the recovered HVGO (hydrotreated VGO). The hydrocracked jet fuel-range distillates co-produced with the HVGO during the LC-Fining operations were not separated from the HVGO and are co-hydroprocessed in the downstream units. Thus, the final HEDF product will have the LC-Finate hydrocrackate and fixed-bed hydrocrackate products co-mingled.

Fixed-Bed Hydrodenitrogenation (HDN)

The primary function of the fixed-bed HDN step is to reduce the nitrogen content of the HVGO sufficiently to protect the downstream selective hydrocracking catalyst, which is sensitive to N poisons. The catalyst selected for this step is Akzo KF-843, a commercial high moly nickel on alumina, first-stage (HDN) hydrocracking catalyst. The thermal operating severity as measured by reaction temperature and

residence time (i.e., space velocity) at constant pressure will be scanned to determine the best conditions for production of hydrodenitrogenated HVGO for the downstream fixed-bed hydrocracking scans.

Fixed-Bed Hydrocracking

The fixed-bed hydrocracking step represents the key in being able to selectively hydrocrack HVGO components to the desirable two-ring and three-ring aromatic precursors to HEDF. The key to the selectivity potential resides in the catalyst type. In this program, three catalysts are under consideration: 1) Akzo KF-1015, a commercial nickel-moly Mild Hydrocracking catalyst; 2) a proprietary Amoco nickel-tungsten catalyst previously tested in Task 3; and 3) a new sulfur-resistant, proprietary zeolitic hydrocracking catalyst being offered by Zeolyst Enterprises.

Each catalyst was evaluated in a series of scans to identify that combination of thermal severity and hydrogen partial pressure that results in maximum HEDF precursor yield and maximum precursor quality, the latter being used as a measure of HEDF energy density. From an analytical viewpoint, HEDF precursor quality may be assessed from FIA analysis, HNMR analysis and density-hydrogen content relationships.

Fixed-Bed Hydrogenation (Aromatics Saturation)

A final aromatics saturation step may be required for final hydro-finishing depending upon the selectivity of the hydrocracking catalyst. The proprietary zeolitic catalyst from Zeolyst Enterprises had dual functionality, namely, hydrocracking and ring saturation. In this situation, a final fixed-bed hydrogenation step was not required. For the other hydrocracking catalysts, fixed-bed hydrogenation is required. The key here is to determine the optimal extent of aromatics saturation that will maximize HEDF energy density. This is a function of the hydrogenation severity. Although many nickel-moly or nickel-tungsten hydrogenation catalysts are commercially available, Katalco K-599, a nickel-moly catalyst used extensively in the earlier Task 3 screening program and for which a database exists, was utilized for this hydroprocessing step. A post-hydrogenation finishing step, namely, clay treating, was used to reduce trace polar compounds that might otherwise detrimentally affect the fuel properties of thermal stability and corrosion resistance.

5.5.3 Subtask 3.1/3.2 Results

The purpose of subtask 3.2 was to explore ways to produce a stable high energy density (130,000+ Btu/gal) HEDF test fuel from raw COALITE feed through a selective hydrocracking/hydrotreating approach. The campaign initiated to achieve this goal is illustrated in Figure 5.5.3-1 and detailed below:

- Step 1. The COALITE feed was charged to the 8" batch distillation unit. Run EBD-41 was an atmospheric distillation to produce a 300°F+ material followed by EBD-42 which was a vacuum distillation to produce the 575°F+ material for the LC-Finingtm reactors.
- Step 2. The 575°F+ COALITE was then fed to the LC-Finingtm unit consisted of 2 expanded-bed reactors in series each loaded with 3000cc of Shell 324M catalyst. The operating conditions were 2000 psig pressure, 765°F average reactor temperature and 1.6 LHSV per bed. The product from the LC-Finingtm stage achieved an HDN rate of 84%, HDS of 98%, 575°F+ conversion of 30 vol%, and a 975°F+ conversion of 65 vol%. Enough LC-Finate was generated to conduct the subsequent HDN, hydrocracking and hydrogenation scans.
- Step 3. The LC-Finate from Step 2 was then processed in an Equilibrium Flash Vaporization Unit (EFV) operated at vacuum to remove the 900°F+ material. The resulting IBP-900°F material was then used as feed for the HDN fixed bed scans.
- Step 4. The IBP-900°F distillate then sent to an HDN fixed bed unit where the nitrogen was reduced from 1700 ppm to 43 ppm. The HDN unit was a downflow fixed bed unit with 2 reactors in series. The catalyst charged to each reactor was 165cc Katalco KF-843 extrudates. A total of 18 scanning runs (Runs FB-194-211) were performed at different pressures, liquid hourly space velocities, and reactor temperatures. Production runs were then made to generate HDN material for subsequent fixed bed hydrocracking and hydrotreating operations. The conditions were 2000 psig unit pressure, 1.0 liquid hourly space velocity, and 780°F average reactor temperatures.
- Step 5. Material from the hydrodenitrogenation step was then hydrocracked in a single stage downflow fixed bed reactor. The scanning tests employed AKZO KF-1015 Ni/Mo catalyst for Runs FBHC 37 and 38 and a proprietary zeolitic catalyst for Runs FBHC 39-43.

Run FBHC-37 was a scanning campaign with seven different conditions of space velocity and reactor temperatures at a set pressure of 2000 psig. As a result of the scanning tests, a production run (Run FBHC-38) was made at 2000 psig, 760°F reactor temperature, and a liquid hourly space velocity of 0.5 hr⁻¹ to generate material for the hydrotreating step.

Run FBHC-39 was a scanning test using the proprietary zeolitic catalyst with six different conditions of space velocity and temperature at a set pressure of 2000 psig. The catalyst activity was so high at the conditions that all

of the material cracked out of the jet fuel range into the 275°F- naphtha range. Based on the above observations a second scanning run (FBHC-40) was initiated at lower operating pressures of 1000 psig and reactor temperatures of 550-650°F. Based on the results of the scanning tests, three different production runs (FBHC-41, 42, and 43) were performed with the proprietary zeolitic catalyst. The activity of this catalyst towards hydrocracking and ring saturation was so high that the final hydrotreating step to produce the desirable cycloparaffins was not required. The products from FBHC-41, 42 and 43 were then fractionated and treated with bentonite clay.

- Step 6. A series of hydrotreating runs was performed with a 2 stage fixed bed reactor system using a) hydrodenitrogenated but not hydrocracked LC-Finate distillate from Run FB-213; and b) hydrocracked LC-Finate distillate from Run FBHC-38.

The fixed bed hydrogenation Run FB-214 employed two reactors in series each containing 165cc of Criterion 424 NiMo catalyst. Three scanning tests were performed with the hydrodenitrogenated LC-Finate distillate prior to a production run (Run FB-214D) at 2000 psig unit pressure, 0.5 liquid hourly space velocity, and 715°F average reactor temperature. This run was followed by a production run (FB-214E) at the same conditions except using the hydrocracked (FBHC-38) hydrodenitrogenated LC-Finate distillate as the feed. After the two production runs, one more test was made with the hydrodenitrogenated LC-Finate distillate at 2000 psig unit pressure, 0.25 liquid hourly space velocity and 750°F reactor temperature. This test was made to assess the impact of a 10°F increase in thermal severity on HEDF fuel properties.

5.5.3.1 LC-Fining Studies

The first step in the overall sequence to produce finished HEDF test fuel from the raw COALITE feed is to hydroprocess the atmospheric resid cut via expanded-bed LC-Fining. The throughput to the LC-Fining unit was specified to insure that there would be a minimum quantity of HEDF precursors in the LC-Finate products necessary for the subsequent screening studies. Run 6LCF-11 was carried out using fresh Shell 324M NiMo catalyst. The 6LCF-11 feed was derived from the 575F+ atmospheric resid fraction recovered during the batch fractionation (in an 8-in batch fractionation unit) of the raw COALITE material.

The pilot plant LC-Fining unit was used because of its large size and short operating time needed for production of the Task 3 quantities of materials required. All of the downstream screening tests for the HDN, selective hydrocracking and aromatics saturation were made in bench-scale unit. After the LC-Finer was successfully pressure tested at 2500 psig hydrogen pressure, it was commissioned with a 350-575F raw COALITE distillate until the catalyst bed temperature was 500°F. At this point, the distillate feed was removed and the 575F+ resid was introduced which increasing the heat inputs until the desired catalyst bed temperature was achieved.

The run proceeded for four days without any major operating problems. The reactor operating conditions were 2000 psig operating pressure, 764F average catalyst bed temperature, 6000 scfb treat gas rate and 1.64 LHSV per each of the two catalyst beds.

As indicated in Table 5.5.3.1-1, the products from this LC-Fining step resulted in an HDN rate of 84%, and HDS rate of 98%, a 575F+ conversion of 30 vol% and a 975F+ conversion of 65 vol%. At the end of run 6LCF-11, the composited heavy oil fraction containing unconverted 975F+ COALITE was processed in the Equilibrium Flash Vaporization unit to remove the vac resid material. The entire IBP-900F LC-Finate distillate, which contains HEDF precursor components as well as the vacuum gas oil (VGO) fractions, was composited and drummed for subsequent processing in the bench-scale, fixed-bed hydrotreating unit for deep denitrogenation.

5.5.3.2 Fixed-Bed Hydrodenitrogenation Studies

A total of 165 cc of KF-843 catalyst was charged to each of the two fixed-bed reactors. The catalysts were calcined in situ at 750F for two hours followed by presulfiding with a 2% H₂S/H₂ gas mixture. After the presulfiding operations following the vendor's procedure, the unit was successfully pressure tested at 2500 psig.

The IBP-900F LC-Finate distillate was then subjected to hydrodenitrogenation in a series of 18 brief scanning runs (Table 5.5.3.2-1) to assess the effects of reactor pressure, LHSV and bed temperature at constant hydrogen treat gas rate. From these scans, the conditions of 2000 psig reactor pressure, 1.0 LHSV and 780F average bed temperature were selected as the preferred conditions for an HDN production run. The material thus produced was used for the downstream fixed-bed hydrocracking and aromatics saturation screening tests.

5.5.3.3 Fixed-Bed Selective Hydrocracking Studies

The full-rane hydrodenitrogenated LC-Finate distillate was then subjected to selective hydrocracking in a single-stage fixed-bed reactor. Two candidate hydrocracking catalysts were evaluated: a NiMo catalyst (Akzo KF-1015) in runs FBHC-37 and -38 and a proprietary zeolitic catalyst (Zeolyst Z704A) in runs FBHC 39-41.

Run FBHC-37 consisted of seven process variable scans of space velocity and bed temperature at 2000 psig reactor pressure and 6000 scfb treat gas rate (see Table 5.5.3.3-1). Based on these scans, a production run (FBHC-38 as delineated in Table 5.5.3.3-2) was made at 2000 psig, 6000 scfb treat gas rate, 0.5 LHSV and average bed temperature of 758F to generate enough HEDF precursors for final aromatics saturation prior to HEDF finishing.

Run FBHC-39 consisted of six process variable scans of space velocity and bed temperature at 2000 psig reactor pressure and 6000 scfb treat gas rate. The hydrocracking activity of this zeolitic catalyst was so high at bed temperatures above about 700F that essentially all of the jet fuel range material was cracked into the naphtha range as shown on Table 5.5.3.3-3.

TABLE 5.5.3.1-1
SUMMARY RESULTS FOR LC-FINING RUN 6LCF-11

PERIOD NUMBER	3
DATE	1990 3/31
AVG. CATALYST TEMP. (1st STAGE)	759
AVG. CATALYST TEMP. (2nd STAGE)	769
TOTAL PRESSURE, PSIG	2000
LHSV, HOURS-1	0.82
CATALYST AGE, BBL/LB	0.17
WDSV, BBL/LB/DAY	0.071
CATALYTIC H2, SCF/BBL	5900
CARBON BALANCE, WT.% RECOVERY	101
OVERALL MAT. BAL., WT.% RECOVERY	96
FEED COALITE (575F+) PROPERTIES	
API GRAVITY	-3.7
CARBON, WT.%	85.37
HYDROGEN, WT.%	8.01
SULFUR, ppm	10200
NITROGEN, ppm	14100
OXYGEN, WT.%	4.03
ASH, WT.%	0.16
975F+ RESID, VOL.%	18
LIGHT OIL PRODUCT PROPERTIES	
API GRAVITY	28.2
CARBON, WT.%	87.82
HYDROGEN, WT.%	12.05
SULFUR, ppm	195
NITROGEN, ppm	1118
OXYGEN, WT.% (DIFF.)	0
575F+ RESID, VOL.%	23
HEAVY OIL PRODUCT PROPERTIES	
API GRAVITY	11.6
CARBON, WT.%	89.32
HYDROGEN, WT.%	10.24
SULFUR, ppm	186
NITROGEN, ppm	3121
OXYGEN, WT.% (DIFF.)	0.11
ASH, WT.%	0.02
575F+ RESID, VOL.%	88.8
975F+ RESID, VOL.%	9.0
DAILY PRODUCT YIELDS, WT.% FEED	
OFFGAS H2S	1.07
OFFGAS NH3 + H2O	5.89
OFFGAS C1	0.69
OFFGAS C2	0.66
OFFGAS C3	0.70
OFFGAS C4	1.66
OFFGAS C5+	0.81
LIGHT OIL	29.68
HEAVY OIL	62.30
TOTAL	103.46
H2 CONSUMPTION, SCF/BBL	2700
DENITRIFICATION, WT.%	84
DESULFURIZATION, WT.%	98
VOL.% 575 DEG. F + CONVERSION	30
VOL.% 975 DEG. F + CONVERSION	65

TABLE 5.5.3.2-1 1 of 3

[illegible]

202

TABLE 5.5.3.2-1 2 of 3

[illegible]

TABLE 5.5.3.2-1 3 of 3

09-04-91

RESULTS OF FIXED-BED HYDROTREATING OF 575 F COALITE LC-FINITE

PROJECT NUMBER: 9-27200003

FILE ID: CCF00003.WKT

PRINTING RANGE: 31-44/105

Re-1: CATALYST, KF-643, VOLUME=185 cc, WEIGHT=142.7 gm %

Re-2: CATALYST, KF-643, VOLUME=185 cc, WEIGHT=142.5 gm %

DATE OF OPERATION (1988)	FEED %	04-18	04-17	04-20	04-20	04-21	04-22	04-23	04-24	04-25	04-26	04-28	04-28
RUN #		FB-208 % 21:00- 23:00	FB-208 % 05:00- 07:00	FB-210 % 06:30- 07:30	FB-211 15:00- 21:00	FB-212 *10 08:30- 21:00	FB-212 08:30- 10:00	FB-212 08:30- 10:00	FB-212 08:30- 10:00	FB-212 08:30- 10:00	FB-212 08:30- 10:00	FB-212 08:30- 10:00	FB-212 08:30- 10:00
H2 TREAT RATE, mol/hr		7000	7000	7000	7000	7000	7000	7000	7000	7000	7000	7000	7000
PRESSURE, psig		2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
SPACE VELOCITY, cc/hr/cc cat.		0.48	0.52	1.00	0.95	0.97	0.97	1.00	0.98	1.03	1.05	1.05	1.05
REACTOR #1													
Re-1 TOP TEMP, F		763	728	(687)	(378)	763	773	773	772	772	772	773	773
Re-1 MID TEMP, F		763	745	740	760	774	774	773	772	772	772	773	773
Re-1 BOTL TEMP, F		761	741	742	761	774	774	773	772	772	772	773	773
Re-1 BTM TEMP, F		688	728	723	741	774	774	773	772	772	772	773	773
AVG TEMP, F %		762	741	741	761	775	775	774	773	773	773	774	774
AVG TEMP, (1/10)*1000		1.55	1.50	1.50	1.47	1.46	1.46	1.46	1.46	1.46	1.46	1.46	1.46
REACTOR #2 %													
Re-2 TOP TEMP, F		689	728	741	763	775	775	774	772	769	769	769	769
Re-2 MID TEMP, F		763	743	740	762	775	775	774	772	774	774	774	774
Re-2 BOTL TEMP, F		760	741	740	761	776	774	774	774	776	774	776	776
Re-2 BTM TEMP, F		762	742	738	768	772	774	773	773	774	773	774	774
AVG TEMP, F %		761	741	740	761	775	773	773	773	773	773	774	774
AVG TEMP, (1/10)*1000		1.55	1.50	1.50	1.47	1.46	1.46	1.46	1.46	1.46	1.46	1.46	1.46
AVG TEMP, Re-1 & Re-2, F		761	741	740	761	775	773	773	773	773	773	774	774
P.L. @ 50 C													
SP. GRV, g/cc		1.263	1.267	1.262	1.267	1.263	1.265	1.265	1.265	1.265	1.267	1.267	1.267
A.P.L. GRAVITY		0.821	0.817	0.816	0.817	0.823	0.825	0.825	0.825	0.825	0.825	0.825	0.825
DISTILLATION, F		18.7	24.8	22.3	22.3	24.1	24.1	24.1	24.1	24.1	24.1	24.1	24.1
180-P		182	208	185	184	188	188	188	188	188	188	188	188
160-P		371	386	341	341	328	328	328	328	328	328	328	328
140-P		503	463	463	463	477	463	463	463	463	463	463	463
120-P		611	662	662	662	668	668	668	668	668	668	668	668
100-P		762	687	687	684	684	684	684	684	684	684	684	684
80-P		911	773	746	746	753	753	753	753	753	753	753	753
60-P		988	947	938	931	918	918	918	918	918	918	918	918
40-P		991	989	983	985	982	982	982	982	982	982	982	982
SMALL DATA RESULTS:													
% 575 F+ CONTENT		57.8	65.0	51.3	48.0	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5
% 575 F- MAKE		3.7	11.0	7.2	7.2	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5
% 575 F+ CONV.		18.8	18.3	12.6	12.6	18.4	18.4	18.4	18.4	18.4	18.4	18.4	18.4
ELEMENTAL													
C wt % %		88	88	88	88	88	88	88	88	88	88	88	88
H wt % %		11	11	11	11	11	11	11	11	11	11	11	11
ORGANIC N ppm %		1794	179	177	68	32	47	38	37	45	45	45	45
ORGANIC S ppm %		289	18	16	4	3	28	<37	<37	43	43	43	43
O (BY DIFF.)													
K(H2O), (1/100)*1000		0.31	0.43	0.53	0.59	1.05	0.97	1.05	1.07	1.01	1.01	1.01	1.01
K(MVC), (1/100)*1000		1.43	3.10	2.75	2.75	5.37	5.37	5.37	5.37	5.37	5.37	5.37	5.37
L I. %		0.035											

* New catalyst, selected @ 400 C for one hour.

* Additional 25 cc of Kellogg QG-100, 1/10P alumina is added to the 575F of catalyst.

KF-643 in Re-1 & Re-2, weight of 11.8 gm & 12.0 gm respectively.

* Feed source: Confiner units -> 9' dist. (200+ P) -> 6LCP-11. (H2O & LQ) -> EPV, #182. (H2O & LQ) ->

* 9' dist. ar. of all the 4 bed tanks. Temp. measured at 1/2, 3/4, 7/10 1/4' in 12' catalyst bed (top to bottom).

* Tested by UECO, CHN-OEL sample not under test.

* Tested by ChemLumina for debenzene method, sample were under test or H2 dropped before test.

* Repeat run #184

* Repeat run #185

* Repeat run #186

* Tested on Chromatograph H2 52

H2 dropped 32.4 30.8

H2 dropped & 31.4 30.8

H2O washed

H2 dropped 3.1

Hg washed

*10 Production run. Start on stream @ 08:00 04/23/88

204

TABLE 5.5.3.3-1

FIXED BED
HYDROCRACKING
RUN FBHC-37

CATALYST: 165cc AKZO KF-1015 Ni/Mo

	FEED*	37A	37B	37C	37D	37E	37F	37G
	----	----	----	----	----	----	----	----
OPERATING CONDITIONS:								
CATALYTIC H ₂ , SCF/BBL	-	6000	6000	6000	6000	6000	6000	6000
RUN DURATION, HRS.	-	2	2	4	2	4	2	1
AVG. RX. TEMP., DEG. F	-	655	656	703	708	754	751	734
PRESSURE, PSIG	-	2000	2000	2000	2000	2000	2000	2000
AVG. FEED RATE, cc/hr	-	85	188	68	163	61	178	310
LHSV, cc/hr/cc cat.	-	0.52	1.14	0.41	0.98	0.37	1.08	1.88
FEED IN, gms.	-	154	341	245	295	220	322	282
TLP OUT, gms.	-	176	318	235	322	222	297	307
RECOVERY, %	-	114	93	96	109	101	92	109

ANALYTICAL RESULTS:

TLP GRAVITY, gms/cc	0.9082	0.8956	0.9013	0.8789	0.8916	0.8639	0.8762	0.8888
TLP GRAVITY, API	24.3	26.5	25.5	29.5	27.2	32.3	30.0	27.7
DISTILLATION:								
IBF-275 F, WT.%	5.3	5.5	5.1	7.0	6.7	8.7	10.5	6.8
275-575 F, WT.%	49.3	50.4	51.8	58.1	53.9	66.6	59.0	57.5
575 F+, WT.%	45.4	44.1	43.1	34.9	39.4	24.7	30.5	35.7
CONV. 575+, WT.%	-	3	5	23	13	46	33	21
JET FUEL CUT, 275-575 F:								
GRAV., gms/cc	0.8860	0.8811	0.8827	0.8713	0.8783	0.8618	0.8729	0.8783
GRAV., API	28.2	29.1	28.8	30.9	29.6	32.7	30.6	29.6
R.I., @ 20 DEG. C	1.4888	1.4817	1.4838	1.4755	1.4819	1.4709	1.4794	1.4840
H/C RATIO	1.65	1.74	1.71	1.78	1.71	1.80	1.70	1.66
ELEMENTALS, WT.%								
CARBON	87.88	87.20	87.38	87.07	87.48	86.84	87.23	87.04
HYDROGEN	12.12	12.67	12.45	12.90	12.50	13.06	12.33	12.03
F.I.A., VOL.%								
AROMATICS	40.7	-	-	-	-	-	-	-
OLEFINS	0.9	-	-	-	-	-	-	-
SATURATES	58.4	-	-	-	-	-	-	-

* THE FEED FOR THE RUN IS COALITE OIL THAT WAS TOPPED TO 300 DEG F+ IN THE 8th BATCH AND PROCESSED IN THE LC-FINING UNIT (RUN 6LCF-11 UPGRADED & REMOVED NITROGEN TO 1000 ppm). THE LC-FINATE WAS THEN RUN THROUGH THE EFV UNIT TO OBTAIN THE 300-975 FRACTION. FINALLY THE FEED WAS HYDROTREATED AND NITROGEN REMOVED (40 ppm) IN FIXED BED RUNS FB-194-199, 202-203, & 211-213. THE SAMPLE # IS 3610.

TABLE 5.5.3.3-2

RUN FBHC-38
HYDROCRACKING COALITE DISTILLATE
MATERIAL BALANCE

PERIOD NUMBER	FEED*	FBHC-38
DATE	1990	8/30
TOTAL PRESSURE, PSIG		2000
LHSV, HOURS-1		0.49
AVERAGE TEMPERATURE, DEG. F		758
CATALYST AGE, BBL/LB		0.947
WDSV, BBL/LB/DAY		0.037
CATALYTIC H ₂ , SCF/BBL		5900
CARBON BALANCE, WT.% RECOVERY		97
OVERALL MAT. BAL., WT.% RECOVERY		98
HYDROGEN CONSUMPTION, SCF/BBL		700
575 DEG F+ CONVERSION, WT.%		61
TLP OIL PRODUCT PROPERTIES		
API GRAVITY	24.3	35.3
CARBON, WT.%	87.99	87.16
HYDROGEN, WT.%	12.00	12.84
SULFUR, ppm	34	9
NITROGEN, ppm	43	0.9
DAILY PRODUCT YIELDS, WT.% FEED		
OFFGAS H ₂ S		0.00
OFFGAS NH ₃ + H ₂ O		0.01
OFFGAS C ₁		0.27
OFFGAS C ₂		0.17
OFFGAS C ₃		0.57
OFFGAS C ₄		0.37
OFFGAS C ₅ +		0.62
IBP-275 DEG. F	5.3	19.42
275-575 DEG. F	49.3	61.83
575 DEG. F +	45.4	17.84
TOTAL	100.00	101.10
JET FUEL CUT (275-575 DEG F) PROPERTIES		
GRAVITY, API	28.2	32.8
GRAVITY, SP. @ 60/60	0.8860	0.8612
ELEMENTALS, WT.%		
CARBON	87.88	87.22
HYDROGEN	12.12	12.57
R.I., @ 20DEG C	1.4888	1.4729
F.I.A., VOL.%		
AROMATICS	42.0	30.5
OLEFINS	0.5	1.0
SATURATES	57.5	68.5

* THE FEED FOR FBHC-38 IS THE SAME AS RUN FBHC-37. REFER TO RUN FBHC-37.

SUMMARY OF FIXED BED HYDROCRACKING RUN
RUN FBHC-39

CATALYST: 165cc ZEOLITE Z-704A

	FEED	39A	39B	39C	39D	39E	39F
	****	----	----	----	----	----	----

OPERATING CONDITIONS:							
CATALYTIC H2 RATE, SCF/BBL	-	6000	6000	6000	6000	6000	6000
RUN DURATION, HRS.	-	4	2	4	2	4	2
AVG. RX. TEMP., DEG. F	-	649	653	701	701	751	750
PRESSURE, PSIG	-	2000	2000	2000	2000	2000	2000
AVG. FEED RATE, cc/hr	-	88	166	85	174	86	165
LHSV, cc/hr/cc cat.	-	0.53	1.01	0.52	1.05	0.52	1.00
FEED IN, gms.	-	318	302	310	316	312	300
TLP OUT, gms.	-	309	307	257	268	196	191
RECOVERY, %	-	97	102	83	85	63	64

ANALYTICAL RESULTS:

TLP GRAVITY, gms/cc	0.9082	0.7796	0.8473	0.7286	0.7475	0.6803	0.6879
TLP GRAVITY, DEG. API	24.3	50.0	35.5	62.7	57.8	76.5	74.2
H/C RATIO	1.64	2.05	1.91	2.17	2.13	2.30	2.24
TLP ELEMENTALS: *							
CARBON	88.00	84.90	86.48	83.64	83.95	81.98	83.18
HYDROGEN	12.00	14.50	13.73	15.10	14.92	15.69	15.52
DISTILLATION:							
IBP, DEG. F	-	105	190	108	115	81	80
ENDPOINT, DEG. F	-	640	720	480	595	310	346
DISTILLATION RECOVERY, % **		93.8	95.9	77.0	67.3	89.1	86.2
IBP-275 F, WT. %	5.3	49.9	14.9	77.3	70.4	98.8	96.4
275-575 F, WT. %	49.3	42.2	61.3	22.7	27.4	1.2	3.6
575 F+, WT. %	45.4	7.9	23.8	0.0	2.2	0.0	0.0
CONV. 575+, WT. %	-	83	48	100	95	100	100
JET FUEL CUT, 275-575 F:							
GRAV., gms/cc	0.8860	0.8222	0.8458	0.7844	0.8090	***	***
GRAV., DEG. API	28.2	40.6	35.8	48.9	43.4	-	-
R.I., @ 20 DEG. C	1.4888	1.4470	1.4585	1.4303	1.4420	1.4168	1.4248
H/C RATIO	1.65	2.00	1.94	2.08	2.03	2.12	2.09
JET FUEL ELEMENTALS, WT. %							
CARBON	87.88	85.33	85.53	84.77	84.62	84.58	85.06
HYDROGEN	12.12	14.20	13.80	14.71	14.34	14.94	14.79

* THE TLP SAMPLES FOR RUNS C THRU F WERE VERY VOLATILE RESULTING IN ERRATIC ELEMENTAL RESULTS.

** THE SAMPLES FROM FBHC-39 C-F WERE VERY VOLATILE. THE D-86 DISTILLATION COULD NOT CAPTURE THE VERY LIGHT ENDS WHICH RESULTED IN POOR RECOVERIES.

*** INSUFFICIENT SAMPLE FOR GRAVITY ANALYSIS.

**** THE FEED FOR FBHC-39 IS THE SAME AS FBHC-37. SEE NOTE ON RUN FBHC-37.

A second scanning test (FBHC-40) was made at a lower hydrogen partial pressure by reducing reactor pressure from 2000 psig to 1000 psig and by reducing bed temperatures to the 550-600F range. This resulted in a reduction in the per pass 575F+ conversion but with a significant increase in the selectivity to the HEDF jet precursor range as shown in Table 5.5.3.3-4. Based on these results, a production run (FBHC-41) was made at 1000 psig, 6000 scfb treat gas rate, 0.5 LHSV and 650F average bed temperature as shown on Table 5.5.3.3-5. During the run as the hyperactivity of the freshly activated catalyst declined, the bed temperature was increased a few degrees in order to maintain the gravity and hydrogen content of the jet range product approximately constant. Upon subsequent analysis of the results, it was determined that this catalyst had dual functionality, namely, simultaneous hydrocracking and ring saturation. Accordingly, the hydrocrackate product did not have to be further hydrotreated as was the case for the hydrocracked products generated from the NiMo based catalysts.

5.5.3.4 Hydrotreating Studies

Two series of two-stage, fixed-bed hydrotreating runs using Criterion 424 NiMo catalyst were performed with a) the hydrodenitrogenated LC-Finate distillate from FB-213; and b) the selectively hydrocracked hydrodenitrogenated LC-Finate distillate from run FBHC-38. The data are summarized on Table 5.5.3.4-1. Three scans were performed with the hydrodenitrogenated LC-Finate distillate and an HEDF production run (FB-214D) was then selected at the following conditions: 2000 psig reactor pressure, 4500 scfb treat gas rate, 0.5 LHSV and 715F average bed temperature. Subsequent to this production run, the feed was replaced with the selectively hydrocracked hydrodenitrogenated LC-Finate distillate (FBHC-38 product) and an HEDF production run was made at the same conditions as that of run FB-214D. After the completion of this run, a final hydrogenation scan was made (FB-214F) with the hydrodenitrogenated LC-Finate feedstock at a hydrogenation severity equivalent to higher temperature/lower space velocity in an effort to increase the degree of hydrogenation (as measured by both specific gravity and aromatics reduction) over and above that of the prior tests.

5.5.3.5 HEDF Finishing

All four candidate HEDF products generated during the production campaigns were fractionated in a laboratory TBP distillation column. The front-end distillate cuts were blended to meet the HEDF jet fuel flash point specification and the back-end distillate cuts were blended to meet the freeze point/viscosity specifications. The resultant composites were then clay treated in a laboratory-scale, glass adsorption column packed with bentonite to remove trace polar compounds. The resultant treated HEDF test fuels were subjected to full analytical testing and the results are presented in Table 5.5.3.5-1.

TABLE 5.5.3.3-4
SUMMARY OF FIXED-BED HYDROCRACKING RUN

RUN FBHC-40

CATALYST: 165cc ZEOLITE Z-704A

	FEED*	40A	40B	40C	40D	40E	40F	40G**
OPERATING CONDITIONS:								
CATALYTIC H ₂ , SCF/BBL	-	6000	6000	6000	6000	6000	6000	6000
RUN DURATION, HRS.	-	2	2	2	2	2	4	4
AVG. RX. TEMP., DEG. F	-	550	551	600	600	652	650	650
PRESSURE, PSIG	-	1000	1000	1000	1000	1000	1000	2000
AVG. FEED RATE, cc/hr	-	167	252	168	250	161	83	90
LHSV, cc/hr/cc cat.	-	1.01	1.53	1.02	1.52	0.98	0.50	0.55
FEED IN, gms.	-	302	458	304	454	292	302	328
TLP OUT, gms.	-	310	457	308	456	297	296	333
RECOVERY, %	-	103	100	101	100	102	98	102

ANALYTICAL RESULTS:

TLP GRAVITY, gms/cc	0.9082	0.8794	0.8879	0.8718	0.8756	0.8483	0.8309	0.8468
TLP GRAVITY, API	24.3	29.4	27.9	30.8	30.1	35.3	38.8	35.6
H/C RATIO	1.64	1.80	1.78	1.83	1.80	1.88	1.94	1.90
TLP ELEMENTALS:								
CARBON	88.00	86.75	86.70	86.48	86.87	85.81	85.84	86.04
HYDROGEN	12.00	12.98	12.87	13.17	13.06	13.44	13.89	13.63
DISTILLATION:								
IBP, DEG. F	-	205	218	190	188	160	130	143
ENDPOINT, DEG. F	-	736	720	738	724	748	678	706
DISTILLATION RECOVERY, %		100.0	100.0	100.0	99.9	90.4	98.1	98.5
IBP-275 F, WT. %	5.3	7.8	14.5	6.6	7.3	15.7	19.6	14.0
275-575 F, WT. %	49.3	52.6	45.3	57.9	57.2	55.3	60.8	60.8
575 F+, WT. %	45.4	39.6	40.2	35.5	35.5	29.0	19.6	25.2
CONV. 575+, WT. %	-	13	11	22	22	36	57	44
JET FUEL CUT, 275-575 F:								
GRAV., gms/cc	0.8860	0.8665	0.8783	0.8545	0.8618	0.8413	0.8403	0.8458
GRAV., API	28.2	31.8	29.6	34.1	32.7	36.7	36.9	35.8
R.I., @ 20 DEG. C	1.4888	1.4707	1.4782	1.4653	1.4685	1.4585	1.4558	1.4575
H/C RATIO	1.65	1.78	1.78	1.87	1.83	1.90	1.92	1.92
JET FUEL ELEMENTALS, WT. %								
CARBON	87.88	86.81	87.10	86.28	86.65	85.70	86.08	86.13
HYDROGEN	12.12	12.89	12.90	13.46	13.23	13.56	13.74	13.76

* THE FEED FOR FBHC-39 IS THE SAME AS FBHC-37. SEE NOTE ON RUN FBHC-37.

** RUN FBHC-40G IS A REPEAT OF RUN FBHC-39A TO CHECK IF THERE IS THE SAME ACTIVITY.

TABLE 5.5.3.3-5

RUN FBHC-41
COMPARISON OF
RUN FBHC-40F WITH RUN FBHC-41

CATALYST: 165cc ZEOLITE Z-704A

DESIGNATION:	FEED*	40F	41	41	41	41	41
DATE, 1990		9/20	10/1	10/2	10/3	10/4	10/5
OPERATING CONDITIONS:							
CATALYTIC H ₂ RATE, SCF/BBL	-	6000	6000	6000	6000	6000	6000
RUN DURATION, HRS.	-	4	2	2	4	4	6
AVG. RX. TEMP., DEG. F	-	650	651	658	657	655	659
PRESSURE, PSIG	-	1000	1000	1000	1000	1200	1200
AVG. FEED RATE, cc/hr	-	83	89	88	86	89	89
LHSV, cc/hr/cc cat.	-	0.50	0.54	0.53	0.52	0.54	0.54
FEED IN, gms.	-	302	161	160	312	324	487
TLP OUT, gms.	-	296	167	147	307	329	492
RECOVERY, %	-	98	104	92	98	101	101

ANALYTICAL RESULTS:

TLP GRAVITY, gms/cc	0.9082	0.8309	0.8423	0.8388	0.8368	0.8468	0.8438
TLP GRAVITY, DEG. API	24.3	38.8	36.5	37.2	37.6	35.6	36.2
H/C RATIO	1.64	1.94	-	-	-	-	-
TLP ELEMENTALS:							
CARBON	88.00	85.84	-	-	-	-	-
HYDROGEN	12.00	13.89	-	-	-	-	-

DISTILLATION:

IBP, DEG. F	-	130	130	130	120	128	125
ENDPOINT, DEG. F	-	678	720	726	702	680	700

DISTILLATION RECOVERY, %		98.1	98.8	99.1	100.0	98.8	99.3
--------------------------	--	------	------	------	-------	------	------

IBP-275 F, WT. %	5.3	19.6	16.0	16.4	18.3	15.1	16.0
275-575 F, WT. %	49.3	60.8	59.9	60.7	58.2	58.2	57.1
575 F+, WT. %	45.4	19.6	24.1	22.9	23.5	26.7	26.9

CONV. 575+, WT. %	-	57	47	50	48	41	41
-------------------	---	----	----	----	----	----	----

JET FUEL CUT, 275-575 F:

GRAV., gms/cc	0.8860	0.8403	0.8438	0.8388	0.8393	0.8433	0.8433
GRAV., DEG. API	28.2	36.9	36.2	37.2	37.1	36.3	36.3

R.I., @ 20 DEG. C	1.4888	1.4558	1.4574	1.4566	1.4575	1.4592	1.4580
-------------------	--------	--------	--------	--------	--------	--------	--------

H/C RATIO	1.65	1.92	1.92	1.93	-	1.91	NA
JET FUEL ELEMENTALS, WT. %							
CARBON	87.88	86.08	85.87	86.18	-	86.08	NA
HYDROGEN	12.12	13.74	13.74	13.85	-	13.73	NA

* THE FEED FOR FBHC-39 IS THE SAME AS FBHC-37. SEE NOTE ON RUN FBHC-37.

TABLE 5.5.3.4-1
FIXED BED
HYDROTREATING
RUN FB-214

CATALYST: USED CRITERION 424
2 REACTORS IN SERIES @ 165 cc CATALYST PER REACTOR

	FEED*	214A SPOT	214A	214B	214C	214D	214E **	214F
	----	----	----	----	----	----	----	----
OPERATING CONDITIONS:								
CATALYTIC H2, SCF/BBL	-	4500	4500	4500	4500	4500	4500	4500
RUN DURATION, HRS.	-	1	3	3	3	48	16	2
DC-101 AVG. TEMP., F	-	655	655	707	725	718	715	755
DC-201 AVG. TEMP., F	-	651	651	707	724	713	713	752
PRESSURE, PSIG	-	2000	2000	2000	2000	2000	2000	2000
AVG. FEED RATE, cc/hr	-	165	162	162	173	170	167	83
LHSV, cc/hr/cc cat.	-	0.50	0.49	0.49	0.53	0.52	0.51	0.25
FEED IN, gms.	-	150	440	440	472	7425	2274	150
TLP OUT, gms.	-	149	461	466	439	7275	2184	149
RECOVERY, %	-	99	105	106	93	98	96	99

ANALYTICAL RESULTS:

TLP GRAVITY, gms/cc	0.9082	0.8789	0.8778	0.8718	0.8660	0.8724	0.8383	0.8576
TLP GRAVITY, API	24.3	29.5	29.7	30.8	31.9	30.7	37.3	33.5
DISTILLATION:								
IBP-275 F, WT. %	5.3	5.1	5.5	5.8	6.8	6.9	15.0	7.5
275-575 F, WT. %	49.3	53.8	56.2	58.2	60.8	57.5	66.6	70.0
575 F+, WT. %	45.4	41.1	38.3	36.0	32.4	35.6	18.4	22.5
CONV. 575+, WT. %	-	9	16	21	29	22	0	50
JET FUEL CUT, 275-575 F:								
GRAV., gms/cc	0.8860	-	0.8586	0.8618	0.8602	0.8607	0.8428	0.8545
GRAV., API	28.2	-	33.2	32.6	32.9	32.8	36.3	34.0
R.I., @ 20 DEG. C	1.4888	1.4676	1.4674	1.4660	1.4665	1.4686	1.4593	1.4670
H/C RATIO	1.65	-	1.86	1.89	1.87	-	1.92	1.84
ELEMENTALS, WT. %								
CARBON	87.88	-	86.42	86.44	86.13	-	86.14	86.64
HYDROGEN	12.12	-	13.43	13.60	13.40	-	13.78	13.29
F.I.A., VOL. %								
AROMATICS	42.0	-	6.5	5.0	8.5	13.8	5.9	-
OLEFINS	0.5	-	0.5	1.0	0.5	0.5	0.9	-
SATURATES	57.5	-	93.0	94.0	91.0	85.7	93.2	-

* THE FEED FOR THE RUN IS COALITE OIL THAT WAS TOPPED TO 300 DEG F+ IN THE 8" BATCH, AND PROCESSED IN THE LC-FINING UNIT (RUN 6LCF-11 UPGRADED & REMOVED NITROGEN TO 1000 ppm). THE LC-FINATE WAS THEN RUN THROUGH THE EFV UNIT TO OBTAIN THE 300-975 FRACTION. FINALLY THE FEED WAS HYDROTREATED AND NITROGEN REMOVED (40 ppm) IN FIXED BED RUNS FB-194-199, 202-203, & 211-213. THE SAMPLE # IS 3610.

** THE FEED FOR RUN FB-214E IS THE TLP FROM THE FIXED BED HYDROCRACKING RUN 37 (RUN FBHC-37) WHICH HAS 30.5 VOL. % AROMATICS & 18 WT. % 575 F+ MATERIAL.

TABLE 5.5.3.5-1
COALITE DERIVED
HEDF FUEL PROPERTIES

TASK 3.2 SCREENING PROGRAM RESULTS

DESIGNATION BOILING RANGE, DEG. F	FBHC-41 300-600	FB-214D 300-610	FB-214E 300-620	FB-214F 300-600
GRAVITY, SP. @60	0.8560	0.8745	0.8571	0.8702
GRAVITY, DEG. API	33.8	30.3	33.6	31.1
ELEMENTALS:				
CARBON, WT. %	86.36	86.84	86.55	86.78
HYDROGEN, WT. %	13.64	13.16	13.45	13.22
NITROGEN, ppm	<1	<1	<1	<1
SULFUR, ppm	5	4	1	<1
VISCOSITY @ -4F, cst.	9.1	14.1	9.3	11.0
FLASH POINT, DEG. F	>120	>145	>140	>150
FREEZE POINT, DEG. F	<-50	<-50	<-50	<-50
SMOKE POINT, mm	22	18	20	20
ANILINE POINT, DEG. C	61.9	58.0	62.0	54.9
F.I.A.:				
AROMATICS, VOL. %	4.6	3.7	6.6	15.2
OLEFINS, VOL. %	0.5	0.5	0.5	0.5
SATURATES, VOL. %	94.9	95.8	92.9	84.3
COPPER CORROSION, @ 212F	3A	1A	1A	1A
POTENTIAL GUM, mg/100ml	7.0	-	7.4	16.4
THERMAL STABILITY (JFTOT):				
TUBE DEPOSIT RATING	0	0	0	2
TUBE DEPOSIT RATING, MAX.	0.5	1.0	1.5	8.0
DIFF. PRESS. MAX., mm Hg	3.0	3.0	3.0	3.0
ENERGY DENSITY, BTU/GAL	130,860	133,992	131,622	132,901

Energy densities of the finished HEDF test fuels varied from a low of 130,860 Btu/gal for FBHC-41 produced during selective hydrocracking with the proprietary zeolitic catalyst to a high of 133,992 Btu/gal for FB-214D produced for the scheme comprised of hydrodenitrogenation of LC-Finate followed by aromatics saturation with Criterion C-424 catalyst.

Although the highest volumetric energy density is desired, there are two other criteria to consider. The first is a function of economics and the resultant tradeoffs between the additional cost of the incremental energy density improvement vs the value of the higher density fuel to the end user. The other criteria concerns the storage stability and thermal stability of the fuel for use in high speed aircraft. One analytical device for assessing stability performance is the Standard Test Method for Thermal Oxidation Stability of Aviation Turbine Fuels (JFTOT Procedure, ASTM D3241-85). JFTOT subjects the test fuel to conditions that are relatable to those occurring in gas turbine engine fuel systems. The fuel is pumped at a fixed volumetric flow rate through a heater after which it enters a precision stainless steel filter where fuel degradation products become trapped. The essential data derived are the amount of deposits on an aluminum heater tube and the rate of plugging of a 17 micron nominal porosity filter located just downstream of the heater tube. This test has long been used by petroleum refiners to meet process specifications for shipment of aviation fuel products to the end users, namely, the commercial airline industry and the U.S. Air Force. With the advent of new aircraft engines and new fuel compositions, the JFTOT test is not always an accurate gauge for assessing on-board fuel stability performance. The Air Force is continually improving technology for on-ground determination of thermal stability of aviation turbine fuels. With regard to the new fuel type, High Energy Density (Category I) fuel, it is not known how applicable the JFTOT test will be for assessing thermal stability.

6.0 SUMMARY OF RESULTS OF COLORADO SHALE OIL OPERATIONS

6.1 Overview

The Work Statement for this contract, which was co-funded by METC's Coal Gasification group and by the Extraction Projects division which is responsible for non-coal resources such as oil shale, tar sands and gases, called for assessment of HEDF test fuel production from several fossil fuel sources. In addition to the MCG liquids generated in the COALITE process, a sample of Colorado shale oil derived from the UNOCAL plant at Parachute Creek. This feedstock is of importance because of its commercial availability and its demonstrated conversion to conventional jet fuel and subsequent on-board testing under past DOE contracts.

6.2 Virgin Distillate Hydrotreating

The results of the several campaigns are summarized in a series of spreadsheet tables with the "A" tables presenting the run performance data and the "B" tables presenting the properties of the full-range hydrotreated distillates. The organization of the tabulated results is as follows:

<u>Table No</u>	<u>Catalyst Type</u>	<u>Feed Boiling Range (F)</u>	<u># Reaction Stages</u>
6.2-1A,B	K-599/MO-1230	350-600	2
6.2-2A,B	K-550/K-599	350-600	2
6.2-3A,B	K-550/K-599	575-1000HDT	2
6.2-4A,B	K-599	300-575HDT	1
6.2-5A,B	Amoco Propr.	575-1000HDT	1
6.2-6A,B	Amoco Propr.	650-975Virgin	1

Several interesting correlations were developed for the hydrotreating of the raw 350-550F and 350-650F COALITE distillates. Correlations were developed of the HEDF properties vs the kinetic hydrotreating severity parameter (KSF described in Section 4). These are shown graphically in Figures 6.2-1 through -6. The data for the COALITE correlations are shown on the figures for reference purposes. Cross-correlations of key HEDF properties vs aromatics contents are depicted in Figures 6.2-7 and -8. Cross-correlations of key HEDF properties vs Refractive Index are shown in Figures 6.2-9 through -11.

Unlike the MCG liquids, the Colorado shale oil distillates are less concentrated in the cyclics and more concentrated in the aliphatic materials as seen in the table below:

	<u>Colo. Shale Oil</u>	<u>COALITE</u>
% Olefins	39.9	11.8
% Saturates (cyclic+aliphatic)	32.9	<13.7
%Aromatics	27.2	>74.5

TABLE 6.2-1A 1 of 2

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COLORADO SHALE OIL

HYDROTREATING TESTS

CATALYST: K-599 (1ST STAGE) / MO-1230 (2ND STAGE)

FILE ID: REPTSE2.WK1

TEST # (FB-)	148	149	150	151	152	153	154	155
DATE (1989)	05-24	05-25	05-25	05-25	05-26	05-26	05-26	05-26
START TIME	16:00	00:00	08:00	16:00	00:00	08:00	16:30	20:00
END TIME	20:00	04:00	12:00	20:00	04:00	12:00	17:30	21:00
FEEDSTOCK	A	A	A	A	A	A	A	A
% HDS								
% HDN								
% HDU								
H2 UPTAKE, scf/bbl	9000	9000	9000	9000	9000	9000	9000	9000
% F.I.A. OLEFINS SATURATION								
% F.I.A. AROMATICS SATURATION								
API IMPROVEMENT	7.3	8.3	10.1	11.5	7.0	5.3	5.6	5.8
R.I. DEPRESSION	0.0167	0.0161	0.0176	0.0194	0.0115	0.0109	0.0097	0.0131
EST. HEAT OF REACTION, Btu/lb								

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-1A 2 of 2

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COLORADO SHALE OIL

HYDROTREATING TESTS

CATALYST: K-599 (1ST STAGE) / MO-1230 (2ND STAGE)

FILE ID: REPTSE2.WK1

TEST # (FB-)	159	160	161	162	163	164
DATE (1989)	06-05/06	06-06/07	06-08	06-08	06-08	06-09
START TIME	16:00	18:00	00:00	08:00	16:00	00:00
END TIME	16:00	18:00	06:00	14:15	22:00	06:00
FEEDSTOCK	A	A	B	B	C	C
% HDS						
% HDN						
% HDO						
H2 UPTAKE, scf/bbl	9000	9000	7000	7000	7000	7000
% F.I.A. OLEFINS SATURATION						
% F.I.A. AROMATICS SATURATION						
API IMPROVEMENT	7.3	6.5	9.5	12.6	12.5	9.0
R.I. DEPRESSION	0.0145	0.0143	0.0249	0.0355	0.0349	0.0241
EST. HEAT OF REACTION, Btu/lb						

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

B: LIQUID PRODUCT FROM FB-159.

C: LIQUID PRODUCT FROM FB-160.

TABLE 6.2-1B 1 of 2

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COLORADO SHALE OIL PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-550 (1ST STAGE) / MO-1230 (2ND STAGE)

TEST # (FB-)	FILE 10: REPTSP2.WK1							
	148	149	150	151	152	153	154	155
DATE (1989)	05-24	05-25	05-25	05-25	05-26	05-26	05-26	05-26
START TIME	16:00	00:00	08:00	16:00	00:00	08:00	16:30	20:00
END TIME	20:00	04:00	12:00	20:00	04:00	12:00	17:30	21:00
FEEDSTOCK	A	A	A	A	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.8304	0.8256	0.8170	0.8104	0.8319	0.8403	0.8388	0.8378
API GRAVITY @ 60 F	38.9	39.9	41.7	43.1	38.6	36.9	37.2	37.4
REFRACTIVE INDEX @ 20 C	1.4618	1.4624	1.4609	1.4591	1.4670	1.4676	1.4688	1.4654
ELEMENTALS, wt%								
C	86.04	86.10	86.41	86.43	85.95	85.68	85.71	86.17
H	13.75	13.66	13.52	13.26	13.29	13.38	13.28	13.63
SIMULATED DISTILLATION, F								
IRP								
10% DISTILLED								
30%								
50%								
70%								
90%								
VOLUM. AVG. BOIL. PT. F								
WATSON Y								
F.I.A. ANALYSIS, 1vol%								
OLEFINS	0.6	0.5	0.7	0.8	1.7	3.9	10.1	3.7
SATURATES	75.6	73.2	71.1	68.3	71.3	68.2	62.4	75.3
AROMATICS	23.8	26.3	28.2	30.9	27	27.9	27.5	20.9
MLHV, Btu/lb	15435		18129	18201	18090			
VLHV, Btu/gal	106767		123379	122868	125359			
FLASH PT., F								
SMOKE PT., °								
FREZE PT., F								
ANILINE PT., F								
CETANE INDEX								
VISCOSITY, cst @ -4 F								

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-1B 2 of 2

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COLORADO SHALE OIL PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: CATALYST: K-550 (1ST STAGE) / MO-1230 (2ND STAGE)

FILE ID: REPTSP2.WK1

TEST # (FB-)	159	160	161	162	163	164
DATE (1989)	06-05/06	06-06/07	06-08	06-08	06-08	06-09
START TIME	16:00	18:00	00:00	08:00	16:00	00:00
END TIME	16:00	18:00	06:00	14:15	22:00	06:00

FEEDSTOCK	A	A	B	B	C	C
SPECIFIC GRAVITY, gm/cc	0.8304	0.8343	0.8198	0.8054	0.8058	0.8222
API GRAVITY @ 60 F	38.9	38.1	41.1	44.2	44.1	40.6
REFRACTIVE INDEX @ 20 C	1.4640	1.4642	1.4536	1.4430	1.4436	1.4544

ELEMENTALS, wt%

C	86.36	86.05	86.32	85.72	86.00	85.87
H	13.64	13.70	14.32	14.57	14.80	14.87

SIMULATED DISTILLATION, F

IBP
10% DISTILLED
30%
50%
70%
90%

WCU, AVG. BOIL. PT., F
WATSON #

F.I.A. ANALYSIS, 1vol%

OLEFINS	1.9	3.0	0.0	1.2	2.3	2.3
SATURATES	74.9	75.1	91.7	90.0	74.4	82.8
AROMATICS	23.2	21.9	6.3	7.9	23.3	14.9

WLMV, Btu/lb
VLMV, Btu/gal

FLASH PT., F
SMOKE PT., #
FREEZE PT., F
ANILINE PT., F
CETANE INDEX
VISCOSITY, cst @ -4 F

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.
B: LIQUID PRODUCT FROM FB-159.
C: LIQUID PRODUCT FROM FB-160.

TABLE 6.2-2A 1 of 3

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COLORADO SHALE OIL

HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE) / K-599 (2nd STAGE)

FILE ID: REPTSE1.WK1

TEST # (FB-)	106	107	108	109	110	111	112	113
DATE (1989)	04-11	04-11/12	04-12	04-12	04-12	04-13	04-13	04-13
START TIME	17:30	23:30	05:30	11:30	18:30	00:30	06:30	13:00
END TIME	19:30	01:30	07:30	13:30	20:30	02:30	08:30	15:00
FEEDSTOCK	A	A	A	A	A	A	A	A
% HDS								
% HDN								
% HDO								
H ₂ UPTAKE, scf/bbl	7000	7030	7000	7000	7000	7000	7000	7000
% F.I.A. OLEFINS SATURATION								
% F.I.A. AROMATICS SATURATION								
API IMPROVEMENT	6.0	8.8	10.6	11.7	9.2	11.8	11.2	11.5
R.I. DEPRESSION	0.0169	0.0242	0.0303	0.0333	0.0256	0.0340	0.0321	0.0322
EST. HEAT OF REACTION, Btu/lb								

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-2A 2 of 3

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COLORADO SHALE OIL

HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE) / K-599 (2nd STAGE)

FILE ID: REPTSE1.WK1

TEST # (FB-)	114	115	116	117	118	119	120	121
DATE (1989)	04-13	04-14	04-14	04-14	04-17	04-17	04-18	04-18
START TIME	22:00	04:00	10:00	16:00	06:30	12:30	19:30	01:30
END TIME	24:00	06:00	12:00	18:00	08:30	14:30	21:30	03:30
FEEDSTOCK	A	A	A	A	A	A	A	A
% HDS								
% HDN								
% HDO								
H ₂ UPTAKE, scf/bbl	7000	7000	7000	7000	7000	7000	7000	7000
% F.I.A. OLEFINS SATURATION								
% F.I.A. AROMATICS SATURATION								
API IMPROVEMENT	5.6	7.8	9.6	10.4	8.4	10.5	13.0	14.3
R.I. DEPRESSION	0.0163	0.0223	0.0269	0.0292	0.0228	0.0298	0.0359	0.0395
EST. HEAT OF REACTION, Btu/lb								

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-2A 3 of 3

SUMMARY OF OPERATING RESULTS FOR FIXED-BED COLORADO SHALE OIL

HYDROTREATING TESTS

CATALYST: K-550 (1ST STAGE) / K-599 (2nd STAGE)

FILE ID: REPTSE1.WK1

TEST # (FB-)	122	123	124	125	128	129	130
DATE (1989)	04-18	04-18	04-18	04-19	04-19/20	04-20/21	04-21
START TIME	07:30	13:30	19:30	01:30	18:30	12:30	07:30
END TIME	09:30	15:30	21:30	03:30	09:30	03:30	21:00
FEEDSTOCK	A	A	A	A	A	A	A
% HDS							
% HDN							
% HDO							
H ₂ UPTAKE, scf/bbl	7000	7000	7000	7000	7000	7000	7000
% F.I.A. OLEFINS SATURATION							
% F.I.A. AROMATICS SATURATION							
API IMPROVEMENT	13.2	9.3	10.3	8.3	10.3	13.6	9.7
R.I. DEPRESSION	0.0370	0.0345	0.0285	0.0225	0.0286	0.0381	0.0269
EST. HEAT OF REACTION, Btu/lb							

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-2B 1 of 3

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COLORADO SHALE OIL PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-550 (1ST STAGE) / K-599 (2ND STAGE)

FILE ID: REPTSP1.WK1

TEST # (FB-)	106	107	108	109	110	111	112	113
DATE (1989)	04-11	04-11/12	04-12	04-12	04-12	04-13	04-13	04-13
START TIME	17:30	23:30	05:30	11:30	18:30	00:00	06:30	13:00
END TIME	19:30	01:30	07:30	13:30	20:30	02:30	08:30	15:00
FEEDSTOCK	A	A	A	A	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.8368	0.8232	0.8146	0.8095	0.8212	0.8090	0.8118	0.8104
API GRAVITY @ 60 F	37.6	40.4	42.2	43.3	40.8	43.4	42.8	43.1
REFRACTIVE INDEX @ 20 C	1.4616	1.4543	1.4482	1.4452	1.4529	1.4445	1.4464	1.4463
ELEMENTALS, wt%								
C	85.70	85.80	85.60	85.43	85.80	85.42	84.86	85.08
H	13.82	14.21	14.47	14.62	14.26	14.62	14.50	14.50
SIMULATED DISTILLATION, F								
IBP								
10% DISTILLED								
30%								
50%								
70%								
90%								
VOLUM. AVG. BOIL. PT., F								
WATSON K								
F.I.A. ANALYSIS, 1vol%								
OLEFINS	1.8	1.0	1.1	0.8	0.9	0.6	0.8	0.5
SATURATES	76.8	84.7	90.8	93.0	83.7	94.6	89.9	91.6
AROMATICS	21.4	14.3	8.1	6.2	15.4	4.8	9.3	7.9
WLMV, Btu/lb	18358	18471	18169	18639				
VLMV, Btu/gal	127965	126660	123288	125685				
FLASH PT., F								
SMOKE PT., °F	25	25	35	35	30	35	35	30
FREZE PT., F								
ANILINE PT., F								
CETANE INDEX								
VISCOSITY, cst @ -4 F								

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-2B 2 of 3

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COLORADO SHALE OIL PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-550 (1ST STAGE) / K-599 (2ND STAGE)

	FILE ID: REPTSP1.WK1							
	114	115	116	117	118	119	120	121
DATE (1989)	04-13	04-14	04-14	04-14	04-17	04-17	04-18	04-18
START TIME	22:00	04:00	10:00	16:00	06:30	12:30	19:30	01:30
END TIME	24:00	06:00	12:00	18:00	08:30	14:30	21:30	03:30
FEEDSTOCK	A	A	A	A	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.8388	0.8280	0.8193	0.8156	0.8251	0.8151	0.8035	0.7976
API GRAVITY @ 60 F	37.2	39.4	41.2	42.0	40.0	42.1	44.6	45.9
REFRACTIVE INDEX @ 20 C	1.4622	1.4562	1.4516	1.4493	1.4557	1.4487	1.4426	1.439
ELEMENTALS, wt%								
C	84.81	85.29	85.41	85.04	85.61	85.37	85.03	8.95
H	13.61	13.96	14.15	14.42	13.96	14.31	14.62	14.87
SIMULATED DISTILLATION, F								
IBP	242							
10% DISTILLED	391							
30%	448							
50%	505							
70%	563							
90%	626							
VOLUM. AVG. BOIL. PT. F	507							
WATSON K	11.71							
F.I.A. ANALYSIS, 1vol%								
OLEFINS	1.2	0.6	0.8	0.6	0.6	0.5	0.3	0.3
SATURATES	79.8	82.0	84.7	89.1	82.4	89.6	93.8	96.7
AROMATICS	19.0	17.4	14.5	10.3	17.0	9.9	5.9	3.0
WLHV, Btu/lb	18320	18431	18497	18587				
VLHV, Btu/gal	128006	127123	126238	126279				
FLASH PT., F	110							
SMOKE PT., °F	30	30	40	40	35			
FREZE PT., F	-0.4							
ANILINE PT., F								
CETANE INDEX								
VISCOSITY, cst @ -4 F								

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-2B 3 of 3

SUMMARY OF PROPERTIES OF FULL-RANGE HYDROTREATED COLORADO SHALE OIL PRODUCTS

FROM FIXED-BED HYDROTREATING

CATALYST: K-550 (1ST STAGE) / K-599 (2ND STAGE)

FILE ID: REPTSP1.WK1

TEST # (FB-)	122	123	124	125	128	129	130
DATE (1989)	04-18	04-18	04-18	04-19	04-19/20	04-20/21	04-21
START TIME	07:30	13:30	19:30	01:30	18:30	12:30	07:30
END TIME	09:30	15:30	21:30	03:30	09:30	03:30	21:00
FEEDSTOCK	A	A	A	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.8026	0.8207	0.8160	0.8256	0.8160	0.8008	0.8189
API GRAVITY @ 60 F	44.8	40.9	41.9	39.9	41.9	45.2	41.3
REFRACTIVE INDEX @ 20 C	1.4415	1.4440	1.4500	1.4560	1.4497	1.4404	1.4516
ELEMENTALS, wt%							
C	85.07				85.89	85.55	85.25
H	14.77				14.35	14.78	14.31
SIMULATED DISTILLATION, F							
IBP							197
10% DISTILLED							371
30%							431
50%							484
70%							541
90%							606
VOLUM. AVG. BOIL. PT., F							487
WATSON K							11.91
F.I.A. ANALYSIS, 1vol%							
OLEFINS	0.3	0.5	0.7	0.9	0.7	0.5	0.7
SATURATES	96.1	95.1	88.4	78.6	86.0	95.7	83.5
AROMATICS	3.6	4.4	10.9	20.5	13.3	3.8	15.8
WLV, Btu/lb					18518	18430	18200
VLHV, Btu/gal					125872	122940	124150
FLASH PT., F							90
SMOKE PT., °							
FREZE PT., F							6.8
ANILINE PT., F							
CETANE INDEX							
VISCOSITY, cst @ -4 F							

FEEDSTOCK TYPE:

A: 355-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-3A

SUMMARY OF OPERATING RESULTS OF FIXED-BED HYDROTREATED PRODUCTS FROM

HYDROPROCESSED COLORADO SHALE OIL DISTILLATE

CATALYST: K-550 (1ST STAGE), K-599 (2ND STAGE)

FILE ID: REPTSLC2.WK1

TEST # (FB-)	186	187
DATE (1989)	08-22/23	08-23/25
START TIME	18:00	18:00
END TIME	18:00	17:00
FEEDSTOCK	A	A
% HDS		
% HDN		
% HDO		
H2 UPTAKE, scf/bbl	7000	7000
% F.I.A. OLEFINS SATURATION		
% F.I.A. AROMATICS SATURATION		
API IMPROVEMENT	7.0	7.7
R.I. DEPRESSION		
EST. HEAT OF REACTION, Btu/lb		

FEEDSTOCK TYPE:

A: 575-1000 F HYDROPROCESSED COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-3B

SUMMARY OF PROPERTIES OF FIXED-BED HYDROTREATED PRODUCTS FROM

HYDROPROCESSED COLORADO SHALE OIL DISTILLATE

CATALYST: K-550 (1ST STAGE), K-599 (2ND STAGE)

FILE ID: REPTSLC3.WK1

TEST # (FB-)	186	187
DATE (1989)	08-22/23	08-23/25
START TIME	18:00	18:00
END TIME	18:00	17:00
FEEDSTOCK	A	A
SPECIFIC GRAVITY, gm/cc	0.8644	0.8612
API GRAVITY @ 60 F	32.2	32.8
REFRACTIVE INDEX @ 20 C		
ELEMENTALS, wt%		
C	86.47	86.41
H	14.04	13.65
SIMULATED DISTILLATION, F		
IBP		
10% DISTILLED		
30%		
50%		
70%		
90%		
VOLUM. AVG. BOIL. PT., F		
WATSON K		
F.I.A. ANALYSIS, 1vol%		
OLIFINS		
SATURATES		
AROMATICS		
WLHV, Btu/lb		
VLHV, Btu/gal		
FLASH PT., F		
SMOKE PT., °F		
FREEZE PT., F		
ANILINE PT., F		
CETANE INDEX		
VISCOSITY, cst @ -4 F		

FEEDSTOCK TYPE:

A: 575-1000 F HYDROPROCESSED COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-4A

SUMMARY OF OPERATING RESULTS OF FIXED-BED HYDROTREATED PRODUCTS FROM

HYDROPROCESSED COLORADO SHALE OIL DISTILLATE

CATALYST: K-599 (2ND STAGE)

FILE ID: REPTSLC2.WK1

TEST # (FB-)	143	144	145
DATE (1989)	05-15/16	05-16	05-16
START TIME	22:30	04:30	10:30
END TIME	00:30	06:30	12:30
FEEDSTOCK	A	A	A
% HDS			
% HDN			
% HDO			
H2 UPTAKE, scf/bbl	7000	7000	7000
% F.I.A. OLEFINS SATURATION			
% F.I.A. AROMATICS SATURATION			
API IMPROVEMENT	8.0	9.0	8.7
R.I. DEPRESSION	0.0250	0.0267	0.0235
EST. HEAT OF REACTION, Btu/lb			

FEEDSTOCK TYPE:

A: 300-575 F HYDROPROCESSED COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-4B

SUMMARY OF PROPERTIES OF FIXED-BED HYDROTREATED PRODUCTS FROM

HYDROPROCESSED COLORADO SHALE OIL DISTILLATE

CATALYST: K-599 (2ND STAGE)

FILE ID: REPTSLC3.WK1

TEST # (FB-)	143	144	145
DATE (1989)	05-15/16	05-16	05-16
START TIME	22:30	04:30	10:30
END TIME	00:30	06:30	12:30

FEEDSTOCK	A	A	A
-----------	---	---	---

SPECIFIC GRAVITY, gm/cc	0.8114	0.8067	0.8081
API GRAVITY @ 60 F	42.9	43.9	43.6
REFRACTIVE INDEX @ 20 C	1.4465	1.4448	1.4480

ELEMENTALS, wt%

C	85.61	85.59	86.06
H	14.44	14.49	14.13

SIMULATED DISTILLATION, F

IBP			
10% DISTILLED			
30%			
50%			
70%			
90%			

VOLUM. AVG. BOIL. PT., F			
WATSON K			

F.I.A. ANALYSIS, 1vol%

OLIFINS	0.5	0.4	0.3
SATURATES	91.9	91.6	81.3
AROMATICS	7.6	8.0	18.4

WLHV, Btu/lb	18401	18552	18400
VLHV, Btu/gal	124372	124666	123859

FLASH PT., F			
SMOKE PT., mm			
FREEZE PT., F			
ANILINE PT., F			
CETANE INDEX			
VISCOSITY, cst @ -4 F			

FEEDSTOCK TYPE:

A: 575-1000 F HYDROPROCESSED COLORADO SHALE OIL DISTILLATE.

TABLE 6.2-5A

SUMMARY OF OPERATING RESULTS FOR FIXED-BED

COLORADO SHALE OIL HYDROCRACKING TESTS

CATALYST: AMOCO PROPRIETARY

FILE ID: REPTSHCS.WK1

TEST # (FBHC-)	28	29	30	31	32	33	34	35
DATE (1989)	08-16	08-17	08-17/18	08-18/21	08-28/29	08-29/30	08-30/31	08-31/09-01
START TIME	06:00	00:00	12:00	13:00	21:00	20:00	20:00	12:00
END TIME	08:00	08:00	08:00	20:00	18:00	18:00	12:00	21:00
FEEDSTOCK	A	A	A	A	B	B	B	B
% HDS								
% HDN	73		84	90				
% HDC								
H ₂ UPTAKE, scf/bbl	7000	7000	7000	7000	7000	6000	6000	6000
% F.I.A. OLIFINS SATURATION								
% F.I.A. AROMATICS SATURATION								
API IMPROVEMENT	6.2	5.6	6.6	9.8	3.9	3.1	1.9	4.4
R.I. DEPRESSION								
EST. HEAT OF REACTION, Btu/lb								

FEEDSTOCK TYPE:

A: 575-1000 F HYDROPROCESSED COLORADO SHALE OIL DISTILLATE .
 B: 575-1000 F, HYDROPROCESSED COLORADO SHALE OIL DISTILLATE
 FOLLOWED BY FIXED-BED HYDROTREATING.

TABLE 6.2-5B

SUMMARY OF PROPERTIES OF HYDROCRACKATES FROM FIXED-BED

COLORADO SHALE OIL HYDROCRACKING

CATALYST: AMOCO PROPRIETARY

TEST # (FBHC-)	FILE ID: REPTSHC6.WK1							
	28	29	30	31	32	33	34	35
DATE (1989)	08-16	08-17	08-17/18	08-18/21	08-28/29	08-29/30	08-30/31	08-31/09-01
START TIME	06:00	00:00	12:00	13:00	21:00	20:00	20:00	12:00
END TIME	08:00	08:00	08:00	20:00	18:00	18:00	12:00	21:00
FEEDSTOCK	A	A	A	A	B	B	B	B
SPECIFIC GRAVITY, gm/cc	0.8686	0.8718	0.8665	0.8499	0.8424	0.8461	0.8523	0.8398
API GRAVITY @ 60 F	31.4	30.8	31.8	35.0	36.5	35.7	34.5	37.0
REFRACTIVE INDEX @ 20 C								
ELEMENTALS, wt %								
C	86.23		86.36	86.07	85.38	85.41	85.43	85.37
H	13.42		13.87	14.21	14.38	14.56	14.30	14.42
DISTILLATION (ASTM D-1160), F								
IBP	319		318	311	275	311	315	304
10% DISTILLED	572		532	456	449	478	520	447
30%	646		630	573	622	615	624	602
50%	710		690	659	694	684	686	672
70%	783		762	737	778	766	763	763
90%	885		858	838	893		858	
VOLUM. AVG. BOIL. PT, F	719		694	653	687	636	690	621
WATSON K	12.09		12.04	12.12	12.35	12.11	12.22	12.14
WLHV, Btu/lb								
VLHV, Btu/gal								

FEEDSTOCK TYPE:

A: 575-1000 F, HYDROPROCESSED COLORADO SHALE OIL DISTILLATE.
 B: 575-1000 F, HYDROPROCESSED COLORADO SHALE OIL DISTILLATE
 FOLLOWED BY FIXED-BED HYDROTREATING.

TABLE 6.2-6A
 SUMMARY OF OPERATING RESULTS FOR FIXED-BED
 COLORADO SHALE OIL HYDROCRACKING TESTS
 CATALYST: AMOCO PROPRIETARY

FILE ID: REPTSHC2.WK1

TEST # (FBHC-)	5	6	7	8	9	10	11	12
DATE (1989)	05-01	05-01	05-01	05-01	05-02	05-02	05-02	05-03
START TIME	07:30	13:30	19:30	01:30	07:30	13:30	19:30	04:30
END TIME	09:30	15:30	21:30	03:30	09:30	15:30	24:30	09:30
FEEDSTOCK	A	A	A	A	A	A	A	A
% HDS								
% HDN								
% HDO								
H2 UPTAKE, scf/bbl	7000	7000	7000	7000	7000	7000	7000	7000
% F.I.A. OLIFINS SATURATION								
% F.I.A. AROMATICS SATURATION								
API IMPROVEMENT	5.6	9.4	7.1	4.6	8.5	11.2	11.4	14.5
R.I. DEPRESSION								
EST. HEAT OF REACTION, Btu/lb								

FEEDSTOCK TYPE:

A: 650-975 F COLORADO SHALE OIL VGO.

A: 555-618 F VIRGIN COLORADO SHALE OIL DISTILLATE.
B: LIQUID PRODUCT FROM FB-159.
C: LIQUID PRODUCT FROM FB-160.

TABLE 6.2-6B

SUMMARY OF PROPERTIES OF HYDROCRACKATES FROM FIXED-BED

COLORADO SHALE OIL HYDROCRACKING

CATALYST: AMOCO PROPRIETARY

TEST # (FBHC-)	FILE ID: REPTSHC3.WK1							
	5	6	7	8	9	10	11	12
DATE (1989)	05-01	05-01	05-01	05-01	05-02	05-02	05-02	05-03
START TIME	07:30	13:30	19:30	01:30	07:30	13:30	19:30	05:30
END TIME	09:30	15:30	21:30	03:30	09:30	15:30	24:30	09:30
FEEDSTOCK	A	A	A	A	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.9141	0.8922	0.9053	0.9200	0.8973	0.8822	0.8811	0.8644
API GRAVITY @ 60 F	23.3	27.1	24.8	22.3	26.2	28.9	29.1	32.2
REFRACTIVE INDEX @ 20 C								
ELEMENTALS, wt %								

C								86.4
H								13.75
SIMULATED DISTILLATION, F								

IBP	273	249	263	321	249	269	242	
10% DISTILLED	581	516	578	654	522	466	483	
30%	729	701	736	757	709	657	673	
50%	788	773	796	811	778	753	759	
70%	843	832	851	862	838	817	825	
90%	918	911	932	943	921	903	910	
VOLUM. AVG. BOIL. PT., F	772	747	779	805	754	719	730	
WATSON K	11.66	11.87	11.80	11.69	11.82	11.91	11.96	
WLHV, Btu/lb								
VLHV, Btu/gal								

FEEDSTOCK TYPE:

A: 650-975 F COLORADO SHALE OIL VGO.

FIGURE 6.2-1

HYDROTREATING SEVERITY VS. VLHV FOR COAL & SHALE-DERIVED JET FUELS

HYDROTREATING SEVERITY, $10000 \cdot P / LHSV \cdot e(-35000/RT)$

FIGURE 6.2-2

HYDROTREATING SEVERITY VS. FIA AROMATICS ANALYSIS FOR COAL & SHALE-DERIVED JET FUELS

HYDROTREATING SEVERITY, $10000 \cdot P / LHSV \cdot e(-35000/RT)$

FIGURE 6.2-3

HYDROTREATING SEVERITY VS. HYDROGEN CONTENT FOR COAL & SHALE-DERIVED JET FUELS

FIGURE 6.2-4

HYDROTREATING SEVERITY VS. API GRAVITY FOR COAL AND SHALE-DERIVED JET FUELS

HYDROTREATING SEVERITY, $10000 \cdot P / \text{LHSV} \cdot e(-35000/RT)$

FIGURE 6.2-5

HYDROTREATING SEVERITY VS. SMOKE POINT FOR COAL & SHALE-DERIVED JET FUELS

HYDROTREATING SEVERITY, $10000 \cdot P / \text{LHSV} \cdot e^{(-35000/RT)}$

HYDROTREATING SEVERITY VS. REFRACTIVE INDEX FOR COAL & SHALE-DERIVED JET FUELS

FIGURE 6.2-6

HYDROTREATING SEVERITY, $10000 \cdot P / LHSV \cdot e(-35000/RT)$

FIGURE 6.2-7

EFFECT OF AROMATICS ON VOLUMETRIC LHV OF COAL & SHALE-DERIVED JET FUELS

F.I.A. AROMATICS CONTENT, |vol|%

FIGURE 6.2-8

EFFECT OF AROMATICS ON SMOKE POINT OF COAL & SHALE-DERIVED TURBINE FUELS

F.I.A. AROMATICS CONTENT, |vol|%

FIGURE 6.2-9

API GRAVITY VS REFRACTIVE INDEX FOR COAL & SHALE-DERIVED DISTILLATES

FIGURE 6.2-10

SMOKE POINT VS REFRACTIVE INDEX OF COAL & SHALE-DERIVED JET FUELS

REFRACTIVE INDEX @ 20C

FIGURE 6.2-11

DISTILLATE HYDROGEN CONTENT VS REFRACTIVE INDEX FOR COAL & SHALE-DERIVED JET FUELS

The COALITE olefins are primarily cyclic in structure, e.g., cyclooctene, cyclodecene, whereas the shale-derived olefins are primarily aliphatic, e.g., n-octene/iso-octene, n-decene/iso-decene. The saturates types, naphthenes vs. paraffins, for these raw synfuels were not readily differentiated by the sulfonation/R.I. technique.

For the case of the Colorado shale oil, the raw 300-600F distillate had a volumetric heat content of only about 127 KBtu/gal, some 3000 Btu/gal below the target. Upon hydrotreatment as seen in Figure 6.2-7, the volumetric energy content decreases significantly away from the target. Thus, the K-550 NiWS and K-599 NiMo catalysts do not appear to have the right functionality to preserve and/or form the desirable cyclic structures. It may be possible to obviate this situation by extending the end point of the distillates beyond 600F and the initial point beyond 300F in order to increase the concentration of the denser 2- and 3-ring cyclics.

One possible alternative to nickel-based aromatics saturation is the use of selective hydroisomerization (or aromatization or reforming) catalysts to reform aliphatics into the desirable aromatic precursor structures. The product of this operation would then be subjected to the nickel-based aromatics saturation catalysts thereby generating the naphthenic-rich HEDF fuels. Current state-of-the-art reforming catalysts are based on noble metals such as platinum, rhenium, palladium, etc. However, these catalysts are extremely sensitive to poisons, e.g., sulfur and nitrogen, and therefore cannot be used without a high severity pretreatment.

Prior to the advent of the noble metal catalysts, there was another family of reforming catalysts that was resistant to heteroatom contamination. These included chromia-alumina and molybdena-alumina catalysts. These catalysts are not as active as the noble metal catalysts and require higher operating severities to achieve comparable performance. A sample of a Harshaw Mo-1230 molybdena catalyst was obtained and used to evaluate the feasibility of this approach. A series of tests was made in the fixed-bed unit to screen the molybdena-based hydroisomerization of the 300-600F Colorado shale oil distillates. The hydroisomerizates were recovered and separately hydroprocessed over the K-599 nickel-moly catalyst to saturate aromatics, those originally present in the raw shale oil distillate as well as any produced during the molybdena reforming step. The data from the tests made did not however achieve the desired improvement. In fact, the highest volumetric energy density (125,359 Btu/gal) achieved was still lower than that achievable with the two-stage NiMo hydrotreating catalysts. Further improvements might be achieved by extending the distillate initial and end points to increase the content of the aromatics as well as the straight or branched chain aliphatics that might be more amenable to hydroisomerization.

6.3 Virgin Atmospheric Resid Cracking

Two campaigns of resid hydrocracking via LC-Fining technology were made and the results are summarized in Tables 6.3-1A,B for the virgin resid feedstock and Tables 6.3-2A,B for the hydroprocessed resid feedstock. One campaign of resid thermal cracking via delayed coking was completed and the results are summarized in Table 6.3-3A (operating results) and 6.3-3B (properties of coker distillate products).

6.4 Cracked Distillate Hydrotreating

Only one test campaign was completed for the hydrotreating of cracked distillates. Tables 6.4-1A,B summarize the results for the tests made with a hydroprocessed distillate derived from fixed-bed hydrocracking of LC-Finate VGO.

6.5 Two-Stage Selective Hydrocracking of Vacuum Gas Oil (VGO)

We previously found that volumetric energy densities of 300-600F raw Colorado shale oils after fixed-bed hydrotreating were limited to about 125,000 Btu/gal. While this value is some 5000 Btu/gal below the spec, it still represents a 5000-10,000 Btu/gal energy density premium above that of conventional jet fuels. Nevertheless, a campaign was initiated with the heavy (550F+) Colorado shale oil fraction following parallel processing routes that successfully generated a 132,000+ Btu/gal energy density HEDF from the 550F+ COALITE feedstock.

The selective hydrocracking route, as successfully implemented with the COALITE feedstock, basically consists of mild expanded-bed hydrofining (LC-Fining) of the 300F+ dewatered feed; fractionation to recover the 550-975F LC-Finate vacuum gas oil (VGO); selective hydrocracking of the VGO over the Amoco proprietary fixed-bed hydrocracking catalyst; and fixed-bed hydrogenation of the VGO hydrocrackate.

In the current campaign with the Colorado shale oil feedstock, the selective hydrocracking route followed the steps delineated below:

- o The whole (IBP to end point), undewatered Colorado shale oil was subjected to the mild LC-Fining (test BLCF-102) step. The water collected in the LC-Finate product receivers was phase separated by decanting. The LC-Finate full-range product was fractionated to generate a 575-975F VGO fraction for downstream hydrocracking/hydrogenation.
- o Since the nitrogen content of the LC-Finate VGO was still very high, ca., 15000 ppm, a subsequent fixed-bed hydrotreating (test FB-186/187) step using a NiW/NiMo two-stage catalyst system was used to reduce nitrogen content to 200 ppm.

TABLE 6.3-1A

SUMMARY OF OPERATING RESULTS FOR LC-FINING (HYDROCRACKING) TESTS

COLORADO SHALE OIL DISTILLATE

CATALYST: SHELL 324 (AGED)

FILE ID: REPTSBL2.WK1

TEST # (BLCF-)	89-1	89-2	89-3	89-4	89-5
DATE (1989)	03-06	03-07	03-07/08	03-08	03-09
START TIME	11:30	21:30	14:00	04:00	13:00
END TIME	20:30	12:00	02:00	13:00	01:30
FEEDSTOCK	A	A	A	A	A
% HDS					
% HDN					
% HDO					
H2 UPTAKE, scf/bbl	10000	10000	10000	10000	10000
API IMPROVEMENT					
R.I. REGRESSION					
EST. HEAT OF REACTION, Btu/lb					

FEEDSTOCK TYPE:

A: COLORADO SHALE OIL ATM RESID 650+ F.

TABLE 6.3-1B

SUMMARY OF PROPERTIES OF FULL-RANGE LC-FINATE TESTS

COLORADO SHALE OIL DISTILLATE

CATALYST: SHELL 324 (AGED)

FILE ID: REPTSBL3.WK1

TEST # (BLCF-)	89-1	89-2	89-3	89-4	89-5
DATE (1989)	03-06	03-07	03-07/08	03-08	03-09
START TIME	11:30	21:30	14:00	04:00	13:00
END TIME	20:30	12:30	02:00	13:00	01:30
FEEDSTOCK	A	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.9934	0.9911	0.8959	0.9094	0.9123
API GRAVITY @ 60F	10.9	11.3	26.4	24.1	23.6
REFRACTIVE INDEX @ 20C					
ELEMENTALS, wt%					
C	85.11	85.63	85.56	85.74	85.72
H	11.6	11.92	12.0	11.86	11.77
SIMULATED DISTILLATION, F					
IBP	196	175	157	160	168
10% Distilled	438	391	344	351	376
30%	665	574	510	517	540
50%	765	716	642	653	677
70%	836	796	748	754	771
90%	929	899	855	858	875
VOLUM. AVG. BOIL. PT., F	727	675	620	627	648
WATSON K	10.6	10.5	11.4	11.2	11.3
WLHV, Btu/lb					
VLHV, Btu/gal					

FEEDSTOCK TYPE:

A: COLORADO SHALE OIL ATM RESID 650+ F.

TABLE 6.3-2A

SUMMARY OF OPERATING RESULTS FOR LC-FINING (HYDROCRACKING) TESTS

COLORADO SHALE OIL DISTILLATE

CATALYST: SHELL 324 (AGED)

FILE ID: REPTSBL2.WK1

TEST # (BLCF-)	91	96	97	98	99
DATE (1989)	04-05	04-12/13	04-13	04-13/14	04-14
START TIME	18:00	20:00	08:00	20:00	12:00
END TIME	24:00	04:00	16:00	08:00	20:00
FEEDSTOCK	B	B	B	B	B
% HDS					
% HDN					
% HDO					
H ₂ UPTAKE, scf/bbl	7500	10000	10000	10000	10000
API IMPROVEMENT					
R.I. REGRESSION					
EST. HEAT OF REACTION, Btu/lb					

FEEDSTOCK TYPE:

B: HYDROPROCESSED COLORADO SHALE OIL DISTILL RESID, 575+ F.

TABLE 6.3-2B

SUMMARY OF PROPERTIES OF FULL-RANGE LC-FINATE TESTS

COLORADO SHALE OIL DISTILLATE

CATALYST: SHELL 324 (AGED)

FILE ID: REPTSBL3.WK1

TEST # (BLCF-)	91	96	97	98	99
DATE (1989)	04-05	04-12/13	04-13	04-13/14	04-14
START TIME	18:00	20:00	08:00	20:00	12:00
END TIME	24:00	04:00	16:00	08:00	20:00
FEEDSTOCK	B	B	B	B	B
SPECIFIC GRAVITY, gm/cc	0.9123	0.9267	0.9188	0.9170	0.9371
API GRAVITY @ 60F	23.6	21.2	22.5	22.8	19.5
REFRACTIVE INDEX @ 20C					
ELEMENTALS, wt%					
C					
H					
SIMULATED DISTILLATION, F					
IBP					
10% Distilled					
30%					
50%					
70%					
90%					
VOLUM. AVG. BOIL. PT., F					
WATSON K					
WLHV, Btu/lb					
VLHV, Btu/gal					

FEEDSTOCK TYPE:

B: HYDROPROCESSED COLORADO SHALE OIL DISTILL RESID, 575+ F.

C: COALITE DISTILLATE, 300+ F.

TABLE 6.3-3A

SUMMARY OF OPERATING RESULTS ON HYDROTREATED PRODUCTS FROM FIXED-BED HYDROTREATING OF

THERMALLY PROCESSED COLORADO SHALE OIL DISTILLATE

CATALYST: K-550 (1ST STAGE) K-599 (2ND STAGE)

FILE ID: REPTSC3.WK1

TEST # (FB-)	131	132	133	134
DATE(1989)	04-24	04-24	04-24	04-25
START TIME	10:00	16:00	21:00	01:30
END TIME	12:00	18:00	22:30	03:00
FEEDSTOCK	A	A	A	A
% HDS				
% HDN				
% HDQ				
H2 UPTAKE, scf/bbl	7000	7000	7000	7000
% F.I.A. OLEFINS SATURATION				
% F.I.A. AROMATICS SATURATION				
API IMPROVEMENT	11.9	12.4	8.9	9.60
R.I. DEPRESSION	0.0364	0.0374	0.0260	0.03
EST. HEAT OF REACTION, Btu/lb				

FEEDSTOCK TYPE:

A: THERMALLY PROCESSED COLORADO SHALE OIL DISTILLATE, 300-575 F.

TABLE 6.3-3B

SUMMARY OF PROPERTIES OF HYDROTREATED PRODUCTS FROM FIXED-BED HYDROTREATING OF

THERMALLY PROCESSED COLORADO SHALE OIL DISTILLATE

CATALYST: K-550 (1ST STAGE) K-599 (2ND STAGE)

FILE ID:REPTSC2.WK1

TEST # (FB-)	131	132	133	134
DATE(1989)	04-24	04-24	04-24	04-25
START TIME	10:00	16:00	21:00	01:30
END TIME	12:00	18:00	22:30	03:00
FEEDSTOCK	A	A	A	A
SPECIFIC GRAVITY, gm/cc	0.8012	0.7990	0.8151	0.8118
API GRAVITY	45.1	45.6	42.1	42.8
REFRACTIVE INDEX @ 20 C	1.4416	1.4406	1.4520	1.4529
ELEMENTAL, wt. %				
C	85.47	85.54	86.04	85.61
H	14.50	14.53	13.89	13.65
DISTILLATION, F				
IBP				
10%				
30%				
50%				
70%				
90%				
VOLUM. YAG. BOIL. PT, F				
RATSON K				
F.I.A. ANALYSIS, lvol. %				
OLEFINS	0.5	0.3	0.5	0.30
SATURATES	91.1	91.7	76.4	75.50
AROMATICS	8.4	8.0	23.1	24.20
WLHV, btu/lb.		18283		18200
VLHV, btu/gal.		121686		123074
FLASH PT., F				
SMOKE PT., °				
FREEZ. PT., F				
ANILINE PT., F				
VISCOSITY, cs @ -4 F				

FEEDSTOCK TYPE:

A:THERMALLY PROCESSED COLORADO SHALE OIL DISTILLATE, 300-575 F.

TABLE 6.4-1A

SUMMARY OF OPERATING RESULTS FOR FIXED-BED HYDROTREATING TESTS OF

HYDROCRACKED COLORADO SHALE OIL DISTILLATE

CATALYST: K-550 (1ST STAGE)/K-599 (2ND STAGE)

FILE ID: REPTSE3.WK1

TEST # (FB-)	188	189
DATE (1989)	09-05	09-05/07
START TIME	06:00	19:00
END TIME	15:00	13:00
FEEDSTOCK	A	A
% HDS		
% HDN		
% HDO		
H2 UPTAKE, scf/bbl	8000	8000
% F.I.A. OLEFINS SATURATION		
% F.I.A. AROMATICS SATURATION		
API IMPROVEMENT		3.0
R.I. DEPRESSION		
EST. HEAT OF REACTION, Btu/lb		

FEEDSTOCK TYPE:

A: CRACKED VIRGIN COLORADO SHALE OIL.
FROM THREE-STEPS, HYDROPROCESSED VIRGIN
COLORADO SHALE OIL FOLLOWED BY FIXED-BED
HYDROTREATING AND HYDROCRACKING.

TABLE 6.4-1B

SUMMARY OF PROPERTIES OF FIXED-BED HYDROTREATED PRODUCTS

FROM HYDROCRACKED COLORADO SHALE OIL DISTILLATE

CATALYST: K-550 (1ST STAGE)/K-599 (2ND STAGE)

FILE ID: REPTSP3

TEST # (FB-)	188	189
DATE (1989)	09-05	09-05/07
START TIME	06:00	19:00
END TIME	15:00	13:00
FEEDSTOCK	A	A
SECIFIC GRAVITY, gm/cc		0.83
API GRAVITY @ 60 F		38.9
REFRACTIVE INDEX, @ 20 C		
ELEMENTAL, wt. %		
C		
H		
SIMULATED DISTILLATION, F		
IBP		195
10% DISTILLED		411
30%		586
50%		660
70%		746
90%		848
VOLUM. AVG. BOIL. PT. F		650
WATSON K		0.26
F.I.A./R.I., 1vol. %		
OLEFINS		
SATURATES		
AROMATICS		
WLHV, btu/lb.		
VLHV, btu/gal.		
FLASH PT. F		
SMOKE PT., mm		
FREEZ. PT., F		
ANILINE PT., F		
CETANE INDEX #6		
VISCOSITY, cs @ -4 F		

FEEDSTOCK TYPE:

A: CRACKED COLORADO SHALE OIL DISTILLATE,
FROM THREE-STEPS, HYDROPROCESSED VIRGIN
COLORADO SHALE OIL FOLLOWED BY FIXED-BED
HYDROTREATING AND HYDROCRACKING.

- o The thus hydrotreated LC-Finate VGO was then subjected to fixed-bed hydrocracking (test FBHC-32/35) over the Amoco proprietary hydrocracking catalyst. The resultant full-range hydrocrackate was then subjected to fixed-bed hydrotreating (FB-188/189) over a NiW/NiMo two-stage catalyst system without fractionating out the unconverted 575-975F gas oil fraction.
- o The hydrogenated hydrocrackate was fractionated to recover a 275-550F HEDF product that met flash point and freeze point specs.

The measured energy density of this latter product was still only about 125,000 Btu/gal, comparable to that generated when hydrotreating the raw 300-600F Colorado shale oil distillate. Thus, the selective hydrocracking of the 575F+ fraction of the Colorado shale oil did not improve energy density quality as was observed with the COALITE feedstock. Furthermore, the per pass conversions during the LC-Fining (BLCF-102) and the fixed-bed hydrocracking (FBHC-32/35) were very low indicating the relative refractory nature of the gas oil fraction of the Colorado shale oils.

This campaign did generate samples of Colorado shale oil-derived HEDF and HEDF precursor streams for testing in the extraction evaluation screening program.

6.6 Extraction Studies

The plan for the evaluation of the extraction/hydrogenation route (schematic diagram shown in Figure 6.6-1) consists of: a) collection of basic equilibrium solvent selectivity data for the two candidate solvents, namely, dimethylformamide (DMF) and tetraethylene glycol (TEG); b) analytical evaluation of the extracts and raffinates with respect to energy density improvements; and c) recommendations for preparation of bench-scale quantities of extracts for demonstration of the potential of fixed-bed hydrotreating (and hydrocracking) to upgrade extracted HEDF precursors to the 130,000 min. Btu/gal energy density spec.

The four feedstocks selected for the initial evaluation include:

- o mildly LC-Fined vac gas oil (BLCF-102 product)
- o severely hydrotreated LC-Finate vac gas oil (FB-186/187)
- o selectively hydrocracked mid-distillate (FB-188/189)
- o hydrotreated raw mid-distillate (FB-130)

The first two feedstocks represent the evaluation of heavier extracts boiling above the HEDF boiling range prior to hydrocracking. The latter two feedstocks to extraction represent HEDF products having nominal 125,000 Btu/gal energy densities.

The test equipment consists of a stirred, externally heated, glass extraction vessel. Testing consisted of three stages of contact using

FIGURE 6.6-1

EXTRACTION/HYDROGENATION ROUTES TO HEDF FROM COLORADO SHALE OILS (CSO)

fresh solvent in each stage. Conditions held constant in these initial tests were as follows:

- o Nominal temperature of 195F
- o Atmospheric pressure
- o Stirrer speed of 5 rpm
- o 1 hour extraction contact time per stage
- o Fresh solvent to feed ratio of 1.5 gm/gm

Raffinate and solvent-rich extract phases were separated by decanting in a separatory funnel. The extract was separated from the solvent by introduction of water which dissolved the solvent and freed the hydrocarbon-rich extract. The two solvents selected were premised on separation from the extract by distillation. The TEG, the heavier boiling solvent (B.P. = 622F), was to have been used for the lighter (275-575F) boiling mid-distillate stream. The DMF, the lighter boiling solvent (B.P. = 307F), was to have been used for the heavier (575-975F) boiling gas oil stream.

The summary of the operating conditions and raffinate properties is presented on the spreadsheet of Table 6.6-1. The initial testing indicated that the DMF solvent demonstrated a good degree of effectiveness in extracting some species from the heavier feedstock. The TEG solvent appeared to have no specificity for any of the components in the lighter distillate feedstock. Since the DMF solvent is soluble in water, it may be separated from the extract in a commercial-scale application by introduction of a third phase, namely, water or an aqueous-rich recycle stream, instead of distillation.

The results are summarized on Table 6.6-2 which shows that DMF extraction of a hydrotreated 300-650F distillate can increase the energy density of the extract by some 2335 Btu/gal over that of the feed but at the expense of a reduction in the energy density of the raffinate.

RESULTS OF SOLVENT EXTRACTION ON HYDROTREATED COLORADO SHALE OILS

SOLVENT A: TETRAETHYLENE GLYCOL
SOLVENT B: N,N-DIMETHYLFORMAMIDE

257

TABLE 6.6-2

LAB EXTRACTION STUDY RESULTS

FEED: HYDROTREATED 300-650F COLO SHALE OIL DISTILLATE
SOLVENT: DIMETHYLFORMAMIDE (DMF)

3-STAGE PERFORMANCE RESULTS

	<u>FEED</u>	<u>EXTRACT</u>	<u>RAFFINATE</u>
MATERIAL BALANCE	100	26.22	73.78
SPECIFIC GRAVITY	0.8189	0.8285	0.8130
Δ API IMPROVEMENT	—	2.0	(1.25)
% HYDROGEN CONTENT	14.31	13.88	14.46
Δ H REDUCTION, scf/bbl	—	232	(80)
VLHV, Btu/gal	124,150	126,485	122,951
Δ VLHV, Btu/gal	—	2335	(1199)

7.0 REFERENCES

1. Pound, G.S., "The Production of Chemicals From Low Temperature Tar", J. Inst. Fuels, Coke & Gas (October 1952)
2. Char Oil Energy Development (COED), Vol I Final Report, FE-1212-F, ERDA Contract E(49-18)-1212, September 1975.
3. M.R. Khan, "Correlations Between Physical and Chemical Properties of Pyrolysis Liquids Derived from Coal, Oil Shale and Tar Sand, Energy & Fuels, 1988, 2, 834-842

8.0 ACKNOWLEDGEMENTS

Lummus would like to acknowledge the following individuals for their guidance and assistance in facilitating the efforts on this HEDF technology screening program:

Charles Byrer	DOE-METC COTR
Jim Burchfield	DOE-METC Extraction Projects
(retired)	Management Division
Joe Masin	AOC Subcontractor, Lead LP Modeling
	Process Engineer

We would also like to acknowledge the following Lummus personnel for their contributions on the screening program:

Marvin Greene	Project Manager/Principal
	Investigator
Steven Huang	Pilot Plant Engineer
Sam Mikhail	Analytical Chemistry Supervisor
Louis Senario	Pilot Plant Operations Supervisor
Vincent Strangio	Pilot Plant Operations Manager
Robert Valente	Pilot Plant Engineer

END

**DATE
FILMED**

12 / 21 / 92